



University of Kentucky
UKnowledge

Agricultural Engineering Energy Series

Biosystems and Agricultural Engineering

8-1978

Energy in Agriculture: Fan Performance on Grain Drying Bins

Otto J. Loewer
University of Kentucky

Thomas C. Bridges
University of Kentucky, tom.bridges2@uky.edu

G. M. White
University of Kentucky

Robert L. Fehr
University of Kentucky, robert.fehr@uky.edu

Larry W. Turner
University of Kentucky

Right click to open a feedback form in a new tab to let us know how this document benefits you.

Follow this and additional works at: https://uknowledge.uky.edu/aees_reports

 Part of the [Bioresource and Agricultural Engineering Commons](#)

Repository Citation


Loewer, Otto J.; Bridges, Thomas C.; White, G. M.; Fehr, Robert L.; and Turner, Larry W., "Energy in Agriculture: Fan Performance on Grain Drying Bins" (1978). *Agricultural Engineering Energy Series*. 32.
https://uknowledge.uky.edu/aees_reports/32

This Report is brought to you for free and open access by the Biosystems and Agricultural Engineering at UKnowledge. It has been accepted for inclusion in Agricultural Engineering Energy Series by an authorized administrator of UKnowledge. For more information, please contact UKnowledge@lsv.uky.edu.

ENERGY IN AGRICULTURE

Fan Performance on Grain Drying Bins

by Otto J. Loewer, Tom C. Bridges, G. M. White, Robert L. Fehr and Larry W. Turner



UNIVERSITY of KENTUCKY
COLLEGE of AGRICULTURE
DEPT. of AGRIC. ENGINEERING
COOPERATIVE EXTENSION SERVICE

in
cooperation
with

KENTUCKY
DEPARTMENT
of
ENERGY

7.

--	--	--	--

8.

--	--	--	--	--	--	--	--

9.

--	--	--	--	--

HORSEPOWER OF FAN MOTOR

TYPE OF GRAIN
(select either corn, milo, wheat or soybeans.)

MAXIMUM DEPTH OF GRAIN IN THE BIN, FT.

The information you receive will be similar to that shown below. Each term is defined below the sample output.

1		2		3		4													
DIAMETER		SRTDEP		STPDEP		DELDEP													
?15		.5		16		.5													
													5						
FAN ID		XL370-7		0															
SP		0.0		0.50		1.00		1.50		2.00		2.50		6					
CFM		24530.		24530.		22420.		19900.		16200.		13300.		7					
DEPTH		9		BU		11		CFM		12		FFM		CFM/BU		HPUSED		EFF	
CORN		8																FF=1.50	
		0.50		71.		1.85		17284.4		97.8		244.52		5.05		50.48			
		1.00		141.		2.44		13670.6		77.4		96.70		5.25		52.48			
		1.50		212.		2.58		11247.7		63.6		53.04		4.57		45.68			
		2.00		283.		2.64		9619.1		54.4		34.02		4.00		39.99			
		2.50		353.		2.68		8449.9		47.8		23.91		3.57		35.72			
		3.00		424.		2.71		7593.4		43.0		17.90		3.25		32.48			
		3.50		495.		2.74		6933.1		39.2		14.01		2.99		29.93			
		4.00		565.		2.76		6405.0		36.2		11.33		2.78		27.85			
		4.50		636.		2.78		5970.9		33.8		9.39		2.61		26.11			
		5.00		707.		2.79		5606.4		31.7		7.93		2.46		24.64			
		5.50		778.		2.80		5294.9		30.0		6.81		2.34		23.37			
		6.00		848.		2.81		5025.1		28.4		5.92		2.23		22.26			
		6.50		919.		2.82		4788.5		27.1		5.21		2.13		21.28			
		7.00		990.		2.83		4579.0		25.9		4.63		2.04		20.40			
		7.50		1060.		2.83		4391.9		24.9		4.14		1.96		19.62			
		8.00		1131.		2.84		4223.6		23.9		3.73		1.89		18.91			
		8.50		1202.		2.85		4071.2		23.0		3.39		1.83		18.26			
		9.00		1272.		2.85		3936.5		22.3		3.09		1.77		17.69			
		9.50		1343.		2.86		3805.6		21.5		2.83		1.71		17.13			
		10.00		1414.		2.86		3676.9		20.8		2.60		1.66		16.58			
		10.50		1484.		2.87		3551.6		20.1		2.39		1.60		16.04			
		11.00		1555.		2.87		3436.9		19.4		2.21		1.55		15.55			
		11.50		1626.		2.87		3332.0		18.9		2.05		1.51		15.09			
		12.00		1696.		2.88		3234.4		18.3		1.91		1.47		14.67			
		12.50		1767.		2.88		3143.5		17.8		1.78		1.43		14.27			
		13.00		1838.		2.89		3058.4		17.3		1.66		1.39		13.90			
		13.50		1909.		2.89		2978.7		16.9		1.56		1.36		13.56			
		14.00		1979.		2.89		2903.8		16.4		1.47		1.32		13.23			
		14.50		2050.		2.89		2833.2		16.0		1.38		1.29		12.92			
		15.00		2121.		2.90		2766.7		15.7		1.30		1.26		12.63			
		15.50		2191.		2.90		2703.7		15.3		1.23		1.23		12.35			
		16.00		2262.		2.90		2644.1		15.0		1.17		1.21		12.09			

1. DIAMETER—Refers to the diameter of the grain bin.
2. SRTDEP—The grain depth at which the fan evaluation begins (ft).
3. STPDEP—The final grain depth to be considered (ft.) Corresponds to the answer given in Question 8.
4. DELDEP—Grain depth increment between each analysis (ft).
5. FAN ID—The identification given in Question 4.
6. SP—The static pressure values provided in Question 5.
7. CFM—The cubic feet per minute (CFM) values corresponding to static pressures given in Question 5.
8. CORN—The grain type considered, Question 7.
9. DEPTH—The 1st column is the depth of grain in the bin (ft).
10. BU—The 2nd column is the bushels of grain that correspond to the grain depth.
11. SP—The 3rd column is the static pressure in inches of water that correspond to the grain depth.

12. CFM—The 4th column is the total cubic feet per minute of air delivered by the fan corresponding to the grain depth.
13. FPM—The 5th column is the velocity of the air in the bin in ft per minute that correspond to the grain depth.
14. CFM/BU—The 6th column is the cubic feet of air per minute delivered to each bushel in the bin corresponding to the grain depth.
15. HPUSED—The 7th column is the horsepower used in actually moving the air through the grain corresponding to the grain depth.
16. EFF—The 8th column is the ratio of the actual horsepower used in moving the air to the total horsepower available.
17. PF—The “packing factor” multiplier; that is, clean loosely filled grain has a value of 1.0. This term serves as a safety factor in fan design.

ESTIMATING DRYING TIME:

The CFM per bushel term is one of several items required to estimate drying time. This value may be easily obtained from the computer output chart (Item 14). For example, if a layer or low-temperature system is being used, the example fan would deliver 1.17 CFM/BU at a grain depth of 16 ft. However, if the grain depth were only 4 ft. such as is typical of batch-in-bin drying, the example fan would deliver 11.33 CFM/BU. Using a computed air flow rate, you may estimate drying time by using one of the available programs listed below (No. 6-8).

ESTIMATING ENERGY USAGE:

An estimate of energy usage may be found with the following equation:

$$\text{Energy used in KW-hr} \approx \left(\frac{\text{hours of fan}}{\text{operation}} \right) \times \left(\frac{\text{horsepower}}{\text{used}} \right) \times 100.0 / (\text{Efficiency Factor})$$

assuming 1 hp-hr = 1000 watts allowing for a motor efficiency of 75%. The efficiency factor is equal to 50.0 or the value given in Column 8, whichever is smaller. The hours of operation may be estimated using the drying programs that are available.

AVAILABLE PROGRAMS:

1. BNDZN: Computer analysis of economics, energy consumption and engineering design of a grain storage system.
2. CHASE: Computer model that evaluates and compares costs of selected methods of harvesting, handling, drying and storage of corn for an individual farmstead. Energy consumption is also estimated.
3. CACHE: Computer model for economic analysis of farm drying and processing systems.
4. SQUASH: Computer simulation of the harvesting-delivery-drying system used to determine bottlenecks in the system.
5. *ESTIMATING FAN SIZES FOR GRAIN DRYING SYSTEMS.
6. *GRAIN DRYING PERFORMANCE EVALUATION
7. *DRYERATION PERFORMANCE EVALUATION
8. *NATURAL AIR—LOW TEMPERATURE DRYING PERFORMANCE EVALUATION
9. *FAN PERFORMANCE ON GRAIN DRYING BINS

ACKNOWLEDGEMENTS:

*These programs were developed by:

Dr. Thomas L. Thompson, Professor
Agricultural Engineering Department
University of Nebraska
Lincoln, Nebraska

The College of Agriculture is an Equal Opportunity Organization with respect to education and employment and is authorized to provide research, educational information and other services only to individuals and institutions that function without regard to race, color, national origin, sex, religion, age and handicap. Inquiries regarding compliance with Title VI and Title VII of the Civil Rights Act of 1964, Title IX of the Educational Amendments, Section 504 of the Rehabilitation Act and other related matters should be directed to Equal Opportunity Office, College of Agriculture, University of Kentucky, Room S-105, Agricultural Science Building-North, Lexington, Kentucky 40546

Issued in furtherance of Cooperative Extension work, Acts of May 8 and June 30, 1914, in cooperation with the U.S. Department of Agriculture. Charles E. Barnhart, Director of Cooperative Extension Service, University of Kentucky College of Agriculture, Lexington, and Kentucky State University, Frankfort.

Issued 8-78, 3M; rev. 11-81, 1.5M