



Kentucky Geological Survey Map and Chart

Kentucky Geological Survey

2006

## Generalized Geologic Map for Land-Use Planning: Pendleton County, Kentucky

Richard A. Smath University of Kentucky, rsmath@uky.edu

Daniel I. Carey University of Kentucky, daniel.carey@uky.edu

Right click to open a feedback form in a new tab to let us know how this document benefits you.

Follow this and additional works at: https://uknowledge.uky.edu/kgs\_mc Part of the <u>Geology Commons</u>

#### **Repository Citation**

Smath, Richard A. and Carey, Daniel I., "Generalized Geologic Map for Land-Use Planning: Pendleton County, Kentucky" (2006). *Kentucky Geological Survey Map and Chart.* 123. https://uknowledge.uky.edu/kgs\_mc/123

This Map and Chart is brought to you for free and open access by the Kentucky Geological Survey at UKnowledge. It has been accepted for inclusion in Kentucky Geological Survey Map and Chart by an authorized administrator of UKnowledge. For more information, please contact UKnowledge@lsv.uky.edu.

#### Kentucky Geological Survey James C. Cobb. State Geologist and Director UNIVERSITY OF KENTUCKY, LEXINGTON

#### Swelling and Shrinking Shales

A problem of considerable concern in this area is the swelling of some of the clay minerals in shale units 2 and 3. Expanding shale can cause backfill to swell and concrete to crack and crumble. It can heave the foundation, the slab, and interior partitions resting on it, and damage upper floors and interior partitions. This phenomenon has been responsible for extensive damage to schools, homes, and businesses in Kentucky. During times of drought, these same shales may shrink, causing foundations to drop. Anyone planning construction on these shales should seek professional advice from a geologist or engineer familiar with the problem.





Some shales, and the soils derived from them, swell when exposed to water or air. These swelling shales and soils can have severe

 $\vdash \vdash \vdash \vdash \vdash \vdash$ 

11/22/05].

10/21/05].

1:24.000.

#### Falmouth, Kentucky



Falmouth, the county seat, lies in the broad Licking River Valley. Pendleton County, with an area of 281 square miles, was established in 1798 in the Outer Bluegrass Region. The population in 2004 was 15,134. Photo by Dan Carey, Kentucky Geological Survey.

#### Shaly Limestone Topography





Steeply rolling knobby hills and cedar trees characterize areas underlain by the shaly limestone rocks of unit 2. Photo by Dan Carey, Kentucky Geological Survey.

#### Earthquake Hazard

Ground shaking (peak particle accelerations) caused by an earthquake in or near the county is minimal for structures situated on or tied into the bedrock foundation. In areas underlain by poorly consolidated soils, site-specific investigations should be conducted to assure that the building codes will conform to any ground deformation such as liquefication, landslides, or surface fault ruptures. See www.uky.edu/KGS/geologichazards/eqhazards.htm for more information.

## **Generalized Geologic Map** for Land-Use Planning:

# Pendleton County, Kentucky

### **Richard A. Smath and Daniel I. Carey**

Acknowledgments Geology adapted from Duncan (2002), Harper and Sparks (2002), Nelson (2002a-d), Thompson (2002), Yang (2002), and Zhang (2002a-c).

#### For Planning Use Only

This map is not intended to be used for selecting individual sites. Its purpose is to inform land-use planners, government officials, and the public in a general way about geologic bedrock conditions that affect the selection of sites for various purposes. The properties of thick soils may supercede those of the underlying bedrock and should be considered on a site-to-site basis. At any site, it is important to understand the characteristics of both the soils and the underlying rock. For further assistance, contact the Kentucky Geological Survey, 859.257.5500. For more information, and to make custom maps of your area, visit the KGS Land-Use Planning Internet Mapping Web Site at kgsmap.uky.edu/website/kyluplan/viewer.htm.



Geese enjoying a mid-winter swim in the Licking River just upstream of the Ky. 177 bridge at Butler. Photo by Dan Carey, Kentucky Geological Survey.









Carmeuse Lime produces 1.4 million tons per year of high-calcium lime for powerplant scrubbers and the steel industry from its 600-foot-deep slope mine on the Ohio River. Aerial photo (2004) by the U.S. Department of Agriculture, Farm Services Administration, National Agricultural Imagery Program.

#### **Slope Failure**

Mass movements or landslides of surficial materials are by far the most frequent and costly geologic hazards in the northern Kentucky area. Northern Kentucky has the greatest monetary loss per capita caused by landslides in the country. The failure of the slope may be rapid, but more commonly is a slow, almost imperceptible movement, called creep, of a few inches per year. Whether rapid or slow, the end results and damage are similar and costly: broken plumbing, cracked walls and foundations, cracked streets and sidewalks, and commonly total loss of the structures.



Virtually all of the mass movements in northern Kentucky occur in colluvium—the weathered soil and rock materials that crumble from the bedrock as it weathers. The lower slopes of unit 2 are commonly thickly mantled with colluvium.

Shales of unit 2 and adjacent unit 3 will break down and weather rapidly when exposed to air and water. These shaly units tend to swell considerably when exposed to water. For this reason, plumbing trenches under walls and foundations should be prevented from accumulating water. Units 2 and 3 may share a translational landslide.

Gravity is the main driving force, but water nearly always plays a critical role by adding weight and lubricating the particles in the colluvium. Cutting into or overloading a slope with structures and fill can also be major contributing factors.

Precautions include taking care of all surface-water runoff by making certain that all runoff from roofs, gutters, patios, sidewalks, and driveways is carried well away from and not toward the house; diverting drainage from areas sloping toward the house; cutting into natural slopes as little as possible and avoiding the use of fill; and trying to place the foundation of the structure on undisturbed bedrock.

When in doubt, consult an engineering geologist or a geotechnical engineer. Old landslides can also be easily reactivated. Look for unusual bulges or cracks in the slope, tilted or curved trees, springs coming out onto the hillside, and tilted and cracked sidewalks, streets, and retaining walls.

#### For more information, see Potter (1996).



Rotational landslides occur in both the thicker colluvium of unit 2 and in glacial deposits. The head or top area has tension cracks or small cliffs; the toe or bottom has transverse ridges or bulges. A principal glide plane connects the top to the bottom. Small tension cracks in the top become large scarps or cliffs as material moves downslope and small bulges in the bottom become larger ones. After Potter (1996).

TRANSLATIONAL SLIDE Colluvium can be less than 6 feet thick. An additional load may sit for years before conditions are right and the ground slides quickly. Debris pile at toe

Shale. limestone

1975, Geologic map of the Berlin quadrangle, Bracken and Pendleton Counties, Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1256, scale 1:24,000.

Nelson, H.L., Jr., 2002b, Spatial database of the Butler quadrangle, Pendleton and Campbell Counties, Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-982. Adapted from Luft, S.J., 1972, Geologic map of the Butler quadrangle, Pendleton and Campbell Counties, Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-982, scale 1:24,000.

Nelson, H.L., Jr., 2002c, Spatial database of the Claysville quadrangle, northeastern Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-1341. Adapted from Luft, S.J., 1976, Geologic map of the Claysville quadrangle, northeastern Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1341, scale 1:24,000.

Nelson, H.L., Jr., 2002d, Spatial database of the Walton quadrangle, northcentral Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-1080. Adapted from Luft, S.J., 1973, Geologic map of the Walton quadrangle, north-central Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1080, scale 1:24,000.

Potter, P.E., 1996, Exploring the geology of the Cincinnati/northern Kentucky region: Kentucky Geological Survey, ser. 12, Special Publication 22, 115 p.

Thompson, M.F., 2002, Spatial database of the Goforth quadrangle, Pendleton and Grant Counties, Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-925. Adapted from Luft, S.J., 1971, Geologic map of the Goforth quadrangle, Pendleton and Grant Counties, Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-925, scale 1:24,000.

U.S. Fish and Wildlife Service, 2003, National Wetlands Inventory, www.nwi.fws.gov [accessed 10/25/05].

- Yang, X.Y., 2002, Spatial database of the Falmouth quadrangle, Pendleton County, Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-1037. Adapted from Luft, S.J., 1972, Geologic map of the Falmouth quadrangle, Pendleton County, Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1037, scale 1:24,000
- Zhang, Q., 2002a, Spatial database of the Berry quadrangle, north-central Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-1284. Adapted from Luft, S.J., 1975, Geologic map of the Berry quadrangle, north-central Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1284, scale 1:24,000.
- Zhang, Q., 2002b, Spatial database of the Kelat quadrangle, Harrison and Pendleton Counties, Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-1172. Adapted from Luft, S.J., 1974, Geologic map of the Kelat quadrangle, Harrison and Pendleton Counties, Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1172, scale 1:24,000.
- Zhang, Q., 2002c, Spatial database of the Moscow quadrangle, Ohio-Kentucky: Kentucky Geological Survey, ser. 12, Digitally Vectorized Geologic Quadrangle Data DVGQ-1069. Adapted from Luft, S.J., Osborne, R.H., and Weiss, M.P., 1973, Geologic map of the Moscow quadrangle, Ohio-Kentucky: U.S. Geological Survey Geologic Quadrangle Map GQ-1069, scale 1:24,000.

Listed below are Web sites for several agencies and organizations that may be of assistance with land-use planning issues in Pendleton County:

<u>ces.ca.uky.edu/pendleton/</u> University of Kentucky Cooperative Extension Service www.kineticnet.net/kyrcd/lrv.html Licking River Valley Resource Conservation and Development Council Inc. www.nkadd.org/ Northern Kentucky Area Development District www.thinkkentucky.com/edis/cmnty/cw011/ Detailed county statistics

FOUNDATION AND EXCAVATION

Accumulation Zone or Toe A transitional landslide is a relatively thin sheet of colluvium that separates

Re

from the underlying bedrock and slides catastrophically downslope more or less as a coherent sheet until it abruptly stops and becomes a crumbled, disorganized pile of debris. Such failures are common on steeper slopes of shale-dominated units (units 2, 3) when both colluvium and the weathered, more permeable bedrock below become fully saturated with water. After Potter (1996).

#### Waste Management and Recycling



Rumpke Industries accepts 1,000 to 1,200 tons per day of municipal solid waste at its permitted 48-acre site off Ky. 1853. Additional acreage at the site is available for future expansion. Griffin Industries operates a processing facility on the adjacent property that converts used cooking oil and meat-processing byproducts into chicken feed and bio-diesel fuel. Aerial photo (2004) by the U.S. Department of Agriculture, Farm Services Administration, National Agricultural Imagery Program.

#### Groundwater

In the valley bottoms of the Licking River, South Fork of the Licking River, Ohio River, and some of the major creeks, most drilled wells will produce enough water for a domestic supply at depths of less than 100 feet. Wells located in the valley bottoms of the larger creeks will produce enough water for a domestic supply, except during dry weather. In upland areas (60 percent of the county), most drilled wells will not produce enough water for a dependable domestic supply. Upland wells drilled along drainage lines may produce enough water except during dry weather. Throughout the county, groundwater is hard or very hard and may contain salt or hydrogen sulfide, especially at depths greater than 100 feet. For more information on groundwater in the county, see Carey and Stickney (2004).





Learn more about Kentucky geology at www.uky.edu/KGS/geoky/



Rural residential development on unit 5 in southern Pendleton County. Photo by Dan Carey, Kentucky Geological Survey.

Reservoir

Areas

(Froedge and Weisen-

Moderate to slight

limitations. Reservoir

are fractured. Sinks

Moderate to slight

are fractured. Sinks

Slight to severe

mitations. Reservoir

may leak where rocks are fractured. Sinks

Not recommended.

Pervious material.

possible

possible.

limitations. Reservoir

may leak where rocks

ossible

may leak where rocks

Refer to soil report

berger, 1980).

Reservoir

Embankments

Not recommended.

Refer to soil report

berger, 1980).

(Froedge and Weisen-

Moderate to severe

limitations. Reservoir

may leak where rocks

are fractured. Sinks

Moderate to severe

limitations. Reservoir

are fractured. Sinks

Slight to severe

Severe to slight

limitations. Un-

stable steep

slopes.

mitations. Reservoir

mav leak where rocks

are fractured. Sinks

may leak where rocks

possible.

possible.

possible.

Underground

Utilities

Not recommended.

Refer to soil report

Moderate to severe

Severe to moderate

limitations. Possible

Severe to moderate

limitations. Possible

rock excavation.

Slight limitations.

rock excavation.

limitations.

excavation.

landslides.

Possible rock

Susceptible to

berger, 1980).

(Froedge and Weisen-

#### 7.5-Minute Topographic Map Index

2	WALTON	DEMOSE	BUTLER	NOSCOW	
Ä	LLAMS'	COFORTH	FRINOUTH	BERLIN	
		BERRY	KELAT	CLAYSVILLE	
		PENDLET COUNT	T <mark>ON</mark> Y	€~-0	

Copyright 2006 by the University of Kentucky, Kentucky Geological Survey

For information on obtaining copies of this map and other Kentucky Geological Survey maps and publications call our Public Information Center at 859.257.3896 or 877.778.7827 (toll free)

View the KGS World Wide Web site at: www.uky.edu/kgs

Planning C	<b>Guidance</b> by	y Rock Unit	Туре
------------	--------------------	-------------	------

The terms "earth" and "rock" excavation are used in the engineering sense; earth can be excavated by hand tools, whereas rock requires heavy equipment or blasting to remove.

<b>LIMITATIONS</b> <b>Slight</b> —A slight limitation is one that commonly requires some corrective measure but can be overcome without a great deal of difficulty or expense.	Rock Unit	Karst Potential Rating	Foundation and Excavation	Septic System	Residence with Basement	Highways and Streets	Access Roads	Light Industry and Malls	Intensive Recreation	Extensive Recreation	
<b>Moderate</b> —A moderate limitation is one that can normally be overcome but the difficulty and expense are great enough that completing the project is commonly a question of feasibility.	1. Clay, silt, sand, and gravel	None, but on-site karst investigation recom- mended where less than 25 feet thick	Fair foundation material; easy to excavate.	Severe limitations. Failed septic systems can contaminate groundwater. Refer to	Water in alluvium may be in direct contact with basements. Refer to soil report	Slight limitations. Refer to soil report (Froedge and Weisen- berger, 1980).	Slight to moderate limitations. Refer to soil report (Froedge and Weisenberger,	Slight to moderate limitations. Avoid construction in flood- plain. Refer to	Refer to soil report (Froedge and Weisen- berger, 1980).	Refer to soil report (Froedge and Weisen- berger, 1980).	Re (F be
<b>Severe</b> —A severe limitation is one that is difficult to overcome and commonly is not feasible because of the expense involved.		over soluble fock.		Weisenberger, 1980).	berger, 1980).		1980).	and Weisenberger, 1980).			
LAND USES	2. Shale*, lime- stone	Medium to low.	Fair to good foun- dation material;	Slight to severe limita- tions, depending on	Severe to moderate limitations. Rock	Moderate to severe limitations. Rock ex-	Moderate limitations. Rock excavation	Slight to severe lim- itations, depending	Slight to moderate limitations, depending	Slight limitations, depending on	N
Septic tank disposal system—A septic tank disposal system consists of a septic tank and a filter field. The filter field is a subsurface tile system laid in such a way that effluent from the septic tank is distributed with reasonable uniformity into the soil.			difficult excavation. Slumps when wet. Avoid steep slopes.	amount of soil cover and depth to imperme- able rock.	excavation may be required. Slumps when wet. Avoid steep slopes.	cavation may be required. Possible steep slopes.	likely. Local drainage problems, especially on shale. Sinks common.	on topography. Rock excavation. Sinks common. Local drainage problems. Groundwater contam-	on activity and topog- raphy. Possible steep wooded slopes.	activity and topog- raphy. Possible steep wooded slopes. Slight limitations for forest or nature preserve.	m ar p
Residences—Ratings are made for residences with basements because the degree of limitation is dependent upon ease and								ination possible.			
required depth of excavation. For example, excavation in limestone has greater limitation than excavation in shale for a house with a basement.	3. Limestone, shale*	High to medium.	Good to excellent foundation material;	Slight to severe limita- tions, depending on	Severe to moderate limitations. Rock	Moderate limitations. Rock excavation	Moderate limitations. Rock excavation	Slight to severe lim- itations, depending	Slight to moderate limitations. Rock	Slight limitations, de- pending on activity	M
<b>Highways and streets</b> —Refers to paved roads in which cuts and fills are made in hilly topography, and considerable work is done preparing subgrades and bases before the surface is applied.			difficult to excavate.	amount of soil cover and depth to imperme- able rock.	excavation may be required.	possible. Local drainage problems, especially on shale. Sinks common and	possible. Possible steep slopes. Slight limitations with suit- able topography.	on topography. Rock excavation. Sinks common. Local drainage problems.	excavation may be required.	and topography. Possible steep wooded slopes. No limitations for nature or forest	ma ar pc
Access roads—These are low-cost roads, driveways, etc., usually surfaced with crushed stone or a thin layer of blacktop. A minimum of cuts and fills are made, little work is done preparing a subgrade, and generally only a thin base is used. The						caves possible.		Groundwater contam- ination possible.		preserve.	
degree of limitation is based on year-around use and would be less severe if not used during the winter and early spring. Some types of recreation areas would not be used during these seasons.	4. Limestone	High.	Excellent founda- tion material; difficult to excavate.	Severe limitations. Impermeable rock. Locally fast drainage	Severe to moderate limitations. Rock excavation may be	Severe limitations. Rock excavation. Possible steep	Severe to moderate limitations. Possible	Slight to moderate limitations, depending	Moderate to slight limitations, depending	Severe to slight limitations, depending	Sli
Light industry and malls—Ratings are based on developments having structures or equivalent load limit requirements of three stories or less, and large paved areas for parking lots. Structures with greater load limit requirements would normally need footings in solid rock, and the rock would need to be core drilled to determine the presence of caverns, cracks, etc.				through fractures and sinks. Danger of groundwater con- tamination.	required.	slopes.	Possible steep slopes and narrow ravines.	excavation possible. Sinks common. Local drainage problems.	raphy. Possible wooded slopes.	raphy. Possible wooded slopes. Slight limitations for nature preserve.	ard pc
Intensive recreation—Athletic fields, stadiums, etc.											
Extensive recreation—Camp sites, picnic areas, parks, etc.	5. Clay, silt, sand, and gravel (high-level terrace deposits and	None, but onsite karst investigation recommended where	Fair foundation material; easy to excavate.	Severe to slight limita- tions, depending on amount of soil cover.	Moderate to slight limitations, depend- ing on slope.	Slight limitations.	Slight limitations, depending on degree of slope.	Slight limitations, depending on degree of slope.	Moderate to slight limitations, depending on activity and topog-	Slight limitations, depending on activity and topog-	Nc P€
Reservoir areas—The floor of the area where the water is impounded. Ratings are based on the permeability of the rock.	glacial outwash)	less than 25 feet thick over soluble							raphy. Possible wooded slopes.	raphy. Possible wooded slopes. Slight limitations	
Reservoir embankments—The rocks are rated on limitations for embankment material.										for nature preserve.	
<b>Underground utilities</b> —Included in this group are sanitary sewers, storm sewers, water mains, and other pipes that require fairly deep trenches.	Some of these shale	 es can shrink during o	dry periods and swe	ll during wet periods a	and cause cracking of	foundations. On hill	l sides, especially whe	ere springs are prese	_  ent, they can also be ∉	susceptible to landslic	l Jes