

Western Washington University Western CEDAR

Salish Sea Ecosystem Conference

2014 Salish Sea Ecosystem Conference (Seattle, Wash.)

May 2nd, 8:30 AM - 10:00 AM

Water Resource Inventory Area 9 Stormwater Retrofit Project: Estimating cost-effective stormwater infrastructure solutions to meet flow and water quality targets

Olivia Wright King County, olivia.wright@kingcounty.gov

Follow this and additional works at: https://cedar.wwu.edu/ssec



Part of the Terrestrial and Aquatic Ecology Commons

Wright, Olivia, "Water Resource Inventory Area 9 Stormwater Retrofit Project: Estimating cost-effective stormwater infrastructure solutions to meet flow and water quality targets" (2014). Salish Sea Ecosystem Conference. 10.

https://cedar.wwu.edu/ssec/2014ssec/Day3/10

This Event is brought to you for free and open access by the Conferences and Events at Western CEDAR. It has been accepted for inclusion in Salish Sea Ecosystem Conference by an authorized administrator of Western CEDAR. For more information, please contact westerncedar@wwu.edu.

WRIA 9 Stormwater Retrofit Project:

Modeling cost-effective solutions to meet flow and water quality targets


Olivia Wright
Salish Sea Ecosystem Conference
05/02/2014

Objective

Estimate planning-level stormwater facility needs and costs for future development in the WRIA 9 study area.

- 1. Model cost-effective combinations of BMPs using the EPA SUSTAIN model.
- 2. Extrapolate model results to future (2040) land use of the study area.


WRIA 9 Study Area



Project Need

Development is projected to increase from 65% to 77%

Puget Sound



Simulated 2040 Future Land Use (Alberti 2009)


LU 2040


2 Medium Urban 3 Light Urban

6, Grass, Grasslands
6, Deciduous and Mixed Force (
7, Conferous Fores)
8, Clearout Fores)

2007 Satellite-derived Existing Land Use (UW 2007)

SUSTAIN: System for Urban Stormwater Treatment and Analysis INtegration






Model Inputs:

BMP Design and Cost Assumptions Flow or water quality goals Decision variables


Source: EPA

Modeling Approach

- Model 135 hypothetical 100-acre catchments representing combinations of:
 - 5 generic land uses
 - 3 soil types
 - 2 slopes
 - 3 precipitation zones
 - 2 land costs




BMP Treatment Train



BMP Unit Design and Cost Assumptions


- Develop conceptual BMP unit designs
- 30-year life cycle costs assuming 5% real discount rate:
 - Capital
 - Operation and Maintenance (O&M)
 - Inspection and enforcement (I&E)
 - Land acquisition cost
- Assume construction of modeled BMP units are distributed over the 30-year period.

SUSTAIN Optimization Target:Reduce Stream Flashiness



High Pulse Count (HPC): Number of times mean daily flows \geq high-flow threshold set at 2 X long-term mean daily flow rate


SUSTAIN Output




Cost (\$ Millions)

Scale to Future Land Use

SUSTAIN Modeled Hypothetical Catchments





Simulated 2040 Future Land Use (Alberti 2009)

Results: BMP Units and Storage


| BMP Unit | #Units | Volume (acre-ft) | Storage (inches) |
|--------------------------|-----------|---------------------|---------------------|
| Cisterns | 24,000 | 200 | 0.02 |
| Rain Gardens | 2,600,000 | 9,600 | 0.90 |
| Roadside Bioretention | 190,000 | 700 | 0.07 |
| Detention Ponds | 75,000 | 19,000 | 1.80 |

~2.7 inches of flow control needed for future development


$$storage = \frac{volume \text{ of facilities}}{developed area}$$

BMP Effectiveness: Improvement in Biological Health

- King County data set from 16 flow and B-IBI stream stations (*DeGasperi et al.* 2009)
- Logarithmic-linear regression equation and confidence limits estimate improvement in B-IBI scores based on improvement in HPC (*Horner 2013*)




Potential Improvement in Hydrologic Indicators and B-IBI Scores




^{*}Results for 446 catchments of study area

Potential B-IBI Improvement

2040 Land Use No Stormwater Management



2040 Land Use Full Stormwater Management



| Biological Condition | B-IBI Range 46 - 50 | |
|----------------------|-------------------------------|--|
| Excellent | | |
| Good | 38 - 44 | |
| Fair | 28 - 36 | |
| Poor | 18 - 26 | |
| Very Poor | 10 - 16 | |

Source: http://pugetsoundstreambenthos.org/

Next step: Estimating Costs

- How will BMPs be implemented across the study area?
- Evaluate implementation strategies:
 - Mitigation required with new and redevelopment
 - Potential public stormwater program
- Identify existing facilities in study area

Questions?

For more details: King County's WRIA 9 Retrofit Project SUSTAIN Modeling Report

Contact info: Olivia.Wright@kingcounty.gov

Acknowledgements, thank you!

- King County: Jim Simmonds, Jeff Burkey, and Curtis DeGasperi
- University of Washington: Dr. Rich Horner and Dr. Erkan Istanbulluoglu
- Funding provided by: U.S. Environmental Protection Agency
- Project Management Team and Stakeholders