



Institutional Repository - Research Portal

Dépôt Institutionnel - Portail de la Recherche

researchportal.unamur.be

RESEARCH OUTPUTS / RÉSULTATS DE RECHERCHE

4-Class UMTS Traffic Emulation

Van Peteghem, Hugues; Schumacher, Laurent

Published in:

Proceedings of the 12th International Union of Radio Science (URSI) Forum - Brussels (Belgium), 10 December 2004

Publication date:

2004

Document Version

Peer reviewed version

[Link to publication](#)

Citation for published version (HARVARD):

Van Peteghem, H & Schumacher, L 2004, '4-Class UMTS Traffic Emulation', *Proceedings of the 12th International Union of Radio Science (URSI) Forum - Brussels (Belgium), 10 December 2004*.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

4-class UMTS Traffic Emulation

Hugues VAN PETEGHEM, Laurent SCHUMACHER*

FACULTES UNIVERSITAIRES NOTRE-DAME DE LA PAIX,
Rue Grangagnage 21, 5000 NAMUR

☎: +32/81/72.49.99, ☎: +32/81/72.67., ✉: hvp@info.fundp.ac.be

* same address, but ☎: +32/81/72.49.80 & ✉: lsc@info.fundp.ac.be

1. INTRODUCTION

Traffic emulation is an essential research phase towards the deployment of the UMTS. We present here an extension to the traffic generator *TG* which enables to generate the four UMTS traffic classes proposed by the 3GPP.

2. TRAFFIC MODEL

In [1] the 3rd Generation Partnership Project (3GPP) has defined four classes of services that need to be provided in UMTS. To characterise a single-user traffic, we fit each of these classes in a three-level model [2]. Here is a quick run-down of their signification: the session-level lasts as long as the application is running, its statistics are mainly influenced by user behaviour. The connection-level describes the connection behaviour of a single session, the pattern chosen for our sources is based on an On-Off (High-Low) model in which it is possible to generate traffic on both states. Finally, for each state of the connection-level, the packet-level describes the packet inter-arrival and size distribution. Based on this level division, we have modeled the four traffic classes in terms of statistical distributions, in line with literature [2,3] or 3GPP standards [4,5] when applicable.

To generate these different traffics, we used an enhanced version of Traffic Generator (*TG'*) implementing the Pareto distribution as well². We simulated five User Equipments (UE) connected to the same NodeB, each of them generating and receiving all kinds of traffic during 50,000 seconds (about 14 hours). The simulation took place on our UMTS testbed³. In order to simultaneously emulate several autonomous UEs, we coded a control panel based on multi-thread programming and virtual network interface management. The role of this control panel is to facilitate the UE management by delegating them a single thread and an IP address.

3. REFERENCES

- [1] Technical Specification Group Radio Access Network. *TS 23.107 V6.1.0, Quality of Service (QoS) concept and architecture*. 3GPP, April 2004.
- [2] Alexander Klemm, Christoph Lindemann, and Marco Lohmann. *Traffic modeling and characterization for UMTS networks*. GLOBECOM 2001.
- [3] A. Reyes, E. Gonzalez-Parada, E. Casilari, J.C. Casasola, and A. Diaz-Estrella. *A page-oriented www traffic model for wireless system simulations*. ITC16, pages 1271-1280, 1999.
- [4] Technical Specification Group Radio Access Network. *TR 25.896 V6.0.0, Feasibility Study for Enhanced Uplink for UTRA FDD*. 3GPP, April 2004.
- [5] Technical Specification Group Radio Access Network. *TR 25.933 V5.4.0, IP transport in UTRAN (Release 5)*. 3GPP, January 2004.

¹ <http://www.postel.org/tg/tg.htm>

² A validation of this distribution implementation and the new version of *TG* are available on: <http://www.info.fundp.ac.be/rech/doc/tg/>

³ A description of our testbed is to be found in the following document: <http://www.info.fundp.ac.be/~hvp/rech/doc/proposition.pdf>