

## Segmentation and Descriptors for Pattern

Praveen Shrivastava<sup>1</sup>  
 Sadhu Vaswani College Bhopal  
 Arvind Gupta<sup>2</sup>  
 Govt. M.V.M College Bhopal  
 S.K.Vijay<sup>3</sup>  
 Govt. Gitanjali College Bhopal

### Abstract

Image segmentation is an essential preliminary step in most automatic pictorial pattern recognition. The purpose of representation and description is used to be the application of Pattern. In the application of image processing, we have to choose an approach and to do description, just like recognition of the image.

**Keywords:** image processing, Pattern

### 1. Introduction

Segmentation is to subdivide an image into constituent regions or objects. In this paper, we apply many different approaches to detect the edge. After an image is segmented into regions, each region is represented and described in a form suitable for further computer processing [1].

### 2. Segmentation Edge-Based

There are three basic types of gray-level discontinuities in a image: points, lines, and edges. The most common way to look for discontinuities is to run a mask through the image[2]. And the response of the mask at any  $u_1 = 3$  point in the image is given by

$$R = w_1 z_1 + w_2 z_2 + \dots + w_9 z_9 = \sum_{i=1}^9 z_i$$

### 3. Fourier Transform

- While a Fourier is useful for periodic functions, the Fourier transform or integral is used for non-periodic functions [14].
- While a Fourier is useful for periodic functions, the Fourier transform or integral is used for non-periodic functions.

The Fourier transform of a function

$$H(f) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^{\infty} h(t) e^{-2\pi f t} dt$$

- For compactness we use the complex exponent function.
- The Fourier transform transforms from the  $t$  domain to the  $f$  domain.
- By convention time  $t$  is used as the functions variable and frequency as the transform variable.

$$H(\omega) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^{\infty} h(t) e^{-i\omega t} dt$$

### 4. Descriptors for Pattern

The Fourier descriptors [3] are starting at an arbitrary point  $(x, y)$ . Each coordinate pair can be treated as a complex number so that

$$s(k) = x(k) + jy(k)$$

This representation has one great advantage that it reduces a 2-D to a 1-D problem. The discrete Fourier transform of  $s(k)$  is

$$a(u) = \frac{1}{K} \sum_{k=0}^{K-1} s(k) e^{-j2\pi uk/K}$$

for  $u = 0, 1, 2, \dots, K-1$ . The complex coefficients  $a(u)$  are called the Fourier descriptors of the boundary.

The inverse Fourier transform of these coefficients restore  $s(k)$ . That is,

$$s(k) = \sum_{u=0}^{K-1} a(u) e^{j2\pi uk/K}$$

for  $k = 0, 1, 2, \dots, K-1$ . Suppose, however, that instead of all the Fourier coefficients, only the first P coefficient is used [4]. This is equivalent to setting  $a(u) = 0$  for  $u > P-1$ . The result is the following approximation to  $s(k)$ :

$$\hat{s}(k) = \sum_{u=0}^{P-1} a(u) e^{j2\pi uk/K}$$

The smaller P becomes, the more detail that is lost on the boundary. And the bigger P becomes, it more similar to boundary.

#### 4 Statistical Moments

The shape of boundary segments can be described quantitatively by using simple statistical moments, such as the mean, variance, and higher-order moments [6] [7]. Let us treat the amplitude of g as a discrete random variable v and form an amplitude histogram  $p(v_i)$ ,  $i = 0, 1, 2, \dots, A-1$ , where A is the number of discrete amplitude increments in which we divide the amplitude scale, and p() is the probability of value vi. The equation of nth moment about its mean is

$$u_n(v) = \sum_{i=0}^{A-1} (v_i - m)^n p(v_i)$$

$$m = \sum_{i=0}^{A-1} v_i p(v_i)$$

An alternative approach is to normalize g(r) to unit area and treat it as a histogram. In other words,  $g(r_i)$  is now treated as the probability of value  $r_i$  occurring. In this case, r is treated as the random variable and the moments are

$$u_n(r) = \sum_{i=0}^{K-1} (r_i - m)^n g(r_i)$$

where

$$m = \sum_{i=0}^{K-1} r_i g(r_i)$$

In this notation, K is the number of points on the boundary, and  $u_n(r)$  is directly related to the shape of g(r). Basically, what we have accomplished is to reduce the description task to that of describing 1-D functions.

#### Future Outcomes of the Present Study

Image segmentation is an essential preliminary step in most automatic pictorial pattern recognition. The purpose of representation and description is used to be future outcomes study in the application of Pattern. In the application of image processing, we have to present an approach and to do descriptors, just like recognition of the picture or pattern. An alternative approach is to normalize in other functions.

#### Basic Reference of Present Study

- Gonzalez R C. and R E. Woods (2008), "Digital Image Processing II edition", Prentice-Hall, 2008, pp.173- 175.
- Mukhopadhyay Susanta and Bhabatosh Chanda (2003), "Multiscale Morphological Segmentation of Gray-Scale Images," in *IEEE Trans. on Image Proc.*, vol. 12, no. 5, May 2003.
- Ilic S. and B. Ulicny (2000), "Seeded Region Growing Method for Image Segmentation", *Assignment for Computer Vision Work Paper Presentation*, The Swiss Federal Institute of Technology, 2000.
- Pavlidis T. and S. L. Horowitz (1974), "Segmentation of Plane Curves" in *IEEE Trans. on Computers*, C-23 (1974), pp. 860-870. **GC:153.**
- Sklansky J. and V. Gonzalez (1980), "Fast polygonal approximation of digitized curves" in *Pattern Recognition*, 12(5): pp.327-331, 1980.
- Schuster G. M. and A. K. Katsaggelos (1998), "An Optimal Polygonal Boundary Encoding Scheme in the Rate Distortion Sense" in *IEEE Transactions on Image Processing*, vol.7, no.1, January 1998.

## Reference

- [1] Mukhopadhyay Susanta and Bhabatosh Chanda (2003), "Multiscale Morphological Segmentation of Gray-Scale Images," in *IEEE Trans. on Image Proc.*, vol. 12, no. 5, May 2003.
- [2] Ilic S. and B. Ulicny (2000), "Seeded Region Growing Method for Image Segmentation", *Assignment for Computer Vision Work Paper Presentation*, The Swiss Federal Institute of Technology, 2000.
- [3] Pavlidis T. and S. L. Horowitz (1974), "Segmentation of Plane Curves" in *IEEE Trans. on Computers*, C-23 (1974), pp. 860-870. **GC:153.**
- [4] Sklansky J. and V. Gonzalez (1980), "Fast polygonal approximation of digitized curves" in *Pattern Recognition*, 12(5): pp.327-331, 1980.
- [5] Schuster G. M. and A. K. Katsaggelos (1998), "An Optimal Polygonal Boundary Encoding Scheme in the Rate Distortion Sense" in *IEEE Transactions on Image Processing*, vol.7, no.1, January 1998.
- [6] Musmann H., M. H'otter, and J. Ostermann (1989), "Object-oriented analysis-synthesis coding of moving images," in *Signal Process.: Image Commun.*, vol. 1, pp. 117-138, Oct. 1989.
- [7] H'otter M. (1990), "Object-oriented analysis-synthesis coding based on moving two-dimensional objects" in *Signal Process.: Image Commun.*, vol. 2, pp.409-428, Dec. 1990.
- [8] Gonzalez R C. and R E. Woods (2008), "*Digital Image Processing III edition*", Prentice-Hall, 2008, pp.361-362.
- [9] Gonzalez R C. and R E. Woods (2008), "*Digital Image Processing II edition*", Prentice-Hall, 2008, pp.173-175.
- [10] Haldun M. Ozaktas and M. Alper Kutay, "*Introduction to the Fractional Fourier Transform and Its Applications*," Advances in Imaging and Electron Physics, vol. 106, pp. 239~286.
- [11] Namias V. (1980), "*The Fractional Order Fourier Transform and Its Application to Quantum Mechanics*," J. Inst. Math. Appl., vol. 25, pp. 241-265, 1980.
- [12] Luis B. Almeida (1994) , "*The Fractional Fourier Transform and Time-Frequency Representations*," IEEE Trans. on Signal Processing, vol. 42, no. 11, November, 1994.
- [13] H. M. Ozaktas and D. Mendlovic (1993), "*Fourier Transforms of Fractional Order and Their Optical Implementation*," J. Opt. Soc. Am. A 10, pp. 1875-1881, 1993.
- [14] Ozaktas H. M., B. Barshan, D. Mendlovic, L. Onural (1994), "*Convolution, filtering, and multiplexing in fractional Fourier domains and their relation to chirp and wavelet transforms*," J. Opt. Soc. Am. A, vol. 11, no. 2, pp. 547-559, Feb. 1994.
- [15] Lohmann A. W. (1993), "*Image Rotation, Wigner Rotation, and the Fractional Fourier Transform*," J. Opt. Soc. Am. 10, pp. 2181-2186, 1993.
- [16] Pei S. C. and J. J. Ding (2007), "*Relations between Gabor Transform and Fractional Fourier Transforms and Their Applications for Signal Processing*," *IEEE Trans. on Signal Processing*, vol. 55, no. 10, pp. 4839-4850, Oct. 2007.

This academic article was published by The International Institute for Science, Technology and Education (IISTE). The IISTE is a pioneer in the Open Access Publishing service based in the U.S. and Europe. The aim of the institute is Accelerating Global Knowledge Sharing.

More information about the publisher can be found in the IISTE's homepage:

<http://www.iiste.org>

## CALL FOR PAPERS

The IISTE is currently hosting more than 30 peer-reviewed academic journals and collaborating with academic institutions around the world. There's no deadline for submission. **Prospective authors of IISTE journals can find the submission instruction on the following page:** <http://www.iiste.org/Journals/>

The IISTE editorial team promises to review and publish all the qualified submissions in a **fast** manner. All the journals articles are available online to the readers all over the world without financial, legal, or technical barriers other than those inseparable from gaining access to the internet itself. Printed version of the journals is also available upon request of readers and authors.

### IISTE Knowledge Sharing Partners

EBSCO, Index Copernicus, Ulrich's Periodicals Directory, JournalTOCS, PKP Open Archives Harvester, Bielefeld Academic Search Engine, Elektronische Zeitschriftenbibliothek EZB, Open J-Gate, OCLC WorldCat, Universe Digital Library, NewJour, Google Scholar

