

**OIST**OKINAWA INSTITUTE OF SCIENCE AND TECHNOLOGY GRADUATE UNIVERSITY
沖縄科学技術大学院大学

Loop-gap microwave resonator for hybrid quantum systems

Author	Jason R. Ball, Yu Yamashiro, Hitoshi Sumiya, Shinobu Onoda, Takeshi Ohshima, Junichi Isoya, Denis Konstantinov, Yuimaru Kubo
journal or publication title	Applied Physics Letters
volume	112
number	20
page range	204102
year	2018-05-14
Rights	(C) 2018 The Author(s). This article may be downloaded for personal use only. Any other use requires prior permission of the author and AIP Publishing. This article appeared in Applied Physics Letters, 112, 20, 204102 (2018) and may be found at https://aip.scitation.org/doi/10.1063/1.5025744
Author's flag	publisher
URL	http://id.nii.ac.jp/1394/00000784/

doi: [info:doi/10.1063/1.5025744](https://doi.org/10.1063/1.5025744)

Publisher's Note: "Loop-gap microwave resonator for hybrid quantum systems" [Appl. Phys. Lett. 112, 204102 (2018)]

Cite as: Appl. Phys. Lett. 113, 039903 (2018); <https://doi.org/10.1063/1.5048381>

Submitted: 11 May 2018 . Published Online: 20 July 2018

Jason R. Ball , Yu Yamashiro , Hitoshi Sumiya , Shinobu Onoda, Takeshi Ohshima , Junichi Isoya, Denis Konstantinov, and Yuimaru Kubo 



View Online



Export Citation



CrossMark

ARTICLES YOU MAY BE INTERESTED IN

[Loop-gap microwave resonator for hybrid quantum systems](#)

Applied Physics Letters **112**, 204102 (2018); <https://doi.org/10.1063/1.5025744>

[Publisher's Note: "The bimodal distribution spin Seebeck effect enhancement in epitaxial \$\text{Ni}_{0.65}\text{Zn}_{0.35}\text{Al}_{0.8}\text{Fe}_{1.2}\text{O}_4\$ thin film" \[Appl. Phys. Lett. 112, 142406 \(2018\)\]](#)

Applied Physics Letters **113**, 039902 (2018); <https://doi.org/10.1063/1.5046678>

[Exclusion of injection efficiency as the primary cause of efficiency droop in semipolar \(\$2\bar{0}\bar{2}\bar{1}\$ \) InGaN/GaN light-emitting diodes](#)

Applied Physics Letters **113**, 031101 (2018); <https://doi.org/10.1063/1.5036761>



Lake Shore
CRYOTRONICS

8600 Series VSM

For fast, highly sensitive
measurement performance

[LEARN MORE](#) 

2017
**R&D
100
WINNER**

Publisher's Note: "Loop-gap microwave resonator for hybrid quantum systems" [Appl. Phys. Lett. 112, 204102 (2018)]

Jason R. Ball,¹ Yu Yamashiro,^{1,2,a)} Hitoshi Sumiya,³ Shinobu Onoda,⁴ Takeshi Ohshima,⁴ Junichi Isoya,⁵ Denis Konstantinov,¹ and Yuimaru Kubo^{1,6,b)}

¹Okinawa Institute of Science and Technology Graduate University, Onna, Okinawa 904-0495, Japan

²Department of Physics, University of the Ryukyus, Nishihara, Okinawa 903-0213, Japan

³Advanced Materials Laboratory, Sumitomo Electric Industries Ltd., Itami, Osaka 664-001, Japan

⁴Takasaki Advanced Radiation Research Institute, National Institutes for Quantum and Radiological Science and Technology, Takasaki, Gunma 370-1292, Japan

⁵Research Center for Knowledge Communities, University of Tsukuba, Tsukuba, Ibaraki 305-8550, Japan

⁶PRESTO, Japan Science and Technology (JST), Kawaguchi, Saitama 332-0012, Japan

(Received 11 May 2018; published online 20 July 2018)

<https://doi.org/10.1063/1.5048381>

This article was originally published online on 14 May 2018. Due to a production error, the initially-published version contained an obsolete version of Fig. 4, displaying a Q_{ext} value

of 3000 instead of the correct 3500. AIP Publishing apologizes for this error. All online versions of the article were corrected on 18 May 2018, and it appears correctly in print.

^{a)}Present address: Department of Physics, Tokyo Institute of Technology, Oh-okayama, Meguro-ku, Tokyo 152-8551, Japan.

^{b)}Electronic mail: yuimaru.kubo@oist.jp.