



POLITECNICO DI TORINO
Repository ISTITUZIONALE

Integration of CUF Micromechanics Framework into NASMAT for Multiscale Analysis of Fiber-Reinforced Composites

Original

Integration of CUF Micromechanics Framework into NASMAT for Multiscale Analysis of Fiber-Reinforced Composites / Kaleel, I.; Petrolo, M.; Carrera, E.; Pineda, E. J.; Ricks, T. M.; Bednarczyk, B. A.; Arnold, and S. M.. - ELETTRONICO. - (2019). ((Intervento presentato al convegno Second International Conference on Mechanics of Advanced Materials and Structures - ICMAMS 2019 tenutosi a Nanjing, China nel 19-22 October 2019.

Availability:

This version is available at: 11583/2763012 since: 2019-10-23T11:26:15Z

Publisher:

Erasmus Carrera, Weiqiu Chen, Cun-Fa Gao, J.N. Reddy

Published

DOI:10.5281/zenodo.3516599

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Integration of CUF micromechanics framework into NASMAT for multiscale analysis of fiber-reinforced composites

I. Kaleel¹, M. Petrolo¹, E. Carrera^{1,*}, E. J. Pineda², T. M. Ricks², B. A. Bednarczyk², and S. M. Arnold²

¹ Politecnico di Torino, Torino, Italy 10129.

² NASA Glenn Research Center, Cleveland, OH, USA 44135.

* Corresponding author: erasmo.carrera@polito.it

Keywords: *Multiscale, Composites, Finite element*

The paper deals with the integration of micromechanics framework developed within the scheme of Carrera Unified Formulation (CUF) into NASA Multiscale Analysis Tool (NASMAT), a new state-of-the-art multiscale framework developed at the NASA Glenn Research Center. NASMAT is intended to be an open-platform, multiscale modeling framework for use on high performance computing systems. Although NASMAT already includes several semi-analytical micromechanics theories [1], one of the primary software development goals behind NASMAT is interoperability with other research and commercial codes. The current work demonstrates the integration of a fully-numerical model, CUF, into the NASMAT framework. The CUF micromechanics framework can effectively capture nonlinear behavior of composite at microscale through component-wise modeling technique. The CUF models are able to resolve accurate three-dimensional strain and stress fields at a reduced computational cost, for instance, approximately one to two orders of magnitude of degrees of freedom less as compared to standard 3D brick elements [2]. Figure 1 compares the transverse stress fields (σ_{22}) for different micromechanics model within NASMAT, namely HFGMC (High-fidelity Generalized Method of Cells) and CUF, for square-packed RVE under transverse tension loading. A numerical




Figure 1: Comparison of transverse stress fields (σ_{22}) under transverse loading condition for different micromechanics models within NASMAT

simulation campaign, including prediction of effective mechanical and thermal properties

of RVE and local resolution of stress fields, shall be undertaken to verify and evaluate the accuracy and efficiency of CUF models in comparison to analytical and semi-analytical micromechanics model within NASMAT.

References

- [1] Aboudi J, Arnold SM, Bednarczyk BA. *Micromechanics of Composite Materials: A Generalized Multiscale Analysis Approach*. Elsevier, Inc, 2013
- [2] Kaleel I., Petrolo M., Waas A.M., Carrera E., "Micromechanical Progressive Failure Analysis of Fiber-Reinforced Composite Using Refined Beam Models", *Journal of Applied Mechanics* (2018), 85.