



Faculty of Electrical Engineering

VOLTAGE SOURCE INVERTER SWITCHES FAULTS CLASSIFICATION AND IDENTIFICATION USING TIME- FREQUENCY DISTRIBUTIONS

Nur Sumayyah Binti Ahmad

Master of Science in Electrical Engineering

2016

**VOLTAGE SOURCE INVERTER SWITCHES FAULTS CLASSIFICATION AND
IDENTIFICATION USING TIME-FREQUENCY DISTRIBUTIONS**

NUR SUMAYYAH BINTI AHMAD

**A thesis submitted
in fulfilment of the requirements for the degree of Master of Science in Electrical
Engineering**

Faculty of Electrical Engineering

UNIVERSITI TEKNIKAL MALAYSIA MELAKA

2016

DECLARATION

I declare that this thesis entitled “Voltage Source Inverter Switches Faults Classification and Identification Using Time-Frequency Distributions” is the result of my own research except as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in the candidature of any other degree.

Signature :

Name : Nur Sumayyah Binti Ahmad

Date :

APPROVAL

I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for award of Master of Science in Electrical Engineering.

Signature :

Supervisor Name : Prof Madya Dr. Abdul Rahim Bin Abdullah

Date :

DEDICATION

This is special dedicated to

My beloved husband,

Khairulzaman Bin Mohd,

my lovely son,

Nur Awfiyah Syahidah & Nur Awliya' Syahidah

my parents,

Ahmad Bin Nordin & Norizan Binti A. Bakar,

and my family for their continuous love and prayers,

also to all my friends for their patient, kindness and cooperation .

I wish to thanks all of you for your support during my studies in UTeM.

May God bless all of them.

ABSTRACT

Three-phase voltage source inverters (VSI) are utilized in a variety of industry applications. Although this technology has already achieved a certain level of maturity, due to their complexity and considering, three-phase VSI are often exposed to high stresses and unexpected faults may occur. Different types of faults occur in three-phase VSI such as open circuit, short circuit and gate misfiring that can influence reliability of entire system and disturb the performance. Hence, detection and classification of the three-phase VSI switches faults important for rectify failures and ensure the quality of power electronics system. This research presents the analysis of time-frequency distributions (TFDs) for three-phase VSI switches faults. The TFDs used are linear TFDs which are short time Fourier transform (STFT) and S-transform and bilinear TFD focusing on smooth-windowed Wigner-Ville distribution (SWWVD). The resulting time-frequency representations (TFRs) represent signals in the jointly time-frequency domains while the parameters of the signals are then estimated from the TFR. The signal parameters are instantaneous of root mean square (RMS) current, RMS fundamental current, average current, total waveform distortion (TWD), total harmonic distortion (THD) and total nonharmonic distortion (TnHD). From the signal parameters, the characteristics of the faults signals are calculated and are then used as input to a rule-based classifier to identify and classify the switches faults. The presented analysis is achieved by analyzing three-phase VSI for open and short circuit switches faults. In addition, based on the signal characteristics measurement, the best TFD is identified in terms accuracy, memory size and computation complexity used. Besides that, an experimental test also conducted to capture the real data for three-phase VSI switches faults. At the end of this research, the comparative analysis of three-phase VSI switches fault using TFDs is reported to highlight the strength and weakness of each technique. Then, the best and effective technique for detection, identification and classification of different types of three-phase VSI switches fault are discussed. The result shows that SWWVD is the best TFD technique for three-phase VSI switches faults detection and classification.

ABSTRAK

Penyongsang tiga-fasa (VSI) akan digunakan dalam pelbagai aplikasi industri. Walaupun teknologi ini sudah telah mencapai satu tahap kematangan, disebabkan oleh kerumitan, penyongsang tiga-fasa VSI seringkali terdedah kepada tekanan yang tinggi dan kerosakan yang tidak di jangka mungkin berlaku. Jenis kesalahan yang berlaku dalam penyongsang tiga-fasa seperti litar terbuka, litar pintas dan pintu misfiring yang boleh mempengaruhi kebolehpercayaan keseluruhan sistem dan mengganggu prestasi. Oleh itu, pengesanan dan pengenalanpastian kesilapan suis VSI penting untuk meminimumkan masalah ini. Kajian ini membentangkan analisis pengagihan masa-frekuensi TFDs) untuk kesilapan suis penyongsang tiga-fasa VSI. TFDs digunakan adalah TFDs linear yang masa pendek jelmaan Fourier (STFT) dan transformasi-s dan dwi-linear seperti pengagihan Wigner-Ville halus-berjendela (SWWVD). Representasi perwakilan masa-frekuensi (TFR) mewakili isyarat dalam domain masa kekerapan bersama manakala parameter isyarat maka dianggarkan dari TFR. Parameter isyarat adalah jumlah sertamerta semasa RMS, RMS asas semasa, purata semasa, herotan bentuk gelombang (TWD), jumlah herotan harmonic (THD) dan jumlah gangguan nonharmonic (TnHD). Daripada parameter isyarat tersebut, ciri-ciri isyarat kerosakan dikira dan digunakan sebagai input kepada pengelas berasaskan peraturan untuk mengklasifikasi dan mengenal pasti kerosakan suis. . Analisis yang dibentangkan dicapai dengan menganalisis penyongsang penyongsang tiga-fasa (VSI) untuk kesalahan litar terbuka dan litar pintas suis. Di samping itu, berdasarkan pengukuran ciri-ciri isyarat, TFD yang terbaik akan dikenalpasti dari segi ketepatan, kerumitan pengiraan dan saiz memori yang digunakan. Selain itu, ujian eksperimen juga dijalankan untuk menangkap data sebenar untuk penyongsang tiga fasa (VSI) suis kesalahan. Pada akhir kajian ini, analisis perbandingan kesalahan penyongsang tiga-fasa (VSI) menggunakan TFD di bincangkan mengenai kelebihan dan kelemahan bagi setiap teknik. Kemudian, teknik terbaik bagi pengesanan, pengenalan dan pengelasan untuk pelbagai jenis kesalahan suis penyongsang tiga-fasa (VSI) di bincangkan. Hasil kajian menunjukkan bahawa, SWWVD adalah TFD yang terbaik untuk pengesanan dan pengelasan bagi kesalahan suis penyongsang tiga-fasa (VSI).

ACKNOWLEDGEMENTS

Bismillaahirrahmaanirahim..

Praise be all to Allah SWT, the Most Gracious, the Most Merciful Shalawat and salam be to Rasulullah Muhammad saw. By the grace of Allah SWT, this research is finally completed to full fill the requirements for Master of Electrical Engineering.

I would like to take this great opportunity my warmest gratitude to my supervisor Prof Madya Dr.Abdul Rahim Bin Abdullah for his guidance, concern and strong support at all the time especially during the difficulties that I faced throughout the completion of this research. His enthusiasm has been a great source inspiration to me and gives me the great sense of honour to be under their wings. Thanks to Ministry of Education (MOE) and Universiti Teknikal Malaysia Melaka (UTeM) for providing the research grants RAGS/2012/FKE/TK07/1-B0011 and ERGS/1/2013/TK02/UTEM/02/02 to support the financial project.

Great thanks to my beloved husband, children, my parents and family for their patience, prayers, support and understanding over the entire period of my studies. Without them, this research would not have been possible.

TABLE OF CONTENTS

	PAGE
DECLARATION	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	viii
LIST OF APPENDICES	xiii
LIST OF SYMBOLS	xiv
LIST OF PUBLICATIONS	xvi
CHAPTER	
1 INTRODUCTION	1
1.1 Introduction	1
1.2 Problem Statements	4
1.3 Objectives of the Research	5
1.4 Scope of Works	6
1.5 Thesis Contributions	7
1.6 Thesis Outline	8
2 LITERATURE REVIEW	10
2.1 Introduction	10
2.2 Three-Phase Voltage Source Inverter	10
2.3 Three-Phase Voltage Source Switches Inverter Faults	11
2.3.1 Open Circuit Switches Fault of Voltage Source Inverter	13
2.3.2 Short Circuit Switches Fault of Voltage Source Inverter	14
2.3.3 Gate Misfiring Faults	15
2.4 Fault Detection Techniques for Voltage Source Inverter	16
2.5 Signal Processing Techniques	20
2.5.1 Fast Fourier transform	21
2.5.2 Short Time Fourier Transform	22
2.5.3 Spectrogram	23
2.5.4 Wavelet Transform	23
2.5.5 S-Transform	24
2.5.6 Bilinear Time-Frequency (Smooth-Windowed Wigner-Ville Distribution)	25
2.6 Summary	26

3	RESEARCH METHODOLOGY	28
3.1	Introduction	28
3.2	Modelling of Three-Phase Voltage Source Inverter Fault	30
3.2.1	Pulse Width Modulation	32
3.2.2	Fault Generation	33
3.2.3	Modelling of Voltage Source Inverter using Simulink MATLAB	36
3.3	Fast Fourier Transform	38
3.4	Time-Frequency Distribution	38
3.4.1	Short Time Fourier Transform and Spectrogram	38
3.4.2	S-Transform	41
3.5	Bilinear Time-Frequency Distribution	44
3.5.1	Smooth-Windowed Wigner-Ville Distribution	44
3.5.2	Performance Measurement of Kernel Parameters	46
3.5.3	Kernel Analysis in Time-Lag Representation	47
3.5.3.1	Bilinear Product of Voltage Source Inverter Fault System	48
3.6	Signal Parameter	50
3.6.1	Instantaneous RMS Current	51
3.6.2	Instantaneous Average Current	51
3.6.3	Instantaneous RMS Fundamental Current	51
3.6.4	Instantaneous Total Nonharmonic Distortion	52
3.6.5	Instantaneous Total Harmonic Distortion	52
3.6.6	Instantaneous Total Waveform Distortion	52
3.7	Characteristic Voltage Source Inverter Switches Fault Signal and Classification	53
3.8	Performance Measurement Time-Frequency Distribution	56
3.8.1	System Accuracy	56
3.8.2	Computation Complexity	57
3.8.3	Memory Size	58
3.9	Experimental Setup	58
3.9.1	General Hardware Configuration	58
3.9.2	Data Logger System	60
3.9.3	Experimental Testing	62
3.10	Summary	63
4	RESULTS AND DISCUSSION	65
4.1	Introduction	65
4.2	Three-Phase Voltage Source Inverter Faults Signal	67
4.2.1	Open Circuit Fault for Three-Phase Voltage Source Inverter	67
4.2.2	Short Circuit Fault for Three-Phase Voltage Source Inverter	68
4.3	Analysis Voltage Source Inverter Signal using Fast Fourier Transform	70
4.4	Analysis Voltage Source Inverter Signal using Linear and Bilinear Time-Frequency Distribution (TFDs)	71
4.4.1	Signal Analysis of VSI Fault using Short Time Fourier	71

	Transform	
4.4.2	Signal Analysis of VSI Fault using S-transform	78
4.4.3	Signal Analysis of VSI Fault using Smooth-Windowed Wigner – Ville Distribution	84
4.5	Performance Comparison Analysis of Time-Frequency Distribution	91
4.5.1	Accuracy	91
4.5.2	Computation Complexity	92
4.5.3	Memory Size	94
4.5.4	The Best Time-Frequency Distribution	96
4.6	Classification of Switches Faults Signal	97
4.7	Experimental Testing	101
4.8	Performance Verification of Switches Fault	115
4.9	Summary	122
5	CONCLUSION AND RECOMMENDATION	124
5.1	Conclusion	116
5.2	Recommendation	126
	REFERENCES	127
	APPENDIX	139

LIST OF TABLES

TABLE	TITLE	PAGE
2.1	Summary of Signal Processing Techniques	26
3.1	The Switching Signal of Voltage Source Inverter	33
3.2	The State of Switching for Voltage Source Inverter Switches Fault	35
3.3	Frequency Band for Short Time Fourier Transform	40
3.4	Frequency band for S-transform	42
3.5	Minimum Threshold for Every VSI Switches	54
3.6	Example of Characteristics Signal Between Threshold	56
4.1	Power Spectrum of Signal Three-Phase Voltage Source Inverter Switches Fault	70
4.2	MAPE of Simulation Results for the Signal Characteristics	91
4.3	Example of Calculation Computation Complexity for Linear TFDs	92
4.4	Computation Complexity of the Switches Faults Signal Analysis	93
4.5	Example of Calculation Computation Complexity for Linear TFDs	94
4.6	Memory Size of TFRs for STFT ,S-transform and SWWVD	95
4.7	The Data Collection for Classification using STFT, S-transform and SWWVD	98
4.8	Calculation of Performance Classification of TFDs	100
4.9	Performance of Switches Fault Signal Classification Between STFT, S-Transform and SWWVD	101

LIST OF FIGURES

FIGURE	TITLE	PAGE
1.1	Flowchart of General the Research Background	3
2.1	Circuit of Voltage Source Inverter	10
2.2	(a) 3-D View Cross-Sectional View (b) Typical IGBT Power	11
2.3	(a) Failure Distribution (b) Fragile Component Distribution	12
2.4	Circuit of Open Circuit Switches Fault Voltage Source Inverter	14
2.5	The output current (a) S11 (b) S12	14
2.6	Circuit of Short Circuit Switches Fault Voltage Source Inverter	15
2.7	Fault Detection System Based on ANN Technique	18
2.8	The circuit of IGBT Fault Detection	19
3.1	Flowchart of the Analysis, Classification and Identification of Switches Fault	29
3.2	Topology of a Three Phase Voltage Source Inverter	31
3.3	The Pulse Width Modulation Signal	32
3.4	Topology of Open Circuit Switches Faults for Voltage Source Inverter	34
3.5	Topology of Short Circuit Switches Fault for Voltage Source Inverter	35
3.6	The Design of Pulse Width Modulation	36
3.7	The Design of Open Circuit Switches Fault Voltage Source Inverter (Upper Switch)	36
3.8	The Design of Fault Generation	37

3.9	The Modelling of Short Circuit Fault Voltage Source Inverter (Lower Switch)	37
3.10	Time-Frequency Characteristics of Short Time Fourier Transform	40
3.11	Variation of Gaussian Window Wide	42
3.12	Time-Frequency Resolution of S-transform	43
3.13	Time-Frequency Characteristics of S-transform	43
3.14	Performance Measurements Used in the Analysis	46
3.15	Bilinear Product of the VSI Faults Signal (The Auto-Terms are Highlighted in Green While the Cross-Terms are Densely Dotted)	48
3.16	Flow Chart of Experimental Voltage Source Inverter	59
3.17	(a) The Structure of Experimental Voltage Source Inverter (b) The Schematic of Inverter Circuit	60
3.18	Block Diagram in Lab View Software	61
3.19	Front Panel of Voltage Source Inverter	62
3.20	The Experimental Setup for Three-Phase Voltage Source Inverter	63
4.1	Analysis Results of This Research	66
4.2	Open Circuit Switches Fault Signal (S ₁₁ switch)	67
4.3	Open Circuit Switches Fault Signal (S ₃₂ switch)	68
4.4	Short Circuit Switches Fault Signal (S ₂₁ switch)	69
4.5	Short Circuit Switches Fault Signal (S ₁₂ switch)	69
4.6	Signal Open Circuit Switches Fault (S ₁₁)	72
4.7	Time-Frequency Representation (TFR)	72
4.8	(a) Instantaneous RMS Current (b) Instantaneous RMS Fundamental Current (c) Instantaneous Average Current	73
4.9	(a) Instantaneous Total Waveform Distortion (b) Instantaneous Total Harmonic Distortion, (c) Instantaneous Total nonharmonic Distortion	74
4.10	(a) Short Circuit Faults of the Upper Switch Signal (b) Time-Frequency Distribution (c) Instantaneous of RMS Current, (d) Instantaneous of Fundamental RMS Current, (e) Instantaneous of RMS Average Current	77

	Current,(f)Instantaneous of Total Waveform Distortion, (g) Instantaneous of Total Nonharmonic Distortion and (h) Instantaneous of Total Harmonic Distortion	
4.11	Short Circuit Switches Fault Signals (S ₂₁)	78
4.12	Time-Frequency Representation (TFR)	78
4.13	(a) Instantaneous of Average Current, (b) Instantaneous of RMS Current and (c) Instantaneous of RMS Fundamental Current	79
4.14	(a) Instantaneous of Total Harmonic Distortion, (b) Total Nonharmonic Distortion and (c) Total Waveform Distortion	80
4.15	(a) Open Circuit Switches Fault Signal (b) Time-Frequency Representation	81
4.16	(a) Instantaneous of RMS Current, (b) Instantaneous of RMS Fundamental Current and (c) Instantaneous of Average Current	82
4.17	(a) Instantaneous of Total Harmonic Distortion, (b) Instantaneous of Total Nonharmonic Distortion (c) Instantaneous of Total Waveform Distortion	83
4.18	(a)Signal of Open Circuit Switches Faults (S ₃₁) (b) Time-Frequency Representation (TFR) (c) Instantaneous of Average Current (d) Instantaneous of RMS Current,(e) Instantaneous of RMS Fundamental Current	86
4.19	(a) Instantaneous of Total Harmonic Distortion, (b) Instantaneous of Total nonharmonic Distortion (c) Instantaneous of Total Waveform Distortion	87
4.20	(a) Short Circuit Switches Faults (S ₂₂) (b) Time-Frequency Representation (TFR) (c) Instantaneous of Average Current, (d) Instantaneous of RMS Current (e) Instantaneous of RMS Fundamental Current	89
4.21	(a) Instantaneous of Total Harmonic Distortion, (b) Instantaneous of Total nonharmonic Distortion (c) Instantaneous of Total Waveform Distortion	90
4.22	MAPE of Signal Characteristics	92
4.23	Average of Computation Complexity Used For Switches Faults Analysis	93
4.24	Average of Memory Size Used For The Switches Faults Signals	95
4.25	Comparison of STFT , S-transform and SWWVD in Terms of Accuracy, Memory Size and Computation Complexity of Analysis	97

4.26	The Signal for Real Time No Fault Condition	102
4.27	The Signal of Experimental Open Circuit Switches Fault (S ₁₁)	103
4.28	Time-Frequency Representation using (a) Short Times Fourier Transform (b) S-Transform (c) Smooth-Window Wigner-Ville Distribution	104
4.29	Instantaneous of Average Current Signal using (a) Short Times Fourier Transform (b) S-Transform (c) Smooth- Window Wigner-Ville Distribution	106
4.30	Instantaneous of RMS Current using (a) Short Times Fourier Transform (b) S-Transform (c) Smooth-Window Wigner-Ville Distribution	107
4.31	Instantaneous of RMS Fundamental using (a) Short Times Fourier Transform (b) S-Transform (c) Smooth-Window Wigner-Ville Distribution	109
4.32	Instantaneous of Total Waveform Distortion using (a) Short Times Fourier Transform (b) S-Transform (c) Smooth-Window Wigner-Ville Distribution	111
4.33	Instantaneous of Total Harmonics Distortion using (a) Short Times Fourier Transform (b) S-Transform (c) Smooth-Window Wigner-Ville Distribution	113
4.34	Instantaneous of Total Nonharmonic Distortion (a) Short Times Fourier Transform (b) S-Transform (c) Smooth-Window Wigner-Ville Distribution	114
4.35	Three-Phase Switches Faults Signal (a) Simulation and (b) Experimental	115
4.36	Time-Frequency Representation (a) Simulation (b) Experimental	116
4.37	Instantaneous of Average Current Signal (a) Simulation (b) Experimental	117
4.38	Instantaneous of RMS Current Signal (a) Simulation (b) Experimental	118
4.39	Instantaneous of RMS Fundamental Current Signal (a) Simulation (b) Experimental	119
4.40	Instantaneous of Total Harmonic Distortion (a) Simulation (b) Experimental	120
4.41	Instantaneous of Total Nonharmonic Distortion (a) Simulation	121

(b) Experimental

4.42 Instantaneous of Total Waveform Distortion (a) Simulation
(b) Experimental

122

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	The example of time-frequency representation of short times Fourier transform with different window	139
B	The examples of time-frequency distribution representation using time-frequency distribution (Short time Fourier transform)	140
C	The examples of time-frequency distribution representation using time-frequency distribution (S-transform)	146
D	The examples of time-frequency distribution representation using time-frequency distribution (Smooth-Windowed Wigner-Ville Distribution)	155
E	Data of simulation analysis	161
F	Project Achievement	174

LIST OF SYMBOLS

A	-	Ampere
ms	-	milliseconds
t	-	Time
f	-	Frequency
f_0	-	Fundamental frequency
f_r	-	Frequency resolution
f_s	-	Frequency sampling
Kx	-	Bilinear product of a signal
Td_{fault}	-	Duration of fault
Tr	-	Time resolution
$w(t)$	-	Window function
FFT	-	Fast Fourier transform
TFD	-	Time frequency distribution
TFR	-	Time frequency representation
STFT	-	Short time Fourier transform
SWWVD	-	Smooth-Windowed Wigner-Ville Distribution
WT	-	Wavelet transform
$x(t)$	-	Observation window in continuous
$I_{ave}(t)$	-	Instantaneous average current

$I_{rms}(t)$	-	Instantaneous root means square current
$I_{lrms}(t)$	-	Instantaneous root means square fundamental current
$ITnHD(t)$	-	Instantaneous total nonharmonic distortion current
$ITHD(t)$	-	Instantaneous total harmonic distortion current
$ITWD(t)$	-	Instantaneous total waveform distortion current
pu	-	Per-unit
THD	-	Total harmonic distortion
$TnHD$	-	Total nonharmonic distortion
TWD	-	Total waveform distortion
AC	-	Alternating Current
DAQ	-	Data acquisition
DC	-	Direct current
PWM	-	Pulse width modulation
MAPE	-	Mean absolute percentage error
VSI	-	Voltage source inverter

LIST OF PUBLICATIONS AND AWARDS

A. Journal & Conferences

1. N.S.Ahmad , A.R.Abdullah, E.F.Shair, A.Jidin (2013),” Open Switch Fault Analysis in Voltage Source Inverter using Spectrogram” International Power Engineering and Optimization Conference (PEOCO), 3-4 June 2013, Pg 438-443
2. N. S. Ahmad, A. R. Abdullah, N. H. Bahari, Mr. M. Manap, A. Jidin, M. H. Jopri, “Short Circuit Faults Analysis in Voltage Source Inverter using Spectrogram”, International Conference on Electrical Machines and Systems 2013 (ICEMS 2013), 26-29 October 2013, Busan, Korea
3. N. S. Ahmad, A. R. Abdullah, N. Bahari, M. A. A. Hassan (2014), “ Switched Faults Analysis of Voltage Source Inverter (VSI) using Short Time Fourier Transform (STFT), International Review of Modelling and Simulations (I.RE.MO.S), Vol. 7, N. 3 June 2014

4. N. S. Ahmad, A. R. Abdullah, N. Bahari (2014), "Open and Short Circuit Switches Fault Detection of Voltage Source Inverter Using Spectrogram", Journal of International Conference on Electrical Machines and Systems, Vol. 3, Issue. 2, Pg. 190-199.
5. N. S. Ahmad, A. R. Abdullah, N. Bahari, S.Daud, M.A.A.Hassan (2014), "Voltage Source Inverter Fault Detection System Using Time Frequency Distribution", Journal of International Conference on Design and Concurrent Engineering

B. Other Publication

1. M. Manap, A. R. Abdullah, N. Z. Saharuddin, N. A. Abidullah, N. S. Ahmad, N. Bahari, " Voltage Source Inverter Switches Faults Analysis Using S-Transform" Applied Mechanics and Materials Journal, 2014.
2. M. Manap , N. S. Ahmad, A. R. Abdullah, N. Bahari (2015), "Comparison of Open and Short-Circuit Switches Faults Voltage Source Inverter Analysis Using Time-Frequency Distributions" Applied Mechanics and Materials Journal, 2015.
3. M. Manap, A. R. Abdullah, N. Z. Saharuddin, N. A. Abidullah, N. S.Ahmad, M. H. Jopri, "Performance Comparison of VSI Switches Faults Analysis Using STFT and S transform" Applied Mechanics and Materials Journal, 2015.

C. Awarded

1. Awarded i-ENVEX 2014 silver medal for the invention “Voltage Source Inverter-Fault Detection System (VSI-FaDS)” at International Engineering Invention & Innovation Exhibitions (i-ENVEX) on 11-13th of April 2014, Universiti Malaysia Perlis, UNIMAP.
2. Awarded INNOFEST 2014 special award for the invention “Voltage Source Inverter- Fault Detection System (VSI-FaDS)” on 18th May 2014, Universiti Teknikal Malaysia Melaka (UTeM)

CHAPTER 1

INTRODUCTION

1.1 Introduction

The voltage source inverter (VSI) is increasingly used in powered wheelchairs, electric vehicles, aerospace, medical and military applications, and nuclear power plants due to its advantages such as high power density, efficiency and simple control. In this application, because the fault can result in huge damages to the human life and environments, the reliability of the drives is one of the most important factors to guarantee the safe, continuous and high performance operation under even some faults. Generally, when a fault occurs, the drive system has to be stopped for emergency or non-programmed maintenance schedule. Due to the high cost of unexpected maintenance, the development of a reliable system is the area of interest (UiMin et al., 2015 and B.Tabbache et al. 2014).

A prompt and accurate diagnosis of faults is needed to ensure the reliability of power electronics and reduce the risk of failure (Iannuzzo et al., 2013). To keep the power electronics reliability at a higher level, an accurate technique is required to determine, classify and diagnose the problem. According to data provided, the reliability of power electronic devices is very important because semiconductor failure and soldering joint failure in power devices take up 34% of power electronics system failures and 38% of faults in variable-speed drives are due to failure of power devices. Besides, statistical data also shows that 63% of the inverter experience faults within the first year of operation