Recent Research in Science and Technology 2014, 6(1): 153-156 ISSN: 2076-5061 Available Online: http://recent-science.com/



Remote sensing and GIS in disasters management-in special reference to Asian countries

Rajesh Shrivastava

Principal (In-charge), Lakhmi Chand Institute of Technology, Bilaspur, (C.G) India

Abstract

During the past five decades, natural hazards such as floods, earthquakes, severe storms and tropical cyclones, droughts, wild land fires, and also manmade disasters such as Nuclear disaster, oil spills, and terrorist attacks have caused major loss of human lives and livelihoods, the destruction of economic and social infrastructure, as well as environmental damages. Disaster reduction is both an issue for consideration in sustainable development agenda and a cross cutting issue relating to social, economic, environmental and humanitarian sectors. These important features have to analyze and there is a need to study. Though, in recent years the Open GIS technology standards have been developed by several agencies, which provide the basis for utilization of geographic information services, also gives an opportunity for data interoperability, data integration and data sharing between different emergency management agencies, However finding suitable services and visualization of geospatial information for decision makers is still a crucial task. Objective of this paper is to assess the state of art literature review in different methodologies of utilizing geospatial technology in managing both natural and manmade disasters dedicated by different authors and also to find new direction in this important area.

Keywords: Natural disasters, Geographical Information system, man-made disasters, Nuclear disaster

INTRODUCTION

A disaster is defined as a serious disruption of the functioning of a community or a society causing widespread human, material, economic or environmental loss that exceed the ability of the affected community or society to cope using its own resources. Disasters interrupt the society by claiming lives, creating victims and destroying infrastructures and houses. Disasters also have negative impacts on the environment as they affect natural resources. Therefore, considering society, economy and environment as the three main components of sustainable development, disasters have a negative impact on sustainable development which making appropriate management of disaster a necessity.

When a disaster occurs, funds and budgets that have been assigned for development purposes are diverted to respond to that disaster and returning quality of life to normal. It is estimated that 70– 80% of information is resolvable to geographic location, therefore the nature and characteristics of geographic information (GI), and the way in which it is used, is paramount in managing crises effectively. Therefore spatial data and related technologies have proven to be crucial for effective collaborative decision-making in disaster management. However, current studies show that although spatial data can facilitate disaster management, there are substantial problems with collection, access, dissemination and usage of required spatial data for disaster management. Such problems become more serious in the disaster response phase with its

Rajesh Shrivastava Principal (In-charge), Lakhmi Chand Institute of Technology, Bilaspur, (C.G) India dynamic and time-sensitive nature.

Natural and manmade disasters

Disasters may be natural or manmade. Natural disaster like earthquake, flood, tsunami, etc will occur and it is not possible to prevent them. Nevertheless their effect on human health and property can be mitigated effectively if appropriate anticipatory measures based on Geospatial technology in a timely, coordinated manner is planned and implemented in each phase of operation like relief, rehabilitation and reconstruction. Earthquakes are caused by the motion of tectonic plates - individual sections that make up the earth's surface like panels on a football. Immense strain accumulates along fault lines where adjacent plates meet. When the rock separating the plates gives way, sudden seismic ground-shaking movements occur. The point where the seismic activity occurs is the epicenter, where the earthquake is strongest. The seismic waves usually travel out from the epicenters, sometimes creating widespread destruction as they pass. Earthquakes lead the list of natural disaster in terms of damage and human loss and they affect very large areas, causing death and destruction on a massive scale. Cyclones are the deadliest of all natural disasters worldwide associated with strong winds, storm surges, heavy precipitation and floods. The property damage caused by winds depends on quality of construction and maximum wind speed. Storm surges which are rapid increase in sea-level along the coast due to strong winds driving the water ashore cause maximum damage. When rain falls, it drains down from hillside to streams, along rivers and out into sea. When this rainfall is incessant, the land becomes saturated and the natural drainage system fails. The upper reaches of rivers quickly fill and force the excess water downstream. In the lower reaches water flows slower. Here the river swells and begins to break its banks.

^{*}Corresponding Author

This results in flooding of the plains especially the low-lying flat wide areas in the lower reaches of a river.

A tsunami is a chain of fast moving waves caused by sudden trauma in the ocean. They can be generated by earthquakes, volcanic eruption or even impact of meteorites. Tsunamis are not tidal waves as they are not caused by changes in tides. They are most common around the edge of the Pacific, where more than half the world's volcanoes are found. These seismic surges can assault coastlines, often with little or no warning. Tsunamis are rare in the Indian Ocean. The tsunami of December 2004 started with an earthquake off the north Sumatra Coast which generated devastating tsunami waves affecting several countries in South East Asia. Landslides are frequent and annually recurring phenomenon in hilly areas. Outward and downward movement of mass, consisting or rock and soils, due to natural or man-made causes is termed as landslide. High intensity rainfall triggered most of the landslides. As long as landslides occur in remote, unpopulated regions, they are treated as just another denudation process sculpting the landscape, but when occur in populated regions; they become subjects of serious study. Most of the landslides occur due to exhaustive deforestation for the development of urbanization and plantation. In these areas rainwater directly penetrates into the soil and cause landslides.

Among the manmade disasters, probably the most devastating (after wars) are industrial disasters. These disasters may be caused by chemical, mechanical, civil, electrical or other process failures in an industrial plant due to accident or negligence, which may cause widespread damage within and/or outside the plant. The worst example globally was the Methyl Iso-cynate gas leak in 1984 from the Union Carbide Factory in Bhopal which has so far claimed more than 20,000 lives and injured few million personals besides stunting the growth of a generation born from the affected population. This disaster triggered a completely new legal regime and practices for preventing such disasters. With increased emphasis on power generation through nuclear technology, the threat of nuclear hazards has also increased. The Department of Atomic Energy (DAE) has been identified as the nodal agency in the country in respect of manmade radiological emergencies in the public domain. Nuclear facilities in India have adopted internationally accepted guidelines for ensuring safety to the public and environment. Apart from this there is also a threat of nuclear disaster through terrorist attack in any of the major cities in India. To overcome this kind of disasters proper decision support system is essential.

Disaster management using GIS

Most of the Natural and manmade Disaster management activities can be accomplished faster by the help of Geographic Information system (GIS), a computerized data base, analyze and visualization system of spatial data. Geographic Information Systems (GIS) provide a range of techniques which allow ready access to data, and the opportunity to overlay graphical location-based information for ease of interpretation. They can be used to solve complex planning and management problems. The disaster management consists of three important phases as Pre disaster phase (planning, preparedness and mitigation), On-Disaster phase or impact phase (response, recovery, evacuation, etc.) and post disaster phase (Rehabilitation, damage Assessment, providing food and medical facilities, etc). All phases of emergency management (reduction, readiness, response and recovery) can benefit from GIS, including applications related to disaster management systems, a critical element in managing effective lifelines in an emergency. Considering GIS as underpinning technology for spatial technologies and its role in facilitating data collection and storage as well as facilitating decision-making based on spatial data processing and analysis, GIS is a good tool for improving decision-making for disaster management.

The Geographic Information System (GIS) - based methodologies are now being developed for disaster loss estimation and risk modeling. These data can be used not only for real - time damage assessment but also for long term planning of efficient land use measure and adoption of building codes (minimum construction standards) or retrofitting methods. The easy availability of such maps, which include details of infrastructure, roads, hospital, school, shelters, engineering structure etc. simplify disaster management and rehabilitation efforts.

In this paper, we survey the literature to identify potential research directions in disaster operations, discuss relevant issues, and provide a starting point for interested researchers. From the literature review it has been concluded the most of the authors worked on the following unique three phases of disaster.

Pre-disaster Phase

Prevention or mitigation is not at all possible for most of the disasters. The time for warning, protective action and possible evacuation of the population may be possible just before the disaster strikes. The effectiveness of protective actions will largely depend on the level of preparedness of the population particularly at community level. The community must be prepared to understand and react to the warning. Sudden natural disasters often do not allow enough time for the implementation of protective measures. In long - term disasters or when an Early Warning System in effective, protective measure will depend on the awareness and preparedness of the community, of the local authorities and of the health staff. During this phase, several activities such as mapping of potential risks, Vulnerability analysis Inventory of existing resources were prepared using GIS.

On-disaster Phase

The movement the disaster strikes is time for destruction, injury and death. It may last a few seconds, as is the case of earthquakes, or days or weeks as is the case of floods and drought. The effects of the impact on healthy vary widely according to several factors, such as the nature of the disaster itself, population density, pre-disaster health and nutritional status, climate, organization of health services, etc. Immediately after impact is the time for rescue, relief and assistance to the victim. In the immediate post-impact period, the local community is isolated and many of the most pressing rescue tasks are accomplished by the survivors themselves with the locally available resources. GIS can be effectively utilized to analyze the worst situation. Shortest route and the emergency evacuation route maps were generated using GIS to serve the affected community.

Post-disaster Phase

The relief phase should lead to the Damage assessment, rehabilitation, reconstruction, rebuilding and restoring of pre-disaster conditions. Damage assessment for residential buildings and

infrastructures may be done for predicting total property damage to the city. For this the latest remote sensing data collected after disaster is incorporated with GIS for generating new thematic maps. Initiatives towards rehabilitation should start immediately after the impact phase and gradually increase during the emergency and reconstruction phases. The rehabilitation measure and their effects on the long-term global development of the affected community should be carefully considered. Too often, measures decided in a hurry tend to obstruct further re-establishment of normal living conditions. However, disasters can also have positive effects in the long run and be considered as an opportunity for development. The additional resources available, the new attitudes and cohesion developed by the community and the strengthening of operational capabilities at all levels can all be used to accelerate the development process of the affected country.




Fig 1. Flow Chart diagram for Disaster Management using GIS

LITERATURE REVIEW General

Disaster operations management is an increasingly important application area for the developing techniques of service science. This paper examines the use of topic maps, a semantic technology, within this environment, and provides a preliminary discussion of the benefits that its implementation can provide in the capture and exchange of contextual information.

Disaster response becomes more sophisticated, it is possible to envisage emergency coordination centres having their own remotely piloted vehicles (RPV) that can be launched from the roof of their building. Using existing technology, such an aircraft could be positioned using GPS and could carry a small video camera and transmitter, similar to that used by television companies for sporting events. One can envisage a computer display showing the digitized map of the disaster area with the position of the RPV superimposed. At the same time, an inset on the screen could show the video images transmitted by the RPV, giving the response coordinator first hand information from the site of the emergency. To calibrate the risk model, past casualties recorded were used. The final outputs include a set of indicators for measuring levels of risk on a country by country basis, a global database on hazard frequencies, an evaluation of the population exposed and the identification of socioeconomical parameters for estimating human vulnerability to natural hazards.

Role of Geospatial Technology in Earthquake Hazard Management

From their study insists, Geographical Information Systems (GIS) are in a state to be used almost in every phases of a disaster management. Creating the scenarios, determining the risks, generating the sustainable plans, implementing the applications are the examples to use GIS for mitigation phase of a disaster management cycle (DMC). Urban and regional planning activities also play important roles in mitigation phases. Similar to planning process, DMC mostly requires integrated data from multiple sources and coordinated institutional structure. Although GIS tools are able to handle different datasets for spatial analysis; integration of that data and organizing the institutes requires modern approaches or frameworks such as Spatial Data Infrastructures (SDI). Present a method of earthquake damage detection by comparing the optical images with panchromatic bands for the Gujarat, India earthquake, which occurred on January 8, 2001, before and after earthquake. They investigate the pre- and post- event satellite images through calculating the differences in the reflection intensity of the two images, which showed significant changes in the reflectance due to earthquake disaster

Role of Geospatial Technology in Flood Hazard Management

Satellite SAR image such as Radar sat SAR or ERS SAR is geometrically corrected and matched with the data from the GIS database such as land use or the geometrical-corrected Landsat TM image. The flood extent can be extracted from SAR image by visual interpretation or automatic extraction with support of DEM or Landsat TM. The flood extent can be overlaid with the data such as land use data from GIS database or Landsat TM and the results such as map and table can be obtained by using GIS. Peak-flow magnitude estimates enable the computation of corresponding flooded areas using Manning's equation and GIS processing. This —regression method is processed on two test-zones situated in North and South America

Role of Geospatial Technology in Coastal Hazard Management

The earthquake was followed by tsunami, surge of waves that killed nearly a quarter of a million people, mostly in Indonesia, Sri Lanka, and India. The earthquake shaking and subsequent tsunami caused substantial damage to structures that include buildings, harbors, overhead water tanks, seaport control towers, and so on. Other important structures, for example, dams, bridges, hangars, and so on, also suffered minor damage without disrupting their functioning. Reinforced concrete structures on the islands were the worst performers, while traditionally constructed timber and masonry structures performed well in response to ground shaking. The mandatory Indian Standards were not complied within the design of many recent structures on the islands located in the most severe seismic zone in India.

A study was conducted to review and evaluate existing emergency evacuation procedures for the Gulf Coast, and to make recommendations for the use of advance technologies to enhance evacuation procedures. An advisory committee of transportation and emergency management officials was involved throughout the project. The study included the examination of existing emergency evacuation plans, interviews with involved individuals and agencies, identification of technologies that can be adopted to improve planning and management of evacuations, simulation of evacuation traffic flows, and other technical steps.

Role of Geospatial Technology in Man Made Disasters Management

The Detonation of a Single Nuclear Bomb or - Warhead Would Cause a Local Disaster on a Scale That Few People in the World have seen and survived. The effect of a single bomb would depend on its power, and where it exploded - high in the air or at ground level and whether in a densely populated and built-up area like a city or in open country like an attack on a missile silo. The nuclear bombs available to the great military powers of the world range in power from several megatons down to a few kilotons. A megaton is the explosive power of one million tons of TNT. A kiloton is the power of one thousand tons of TNT. Bombs likely to be available to terrorist organizations or governments other than the great military powers would be in the 10- to 100-kiloton range. An atomic bomb explosion results in a great amount of damage due to blast and fire, followed by the highly radioactive fallout. At Chernobyl there was no nuclear detonation so the initial local damage was limited to the Unit 3 Reactor Building and adjacent structures. However, the amount of radioactive material released during the accident was far more than would have resulted from a nuclear explosion. The fire in the reactor core burned for approximately three weeks and a huge quantity of fallout was produced. Large areas around the power plant had to be abandoned and contamination was spread as far as Western Europe, Africa and the Far East.

CONCLUSION

In this paper a general review of disaster management for both natural and manmade disasters using Geospatial technology and Geographical Information system (GIS) was presented. From this literature review it has been concluded the most of the authors worked on the unique three phases of disaster management such as Pre disaster management, on disaster management and Post disaster management. This paper also concludes that using Geo spatial technology the disaster could not be able to completely mitigate but to some extent the administrators could use this technique for planning preventive measures before disaster and to react during emergencies situation. It is also appropriate to review the work so far accomplished in different fields of various disasters and to identify the necessary directions for future research.

REFERENCES

- Abdul Mannan, 2007. Preventing Nuclear Terrorism in Pakistan: Sabotage of a Spent Fuel Cask or a Commercial Irradiation Source in Transport, Pakistan Nuclear Regulatory Authority.
- [2] Akhilesh Pal, Michael H. Triche, Andrew Graettinger, Karri Veerabhadra Rao, John McFadden, and Daniel S. Turner, 2002. Enhancements to Emergency Evacuation Procedures, UTCA Report 01105.
- [3] Alan F. Phillips, 2003. Tthe Effects of a Nuclear Bomb Explosion on the Inhabitants of a City, Physicians for Global Survival (Canada).
- [4] Amini Hosseini. K, M. Hosseini, M.K. Jafari and S. Hosseinioon, 2009. Recognition of Vulnerable Urban Fabrics in Earthquake Zones: A Case Study of the Tehran Metropolitan Area, JSEE / winter Vol. 10, No. 4, Available online at: http://www.iiees.ac.ir/jsee
- [5] André Sabino, RuiNóbrega, Armanda Rodrigues & NunoCorreia, 2008. Life-Saver: Flood Emergency Simulator Proceedings of the 5th International ISCRAM Conference – Washington, DC, USA, F. Fiedrich and B. Van de Walle, eds.
- [6] www.google.com