

Multi-Objective Design Exploration and Aeroelastic Analysis for Next-Generation Regional Jet Development

著者	森野 裕行
号	58
学位授与機関	Tohoku University
学位授与番号	工博第004910号
URL	http://hdl.handle.net/10097/58900

氏名	もりの ひろゆき 森野 裕行
授与学位	博士(工学)
学位授与年月日	平成26年3月26日
学位授与の根拠法規	学位規則第4条第1項
研究科, 専攻の名称	東北大学大学院工学研究科(博士課程)航空宇宙工学専攻
学位論文題目	Multi-Objective Design Exploration and Aeroelastic Analysis for Next-Generation Regional Jet Development (次世代リージョナルジェット機開発のための多目的設計探査と 空力弾性解析)
指導教員	東北大学教授 大林 茂
論文審査委員	主査 東北大学教授 大林 茂 東北大学教授 澤田 恵介 東北大学教授 浅井 圭介 東北大学准教授 岡部 朋永

論文内容要旨

According to the recent jet fleet forecast, in the regional jet segment (60 – 99-seat class), the fleet size will rise from 1881 in 2012 to 3866 in 2032, and there will be demand for 3145 airplanes. The regional jet market is attractive to airframe manufacturers but there are many competitors in this class: CRJ700/900/1000 (Bombardier), ERJ170/190 (Embraer), ARJ21 (China's COMAC), and Superjet100 (Russian's Sukhoi). To compete for market share, new regional jets must meet strong demands on environmental friendliness, such as low fuel burn, low noise, and low emission.

In March 2008, Mitsubishi Heavy Industries, Ltd. (MHI) officially launched the Mitsubishi Regional Jet (MRJ), a next-generation regional jetliner, and Mitsubishi Aircraft Corporation was established by MHI to conduct MRJ's development and its business. The MRJ is the next generation regional jet designed by combining cutting-edge technologies in aerodynamic design, noise analysis, composite materials, and engines. With more than 20% higher fuel efficiency than conventional jets of the same class and a significant reduction in noise and emission gas, the MRJ excels both in operational economic efficiency and environmental friendly.

The development of MRJ, which is the first commercial jetliner in Japan, in addition to being the first Japanese passenger aircraft since the YS-11 produced 40 years ago. Therefore, an industrial-academic- government cooperation in Japan has been actively used to develop the cutting-edge technologies towards success of the MRJ project.

In the MRJ project, MHI and Tohoku University have developed the multidisciplinary design optimization (MDO) system and the multi-objective design exploration (MODE) approach was successfully applied to wing design and engine-wing integration. In these applications, both aerodynamic performance, such as aerodynamic

drag under cruising conditions, and structural weight were optimized with constraints of strength and flutter requirements, and useful knowledge regarding aerodynamic and structural wing design was successfully extracted. However, these previous MODE applications left room for further improvements in the following.

- Need to introduce detailed buckling evaluation using a realistic aircraft structure model
- Need to introduce more accurate but efficient aeroelastic analysis in transonic region
- Need to introduce aeroelastic analysis with structural nonlinearity due to control surface free-play

The objective of the present thesis is to establish the MODE method and advanced aeroelastic analysis methods for next-generation regional jet development. These methods are for the previous MODE improvements and should be applicable to the design process of a real aircraft. To achieve this goal, MODE focusing on structural design with buckling evaluation and aeroelastic reduced-order models (ROMs) for wing flutter and control surface limit cycle oscillation (LCO) have been proposed.

First, a MODE was performed for structural design of a regional jet horizontal tail. In this study, combination between the stringer-pitch and the rib-pitch was optimized based on detailed buckling evaluation and MSC/NASTRAN static analysis using a realistic aircraft structural model. The resulting Kriging model provided several solutions with improvements, in both the structural weight and the number of structural components, compared with the baseline design. Furthermore, visual data mining for the design space was performed using self-organizing map (SOM). SOM divided the design space into clusters with specific design features. With regard to the stringer-pitch, the particular pitch size was effective to reduce both the inboard and outboard weights. On the other hand, smaller and larger rib-pitch were effective to reduce the inboard and outboard weights, respectively. The present MODE application not only provided the optimal solutions, but also redefined the design problem itself from the fixed-rib-pitch problem into a rib-pitch variable problem for further improved design solution. The design knowledge acquired from the present application was utilized in the Mitsubishi Regional Jet (MRJ) horizontal tail design.

Next, a CFD-based aeroelastic ROM for a regional jet wing was proposed and validated by the experimental data as the second study. In this study, the unsteady aerodynamic state-space model was generated from aerodynamic responses to step excitation of individual mode using the eigensystem realization algorithm (ERA) system identification technique and connected to the structural dynamic state-space models within the MATLAB/SIMULINK environment to simulate combined static and dynamic aeroelastic responses. The present ROM was first validated for its capability to simulate aeroelastic responses of the AGARD 445.6 wing, not including the static aeroelastic effect, and showed excellent prediction of the aeroelastic responses compared to those computed directly using the full-order aeroelastic model of the Tohoku University Aerodynamic Simulation (TAS) code. The ROM was then validated using the transonic wind tunnel testing (WTT) data of a wing-pylon-nacelle (WPN) model. The step amplitudes for generating the unsteady aerodynamic ERA model were

chosen from the static aeroelastic solutions in the dynamic pressure range of interest and the initial generalized aerodynamic forces (GAFs) were computed directly from the restart of the steady rigid solution to simulate the static aeroelastic effects. Although the present ROM showed some discrepancies in the unsteady component of the aeroelastic responses at higher dynamic pressures, possibly due to insufficient step excitation amplitude of the first mode, the ROM provided good prediction of the combined static and dynamic aeroelastic responses and good agreement with the TAS solution on flutter speed, at which damping trend of the time histories of modal displacement shifts from stable to unstable. The present ROM can reduce the computation costs in simulating the aeroelastic responses of the wing and WPN configuration, including static aeroelastic effects, by more than one order of magnitude compared to the CFD-based full-order aeroelastic model. The present aeroelastic ROM appeared promising in enabling practical use of CFD-based flutter prediction in actual aircraft design.

In the next study, a CFD-based aeroelastic analysis method was proposed to simulate control surface LCO induced by free-play gap. The present method is based on the aeroelastic ROM proposed above and extended to treat structural nonlinearity due to the control surface free-play by generating the additional feedback line of generalized residual forces in the MATLAB/SIMULINK model. To reduce the problem size and computation time, the fictitious mass (FM) modal approach was used, which can afford the possible local change of stiffness. The present method was first validated for its capability to simulate aeroelastic responses of a regional jet horizontal tail (HT) model without free-play, and showed good prediction of flutter characteristics measured in the transonic flutter WTT. The present method was applied to the HT model with the elevator free-play gaps. Although there were some differences between computed and measured LCO ranges, the present method well predicted the nonlinear LCO behavior in its amplitude and frequency measured in the test and showed potential for accurate prediction of control surface LCO due to its free-play gap. The discrepancy in computed and measured LCO ranges is possibly due to inaccurate prediction of the static hinge moment and additional study is underway to fully understand the source of the discrepancy, focusing on CFD mesh quality, flow viscosity, and static aeroelastic deformation.

The methods developed in this study contributed to the development of a next-generation regional jet aircraft. The achievements described in this thesis will open the possibility of MODE approach and aeroelastic analysis for further detailed aircraft design and certification activities. For the future work, the prediction accuracy of static hinge moment by the present CFD should be further investigated with considering its effects on LCO characteristics. Moreover, the aeroelastic ROM methods proposed in Chapter 3 and Chapter 4 have to be validated in the MRJ flight testing towards the type certification activities. MODE approach with further improved aeroelastic analysis will be indispensable for future aircraft.

論文審査結果の要旨

リージョナルジェット機の市場は今後 20 年間で 3000 機以上の新規需要が見込まれており、日本においても三菱リージョナルジェット機 (MRJ) の開発が進められている。MRJ の開発では、三菱重工業と東北大学の共同研究成果として、数値流体力学 (CFD)、最適化技術、データマイニング手法を駆使した多目的設計探索 (MODE) が積極的に活用され、主翼の空力設計に大きく貢献した。しかし、これまでの MODE には、簡易構造モデルの使用、CFD 利用による計算時間の増大、空力弾性解析における線形構造モデルの使用という 3 つの課題が残されていることから、MRJ 開発における MODE の適用範囲は限定されてきた。本論文の研究はこの課題を克服することにより、MRJ のような次世代のリージョナルジェット機開発の設計において MODE の適用範囲を広げることを目的としている。本論文は、これらの研究成果をまとめたものであり、全編 5 章からなる。

第 1 章は序論であり、本研究の背景、目的および構成を述べている。

第 2 章では、第 1 の課題克服を目的として、詳細構造モデルによる座屈強度評価を MODE に導入し、MRJ 水平尾翼構造への設計適用を図っている。リブピッチとストリンガーピッチを設計変数、構造重量および部品点数の最小化を目的関数とした最適化を行い、軽量化および部品点数削減が可能な最適解を取得するとともに、リブを等間隔に配置するのではなく、リブ間隔を変更配置することでさらなる軽量化が期待できる、といった設計知見を取得している。これは、MODE が単なる最適化ではなく、設計問題そのものを改善できることを示したものであり、非常に有効かつ重要な成果である。

第 3 章では、第 2 の課題克服を目的として、CFD を用いた空力弾性縮約モデルを導入し、計算コストの増大を回避しつつ、遷音速域での主翼フラッター特性の推算精度を改善している。フラッター特性の推算精度改善は航空機の飛行安全性を損なうことなく、構造軽量化を進める上で必要不可欠であるため、MRJ 開発への適用に向けた重要な成果である。

第 4 章では、第 3 の課題克服を目的として、舵面ガタに代表される構造非線形を考慮した空力弾性解析を導入し、飛行中のリミットサイクル振動 (LCO) の解析予測を可能としている。民間航空機の型式証明では、LCO の発生を防止するために舵面に許容ガタ量を設定し、その妥当性を証明することが求められる。過度なガタ要求は航空機の点検や整備を頻繁に行うことをエアラインに強いることになるため、LCO 発生を回避できる必要最小限のガタ量を見極めることが重要となる。よって本研究成果は、型式証明が必要となる航空機開発にとって非常に有効である。

第 5 章は結論である。

以上要するに本論文は、次世代のリージョナルジェット機開発の設計において、詳細構造モデルの導入、縮約モデルによる CFD 計算時間の短縮、構造非線形を考慮した空力弾性解析法の構築により、MODE の適用範囲を広げることで、より高い商品競争力を備えた航空機の開発に貢献するものであり、航空宇宙工学の発展に寄与するところが少なくない。

よって、本論文は博士(工学)の学位論文として合格と認める。