

VIRTUAL FULL-DUPLEX MULTIPLE-INPUT MULTIPLE-OUTPUT RELAYING IN THE PRESENCE OF INTER-RELAY INTERFERENCE

IGBAFE ORIKUMHI

UNIVERSITI TEKNOLOGI MALAYSIA

VIRTUAL FULL-DUPLEX MULTIPLE-INPUT MULTIPLE-OUTPUT RELAYING
IN THE PRESENCE OF INTER-RELAY INTERFERENCE

IGBAFE ORIKUMHI

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Electrical Engineering)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

JUNE 2017

*To God Almighty, my dear family, friends and my lovely fiancée Juliet Ogele Yahaya.
Also, to my late aunt Tina Orikumhi your memories will always remain with us.*

ACKNOWLEDGEMENT

In every victory, let it be said of me, my source of strength and hope is Christ alone. Therefore, all glory to God almighty for the life and power to bring the doctorate program to a successful completion.

I would like to acknowledge my supervisor and mentor Dr. Leow Chee Yen (Bruce) for his guidance, encouragement, advice, patience and constructive comments which have been my moral boost throughout this PhD journey.

I would also like to acknowledge my friends in Southern Cross Gospel Chapel for their encouragement and support which has contributed immensely to the completion of my PhD program and improving my Bible knowledge. Of course, not forgetting Pastor Mike, Pastor Francis and Pastor Augustine of the Deeper Life Bible Church, for their constant concerns and prayers, God will continue to bless you all.

I also acknowledge the support of my entire family, not forgetting Precious, Deborah, Elisha, my dear cousins Joy, Abdul, Jemila and all my relatives who played an active role in my life, once again thank you all for your encouragements and motivation throughout this journey. You all are great and will always remain the best.

I would also like to acknowledge the support of my dear friends Marcus, Mercy Ugbah, Patience, Laraba, Bassey, Vera, Onome, Mutiu, Tunde, Lola, Florence, Dr. Richard, Dr. Andrew, Elijah, Charles, Visa, Obadiah, Daphne, Christella, Jonathan and Benjamin Yong, Hua Min, Dr. Mike David, Dr. Binfa, Dr. Jonathan, the entire Damisa's family, the entire Godwin's family, the entire family of Mr. and Mrs. Joel Oluwi, the entire family of Mr. and Mrs. Alfred Fowowe and the list goes on and on. For those wonderful friends whose names could not make the prints I also want to thank you for your moral support. I also acknowledge the entire members of the Wireless Communication Centre UTM for making the entire PhD journey a fun fare.

Finally, to my lovely fiancée Juliet Ogele Yahaya, thanks for all your support. Now that this chapter of my life is ending, I am fortunate that this chapter ended with sweet memories of someone as special as you.

ABSTRACT

Driven by the increasing demand for wireless broadband, low latency and power-efficient networks, multiple-input multiple-output (MIMO) full-duplex relaying (FDR) schemes have gained much attention in recent years. However, the performance of FDR schemes is impaired by sophisticated self-interference suppression techniques. As such, MIMO virtual FDR (VFDR) schemes have been considered as practical alternatives to recover spectral efficiency loss in half-duplex relays (HDR) without the need for sophisticated self-interference suppression algorithms. Successive relaying (SR) scheme is one of the VFDR techniques which uses a pair of HD relays that alternate between reception and retransmission of the source information to the destination. The performance of the SR based VFDR scheme is affected by inter-relay interference (IRI) due to the concurrent transmission of the source and relay nodes. The interference in VFDR schemes is conventionally treated as a degrading factor on the information decoding receivers resulting in the design of several interference avoidance and cancellation techniques. On the contrary, this thesis developed several VFDR schemes which exploit the interference to achieve performance improvement. In this study, interference management techniques, transmit/receive beamforming matrices, power allocation and joint optimisation algorithms were developed. First, a reliable MIMO VFDR scheme in the presence of IRI was designed, where the IRI was exploited for reliability improvements. The results showed significant reliability improvement over the existing schemes. Second, a joint power allocation for MIMO VFDR schemes under network power constraint was developed. The power allocation problem in the presence of IRI was formulated based on primal-dual algorithm. The results showed that the joint optimisation algorithm can efficiently utilise the network power when compared with the conventional approach. Third, simultaneous wireless information and power transfer (SWIPT) in MIMO VFDR system was proposed, where the transmit beamforming matrices which optimise the achievable rate and harvested energy at the relays were jointly designed. The results showed that the interference energy can be harnessed to improve the SWIPT system throughput. Finally, a joint optimisation of the power split and relay position in SWIPT MIMO VFDR network were investigated. Results showed that the joint optimisation of the power split and distance factors can greatly improve the system outage performance. The analytical and numerical results in the research showed that IRI can be exploited to improve the throughput, reliability and energy harvesting of a wireless communication system. The results also showed a minimum achievable rate improvement of 80% over the HDR schemes and a reliability of 100% over the FDR schemes.

ABSTRAK

Didorong oleh permintaan yang semakin meningkat terhadap jalur lebar wayarles, pendaman rendah dan rangkaian berkuasa cekap, geganti dupleks penuh (FDR) berbilang-input berbilang-output (MIMO) telah mendapat banyak perhatian kebelakangan ini. Bagaimanapun, prestasi skim FDR terjejas oleh penindasan gangguan diri yang kompleks. Oleh itu, MIMO FDR maya (VFDR) telah dipertimbangkan sebagai alternatif praktikal untuk mendapatkan semula kehilangan kecekapan spektrum dalam geganti dupleks separuh (HD) tanpa memerlukan algoritma penindasan gangguan sendiri yang rumit. Geganti berturut-turut (SR) adalah salah satu teknik VFDR yang menggunakan sepasang geganti HD silih-ganti antara penerimaan dengan penghantaran semula isyarat maklumat dari sumber ke destinasi. Prestasi skim VFDR berdasarkan SR terjejas oleh gangguan antara geganti (IRI) akibat penghantaran isyarat serentak dari sumber dan geganti. Gangguan dalam skim VFDR lazimnya dianggap sebagai faktor degradasi penerima penyahkodan informasi yang membawa kepada reka bentuk beberapa teknik penghindaran gangguan dan pembatalan gangguan. Sebaliknya, tesis ini membangunkan beberapa skim VFDR yang mengeksploitasi gangguan bagi mencapai peningkatan prestasi. Dalam kajian ini, teknik pengurusan gangguan, pembentukan alur penghantar/penerima, peruntukan kuasa dan algoritma pengoptimuman bersama telah direka. Pertama, satu skim MIMO VFDR yang boleh dipercayai dalam kehadiran IRI telah direka, iaitu IRI dimanfaatkan untuk penambahbaikan kebolehpercayaan. Hasil kajian menunjukkan peningkatan kebolehpercayaan yang memberangsangkan berbanding skim sedia ada. Kedua, satu peruntukan kuasa bersama untuk MIMO VFDR di bawah kekangan kuasa rangkaian telah dibangunkan. Masalah peruntukan kuasa dalam kehadiran IRI dirumus menggunakan algoritma *primal-dual*. Hasil kajian menunjukkan bahawa algoritma pengoptimuman bersama boleh menggunakan kuasa rangkaian secara cekap berbanding dengan pendekatan konvensional. Ketiga, pemindahan maklumat wayarles dan tenaga serentak (SWIPT) dalam sistem MIMO VFDR telah dicadangkan, iaitu matriks pembentukan alur penghantaran yang mengoptimumkan kadar yang dapat dicapai dan tenaga yang dituai telah direka bersama. Keputusan menunjukkan bahawa tenaga gangguan boleh dimanfaatkan untuk menambahbaik daya pemprosesan sistem SWIPT. Akhir sekali, pengoptimuman bersama pembahagian kuasa dan kedudukan geganti dalam rangkaian SWIPT MIMO VFDR telah dikaji. Hasil kajian menunjukkan bahawa pengoptimuman bersama faktor-faktor pembahagian kuasa dan kedudukan boleh menambahbaik secara ketara kebarangkalian gangguan sistem. Dapatan analisis dan dapatan berangka dalam kajian ini menunjukkan bahawa IRI boleh dimanfaatkan untuk meningkatkan daya pemprosesan, kebolehpercayaan dan penuaian tenaga dalam sistem perhubungan wayarles. Keputusan tersebut juga menunjukkan kadar minimum penambahbaikan sebanyak 80% pada skim HDR dan kebolehpercayaan sebanyak 100% pada skim FDR.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATIONS	xvi
	LIST OF SYMBOLS	xviii
	LIST OF APPENDICES	xix
1	INTRODUCTION	1
	1.1 Problem Background	4
	1.2 State-of-the-Arts	6
	1.3 Problem Statement	8
	1.4 Objective of Research	9
	1.5 Scope of Work	11
	1.6 Contributions and Organisation of the Thesis	12
2	LITERATURE REVIEW	15
	2.1 Wireless Fading Channel	15
	2.1.1 Wireless Channel Characteristics	15
	2.1.2 Statistical Models for Wireless Fading Channel	18
	2.2 Capacity and Reliability Improvements with Multiple Antennas	19
	2.2.1 Single Input Single Output Systems	19
	2.2.2 Multiple Antenna Systems	21

	2.2.2.1	SIMO and MISO Systems	21
	2.2.2.2	MIMO Systems	22
	2.2.2.3	MIMO Beamforming	23
	2.2.2.4	Outage Probability	26
	2.2.2.5	Diversity-Multiplexing Tradeoff	27
	2.2.2.6	Rate-Energy Tradeoff	28
2.3		Relaying in Wireless Network	30
	2.3.1	Full-Duplex Relaying	32
	2.3.2	Virtual FD Relaying	36
	2.3.2.1	One-Way Relaying	37
	2.3.2.2	Two-Way Relaying	38
	2.3.2.3	Successive Relaying	38
2.4		Successive Relaying Based Virtual FD Relaying	43
	2.4.1	Inter-Relay Interference Mitigation in SR Based VFD	43
	2.4.2	Relay Antenna Selection	46
	2.4.3	Joint Beamforming and Power Allocation	46
2.5		Simultaneous Wireless Information and Power Transfer	50
	2.5.1	Separate Receiver Architecture	51
	2.5.2	Integrated Power Split Receiver Architecture	52
	2.5.3	Integrated Time Switching Receiver Architecture	53
	2.5.4	Integrated Antenna Switching Receiver Architecture	53
2.6		Chapter Conclusion	55
3		RESEARCH METHODOLOGY	56
	3.1	Research Process	56
	3.2	System Models	59
	3.3	Antenna Selection	64
	3.3.1	Random Antenna Selection	64
	3.3.2	Maximum Capacity Antenna Selection	65
	3.4	Monte Carlo Simulations	66
	3.5	Mathematical Analysis	67
	3.6	Convex Optimisation	69

4	EXPLOITING INTER-RELAY INTERFERENCE IN MIMO VIRTUAL FULL-DUPLEX RELAYING SCHEME	72
4.1	Chapter Introduction	73
4.2	Description of the Proposed Protocol	77
4.2.1	Initialisation	78
4.3	Proposed Relay Receiver Beamforming and Trans- mit Antenna Selection	80
4.3.1	Design of Relay Receive Beamforming Matrix \mathbf{G}	81
4.3.2	Relay Transmit Antenna Selection	82
4.3.2.1	Random Antenna Selection (RAS)	83
4.3.2.2	Maximum Capacity Antenna Selection (MCAS)	83
4.3.3	Design of Relay Transmit Beamforming matrix \mathbf{W}_j	84
4.3.4	Destination Receiver	84
4.3.5	End to End Capacity	85
4.4	Ergodic Capacity Analysis	85
4.5	Outage Probability Analysis	89
4.5.1	Case 1: Two Relays can Successfully Decode	90
4.5.2	Case 2: One Relay can Successfully Decode	92
4.6	Reference Schemes	93
4.6.1	Ideal SR Scheme	93
4.6.2	Ideal FD Relaying	94
4.7	Numerical Results	95
4.8	Chapter Conclusion	101
5	POWER ALLOCATION OPTIMISATION IN MIMO VFD RELAYING UNDER NETWORK POWER CON- STRAINT	104
5.1	Chapter Introduction	105
5.2	Description of the Proposed Protocol	107
5.2.1	Power Constraint	110
5.2.2	Problem Formulation	112
5.3	Joint Source-Relay Power Allocation	113

5.4	Discussion of Results	115
5.5	Chapter Conclusion	119
6	MIMO VFD RELAYING WITH SEPARATE SWIPT ENABLED RELAY RECEIVERS	121
6.1	Chapter Introduction	121
6.2	Description of the Proposed Protocol	125
6.2.1	Transmission Protocol	126
6.2.2	Interference Avoidance	129
6.2.3	Proposed Interference Management Scheme	130
6.2.3.1	Antenna Selection Criterion	130
6.2.3.2	Proposed Beamforming Matrix Design	131
6.3	Proposed Precoding Matrix Optimisation	133
6.3.1	Optimisation of Information Rate at the Relay ID Receiver	135
6.3.2	Optimisation of Harvested Energy at the Relay EH Receiver	137
6.3.3	Optimisation of Relay to Destination Link	139
6.4	Numerical Results	140
6.5	Chapter Conclusion	147
7	OPTIMISATION OF POWER SPLIT AND RELAY DIS- TANCE IN SWIPT MIMO VFD RELAYING SCHEME	149
7.1	Chapter Introduction	149
7.2	Description of the Proposed Protocol	153
7.2.1	Case 1: MIMO Virtual FD Relaying without IRI	156
7.2.2	Case 2: MIMO Virtual FD Relaying with IRI	159
7.2.2.1	Case 2a	159
7.2.2.2	Case 2b	160
7.3	Rate-Energy Tradeoff	162
7.4	Outage Probability Analysis	163
7.4.1	Case 1: IRI is not present in the system ($\mathbf{H}_{r_j r_i} = 0$)	164

	7.4.2	Case 2: IRI is Present in the System ($\mathbf{H}_{r_j r_i} \neq 0$)	169
	7.5	Numerical Results	171
	7.6	Chapter Conclusion	179
8		CONCLUSION AND FUTURE WORKS	180
	8.1	Conclusion and Research Outcomes	180
	8.2	Future Works	183
		REFERENCES	185
		Appendices A – D	202 – 212

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Path loss exponent for different environment	17
2.2	Summary of review on relaying in wireless networks	40
2.3	Summary of review on SR based VFD relaying schemes.	48
2.4	Summary of review on SWIPT	54
4.1	Transmission schedule for one block length L	79
5.1	Algorithm: search algorithm to solve equation (5.33)	116
6.1	Algorithm for proposed solution to (P1)	135
7.1	Comparison of the system models in Chapters 6 and 7.	156
C.1	Complexity of key operations in Chapter 4	209
C.2	Complexity of key operations in Chapter 5	210
C.3	Complexity of key operations in Chapter 6	210
C.4	Complexity of key operations in Chapter 7	211

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Wireless network scenario	16
2.2	Received power versus distance. Fixed parameter: Source transmit power = 20 dBm.	17
2.3	Ergodic capacity of various antenna configurations	25
2.4	Outage probability at a fixed rate of $R = 2$ bits/s/Hz for various antenna configurations	26
2.5	Diversity-multiplexing tradeoff for various antenna configuration.	28
2.6	R-E tradeoff curve	29
2.7	Relay network scenario	31
2.8	Relaying protocols without the direct link between the source and destination: (a) Half-duplex relaying; (b) Buffer aided half-duplex relaying; (c) Frame level virtual FD relaying; (d) Out-of-band FD relay; (e) Two-way relaying; (f) Successive relaying.	36
2.9	SWIPT receiver structure; (a) Separate receiver architecture; (b) Integrated power split receiver architecture, where β denote the power split factor; (c) Integrated time switching receiver architecture, where α denote the time switching factor and T is the duration of the transmission block; (d) Antenna switching receiver architecture.	51
3.1	Flowchart of the research process	57
3.2	Flowchart of transmission protocol where inter-relay interference is assumed to be useful	60
3.3	Flowchart of antenna selection process	65
4.1	Proposed SR protocol	77
4.2	Ergodic capacity versus SNR of the proposed CM-SR +RAS and CM-SR + MCAS schemes in comparison with the bounds. Fixed parameters: $N_s = 2$, $N_r = 4$, $N_t = 2$, $N_d = 2$	95

4.3	Ergodic capacity versus SNR of various schemes with (N_s, N_r, N_t, N_d) antenna configuration. Fixed parameter $L=50$.	96
4.4	Probability that \mathcal{D} relays fall within the decoding set versus SNR of the proposed scheme with two available relays in the network. Fixed parameters: $R=6$ bits/s/Hz	97
4.5	Outage probability versus SNR of the proposed CM-SR +RAS and CM-SR + MCAS schemes in comparison with the comparable schemes. Fixed parameters: $R=6$ bits/s/Hz.	98
4.6	Outage probability versus SNR of analytical single stream CM-SR + MCAS schemes in comparison with simulated single stream CM-SR + MCAS scheme, MISO and SIMO case. Fixed parameters: $R=3$ bits/s/Hz, $N_r = 4$, $N_t = 1$, $N_d = 2$.	99
4.7	Analytical outage probability versus SNR of the proposed CM-SR +RAS in comparison with simulated outage probability when \mathcal{D} relays can successfully decode Fixed parameters: $R=3$ bits/s/Hz, $N_r = 4$, $N_t = 1$, $N_d = 2$.	100
4.8	Outage probability versus SNR of the proposed CM-SR + MCAS schemes with varying N_r Fixed parameters: $N_s = 2$, $N_t = 2$, $N_d = 2$ and $R=6$ bits/s/Hz	101
4.9	Diversity-multiplexing tradeoff curve for several schemes with (N_s, N_r, N_t, N_d) antenna configurations.	102
5.1	Achievable rates versus SNR with uniform power allocation	116
5.2	Achievable rates versus SNR with joint power allocation	117
5.3	Outage probability versus SNR with uniform power allocation	118
5.4	Outage probability versus SNR with joint power allocation	119
6.1	Proposed SWIPT virtual FD design	124
6.2	Harvested energy versus the source transmit power of the proposed scheme.	141
6.3	Harvested energy versus source to relay distance of the proposed scheme.	142
6.4	Achievable rate versus source to relay distance of the proposed scheme with fixed source and relay transmit powers.	143
6.5	Link rates versus source transmit power of the proposed scheme.	144
6.6	Achievable rate versus source transmit power of the proposed scheme compared with FD and HD relaying schemes.	144

6.7	Energy saving versus source transmit power of the proposed scheme	146
6.8	Energy saving versus source to relay distance of the proposed scheme.	147
7.1	Proposed SWIPT virtual FD relaying	154
7.2	R-E region for Cases 1 and 2b	172
7.3	Power split factor versus relative relay distance between the source and destination. Fixed parameters: $N_s = N_{t_j} = N_d = 2$	173
7.4	Harvested energy with optimal power split factor β_i for a given distance factor μ .	174
7.5	Harvested energy versus source transmit power with optimal β_i at $\mu = 0.5$.	175
7.6	Achievable rate versus SNR of various schemes with optimal β_i for each scheme at $\mu = 0.5$. Fixed parameters: $N_s = 2$, $N_t = 2$, $N_d = 2$, $L = 50$.	176
7.7	Outage probability with optimal (β_i or μ) versus SNR for Case 2. Fixed parameters: $N_s = 2$, $N_r = 4$, $N_t = 2$, $N_d = 2$, $\hat{\gamma} = 10$ dB.	177
7.8	Outage probability versus SNR of $s - r_i$ and $r_j - d$ links. Fixed parameters for Case 1: $N_s = 2$, $N_r = 4$, $N_t = 2$, $N_d = 2$, $\hat{\gamma} = 10$ dB.	177
7.9	Outage probability versus SNR of various schemes. Fixed parameters: $N_s = 2$, so h $N_t = 2$, $N_d = 2$, $\hat{\gamma} = 10$ dB.	178

LIST OF ABBREVIATIONS

AF	-	Amplify and Forward
APC	-	Aggregate Power Constraint
CDF	-	Cumulative Density Function
CSI	-	Channel State Information
CSIR	-	Channel State Information at the Receiver
CSIT	-	Channel State Information at the Transmitter
CVX	-	Convex Optimization
DF	-	Decode and Forward
DMT	-	Diversity-multiplexing Tradeoff
FD	-	Full-Duplex
FDD	-	Frequency Division Duplexing
HD	-	Half-Duplex
i.i.d	-	independent and identically distributed
IPC	-	Individual Power Constraint
IRI	-	Inter-Relay Interference
LTE-A	-	Long Term Evolution-Advanced
MCAS	-	Maximum Capacity Antenna Selection
MIMO	-	Multiple Input Multiple Output
MISO	-	Multiple Input Single Output
NOMA	-	Non-Orthogonal Multiple Access
OFDM	-	Orthogonal Frequency Division Multiplexing
PDF	-	Probability Density Function
QoS	-	Quality of Service
RAS	-	Random Antenna Selection
R-E Tradeoff	-	Rate-Energy Tradeoff
RF	-	Radio Frequency
SIC	-	Successive Interference Cancellation

SIMO	-	Single Input Multiple Output
SISO	-	Single Input Single Output
SINR	-	Signal to Interference and Noise Ratio
SNR	-	Signal to Noise Ratio
SR	-	Successive Relaying
SVD	-	Singular Value Decomposition
SWIPT	-	Simultaneous Wireless Information and Power Transfer
TDD	-	Time Division Duplexing
VFD	-	Virtual Full-Duplex
WiFi	-	Wireless Fidelity
WIT	-	Wireless Information Transfer
WPT	-	Wireless Power Transfer
ZF	-	Zero-Forcing
ZFBF	-	Zero-Forcing Beamforming

LIST OF SYMBOLS

a	-	denote scalars
\mathbf{A}	-	boldface upper case letters denote matrices
\mathbf{a}	-	boldface lower case letters denote vectors
\mathbf{A}^H	-	Hermitian transpose of matrix \mathbf{A}
\mathbf{A}^T	-	transpose of matrix \mathbf{A}
\mathbf{A}^\dagger	-	pseudo inverse of matrix \mathbf{A}
$\ \cdot \ _F$	-	Frobenius norm
$\log_a(A)$	-	logarithm of A to base a
$E_A\{a\}$	-	expectation of a over the random variable of A
$[\mathbf{A}]_{i,j}$	-	(i, j) -th element of matrix \mathbf{A}
$\text{tr}(\mathbf{A})$	-	trace of matrix \mathbf{A}
$\exp(a)$	-	exponent (a)
$[a]^+$	-	$\max(a, 0)$
\mathbb{N}^n	-	$n \times n$ dimensional Hermitian matrix set
\forall	-	for all
\preceq, \succeq	-	componentwise inequality
\in	-	is an element of
A	-	set of A
$a \rightarrow \infty$	-	a tends to positive ∞
$\text{Pr}(A)$	-	probability of event A
$a!$	-	factorial of a
$\text{diag}(\lambda_1, \lambda_2, \dots)$	-	diagonal matrix with element $\lambda_1, \lambda_2, \dots$
$\mathcal{CN}(\mu, \sigma^2)$	-	circular symmetric Gaussian random variable with mean μ and variance σ^2

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Proof of Theorem and Lemma	202
B	Proof of Proposition 3	208
C	Complexity Analysis	209
D	Publications	212

CHAPTER 1

INTRODUCTION

Current wireless communication systems promise high quality of service in voice and data communication. Other features such as massive number of connected devices, high mobility, low latency, reliability, resilience, security, long battery life and more have led to numerous research in the ongoing 5-th generation standardisation process [1]. Although several solutions have been provided in the 5-th generation standardisation process, several key issues are still being addressed. One key challenge of wireless communication is the cell edge coverage issue. When wireless signals are transmitted through space, the transmit power attenuates exponentially [2], leading to low data rates at the cell edge and shadowed environments. Among several solutions, the advantage of using relays to overcome the coverage hole and assist the network has been studied and the progress made so far can be found in the numerous research articles.

In recent and future wireless communications, relays have been adopted as one of the key technology to improve service coverage at the cell edge, eliminate dead spot, reduce energy consumption, enhance capacity and increase network reliability [3,4]. The advantages provided by relay networks have attracted interest in the wireless communication field. This has led to several research works aimed at studying the performance benefits in both dedicated and user-based relay networks. In general, relays can operate in half-duplex (HD) mode (transmit and receive in the orthogonal time slot or orthogonal frequencies) or full-duplex (FD) mode (simultaneously transmit

and receive in the same time slot and frequencies).

However, the use of HD relays in 3rd Generation Partnership Project (3GPP) and Long Term Evolution-Advanced (LTE-A) is limited by HD constraint. This constraint describes the inability of a relay to transmit and receive simultaneously, consequently, a spectral efficiency loss of at least 50% is experienced, since extra dedicated bandwidth is always required for relaying transmission. On the other hand, FD relays have also been recently introduced in wireless networks, but their performance is limited by self-interference and loop back residual interference. The self-interference in FD relays exist due to the simultaneous reception and transmission on the same channel resulting in power leakage from the transmitter of the relay to its receiver, the interference from the transmitter could saturate its own receiver's analogue to digital converter. The isolation of transmitter and receiver chains in FD relaying are characterised with the self-interference or co-channel interference. Although several techniques have been proposed to combat the self-interference in FD relays [5], researchers have highlighted that a part of the self-interference could still exist in the system, such interference is referred to as residual self-interference. Due to the challenges in the use of FD relays especially in multi-antenna scenarios, the majority of research results are still based on the HD signal models, as they can be deployed in a more practical scenario. However, the challenge remains on how to overcome HD constraint in HD relays.

Several schemes have been proposed to combat HD constraint in HD relaying networks [6], such as two-way relaying scheme [7], cognitive cooperative relaying scheme [8] and successive relaying (SR) scheme [9]. These schemes are termed virtual FD (VFD) relaying schemes, by exploiting these schemes the spectral efficiency loss in HD relays can be recovered and the system performance can be improved. VFD relaying achieves close to the performance limits of FD relaying by separating the reception and transmission of FD relaying either in space or time. Two-way relaying

achieves VFD relaying modes by receiving and transmitting at least two streams of data in orthogonal time. In SR, two or more relays which are separated by space, alternate between reception and transmission of signals from the source to the destination. SR protocol is able to recover the losses in one-way HD relays if the relays are properly positioned and the inter-relay interference is properly managed. The improvement in spectral efficiency introduced by the SR relaying scheme has motivated its applications in multiple users and multiple antennas scenarios. Single-antenna SR networks have been broadly studied while only a few studies have been carried out on multi-antenna SR schemes which has motivated the study in this thesis.

Although several performance benefits can be achieved in cooperative schemes, it is important to note that the cooperating nodes or relays could be fixed node such as infrastructural relays or mobile nodes such as handheld devices (Mobile phones, tablets, laptops etc.). While the infrastructural relays can be connected to a power grid, handheld devices usually rely on batteries. The lifetime of battery-powered devices is limited and therefore requires energy replenishing. These mobile devices can be remotely charged by wireless power transfer while simultaneously receiving information from the same RF signal, which has motivated the study of simultaneous wireless information and power transfer (SWIPT) in this thesis.

The rest of this chapter is organised as follows. The problem background is presented in Section 1.1. The current state of the art related to this thesis is presented in Section 1.2. The problem statements are highlighted in Section 1.3. The objectives of this thesis are presented in Section 1.4. The scope of the thesis is presented in Section 1.5. The chapter is concluded with the contributions and organisation of the thesis in Section 1.6.

1.1 Problem Background

Wireless communication is evolving to meet the increasing quality of service (QoS) and bandwidth demands. As the demand for wireless broadband continues to increase, current and future wireless networks continue to promise reliable communication and data rate improvements [10]. To ensure reliable communication at the promised data rate between the user at the cell edge and the base station through a direct transmission can be very expensive, due to the transmission power required as the distance between the user and the base station increases. Relays can bridge this gap by improving the link quality, reliability and signal to noise ratio between the base station and the cell edge users. Although signal to noise ratio improvements can be achieved by employing relays, the use of HD relay still shows about 50% spectral efficiency losses which cannot be ignored for real-time applications such as video conferencing. VFD relaying schemes have been proposed as a possible solution to recover the losses due to HD constraint while providing an easier means of tackling the self-interference in FD relaying scheme. In addition, VFD relaying schemes provide means of increasing signal reliability and power efficiency.

As wireless signals travel from a source to the destination, its power decays exponentially. Several studies have shown that the use of relays in networks (either infrastructural or user enabled relays) can provide diversity gain and data rate improvements in cooperative communication [11, 12]. The diversity gain provides redundant paths for the signal to combat the effect of deep fade, thereby improving the user's capacity and QoS. Given the numerous benefits of cooperative communications, reliable and efficient algorithms are required to exploit these benefits.

In SR based VFD relaying scheme, two or more HD relays are implemented to mimic an FD relay. The participating relays alternate between reception and transmission to enable the source to transmit new messages to the destination

continuously. However, due to the co-channel operation of the participating relays, the performance of the SR scheme can be degraded by inter-relay interference (IRI) [13]. In the existing SR schemes, the IRI is either avoided using interference avoidance techniques or cancelled out using successive interference cancellation (SIC) [14] while beamforming techniques have been applied in multiple antenna scenarios [15]. The cancellation or avoidance of the IRI can greatly improve the capacity of the SR scheme, but the full diversity provided by the SR scheme cannot be achieved. In general, IRI has always been considered as an unwanted signal in SR scheme. However, improving the reliability of user's information in wireless communication requires sending multiple copies of the same signal to the user, either in the frequency domain, time domain or spatial domain [16]. This thesis is motivated by the fact that the IRI can be decoded as shown by the successive interference cancellation schemes. However, instead of discarding the decoded IRI, it can be retransmitted to the user, thereby improving the user's signal reliability. Another motivating factor is, by improving the reliability of the user, beamforming and power allocation algorithms can be implemented to improve the network power allocations.

To further improve the system performance, power efficiency is a vital design consideration. Although power allocation schemes have been widely studied in multiple input multiple output (MIMO) systems [17–19], the existing schemes cannot be directly applied to SR schemes where the IRI is exploited. This is due to the different power requirements from the source and inter-relay link. Uniform power allocation at each node has been generally adopted for ease of analysis and computation. Meanwhile, in MIMO systems, it has been shown that water filling power allocation is optimal. However, in a MIMO relay network, individual power allocation and aggregate power allocation have been shown to further improve the system power efficiency in one way relaying scheme [17] and can further be extended to SR schemes.

Attracted by the benefits of simultaneous wireless information and power

transfer in replenishing the batteries of mobile users. Users cooperation can be encouraged if the mobile users who are serving as relays can harvest energy from the RF signals and use the harvested energy to forward the signal [20]. Recent studies in SWIPT have shown that several factors such as; increasing the number of relay receive antennas, relay positioning in the network and beamforming designs can help to improve energy harvesting efficiency at the relay. In FD relay networks, energy harvesting can be enhanced by utilising the self-interference [21], while energy harvesting utilising IRI in SR based VFD relaying scheme has not been explored. Note that SWIPT systems can be implemented with separate or co-located information decoders (ID) and energy harvesting (EH) receiver architecture. In the co-located SWIPT design, the ID and EH receivers possess the same channel coefficients from the source, while in the separate architecture the ID and EH receivers possess different channels coefficients from the source [22].

IRI has traditionally been assumed as a performance degrading factor to the ID receiver. However, this thesis exploits the IRI for energy harvesting and data rates improvements with respect to the relay distance and power split factor. The optimisation of relay position and power split factor have been widely investigated in several literatures, these two optimisations are usually studied separately [23, 24]. Given that the relay position and power split factor determines the path loss of the adjacent hop, this thesis studies the joint optimal relay position and power split parameter that minimises the end to end outage probability of the SR scheme with and without IRI.

1.2 State-of-the-Arts

The future 5-th generation (5G) network is currently being studied. A survey on 5G is presented in [25], where it is highlighted that the technology will operate within small cells. Hence, relays will play an important role in connecting several devices,

small cells and the base station [26, 27]. Also as the cell size becomes smaller, the difference between the transmit and receive power in an FD relays network become smaller, therefore FD relays are currently being studied as the key technology to facilitate the implementation of 5G and beyond. The key issues with the FD relays are self-interference and the complexity in the design of the transmit and receive chains as the number of antennas increases [5]. Note that the future 5G network proposes to deliver high data rate by implementing a large number of antenna array known as massive multiple input multiple output (Massive MIMO).

SWIPT enabled relays are also currently being studied as they could be vital in the energy efficiency of battery-powered devices. The rate-energy (R-E) tradeoff of SWIPT systems for direct transmission has been studied in [22, 28]. In [29], practical receivers for SWIPT systems are investigated. The authors also defined the R-E tradeoff for single antenna system with power split and time switch architectures. The architectures are extended to MIMO receivers and the optimal beamforming matrices for MIMO broadcast SWIPT network are presented in [22], where the R-E tradeoff is also discussed.

However, with the current research activities and the issue with self-interference in FD relaying schemes, there is a need to develop relaying schemes that can fully mimic the FD relays with less sophisticated interference suppression techniques using HD relays while recovering the loss in spectral efficiency due to HD constraint. In addition, there is a need to consider the use of IRI in such network to improve the system reliability and enhance energy harvesting efficiency while encouraging cooperation between users. This is important as billions of devices are expected to be connected in 5G networks.

1.3 Problem Statement

Bandwidth is a limited resource and requires efficient utilisation. SR based VFD relaying schemes can efficiently utilise the limited bandwidth [30], but their performance is degraded by inter-relay interference [31]. Although interference avoidance and cancellation schemes have been proposed, they fail to exploit the full diversity provided by the SR based VFD scheme. Due to the inefficient utilisation of the diversity, the current SR based VFD relaying schemes exhibit poor outages and inefficient power allocation.

The interference cancellation and avoidance techniques also show significant losses in terms of achievable rates and energy harvesting in SWIPT systems. Based on the current studies SWIPT systems can thrive if the amount of harvested energy is sufficiently high [21, 32]. By using properly designed beamforming and interference mitigation techniques, the performance of the VFD relaying systems can be improved with information decoding relay receivers only or with SWIPT enabled relay receiver nodes. In addition, the VFD relaying scheme with only information decoding receivers stand to gain from exploiting interference to improve the diversity-multiplexing tradeoff, outage probability, efficient network power utilisation and achievable rates, while the VFD relaying scheme with SWIPT enabled relay receivers can exploit IRI to improve the amount of harvested energy, achievable rates, R-E tradeoff and outage probability with optimised beamforming and covariance matrices.

The development of new VFD relaying schemes in the presence of inter-relay interference is crucial to overcoming the sophisticated interference cancellation techniques in FD relays [33, 34]. The development is also crucial in 5G wireless communication networks with billion of connected devices [35–37], where the systems have to learn to cope with interference [38]. To this end, this thesis investigates the effect of IRI in SR based VFD relaying network with emphasis on the user data rate,

outage probability, diversity and multiplexing tradeoff, energy harvesting, R-E tradeoff etc. These problems will be addressed by answering the following research questions.

1. How can inter-relay interference be exploited to improve the achievable throughput and reliability of the user?
2. How can power allocation improve the end to end system performance in terms of throughput and outage probability in the presence of IRI?
3. How can IRI be exploited to improve the achievable rate and energy harvesting in SWIPT networks?
4. What are the optimal power split and distance factors for a SWIPT VFD relaying network that minimise the end to end outage probability?

In summary, it is observed that the inter-relay interference which has conventionally been assumed as a degrading factor in VFD relaying schemes, can be exploited by proper interference mitigation and beamforming techniques to improve VFD relaying system performance.

1.4 Objective of Research

This thesis aims to demonstrate the use of inter-relay interference in enhancing system reliability, improving the system data rate and improving the power efficiency in VFD relaying systems. Based on the aforementioned aims, the main objectives of this thesis are presented in the following paragraphs.

1. The first objective is to propose a reliable MIMO virtual FD relaying scheme in the presence of inter-relay interference.
2. The second objective is to propose an efficient power allocation scheme in a MIMO VFD relaying network to improve the system capacity and outage performance in the presence of IRI.
3. The third objective is to design the source transmit beamforming matrices which optimise the information rate at the ID receiver and the energy harvesting at the EH receiver for a MIMO VFD SWIPT relaying system, where the system is implemented with separate information decoding and energy harvesting receivers in the presence of IRI.
4. The final objective is to design the optimal power allocation to the ID and EH receivers and the optimal relay position for a simultaneous wireless information and power transfer enabled MIMO VFD relaying scheme, where the scheme is implemented with co-located information decoders and energy harvesters in the presence of IRI.

In summary, HD relays exhibit a spectral efficiency loss of about 50% since they require addition time or frequency resource. On the other hand, FD relaying schemes requires sophisticated self-interference suppression algorithms. This thesis presents VFD relaying schemes to bridge the gap between the HD and FD relaying schemes using HD relays in the presence of IRI. Unlike the existing schemes, this thesis proposes VFD relaying schemes to recover the spectral efficiency loss in HD relaying networks, while achieving the performance of FD relaying schemes with less sophisticated interference mitigation techniques. In addition, the research aims to exploit the IRI for system improvements in terms of capacity, reliability, energy harvesting etc.

1.5 Scope of Work

The scope of this thesis includes developing receive and transmit beamforming matrix for multiple antenna VFD relaying system in the presence of IRI. Relay transmit antenna selection algorithm will be implemented to reduce the dimension of IRI. The scope is limited to numerical and analytical simulations of the proposed schemes. The user analysis in terms of capacity, outage probability, energy harvesting, power optimisation and relay position optimisation will be addressed. The research also focuses only on the physical layer. The performance analysis will be evaluated using MATLAB simulator, while convex optimisation tools such as CVX and Nsolve in Mathematical will be used for optimisation algorithms. The scenarios of interest are listed as follows.

1. Perfect channel state information (CSI) is assumed in this thesis.
2. A four-node network with a single source, single destination and two HD decode and forward relays are considered.
3. The direct link between the source and the destination is assumed to be weak and disconnected.
4. The relays are assumed to be information decoding receivers in both Chapters 4 and 5.
5. The relays are assumed to be separate information decoding and energy harvesting receivers in Chapter 6.
6. The relays are assumed to be integrated information decoding and energy harvesting receivers in Chapter 7.

The following are beyond the scope of this thesis.

1. The performance of the proposed scheme in 5G networks.
2. The performance of the scheme in frequency selective and fast fading channels.
3. The RF power consumption at the nodes.

4. The performance of the proposed scheme in multiple relays greater than two.

1.6 Contributions and Organisation of the Thesis

The main contributions of this thesis are summarised as follows,

- In Chapter 4, a system which exploits IRI in MIMO VFD relaying network is proposed. The IRI is managed by the use of relay transmit antenna selections and relay receive beamforming matrix. The proposed scheme jointly decodes the source and the IRI symbols at the relay receiver, a superposition of the decoded symbols are transmitted to the destination. Analytical and numerical results are provided to validate the performance of the proposed scheme. The analytical and numerical results show that the proposed scheme can achieve the full diversity provided by SR scheme while maintaining the multiplexing gain of the FD relaying scheme. The results also show that the proposed scheme can outperform conventional SR based VFD relaying scheme in terms of outage probability, diversity and multiplexing gain even in the presence of IRI.
- Power allocation optimisation for MIMO VFD relaying scheme under network power constraint is proposed in Chapter 5. Individual power constraint at each antenna and the aggregate power constraint at each node are addressed. A joint power allocation problem under network power constraint is also formulated as a convex optimisation problem. The formulated problem is addressed using the low complexity and high computational efficient Lagrangian primal-dual optimisation algorithm [39]. Due to the effect of the IRI power on the relay receiver, an iterative algorithm is presented to address the joint power allocation problem. The results justify the achieved improvements in capacity and outage probability of the proposed scheme.

- A MIMO VFD relaying scheme with separate information decoding and energy harvesting receivers is proposed in Chapter 6. The source and relay transmit beamforming matrix are designed for a VFD relaying scheme with separate information decoding and energy harvesting receivers. The harvested energy at the relay of the proposed scheme is used to forward the relay decoded message to the destination. The results show that by properly designing the precoding matrices for the separate information decoding and energy harvesting receivers, the end to end capacity of the VFD relaying scheme can be improved. In addition, it is shown that EH receivers can rely on interference sources to improve the amount of harvested energy.
- A MIMO VFD relaying scheme with co-located information decoding and energy harvesting receivers is proposed in Chapter 7. The R-E tradeoff for co-located receivers of the proposed scheme is presented. The optimal power split factor for a fixed relay distance factor, the optimal distance factor for a fixed power split factor as well as the optimal joint power and distance factors which minimise the end to end outage probability are also studied. The results show that inter-relay interference can improve the R-E tradeoff of the SWIPT VFD relaying scheme. In addition, the joint optimisation of the power split and distance factors improves the outage performance of the system compared to the conventional schemes where the distance or the power allocation factors are optimised separately.

In summary, this thesis proposes new techniques of handling inter-relay interference in a MIMO VFD relay system. The proposed schemes employ beamforming, power allocation, antenna selection, energy harvesting to achieve improved performance. The proposed schemes are able to achieve better throughput, outage probability, power efficiency, diversity and reliability.

The rest of the thesis is organised as follows. In Chapter 2, related works are investigated and presented in a literature review. Chapter 3 presents the research methodology. In Chapter 4, the proposed reliable virtual FD relaying scheme in the presence of inter-relay interference is discussed. Chapter 5 presents the proposed joint power allocation for decode and forward (DF) concatenated MIMO VFD relaying scheme under network power constraint. In Chapter 6, the proposed wireless information and power transfer in MIMO virtual FD relaying system is discussed. The power split and relay position optimisation for SWIPT MIMO virtual FD relaying network are studied in Chapter 7. Finally, the conclusions of the thesis and suggestions on the future works are given in Chapter 8.

REFERENCES

1. Andrews, J. G., Buzzi, S., Choi, W., Hanly, S. V., Lozano, A., Soong, A. C. and Zhang, J. C. What will 5G be? *IEEE Journal on selected areas in communications*, 2014. 32(6): 1065–1082.
2. Chan, A. and Li, K. Wireless communication systems, 2005. US Patent App. 11/113,266.
3. Susitaival, R. Protocol Impact of LTE Relays on User Performance. *Vehicular Technology Conference (VTC Spring), 2012 IEEE 75th*. IEEE. 2012. 1–5.
4. Saleh, A. B., Redana, S., Raaf, B., Riihonen, T., Hamalainen, J. and Wichman, R. Performance of amplify-and-forward and decode-and-forward relays in LTE-advanced. *Vehicular Technology Conference Fall (VTC 2009-Fall), 2009 IEEE 70th*. IEEE. 2009. 1–5.
5. Bharadia, D., McMillin, E. and Katti, S. Full duplex radios. *ACM SIGCOMM Computer Communication Review*. ACM. 2013, vol. 43. 375–386.
6. Rankov, B. and Wittneben, A. Spectral efficient protocols for half-duplex fading relay channels. *Selected Areas in Communications, IEEE Journal on*, 2007. 25(2): 379–389.
7. Lee, K., Kwon, H. M., Yang, J., Sawan, E. M. and Park, H. Two-Way AF MIMO Beamforming Relay Strategies under Transmit Power Constraint. *Military Communications Conference, MILCOM 2013-2013 IEEE*. IEEE. 2013. 533–537.
8. Luo, H., Zhang, Z. and Yu, G. Cognitive cooperative relaying. *Communication Systems, 2008. ICCS 2008. 11th IEEE Singapore International Conference on*. IEEE. 2008. 1499–1503.
9. Basar, E., Aygolu, U., Panayirci, E. and Poor, H. V. Reliable two-path successive relaying. *Personal Indoor and Mobile Radio Communications (PIMRC), 2013 IEEE 24th International Symposium on*. IEEE. 2013. 1411–1415.
10. Mogensen, P. E., Koivisto, T., Pedersen, K. I., Kovacs, I. Z., Raaf, B., Pajukoski, K. and Rinne, M. J. LTE-advanced: the path towards gigabit/s

- in wireless mobile communications. *Wireless Communication, Vehicular Technology, Information Theory and Aerospace & Electronic Systems Technology, 2009. Wireless VITAE 2009. 1st International Conference on.* IEEE. 2009. 147–151.
11. Narayanan, S., Di Renzo, M., Graziosi, F. and Haas, H. Distributed Spatial Modulation: A Cooperative Diversity Protocol for Half-Duplex Relay-Aided Wireless Networks. *IEEE Transactions on Vehicular Technology*, 2016. 65(5): 2947–2964.
 12. Xie, K., Wang, X., Wen, J. and Cao, J. Cooperative Routing With Relay Assignment in Multiradio Multihop Wireless Networks. *IEEE/ACM Transactions on Networking*, 2016. 24(2): 859–872.
 13. Lu, H., Hong, P. and Xue, K. Generalized Interrelay Interference Cancellation for Two-Path Successive Relaying Systems. *Vehicular Technology, IEEE Transactions on*, 2014. 63(8): 4113–4118.
 14. Wicaksana, H., Ting, S. H., Guan, Y. L. and Xia, X.-G. Decode-and-forward two-path half-duplex relaying: diversity-multiplexing tradeoff analysis. *Communications, IEEE Transactions on*, 2011. 59(7): 1985–1994.
 15. Lee, S., Kwon, H. M., Lee, K. and Park, H. AF MIMO Beamforming Relay Networks under Various Power Constraints. *MILCOM 2013 - 2013 IEEE Military Communications Conference*. 2013. ISSN 2155-7578. 1273–1277. doi:10.1109/MILCOM.2013.217.
 16. Tse, D. and Viswanath, P. *Fundamentals of wireless communication*. Cambridge university press. 2005.
 17. Lu, F., Liu, C., Fu, Y. and Zhao, H. A. Joint Power Allocation for DF MIMO Relay Links with Hybrid Power Constraints. *Wireless Communications, Networking and Mobile Computing (WiCOM), 2012 8th International Conference on*. 2012. ISSN 2161-9646. 1–4. doi:10.1109/WiCOM.2012.6478557.
 18. Hammerstrom, I. and Wittneben, A. Power allocation schemes for amplify-and-forward MIMO-OFDM relay links. *Wireless Communications, IEEE Transactions on*, 2007. 6(8): 2798–2802.
 19. Li, C., Wang, X., Yang, L. and Zhu, W.-P. A joint source and relay power allocation scheme for a class of MIMO relay systems. *Signal Processing, IEEE Transactions on*, 2009. 57(12): 4852–4860.
 20. Krikidis, I., Timotheou, S., Nikolaou, S., Zheng, G., Ng, D. W. K. and Schober, R. Simultaneous wireless information and power transfer in modern

- communication systems. *IEEE Communications Magazine*, 2014. 52(11): 104–110.
21. Xu, J., Duan, L. and Zhang, R. Harnessing Self-Interference in Full-Duplex Relaying: An Analog Filter-and-Forward Approach. *arXiv preprint arXiv:1607.00510*, 2016.
 22. Zhang, R. and Ho, C. K. MIMO Broadcasting for Simultaneous Wireless Information and Power Transfer. *Wireless Communications, IEEE Transactions on*, 2013. 12(5): 1989–2001. ISSN 1536-1276. doi:10.1109/TWC.2013.031813.120224.
 23. Liu, H., Kim, K. J., Kwak, K. S. and Poor, H. V. Power Splitting-Based SWIPT With Decode-and-Forward Full-Duplex Relaying. *IEEE Transactions on Wireless Communications*, 2016. 15(11): 7561–7577. ISSN 1536-1276. doi:10.1109/TWC.2016.2604801.
 24. Liao, Q. Y. and Leow, C. Y. Study of relay position in two-path successive relaying with interference cancellation. *Wireless and Mobile, 2014 IEEE Asia Pacific Conference on*. 2014. 254–259. doi:10.1109/APWiMob.2014.6920308.
 25. Wang, L.-C. and Rangapillai, S. A survey on green 5G cellular networks. *Signal Processing and Communications (SPCOM), 2012 International Conference on*. IEEE. 2012. 1–5.
 26. Tehrani, M. N., Uysal, M. and Yanikomeroglu, H. Device-to-device communication in 5G cellular networks: challenges, solutions, and future directions. *IEEE Communications Magazine*, 2014. 52(5): 86–92. ISSN 0163-6804. doi:10.1109/MCOM.2014.6815897.
 27. Gupta, A. and Jha, R. K. A Survey of 5G Network: Architecture and Emerging Technologies. *IEEE Access*, 2015. 3: 1206–1232. ISSN 2169-3536. doi:10.1109/ACCESS.2015.2461602.
 28. Huang, K. and Larsson, E. Simultaneous Information and Power Transfer for Broadband Wireless Systems. *Signal Processing, IEEE Transactions on*, 2013. 61(23): 5972–5986. ISSN 1053-587X. doi:10.1109/TSP.2013.2281026.
 29. Zhou, X., Zhang, R. and Ho, C. K. Wireless Information and Power Transfer: Architecture Design and Rate-Energy Tradeoff. *IEEE Transactions on Communications*, 2013. 61(11): 4754–4767. ISSN 0090-6778. doi:10.1109/TCOMM.2013.13.120855.
 30. Li, Q., Yu, M., Pandharipande, A., Ge, X., Zhang, J. and Zhang, J.

- Performance of virtual full-duplex relaying on cooperative multi-path relay channels. *IEEE Transactions on Wireless Communications*, 2016. 15(5): 3628–3642.
31. Kim, S. M. and Bengtsson, M. Virtual Full-Duplex Buffer-Aided Relaying in the Presence of Inter-Relay Interference. *IEEE Transactions on Wireless Communications*, 2016. PP(99): 1–1. ISSN 1536-1276. doi:10.1109/TWC.2015.2514103.
 32. Chen, Y. Energy-Harvesting AF Relaying in the Presence of Interference and Nakagami- m Fading. *IEEE Transactions on Wireless Communications*, 2016. 15(2): 1008–1017.
 33. Riihonen, T., Werner, S. and Wichman, R. Mitigation of loopback self-interference in full-duplex MIMO relays. *IEEE Transactions on Signal Processing*, 2011. 59(12): 5983–5993.
 34. Hong, S. N. and Caire, G. Virtual Full-Duplex Relaying With Half-Duplex Relays. *IEEE Transactions on Information Theory*, 2015. 61(9): 4700–4720. ISSN 0018-9448. doi:10.1109/TIT.2015.2453942.
 35. Xiang, W., Zheng, K. and Shen, X. S. 5G Mobile Communications. 2016.
 36. Alonso-Zarate, J. and Dohler, M. M2M Communications in 5G. In: *5G Mobile Communications*. Springer. 361–379. 2017.
 37. Liu, G. and Jiang, D. 5G: Vision and Requirements for Mobile Communication System towards Year 2020. *Chinese Journal of Engineering*, 2016. 2016.
 38. Xue, Q., Li, B., Zuo, X., Yan, Z. and Yang, M. Cell capacity for 5G cellular network with inter-beam interference. *Signal Processing, Communications and Computing (ICSPCC), 2016 IEEE International Conference on*. IEEE. 2016. 1–5.
 39. Gill, P. E. and Robinson, D. P. A primal-dual augmented Lagrangian. *Computational Optimization and Applications*, 2012. 51(1): 1–25.
 40. Erceg, V., Greenstein, L. J., Tjandra, S. Y., Parkoff, S. R., Gupta, A., Kulic, B., Julius, A. A. and Bianchi, R. An empirically based path loss model for wireless channels in suburban environments. *IEEE Journal on selected areas in communications*, 1999. 17(7): 1205–1211.
 41. Goldsmith, A. *Wireless communications*. Cambridge university press. 2005.
 42. Owen, F. and Pudney, C. Radio propagation for digital cordless telephones at 1700 MHz and 900 MHz. *Electronics Letters*, 1989. 25(1): 52–53.

43. Rappaport, T. S. *et al.* *Wireless communications: principles and practice*. vol. 2. Prentice Hall PTR New Jersey. 1996.
44. Seidel, S. Y., Rappaport, T. S., Jain, S., Lord, M. L. and Singh, R. Path loss, scattering and multipath delay statistics in four European cities for digital cellular and microcellular radiotelephone. *IEEE Transactions on Vehicular Technology*, 1991. 40(4): 721–730.
45. De Toledo, A. and Turkmani, A. Propagation into and within buildings at 900, 1800 and 2300 MHz. *Vehicular Technology Conference, 1992, IEEE 42nd*. IEEE. 1992. 633–636.
46. De Toledo, A. F., Turkmani, A. M. and Parsons, J. D. Estimating coverage of radio transmission into and within buildings at 900, 1800, and 2300 MHz. *IEEE Personal Communications*, 1998. 5(2): 40–47.
47. Simon, M. K. and Alouini, M.-S. *Digital communication over fading channels*. vol. 95. John Wiley & Sons. 2005.
48. German, G., Spencer, Q., Swindlehurst, L. and Valenzuela, R. Wireless indoor channel modeling: statistical agreement of ray tracing simulations and channel sounding measurements. *2001 IEEE International Conference on Acoustics, Speech, and Signal Processing. Proceedings (Cat. No.01CH37221)*. 2001, vol. 4. ISSN 1520-6149. 2501–2504 vol.4. doi: 10.1109/ICASSP.2001.940509.
49. Molisch, A. F., Foerster, J. R. and Pendergrass, M. Channel models for ultrawideband personal area networks. *IEEE Wireless Communications*, 2003. 10(6): 14–21. ISSN 1536-1284. doi:10.1109/MWC.2003.1265848.
50. Zhang, J., Woods, R., Duong, T. Q., Marshall, A. and Ding, Y. Experimental study on channel reciprocity in wireless key generation. *Signal Processing Advances in Wireless Communications (SPAWC), 2016 IEEE 17th International Workshop on*. IEEE. 2016. 1–5.
51. Ghassemlooy, Z., Popoola, W. and Zvanovec, S. Diversity for Mitigating Channel Effects. In: *Optical Wireless Communications*. Springer. 431–450. 2016.
52. Guimarães, A. A. P. and Cavalcante, C. C. An upper-bound on the ergodic capacity of rayleigh-fading MIMO channels using majorization theory. *Simpósio Brasileiro de Telecomunicações*. 2012.
53. Aalo, V. A., Mukasa, C. and Efthymoglou, G. P. Effect of Mobility on the Outage and BER Performances of Digital Transmissions over Nakagami-Fading Channels. *IEEE Transactions on Vehicular Technology*, 2016. 65(4):

2715–2721.

54. Stirzaker, D. *Elementary probability*. Cambridge University Press. 2003.
55. Brown, T., Kyritsi, P. and De Carvalho, E. *Practical guide to MIMO radio channel: With MATLAB examples*. John Wiley & Sons. 2012.
56. Biglieri, E., Calderbank, R., Constantinides, A., Goldsmith, A., Paulraj, A. and Poor, H. V. *MIMO wireless communications*. Cambridge university press. 2007.
57. Azarian, K., El Gamal, H. and Schniter, P. On the achievable diversity-multiplexing tradeoff in half-duplex cooperative channels. *Information Theory, IEEE Transactions on*, 2005. 51(12): 4152–4172.
58. Gharan, S. O., Bayesteh, A. and Khandani, A. K. Diversity-Multiplexing Tradeoff in Multiantenna Multirelay Networks: Improvements and Some Optimality Results. *Information Theory, IEEE Transactions on*, 2013. 59(6): 3892–3914.
59. Zheng, L. and Tse, D. N. C. Diversity and multiplexing: a fundamental tradeoff in multiple-antenna channels. *Information Theory, IEEE Transactions on*, 2003. 49(5): 1073–1096.
60. Costa, N. and Haykin, S. *Multiple-input, multiple-output channel models : theory and practice*. Wiley series in adaptive and learning systems for signal processing, communication and control. IEEE, Institute of Electrical and Electronic Engineers Hoboken, N.J. John Wiley. 2010.
61. Ding, Z., Krikidis, I., Sharif, B. and Poor, H. V. Impact of channel state information on wireless energy harvesting cooperative networks with spatially random relays. *2014 IEEE International Conference on Communications (ICC)*. 2014. ISSN 1550-3607. 4072–4076. doi: 10.1109/ICC.2014.6883958.
62. Burghal, D. and Molisch, A. F. Efficient Channel State Information Acquisition for Device-to-Device Networks. *IEEE Transactions on Wireless Communications*, 2016. 15(2): 965–979.
63. Laiho, J., Wacker, A. and Novosad, T. *Radio network planning and optimisation for UMTS*. John Wiley & Sons. 2006.
64. Shin, H. and Lee, J. H. Closed-form formulas for ergodic capacity of MIMO Rayleigh fading channels. *Communications, 2003. ICC'03. IEEE International Conference on*. IEEE. 2003, vol. 5. 2996–3000.
65. Alamouti, S. A simple transmit diversity technique for wireless

- communications. *Selected Areas in Communications, IEEE Journal on*, 1998. 16(8): 1451–1458.
66. Laneman, J. N. and Wornell, G. W. Distributed space-time-coded protocols for exploiting cooperative diversity in wireless networks. *Information Theory, IEEE Transactions on*, 2003. 49(10): 2415–2425.
 67. Kong, L., Ng, S. X., Maunder, R. G. and Hanzo, L. Near-capacity cooperative space-time coding employing irregular design and successive relaying. *Communications, IEEE Transactions on*, 2010. 58(8): 2232–2241.
 68. Rupp, M., Mecklenbrauker, C. and Gritsch, G. High diversity with simple space time block-codes and linear receivers. *Global Telecommunications Conference, 2003. GLOBECOM'03. IEEE. IEEE*. 2003, vol. 1. 302–306.
 69. Lee, K.-J., Sung, H., Park, E. and Lee, I. Joint optimization for one and two-way MIMO AF multiple-relay systems. *Wireless Communications, IEEE Transactions on*, 2010. 9(12): 3671–3681.
 70. Van Der Meulen, E. C. Three-terminal communication channels. *Advances in applied Probability*, 1971: 120–154.
 71. Shende, N., Gurbuz, O. and Erkip, E. Half-duplex or full-duplex relaying: A capacity analysis under self-interference. *Information Sciences and Systems (CISS), 2013 47th Annual Conference on. IEEE*. 2013. 1–6.
 72. Suraweera, H., Krikidis, I., Zheng, G., Yuen, C. and Smith, P. Low-Complexity End-to-End Performance Optimization in MIMO Full-Duplex Relay Systems. 2014.
 73. Luo, S., Liu, P. and Panwar, S. Full-Duplex Relaying in an Infrastructure-based Wireless Network. *Vehicular Technology Conference (VTC Fall), 2014 IEEE 80th. IEEE*. 2014. 1–6.
 74. Choi, J. I., Jain, M., Srinivasan, K., Levis, P. and Katti, S. Achieving single channel, full duplex wireless communication. *Proceedings of the sixteenth annual international conference on Mobile computing and networking. ACM*. 2010. 1–12.
 75. Sharma, G., Sharma, P. K. and Garg, P. Performance analysis of full duplex relaying in multicell environment. *Advances in Computing, Communications and Informatics (ICACCI, 2014 International Conference on. IEEE*. 2014. 2501–2505.
 76. Dohler, M. and Li, Y. *Cooperative communications: hardware, channel and PHY*. John Wiley & Sons. 2010.

77. UMTS Forum. Mobile traffic forecasts 2010-2020 report, London, U.K., [Online]. URL http://www.ums-forum.org/component/option,com_docman/task,cat_view/gid,485/Itemid,213/.
78. Monteiro, F. A. T. B. N. In-Band Full-Duplex Architectures for Future 5G Multi-Hop Networks. 2015.
79. Wichman, R. *Optimized Full-Duplex Multi-Antenna Relay in Single-Input Single-Output Link*. Ph.D. Thesis. Aalto University. 2013.
80. Duarte, M., Sabharwal, A., Aggarwal, V., Jana, R., Ramakrishnan, K., Rice, C. W. and Shankaranarayanan, N. Design and characterization of a full-duplex multiantenna system for WiFi networks. *IEEE Transactions on Vehicular Technology*, 2014. 63(3): 1160–1177.
81. Everett, E., Sahai, A. and Sabharwal, A. Passive self-interference suppression for full-duplex infrastructure nodes. *IEEE Transactions on Wireless Communications*, 2014. 13(2): 680–694.
82. Sabharwal, A., Schniter, P., Guo, D., Bliss, D. W., Rangarajan, S. and Wichman, R. In-band full-duplex wireless: Challenges and opportunities. *IEEE Journal on Selected Areas in Communications*, 2014. 32(9): 1637–1652.
83. Aryafar, E., Khojastepour, M. A., Sundaresan, K., Rangarajan, S. and Chiang, M. MIDU: enabling MIMO full duplex. *Proceedings of the 18th annual international conference on Mobile computing and networking*. ACM. 2012. 257–268.
84. Chen, S., Beach, M. and McGeehan, J. Division-free duplex for wireless applications. *Electronics Letters*, 1998. 34(2): 147–148.
85. Slingsby, W. and McGeehan, J. Antenna isolation measurements for on-frequency radio repeaters. *Antennas and Propagation, 1995., Ninth International Conference on (Conf. Publ. No. 407)*. IET. 1995. 239–243.
86. Everett, E., Duarte, M., Dick, C. and Sabharwal, A. Empowering full-duplex wireless communication by exploiting directional diversity. *2011 Conference Record of the Forty Fifth Asilomar Conference on Signals, Systems and Computers (ASILOMAR)*. IEEE. 2011. 2002–2006.
87. Duarte, M. and Sabharwal, A. Full-duplex wireless communications using off-the-shelf radios: Feasibility and first results. *2010 Conference Record of the Forty Fourth Asilomar Conference on Signals, Systems and Computers*. IEEE. 2010. 1558–1562.

88. Duarte, M., Dick, C. and Sabharwal, A. Experiment-driven characterization of full-duplex wireless systems. *IEEE Transactions on Wireless Communications*, 2012. 11(12): 4296–4307.
89. Day, B. P., Margetts, A. R., Bliss, D. W. and Schniter, P. Full-duplex bidirectional MIMO: Achievable rates under limited dynamic range. *IEEE Transactions on Signal Processing*, 2012. 60(7): 3702–3713.
90. Fan, Y., Wang, C., Thompson, J. and Poor, H. V. Recovering multiplexing loss through successive relaying using repetition coding. *Wireless Communications, IEEE Transactions on*, 2007. 6(12): 4484–4493.
91. Ding, Z., Krikidis, I., Rong, B., Thompson, J. S., Wang, C. and Yang, S. On combating the half-duplex constraint in modern cooperative networks: protocols and techniques. *Wireless Communications, IEEE*, 2012. 19(6): 20–27.
92. Hong, B. and Choi, W. Overcoming half-duplex loss in multi-relay networks: multiple relay coded cooperation for optimal DMT. 2015.
93. Nomikos, N., Vouyioukas, D., Charalambous, T., Krikidis, I., Skoutas, D. and Johansson, M. Capacity improvement through buffer-aided successive opportunistic relaying. *Wireless Communications, Vehicular Technology, Information Theory and Aerospace & Electronic Systems (VITAE), 2013 3rd International Conference on*. IEEE. 2013. 1–5.
94. Zlatanov, N. and Schober, R. Buffer-aided half-duplex relaying can outperform ideal full-duplex relaying. *IEEE Communications Letters*, 2013. 17(3): 479–482.
95. Guo, D. and Zhang, L. Virtual full-duplex wireless communication via rapid on-off-division duplex. *Communication, Control, and Computing (Allerton), 2010 48th Annual Allerton Conference on*. IEEE. 2010. 412–419.
96. Sahin, O., Simeone, O. and Erkip, E. Interference channel with an out-of-band relay. *IEEE Transactions on Information Theory*, 2011. 57(5): 2746–2764.
97. Lameiro, C., Vía, J. and Santamaría, I. Amplify-and-Forward Strategies in the Two-Way Relay Channel With Analog Tx–Rx Beamforming. *Vehicular Technology, IEEE Transactions on*, 2013. 62(2): 642–654.
98. Leow, C. Y., Ding, Z., Leung, K. K. and Goeckel, D. L. On the study of analogue network coding for multi-pair, bidirectional relay channels. *Wireless Communications, IEEE Transactions on*, 2011. 10(2): 670–681.

99. Leow, C. Y., Ding, Z. and Leung, K. K. Linear precoded cooperative transmission protocol for wireless broadcast channels. *Vehicular Technology, IEEE Transactions on*, 2011. 60(7): 3509–3515.
100. Gunduz, D., Khojastepour, M. A., Goldsmith, A. and Poor, H. V. Multi-hop MIMO relay networks: diversity-multiplexing trade-off analysis. *Wireless Communications, IEEE Transactions on*, 2010. 9(5): 1738–1747.
101. Oechtering, T. and Sezgin, A. A new cooperative transmission scheme using the space-time delay code. *Smart Antennas, 2004. ITG Workshop on*. IEEE. 2004. 41–48.
102. Ribeiro, A., Cai, X. and Giannakis, G. B. Opportunistic multipath for bandwidth-efficient cooperative networking. *Acoustics, Speech, and Signal Processing, 2004. Proceedings.(ICASSP'04). IEEE International Conference on*. IEEE. 2004, vol. 4. iv–549.
103. Li, L., Wang, L. and Hanzo, L. Capacity analysis of the successive AF relaying aided cooperative DS-CDMA uplink. *Wireless Communications and Networking Conference (WCNC), 2012 IEEE*. IEEE. 2012. 3057–3062.
104. Li, L., Wang, L. and Hanzo, L. Successive DF relaying: MS-DIS aided interference suppression and three-stage concatenated architecture design. *Communications (ICC), 2012 IEEE International Conference on*. IEEE. 2012. 4447–4451.
105. Li, L., Wang, L. and Hanzo, L. Successive AF/DF relaying in the cooperative DS-CDMA uplink: Capacity analysis and its system architecture. *Vehicular Technology, IEEE Transactions on*, 2013. 62(2): 655–666.
106. Luo, C., Gong, Y. and Zheng, F. Full interference cancellation for two-path relay cooperative networks. *Vehicular Technology, IEEE Transactions on*, 2011. 60(1): 343–347.
107. Ji, Y., Han, C., Wang, A. and Shi, H. Partial Inter-Relay Interference Cancellation in Two Path Successive Relay Network. *IEEE Communications Letters*, 2014. 18(3): 451–454. ISSN 1089-7798. doi:10.1109/LCOMM.2014.011714.140016.
108. Park, H. and Chun, J. Inter-Relay Interference Cancellation for AF MIMO Two-Path Relay Systems. *Vehicular Technology Conference (VTC Fall), 2012 IEEE*. IEEE. 2012. 1–5.
109. Hu, Y., Li, K. H. and Teh, K. C. An efficient successive relaying protocol for multiple-relay cooperative networks. *Wireless Communications, IEEE Transactions on*, 2012. 11(5): 1892–1899.

110. Jiang, Y. and Varanasi, M. K. Diversity-multiplexing tradeoff of MIMO systems with antenna selection. *Information Theory, 2007. ISIT 2007. IEEE International Symposium on*. IEEE. 2007. 2836–2840.
111. Zhou, L. and Ohashi, Y. Fast and efficient transmit antenna selection algorithms in spatial multiplexing systems. *European Wireless, 2012. EW. 18th European Wireless Conference*. VDE. 2012. 1–5.
112. Moradi, S., Doostnejad, R. and Gulak, P. G. Downlink Beamforming for FDD Systems with Precoding and Beam Steering. *Global Telecommunications Conference (GLOBECOM 2011), 2011 IEEE*. IEEE. 2011. 1–6.
113. Wang, C., Fan, Y., Krikidis, I., Thompson, J. S. and Poor, H. V. Superposition-coded concurrent decode-and-forward relaying. 2008: 2390–2394. ISSN 2157-8095. doi:10.1109/ISIT.2008.4595419.
114. Zhong, C., Suraweera, H., Zheng, G., Krikidis, I., Zhang, Z. *et al.* Wireless information and power transfer with full duplex relaying. *Communications, IEEE Transactions on*, 2014. 62(10): 3447–3461.
115. Shinohara, N. Power without wires. *IEEE Microwave Magazine*, 2011. 12(7): S64–S73.
116. Sample, A. and Smith, J. R. Experimental results with two wireless power transfer systems. *2009 IEEE Radio and Wireless Symposium*. IEEE. 2009. 16–18.
117. Varshney, L. R. Transporting information and energy simultaneously. *2008 IEEE International Symposium on Information Theory*. IEEE. 2008. 1612–1616.
118. Liu, Y., Ding, Z., El Kashlan, M. and Poor, H. V. Cooperative Non-orthogonal Multiple Access With Simultaneous Wireless Information and Power Transfer. *IEEE Journal on Selected Areas in Communications*, 2016. 34(4): 938–953. ISSN 0733-8716. doi:10.1109/JSAC.2016.2549378.
119. Diamantoulakis, P., Pappi, K., Ding, Z. and Karagiannidis, G. Wireless Powered Communications with Non-Orthogonal Multiple Access. *IEEE Transactions on Wireless Communications*, 2016. PP(99): 1–1. ISSN 1536-1276. doi:10.1109/TWC.2016.2614937.
120. Dong, Y., Hossain, M. J. and Cheng, J. Joint power control and time switching for SWIPT systems with heterogeneous QoS requirements. *IEEE Communications Letters*, 2016. 20(2): 328–331.

121. Ding, Z., Zhong, C., Ng, D. W. K., Peng, M., Suraweera, H. A., Schober, R. and Poor, H. V. Application of smart antenna technologies in simultaneous wireless information and power transfer. *IEEE Communications Magazine*, 2015. 53(4): 86–93. ISSN 0163-6804. doi:10.1109/MCOM.2015.7081080.
122. Benkhelifa, F., Salem, A. and Alouini, M.-S. Simultaneous Wireless Information and Power Transfer for Decode-and-Forward MIMO Relay Communication Systems. *Vehicular Technology Conference (VTC Spring), 2015 IEEE 81st*. 2015. 1–5. doi:10.1109/VTCSpring.2015.7146087.
123. Chen, Z., Yuan, J. and Vucetic, B. Analysis of transmit antenna selection/maximal-ratio combining in Rayleigh fading channels. *IEEE Transactions on Vehicular Technology*, 2005. 54(4): 1312–1321.
124. Xu, W., Yang, Z., Ding, Z., Wang, L. and Fan, P. Wireless information and power transfer in two-way relaying network with non-coherent differential modulation. *EURASIP Journal on Wireless Communications and Networking*, 2015. 2015(1): 131.
125. Wang, J., Kim, Y., Song, I., Cosman, P. and Milstein, L. Cooperative Relaying of Superposition Coding with Simple Feedback for Layered Source Transmission. 2013.
126. Xiong, K., Fan, P., Xu, Z., Yang, H. and Letaief, K. Optimal Cooperative Beamforming Design for MIMO Decode-and-Forward Relay Channels. 2014. 62(6): 1476–1489.
127. Hu, R. and Lok, T. M. Power splitting and relay optimization for two-way relay SWIPT systems. *2016 IEEE International Conference on Communications (ICC)*. 2016. 1–6. doi:10.1109/ICC.2016.7510858.
128. Kanchan, A. and Dwivedi, S. Comparison of BER Performance in OFDM Using Different Equalization Techniques. *International Journal of Engineering and Advanced Technology*, 2012. 1(6).
129. Zhao, S., Li, Q., Zhang, Q. and Qin, J. Antenna selection for simultaneous wireless information and power transfer in MIMO systems. *Communications Letters, IEEE*, 2014. 18(5): 789–792.
130. Mahadevan, S. Monte carlo simulation. *MECHANICAL ENGINEERING-NEW YORK AND BASEL-MARCEL DEKKER-*, 1997: 123–146.
131. Tuy, H. *Convex analysis and global optimization*. vol. 22. Springer Science & Business Media. 2013.
132. Boyd, S. and Vandenberghe, L. *Convex optimization*. Cambridge university

- press. 2004.
133. Rezaei, S. S. C., Gharan, S. O. and Khandani, A. K. Cooperative strategies for the half-duplex Gaussian parallel relay channel: simultaneous relaying versus successive relaying. *Communication, Control, and Computing, 2008 46th Annual Allerton Conference on*. IEEE. 2008. 1309–1316.
 134. Chen, W., Chen, Z. and Zhou, C. Joint source-relay optimization for two-path MIMO AF relay system. *Wireless Communications, Networking and Mobile Computing (WiCOM), 2012 8th International Conference on*. IEEE. 2012. 1–5.
 135. Zhang, Y., Zhang, Z., Ping, L., Chen, X. and Zhong, C. Capacity scaling of relay networks with successive relaying. *2015 IEEE International Symposium on Information Theory (ISIT)*. 2015. ISSN 2157-8095. 176–180. doi:10.1109/ISIT.2015.7282440.
 136. Chen, W. CAO-SIR: Channel Aware Ordered Successive Relaying. *IEEE Transactions on Wireless Communications*, 2014. 13(12): 6513–6527. ISSN 1536-1276. doi:10.1109/TWC.2014.2363453.
 137. Li, L., Wang, L. and Hanzo, L. Generalized Adaptive Network Coding Aided Successive Relaying for Noncoherent Cooperation. *IEEE Transactions on Communications*, 2013. 61(5): 1750–1763. ISSN 0090-6778. doi:10.1109/TCOMM.2013.022713.120339.
 138. Gupta, S., Zhang, R. and Hanzo, L. Throughput Maximization for a Buffer-Aided Successive Relaying Network Relying on Energy Harvesting. *IEEE Transactions on Vehicular Technology*, 2015. PP(99): 1–1. ISSN 0018-9545. doi:10.1109/TVT.2015.2477808.
 139. Rui, X., Wang, M. and Liu, S. Inter-relay interference suppression for two-path MIMO relay systems. *Electronics Letters*, 2016. 52(9): 774–776. ISSN 0013-5194. doi:10.1049/el.2015.4006.
 140. Chen, S., Zhang, Z., Yin, R., Chen, X. and Wang, W. Concatenated channel-and-network coding scheme for two-path successive relay network. *Communications, IET*, 2013. 7(1): 82–90.
 141. Lehmann, F. A factor graph approach to iterative channel estimation, detection and decoding for two-path successive relay networks. *IEEE Transactions on Wireless Communications*, 2016. PP(99): 1–1. ISSN 1536-1276. doi:10.1109/TWC.2016.2558188.
 142. Zhao, Y., Tan, C. W., Avestimehr, A. S., Diggavi, S. N. and Pottie, G. J. On the Maximum Achievable Sum-Rate With Successive Decoding

- in Interference Channels. *IEEE Transactions on Information Theory*, 2012. 58(6): 3798–3820. ISSN 0018-9448. doi:10.1109/TIT.2012.2190040.
143. Wicaksana, H., Ting, S. H., Ho, C. K., Chin, W. H. and Guan, Y. L. AF two-path half duplex relaying with inter-relay self interference cancellation: diversity analysis and its improvement. *IEEE Transactions on Wireless Communications*, 2009. 8(9): 4720–4729. ISSN 1536-1276. doi:10.1109/TWC.2009.081249.
 144. Jeffrey, A. and Zwillinger, D. *Table of integrals, series, and products*. Academic Press. 2007.
 145. Molisch, A. F., Win, M. Z. and Winters, J. H. Reduced-complexity transmit/receive-diversity systems. *Signal Processing, IEEE Transactions on*, 2003. 51(11): 2729–2738.
 146. Paulraj, A., Nabar, R. and Gore, D. *Introduction to space-time wireless communications*. Cambridge university press. 2003.
 147. Telatar, E. Capacity of Multi-antenna Gaussian Channels. *European transactions on telecommunications*, 1999. 10(6): 585–595.
 148. Chu, C.-C., Wang, H.-C. and Wang, C.-L. Suboptimal power allocation for a two-path successive relay system with full interference cancellation. *Vehicular Technology Conference (VTC Spring), 2012 IEEE 75th*. IEEE. 2012. 1–5.
 149. Luo, C., Gong, Y. and Zheng, F. Full interference cancellation for two-path cooperative communications. *Wireless Communications and Networking Conference, 2009. WCNC 2009. IEEE*. IEEE. 2009. 1–5.
 150. Jiang, M. and Hou, W. Inter-Relay Interference Mitigation for AF-Based Successive Relay Systems. *2014 IEEE 80th Vehicular Technology Conference (VTC2014-Fall)*. 2014. ISSN 1090-3038. 1–5. doi:10.1109/VTCFall.2014.6966019.
 151. Feng, L., Chen, L. and Hua-An, Z. On the joint optimal power allocation for df relaying and beamforming communication systems. *IEICE transactions on communications*, 2012. 95(3): 889–897.
 152. Fang, B., Zhong, W., Qian, Z., Jin, S., Wang, J. and Shao, W. Distributed precoding for wireless information and power transfer in MIMO DF relay networks. *Wireless Communications and Signal Processing (WCSP), 2014 Sixth International Conference on*. 2014. 1–6. doi:10.1109/WCSP.2014.6992082.

153. Chalise, B., Ma, W.-K., Zhang, Y., Suraweera, H. and Amin, M. Optimum Performance Boundaries of OSTBC Based AF-MIMO Relay System With Energy Harvesting Receiver. *Signal Processing, IEEE Transactions on*, 2013. 61(17): 4199–4213. ISSN 1053-587X. doi:10.1109/TSP.2013.2265224.
154. Liu, H., Kim, K. J. and Kwak, K. S. Relay Control for Full-Duplex Relaying with Wireless Information and Energy Transfer. *arXiv preprint arXiv:1503.04381*, 2015.
155. Mohammadi, M., Suraweera, H. A., Zheng, G., Zhong, C. and Krikidis, I. Full-Duplex MIMO Relaying Powered by Wireless Energy Transfer. *arXiv preprint arXiv:1505.00080*, 2015.
156. Nintanavongsa, P., Muncuk, U., Lewis, D. R. and Chowdhury, K. R. Design Optimization and Implementation for RF Energy Harvesting Circuits. *IEEE Journal on Emerging and Selected Topics in Circuits and Systems*, 2012. 2(1): 24–33. ISSN 2156-3357. doi:10.1109/JETCAS.2012.2187106.
157. Park, J. and Clerckx, B. Joint Wireless Information and Energy Transfer in a-User MIMO Interference Channel. *Wireless Communications, IEEE Transactions on*, 2014. 13(10): 5781–5796.
158. Proakis, J. *Digital Communications*. 3rd ed. New York:McGraw-Hill. 1995. ISBN 9780072321111.
159. Cover, T. M. and Thomas, J. A. *Elements of information theory*. John Wiley & Sons. 2012.
160. Medepally, B. and Mehta, N. B. Voluntary Energy Harvesting Relays and Selection in Cooperative Wireless Networks. *IEEE Transactions on Wireless Communications*, 2010. 9(11): 3543–3553. ISSN 1536-1276. doi:10.1109/TWC.2010.091510.100447.
161. Loy, M. Understanding and enhancing sensitivity in receivers for wireless applications. *TI Technical Brief SWRA030*, 1999.
162. Lu, X., Wang, P., Niyato, D., Kim, D. I. and Han, Z. Wireless networks with RF energy harvesting: A contemporary survey. *Communications Surveys & Tutorials, IEEE*, 2015. 17(2): 757–789.
163. Sudevalayam, S. and Kulkarni, P. Energy harvesting sensor nodes: Survey and implications. *Communications Surveys & Tutorials, IEEE*, 2011. 13(3): 443–461.
164. Peng, S., Wang, T. and Low, C. Energy neutral clustering for energy harvesting wireless sensors networks. *Ad Hoc Networks*, 2015. 28: 1–16.

165. Mogensen, P., Pajukoski, K., Tirola, E., Lähetkangas, E., Vihriälä, J., Vesterinen, S., Laitila, M., Berardinelli, G., Da Costa, G. W. O., Garcia, L. G. U. *et al.* 5G small cell optimized radio design. *IEEE*. 2013.
166. Nikolov, M. and Haas, Z. J. Relay Placement in Wireless Networks: Minimizing Communication Cost. *IEEE Transactions on Wireless Communications*, 2016. 15(5): 3587–3602. ISSN 1536-1276. doi:10.1109/TWC.2016.2523984.
167. Chen, X., Song, S. H. and Letaief, K. B. Relay Position Optimization Improves Finite-SNR Diversity Gain of Decode-and-Forward MIMO Relay Systems. *IEEE Transactions on Communications*, 2012. 60(11): 3311–3321. ISSN 0090-6778. doi:10.1109/TCOMM.2012.100312.110033.
168. Gu, Y. and Aissa, S. Interference aided energy harvesting in decode-and-forward relaying systems. *Communications (ICC), 2014 IEEE International Conference on*. IEEE. 2014. 5378–5382.
169. Katti, S., Gollakota, S. and Katabi, D. Embracing wireless interference: analog network coding. *ACM SIGCOMM Computer Communication Review*. ACM. 2007, vol. 37. 397–408.
170. Efrat, A., Fekete, S. P., Gaddehosur, P. R., Mitchell, J. S., Polishchuk, V. and Suomela, J. Improved approximation algorithms for relay placement. In: *Algorithms-ESA 2008*. Springer. 356–367. 2008.
171. Khakurel, S., Mehta, M. and Karandikar, A. Optimal relay placement for coverage extension in LTE-A cellular systems. *Communications (NCC), 2012 National Conference on*. IEEE. 2012. 1–5.
172. Bao, V. N. Q., Thanh, T. T., Nguyen, T. D. and Vu, T. D. Spectrum sharing-based multi-hop decode-and-forward relay networks under interference constraints: Performance analysis and relay position optimization. *Communications and Networks, Journal of*, 2013. 15(3): 266–275.
173. Scutari, G., Palomar, D. P. and Barbarossa, S. The MIMO iterative waterfilling algorithm. *Signal Processing, IEEE Transactions on*, 2009. 57(5): 1917–1935.
174. Lozano, A., Tulino, A. M. and Verdú, S. Multiple-antenna capacity in the low-power regime. *Information Theory, IEEE Transactions on*, 2003. 49(10): 2527–2544.
175. Leadbetter, M. Extreme value theory under weak mixing conditions. *Studies in Probability Theory, MAA Studies in Mathematics*, 1978. 18: 46–110.

176. Gore, D. A., Heath, R. W. and Paulraj, A. J. Transmit selection in spatial multiplexing systems. *Communications Letters, IEEE*, 2002. 6(11): 491–493.
177. Golub, G. H. and Van Loan, C. F. *Matrix computations*. vol. 3. JHU Press. 2012.