



US009297205B2

(12) **United States Patent**
Benson et al.

(10) **Patent No.:** **US 9,297,205 B2**
(45) **Date of Patent:** **Mar. 29, 2016**

(54) **SYSTEM AND METHOD FOR CONTROLLING A DRILLING PATH BASED ON DRIFT ESTIMATES**

(71) Applicants: **HUNT ADVANCED DRILLING TECHNOLOGIES, L.L.C.**, Dallas, TX (US); **BOARD OF REGENTS, THE UNIVERSITY OF TEXAS SYSTEM**, Austin, TX (US)

(72) Inventors: **Todd W. Benson**, Dallas, TX (US); **Teddy Chen**, Austin, TX (US); **Sashmit Bhaduri**, Austin, TX (US)

(73) Assignees: **Hunt Advanced Drilling Technologies, LLC**, Dallas, TX (US); **Board of Regents, The University of Texas System**, Austin, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/677,648**

(22) Filed: **Apr. 2, 2015**

(65) **Prior Publication Data**

US 2015/0233229 A1 Aug. 20, 2015

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/095,073, filed on Dec. 3, 2013, which is a continuation of application No. 13/530,298, filed on Jun. 22, 2012, now Pat. No. 8,596,385, which is a continuation-in-part of application No. 13/334,370, filed on Dec. 22, 2011, now Pat. No. 8,210,283.

(51) **Int. Cl.**
E21B 7/06 (2006.01)
E21B 7/10 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC ... **E21B 7/06** (2013.01); **E21B 7/10** (2013.01); **G05B 15/02** (2013.01); **E21B 47/024** (2013.01)

(58) **Field of Classification Search**
CPC E21B 7/06; E21B 7/10; E21B 47/024
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,794,534 A 12/1988 Millheim
5,193,628 A 3/1993 Hill et al.

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2236782 A 4/1991
WO 2005071441 A1 8/2005

(Continued)

OTHER PUBLICATIONS

Saputelli, L. et al., "Real-Time Decision-Making for Value Creation While Drilling," SPE/IADC 85314; Middle East Drilling Technology Conference & Exhibition Held in Abu Dhabi, UAE, Oct. 20-22, 2003; 19 Pages.

(Continued)


Primary Examiner — Blake Michener

(74) *Attorney, Agent, or Firm* — Howison & Arnott, LLP

(57) **ABSTRACT**

A method includes receiving toolface information corresponding to a location of the bottom hole assembly (BHA) with respect to a target drilling path and drift information. The surface steerable system calculates a first toolface vector from a first location of the BHA to the target drilling path to create a convergence path to the target drilling path and calculates an adjustment of the first toolface vector to a second toolface vector to account for system drift defined by the drift information such that the BHA will converge with the target drilling path by drilling in accordance with the second toolface vector. The surface steerable system modifies at least one drilling parameter to alter a drilling direction of the BHA based on the calculated second toolface vector and transmits the at least one drilling parameter to the drilling rig to target the BHA in accordance with the second toolface vector.

20 Claims, 24 Drawing Sheets



(51)	<p>Int. Cl. <i>E21B 47/024</i> (2006.01) <i>G05B 15/02</i> (2006.01)</p>	<p>2004/0222023 A1* 11/2004 Hacı et al. 175/61 2004/0238222 A1* 12/2004 Harrison 175/61 2005/0194130 A1 9/2005 Best et al. 2005/0194185 A1 9/2005 Gleitman 2006/0151214 A1 7/2006 Prange et al. 2008/0172272 A1 7/2008 Back et al. 2009/0076873 A1 3/2009 Johnson et al. 2009/0090555 A1 4/2009 Boone et al. 2009/0120690 A1 5/2009 Phillips 2010/0139977 A1 6/2010 Watkins et al. 2011/0067928 A1 3/2011 Hulden et al. 2012/0024606 A1 2/2012 Pirovolou et al. 2012/0048621 A1 3/2012 Stewart et al. 2013/0032402 A1 2/2013 Byreddy et al. 2013/0092441 A1 4/2013 Hummes et al. 2013/0161096 A1* 6/2013 Benson et al. 175/26 2013/0262048 A1 10/2013 Tang et al. 2013/0340999 A1 12/2013 Benson 2015/0006227 A1* 1/2015 Benson et al. 705/7.23</p>
(56)	<p style="text-align: center;">References Cited</p> <p style="text-align: center;">U.S. PATENT DOCUMENTS</p> <p>5,220,963 A 6/1993 Patton 5,812,068 A 9/1998 Wisler et al. 6,233,524 B1 5/2001 Harrell et al. 6,272,434 B1 8/2001 Wisler et al. 6,408,953 B1 6/2002 Goldman et al. 6,424,919 B1 7/2002 Moran et al. 6,523,623 B1 2/2003 Schuh 6,577,954 B2 6/2003 Alft et al. 6,612,382 B2 9/2004 King 6,732,052 B2 5/2004 MacDonald et al. 7,000,710 B1 2/2006 Umbach 7,003,439 B2 2/2006 Aldred et al. 7,032,689 B2 4/2006 Goldman et al. 7,054,750 B2 5/2006 Rodney et al. 7,085,696 B2 8/2006 King 7,136,795 B2 11/2006 Downton 7,142,986 B2 11/2006 Moran 7,460,957 B2 12/2008 Prange et al. 7,606,666 B2 10/2009 Repin et al. 7,653,563 B2 1/2010 Veeningen et al. 7,684,929 B2 3/2010 Prange et al. 7,823,655 B2 11/2010 Boone et al. 7,860,593 B2 12/2010 Boone 7,938,197 B2 5/2011 Boone et al. 7,945,488 B2 5/2011 Karr et al. 8,010,290 B2 8/2011 Illfelder 8,210,283 B1* 7/2012 Benson et al. 175/61 2001/0042642 A1 11/2001 King 2001/0054514 A1 12/2001 Sullivan et al. 2002/0104685 A1* 8/2002 Pinckard et al. 175/61 2002/0139581 A1 10/2002 Schultz et al. 2003/0024738 A1 2/2003 Schuh</p>	<p style="text-align: center;">FOREIGN PATENT DOCUMENTS</p> <p>WO 2009039448 A2 3/2009 WO 2009129461 A2 10/2009 WO 2011130159 A2 10/2011</p> <p style="text-align: center;">OTHER PUBLICATIONS</p> <p>Patent Cooperation Treaty: International Search Report and Written Opinion for PCT/US2013/047054; Jun. 25, 2014, Brassart, P., 17 pages. Mitchell, Robert et al.; "Lateral Buckling—The Key to Lockup," SPE/IADC Drilling Conference and Exhibition, Sep. 30, 2011, XP055122198, DOI: 10.2118/139824-MS, p. 1, col. 2, lines 14-16. Patent Cooperation Treaty: International Preliminary Report on Patentability for PCT/US2013/047054; Dec. 23, 2014, Brassart, P., 9 pages.</p> <p>* cited by examiner</p>




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3





FIG. 4






FIG. 6




FIG. 8A




FIG. 8B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8C




FIG. 8D




FIG. 9




FIG. 10




FIG. 11




FIG. 12










FIG. 13






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25





FIG. 28




FIG. 27A




FIG. 27B




FIG. 27C

SYSTEM AND METHOD FOR CONTROLLING A DRILLING PATH BASED ON DRIFT ESTIMATES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 14/095,073, filed Dec. 3, 2013, and entitled "SYSTEM AND METHOD FOR DETERMINING INCREMENTAL PROGRESSION BETWEEN SURVEY POINTS WHILE DRILLING", which is a continuation of U.S. patent application Ser. No. 13/530,298, filed Jun. 22, 2012, and entitled "SYSTEM AND METHOD FOR DETERMINING INCREMENTAL PROGRESSION BETWEEN SURVEY POINTS WHILE DRILLING," now U.S. Pat. No. 8,596,385, issued Dec. 3, 2013, which is a continuation-in-part of U.S. patent application Ser. No. 13/334,370, filed on Dec. 22, 2011, and entitled "SYSTEM AND METHOD FOR SURFACE STEERABLE DRILLING," now U.S. Pat. No. 8,210,283, issued Jul. 3, 2013, the specifications of which are incorporated by reference herein in their entirety.

TECHNICAL FIELD

This application is directed to the creation of wells, such as oil wells, and more particularly to the planning and drilling of such wells.

SUMMARY

The present invention, as disclosed and described herein, in one aspect thereof, includes a surface steerable system for receiving toolface information from a bottom hole assembly (BHA) located in a borehole. The toolface information corresponds to a location of the BHA with respect to a target drilling path and drift information. The surface steerable system calculates a first toolface vector from a first location of the BHA to the target drilling path to create a convergence path from the location of the BHA to the target drilling path. The surface steerable system calculates an adjustment of the first toolface vector to a second toolface vector to account for system drift defined by the drift information such that the BHA will converge with the target drilling path by drilling in accordance with the second toolface vector. The surface steerable system modifies at least one drilling parameter in order to alter a drilling direction of the BHA based on the calculated second toolface vector and transmits the at least one drilling parameter to the drilling rig to target the BHA in accordance with the second toolface vector.

BACKGROUND

Drilling a borehole for the extraction of minerals has become an increasingly complicated operation due to the increased depth and complexity of many boreholes, including the complexity added by directional drilling. Drilling is an expensive operation and errors in drilling add to the cost and, in some cases, drilling errors may permanently lower the output of a well for years into the future. Current technologies and methods do not adequately address the complicated nature of drilling. Accordingly, what is needed are a system and method to improve drilling operations and minimize drilling errors.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding, reference is now made to the following description taken in conjunction with the accompanying drawings in which:

FIG. 1A illustrates one embodiment of a drilling environment in which a surface steerable system may operate;

FIG. 1B illustrates one embodiment of a more detailed portion of the drilling environment of FIG. 1A;

FIG. 1C illustrates one embodiment of a more detailed portion of the drilling environment of FIG. 1B;

FIG. 2A illustrates one embodiment of the surface steerable system of FIG. 1A and how information may flow to and from the system;

FIG. 2B illustrates one embodiment of a display that may be used with the surface steerable system of FIG. 2A;

FIG. 3 illustrates one embodiment of a drilling environment that does not have the benefit of the surface steerable system of FIG. 2A and possible communication channels within the environment;

FIG. 4 illustrates one embodiment of a drilling environment that has the benefit of the surface steerable system of FIG. 2A and possible communication channels within the environment;

FIG. 5 illustrates one embodiment of data flow that may be supported by the surface steerable system of FIG. 2A;

FIG. 6 illustrates one embodiment of a method that may be executed by the surface steerable system of FIG. 2A;

FIG. 7A illustrates a more detailed embodiment of the method of FIG. 6;

FIG. 7B illustrates a more detailed embodiment of the method of FIG. 6;

FIG. 7C illustrates one embodiment of a convergence plan diagram with multiple convergence paths;

FIG. 8A illustrates a more detailed embodiment of a portion of the method of FIG. 7B;

FIG. 8B illustrates a more detailed embodiment of a portion of the method of FIG. 6;

FIG. 8C illustrates a more detailed embodiment of a portion of the method of FIG. 6;

FIG. 8D illustrates a more detailed embodiment of a portion of the method of FIG. 6;

FIG. 9 illustrates one embodiment of a system architecture that may be used for the surface steerable system of FIG. 2A;

FIG. 10 illustrates one embodiment of a more detailed portion of the system architecture of FIG. 9;

FIG. 11 illustrates one embodiment of a guidance control loop that may be used within the system architecture of FIG. 9;

FIG. 12 illustrates one embodiment of an autonomous control loop that may be used within the system architecture of FIG. 9;

FIG. 13 illustrates one embodiment of a computer system that may be used within the surface steerable system of FIG. 2A;

FIGS. 14A-14D illustrate embodiments of a portion of the drilling environment of FIG. 1B;

FIG. 14E illustrates FIGS. 14B-14D overlaid on one another;

FIG. 15 illustrates one embodiment of a three-dimensional borehole space.

FIG. 16 illustrates one embodiment of a method that may be executed by the surface steerable system of FIG. 2A to estimate a drill bit position between survey points.

FIG. 17 illustrates one embodiment of a method that represents a portion of the method of FIG. 16 in greater detail.

FIG. 18 illustrates one embodiment of a two-dimensional borehole space.

FIG. 19 illustrates another embodiment of a two-dimensional borehole space.

FIG. 20 illustrates another embodiment of the two-dimensional borehole space of FIG. 19.

FIG. 21 illustrates one embodiment of a method that represents a portion of the method of FIG. 16 in greater detail.

FIG. 22 illustrates one embodiment of a method that represents a portion of the method of FIG. 21 in greater detail.

FIG. 23 illustrates one embodiment of a method that may be executed by the surface steerable system of FIG. 2A.

FIG. 24 illustrates another embodiment of the display of FIG. 2B;

FIG. 25 illustrates one embodiment of a three-dimensional graph illustrating vectors representing information that may be displayed on the display of FIG. 24;

FIG. 26 illustrates a more particular embodiment of the slide planner for determining a drilling path responsive to drift information;

FIG. 27A illustrates a drilling path target selection using a sequence of slides and rotations;

FIG. 27B illustrates the generation of compensated drill paths based on formation drift;

FIG. 27C illustrates the generation of multiple portable compensated drill paths; and

FIG. 28 is a flow diagram illustrating the process of compensating a drilling path based on drift information.

DETAILED DESCRIPTION

Referring now to the drawings, wherein like reference numbers are used herein to designate like elements throughout, the various views and embodiments of a system and method for surface steerable drilling are illustrated and described, and other possible embodiments are described. The figures are not necessarily drawn to scale, and in some instances the drawings have been exaggerated and/or simplified in places for illustrative purposes only. One of ordinary skill in the art will appreciate the many possible applications and variations based on the following examples of possible embodiments.

Referring to FIG. 1A, one embodiment of an environment 100 is illustrated with multiple wells 102, 104, 106, 108, and a drilling rig 110. In the present example, the wells 102 and 104 are located in a region 112, the well 106 is located in a region 114, the well 108 is located in a region 116, and the drilling rig 110 is located in a region 118. Each region 112, 114, 116, and 118 may represent a geographic area having similar geological formation characteristics. For example, region 112 may include particular formation characteristics identified by rock type, porosity, thickness, and other geological information. These formation characteristics affect drilling of the wells 102 and 104. Region 114 may have formation characteristics that are different enough to be classified as a different region for drilling purposes, and the different formation characteristics affect the drilling of the well 106. Likewise, formation characteristics in the regions 116 and 118 affect the well 108 and drilling rig 110, respectively.

It is understood the regions 112, 114, 116, and 118 may vary in size and shape depending on the characteristics by which they are identified. Furthermore, the regions 112, 114, 116, and 118 may be sub-regions of a larger region. Accordingly, the criteria by which the regions 112, 114, 116, and 118 are identified is less important for purposes of the present disclosure than the understanding that each region 112, 114,

116, and 118 includes geological characteristics that can be used to distinguish each region from the other regions from a drilling perspective. Such characteristics may be relatively major (e.g., the presence or absence of an entire rock layer in a given region) or may be relatively minor (e.g., variations in the thickness of a rock layer that extends through multiple regions).

Accordingly, drilling a well located in the same region as other wells, such as drilling a new well in the region 112 with already existing wells 102 and 104, means the drilling process is likely to face similar drilling issues as those faced when drilling the existing wells in the same region. For similar reasons, a drilling process performed in one region is likely to face issues different from a drilling process performed in another region. However, even the drilling processes that created the wells 102 and 104 may face different issues during actual drilling as variations in the formation are likely to occur even in a single region.

Drilling a well typically involves a substantial amount of human decision making during the drilling process. For example, geologists and drilling engineers use their knowledge, experience, and the available information to make decisions on how to plan the drilling operation, how to accomplish the plan, and how to handle issues that arise during drilling. However, even the best geologists and drilling engineers perform some guesswork due to the unique nature of each borehole. Furthermore, a directional driller directly responsible for the drilling may have drilled other boreholes in the same region and so may have some similar experience, but it is impossible for a human to mentally track all the possible inputs and factor those inputs into a decision. This can result in expensive mistakes, as errors in drilling can add hundreds of thousands or even millions of dollars to the drilling cost and, in some cases, drilling errors may permanently lower the output of a well, resulting in substantial long term losses.

In the present example, to aid in the drilling process, each well 102, 104, 106, and 108 has corresponding collected data 120, 122, 124, and 126, respectively. The collected data may include the geological characteristics of a particular formation in which the corresponding well was formed, the attributes of a particular drilling rig, including the bottom hole assembly (BHA), and drilling information such as weight-on-bit (WOB), drilling speed, and/or other information pertinent to the formation of that particular borehole. The drilling information may be associated with a particular depth or other identifiable marker so that, for example, it is recorded that drilling of the well 102 from 1000 feet to 1200 feet occurred at a first ROP through a first rock layer with a first WOB, while drilling from 1200 feet to 1500 feet occurred at a second ROP through a second rock layer with a second WOB. The collected data may be used to recreate the drilling process used to create the corresponding well 102, 104, 106, or 108 in the particular formation. It is understood that the accuracy with which the drilling process can be recreated depends on the level of detail and accuracy of the collected data.

The collected data 120, 122, 124, and 126 may be stored in a centralized database 128 as indicated by lines 130, 132, 134, and 136, respectively, which may represent any wired and/or wireless communication channel(s). The database 128 may be located at a drilling hub (not shown) or elsewhere. Alternatively, the data may be stored on a removable storage medium that is later coupled to the database 128 in order to store the data. The collected data 120, 122, 124, and 126 may be stored in the database 128 as formation data 138, equipment data 140, and drilling data 142 for example. Formation data 138 may include any formation information, such as rock

type, layer thickness, layer location (e.g., depth), porosity, gamma readings, etc. Equipment data **140** may include any equipment information, such as drilling rig configuration (e.g., rotary table or top drive), bit type, mud composition, etc. Drilling data **142** may include any drilling information, such as drilling speed, WOB, differential pressure, toolface orientation, etc. The collected data may also be identified by well, region, and other criteria, and may be sortable to enable the data to be searched and analyzed. It is understood that many different storage mechanisms may be used to store the collected data in the database **128**.

With additional reference to FIG. 1B, an environment **160** (not to scale) illustrates a more detailed embodiment of a portion of the region **118** with the drilling rig **110** located at the surface **162**. A drilling plan has been formulated to drill a borehole **164** extending into the ground to a true vertical depth (TVD) **166**. The borehole **164** extends through strata layers **168** and **170**, stopping in layer **172**, and not reaching underlying layers **174** and **176**. The borehole **164** may be directed to a target area **180** positioned in the layer **172**. The target **180** may be a subsurface point or points defined by coordinates or other markers that indicate where the borehole **164** is to end or may simply define a depth range within which the borehole **164** is to remain (e.g., the layer **172** itself). It is understood that the target **180** may be any shape and size, and may be defined in any way. Accordingly, the target **180** may represent an endpoint of the borehole **164** or may extend as far as can be realistically drilled. For example, if the drilling includes a horizontal component and the goal is to follow the layer **172** as far as possible, the target may simply be the layer **172** itself and drilling may continue until a limit is reached, such as a property boundary or a physical limitation to the length of the drillstring. A fault **178** has shifted a portion of each layer downwards. Accordingly, the borehole **164** is located in non-shifted layer portions **168A-176A**, while portions **168B-176B** represent the shifted layer portions.

Current drilling techniques frequently involve directional drilling to reach a target, such as the target **180**. The use of directional drilling generally increases the amount of reserves that can be obtained and also increases production rate, sometimes significantly. For example, the directional drilling used to provide the horizontal portion shown in FIG. 1B increases the length of the borehole in the layer **172**, which is the target layer in the present example. Directional drilling may also be used alter the angle of the borehole to address faults, such as the fault **178** that has shifted the layer portion **172B**. Other uses for directional drilling include sidetracking off of an existing well to reach a different target area or a missed target area, drilling around abandoned drilling equipment, drilling into otherwise inaccessible or difficult to reach locations (e.g., under populated areas or bodies of water), providing a relief well for an existing well, and increasing the capacity of a well by branching off and having multiple boreholes extending in different directions or at different vertical positions for the same well. Directional drilling is often not confined to a straight horizontal borehole, but may involve staying within a rock layer that varies in depth and thickness as illustrated by the layer **172**. As such, directional drilling may involve multiple vertical adjustments that complicate the path of the borehole.

With additional reference to FIG. 1C, which illustrates one embodiment of a portion of the borehole **164** of FIG. 1B, the drilling of horizontal wells clearly introduces significant challenges to drilling that do not exist in vertical wells. For example, a substantially horizontal portion **192** of the well may be started off of a vertical borehole **190** and one drilling consideration is the transition from the vertical portion of the

well to the horizontal portion. This transition is generally a curve that defines a build up section **194** beginning at the vertical portion (called the kick off point and represented by line **196**) and ending at the horizontal portion (represented by line **198**). The change in inclination per measured length drilled is typically referred to as the build rate and is often defined in degrees per one hundred feet drilled. For example, the build rate may be $6^\circ/100$ ft, indicating that there is a six degree change in inclination for every one hundred feet drilled. The build rate for a particular build up section may remain relatively constant or may vary.

The build rate depends on factors such as the formation through which the borehole **164** is to be drilled, the trajectory of the borehole **164**, the particular pipe and drill collars/BHA components used (e.g., length, diameter, flexibility, strength, mud motor bend setting, and drill bit), the mud type and flow rate, the required horizontal displacement, stabilization, and inclination. An overly aggressive built rate can cause problems such as severe doglegs (e.g., sharp changes in direction in the borehole) that may make it difficult or impossible to run casing or perform other needed tasks in the borehole **164**. Depending on the severity of the mistake, the borehole **164** may require enlarging or the bit may need to be backed out and a new passage formed. Such mistakes cost time and money. However, if the built rate is too cautious, significant additional time may be added to the drilling process as it is generally slower to drill a curve than to drill straight. Furthermore, drilling a curve is more complicated and the possibility of drilling errors increases (e.g., overshoot and undershoot that may occur trying to keep the bit on the planned path).

Two modes of drilling, known as rotating and sliding, are commonly used to form the borehole **164**. Rotating, also called rotary drilling, uses a topdrive or rotary table to rotate the drillstring. Rotating is used when drilling is to occur along a straight path. Sliding, also called steering, uses a downhole mud motor with an adjustable bent housing and does not rotate the drillstring. Instead, sliding uses hydraulic power to drive the downhole motor and bit. Sliding is used in order to control well direction.

To accomplish a slide, the rotation of the drill string is stopped. Based on feedback from measuring equipment such as a MWD tool, adjustments are made to the drill string. These adjustments continue until the downhole toolface that indicates the direction of the bend of the motor is oriented to the direction of the desired deviation of the borehole. Once the desired orientation is accomplished, pressure is applied to the drill bit, which causes the drill bit to move in the direction of deviation. Once sufficient distance and angle have been built, a transition back to rotating mode is accomplished by rotating the drill string. This rotation of the drill string neutralizes the directional deviation caused by the bend in the motor as it continuously rotates around the centerline of the borehole.

Referring again to FIG. 1A, the formulation of a drilling plan for the drilling rig **110** may include processing and analyzing the collected data in the database **128** to create a more effective drilling plan. Furthermore, once the drilling has begun, the collected data may be used in conjunction with current data from the drilling rig **110** to improve drilling decisions. Accordingly, an on-site controller **144** is coupled to the drilling rig **110** and may also be coupled to the database **128** via one or more wired and/or wireless communication channel(s) **146**. Other inputs **148** may also be provided to the on-site controller **144**. In some embodiments, the on-site controller **144** may operate as a stand-alone device with the drilling rig **110**. For example, the on-site controller **144** may not be communicatively coupled to the database **128**.

Although shown as being positioned near or at the drilling rig **110** in the present example, it is understood that some or all components of the on-site controller **144** may be distributed and located elsewhere in other embodiments.

The on-site controller **144** may form all or part of a surface steerable system. The database **128** may also form part of the surface steerable system. As will be described in greater detail below, the surface steerable system may be used to plan and control drilling operations based on input information, including feedback from the drilling process itself. The surface steerable system may be used to perform such operations as receiving drilling data representing a drill path and other drilling parameters, calculating a drilling solution for the drill path based on the received data and other available data (e.g., rig characteristics), implementing the drilling solution at the drilling rig **110**, monitoring the drilling process to gauge whether the drilling process is within a defined margin of error of the drill path, and/or calculating corrections for the drilling process if the drilling process is outside of the margin of error.

Referring to FIG. 2A, a diagram **200** illustrates one embodiment of information flow for a surface steerable system **201** from the perspective of the on-site controller **144** of FIG. 1A. In the present example, the drilling rig **110** of FIG. 1A includes drilling equipment **216** used to perform the drilling of a borehole, such as top drive or rotary drive equipment that couples to the drill string and BHA and is configured to rotate the drill string and apply pressure to the drill bit. The drilling rig **110** may include control systems such as a WOB/differential pressure control system **208**, a positional/rotary control system **210**, and a fluid circulation control system **212**. The control systems **208**, **210**, and **212** may be used to monitor and change drilling rig settings, such as the WOB and/or differential pressure to alter the ROP or the radial orientation of the toolface, change the flow rate of drilling mud, and perform other operations.

The drilling rig **110** may also include a sensor system **214** for obtaining sensor data about the drilling operation and the drilling rig **110**, including the downhole equipment. For example, the sensor system **214** may include measuring while drilling (MWD) and/or logging while drilling (LWD) components for obtaining information, such as toolface and/or formation logging information, that may be saved for later retrieval, transmitted with a delay or in real time using any of various communication means (e.g., wireless, wireline, or mud pulse telemetry), or otherwise transferred to the on-site controller **144**. Such information may include information related to hole depth, bit depth, inclination, azimuth, true vertical depth, gamma count, standpipe pressure, mud flow rate, rotary rotations per minute (RPM), bit speed, ROP, WOB, and/or other information. It is understood that all or part of the sensor system **214** may be incorporated into one or more of the control systems **208**, **210**, and **212**, and/or in the drilling equipment **216**. As the drilling rig **110** may be configured in many different ways, it is understood that these control systems may be different in some embodiments, and may be combined or further divided into various subsystems.

The on-site controller **144** receives input information **202**. The input information **202** may include information that is pre-loaded, received, and/or updated in real time. The input information **202** may include a well plan, regional formation history, one or more drilling engineer parameters, MWD tool face/inclination information, LWD gamma/resistivity information, economic parameters, reliability parameters, and/or other decision guiding parameters. Some of the inputs, such as the regional formation history, may be available from a drilling hub **216**, which may include the database **128** of FIG.

1A and one or more processors (not shown), while other inputs may be accessed or uploaded from other sources. For example, a web interface may be used to interact directly with the on-site controller **144** to upload the well plan and/or drilling engineer parameters. The input information **202** feeds into the on-site controller **144** and, after processing by the on-site controller **144**, results in control information **204** that is output to the drilling rig **110** (e.g., to the control systems **208**, **210**, and **212**). The drilling rig **110** (e.g., via the systems **208**, **210**, **212**, and **214**) provides feedback information **206** to the on-site controller **144**. The feedback information **206** then serves as input to the on-site controller **144**, enabling the on-site controller **144** to verify that the current control information is producing the desired results or to produce new control information for the drilling rig **110**.

The on-site controller **144** also provides output information **203**. As will be described later in greater detail, the output information **203** may be stored in the on-site controller **144** and/or sent offsite (e.g., to the database **128**). The output information **203** may be used to provide updates to the database **128**, as well as provide alerts, request decisions, and convey other data related to the drilling process.

Referring to FIG. 2B, one embodiment of a display **250** that may be provided by the on-site controller **144** is illustrated. The display **250** provides many different types of information in an easily accessible format. For example, the display **250** may be a viewing screen (e.g., a monitor) that is coupled to or forms part of the on-site controller **144**.

The display **250** provides visual indicators such as a hole depth indicator **252**, a bit depth indicator **254**, a GAMMA indicator **256**, an inclination indicator **258**, an azimuth indicator **260**, and a TVD indicator **262**. Other indicators may also be provided, including a ROP indicator **264**, a mechanical specific energy (MSE) indicator **266**, a differential pressure indicator **268**, a standpipe pressure indicator **270**, a flow rate indicator **272**, a rotary RPM indicator **274**, a bit speed indicator **276**, and a WOB indicator **278**.

Some or all of the indicators **264**, **266**, **268**, **270**, **272**, **274**, **276**, and/or **278** may include a marker representing a target value. For purposes of example, markers are set as the following values, but it is understood that any desired target value may be representing. For example, the ROP indicator **264** may include a marker **265** indicating that the target value is fifty ft/hr. The MSE indicator **266** may include a marker **267** indicating that the target value is thirty-seven ksi. The differential pressure indicator **268** may include a marker **269** indicating that the target value is two hundred psi. The ROP indicator **264** may include a marker **265** indicating that the target value is fifty ft/hr. The standpipe pressure indicator **270** may have no marker in the present example. The flow rate indicator **272** may include a marker **273** indicating that the target value is five hundred gpm. The rotary RPM indicator **274** may include a marker **275** indicating that the target value is zero RPM (due to sliding). The bit speed indicator **276** may include a marker **277** indicating that the target value is one hundred and fifty RPM. The WOB indicator **278** may include a marker **279** indicating that the target value is ten klbs. Although only labeled with respect to the indicator **264**, each indicator may include a colored band **263** or another marking to indicate, for example, whether the respective gauge value is within a safe range (e.g., indicated by a green color), within a caution range (e.g., indicated by a yellow color), or within a danger range (e.g., indicated by a red color). Although not shown, in some embodiments, multiple markers may be present on a single indicator. The markers may vary in color and/or size.

A log chart **280** may visually indicate depth versus one or more measurements (e.g., may represent log inputs relative to a progressing depth chart). For example, the log chart **280** may have a y-axis representing depth and an x-axis representing a measurement such as GAMMA count **281** (as shown), ROP **283** (e.g., empirical ROP and normalized ROP), or resistivity. An autopilot button **282** and an oscillate button **284** may be used to control activity. For example, the autopilot button **282** may be used to engage or disengage an autopilot, while the oscillate button **284** may be used to directly control oscillation of the drill string or engage/disengage an external hardware device or controller via software and/or hardware.

A circular chart **286** may provide current and historical toolface orientation information (e.g., which way the bend is pointed). For purposes of illustration, the circular chart **286** represents three hundred and sixty degrees. A series of circles within the circular chart **286** may represent a timeline of toolface orientations, with the sizes of the circles indicating the temporal position of each circle. For example, larger circles may be more recent than smaller circles, so the largest circle **288** may be the newest reading and the smallest circle **289** may be the oldest reading. In other embodiments, the circles may represent the energy and/or progress made via size, color, shape, a number within a circle, etc. For example, the size of a particular circle may represent an accumulation of orientation and progress for the period of time represented by the circle. In other embodiments, concentric circles representing time (e.g., with the outside of the circular chart **286** being the most recent time and the center point being the oldest time) may be used to indicate the energy and/or progress (e.g., via color and/or patterning such as dashes or dots rather than a solid line).

The circular chart **286** may also be color coded, with the color coding existing in a band **290** around the circular chart **286** or positioned or represented in other ways. The color coding may use colors to indicate activity in a certain direction. For example, the color red may indicate the highest level of activity, while the color blue may indicate the lowest level of activity. Furthermore, the arc range in degrees of a color may indicate the amount of deviation. Accordingly, a relatively narrow (e.g., thirty degrees) arc of red with a relatively broad (e.g., three hundred degrees) arc of blue may indicate that most activity is occurring in a particular toolface orientation with little deviation. For purposes of illustration, the color blue extends from approximately 22-337 degrees, the color green extends from approximately 15-22 degrees and 337-345 degrees, the color yellow extends a few degrees around the 13 and 345 degree marks, and the color red extends from approximately 347-10 degrees. Transition colors or shades may be used with, for example, the color orange marking the transition between red and yellow and/or a light blue marking the transition between blue and green.

This color coding enables the display **250** to provide an intuitive summary of how narrow the standard deviation is and how much of the energy intensity is being expended in the proper direction. Furthermore, the center of energy may be viewed relative to the target. For example, the display **250** may clearly show that the target is at ninety degrees but the center of energy is at forty-five degrees.

Other indicators may be present, such as a slide indicator **292** to indicate how much time remains until a slide occurs and/or how much time remains for a current slide. For example, the slide indicator may represent a time, a percentage (e.g., current slide is fifty-six percent complete), a distance completed, and/or a distance remaining. The slide indicator **292** may graphically display information using, for example, a colored bar **293** that increases or decreases with

the slide's progress. In some embodiments, the slide indicator may be built into the circular chart **286** (e.g., around the outer edge with an increasing/decreasing band), while in other embodiments the slide indicator may be a separate indicator such as a meter, a bar, a gauge, or another indicator type.

An error indicator **294** may be present to indicate a magnitude and/or a direction of error. For example, the error indicator **294** may indicate that the estimated drill bit position is a certain distance from the planned path, with a location of the error indicator **294** around the circular chart **286** representing the heading. For example, FIG. 2B illustrates an error magnitude of fifteen feet and an error direction of fifteen degrees. The error indicator **294** may be any color but is red for purposes of example. It is understood that the error indicator **294** may present a zero if there is no error and/or may represent that the bit is on the path in other ways, such as being a green color. Transition colors, such as yellow, may be used to indicate varying amounts of error. In some embodiments, the error indicator **294** may not appear unless there is an error in magnitude and/or direction. A marker **296** may indicate an ideal slide direction. Although not shown, other indicators may be present, such as a bit life indicator to indicate an estimated lifetime for the current bit based on a value such as time and/or distance.

It is understood that the display **250** may be arranged in many different ways. For example, colors may be used to indicate normal operation, warnings, and problems. In such cases, the numerical indicators may display numbers in one color (e.g., green) for normal operation, may use another color (e.g., yellow) for warnings, and may use yet another color (e.g., red) if a serious problem occurs. The indicators may also flash or otherwise indicate an alert. The gauge indicators may include colors (e.g., green, yellow, and red) to indicate operational conditions and may also indicate the target value (e.g., an ROP of 100 ft/hr). For example, the ROP indicator **264** may have a green bar to indicate a normal level of operation (e.g., from 10-300 ft/hr), a yellow bar to indicate a warning level of operation (e.g., from 300-360 ft/hr), and a red bar to indicate a dangerous or otherwise out of parameter level of operation (e.g., from 360-390 ft/hr). The ROP indicator **264** may also display a marker at 100 ft/hr to indicate the desired target ROP.

Furthermore, the use of numeric indicators, gauges, and similar visual display indicators may be varied based on factors such as the information to be conveyed and the personal preference of the viewer. Accordingly, the display **250** may provide a customizable view of various drilling processes and information for a particular individual involved in the drilling process. For example, the surface steerable system **201** may enable a user to customize the display **250** as desired, although certain features (e.g., standpipe pressure) may be locked to prevent removal. This locking may prevent a user from intentionally or accidentally removing important drilling information from the display. Other features may be set by preference. Accordingly, the level of customization and the information shown by the display **250** may be controlled based on who is viewing the display and their role in the drilling process.

Referring again to FIG. 2A, it is understood that the level of integration between the on-site controller **144** and the drilling rig **110** may depend on such factors as the configuration of the drilling rig **110** and whether the on-site controller **144** is able to fully support that configuration. One or more of the control systems **208**, **210**, and **212** may be part of the on-site controller **144**, may be third-party systems, and/or may be part of the drilling rig **110**. For example, an older drilling rig **110** may have relatively few interfaces with which the on-site control-

ler **144** is able to interact. For purposes of illustration, if a knob must be physically turned to adjust the WOB on the drilling rig **110**, the on-site controller **144** will not be able to directly manipulate the knob without a mechanical actuator. If such an actuator is not present, the on-site controller **144** may output the setting for the knob to a screen, and an operator may then turn the knob based on the setting. Alternatively, the on-site controller **144** may be directly coupled to the knob's electrical wiring.

However, a newer or more sophisticated drilling rig **110**, such as a rig that has electronic control systems, may have interfaces with which the on-site controller **144** can interact for direct control. For example, an electronic control system may have a defined interface and the on-site controller **144** may be configured to interact with that defined interface. It is understood that, in some embodiments, direct control may not be allowed even if possible. For example, the on-site controller **144** may be configured to display the setting on a screen for approval, and may then send the setting to the appropriate control system only when the setting has been approved.

Referring to FIG. 3, one embodiment of an environment **300** illustrates multiple communication channels (indicated by arrows) that are commonly used in existing directional drilling operations that do not have the benefit of the surface steerable system **201** of FIG. 2A. The communication channels couple various individuals involved in the drilling process. The communication channels may support telephone calls, emails, text messages, faxes, data transfers (e.g., file transfers over networks), and other types of communications.

The individuals involved in the drilling process may include a drilling engineer **302**, a geologist **304**, a directional driller **306**, a tool pusher **308**, a driller **310**, and a rig floor crew **312**. One or more company representatives (e.g., company men) **314** may also be involved. The individuals may be employed by different organizations, which can further complicate the communication process. For example, the drilling engineer **302**, geologist **304**, and company man **314** may work for an operator, the directional driller **306** may work for a directional drilling service provider, and the tool pusher **308**, driller **310**, and rig floor crew **312** may work for a rig service provider.

The drilling engineer **302** and geologist **304** are often located at a location remote from the drilling rig (e.g., in a home office/drilling hub). The drilling engineer **302** may develop a well plan **318** and may make drilling decisions based on drilling rig information. The geologist **304** may perform such tasks as formation analysis based on seismic, gamma, and other data. The directional driller **306** is generally located at the drilling rig and provides instructions to the driller **310** based on the current well plan and feedback from the drilling engineer **302**. The driller **310** handles the actual drilling operations and may rely on the rig floor crew **312** for certain tasks. The tool pusher **308** may be in charge of managing the entire drilling rig and its operation.

The following is one possible example of a communication process within the environment **300**, although it is understood that many communication processes may be used. The use of a particular communication process may depend on such factors as the level of control maintained by various groups within the process, how strictly communication channels are enforced, and similar factors. In the present example, the directional driller **306** uses the well plan **318** to provide drilling instructions to the driller **310**. The driller **310** controls the drilling using control systems such as the control systems **208**, **210**, and **212** of FIG. 2A. During drilling, information from sensor equipment such as downhole MWD equipment

316 and/or rig sensors **320** may indicate that a formation layer has been reached twenty feet higher than expected by the geologist **304**. This information is passed back to the drilling engineer **302** and/or geologist **304** through the company man **314**, and may pass through the directional driller **306** before reaching the company man **314**.

The drilling engineer **302**/well planner (not shown), either alone or in conjunction with the geologist **306**, may modify the well plan **318** or make other decisions based on the received information. The modified well plan and/or other decisions may or may not be passed through the company man **314** to the directional driller **306**, who then tells the driller **310** how to drill. The driller **310** may modify equipment settings (e.g., toolface orientation) and, if needed, pass orders on to the rig floor crew **312**. For example, a change in WOB may be performed by the driller **310** changing a setting, while a bit trip may require the involvement of the rig floor crew **312**. Accordingly, the level of involvement of different individuals may vary depending on the nature of the decision to be made and the task to be performed. The proceeding example may be more complex than described. Multiple intermediate individuals may be involved and, depending on the communication chain, some instructions may be passed through the tool pusher **308**.

The environment **300** presents many opportunities for communication breakdowns as information is passed through the various communication channels, particularly given the varying types of communication that may be used. For example, verbal communications via phone may be misunderstood and, unless recorded, provide no record of what was said. Furthermore, accountability may be difficult or impossible to enforce as someone may provide an authorization but deny it or claim that they meant something else. Without a record of the information passing through the various channels and the authorizations used to approve changes in the drilling process, communication breakdowns can be difficult to trace and address. As many of the communication channels illustrated in FIG. 3 pass information through an individual to other individuals (e.g., an individual may serve as an information conduit between two or more other individuals), the risk of breakdown increases due to the possibility that errors may be introduced in the information.

Even if everyone involved does their part, drilling mistakes may be amplified while waiting for an answer. For example, a message may be sent to the geologist **306** that a formation layer seems to be higher than expected, but the geologist **306** may be asleep. Drilling may continue while waiting for the geologist **306** and the continued drilling may amplify the error. Such errors can cost hundreds of thousands or millions of dollars. However, the environment **300** provides no way to determine if the geologist **304** has received the message and no way to easily notify the geologist **304** or to contact someone else when there is no response within a defined period of time. Even if alternate contacts are available, such communications may be cumbersome and there may be difficulty in providing all the information that the alternate would need for a decision.

Referring to FIG. 4, one embodiment of an environment **400** illustrates communication channels that may exist in a directional drilling operation having the benefit of the surface steerable system **201** of FIG. 2A. In the present example, the surface steerable system **201** includes the drilling hub **216**, which includes the regional database **128** of FIG. 1A and processing unit(s) **404** (e.g., computers). The drilling hub **216** also includes communication interfaces (e.g., web portals) **406** that may be accessed by computing devices capable of wireless and/or wireline communications, including desktop

computers, laptops, tablets, smart phones, and personal digital assistants (PDAs). The on-site controller **144** includes one or more local databases **410** (where “local” is from the perspective of the on-site controller **144**) and processing unit(s) **412**.

The drilling hub **216** is remote from the on-site controller **144**, and various individuals associated with the drilling operation interact either through the drilling hub **216** or through the on-site controller **144**. In some embodiments, an individual may access the drilling project through both the drilling hub **216** and on-site controller **144**. For example, the directional driller **306** may use the drilling hub **216** when not at the drilling site and may use the on-site controller **144** when at the drilling site.

The drilling engineer **302** and geologist **304** may access the surface steerable system **201** remotely via the portal **406** and set various parameters such as rig limit controls. Other actions may also be supported, such as granting approval to a request by the directional driller **306** to deviate from the well plan and evaluating the performance of the drilling operation. The directional driller **306** may be located either at the drilling rig **110** or off-site. Being off-site (e.g., at the drilling hub **216** or elsewhere) enables a single directional driller to monitor multiple drilling rigs. When off-site, the directional driller **306** may access the surface steerable system **201** via the portal **406**. When on-site, the directional driller **306** may access the surface steerable system via the on-site controller **144**.

The driller **310** may get instructions via the on-site controller **144**, thereby lessening the possibility of miscommunication and ensuring that the instructions were received. Although the tool pusher **308**, rig floor crew **312**, and company man **314** are shown communicating via the driller **310**, it is understood that they may also have access to the on-site controller **144**. Other individuals, such as a MWD hand **408**, may access the surface steerable system **201** via the drilling hub **216**, the on-site controller **144**, and/or an individual such as the driller **310**.

As illustrated in FIG. 4, many of the individuals involved in a drilling operation may interact through the surface steerable system **201**. This enables information to be tracked as it is handled by the various individuals involved in a particular decision. For example, the surface steerable system **201** may track which individual submitted information (or whether information was submitted automatically), who viewed the information, who made decisions, when such events occurred, and similar information-based issues. This provides a complete record of how particular information propagated through the surface steerable system **201** and resulted in a particular drilling decision. This also provides revision tracking as changes in the well plan occur, which in turn enables entire decision chains to be reviewed. Such reviews may lead to improved decision making processes and more efficient responses to problems as they occur.

In some embodiments, documentation produced using the surface steerable system **201** may be synchronized and/or merged with other documentation, such as that produced by third party systems such as the WellView product produced by Peloton Computer Enterprises Ltd. of Calgary, Canada. In such embodiments, the documents, database files, and other information produced by the surface steerable system **201** is synchronized to avoid such issues as redundancy, mismatched file versions, and other complications that may occur in projects where large numbers of documents are produced, edited, and transmitted by a relatively large number of people.

The surface steerable system **201** may also impose mandatory information formats and other constraints to ensure that predefined criteria are met. For example, an electronic form provided by the surface steerable system **201** in

response to a request for authorization may require that some fields are filled out prior to submission. This ensures that the decision maker has the relevant information prior to making the decision. If the information for a required field is not available, the surface steerable system **201** may require an explanation to be entered for why the information is not available (e.g., sensor failure). Accordingly, a level of uniformity may be imposed by the surface steerable system **201**, while exceptions may be defined to enable the surface steerable system **201** to handle various scenarios.

The surface steerable system **201** may also send alerts (e.g., email or text alerts) to notify one or more individuals of a particular problem, and the recipient list may be customized based on the problem. Furthermore, contact information may be time-based, so the surface steerable system **201** may know when a particular individual is available. In such situations, the surface steerable system **201** may automatically attempt to communicate with an available contact rather than waiting for a response from a contact that is likely not available.

As described previously, the surface steerable system **201** may present a customizable display of various drilling processes and information for a particular individual involved in the drilling process. For example, the drilling engineer **302** may see a display that presents information relevant to the drilling engineer’s tasks, and the geologist **304** may see a different display that includes additional and/or more detailed formation information. This customization enables each individual to receive information needed for their particular role in the drilling process while minimizing or eliminating unnecessary information.

Referring to FIG. 5, one embodiment of an environment **500** illustrates data flow that may be supported by the surface steerable system **201** of FIG. 2A. The data flow **500** begins at block **502** and may move through two branches, although some blocks in a branch may not occur before other blocks in the other branch. One branch involves the drilling hub **216** and the other branch involves the on-site controller **144** at the drilling rig **110**.

In block **504**, a geological survey is performed. The survey results are reviewed by the geologist **304** and a formation report **506** is produced. The formation report **506** details formation layers, rock type, layer thickness, layer depth, and similar information that may be used to develop a well plan. In block **508**, a well plan is developed by a well planner **524** and/or the drilling engineer **302** based on the formation report and information from the regional database **128** at the drilling hub **216**. Block **508** may include selection of a BHA and the setting of control limits. The well plan is stored in the database **128**. The drilling engineer **302** may also set drilling operation parameters in step **510** that are also stored in the database **128**.

In the other branch, the drilling rig **110** is constructed in block **512**. At this point, as illustrated by block **526**, the well plan, BHA information, control limits, historical drilling data, and control commands may be sent from the database **128** to the local database **410**. Using the receiving information, the directional driller **306** inputs actual BHA parameters in block **514**. The company man **314** and/or the directional driller **306** may verify performance control limits in block **516**, and the control limits are stored in the local database **410** of the on-site controller **144**. The performance control limits may include multiple levels such as a warning level and a critical level corresponding to no action taken within feet/minutes.

Once drilling begins, a diagnostic logger (described later in greater detail) **520** that is part of the on-site controller **144** logs information related to the drilling such as sensor infor-

mation and maneuvers and stores the information in the local database **410** in block **526**. The information is sent to the database **128**. Alerts are also sent from the on-site controller **144** to the drilling hub **216**. When an alert is received by the drilling hub **216**, an alert notification **522** is sent to defined individuals, such as the drilling engineer **302**, geologist **304**, and company man **314**. The actual recipient may vary based on the content of the alert message or other criteria. The alert notification **522** may result in the well plan and the BHA information and control limits being modified in block **508** and parameters being modified in block **510**. These modifications are saved to the database **128** and transferred to the local database **410**. The BHA may be modified by the directional driller **306** in block **518**, and the changes propagated through blocks **514** and **516** with possible updated control limits. Accordingly, the surface steerable system **201** may provide a more controlled flow of information than may occur in an environment without such a system.

The flow charts described herein illustrate various exemplary functions and operations that may occur within various environments. Accordingly, these flow charts are not exhaustive and that various steps may be excluded to clarify the aspect being described. For example, it is understood that some actions, such as network authentication processes, notifications, and handshakes, may have been performed prior to the first step of a flow chart. Such actions may depend on the particular type and configuration of communications engaged in by the on-site controller **144** and/or drilling hub **216**. Furthermore, other communication actions may occur between illustrated steps or simultaneously with illustrated steps.

The surface steerable system **201** includes large amounts of data specifically related to various drilling operations as stored in databases such as the databases **128** and **410**. As described with respect to FIG. 1A, this data may include data collected from many different locations and may correspond to many different drilling operations. The data stored in the database **128** and other databases may be used for a variety of purposes, including data mining and analytics, which may aid in such processes as equipment comparisons, drilling plan formulation, convergence planning, recalibration forecasting, and self-tuning (e.g., drilling performance optimization). Some processes, such as equipment comparisons, may not be performed in real time using incoming data, while others, such as self-tuning, may be performed in real time or near real time. Accordingly, some processes may be executed at the drilling hub **216**, other processes may be executed at the on-site controller **144**, and still other processes may be executed by both the drilling hub **216** and the on-site controller **144** with communications occurring before, during, and/or after the processes are executed. As described below in various examples, some processes may be triggered by events (e.g., recalibration forecasting) while others may be ongoing (e.g., self-tuning).

For example, in equipment comparison, data from different drilling operations (e.g., from drilling the wells **102**, **104**, **106**, and **108**) may be normalized and used to compare equipment wear, performance, and similar factors. For example, the same bit may have been used to drill the wells **102** and **106**, but the drilling may have been accomplished using different parameters (e.g., rotation speed and WOB). By normalizing the data, the two bits can be compared more effectively. The normalized data may be further processed to improve drilling efficiency by identifying which bits are most effective for particular rock layers, which drilling parameters resulted in the best ROP for a particular formation, ROP versus reliability tradeoffs for various bits in various rock layers, and similar factors. Such comparisons may be used to select a bit for

another drilling operation based on formation characteristics or other criteria. Accordingly, by mining and analyzing the data available via the surface steerable system **201**, an optimal equipment profile may be developed for different drilling operations. The equipment profile may then be used when planning future wells or to increase the efficiency of a well currently being drilled. This type of drilling optimization may become increasingly accurate as more data is compiled and analyzed.

In drilling plan formulation, the data available via the surface steerable system **201** may be used to identify likely formation characteristics and to select an appropriate equipment profile. For example, the geologist **304** may use local data obtained from the planned location of the drilling rig **110** in conjunction with regional data from the database **128** to identify likely locations of the layers **168A-176A** (FIG. 1B). Based on that information, the drilling engineer **302** can create a well plan that will include the build curve of FIG. 1C.

Referring to FIG. 6, a method **600** illustrates one embodiment of an event-based process that may be executed by the on-site controller **144** of FIG. 2A. For example, software instructions needed to execute the method **600** may be stored on a computer readable storage medium of the on-site controller **144** and then executed by the processor **412** that is coupled to the storage medium and is also part of the on-site controller **144**.

In step **602**, the on-site controller **144** receives inputs, such as a planned path for a borehole, formation information for the borehole, equipment information for the drilling rig, and a set of cost parameters. The cost parameters may be used to guide decisions made by the on-site controller **144** as will be explained in greater detail below. The inputs may be received in many different ways, including receiving document (e.g., spreadsheet) uploads, accessing a database (e.g., the database **128** of FIG. 1A), and/or receiving manually entered data.

In step **604**, the planned path, the formation information, the equipment information, and the set of cost parameters are processed to produce control parameters (e.g., the control information **204** of FIG. 2A) for the drilling rig **110**. The control parameters may define the settings for various drilling operations that are to be executed by the drilling rig **110** to form the borehole, such as WOB, flow rate of mud, toolface orientation, and similar settings. In some embodiments, the control parameters may also define particular equipment selections, such as a particular bit. In the present example, step **604** is directed to defining initial control parameters for the drilling rig **110** prior to the beginning of drilling, but it is understood that step **604** may be used to define control parameters for the drilling rig **110** even after drilling has begun. For example, the on-site controller **144** may be put in place prior to drilling or may be put in place after drilling has commenced, in which case the method **600** may also receive current borehole information in step **602**.

In step **606**, the control parameters are output for use by the drilling rig **110**. In embodiments where the on-site controller **144** is directly coupled to the drilling rig **110**, outputting the control parameters may include sending the control parameters directly to one or more of the control systems of the drilling rig **110** (e.g., the control systems **210**, **212**, and **214**). In other embodiments, outputting the control parameters may include displaying the control parameters on a screen, printing the control parameters, and/or copying them to a storage medium (e.g., a Universal Serial Bus (USB) drive) to be transferred manually.

In step **608**, feedback information received from the drilling rig **110** (e.g., from one or more of the control systems **210**, **212**, and **214** and/or sensor system **216**) is processed. The

feedback information may provide the on-site controller **144** with the current state of the borehole (e.g., depth and inclination), the drilling rig equipment, and the drilling process, including an estimated position of the bit in the borehole. The processing may include extracting desired data from the feedback information, normalizing the data, comparing the data to desired or ideal parameters, determining whether the data is within a defined margin of error, and/or any other processing steps needed to make use of the feedback information.

In step **610**, the on-site controller **144** may take action based on the occurrence of one or more defined events. For example, an event may trigger a decision on how to proceed with drilling in the most cost effective manner. Events may be triggered by equipment malfunctions, path differences between the measured borehole and the planned borehole, upcoming maintenance periods, unexpected geological readings, and any other activity or non-activity that may affect drilling the borehole. It is understood that events may also be defined for occurrences that have a less direct impact on drilling, such as actual or predicted labor shortages, actual or potential licensing issues for mineral rights, actual or predicted political issues that may impact drilling, and similar actual or predicted occurrences. Step **610** may also result in no action being taken if, for example, drilling is occurring without any issues and the current control parameters are satisfactory.

An event may be defined in the received inputs of step **602** or defined later. Events may also be defined on site using the on-site controller **144**. For example, if the drilling rig **110** has a particular mechanical issue, one or more events may be defined to monitor that issue in more detail than might ordinarily occur. In some embodiments, an event chain may be implemented where the occurrence of one event triggers the monitoring of another related event. For example, a first event may trigger a notification about a potential problem with a piece of equipment and may also activate monitoring of a second event. In addition to activating the monitoring of the second event, the triggering of the first event may result in the activation of additional oversight that involves, for example, checking the piece of equipment more frequently or at a higher level of detail. If the second event occurs, the equipment may be shut down and an alarm sounded, or other actions may be taken. This enables different levels of monitoring and different levels of responses to be assigned independently if needed.

Referring to FIG. **7A**, a method **700** illustrates a more detailed embodiment of the method **600** of FIG. **6**, particularly of step **610**. As steps **702**, **704**, **706**, and **708** are similar or identical to steps **602**, **604**, **606**, and **608**, respectively, of FIG. **6**, they are not described in detail in the present embodiment. In the present example, the action of step **610** of FIG. **6** is based on whether an event has occurred and the action needed if the event has occurred.

Accordingly, in step **710**, a determination is made as to whether an event has occurred based on the inputs of steps **702** and **708**. If no event has occurred, the method **700** returns to step **708**. If an event has occurred, the method **700** moves to step **712**, where calculations are performed based on the information relating to the event and at least one cost parameter. It is understood that additional information may be obtained and/or processed prior to or as part of step **712** if needed. For example, certain information may be used to determine whether an event has occurred, and additional information may then be retrieved and processed to determine the particulars of the event.

In step **714**, new control parameters may be produced based on the calculations of step **712**. In step **716**, a determi-

nation may be made as to whether changes are needed in the current control parameters. For example, the calculations of step **712** may result in a decision that the current control parameters are satisfactory (e.g., the event may not affect the control parameters). If no changes are needed, the method **700** returns to step **708**. If changes are needed, the on-site controller **144** outputs the new parameters in step **718**. The method **700** may then return to step **708**. In some embodiments, the determination of step **716** may occur before step **714**. In such embodiments, step **714** may not be executed if the current control parameters are satisfactory.

In a more detailed example of the method **700**, assume that the on-site controller **144** is involved in drilling a borehole and that approximately six hundred feet remain to be drilled. An event has been defined that warns the on-site controller **144** when the drill bit is predicted to reach a minimum level of efficiency due to wear and this event is triggered in step **710** at the six hundred foot mark. The event may be triggered because the drill bit is within a certain number of revolutions before reaching the minimum level of efficiency, within a certain distance remaining (based on strata type, thickness, etc.) that can be drilled before reaching the minimum level of efficiency, or may be based on some other factor or factors. Although the event of the current example is triggered prior to the predicted minimum level of efficiency being reached in order to proactively schedule drilling changes if needed, it is understood that the event may be triggered when the minimum level is actually reached.

The on-site controller **144** may perform calculations in step **712** that account for various factors that may be analyzed to determine how the last six hundred feet is drilled. These factors may include the rock type and thickness of the remaining six hundred feet, the predicted wear of the drill bit based on similar drilling conditions, location of the bit (e.g., depth), how long it will take to change the bit, and a cost versus time analysis. Generally, faster drilling is more cost effective, but there are many tradeoffs. For example, increasing the WOB or differential pressure to increase the rate of penetration may reduce the time it takes to finish the borehole, but may also wear out the drill bit faster, which will decrease the drilling effectiveness and slow the drilling down. If this slowdown occurs too early, it may be less efficient than drilling more slowly. Therefore, there is a tradeoff that must be calculated. Too much WOB or differential pressure may also cause other problems, such as damaging downhole tools. Should one of these problems occur, taking the time to trip the bit or drill a sidetrack may result in more total time to finish the borehole than simply drilling more slowly, so faster may not be better. The tradeoffs may be relatively complex, with many factors to be considered.

In step **714**, the on-site controller **144** produces new control parameters based on the solution calculated in step **712**. In step **716**, a determination is made as to whether the current parameters should be replaced by the new parameters. For example, the new parameters may be compared to the current parameters. If the two sets of parameters are substantially similar (e.g., as calculated based on a percentage change or margin of error of the current path with a path that would be created using the new control parameters) or identical to the current parameters, no changes would be needed. However, if the new control parameters call for changes greater than the tolerated percentage change or outside of the margin of error, they are output in step **718**. For example, the new control parameters may increase the WOB and also include the rate of mud flow significantly enough to override the previous control parameters. In other embodiments, the new control parameters may be output regardless of any differences, in

which case step 716 may be omitted. In still other embodiments, the current path and the predicted path may be compared before the new parameters are produced, in which case step 714 may occur after step 716.

Referring to FIG. 7B and with additional reference to FIG. 7C, a method 720 (FIG. 7B) and diagram 740 (FIG. 7C) illustrate a more detailed embodiment of the method 600 of FIG. 6, particularly of step 610. As steps 722, 724, 726, and 728 are similar or identical to steps 602, 604, 606, and 608, respectively, of FIG. 6, they are not described in detail in the present embodiment. In the present example, the action of step 610 of FIG. 6 is based on whether the drilling has deviated from the planned path.

In step 730, a comparison may be made to compare the estimated bit position and trajectory with a desired point (e.g., a desired bit position) along the planned path. The estimated bit position may be calculated based on information such as a survey reference point and/or represented as an output calculated by a borehole estimator (as will be described later) and may include a bit projection path and/or point that represents a predicted position of the bit if it continues its current trajectory from the estimated bit position. Such information may be included in the inputs of step 722 and feedback information of step 728 or may be obtained in other ways. It is understood that the estimated bit position and trajectory may not be calculated exactly, but may represent an estimate of the current location of the drill bit based on the feedback information. As illustrated in FIG. 7C, the estimated bit position is indicated by arrow 743 relative to the desired bit position 741 along the planned path 742.

In step 732, a determination may be made as to whether the estimated bit position 743 is within a defined margin of error of the desired bit position. If the estimated bit position is within the margin of error, the method 720 returns to step 728. If the estimated bit position is not within the margin of error, the on-site controller 144 calculates a convergence plan in step 734. With reference to FIG. 7C, for purposes of the present example, the estimated bit position 743 is outside of the margin of error.

In some embodiments, a projected bit position (not shown) may also be used. For example, the estimated bit position 743 may be extended via calculations to determine where the bit is projected to be after a certain amount of drilling (e.g., time and/or distance). This information may be used in several ways. If the estimated bit position 743 is outside the margin of error, the projected bit position 743 may indicate that the current bit path will bring the bit within the margin of error without any action being taken. In such a scenario, action may be taken only if it will take too long to reach the projected bit position when a more optimal path is available. If the estimated bit position is inside the margin of error, the projected bit position may be used to determine if the current path is directing the bit away from the planned path. In other words, the projected bit position may be used to proactively detect that the bit is off course before the margin of error is reached. In such a scenario, action may be taken to correct the current path before the margin of error is reached.

The convergence plan identifies a plan by which the bit can be moved from the estimated bit position 743 to the planned path 742. It is noted that the convergence plan may bypass the desired bit position 741 entirely, as the objective is to get the actual drilling path back to the planned path 742 in the most optimal manner. The most optimal manner may be defined by cost, which may represent a financial value, a reliability value, a time value, and/or other values that may be defined for a convergence path.

As illustrated in FIG. 7C, an infinite number of paths may be selected to return the bit to the planned path 742. The paths may begin at the estimated bit position 743 or may begin at other points along a projected path 752 that may be determined by calculating future bit positions based on the current trajectory of the bit from the estimated bit position 752. In the present example, a first path 744 results in locating the bit at a position 745 (e.g., a convergence point). The convergence point 745 is outside of a lower limit 753 defined by a most aggressive possible correction (e.g., a lower limit on a window of correction). This correction represents the most aggressive possible convergence path, which may be limited by such factors as a maximum directional change possible in the convergence path, where any greater directional change creates a dogleg that makes it difficult or impossible to run casing or perform other needed tasks. A second path 746 results in a convergence point 747, which is right at the lower limit 753. A third path 748 results in a convergence point 749, which represents a mid-range convergence point. A third path 750 results in a convergence point 751, which occurs at an upper limit 754 defined by a maximum convergence delay (e.g., an upper limit on the window of correction).

A fourth path 756 may begin at a projected point or bit position 755 that lies along the projected path 752 and result in a convergence point 757, which represents a mid-range convergence point. The path 756 may be used by, for example, delaying a trajectory change until the bit reaches the position 755. Many additional convergence options may be opened up by using projected points for the basis of convergence plans as well as the estimated bit position.

A fifth path 758 may begin at a projected point or bit position 760 that lies along the projected path 750 and result in a convergence point 759. In such an embodiment, different convergence paths may include similar or identical path segments, such as the similar or identical path shared by the convergence points 751 and 759 to the point 760. For example, the point 760 may mark a position on the path 750 where a slide segment begins (or continues from a previous slide segment) for the path 758 and a straight line path segment begins (or continues) for the path 750. The surface steerable system 144 may calculate the paths 750 and 758 as two entirely separate paths or may calculate one of the paths as deviating from (e.g., being a child of) the other path. Accordingly, any path may have multiple paths deviating from that path based on, for example, different slide points and slide times.

Each of these paths 744, 746, 748, 750, 756, and 758 may present advantages and disadvantages from a drilling standpoint. For example, one path may be longer and may require more sliding in a relatively soft rock layer, while another path may be shorter but may require more sliding through a much harder rock layer. Accordingly, tradeoffs may be evaluated when selecting one of the convergence plans rather than simply selecting the most direct path for convergence. The tradeoffs may, for example, consider a balance between ROP, total cost, dogleg severity, and reliability. While the number of convergence plans may vary, there may be hundreds or thousands of convergence plans in some embodiments and the tradeoffs may be used to select one of those hundreds or thousands for implementation. The convergence plans from which the final convergence plan is selected may include plans calculated from the estimated bit position 743 as well as plans calculated from one or more projected points along the projected path.

In some embodiments, straight line projections of the convergence point vectors, after correction to the well plan 742, may be evaluated to predict the time and/or distance to the

next correction requirement. This evaluation may be used when selecting the lowest total cost option by avoiding multiple corrections where a single more forward thinking option might be optimal. As an example, one of the solutions provided by the convergence planning may result in the most cost effective path to return to the well plan **742**, but may result in an almost immediate need for a second correction due to a pending deviation within the well plan. Accordingly, a convergence path that merges the pending deviation with the correction by selecting a convergence point beyond the pending deviation might be selected when considering total well costs.

It is understood that the diagram **740** of FIG. **7C** is a two dimensional representation of a three dimensional environment. Accordingly, the illustrated convergence paths in the diagram **740** of FIG. **7C** may be three dimensional. In addition, although the illustrated convergence paths all converge with the planned path **742**, it is understood that some convergence paths may be calculated that move away from the planned path **742** (although such paths may be rejected). Still other convergence paths may overshoot the actual path **742** and then converge (e.g., if there isn't enough room to build the curve otherwise). Accordingly, many different convergence path structures may be calculated.

Referring again to FIG. **7B**, in step **736**, the on-site controller **144** produces revised control parameters based on the convergence plan calculated in step **734**. In step **738**, the revised control parameters may be output. It is understood that the revised control parameters may be provided to get the drill bit back to the planned path **742** and the original control parameters may then be used from that point on (starting at the convergence point). For example, if the convergence plan selected the path **748**, the revised control parameters may be used until the bit reaches position **749**. Once the bit reaches the position **749**, the original control parameters may be used for further drilling. Alternatively, the revised control parameters may incorporate the original control parameters starting at the position **749** or may re-calculate control parameters for the planned path even beyond the point **749**. Accordingly, the convergence plan may result in control parameters from the bit position **743** to the position **749**, and further control parameters may be reused or calculated depending on the particular implementation of the on-site controller **144**.

Referring to FIG. **8A**, a method **800** illustrates a more detailed embodiment of step **734** of FIG. **7B**. It is understood that the convergence plan of step **734** may be calculated in many different ways, and that **800** method provides one possible approach to such a calculation when the goal is to find the lowest cost solution vector. In the present example, cost may include both the financial cost of a solution and the reliability cost of a solution. Other costs, such as time costs, may also be included. For purposes of example, the diagram **740** of FIG. **7C** is used.

In step **802**, multiple solution vectors are calculated from the current position **743** to the planned path **742**. These solution vectors may include the paths **744**, **746**, **748**, and **750**. Additional paths (not shown in FIG. **7C**) may also be calculated. The number of solution vectors that are calculated may vary depending on various factors. For example, the distance available to build a needed curve to get back to the planned path **742** may vary depending on the current bit location and orientation relative to the planned path. A greater number of solution vectors may be available when there is a greater distance in which to build a curve than for a smaller distance since the smaller distance may require a much more aggressive build rate that excludes lesser build rates that may be used for the greater distance. In other words, the earlier an error is

caught, the more possible solution vectors there will generally be due to the greater distance over which the error can be corrected. While the number of solution vectors that are calculated in this step may vary, there may be hundreds or thousands of solution vectors calculated in some embodiments.

In step **804**, any solution vectors that fall outside of defined limits are rejected, such as solution vectors that fall outside the lower limit **753** and the upper limit **754**. For example, the path **744** would be rejected because the convergence point **745** falls outside of the lower limit **753**. It is understood that the path **744** may be rejected for an engineering reason (e.g., the path would require a dogleg of greater than allowed severity) prior to cost considerations, or the engineering reason may be considered a cost.

In step **806**, a cost is calculated for each remaining solution vector. As illustrated in FIG. **7C**, the costs may be represented as a cost matrix (that may or may not be weighted) with each solution vector having corresponding costs in the cost matrix. In step **808**, a minimum of the solution vectors may be taken to identify the lowest cost solution vector. It is understood that the minimum cost is one way of selecting the desired solution vector, and that other ways may be used. Accordingly, step **808** is concerned with selecting an optimal solution vector based on a set of target parameters, which may include one or more of a financial cost, a time cost, a reliability cost, and/or any other factors, such as an engineering cost like dogleg severity, that may be used to narrow the set of solution vectors to the optimal solution vector.

By weighting the costs, the cost matrix can be customized to handle many different cost scenarios and desired results. For example, if time is of primary importance, a time cost may be weighted over financial and reliability costs to ensure that a solution vector that is faster will be selected over other solution vectors that are substantially the same but somewhat slower, even though the other solution vectors may be more beneficial in terms of financial cost and reliability cost. In some embodiments, step **804** may be combined with step **808** and solution vectors falling outside of the limits may be given a cost that ensures they will not be selected. In step **810**, the solution vector corresponding to the minimum cost is selected.

Referring to FIG. **8B**, a method **820** illustrates one embodiment of an event-based process that may be executed by the on-site controller **144** of FIG. **2A**. It is understood that an event may represent many different scenarios in the surface steerable system **201**. In the present example, in step **822**, an event may occur that indicates that a prediction is not correct based on what has actually occurred. For example, a formation layer is not where it is expected (e.g., too high or low), a selected bit did not drill as expected, or a selected mud motor did not build curve as expected. The prediction error may be identified by comparing expected results with actual results or by using other detection methods.

In step **824**, a reason for the error may be determined as the surface steerable system **201** and its data may provide an environment in which the prediction error can be evaluated. For example, if a bit did not drill as expected, the method **820** may examine many different factors, such as whether the rock formation was different than expected, whether the drilling parameters were correct, whether the drilling parameters were correctly entered by the driller, whether another error and/or failure occurred that caused the bit to drill poorly, and whether the bit simply failed to perform. By accessing and analyzing the available data, the reason for the failure may be determined.

In step **826**, a solution may be determined for the error. For example, if the rock formation was different than expected, the database **128** may be updated with the correct rock information and new drilling parameters may be obtained for the drilling rig **110**. Alternatively, the current bit may be tripped and replaced with another bit more suitable for the rock. In step **828**, the current drilling predictions (e.g., well plan, build rate, slide estimates) may be updated based on the solution and the solution may be stored in the database **128** for use in future predictions. Accordingly, the method **820** may result in benefits for future wells as well as improving current well predictions.

Referring to FIG. **8C**, a method **830** illustrates one embodiment of an event-based process that may be executed by the on-site controller **144** of FIG. **2A**. The method **830** is directed to recalibration forecasting that may be triggered by an event, such as an event detected in step **610** of FIG. **6**. It is understood that the recalibration described in this embodiment may not be the same as calculating a convergence plan, although calculating a convergence plan may be part of the recalibration. As an example of a recalibration triggering event, a shift in ROP and/or GAMMA readings may indicate that a formation layer (e.g., the layer **170A** of FIG. **1B**) is actually twenty feet higher than planned. This will likely impact the well plan, as build rate predictions and other drilling parameters may need to be changed. Accordingly, in step **832**, this event is identified.

In step **834**, a forecast may be made as to the impact of the event. For example, the surface steerable system **201** may determine whether the projected build rate needed to land the curve can be met based on the twenty foot difference. This determination may include examining the current location of the bit, the projected path, and similar information.

In step **836**, modifications may be made based on the forecast. For example, if the projected build rate can be met, then modifications may be made to the drilling parameters to address the formation depth difference, but the modifications may be relatively minor. However, if the projected build rate cannot be met, the surface steerable system **201** may determine how to address the situation by, for example, planning a bit trip to replace the current BHA with a BHA capable of making a new and more aggressive curve.

Such decisions may be automated or may require input or approval by the drilling engineer **302**, geologist **304**, or other individuals. For example, depending on the distance to the kick off point, the surface steerable system **201** may first stop drilling and then send an alert to an authorized individual, such as the drilling engineer **302** and/or geologist **304**. The drilling engineer **302** and geologist **304** may then become involved in planning a solution or may approve of a solution proposed by the surface steerable system **201**. In some embodiments, the surface steerable system **201** may automatically implement its calculated solution. Parameters may be set for such automatic implementation measures to ensure that drastic deviations from the original well plan do not occur automatically while allowing the automatic implementation of more minor measures.

It is understood that such recalibration forecasts may be performed based on many different factors and may be triggered by many different events. The forecasting portion of the process is directed to anticipating what changes may be needed due to the recalibration and calculating how such changes may be implemented. Such forecasting provides cost advantages because more options may be available when a problem is detected earlier rather than later. Using the previ-

ous example, the earlier the difference in the depth of the layer is identified, the more likely it is that the build rate can be met without changing the BHA.

Referring to FIG. **8D**, a method **840** illustrates one embodiment of an event-based process that may be executed by the on-site controller **144** of FIG. **2A**. The method **840** is directed to self-tuning that may be performed by the on-site controller **144** based on factors such as ROP, total cost, and reliability. By self-tuning, the on-site controller **144** may execute a learning process that enables it to optimize the drilling performance of the drilling rig **110**. Furthermore, the self-tuning process enables a balance to be reached that provides reliability while also lowering costs. Reliability in drilling operations is often tied to vibration and the problems that vibration can cause, such as stick-slip and whirling. Such vibration issues can damage or destroy equipment and can also result in a very uneven surface in the borehole that can cause other problems such as friction loading of future drilling operations as pipe/casing passes through that area of the borehole. Accordingly, it is desirable to minimize vibration while optimizing performance, since over-correcting for vibration may result in slower drilling than necessary. It is understood that the present optimization may involve a change in any drilling parameter and is not limited to a particular piece of equipment or control system. In other words, parameters across the entire drilling rig **110** and BHA may be changed during the self-tuning process. Furthermore, the optimization process may be applied to production by optimizing well smoothness and other factors affecting production. For example, by minimizing dogleg severity, production may be increased for the lifetime of the well.

Accordingly, in step **842**, one or more target parameters are identified. For example, the target parameter may be an MSE of 50 ksi or an ROP of 100 ft/hr that the on-site controller **144** is to establish and maintain. In step **844**, a plurality of control parameters are identified for use with the drilling operation. The control parameters are selected to meet the target MSE of 50 ksi or ROP of 100 ft/hr. The drilling operation is started with the control parameters, which may be used until the target MSE or ROP is reached. In step **846**, feedback information is received from the drilling operation when the control parameters are being used, so the feedback represents the performance of the drilling operation as controlled by the control parameters. Historical information may also be used in step **846**. In step **848**, an operational baseline is established based on the feedback information.

In step **850**, at least one of the control parameters is changed to modify the drilling operation, although the target MSE or ROP should be maintained. For example, some or all of the control parameters may be associated with a range of values and the value of one or more of the control parameters may be changed. In step **852**, more feedback information is received, but this time the feedback reflects the performance of the drilling operation with the changed control parameter. In step **854**, a performance impact of the change is determined with respect to the operational baseline. The performance impact may occur in various ways, such as a change in MSE or ROP and/or a change in vibration. In step **856**, a determination is made as to whether the control parameters are optimized. If the control parameters are not optimized, the method **840** returns to step **850**. If the control parameters are optimized, the method **840** moves to step **858**. In step **858**, the optimized control parameters are used for the current drilling operation with the target MSE or ROP and stored (e.g., in the database **128**) for use in later drilling operations and operational analyses. This may include linking formation information to the control parameters in the regional database **128**.

Referring to FIG. 9, one embodiment of a system architecture **900** is illustrated that may be used for the on-site controller **144** of FIG. 1A. The system architecture **900** includes interfaces configured to interact with external components and internal modules configured to process information. The interfaces may include an input driver **902**, a remote synchronization interface **904**, and an output interface **918**, which may include at least one of a graphical user interface (GUI) **906** and an output driver **908**. The internal modules may include a database query and update engine/diagnostic logger **910**, a local database **912** (which may be similar or identical to the database **410** of FIG. 4), a guidance control loop (GCL) module **914**, and an autonomous control loop (ACL) module **916**. It is understood that the system architecture **900** is merely one example of a system architecture that may be used for the on-site controller **144** and the functionality may be provided for the on-site controller **144** using many different architectures. Accordingly, the functionality described herein with respect to particular modules and architecture components may be combined, further separated, and organized in many different ways.

It is understood that the computer steerable system **144** may perform certain computations to prevent errors or inaccuracies from accumulating and throwing off calculations. For example, as will be described later, the input driver **902** may receive Wellsite Information Transfer Specification (WITS) input representing absolute pressure, while the surface steerable system **144** needs differential pressure and needs an accurate zero point for the differential pressure. Generally, the driller will zero out the differential pressure when the drillstring is positioned with the bit off bottom and full pump flow is occurring. However, this may be a relatively sporadic event. Accordingly, the surface steerable system **144** may recognize when the bit is off bottom and target flow rate has been achieved and zero out the differential pressure.

Another computation may involve block height, which needs to be calibrated properly. For example, block height may oscillate over a wide range, including distances that may not even be possible for a particular drilling rig. Accordingly, if the reported range is sixty feet to one hundred and fifty feet and there should only be one hundred feet, the surface steerable system **144** may assign a zero value to the reported sixty feet and a one hundred foot value to the reported one hundred and fifty feet. Furthermore, during drilling, error gradually accumulates as the cable is shifted and other events occur. The surface steerable system **144** may compute its own block height to predict when the next connection occurs and other related events, and may also take into account any error that may be introduced by cable issues.

Referring specifically to FIG. 9, the input driver **902** provides output to the GUI **906**, the database query and update engine/diagnostic logger **910**, the GCL **914**, and the ACL **916**. The input driver **902** is configured to receive input for the on-site controller **144**. It is understood that the input driver **902** may include the functionality needed to receive various file types, formats, and data streams. The input driver **902** may also be configured to convert formats if needed. Accordingly, the input driver **902** may be configured to provide flexibility to the on-site controller **144** by handling incoming data without the need to change the internal modules. In some embodiments, for purposes of abstraction, the protocol of the data stream can be arbitrary with an input event defined as a single change (e.g., a real time sensor change) of any of the given inputs.

The input driver **902** may receive various types of input, including rig sensor input (e.g., from the sensor system **214** of FIG. 2A), well plan data, and control data (e.g., engineering

control parameters). For example, rig sensor input may include hole depth, bit depth, toolface, inclination, azimuth, true vertical depth, gamma count, standpipe pressure, mud flow rate, rotary RPMs, bit speed, ROP, and WOB. The well plan data may include information such as projected starting and ending locations of various geologic layers at vertical depth points along the well plan path, and a planned path of the borehole presented in a three dimensional space. The control data may be used to define maximum operating parameters and other limitations to control drilling speed, limit the amount of deviation permitted from the planned path, define levels of authority (e.g., can an on-site operator make a particular decision or should it be made by an off-site engineer), and similar limitations. The input driver **902** may also handle manual input, such as input entered via a keyboard, a mouse, or a touch screen. In some embodiments, the input driver **902** may also handle wireless signal input, such as from a cell phone, a smart phone, a PDA, a tablet, a laptop, or any other device capable of wirelessly communicating with the on-site controller **144** through a network locally and/or offsite.

The database query and update engine/diagnostic logger **910** receives input from the input driver **902**, the GCL **914**, and ACL **916**, and provides output to the local database **912** and GUI **906**. The database query and update engine/diagnostic logger **910** is configured to manage the archiving of data to the local database **912**. The database query and update engine/diagnostic logger **910** may also manage some functional requirements of a remote synchronization server (RSS) via the remote synchronization interface **904** for archiving data that will be uploaded and synchronized with a remote database, such as the database **128** of FIG. 1A. The database query and update engine/diagnostic logger **910** may also be configured to serve as a diagnostic tool for evaluating algorithm behavior and performance against raw rig data and sensor feedback data.

The local database **912** receives input from the database query and update engine/diagnostic logger **910** and the remote synchronization interface **904**, and provides output to the GCL **914**, the ACL **916**, and the remote synchronization interface **904**. It is understood that the local database **912** may be configured in many different ways. As described in previous embodiments, the local database **912** may store both current and historic information representing both the current drilling operation with which the on-site controller **144** is engaged as well as regional information from the database **128**.

The GCL **914** receives input from the input driver **902** and the local database **912**, and provides output to the database query and update engine/diagnostic logger **910**, the GUI **906**, and the ACL **916**. Although not shown, in some embodiments, the GCL **906** may provide output to the output driver **908**, which enables the GCL **914** to directly control third party systems and/or interface with the drilling rig alone or with the ACL **916**. An embodiment of the GCL **914** is discussed below with respect to FIG. 11.

The ACL **916** receives input from the input driver **902**, the local database **912**, and the GCL **914**, and provides output to the database query and update engine/diagnostic logger **910** and output driver **908**. An embodiment of the ACL **916** is discussed below with respect to FIG. 12.

The output interface **918** receives input from the input driver **902**, the GCL **914**, and the ACL **916**. In the present example, the GUI **906** receives input from the input driver **902** and the GCL **914**. The GUI **906** may display output on a monitor or other visual indicator. The output driver **908** receives input from the ACL **916** and is configured to provide

an interface between the on-site controller **144** and external control systems, such as the control systems **208**, **210**, and **212** of FIG. 2A.

It is understood that the system architecture **900** of FIG. 9 may be configured in many different ways. For example, various interfaces and modules may be combined or further separated. Accordingly, the system architecture **900** provides one example of how functionality may be structured to provide the on-site controller **144**, but the on-site controller **144** is not limited to the illustrated structure of FIG. 9.

Referring to FIG. 10, one embodiment of the input driver **902** of the system architecture **900** of FIG. 9 is illustrated in greater detail. In the present example, the input driver **902** may be configured to receive input via different input interfaces, such as a serial input driver **1002** and a Transmission Control Protocol (TCP) driver **1004**. Both the serial input driver **1002** and the TCP input driver **1004** may feed into a parser **1006**.

The parser **1006** in the present example may be configured in accordance with a specification such as WITS and/or using a standard such as Wellsite Information Transfer Standard Markup Language (WITSML). WITS is a specification for the transfer of drilling rig-related data and uses a binary file format. WITS may be replaced or supplemented in some embodiments by WITSML, which relies on eXtensible Markup Language (XML) for transferring such information. The parser **1006** may feed into the database query and update engine/diagnostic logger **910**, and also to the GCL **914** and GUI **906** as illustrated by the example parameters of block **1010**. The input driver **902** may also include a non-WITS input driver **1008** that provides input to the ACL **916** as illustrated by block **1012**.

Referring to FIG. 11, one embodiment of the GCL **914** of FIG. 9 is illustrated in greater detail. In the present example, the GCL **914** may include various functional modules, including a build rate predictor **1102**, a geo modified well planner **1104**, a borehole estimator **1106**, a slide estimator **1108**, an error vector calculator **1110**, a geological drift estimator **1112**, a slide planner **1114**, a convergence planner **1116**, and a tactical solution planner **1118**. In the following description of the GCL **914**, the term external input refers to input received from outside the GCL **914** (e.g., from the input driver **902** of FIG. 9), while internal input refers to input received by a GCL module from another GCL module.

The build rate predictor **1102** receives external input representing BHA and geological information, receives internal input from the borehole estimator **1106**, and provides output to the geo modified well planner **1104**, slide estimator **1108**, slide planner **1114**, and convergence planner **1116**. The build rate predictor **1102** is configured to use the BHA and geological information to predict the drilling build rates of current and future sections of a well. For example, the build rate predictor **1102** may determine how aggressively the curve will be built for a given formation with given BHA and other equipment parameters.

The build rate predictor **1102** may use the orientation of the BHA to the formation to determine an angle of attack for formation transitions and build rates within a single layer of a formation. For example, if there is a layer of rock with a layer of sand above it, there is a formation transition from the sand layer to the rock layer. Approaching the rock layer at a ninety degree angle may provide a good face and a clean drill entry, while approaching the rock layer at a forty-five degree angle may build a curve relatively quickly. An angle of approach that is near parallel may cause the bit to skip off the upper surface of the rock layer. Accordingly, the build rate predictor **1102** may calculate BHA orientation to account for formation

transitions. Within a single layer, the build rate predictor **1102** may use BHA orientation to account for internal layer characteristics (e.g., grain) to determine build rates for different parts of a layer.

The BHA information may include bit characteristics, mud motor bend setting, stabilization and mud motor bit to bend distance. The geological information may include formation data such as compressive strength, thicknesses, and depths for formations encountered in the specific drilling location. Such information enables a calculation-based prediction of the build rates and ROP that may be compared to both real time results (e.g., obtained while drilling the well) and regional historical results (e.g., from the database **128**) to improve the accuracy of predictions as the drilling progresses. Future formation build rate predictions may be used to plan convergence adjustments and confirm that targets can be achieved with current variables in advance.

The geo modified well planner **1104** receives external input representing a well plan, internal input from the build rate predictor **1102** and the geo drift estimator **1112**, and provides output to the slide planner **1114** and the error vector calculator **1110**. The geo modified well planner **1104** uses the input to determine whether there is a more optimal path than that provided by the external well plan while staying within the original well plan error limits. More specifically, the geo modified well planner **1104** takes geological information (e.g., drift) and calculates whether another solution to the target may be more efficient in terms of cost and/or reliability. The outputs of the geo modified well planner **1104** to the slide planner **1114** and the error vector calculator **1110** may be used to calculate an error vector based on the current vector to the newly calculated path and to modify slide predictions.

In some embodiments, the geo modified well planner **1104** (or another module) may provide functionality needed to track a formation trend. For example, in horizontal wells, the geologist **304** may provide the surface steerable system **144** with a target inclination that the surface steerable system **144** is to attempt to hold. For example, the geologist **304** may provide a target to the directional driller **306** of 90.5-91 degrees of inclination for a section of the well. The geologist **304** may enter this information into the surface steerable system **144** and the directional driller **306** may retrieve the information from the surface steerable system **144**. The geo modified well planner **1104** may then treat the target as a vector target, for example, either by processing the information provided by the geologist **304** to create the vector target or by using a vector target entered by the geologist **304**. The geo modified well planner **1104** may accomplish this while remaining within the error limits of the original well plan.

In some embodiments, the geo modified well planner **1104** may be an optional module that is not used unless the well plan is to be modified. For example, if the well plan is marked in the surface steerable system **201** as non-modifiable, the geo modified well planner **1104** may be bypassed altogether or the geo modified well planner **1104** may be configured to pass the well plan through without any changes.

The borehole estimator **1106** receives external inputs representing BHA information, measured depth information, survey information (e.g., azimuth and inclination), and provides outputs to the build rate predictor **1102**, the error vector calculator **1110**, and the convergence planner **1116**. The borehole estimator **1106** is configured to provide a real time or near real time estimate of the actual borehole and drill bit position and trajectory angle. This estimate may use both straight line projections and projections that incorporate sliding. The borehole estimator **1106** may be used to compensate for the fact that a sensor is usually physically located some

distance behind the bit (e.g., fifty feet), which makes sensor readings lag the actual bit location by fifty feet. The borehole estimator **1106** may also be used to compensate for the fact that sensor measurements may not be continuous (e.g., a sensor measurement may occur every one hundred feet).

The borehole estimator **1106** may use two techniques to accomplish this. First, the borehole estimator **1106** may provide the most accurate estimate from the surface to the last survey location based on the collection of all survey measurements. Second, the borehole estimator **1106** may take the slide estimate from the slide estimator **1108** (described below) and extend this estimation from the last survey point to the real time drill bit location. Using the combination of these two estimates, the borehole estimator **1106** may provide the on-site controller **144** with an estimate of the drill bit's location and trajectory angle from which guidance and steering solutions can be derived. An additional metric that can be derived from the borehole estimate is the effective build rate that is achieved throughout the drilling process. For example, the borehole estimator **1106** may calculate the current bit position and trajectory **743** in FIG. 7C.

The slide estimator **1108** receives external inputs representing measured depth and differential pressure information, receives internal input from the build rate predictor **1102**, and provides output to the borehole estimator **1106** and the geo modified well planner **1104**. The slide estimator **1108**, which may operate in real time or near real time, is configured to sample toolface orientation, differential pressure, measured depth (MD) incremental movement, MSE, and other sensor feedback to quantify/estimate a deviation vector and progress while sliding.

Traditionally, deviation from the slide would be predicted by a human operator based on experience. The operator would, for example, use a long slide cycle to assess what likely was accomplished during the last slide. However, the results are generally not confirmed until the MWD survey sensor point passes the slide portion of the borehole, often resulting in a response lag defined by the distance of the sensor point from the drill bit tip (e.g., approximately fifty feet). This lag introduces inefficiencies in the slide cycles due to over/under correction of the actual path relative to the planned path.

With the slide estimator **1108**, each toolface update is algorithmically merged with the average differential pressure of the period between the previous and current toolfaces, as well as the MD change during this period to predict the direction, angular deviation, and MD progress during that period. As an example, the periodic rate may be between ten and sixty seconds per cycle depending on the tool face update rate of the MWD tool. With a more accurate estimation of the slide effectiveness, the sliding efficiency can be improved. The output of the slide estimator **1108** is periodically provided to the borehole estimator **1106** for accumulation of well deviation information, as well as to the geo modified well planner **1104**. Some or all of the output of the slide estimator **1108** may be output via a display such as the display **250** of FIG. 2B.

The error vector calculator **1110** receives internal input from the geo modified well planner **1104** and the borehole estimator **1106**. The error vector calculator **1110** is configured to compare the planned well path to the actual borehole path and drill bit position estimate. The error vector calculator **1110** may provide the metrics used to determine the error (e.g., how far off) the current drill bit position and trajectory are from the plan. For example, the error vector calculator **1110** may calculate the error between the current position **743** of FIG. 7C to the planned path **742** and the desired bit position

741. The error vector calculator **1110** may also calculate a projected bit position/projected path representing the future result of a current error as described previously with respect to FIG. 7B.

The geological drift estimator **1112** receives external input representing geological information and provides outputs to the geo modified well planner **1104**, slide planner **1114**, and tactical solution planner **1118**. During drilling, drift may occur as the particular characteristics of the formation affect the drilling direction. More specifically, there may be a trajectory bias that is contributed by the formation as a function of drilling rate and BHA. The geological drift estimator **1112** is configured to provide a drift estimate as a vector. This vector can then be used to calculate drift compensation parameters that can be used to offset the drift in a control solution.

The drift vector information may also be used in determinations involving creation of a convergence path wherein the drift vector effect on drilling direction may be utilized in determining a drilling direction in order that a direction of drilling may be utilized in order to take into account the drift vector provided by the present formation characteristic and drill bit characteristics as will be more fully described hereinbelow.

The slide planner **1114** receives internal input from the build rate predictor **1102**, the geo modified well planner **1104**, the error vector calculator **1110**, and the geological drift estimator **1112**, and provides output to the convergence planner **1116** as well as an estimated time to the next slide. The slide planner **1114** is configured to evaluate a slide/drill ahead cost equation and plan for sliding activity, which may include factoring in BHA wear, expected build rates of current and expected formations, and the well plan path. During drill ahead, the slide planner **1114** may attempt to forecast an estimated time of the next slide to aid with planning. For example, if additional lubricants (e.g., beads) are needed for the next slide and pumping the lubricants into the drill string needs to begin thirty minutes before the slide, the estimated time of the next slide may be calculated and then used to schedule when to start pumping the lubricants.

Functionality for a loss circulation material (LCM) planner may be provided as part of the slide planner **1114** or elsewhere (e.g., as a stand-alone module or as part of another module described herein). The LCM planner functionality may be configured to determine whether additives need to be pumped into the borehole based on indications such as flow-in versus flow-back measurements. For example, if drilling through a porous rock formation, fluid being pumped into the borehole may get lost in the rock formation. To address this issue, the LCM planner may control pumping LCM into the borehole to clog up the holes in the porous rock surrounding the borehole to establish a more closed-loop control system for the fluid.

The slide planner **1114** may also look at the current position relative to the next connection. A connection may happen every ninety to one hundred feet (or some other distance or distance range based on the particulars of the drilling operation) and the slide planner **1114** may avoid planning a slide when close to a connection and/or when the slide would carry through the connection. For example, if the slide planner **1114** is planning a fifty foot slide but only twenty feet remain until the next connection, the slide planner **1114** may calculate the slide starting after the next connection and make any changes to the slide parameters that may be needed to accommodate waiting to slide until after the next connection. This avoids inefficiencies that may be caused by starting the slide, stopping for the connection, and then having to reorient the toolface before finishing the slide. During slides, the slide

planner 1114 may provide some feedback as to the progress of achieving the desired goal of the current slide.

In some embodiments, the slide planner 1114 may account for reactive torque in the drillstring. More specifically, when rotating is occurring, there is a reactional torque wind up in the drillstring. When the rotating is stopped, the drillstring unwinds, which changes toolface orientation and other parameters. When rotating is started again, the drillstring starts to wind back up. The slide planner 1114 may account for this reactional torque so that toolface references are maintained rather than stopping rotation and then trying to adjust to an optimal tool face orientation. While not all MWD tools may provide toolface orientation when rotating, using one that does supply such information for the GCL 914 may significantly reduce the transition time from rotating to sliding.

In additional embodiments, the slide planner 1114 may also use drift information provided from the geo drift estimator 1112 in order to perform tool face targeting calculations in order to plan a drilling segment from a present bit location to a target bit location at a location that attempts to bring the bit more in line with a predetermined drilling target path.

Referring now also to FIG. 26, there is more particularly illustrated the slide planner 1114 and the components associated with determining a convergence path that takes into account drift information provided by the drift estimator 1112. Initially, a look ahead estimator 2602 utilizes information provided by the system on the system build rate, an error vector associated with error vector calculations from the error vector calculator 110 indicating the degree of error from a target well path and a present well plan provided by the well planner 1104. The well plan provides information with respect to the desired target path where the bottom hole assembly should presently be located. The error vector provides information with respect to the error from the indicated well path, and the build rate demonstrates the predicted build rate that has been determined thus far within the drilling. Each of these pieces of information are provided to the look ahead estimator 2602 that determines a look ahead point that is a fixed distance ahead of the bottom hole assembly for getting the bottom hole assembly back on target with respect to the well plan. The look ahead estimator 2602 calculates a direction of drilling toward the look ahead point by establishing a tool face vector for the bottom hole assembly. The tool face vector comprises a vector toward the look ahead point transposed onto a plane that is perpendicular to the bottom hole assembly. The toolface vector shows the orientation of the toolface while sliding to help achieve convergence with the target well path as the bottom hole assembly drills toward moving look ahead point that is a fixed distance ahead of the bottom hole assembly. The calculated tool face vector is provided to a drift compensator 2604 which additionally receives the drift estimate information from the drift estimator 1112. The drift compensator 2604 determines a new adjusted toolface vector that adjusts the toolface vector based upon the drift associated with the present geological formation that the bottom hole assembly is passing through in an attempt to bring the bottom hole assembly back into convergence with the target well path as the bottom hole assembly travel toward its moving look ahead point that is a fixed distance ahead of the bottom hole assembly. The adjustment to the tool face vector direction takes into account the geological formation drift that has been calculated from recent drilling operations.

Referring now also to FIG. 27A there is more particularly illustrated the drilling path associated with this process. Dashed line 2702 illustrates the target drill path that the

bottom hole assembly is attempting to drill along according to a created well plan. Line 2704 up to point 2706 illustrates the actual drill path that has been achieved up to a selected point in time. As can be seen, the point 2706 is not located upon the desired target path 2702. Using the look ahead estimator 2602, a toolface vector is determined from the current position 2706 to cause the bottom hole assembly to converge toward the target drill path 2702 as the bottom hole assembly moves from the present toolface location 2706 toward the moving look ahead point 2708 that remains a fixed distance 2710 out from the front of the bottom hole assembly. The drilling path back toward convergence with the target path 2702 consists of a series of slides 2712 represented by curved portions of the drill path and rotations 2714 represented by the straight portions of the drill path that take the bit back toward convergence with the target path 2702. However, the slides 2712 of the drill path 2710 does not take into account the geological drift associated with the geological formation that the bottom hole assembly is drilling through. In actual operation, the drift associated with the drilling operation will affect the drill path location such that attempting to drill along a toolface vector that attempts to create path 2710 will cause the bottom hole assembly to actually follow a path above or below the desired drilling path that either overshoots or undershoots that target drill path 2702.

In order to compensate for this, the drift compensator 2604 will alter the toolface vector to take into account the geological drift occurring when drilling over the rotation portions of the drilling path. Referring now to FIG. 25B, slide 2718 and rotation 2720 represent an ideal slide/rotation drilling sequence that is not affected by geological drift. In this case the bit would move from an initial point 2722 to an ending point 2724 as expected. In the case of drift that drift is forcing the bit to move downward as illustrated generally at 2726, the slide 2728 will appear to point the bit above the desired endpoint 2724 after the rotation portion 2730. However the downward drift 2726 will force the bit in a downward direction such that the bit will end up at point 2724. This type of toolface vector would be utilized when the geological drift tendency would be to drive the bottom hole assembly below the planned drill path 2702.

In a similar manner, when the drift is forcing the bit to move upward as illustrated generally at 2732, the slide 2734 will appear to point the bit above the desired endpoint 2724 after the rotation portion 2736. However the upward drift 2726 will force the bit in an upward direction such that the bit will end up at point 2724 after the slide 2734 and rotation 2736. This type of toolface vector would be utilized when the geological drift tendency would be to drive the bottom hole assembly above the planned drill path 2702. Thus, the drift adjusted toolface vectors for providing slides 2728 or 2734 compensate for the natural drift tendency of the geological formation during the rotation portions of drilling to arrive at a desired target location.

While the present description with respect to FIG. 27 has been made with respect to establishing a toolface vector to create a path above or below a target path 2702 in the Y axis, the drift associated with a drilling bit may occur in three dimensions. Thus, the drift adjusted toolface vector may be established anywhere in three dimensions in order to ultimately achieve a convergence with the desired target path 2702 while taking into account any number of drift forces acting on the bit.

For example, assume the drilling operator is looking a distance of 100 feet ahead of the present drill point location on the well plan. If the recent historical drift information is causing the drill bit to drift up 2 degrees per 100 feet, the

toolface vector would use an average angle over the 100 foot window to determine a net 1.8 foot upward migration to achieve intersection with the target path at the desired location. To compensate a toolface vector down from the well plan by 1.8 feet at a distance of 100 feet ahead of the current position would be utilized for the look ahead reference target point.

Referring now to FIG. 27C, rather than calculating a single toolface vector or group of toolface vectors to determine a convergence path from the present bit location 2706 to a target drill path, the drift compensator 2604 may determine a number of potential toolface vectors associate with different slides 2740 and rotations 2742 to provide a plurality of drill paths 2744 to enable a system to further base target convergence decisions on cost of drilling paths that utilized multiple drilling paths. Thus, multiple toolface vectors may be determined for each slide point creating multiple paths accounting for drift, and a most cost effective path selected. In some cases, the most direct drilling path may not be the most cost effective one and variations from the most direct toolface vector may be utilized in order to carry out various cost concerns.

In addition to determining a sweep of toolface vectors for determining a most cost effective drilling path, a sweep of toolface vectors may be selected for addressing total vertical depth (TVD) errors and to determining more aggressive convergence paths for the BHA to the target drill path. In this manner various ways for correcting TVD errors or more quickly seeking a convergence path may be presented and selected based upon differing drilling needs.

Referring now to FIG. 28, there is more particularly illustrated a flow chart describing the process of FIGS. 26 and 27. Initially, at step 2802, a present position of the drilling tool is determined during a slide. A toolface vector necessary to converge with a desired target path at a look ahead point a fixed distance ahead of the bit is calculated at step 2804 utilizing information such as the build rate, present error vector and well plan information within the look ahead estimator 2602. The desired toolface vector is further combined with geologic formation drift estimate information within the drift estimator 2604 to move the look ahead point and determine the compensated toolface vector at step 2806. The bottom hole assembly is oriented during sliding in accordance with the compensated toolface vector and then through a rotation at steps 2808 and 2810 providing a path that achieves the desired convergence. Inquiry step 2810 determines if the desired convergence with the target path has been achieved. If not control passes back to step 2802. If a desired convergence has been achieved, the processed is determined to complete at step 2812.

Thus, the above-described feature operates in a similar fashion to that of a sharp shooter when adjusting their scope to account for their movement in a bullet over a long target distance. The sharp shooter must account for bullet drop occurring due to gravity and side to side compensation due to a cross-wind. The toolface vector is adjusted in a similar manner to have the bottom hole assembly converge with the target drill path utilizing the recent drift information associated with the bottom hole assembly.

While a foregoing discussion has been done with respect to the drift forces applied to a bottom hole assembly as it is drilling through a drilling formation, the same concepts may be applied to any forces acting upon the bottom hole assembly to cause the bottomhole assembly to move indirectly from a first point toward a second point when the drilling rig is driving the bit from a first point toward a second point.

The convergence planner 1116 receives internal inputs from the build rate predictor 1102, the borehole estimator 1106, and the slide planner 1114, and provides output to the tactical solution planner 1118. The convergence planner 1116 is configured to provide a convergence plan when the current drill bit position is not within a defined margin of error of the planned well path. The convergence plan represents a path from the current drill bit position to an achievable and optimal convergence target point along the planned path. The convergence plan may take account the amount of sliding/drilling ahead that has been planned to take place by the slide planner 1114. The convergence planner 1116 may also use BHA orientation information for angle of attack calculations when determining convergence plans as described above with respect to the build rate predictor 1102. The solution provided by the convergence planner 1116 defines a new trajectory solution for the current position of the drill bit. The solution may be real time, near real time, or future (e.g., planned for implementation at a future time). For example, the convergence planner 1116 may calculate a convergence plan as described previously with respect to FIGS. 7C and 8.

The tactical solution planner 1118 receives internal inputs from the geological drift estimator 1112 and the convergence planner 1116, and provides external outputs representing information such as toolface orientation, differential pressure, and mud flow rate. The tactical solution planner 1118 is configured to take the trajectory solution provided by the convergence planner 1116 and translate the solution into control parameters that can be used to control the drilling rig 110. For example, the tactical solution planner 1118 may take the solution and convert the solution into settings for the control systems 208, 210, and 212 to accomplish the actual drilling based on the solution. The tactical solution planner 1118 may also perform performance optimization as described previously. The performance optimization may apply to optimizing the overall drilling operation as well as optimizing the drilling itself (e.g., how to drill faster).

Other functionality may be provided by the GCL 914 in additional modules or added to an existing module. For example, there is a relationship between the rotational position of the drill pipe on the surface and the orientation of the downhole toolface. Accordingly, the GCL 914 may receive information corresponding to the rotational position of the drill pipe on the surface. The GCL 914 may use this surface positional information to calculate current and desired toolface orientations. These calculations may then be used to define control parameters for adjusting the top drive or Kelly drive to accomplish adjustments to the downhole toolface in order to steer the well.

For purposes of example, an object-oriented software approach may be utilized to provide a class-based structure that may be used with the GCL 914 and/or other components of the on-site controller 144. In the present embodiment, a drilling model class is defined to capture and define the drilling state throughout the drilling process. The class may include real time information. This class may be based on the following components and sub-models: a drill bit model, a borehole model, a rig surface gear model, a mud pump model, a WOB/differential pressure model, a positional/rotary model, an MSE model, an active well plan, and control limits. The class may produce a control output solution and may be executed via a main processing loop that rotates through the various modules of the GCL 914.

The drill bit model may represent the current position and state of the drill bit. This model includes a three dimensional position, a drill bit trajectory, BHA information, bit speed, and toolface (e.g., orientation information). The three dimen-

sional position may be specified in north-south (NS), east-west (EW), and true vertical depth (TVD). The drill bit trajectory may be specified as an inclination and an azimuth angle. The BHA information may be a set of dimensions defining the active BHA. The borehole model may represent the current path and size of the active borehole. This model includes hole depth information, an array of survey points collected along the borehole path, a gamma log, and borehole diameters. The hole depth information is for the current drilling job. The borehole diameters represent the diameters of the borehole as drilled over the current drill job.

The rig surface gear model may represent pipe length, block height, and other models, such as the mud pump model, WOB/differential pressure model, positional/rotary model, and MSE model. The mud pump model represents mud pump equipment and includes flow rate, standpipe pressure, and differential pressure. The WOB/differential pressure model represents drawworks or other WOB/differential pressure controls and parameters, including WOB. The positional/rotary model represents top drive or other positional/rotary controls and parameters including rotary RPM and spindle position. The active well plan represents the target borehole path and may include an external well plan and a modified well plan. The control limits represent defined parameters that may be set as maximums and/or minimums. For example, control limits may be set for the rotary RPM in the top drive model to limit the maximum RPMs to the defined level. The control output solution represents the control parameters for the drilling rig 110.

The main processing loop can be handled in many different ways. For example, the main processing loop can run as a single thread in a fixed time loop to handle rig sensor event changes and time propagation. If no rig sensor updates occur between fixed time intervals, a time only propagation may occur. In other embodiments, the main processing loop may be multi-threaded.

Each functional module of the GCL 914 may have its behavior encapsulated within its own respective class definition. During its processing window, the individual units may have an exclusive portion in time to execute and update the drilling model. For purposes of example, the processing order for the modules may be in the sequence of geo modified well planner 1104, build rate predictor 1102, slide estimator 1108, borehole estimator 1106, error vector calculator 1110, slide planner 1114, convergence planner 1116, geological drift estimator 1112, and tactical solution planner 1118. It is understood that other sequences may be used.

In the present embodiment, the GCL 914 may rely on a programmable timer module that provides a timing mechanism to provide timer event signals to drive the main processing loop. While the on-site controller 144 may rely purely on timer and date calls driven by the programming environment (e.g., java), this would limit timing to be exclusively driven by system time. In situations where it may be advantageous to manipulate the clock (e.g., for evaluation and/or testing), the programmable timer module may be used to alter the time. For example, the programmable timer module may enable a default time set to the system time and a time scale of 1.0, may enable the system time of the on-site controller 144 to be manually set, may enable the time scale relative to the system time to be modified, and/or may enable periodic event time requests scaled to the time scale to be requested.

Referring to FIG. 12, one embodiment of the ACL 916 provides different functions to the on-site controller 144. The ACL 916 may be considered a second feedback control loop that operates in conjunction with a first feedback control loop provided by the GCL 914. The ACL 916 may also provide

actual instructions to the drilling rig 110, either directly to the drilling equipment 216 or via the control systems 208, 210, and 212. The ACL 916 may include a positional/rotary control logic block 1202, WOB/differential pressure control logic block 1204, fluid circulation control logic block 1206, and a pattern recognition/error detection block 1208.

One function of the ACL 916 is to establish and maintain a target parameter (e.g., an ROP of a defined value of ft/hr) based on input from the GCL 914. This may be accomplished via control loops using the positional/rotary control logic block 1202, WOB/differential pressure control logic block 1204, and fluid circulation control logic block 1206. The positional/rotary control logic block 1202 may receive sensor feedback information from the input driver 902 and set point information from the GCL 914 (e.g., from the tactical solution planner 1118). The differential pressure control logic block 1204 may receive sensor feedback information from the input driver 902 and set point information from the GCL 914 (e.g., from the tactical solution planner 1118). The fluid circulation control logic block 1206 may receive sensor feedback information from the input driver 902 and set point information from the GCL 914 (e.g., from the tactical solution planner 1118).

The ACL 916 may use the sensor feedback information and the set points from the GCL 914 to attempt to maintain the established target parameter. More specifically, the ACL 916 may have control over various parameters via the positional/rotary control logic block 1202, WOB/differential pressure control logic block 1204, and fluid circulation control logic block 1206, and may modulate the various parameters to achieve the target parameter. The ACL 916 may also modulate the parameters in light of cost-driven and reliability-driven drilling goals, which may include parameters such as a trajectory goal, a cost goal, and/or a performance goal. It is understood that the parameters may be limited (e.g., by control limits set by the drilling engineer 306) and the ACL 916 may vary the parameters to achieve the target parameter without exceeding the defined limits. If this is not possible, the ACL 916 may notify the on-site controller 144 or otherwise indicate that the target parameter is currently unachievable.

In some embodiments, the ACL 916 may continue to modify the parameters to identify an optimal set of parameters with which to achieve the target parameter for the particular combination of drilling equipment and formation characteristics. In such embodiments, the on-site controller 144 may export the optimal set of parameters to the database 128 for use in formulating drilling plans for other drilling projects.

Another function of the ACL 916 is error detection. Error detection is directed to identifying problems in the current drilling process and may monitor for sudden failures and gradual failures. In this capacity, the pattern recognition/error detection block 1208 receives input from the input driver 902. The input may include the sensor feedback received by the positional/rotary control logic block 1202, WOB/differential pressure control logic block 1204, and fluid circulation control logic block 1206. The pattern recognition/error detection block 1208 monitors the input information for indications that a failure has occurred or for sudden changes that are illogical.

For example, a failure may be indicated by an ROP shift, a radical change in build rate, or any other significant changes. As an illustration, assume the drilling is occurring with an expected ROP of 100 ft/hr. If the ROP suddenly drops to 50 ft/hr with no change in parameters and remains there for some defined amount of time, an equipment failure, formation shift, or another event has occurred. Another error may be indicated

when MWD sensor feedback has been steadily indicating that drilling has been heading north for hours and the sensor feedback suddenly indicates that drilling has reversed in a few feet and is heading south. This change clearly indicates that a failure has occurred. The changes may be defined and/or the pattern recognition/error detection block **1208** may be configured to watch for deviations of a certain magnitude. The pattern recognition/error detection block **1208** may also be configured to detect deviations that occur over a period of time in order to catch more gradual failures or safety concerns.

When an error is identified based on a significant shift in input values, the on-site controller **201** may send an alert. This enables an individual to review the error and determine whether action needs to be taken. For example, if an error indicates that there is a significant loss of ROP and an intermittent change/rise in pressure, the individual may determine that mud motor chunking has likely occurred with rubber tearing off and plugging the bit. In this case, the BHA may be tripped and the damage repaired before more serious damage is done. Accordingly, the error detection may be used to identify potential issues that are occurring before they become more serious and more costly to repair.

Another function of the ACL **916** is pattern recognition. Pattern recognition is directed to identifying safety concerns for rig workers and to provide warnings (e.g., if a large increase in pressure is identified, personnel safety may be compromised) and also to identifying problems that are not necessarily related to the current drilling process, but may impact the drilling process if ignored. In this capacity, the pattern recognition/error detection block **1208** receives input from the input driver **902**. The input may include the sensor feedback received by the positional/rotary control logic block **1202**, WOB/differential pressure control logic block **1204**, and fluid circulation control logic block **1206**. The pattern recognition/error detection block **1208** monitors the input information for specific defined conditions. A condition may be relatively common (e.g., may occur multiple times in a single borehole) or may be relatively rare (e.g., may occur once every two years). Differential pressure, standpipe pressure, and any other desired conditions may be monitored. If a condition indicates a particular recognized pattern, the ACL **916** may determine how the condition is to be addressed. For example, if a pressure spike is detected, the ACL **916** may determine that the drilling needs to be stopped in a specific manner to enable a safe exit. Accordingly, while error detection may simply indicate that a problem has occurred, pattern recognition is directed to identifying future problems and attempting to provide a solution to the problem before the problem occurs or becomes more serious.

Referring to FIG. **13**, one embodiment of a computer system **1300** is illustrated. The computer system **1300** is one possible example of a system component or device such as the on-site controller **144** of FIG. **1A**. In scenarios where the computer system **1300** is on-site, such as at the location of the drilling rig **110** of FIG. **1A**, the computer system may be contained in a relatively rugged, shock-resistant case that is hardened for industrial applications and harsh environments.

The computer system **1300** may include a central processing unit ("CPU") **1302**, a memory unit **1304**, an input/output ("I/O") device **1306**, and a network interface **1308**. The components **1302**, **1304**, **1306**, and **1308** are interconnected by a transport system (e.g., a bus) **1310**. A power supply (PS) **1312** may provide power to components of the computer system **1300**, such as the CPU **1302** and memory unit **1304**. It is understood that the computer system **1300** may be differently configured and that each of the listed components may actu-

ally represent several different components. For example, the CPU **1302** may actually represent a multi-processor or a distributed processing system; the memory unit **1304** may include different levels of cache memory, main memory, hard disks, and remote storage locations; the I/O device **1306** may include monitors, keyboards, and the like; and the network interface **1308** may include one or more network cards providing one or more wired and/or wireless connections to a network **1314**. Therefore, a wide range of flexibility is anticipated in the configuration of the computer system **1300**.

The computer system **1300** may use any operating system (or multiple operating systems), including various versions of operating systems provided by Microsoft (such as WINDOWS), Apple (such as Mac OS X), UNIX, and LINUX, and may include operating systems specifically developed for handheld devices, personal computers, and servers depending on the use of the computer system **1300**. The operating system, as well as other instructions (e.g., software instructions for performing the functionality described in previous embodiments) may be stored in the memory unit **1304** and executed by the processor **1302**. For example, if the computer system **1300** is the on-site controller **144**, the memory unit **1304** may include instructions for performing methods such as the methods **600** of FIG. **6**, **700** of FIG. **7A**, **720** of FIG. **7B**, **800** of FIG. **8A**, **820** of FIG. **8B**, **830** of FIG. **8C**, and **840** of FIG. **8D**.

Referring to FIGS. **14A-14D**, embodiments of sections of the borehole **164** of FIG. **1B** are illustrated. FIG. **14A** illustrates an embodiment of the borehole **164** where the slide occurs in the middle of the section. The slide is planned to begin at a point marked by line **1402** and end at a point marked by line **1404**. Sequential survey points **1406** and **1408** mark locations where measured surveys occur. Being sequential, there is no survey point between the two survey points **1406** and **1408**. FIG. **14B** illustrates an embodiment of the borehole **164a** where the slide occurs at the beginning of the section (e.g., right after the survey point **1406**). FIG. **14C** illustrates an embodiment of the borehole **164b** where the slide occurs at the end of the section (e.g., leading up to the survey point **1408**). FIG. **14D** illustrates an embodiment of the borehole **164c** where the slide occurs for the entire distance between the survey points **1406** and **1408**. FIG. **14E** illustrates the boreholes **164a-164c** (not to scale) overlaid on one another.

Referring specifically to FIG. **14A**, in the present example, two possible paths **1410** and **1412** are illustrated between the survey points **1406** and **1408**. The two paths **1410** and **1412** are used herein to illustrate what may happen in the borehole **164** between the two survey points **1406** and **1408**. As described previously, surveys may occur at defined intervals, such as every thirty, forty-five, or ninety feet. For example, a survey may occur each time a new section of pipe (e.g., a joint) is added to the drill string. If the sections are approximately thirty feet long and a survey is taken every three sections (e.g., a stand), the surveys may occur approximately every ninety feet. Constant surveying is generally not practical as performing a survey may take a relatively substantial amount of time (e.g., from five to twenty minutes) and, in addition, control of the reactional torque neutral point may be lost. Between surveys, the state of the drilling (e.g., orientation of the bit and distance drilled) is not generally known. Accordingly, the path between the survey points **1406** and **1408** is unknown. This lack of knowledge may affect various aspects of drilling the borehole **164**, as well as the final efficiency of the well.

For example, assume that the planned borehole **164** includes a fifty foot slide (from point **1402** to point **1404**) and the slide occurs between the survey points **1406** and **1408**.

One possible path **1410** for the slide occurs when the drilling is held almost perfectly on course, which would result in a slide of approximately fifty feet (assuming other factors are ideal). However, another possible path **1412** occurs when the drilling does not stay on course. In the present example, the path **1412** is not even on course prior to the line **1402** that represents the beginning of the slide. As the shortest distance between the points **1406** and **1408** is a straight line (or an arc at the maximum build rate), the path **1410** is more efficient than the path **1412** in making progress toward the target. Furthermore, not only is the path **1412** less efficient in reaching the target, it also forms a less ideal borehole in terms of tortuosity as described in greater detail below.

It is understood, as described previously, that there may be a survey point offset where the survey point is actually located some distance behind the bit and so the survey location may not represent the actual bit location. Because of this offset distance, a survey is accurate only to a certain distance (e.g., fifty feet behind the bit) and there is usually some uncertainty in the path ahead of the survey point to where the bit is actually located. Accordingly, knowing the actual path past a survey point may also be beneficial as illustrated by path segment **1413** extending from survey point **1408**.

In addition to providing information about drilling efficiency, knowing what occurs between the survey points **1406** and **1408** may enable the effective build rate of the BHA to be assessed more objectively because the build rate orientation stability can be taken into account. If the build rate orientation stability is not taken into account, the second path **1412** that lacks orientation stability may be included in the assessment, which would make the BHA seem less efficient than it actually was. In turn, the more accurate assessment of the actual path of the BHA aids in the accuracy of later drilling predictions (e.g., build rate predictions).

Knowledge of what occurs between survey points may also aid in addressing drilling problems such as tortuosity in the borehole that may impact whether casing can be run, increase friction in the drill string, affect lubrication planning for slides, and other issues. For example, dogleg severity is often viewed as the change of angle between two sequential survey points. However, this view provides no information as to whether a dogleg exists between the survey points and, if one does exist, how severe it is. Furthermore, the orientation of the doglegs may create even more severe problems. For example, a dogleg created by a left arc that is immediately followed by a dogleg created by a right arc may be more problematic than if the following dogleg is also a left arc. In other words, sequential doglegs that arc in generally the same direction may be preferable to sequential doglegs that arc in opposite directions. Accordingly, the survey points may show a dogleg characterized by a five degree per hundred foot severity ($5^{\circ}/100'$), while the actual path may include a dogleg of $10^{\circ}/100'$ at one point, $5^{\circ}/100'$ at another point, et cetera, between the survey points, and these doglegs may have different orientations.

Knowing what is happening between the survey points and accumulating such information over the course of the well enables problems to be addressed by implementing one or more solutions before drilling continues, during later drilling, and even after drilling. For example, the ability to measure tortuosity in real time or near real time may enable determinations to be made during drilling such as whether lubrication is needed, how and when to apply the lubrication, and whether back reaming a particular section of the borehole is needed. Such information may also be used to determine whether a planned well should be stopped early. After the well is completed, the use of path information that is higher reso-

lution than the information provided by the survey points may be used to improve the well, such as in a determination on where to focus reaming activity (e.g., at a problem area at ten thousand feet).

It is understood that information about what is occurring between survey points may also be useful even when not sliding. For example, drift caused by formation characteristics may affect the path even when drilling straight ahead. Accordingly, current location estimates may be useful regardless of the type of drilling (e.g., rotating or sliding).

Referring to FIG. **15**, one embodiment of a three-dimensional borehole space **1500** is illustrated with two measured survey points **1502** (also labeled as "A") and **1504** (also labeled as "C"). A borehole path (not shown) extends between the two survey points **1502** and **1504**, but the actual path is unknown. Current borehole projection methods frequently use a minimum curvature technique for estimating the borehole projection between the two survey points **1502** and **1504**. Assuming the initial borehole position is known as well as its initial survey trajectory, there may be only a subsequent measure of additional borehole length and a new survey trajectory that can be measured from surface and downhole instruments that are available.

In FIG. **15**, the borehole space is presented in Cartesian space with a North-South (N) axis **1508**, an East-West (E) axis **1510**, an Up-Down Vertical (V) axis **1512**, and a borehole trajectory where an inclination angle represents the vertical component and a compass style azimuth angle represents the horizontal component. The initial survey point **1502** has an inclination and azimuth trajectory of α_1 and ϵ_1 , respectively, and the second survey point **1504** has an inclination and azimuth trajectory of α_2 and ϵ_2 , respectively.

With only new survey trajectory and path length information available, an assumption must be made about the shape of the borehole between the survey points **1502** and **1504**. The minimum curvature method works off the assumption that the borehole moves along the smoothest possible arc between two survey points. This arc is represented by arc **1514**. The change in trajectory angle from survey point **1502** to survey point **1504** (β) is often referred to as a dogleg in the context of surveying. The path ABC (where B is also labeled as point **1506**) represents the balanced tangential method path, whereby a borehole projection is estimated by two line segments which intersect at the point where the curvature angle, β , is evenly bisected. This bisection point is point **1506** in the present example. This is a useful case, as the minimum curvature method represents a special case of the balanced tangential method where the two line segments are substituted with a circular arc curve (e.g., the arc **1514**) that also passes through points **1502** and **1504** with tangents at those points aligned with their respective trajectories. The equations for the curve AB are the same as the balanced tangential method for calculating path ABC except for the application of the ratio factor (RF):

$$\Delta V = \frac{\Delta MD}{2} [\cos\alpha_1 + \cos\alpha_2] \times RF \quad (\text{Equation 1})$$

$$\Delta N = \frac{\Delta MD}{2} [\sin\alpha_1 \times \cos\epsilon_1 + \sin\alpha_2 \times \cos\epsilon_2] \times RF \quad (\text{Equation 2})$$

$$\Delta E = \frac{\Delta MD}{2} [\sin\alpha_1 \times \sin\epsilon_1 + \sin\alpha_2 \times \sin\epsilon_2] \times RF \quad (\text{Equation 3})$$

When using Equations 1-3 for estimating borehole positions between measured survey points, ΔMD represents an increase in measured depth progress between two survey trajectory measurements.

The ratio factor (RF) is used to account for the path length difference between the length of ABC and the length of the minimum curvature arc which crosses through AC. RF is given by the equation:

$$RF = \frac{2}{\beta} \tan \frac{\beta}{2} \tag{Equation 4}$$

The minimum curvature method may result in significant inaccuracy as shown in the following examples. There are two basic assumptions in these examples. The first is that the example starts from a ninety degree inclination. The second is that all sliding is two-dimensional in the vertical plane.

Table 1, shown below, illustrates a scenario where a slide has occurred.

TABLE 1

Description	Value	Units
Total MD Increment Between Surveys	100	ft
Slide/Build Duration	15	ft
Instantaneous Build Rate	12	Degrees/100 ft
Inclination Change	1.8	Degrees

For purposes of illustration, the distance between surveys is equal to one hundred feet and is used as a surface measurement of the total measured depth increment. Accordingly, the total measured depth increment between surveys in Table 1 is one hundred feet. The slide lasted for fifteen feet and had an instantaneous build rate of twelve degrees per one hundred feet, so the inclination change over the twelve foot slide was 1.8 degrees.

Table 2, shown below, illustrates two scenarios where a slide has occurred. The first column contains two rows, with each row indicating whether the slide occurred at the beginning of the one hundred foot distance (one embodiment of which is illustrated in FIG. 14B) or at the end (one embodiment of which is illustrated in FIG. 14C).

TABLE 2

	MD change (ft)	TVD change (ft)	Traditional Curve Fit TVD change (ft)	Interpreted TVD error (ft)	Interpreted Formation Dip Error Over Survey Period Due to TVD Error (degrees)
Slide before Rotate	100	2.906	1.571	1.335	0.765
Rotate before Slide	100	0.236	1.571	-1.335	-0.765

In the first row where sliding occurred before rotation, the TVD change is 2.906 feet. Using the previously presented equations for curve fitting, the curve fit TVD change is 1.571 feet. This results in an interpreted TVD error of 1.335 feet and an interpreted formation dip error of 0.765 degrees. In the second row where sliding occurred after rotation, the TVD change is 0.236 feet. Using the previously presented equations for curve fitting, the curve fit TVD change is 1.571 feet.

In other words, the curve fit TVD change is the same as in row one. The curve fit TVD change of 1.571 results in an interpreted TVD error of -1.335 feet and an interpreted formation dip error of -0.765 degrees.

Although the errors may cancel each other out relative to the entire well (e.g., an error in one direction may be canceled by an equal error in the opposite direction), the errors in a given direction accumulate and there is more accumulation the longer that a slide occurs in a particular direction.

As illustrated in Table 2, the curve fit TVD change for a particular set of slide/build duration and instantaneous build rate values remains constant regardless of whether sliding occurs before or after rotation even though the TVD change is different based on whether sliding occurs before or after rotation. This difference between the curve fit TVD change and the total TVD change occurs for different values of slide/build duration and instantaneous build rate in Table 1. The curve fit TVD change and the total TVD change may only match in two scenarios. The first is when the slide occurs for the full one hundred feet (e.g., slide/build duration is set to 100 in Table 1), as the borehole shape may be estimated as an arc between the two survey points (one embodiment of which is illustrated in FIG. 14D). The second is when the slide is symmetrically centered on the midpoint between survey points. As illustrated in FIG. 14E, the boreholes 164a-164c of FIGS. 14B-14D may vary significantly for the same curve fit TVD change.

Accordingly, using only information from two measured survey points to estimate the state of the drilling (e.g., orientation of the bit and distance drilled) between the two survey points may result in significant inaccuracies. These inaccuracies may negatively impact drilling efficiency, the ability to objectively identify well plan corrections, the ability to characterize formation position and dip angles, and/or similar issues. Furthermore, problems such as tortuosity may be more difficult to identify and address. Inaccurate TVD information may result in difficulties in following the target layer (e.g., the layer 172A of FIG. 1B), as even seemingly minor variations in inclination (e.g., one half of one degree) may cause the drill bit to exit the target layer.

Referring to FIG. 16, a method 1600 illustrates one embodiment of a process that may be executed by the on-site controller 144 of FIG. 2A and/or another part of the surface steerable system 201. For example, software instructions needed to execute the method 1600 may be stored on a computer readable storage medium of the on-site controller 144 and then executed by the processor 412 that is coupled to the storage medium and is also part of the on-site controller 144.

In the present example, the method 1600 may be used to estimate the position of the drill bit between survey points during straight drilling and/or during a sliding operation. The method 1600 may provide more accurate information on the state of the drilling (e.g., orientation of the bit and distance drilled) than that provided by the minimum curvature method described above.

In step 1602, toolface and other non-survey sensor information is received. The toolface information may be relayed from the toolface periodically, such as at set intervals of between ten and thirty seconds. The non-survey sensor information may include any type of data, such as differential pressure and may be continuous or non-continuous. As the toolface information may be obtained at set intervals and the other non-survey sensor information may be continuous, non-survey sensor information may be obtained between orientation updates. The non-survey sensor information may be averaged (symmetrically or otherwise) to relate the sensor information to the toolface information.

In step **1604**, calculations are performed on the non-survey sensor information to estimate the amount of progress made by the drill bit since the last estimate. For example, the differential pressure may be used to estimate the force on the bit, which may be used with formation information to determine the distance that the bit should have drilled in the current formation layer.

One difficulty in measuring drilling information between survey points is that measurements made at the top of the drill string may not accurately reflect events at the BHA. For example, a ten thousand foot drill string may be viewed as a big spring, and when motion is stopped at the surface, the spring force may continue to increase the length of the drill string and the BHA may make progress in a certain direction. In another example, if a foot of pipe is moved into the hole, the drill string may compress and/or buckle and the bit may move little, if at all.

Accordingly, predictions about the current orientation and progress of the drill bit may vary in accuracy depending on the information on which the predictions are based. For example, rather than exclusively using surface deviation, energy produced by the bit and a combination of differential pressure, MSE, and/or other measurements may be used. In some embodiments, more sensors may be placed downhole to provide more accurate information. Depending on the particular embodiment, calculations may be performed based on sensors at various levels of the drillstring to predict actual progress between surveys. For example, calculations may be used to approximate the fluid pressure to how much force is on the bit. Other calculations may be made to account for drill string compression, tension, and/or buckling.

It is understood that the calculations may differ based on the configuration of the drilling equipment and/or the BHA. For example, if an autodrilling system is used, the drilling rig may have a fixed value for ROP, WOB, DP, and/or other characteristics. Such fixed values may affect the particular calculations used. For example, if DP is fixed, the calculations may not rely on changes in DP as the autodrilling system may attempt to maintain the fixed DP value. In another example, if ROP is fixed, measurements of DP may have a wide range due to the attempt to maintain the fixed ROP value. If an autodrilling system is not used to control drilling functions, more flexibility may be available in the calculations that are used.

In step **1606**, calculations may be performed to obtain an estimate of the BHA's location using the toolface information and the calculated amount of progress. This calculation may be performed in a variety of ways, including the calculation of a vector as a three-dimensional estimate of the drill bit's current location and orientation. The vector progress (e.g., degrees/100 feet) may come from the build rate predictor **1102** of FIG. **11**, and may also include the use of formation information.

In step **1608**, a determination may be made as to whether survey data has been received. If not, the method **1600** may return to step **1602** and calculate another location estimate (e.g., another vector) of the BHA's incremental progression. As these estimates are calculated, an estimated path of the BHA between the two survey points is developed. If survey data has been received, the method **1600** moves to step **1610**, where the survey data is used to update the estimated location. The method **1600** may then return to step **1602** and calculate another location estimate using the new survey data as the baseline for the current estimate.

Accordingly, the survey data may serve as truth data against which the estimates can be measured. This enables the calculations used for the estimates to be refined in conjunction with formation information as more survey point data is

received. For example, if the estimates use a particular drilling speed through the current formation layer and the survey data indicates that the drilling speed is incorrect, future estimates may be calculated based on the revised drilling speed to provide a higher level of accuracy. Furthermore, although not shown in FIG. **16**, it is understood that the survey data may also be used to check the estimated build rate and, if needed, recalibrate the build rate (e.g., the build rate predictor **1102** of FIG. **11**) to correspond to the survey data.

Referring to FIG. **17**, a method **1700** illustrates one embodiment of a process that may be executed by the on-site controller **144** of FIG. **2A** and/or another part of the surface steerable system **201**. For example, software instructions needed to execute the method **1700** may be stored on a computer readable storage medium of the on-site controller **144** and then executed by the processor **412** that is coupled to the storage medium and is also part of the on-site controller **144**. In the present example, the method **1700** illustrates a more detailed example of steps **1602-1606** of FIG. **16**.

In step **1702**, the average differential pressure is determined for a toolface update period (e.g., the length of time between toolface updates). The differential pressure may be acquired or calculated. The toolface update period may vary based on factors such as the speed at which the MWD component is set to run, the priority given to the toolface information in the MWD component, the overall bandwidth available to the MWD component, and/or other factors.

In step **1704**, the average ROP is determined. For example, the differential pressure determined in step **1702** may be used to assist in a database lookup. More specifically, the average ROP for the current formation using the current BHA at the average differential pressure may be acquired from the database.

In step **1706**, the average ROP is applied over the toolface update period to determine the borehole distance increase since the last iteration. For example, if the ROP retrieved from the database indicates that the ROP is fifty feet per hour and the toolface update period is thirty seconds, then the distance increase should be approximately five inches.

In steps **1708** and **1710**, the new toolface sample is used to derive a plane of arc to use in a curvature projection. In the current example, applying observations from the previously described minimum curvature method may be useful when developing a method for estimating borehole position and trajectory from toolface measurements between survey measurements. Certain parameters used in the minimum curvature method may be estimated instead of directly measured.

With additional reference to FIG. **18**, one embodiment of a two-dimensional borehole space **1800** illustrates the minimum curvature path **1801** in the plane of the curvature arc. The space **1800** is illustrated with two measured survey points **1802** (also labeled as "A") and **1804** (also labeled as "C").

As illustrated in FIG. **18**, the angle β can be seen intuitively as the arc angle along which the minimum curvature path is made and the change in trajectory between the two path points. Angle β would normally be calculated from survey trajectory angles using an additional formula. In the context of directional well steering where the angle β is deliberately controlled, it can also be considered an angle of desired or target build. In the case of projecting build in real time, an instantaneous β estimate may be needed. The complexity of such an estimate may vary. For example, a relatively simple approach may use a geometric formula of BHA dimensions. In other examples, more detailed approaches may account for factors from previous and instantaneous rig sensor data, formation data, etc., in order to provide an improved prediction of an instantaneous build rate while drilling. The build rate

predictor **1102** of FIG. **11** may provide a functional component used to perform this task within the surface steerable system **201**.

In the minimum curvature method, ΔMD may be directly obtained from the surface measurement of the difference in drill string lengths between surveys. When accounting for the position of the bit, this method of using surface changes in drill string lengths may be used in a relatively simple approach for an estimate. However, accounting for drill string tension, compression, buckling, and other factors that impact drill string length may provide a better estimate of the current drill bit position as it is drilling new borehole.

In the case of updating borehole trajectory over a given change in borehole depth, survey measurements may be used when available. In such cases, one goal of slide estimation may be to estimate trajectory along the bit path by using toolface history along the intervals ahead of where survey data is available to allow a real time or near real time estimate of bit location.

With additional reference to FIG. **19**, one embodiment of a two-dimensional borehole space **1900** illustrates slide estimation by integration of a single toolface measurement using the minimum curvature path **1801** of FIG. **18**. More specifically, the present example addresses the application of a toolface vector **1902** that is a direct linear projection of an individual toolface. This projection is overlaid against the minimum curvature path **1801** for purposes of illustration. It is understood that while the present example uses a gravity toolface frame of reference, magnetic references can also be used with variations in some formulas described below to account for the use of magnetic references.

In this case, the borehole is assumed to be moving in a straight path along the trajectory AB until encountering a measured toolface. Upon encountering the toolface at point **1806** (B), the toolface is applied directly to the trajectory BC as follows:

$$\alpha_2 = \alpha_1 + \cos TF \times \beta \quad (\text{Equation 5})$$

$$\epsilon_2 = \epsilon_1 + \sin TF \times \beta \quad (\text{Equation 6})$$

where TF is the toolface vector angle presented relative to the gravity "up" vector. The position estimates for the path between AC may be given by:

$$\Delta V = \Delta BD \times \cos \alpha_1 \quad (\text{Equation 7})$$

$$\Delta N = \Delta BD \times [\sin \alpha_1 \times \cos \epsilon_1] \quad (\text{Equation 8})$$

$$\Delta E = \Delta BD \times [\sin \alpha_1 \times \sin \epsilon_1] \quad (\text{Equation 9})$$

The equations 7-9 represent the simple projection of the straight line AB in Cartesian space since the toolface would not be applied until point B. When overlaid on the curvature model, it is evident that this estimate is analogous to the balanced tangential method where the starting and finishing points A and C and the path ABC lie apart from the overlying smooth circular arc.

With additional reference to FIG. **20**, one embodiment of the two-dimensional borehole space **1900** of FIG. **19** is illustrated using the minimum curvature concept to yield a better estimate of actual borehole displacement by modeling the borehole as an arc rather than bending line segments. When framed as a single arc curve displacement **2002**, the projection of the single toolface may appear as illustrated in FIG. **20**.

In this case, the toolface influence on trajectory may be modeled to yield the same tangent trajectory from the toolface build vector **1902** as follows:

$$\alpha_2 = \alpha_1 + \cos TF \times \beta \quad (\text{Equation 10})$$

$$\epsilon_2 = \epsilon_1 + \sin TF \times \beta \quad (\text{Equation 11})$$

After deriving trajectory changes, the minimum curvature method equations are again applicable for determining the positional displacements over the interval as follows:

$$\Delta V = \frac{\Delta BD}{2} [\cos \alpha_1 + \cos \alpha_2] \times RF \quad (\text{Equation 12})$$

$$\Delta N = \frac{\Delta BD}{2} [\sin \alpha_1 \times \cos \epsilon_1 + \sin \alpha_2 \times \cos \epsilon_2] \times RF \quad (\text{Equation 13})$$

$$\Delta E = \frac{\Delta BD}{2} [\sin \alpha_1 \times \sin \epsilon_1 + \sin \alpha_2 \times \sin \epsilon_2] \times RF \quad (\text{Equation 14})$$

In this case, the line path to arc relationship works out to be the same as the minimum curvature RF:

$$RF = \frac{2}{\beta} \tan \frac{\beta}{2} \quad (\text{Equation 15})$$

While the preceding example illustrates slide estimation by integration of a single toolface measurement, it is understood that a range of toolface measurements may be used. As described above, the integration of individual toolface projections may provide a useful method of slide and borehole estimation on a near real time basis. However, like the use of minimum curvature on a smaller scale, this process may be subject to cumulative errors over longer intervals. Accordingly, a range of toolfaces may be used over an interval to address this issue. For example, the range of toolfaces may be used to provide a net effective toolface direction and a net effective β build rate angle may also be estimated. In both cases, the benefit of larger data sets (e.g., toolface histories) may enable the application of more sophisticated statistical methods and filtering techniques. For example, over a path interval, a target toolface may be desired and attempted to be maintained. In practice, the ability to control the toolface over these intervals can be evaluated in statistical metrics, like a circular distribution. These metrics can then be used to refine the effective build rate and toolface direction over the evaluation interval.

Referring again specifically to FIG. **17**, in step **1712**, an updated spatial estimate of the borehole position may be estimated based on the preceding steps. The estimated spatial estimate may be provided to the display **250** of FIG. **2B** (e.g., for display to the driller **310** of FIG. **3**), provided as feedback to the convergence planner **1116** of FIG. **11**, and/or otherwise used.

Referring to FIG. **21**, a method **2100** illustrates one embodiment of a process that may be executed by the on-site controller **144** of FIG. **2A** and/or another part of the surface steerable system **201**. For example, software instructions needed to execute the method **2100** may be stored on a computer readable storage medium of the on-site controller **144** and then executed by the processor **412** that is coupled to the storage medium and is also part of the on-site controller **144**. In the present example, the method **2100** may provide a more detailed example of steps **1602-1606** of FIG. **16**.

In step **2102**, the increase in measured depth is determined for the toolface update period. The increase may be acquired or calculated. For example, the measured depth may be acquired based on a surface measurement of the length of pipe inserted into the borehole between the last toolface update period and the current toolface update period. In other examples, the measured depth may be calculated based on measurements received from downhole sensors.

In step **2104**, the method **2100** may account for deviations in the overall drillstring length due to issues such as compression, tension, and/or buckling. In some embodiments, step **2104** may be omitted and the measured depth determined in step **2102** may be used with accounting for such deviations. Steps **2106**, **2108**, and **2110** may be similar or identical to steps **1708**, **1710**, and **1712**, respectively, with the estimate using the information from steps **2102** and **2104**.

Referring to FIG. **22**, a method **2200** illustrates one embodiment of a process that may be executed by the on-site controller **144** of FIG. **2A** and/or another part of the surface steerable system **201**. For example, software instructions needed to execute the method **2200** may be stored on a computer readable storage medium of the on-site controller **144** and then executed by the processor **412** that is coupled to the storage medium and is also part of the on-site controller **144**. In the present example, the method **2200** may provide a more detailed example of step **2104** of FIG. **21**, although it is understood that the method **2200** may be used with the other methods described herein.

In step **2202**, a hookload measurement is acquired and compared to the static weight of the drill string vertical section excluding the mass of the surface equipment. The static weight of the drill string vertical section excluding the mass of the surface equipment may be determined, for example, from information available from the local database **912** of FIG. **9** and/or regional database **128** of FIG. **1A**.

In step **2204**, the tensile elastic deformation of the drill string components in the vertical section is determined. This determination may use, for example, average cross-section and mechanical properties of the drill string components in the vertical section. The average cross-section and mechanical properties may be determined, for example, from information available from the local database **912** of FIG. **9** and/or regional database **128** of FIG. **1A**.

In step **2206**, a real time or near real time WOB value is determined. For example, the WOB value may be obtained using a downhole sensor. In another example, the WOB value may be approximated using differential pressure and mud motor properties.

In step **2208**, the compressive elastic deformation of the drill string components in the horizontal section of the borehole (if any) is determined. This determination may use, for example, average cross-section and mechanical properties of the drill string components in the vertical section. The average cross-section and mechanical properties may be determined, for example, from information available from the local database **912** of FIG. **9** and/or regional database **128** of FIG. **1A**.

In step **2210**, the total drill string length dynamic offset from the measured depth is determined. This total length dynamic offset accounts for variations between the measured depth and the actual drillstring length due to issues such as compression, tension, and/or buckling in the drillstring.

Referring to FIG. **23** and with additional reference to FIGS. **24** and **25**, a method **2300** illustrates one embodiment of a process that may be executed by the on-site controller **144** of FIG. **2A** and/or another part of the surface steerable system **201**. For example, software instructions needed to execute the method **2300** may be stored on a computer readable storage medium of the on-site controller **144** and then executed by the processor **412** that is coupled to the storage medium and is also part of the on-site controller **144**.

In step **2302**, information is received by the surface steerable system **201**. The information may be any type of information displayed by the display **250**. For purposes of

example, the information may include the orientation and progress estimate from FIG. **16**.

In step **2304**, the GUI (e.g., the circular chart **286**) may be updated with the information representing the orientation and progress of the drill bit. Referring specifically to FIG. **24**, an embodiment of the circular chart **286** of the display **250** (FIG. **2B**) is illustrated with differently positioned circles than those shown in FIG. **2B** and may be used to show the orientation and/or mechanical progress of the drill bit at survey points and/or between surveys. More specifically, FIG. **2B** illustrates a particular positioning of the circles ranging from the largest circle **288** to the smallest circle **289**. FIG. **24** illustrates a different positioning of circles labeled **2402** (the smallest circle), **2404**, **2406**, **2408**, **2410**, **2412**, **2414**, and **2416** (the largest circle). As described with respect to FIG. **2B**, the series of circles may represent a timeline of toolface orientations, with the sizes of the circles indicating the temporal position of each circle. In the present example, the largest circle **2416** is the newest orientation and the smallest circle **2402** is the oldest orientation. The circular chart **286** may provide insight into what is happening in the borehole between surveys (e.g., using variations in size, color, shape, and/or other indicators). As described previously, the lack of knowledge about orientation and progress between surveys may affect various aspects of drilling, as well as the final efficiency of the well.

With additional reference to FIG. **25**, a three-dimensional chart **2500** illustrates vectors **2502**, **2504**, **2506**, **2508**, **2510**, **2512**, **2514**, and **2516** corresponding to circles **2402**, **2404**, **2406**, **2408**, **2410**, **2412**, **2414**, and **2416**, respectively. The vectors **2502**, **2504**, **2506**, **2508**, **2510**, **2512**, **2514**, and **2516** are plotted against a TVD axis **2518** and compass directions indicated by an axis **2520** representing east-west and an axis **2522** representing north-south.

Each vector **2502**, **2504**, **2506**, **2508**, **2510**, **2512**, **2514**, and **2516** provides a three dimensional representation of the orientation of the bit, as well as an amplitude that may be used to represent the mechanical progress (e.g., distance traveled) of the bit and/or one or more other indicators. The amplitude may represent a measurement such as MSE or WOB. In some embodiments, the amplitude may be a combination of measurements and/or may represent the results of calculations based on such measurements. Accordingly, the circular chart **286** may provide a graphical illustration of the vectors **2502**, **2504**, **2506**, **2508**, **2510**, **2512**, **2514**, and **2516**. Although not shown, each estimate of FIG. **16** may result in one of the vectors **2502**, **2504**, **2506**, **2508**, **2510**, **2512**, **2514**, and **2516**, which may be combined to provide an estimated path.

Referring again specifically to step **2304** of FIG. **23**, for example, the circle **2416** may represent the latest toolface orientation information that is used to calculate the vector **2516** of FIG. **25** when the information used to calculate the previous vector **2514** was represented on the circular chart **286** by the circle **2414**. In addition, the slide indicator **292** and/or colored bar **293** may be updated to provide a visual indication of the current status of an ongoing slide.

In step **2306**, a determination may be made as to whether a correction is needed according to the information. For example, if the heading is off by five degrees, the surface steerable system **201** may identify this error. In step **2308**, the GUI may be updated to reflect this error. For example, the error indicator **294** may be updated. In some embodiments, the surface steerable system **201** may correct the heading automatically, while in other embodiments the target toolface pointer **296** may change to indicate an updated correct heading. For example, as the actual toolface veers off course, the GUI may be repeatedly updated to indicate an offsetting correction that should be made in cases where the GUI is used

to notify an individual for manual correction of the toolface. Although continuous or near continuous error calculations may be provided to the driller **310**, the steerable system **201** may plan a solution that uses periodic corrections, rather than instantaneous corrections. Accordingly, the display **250** may provide the recommended corrections to the driller **310** so that controlled, gradual, incremental step changes are made. In cases where the solution has a helical or otherwise continuous correction path, instantaneous or periodic corrections may be displayed to the driller **310**. For example, the incremental step correction may be a function of the tortuosity of the well, amount of friction, and/or the overall depth of the BHA. In another example, in cases where the toolface is automatically controlled (e.g., via Top Drive), the method **2300** may make the correction via instructions to the Top Drive controller, via another controller, or directly.

It will be appreciated by those skilled in the art having the benefit of this disclosure that this system and method for surface steerable drilling provides a way to plan a drilling process and to correct the drilling process when either the process deviates from the plan or the plan is modified. It should be understood that the drawings and detailed description herein are to be regarded in an illustrative rather than a restrictive manner, and are not intended to be limiting to the particular forms and examples disclosed. On the contrary, included are any further modifications, changes, rearrangements, substitutions, alternatives, design choices, and embodiments apparent to those of ordinary skill in the art, without departing from the spirit and scope hereof, as defined by the following claims. Thus, it is intended that the following claims be interpreted to embrace all such further modifications, changes, rearrangements, substitutions, alternatives, design choices, and embodiments.

What is claimed is:

1. A method for drilling, comprising:
 - receiving, by a surface steerable system coupled to a drilling rig, BHA information from a bottom hole assembly (BHA) located in a borehole, wherein the BHA information corresponds to a first location of the BHA with respect to a target drilling path and geological formation drift information;
 - calculating, by the surface steerable system, a first toolface vector to create a convergence path from the first location of the BHA to the target drilling path that does not account for geological formation drift;
 - calculating, by the surface steerable system, an adjustment of the first toolface vector to a second toolface vector to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling in accordance with the second toolface vector;
 - causing, by the surface steerable system, at least one drilling parameter to be modified in order to alter a drilling direction of the BHA based on the calculated second toolface vector;
 - transmitting the at least one drilling parameter to the drilling rig to target the BHA in accordance with the second toolface vector; and
 - drilling the borehole using the BHA in response to the at least one drilling parameter.
2. The method of claim 1, wherein the step of calculating the adjustment further comprises the step of calculating the adjustment of the first toolface vector to create the convergence path toward any point in a two-dimensional relationship from the location of the BHA.

3. The method of claim 1, wherein the step of calculating the adjustment is further responsive to any forces forcing the BHA to miss convergence with the target drilling path.

4. The method of claim 1, wherein the step of calculating the adjustment further comprises calculating a plurality of adjustments of the first toolface vector to a plurality of second toolface vectors, each of the plurality of second toolface vectors having a different cost associated therewith, to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling along each of the second toolface vectors.

5. The method of claim 1, further comprising calculating the location of the BHA with respect to the target drilling path responsive to the received toolface information.

6. The method of claim 1, wherein the step of calculating the adjustment is further responsive to any forces forcing the BHA to miss the target drilling path.

7. The method of claim 1, wherein the step of calculating the adjustment further comprises calculating a plurality of adjustments of the first toolface vector to a plurality of second toolface vectors, each of the plurality of second toolface vectors having a different cost associated therewith, to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling in accordance with each of the second toolface vectors.

8. A surface steerable system for use with a drilling rig comprising:

- a network interface;
- a processor coupled to the network interface; and
- a non-transitory memory coupled to the processor, the memory storing a plurality of instructions for execution by the processor, the plurality of instructions including:
 - instructions for receiving, by the surface steerable system coupled to the drilling rig, BHA information from a bottom hole assembly (BHA) located in a borehole, wherein the BHA information corresponds to a first location of the BHA with respect to a target drilling path and geological formation drift information;
 - instructions for calculating, by the surface steerable system, a first toolface vector from the first location of the BHA to the target drilling path for creating a convergence path from the location of the BHA to the target drilling path that does not account for geological formation drift;
 - instructions for calculating, by the surface steerable system, an adjustment of the first toolface vector to a second toolface vector to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling in accordance with the second toolface vector;
 - instructions for causing, by the surface steerable system, at least one drilling parameter to be modified in order to alter a drilling direction of the BHA based on the calculated second toolface vector; and
 - instructions for transmitting the at least one drilling parameter to the drilling rig to align the BHA in accordance with the second toolface vector.

9. The surface steerable system of claim 8 further comprising instructions for drilling the borehole using the BHA in response to the at least one drilling parameter.

10. The surface steerable system of claim 8, wherein the instructions for calculating an adjustment further comprises

instructions for calculating the adjustment of the first toolface vector to any point in a two-dimensional relationship from the location of the BHA.

11. The surface steerable system of claim 8, wherein the instructions for calculating the adjustment is further responsive to any forces forcing the BHA to miss convergence with the target drilling path.

12. The surface steerable system of claim 8, wherein the instructions for calculating the adjustment further comprises instructions for calculating a plurality of adjustments of the first toolface vector to a plurality of second toolface vectors, each of the plurality of second toolface vectors having a different cost associated therewith, to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling along each of the second toolface vectors.

13. The surface steerable system of claim 8, further comprising instructions for calculating the location of the BHA with respect to the target drilling path responsive to the received toolface information.

14. A drilling system, comprising:

a bottom hole assembly for drilling a borehole through a geological formation responsive to steering control signals;

a drilling rig for driving the bottom hole assembly through a drill string;

a surface steerable system for generating the steering control signals to control the bottom hole assembly, wherein the surface steerable system receives BHA information from the bottom hole assembly (BHA) located in the borehole, the BHA information corresponds to a location of the BHA with respect to a target drilling path and geological formation drift information, the surface steerable system calculates a first toolface vector for creating a convergence path from the location of the BHA to the target drilling path that does not account for geological formation drift, calculates an adjustment of the first toolface vector to a second toolface vector to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling along the second toolface vector, modifies at least one drilling parameter in order to alter a drilling direction of the BHA based on the calculated second toolface vector and transmits the at least one drilling parameter to the drilling rig to target the BHA toward the target drilling path.

15. The drilling system of claim 14, wherein the bottom hole assembly drills the borehole using the BHA in response to the at least one drilling parameter.

16. The drilling system of claim 14, wherein the surface steerable system calculates the adjustment of the first toolface vector toward at any point in a two-dimensional relationship with the location of the BHA.

17. The drilling system of claim 14, wherein the surface steerable system calculates the adjustment responsive to any forces forcing the BHA to miss the convergence with the target path.

18. The drilling system of claim 14, wherein the surface steerable system calculates a plurality of adjustments of the first toolface vector to a plurality of second toolface vectors, each of the plurality of second toolface vectors having a different cost associated therewith, to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling in accordance with each of the second toolface vectors.

19. The drilling system of claim 14, wherein the surface steerable system further calculates the location of the BHA with respect to the target drilling path responsive to the received toolface information.

20. A method for drilling, comprising:

(a) receiving, by a surface steerable system coupled to a drilling rig, BHA information from a bottom hole assembly (BHA) located in a borehole, wherein the BHA information corresponds to a first location of the BHA with respect to a target drilling path and geological formation drift information;

(b) calculating the location of the BHA with respect to the target drilling path responsive to the received toolface information;

(c) calculating, by the surface steerable system, a first toolface vector from the first location of the BHA to the target drilling path for creating a convergence path from the location of the BHA to the target drilling path that does not account for geological formation drift;

(d) calculating, by the surface steerable system, an adjustment of the first toolface vector to a second toolface vector at any point in a three dimensional relationship with the location of the BHA to account for the geological formation drift defined by the geological formation drift information such that the BHA will converge with the target drilling path by drilling in accordance with the second toolface vector;

(e) causing, by the surface steerable system, at least one drilling parameter to be modified in order to alter a drilling direction of the BHA based on the calculated second toolface vector;

(f) transmitting the at least one drilling parameter to the drilling rig to target the BHA along the second toolface vector;

(g) drilling the borehole using the BHA in response to the at least one drilling parameter; and

(h) repeating steps (a)-(g) at least one time until the BHA substantially converges with the target drilling path.

* * * * *