

## Development of EEG-based stress index

*Norizam Sulaiman<sup>1,2</sup>, Mohd Nasir Taib<sup>2</sup>, Sahrim Lias<sup>2</sup>, Zunairah Hj Murat<sup>2</sup>, Siti Armiza Mohd Aris<sup>2</sup>, Mahfuzah Mustafa<sup>2</sup>, Nazre Abdul Rashid<sup>2</sup>*

<sup>1</sup> Faculty of Electrical & Electronics Engineering, Universiti Malaysia Pahang, 26300 Kuantan, Pahang, Malaysia

<sup>2</sup> Faculty of Electrical Engineering, Universiti Teknologi MARA, 40450 Shah Alam, Selangor, Malaysia

### ABSTRACT

This paper presents a non-parametric method to produce stress index using Electroencephalogram (EEG) signals. 180 EEG datasets from healthy subjects were evaluated at two cognitive states; resting state (Eyes Closed) and working state (Eyes Open). In working cognitive state, subjects were asked to answer the Intelligence Quotient (IQ) test questions. The EEG datasets were categorized into 4 groups. Energy Spectral Density (ESD) ratios and Spectral Centroids (SC) from the two tasks were calculated and selected as input features to k-Nearest Neighbor (k-NN) classifier. Shannon's Entropy (SE) was used to detect and quantify the distribution of ESD due to stressors (stress factors). The stress indexes were assigned based on the results of classification, ESD ratios, SC and SE. There were 3 types of stress indexes can be assigned which represent the stress level (low stress, moderate stress and high stress) at classification accuracy of 88.89%. The regression coefficient of the SC of Beta and Alpha was 77%.

### KEYWORDS

Cognitive states; EEG; Energy spectral density; Shannon entropy; Spectral centroids; k-NN; Stress index

**ACKNOWLEDGMENT**

The authors would like to acknowledge the support and contribution given by staffs and researchers in Advanced Signal Processing Research Group, Biomedical Research and Development Laboratory for Human Potential, Nondestructive Biomedical and Pharmaceutical Research Centre and Faculty of Electrical Engineering, Universiti Teknologi MARA (UiTM), Malaysia.