

Mechanical properties of oil palm waste lightweight aggregate concrete with fly ash as fine aggregate replacement

Muhammad Nazrin Akmal Ahmad Zawawi^a, Khairunisa Muthusamy^{ab}, Anwar P.P. Abdul Majeed^c, Rabiu Muazu Musa^e, Ahmed Mokhtar Albshir Budied^d

^aFaculty of Civil Engineering and Earth Resources, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300, Gambang, Malaysia

^bEarth Resources and Sustainability Center, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300, Gambang, Malaysia

^cInnovative Manufacturing, Mechatronics and Sports Laboratory, Faculty of Manufacturing Engineering, Universiti Malaysia Pahang, Pekan Campus, 26600, Pekan, Malaysia

^dFaculty of Civil and Environmental Engineering, Universiti Tun Hussein Onn Malaysia, 86400, Parit Raja, Batu Pahat, Johor, Malaysia

^eCentre for Foundation and Liberal Education, Universiti Malaysia Terengganu, 21030 Kuala Nerus, Terengganu, Malaysia

ABSTRACT

Environmental degradation posed by fly ash (FA) disposal from coal power plants and shell from the oil palm fruit processing trade is non-trivial. The destruction of flora and fauna resulting from the extraction of river sand and granite aggregate from the green hills in an uncontrolled fashion for the production of concrete that is widely used in the construction industry does also require a solution. Introducing oil palm shell (OPS) and fly ash as a mixing ingredient in zero granite lightweight aggregate concrete production is an appealing notion. Success in utilising the available solid waste would reduce dumping of these by-products and consumption of natural aggregates, thus ensuring the preservation of the environment for the future generation. Therefore, this research explores the influence of FA content as sand replacement towards the mechanical and durability properties of agro-based lightweight concrete. Five concrete mixes with FA quantity ranging from 0% to 40% were prepared. Two forms of curing procedure were practised viz. water and indoor air curing. All the mixes were tested for fresh and hardened characteristic as well as sulphate resistance. The test results demonstrated that a substitution of 10% sand with FA yielded better mechanical properties and denser concrete with more resistant to sulphate attack in comparison to the control mix. The utilisation of two industrial waste materials such as FA and OPS may address the issue of paucity of natural resources that is experienced in the construction industry, particularly in the case of natural granite and river sand.

KEYWORDS: Oil palm shell; Fly ash; Fine aggregate replacement; Lightweight aggregate concrete; Mechanical properties

DOI: <https://doi.org/10.1016/j.jobe.2019.100924>

ACKNOWLEDGEMENTS

The authors thank Universiti Malaysia Pahang, Malaysia for the funding provided through RDU190342. Special thanks to Prof. Ir. Dr. Mohd Warid Hussin, Dr. Payam Shafigh and Mrs. Nur Azzimah Zamri for their valuable support and help.