Technical University of Denmark



Challenges in subsurface in situ remediation of chlorinated solvents

Broholm, Mette Martina; Fjordbøge, Annika Sidelmann; Christiansen, Camilla Maymann; Hønning, J.; Hansen, B. H.; Nedergaard, L. W.; Kern, Kristina; Uthuppu, Basil; Jakobsen, Mogens Havsteen; Kjeldsen, Peter; Bjerg, Poul Løgstrup; Ottesen, L.

Published in: In Situ Remediation' 14

Publication date: 2014

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA): Broholm, M. M., Fjordbøge, A. S., Christiansen, C. M., Hønning, J., Hansen, B. H., Nedergaard, L. W., ... Ottesen, L. (2014). Challenges in subsurface in situ remediation of chlorinated solvents. In In Situ Remediation' 14: Book of Abstracts (pp. 26-26)

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



In Situ Remediation Conference '14

2nd - 4th September 2014





BOOK OF ABSTRACTS

Session 1: Urban groundwater contamination and emerging contaminants

Challenges in Urban Hydrogeology – Examples from Berlin1
Groundwater energy and remediation: realising the synergy in the Netherland2
Emerging contaminants in urban groundwater in areas of Doncaster4
Carbon and chlorine isotopes fractionation of chlorinated ethenes during diffusive transport in low permeability
sediments5
Adaptation: A requeriment when assessing and managing emergining contaminants – Perfluoroctane Sulfonate (PFOs)
as a case study
Identification of hotspots of surface water quality on a large pre alpine catchment7
Evidence fo ion exclusion effect during transport of Perfluoroctane Sulfonate (PFOs) in groundwater
Oxidative treatment of clopyralid9
Feasibility of bioscreens for regional VOC-plume in industrial urban area10

Session 2: Novel methods for the assessment of in situ remediation processes and performance

Radon - an effective environmental tracer for subsurface NAPL contamination and in situ remediation assessment11
Removal of diesel hydrocarbons by constructed wetlands – isotopic methods to describe degradation
To what extent can isotopes help substantiate natural attenuation of chlorinated ethenes
Assessment of residual dense non-aquous phase liquid (DNAPL)14
Microbial nitrogen transformation in constructed wetlands treating contaminated groundwater
Implementing and assessing progress of remediation projects using performance based contracts: a fair way of contracting remediation works?
Bench scale remediation efficiency trials for in situ remediation
Improved recirculation system to treat chlorinated solvent contamination and to allow for heat recuperation
Assessment of contaminant natural attenuation in a double aquifer system with a complex industrial history: a regional case study with a combined hydrochemical-multiple isotope approach
Tracer testing to assess light non aquous phase liquid mobility: first application in the UK
The use of smart dual phase extraction and real time data for maximising the return on investment in land contamination remediation
Use of practical tracers for effective design and implementation of in situ remediation technologies
Nitrogen and oxygen isotopes reveal the sources and sinks of inorganic nitrogen in an industrially contaminated
groundwater system

GWSDAT (GroundWater Spatiotemporal Data Analysis Tool)25
Session 3: Permeable reactive barriers, in situ chemical oxidation, enhanced abiotic and thermal treatment technologies
Challenges in subsurface in situ remediation of chlorinated solvents
Integrating sustainable in situ thermal and biological treatment at a fractured bedrock site
Use of electrokinetically-enhanced bioremediation (EK-BIO) and chemical oxidation (EK-ISCO) to remediate source areas in clay and silt
Application of Permeable Reactive Barriers for sustainable remediation of groundwater contaminated by heavy metals and BTEX
A combination of high vacuum extraction and in situ chemical oxidation for the recovery and destruction of chlorinated hydrocarbons
Innovative gas powered in-situ thermal desorption to remediate PCBs in low permeability soils at a facility in Spain 31
Carbo-Iron [®] - one of the studied particles in NanoRem
Remediation of a mixture of organic compounds by electrical resistance heating and pump & treat
In situ thermal technology for a variety of applications
Use of alternative materials in a permeable reactive barrier to treat TCE contaminated groundwater
Thermally enhanced soil vapour extraction at a site contaminated with volatile chlorinated hydrocarbons – from pilot test to full scale remediation
Self-sustaining treatment for active remediation (STAR): overview and in situ and ex situ applications of the technology
High Efficiency In Situ Treatment Technology (HEISTT)
Surfactant enhanced aquifer restoration at a former chemical weapons manufacturing site
Using phytoremediation for priority soil contaminants recovery and subsequent biomass valorisation: an integrated solution from the UK perspective
Carbon dioxide (CO2) supersaturated water injection (SWI) to enhance dense non-aqueous phase chlorinated hydrocarbons mass recovery: first UK field trial

Session 4: Natural attenuation and engineered in situ bioremediation

Permeable reactive interceptors: blocking diffuse nutrient and greenhouse gases losses in key areas of the farming
landscape
Enhanced biodegradation: pilot scale application of nano-sized iron oxides
Bioremediation of groundwater enhanced by microbial interaction with solid state electrodes
Particle size effects on the reduction of sand hydraulic conductivity through biological clogging
A unique innovation to increase rate and performance of in situ bioremediation – Development of a new product 48
In situ enhanced reductive dechlorination the case for optimization via bioaugumentation and/or closed loop groundwater recirculation
Assessment of natural attenuation at a complex site
Metal bioprecipitation in particulate media – effect of particle and flow heterogeneity
Uranium biominerals; enhancing microbial metabolism to control radionuclide migration in groundwater
Electrokinetic injection of nitrate through media with varying permeability contrasts
Session 5: Fate and transport of contaminants in the vadose zone
Optimization of remediation strategies using vadose zone monitoring systems
Vadose zone studies at an industrial contaminated site: the vadose zone monitoring system and cross-hole geophysics
LNAPL transport and fate in the subsurface: Remediation industry best practice guidance
Reactive transport in porous media: verification of the subsurface processes with stable isotope fractionation
Investigating the impact of heterogeneity in streambed sediments on flow, transport and biodegradation processes in the hyporheic zone
Fate and transport of petroleum fuels in fractured rocks: a case study in chalk
Experimental investigation and modeling of fate and transport of nanoparticles in unsaturated sand
Session 6: Sustainability assessments of in situ remediation technologies, including economic aspects and feasibility studies
Innovative remediation techniques: The key to sustainable and green remediation?
Sustainable application of steam enhanced dual phase extraction in the treatment of heavier end and high viscosity hydrocarbons
Sustainability assessment and temporal variations between remediation technologies
A review of the legislative and regulatory basis for sustainable remediation in the European Union and United
Kingdom

The influence of feasibility study in selecting a sustainable approach for the remediation of soils and deep impacted
groundwater at active petrol stations
I+DARTS project: Sustainable in situ remediation for Arsenic polluted sites
Not only Hg: Environmental forensics applied to define remediation targets in an abandoned Hg mining-metallurgical
site
A holistic approach to support sustainable urban renewal through the redevelopment of brownfields (BALANCE 4P)
Remediation techniques for in-situ treatment of contaminated soil and water: extensive pilot tests applied to a large
brownfield area in Belgium71

Session 3

Permeable reactive barriers, in situ chemical oxidation, enhanced abiotic and thermal treatment technologies

Challenges in subsurface in situ remediation of chlorinated solvents

Broholm, M.M.¹, Fjordbøge, A.S.¹, Christiansen, C.M.¹, Hønning, J.¹, Hansen, B.H.¹, Nedergaard, L.W.¹, Kern, K.¹, Uthuppu, B.², Jakobsen, M.H.², Kjeldsen, P.¹, Bjerg, P.L.¹ and Ottesen, L.³

¹Technical University of Denmark, DTU Environment, Miljøvej, DTU B113, DK-2800 Kgs. Lyngby, Denmark, +45 45251475, mmbr@env.dtu.dk

² Technical University of Denmark, DTU Nanotech, Ørsteds Plads, DTU B345E, DK-2800 Kgs. Lyngby, Denmark

³ Technical University of Denmark, DTU BYG, Brovej, DTU B118, DK-2800 Kgs. Lyngby, Denmark

Chlorinated solvent source zones in the subsurface pose a continuous threat to groundwater quality at many sites worldwide. In situ remediation of these sites is particularly challenging in heterogeneous fractured media and where the solvents are present as DNAPL. In situ remediation by chemical as well as biological degradation of chlorinated solvents is a contact sport and requires direct contact between the contaminant and the reactants and/or degrading microorganisms. In fractured geologic media, where contaminants have spread to the low permeability matrix by diffusion, the contact between contaminant and reactant is limited by slow back diffusion of contaminant and indiffusion of reactant if the only access for the reactant is via the high permeability fractures/conduits. Where DNAPL is present the mass distribution is very heterogeneous and the reactive degradation is often limited by dissolution of the DNAPL. Most recent research has been aimed at overcoming these challenges by enhanced and targeted reactant delivery methods. These include a wide range of very diverse technologies such as: enhanced injection methods, including fracturing; electrokinetic enhancement of delivery; ZVI-clay mixing for contact; hydrophobic and/or mobile nano-reactants targeting DNAPL. The complexity of the technologies varies greatly and the current level of implementation ranges from multiple full scale applications to bench scale testing. However, the basic degradation reaction involved is usually well established. Enhanced injection with fracturing increases the access to contaminants in clay/clayey media matrixes by shortening the diffusive distance and with ZVI-clay technology by physically mixing the reactant with the contaminated clay/clayey media. The efficiency of the injection technologies has been very variable and rather unpredictable in heterogeneous geologic media, hence, further developments are needed. The novel techniques involving electrokinetics induce migration of primarily ionic species/reactants independent of hydraulic permeability differences, hence transporting the reactant into the contaminated matrix and may be applicable for limestone/bedrock as well as clayey media. Only laboratory studies of electrokinetic enhancement have yet been published, and there is a need for thorough pilot scale studies and supporting laboratory studies. Injectable nano-particles with an affinity for DNAPL surfaces (or phases) may overcome dissolution limitations and provide direct contact with contaminant, limiting reactions with other reactive sites in the subsurface. Challenges lie in obtaining stability and mobility in water, affinity for DNAPL and at the same time maintain reactivity with contaminants. Upscaling to production for pilot studies without loss of efficiency is not trivial. In conclusion there continues to be a need for research and development and in particular for well documented pilot/full scale field studies.



www.theadvocateproject.eu www.claire.co.uk

This conference is organised within the framework of the Marie Curie Initial Training Network ADVOCATE - Advancing sustainable in situ remediation for contaminated land and groundwater, funded by the European Commission, Marie Curie Actions Project No. 265063