

EUROPEAN ORGANISATION FOR NUCLEAR RESEARCH

CERN - PS DIVISION

CERN/PS 2000-058 (PP)
CERN-NUFACT 42

EXOTIC ION-BEAMS TARGETS AND SOURCES

J.A. Lettry
ISOLDE

Abstract

Exotic beams of short-lived radioisotopes are produced in nuclear reactions such as thermal neutron induced fission, target or projectile fragmentation and fusion reactions. For a given radioactive ion beams (RIB), different production mode are in competition. For each of them the cross section, the intensity of the projectile beam and the target thickness define an upper production rate. The final yield relies on the optimisation of the ion-source, which shall be fast and highly efficient in view of the limited production cross section and on minimum diffusion time out of the target matrix or fragment catcher to reduce decay losses. Eventually, either chemical or isobaric selectivity is needed to confine unwanted elements near to the production site.

These constraints are discussed for pulsed or dc driven RIB facilities and the solutions to some of the technical challenges will be illustrated by examples of actually scarcely produced near drip line elements.

Presented at the XXth International Linac Conference,
21-25 August 2000, Monterey, California, USA

Geneva, Switzerland

18 August 2000

EXOTIC ION-BEAMS TARGETS AND SOURCES

J.A. Lettry, CERN-ISOLDE, Geneva, Switzerland

Abstract

Exotic beams of short-lived radioisotopes are produced in nuclear reactions such as thermal neutron induced fission, target or projectile fragmentation and fusion reactions. For a given radioactive ion beams (RIB), different production mode are in competition. For each of them the cross section, the intensity of the projectile beam and the target thickness define an upper production rate. The final yield relies on the optimisation of the ion-source, which shall be fast and highly efficient in view of the limited production cross section and on minimum diffusion time out of the target matrix or fragment catcher to reduce decay losses. Eventually, either chemical or isobaric selectivity is needed to confine unwanted elements near to the production site.

These constraints are discussed for pulsed or dc driven RIB facilities and the solutions to some of the technical challenges will be illustrated by examples of actually scarcely produced near drip line elements.

1 INTRODUCTION

Over the last 30 years, Isotope On Line (ISOL) and in-flight fragment separators based RIB facilities [1-4] played a major role in very different research domains such as astrophysics atomic physics, nuclear physics, solid state physics and nuclear medicine.

Nuclei far from stability (so called exotic nuclei) are produced in spallation, fragmentation, fission and fusion nuclear reaction between the primary beam and the target nucleus. RIB facilities consist of four parts: The *driver* producing a primary beam of particles and directing them to the *target* where the nuclear reaction takes place eventually followed by the *ion source* and the *separator* which ionise respectively select the isotopes and direct them to the physics experiment. The drivers at the origin of the nuclear reaction are based on light or heavy ion accelerators and on various actinides fission processes. The fission of uranium produced via high energy protons or thermal neutron is on the way to be completed by fast neutrons induced fission [5] and even photofission [6].

Actual RIB facilities can be ordered according to the typical time span between the nuclear reaction and the delivery of the radioisotope to the experimental set-up in three complementary categories: the μ s-class regrouping the in-flight fragment separators, the ms-class where fragments are caught and thermalized in a noble gas beam stopper and the s-class where fragments or fission products are stopped or produced at rest in solids, diffuse out of the target material and eventually get ionised in the

ion source. Ion sources will be described in section 2 and targets in section 3.

2 ION-SOURCES ALONG MENDELEEV'S TABLE

RIB ion sources shall be *fast* to limit the decay losses of short lived isotopes, *efficient* as the available amount is limited by the production cross section and *chemically selective* to reduce isobar contaminants and eventually to confine unwanted species as close as possible to the production area. In this section, a selection of single charge ion sources are briefly presented according to their chemical properties, all of them were designed to work close to the high radiation field target area.

2.1 Alkalis, alkaline earth and rare earth

A common feature to Alkalis, alkaline earth and rare earth elements is their low ionisation potential (between 3.9 and 6 eV). This property, shared by some diatomic molecules, allows a very efficient ionisation on a high temperature metallic surface. The ionisation of an atom bouncing from a high temperature metallic surface was observed for the first time in 1923. Its efficiency is described as a function of the difference between the energy required to remove an electron from its surface (its work function) and the ionisation potential of the atom. Since then, high temperature cavities were designed to optimise the ion fraction caught by the extraction field. A commonly used geometry consists of a simple refractory metal (Nb, Ta, W, Re) tube heated by a dc-current.

2.2 Metals

Plasma ion sources are based on a controlled electron beam of a few hundred eV used to generate a plasma sustained with a low pressure of noble gas in a high temperature cavity under a low magnetic field. The Forced Electron Beam Arc Discharge (FEBIAD) [6-7] efficiently ionise all elements which do not have strong chemical reaction with the ion source materials. Their intrinsic low chemical selectivity is improved via thermo-chromatographic methods. The material and the temperature of the transfer line between the target and the ion source is chosen accordingly to the elements to be condensed.

The Resonant Ionisation Laser Ion Source (RILIS) [8,9] is based on the stepwise excitation of 2 or 3 atomic transitions leading either to auto-ionising states or directly to the continuum. The interaction between the laser beams and the atoms take place in a high temperature metallic

cavity. While drifting towards the extraction field, the RILIS ions are confined by a radial potential well originating from the electron layer at the surface of the hot metal. The RILIS elegantly solves the selectivity issue with a noticeable exception for the alkalis ionised in the high temperature cavity. It has proven records for the efficient production of radioisotopes of 19 elements. In principle a proper ionisation scheme can be developed for 75% of the elements [10]. The RILIS ions are ionised within the few ns laser pulse, the different path length to drift towards the extraction leads to a RILIS ion bunch of typically a few tens of μs duration. The micro gating technique consists in deflecting the surface ionised ions from the experimental set-up to a beam dump between two RILIS ion bunches. The selectivity towards surface ionised isobars can be increased up to a factor of 10 via micro gating [11]. A very elegant solution to the selective ionisation of refractory elements is the Ion Guide Laser Ion Source (IGLIS) [12] at Leuven: Recoiling refractory metals fragments are stopped in a noble gas catcher, thermalized and neutralized and eventually ionised via resonant laser ionization.

2.3 Halogens

Halogens do have high electron affinities, therefore, an halogen atom hitting a low work function material has a tendency to pick an electron from the surface and to be released as a negative ion. The LaB₆ ISOLDE surface ion source [13] efficiently produced negatively charged beam of chlorine, bromine, iodine and astatine. Due to its reactivity, fluorine beams could not be produced this way but rather as a molecular side band (AlF⁺) in a plasma ion source [14] A dedicated Cs sputter ion sources was tested off line for fluorine production Alton [15].

2.4 Gaseous elements

Despite their high ionisation potentials, noble gases, nitrogen and oxygen are very efficiently ionised in ECR ion sources. Beside the standard high charge state ECR, a new generation of ECR designed for single charge ions was developed [16]. Compact, equipped with permanent magnets and fed with the commercially 2.45MHz RF generators. They yield efficiencies of the order of 90% for 1⁺ argon.

FEBIAD ion sources equipped with a cooled Cu-transfer line are very selective, the only contaminants are the higher charge state of the heavier noble gases. Their efficiency is of the order of 50% for the heavier ones drops down to typically 1% for the lightest.

3 SELECTED DRIVERS, TARGETS AND ION BEAMS

This section is dedicated to the presentation of examples of target and drivers dedicated to the production of radioisotopes belonging to specific regions of the chart

of nuclides. As more powerful drivers are planned, targets are designed to cope with higher power densities with the challenge to dissipate the deposited heat in a target that must be kept at high temperature for maximum diffusion speed. In the presented cases, the radioisotopes are stopped or produced at rest. The release of radioisotopes from thick targets is governed by diffusion out of the target matrix, folded with the usually faster effusion from the surface of the target material to the ion source [17]. A release function gives the probability density for an atom produced at $t=0$ to be released at a given time [18]. It is the normalised and decay-losses corrected equivalent to the time dependence of the radioisotope current. The sharp rise of the first few ms is usually associated to the effusion process while the slower tail gives information on the diffusion process. As release curves are often measured with pulsed beams, the induced temperature shock affects the release during the heat transport transient time of typically 1s. The last part of the release function being representative for the diffusion process.

Neutron rich isotopes are mainly produced in the fission of actinides to benefit from the neutron excess. Fission can be induced by high-energy charged ions, thermal or fast neutrons and even photons [19]. The distribution of the fission fragments in the chart of nuclides depends on the energy of the primary particle, the distribution is widest for high-energy primary particles. In this last case, fragmentation and spallation reactions do contribute to the production of light respectively heavy radioisotopes on top of the fission products. Among the highest cross-sections, the fission of ²³⁵U via thermal neutrons is characterised by its well-known double peak. On the other side of the valley of stability, isotopes close to the proton drip line have to be produced by spallation of a slightly heavier element or by fragmentation.

3.1 A target for high flux reactor

Thermal neutrons induced fission is thank to its very high cross section a very powerful tool for the production of fission fragments as demonstrated for decades by the OSIRIS facility in Studsvik. The next generation of these facilities was proposed at Grenoble (PIAFE project at the ILL high flux reactor [20]) and Munich (Munich Accelerator for Fission Fragments MAFF [21]) currently under construction. One of the objectives of MAFF is the production of superheavy elements via fusion reaction between two different neutron rich fission products. This would be realised by implanting on line neutron rich fission fragments on a substrate to constantly regenerate a thin very neutron rich target and, simultaneously, accelerate other fission fragments at high energy onto this target [22]. The ²³⁵U primary target consists of 1g uranium carbide in a porous graphite matrix. It is confined in a rhenium vessel directly connected to the ion source (surface plasma or laser). The lifetime of the target and ion source system has to be comparable to the cycle of the

reactor of 52 days. One of the preferred ion sources to match this challenge is the RILIS as all complex parts are out of the highly active region up to a simple high temperature metallic cavity.

The neutron flux of maximum 3×10^{11} n/cm²s can be adjusted via the position of the target at the edge of the reactor. The fission power heats up the target to a nominal temperature above 2000°C. A higher fission rate density can be achieved than with charged particles induced fission schemes where energy losses contribute to the heating. The expected fission rate is 10^{14} 1/s.

3.2 Dc vs. pulsed proton beams drivers

The ISOLDE facility driver was a 600MeV synchrocyclotron (SC) for 2 decades. Following the move of the facility, all targets developed during this period were tested with low frequency proton pulses at CERN's Proton Synchrotron Booster (PSB) [23,24]. Similar targets are currently very successful at TRIUMF [25] with one order of magnitude higher power. The effects of the 3 orders of magnitude energy density increase between the almost continuous SC and the pulsed PSB proton beam are briefly described in this section.

Molten metal targets: The thermal shock generated pressure wave during the 2.4μs proton pulse was sufficient to break the welds of the target container, to generate vapour pressure bursts and to splash the molten metal into the ion-source [26]. Corrosion and even cavitation like attacks were observed on a molten lead Ta-container. The transfer lines between the containers and the ion-sources were equipped with temperature controlled baffle systems also designed to condense the excess of vapours. This intermediate temperature control allows in some cases to reach higher temperature. The power of a 1GeV proton beam at an average current of 1μA heats up a lead target unit up to 800°C and sets the power dissipation limit of the current design, this can be improved via dedicated cooling.

Metal foil targets: The rapid release from metal targets benefits from the pulsed production of the radioisotopes, which allow additional noise suppression by only collecting data after the proton pulses according to the release and to the specific half life. On the other hand, the temperature increase following the proton pulse can reach up to 600°C and occurs on metals which are often beyond their elasticity domain. This lead to the destruction of the target container and rapid sintering of the target material. Spatial defocalisation of the proton beam gives us a control over the maximum temperature increase and measurements shows the expected increase of the rapidly released isotopes.

The synchronous production of isotopes with half-lives of few ms duration reduces dramatically the data acquisition time fraction. As an example, for ¹⁴Be (4.35ms) the background is reduced by a factor 200 for a more than 12 half lives data acquisition.

The pulsed generation of radioisotopes in a target without or with a very reduced thermal shock is possible for fission products if the fission is generated with pulsed neutrons. A uranium carbide target placed in the vicinity of a tantalum cylinder bombarded with high energy pulsed protons corresponds to this description and is presently under test at ISOLDE. The principle of the conversion has been demonstrated at Orsay (section 3.3), Gatchina (ISIS) [27] and of course in spallation neutron sources.

3.3 Molten Uranium target

Fast neutrons resulting from the interaction of deuterium on a light converter (Be, C, liquid Li) do induce ²³⁸U fission. One of the aims of the first proposal by Nolen [5] was to separate the charged particle energy losses from the high temperature uranium target. This concept was partly tested within the PARRNe project [28,29]. The primary target called neutron converter were built out of low Z material but as demonstrated by the spallation sources high Z materials including uranium can be envisaged. The RIB production of uranium carbide and molten uranium targets coupled to graphite and beryllium converters were compared at deuteron energies between 15 and 150MeV. The net gain of neutron production using Be converters was reduced by geometrical effects as the C-converter can be placed closer to the high temperature target. While the fast release from UC₂ matrix is well-known, the first measurement from molten uranium confirmed the usually slow (tens of seconds) release behaviour common to all molten metal targets. The challenging container for molten uranium at high temperature was made out of a sintered yttria and kept 200g uranium at temperatures up to 1700°C [30] for a few days. Post observations showed no damages but a blackening of the yttria (equivalent to oxygen losses).

These tests will be used as a benchmark for the simulation codes necessary to optimise the numerous parameters such as deuteron energy, converter and target thickness and geometry. With this technique applied in SPIRAL-II, a target of typically 3kg ²³⁸U would be necessary to achieve of the order of 10^{14} fissions/s.

3.4 Very thin Ta-foil target for neutron halo nuclides)

The half-life of the neutron halo nuclides ¹¹Li (8.7ms) and ¹⁴Be (4.34ms) are comparable to the typical effusion time from a standard tantalum foil targets. Their diffusion time constants is even orders of magnitude larger. Therefore, the target geometry and the diffusion thickness must be optimised to reduce the four orders of magnitude large decay losses. Instead of the 130 g/cm² 20μm Ta-foils contained in a 20 cm long 2 cm diameter oven only 10 g/cm² 2μm Ta-foils were deposited in a u-shaped support and oriented along the beam axis inside of the above mentioned oven or target container [31]. This container was connected to a surface ion-source consisting of a

3mm-diameter 30mm long tungsten cavity. While lithium was ionised on the 2400°C surface, the RILIS laser beams ionised the beryllium isotopes. The specific yield from ^{11}Li increased by a factor of more than 20 and its absolute yield reached 7000 $1/\mu\text{C}$ (1.4GeV protons). The best obtained yield of ^{12}Be (23.6ms) increased by an order of magnitude and doubled for ^{14}Be . This successful example demonstrates that a target eventually has to be designed for one or a few specific isotopes.

3.5 Radiation cooled high power target

Radiation cooled target or very refractory materials were first proposed by Bennet et al. [32] within the RIST project. The RIST target consists of a succession of diffusion bounded 25 μm Ta-spacers and discs. A hole of decreasing diameter is cut in the centre to distribute the power along the axis. The target is designed to work with 100 μA pulsed beam of 800MeV protons. The total electrical power that could be dissipated by radiation at 2400°C in an off-line test reached 30kW.

The heavy ion beam from GANIL foreseen for the SPIRAL project has a total power of 6kW. The short range of heavy ions in materials sets stringent constraints on the target/catcher material. The shape of the graphite target developed for noble gases isotopes is a succession of increasing diameter 0.5mm thick disks hold on a central axis which can also be used as heating resistor. The heavy ion beam is circled around the axis. The target is contained in a water-cooled box and the gaps between two adjacent disks were designed to increase the heat radiation surface (2500°C). In addition they allow a rapid effusion towards the ECR ion source and the micrometer size graphite structure is optimum for fast diffusion. During the test of the very first prototype, the sublimation temperature of graphite was reached and resulted in a hole located at the Bragg peak. A heat transfer code including heat radiation was developed to define the final geometry of a target which was then able to dissipate the power.

A complementary approach based on conductive cooling was tested at TRIUMF, a water-cooled set of diffusion bounded disks of molybdenum representing a medium temperature target were submitted to a 100 μA of 500MeV protons. The heat transfer calculations showed small discrepancies vs. the recorded temperatures [33].

3.6 Target for alkali suppression

The on line production of neutron rich copper isotopes is very efficient with high-energy protons impacting on a thorium (or uranium) target. Unfortunately, the yield of rubidium isobars is four orders of magnitude higher. A target unit was therefore designed to purify the copper signal from its rubidium isobars. The micro-gating technique around the typically 30 μs laser ionised Cu bunches contributes to the selectivity by a factor of 4. Thank to its low ionisation potential, rubidium isotopes will be in a positive charge state already inside the target

oven. The dc heated high temperature tantalum oven generates an electrical field, which directs rubidium ions opposite to the RILIS cavity. At this point, a small aperture extraction system collect them. The selectivity gain measured on a Ta-foil target is of 5 for rubidium and caesium, it rapidly drops for elements with higher ionisation potentials. The last but not least way to reduce the production of rubidium is to generate the fission via fast neutrons produced in a converter placed close to the target oven. The expected cross section ratios contribute to the selectivity up to an order of magnitude. These suppression systems are directly reinforced by the resolving power of the mass separator.

3.7 Ion beam manipulation

The characteristics of radioactive ion beams such as emittance, energy spread or charge states sometimes have to be matched to the physics set-up or to the acceptance of the following beam optics element. For this purposes and increasing number of facilities makes use of ion traps and gas cells. An ion traps acting as buncher and used to improve the beam emittance is installed in the REX-ISOLDE LINAC [34] which requires a q/m larger than 0.25. Its charge state breeding relies on the trapping and bunching of the ions prior to the injection in an Electron Beam Ion Source (EBIS). In this trap, up to 10^7 ions are accumulated and bunched and the emittance is reduced by one order of magnitude to match the acceptance and the time structure of the EBIS. At the Ion Guide Isotope Separator Leuven (IGISOL) facility, of the laser ionised refractory metal fragments are transported via a noble gas flow. The skimmer electrode used to extract the singly charge fragments induced an energy straggling which vanished when the skimmer was replaced by a Sextupole Ion Guide (SPIG).

The Rare Isotope Separator (RIA) includes beside the standard ISOL an in-flight separation a new production schemes. In this variant, the fragments (possibly produced on a liquid Li target) will be stopped in a noble gas cell where, after thermalization, the singly charge ions are transported by weak electrical fields towards the ion beam optics. Preliminary tests showed that the release time from such a gas cell is well below 1s [35] depending on the thickness of the gas cell (in this case length \times pressure). This part of the RIA project aim at combining the ion beam quality from an ISOL technique and release delays approaching those of a fragment separator.

3.8 Conclusion

The standard complementary methods used in RIB facilities are now completed with an intermediate one, namely the stopping of fragments in gas cells included in the RIA project. The increase of the total beam power available at TRIUMF or expected for the SIRIUS project

has triggered a large effort in the development of high power targets for high-energy proton driver schemes. The targets developed for moderate intensities or dc. Beams could be adapted for beam intensities up to 20 μ A and for the actual pulsed drivers. The limitation of the maximum power, which can be deposited in a small target volume, can partially be overcome for the production of fission products by the introduction of a converter producing fast neutrons. However, fission in reactor based facilities like MAFF sets a challenging goal of 10¹⁴ fissions/s.

A large R&D effort from the whole RIB community is visible witnessed the RIA project and by the creation of study groups on target, traps and ion-sources triggered by the EURISOL facility project. Obviously, with the expected intensities, not only the target area but in a less critical manner the beam transport, traps and experimental set-ups will have to be handled in regard of their contamination in handling the very intense beams foreseeable in a near future.

REFERENCES

- [1] H. Grunder, Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [2] B. Jonson, Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [3] I. Tanihata, ENAM 98 AIP conf. proc. **455**, 943 (1998).
- [4] H. Ravn, Radioactive ion-beam projects based on the two accelerator or ISOL principle, Phil. Trans. R. Soc. Lond. A **365**, 1955 (1998).
- [5] J. Nolen, RNB-3 conf. Proc. D. Morissey Ed., Editions Frontières, Gif sur Yvette. 111, (1993).
- [6] R. Kirchner and E. Roeckl, Nucl. Instrum. and Meth. **133**, 187 (1976).
- [7] R. Kirchner, K. H. Burkard, W. Hüller and O. Klepper, Nucl. Instrum. and Meth. **186**, 295 (1981).
- [8] V.I. Mishin, V.N. Fedoseyev, H.J Kluge, V.S. Letokhov, H.L. Ravn, F. Scheerer, S. Sundell, Y. Shirakabe, O. Tengblad. Nucl. Instrum. and Meth. **B 73**, 550 (1993).
- [9] A. E. Barzakh, V.P. Denisov, D.V. Fedorov, S. Yu. Orlov, M.D. Seliverstov, Nucl. instrum. and meth. **B 126**, 85 (1997).
- [10] U. Koester et al., Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [11] J. Lettry, R. Catherall, G.J. Focker, O. C. Jonsson, E. Kugler, H. Ravn, C. Tamburella, V.N. Fedoseyev, V.I. Mishin., G. Huber, V. Sebastian, M. Koizumi, U. Köster, Rev. Sci Instrum., **69**, 761 (1997).
- [12] Y. Kudriavtsev, A. Andrzejewski, N. Bijmens, S. Franchoo, J. Gentsens, M. Huyse, A. Piechaczek, J. Sezerypo, I. Reusen, P. Van Duppen, P. Van den Bergh, L. Vermeeren, J. Wauters and A. Wöhr, Nucl. Instrum. and Meth. **B 114**, 350 (1996).
- [13] B. Vosicki, T. Björnstad, L. Carraz, J. Heinemeier and H. Ravn, Nucl instrum. and meth. **186**, 307 (1981).
- [14] R. Welton et al., Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [15] G. Atlton, private communication.
- [16] A. Villari et al., Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [17] J.R.R. Bennett, Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [18] J. Lettry, R. Catherall, P. Drumm, P. Van Duppen, A. Evensen, G. Focker, A. Jokinen, O.C. Jonsson, E. Kugler, H.L. Ravn, Nucl. Instrum. and Meth. **B 126** (1997) 130.
- [19] Y. Oganessian, Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [20] PIAFE project report, ed. By U. Köster and J.-A. Pinston, ISN Grenoble, 1998.
- [21] D. Habs et al., Nucl. Phys. A616 (1997) 39c [MAFF – Munich Accelerator for Fission Fragments, Physics case and technical description, ed. By D. Habs et al. 1999, <http://www.ha.physik.uni-muenchen.de/maff/>]
- [22] U. Köster, AIP conf. Proc. 475, 269, (1998).
- [23] Move of ISOLDE - Implications for the PS BOOSTER, CERN PS/BI 89-7.
- [24] ISOLDE at the PS BOOSTER, CERN PS/92-46 (PA).
- [25] R. Laxdal, R. Baartman, P. Bricault, M. Dombiski, G. Dutto, A. Mitra, R. Poirier, P. Schmor, G. Stanford, A. Facco, These proceedings.
- [26] J. Lettry, R. Catherall, G. Cyvoct, P. Drumm, A.H.M. Evensen, M. Lindroos, O.C. Jonsson, E. Kugler, J. Obert, J.C. Putaux, H. Ravn, J. Sauvage, K. Schindl, E. Wildner, and the ISOLDE Collaboration, Nucl. Instrum. and Meth. **B 126** 171, (1997).
- [27] J. Nolen and V. Panteleev, communication to the TWIST workshop GANIL Caen 2000.
- [28] S. Kandri-Rody et al., Nucl. Instrum. and Meth. **B 160**, 1, (2000)
- [29] F. Clapier et al., Phys. Rev. Special topics, Accelerators and Beams, 1, 013501 (1988).
- [30] O. Bajeat, communication to the TWIST workshop GANIL Caen 2000.
- [31] J.R.R. Bennett, U. Bergmann, P. Drumm, J. Lettry, T. Nilsson, R. Catherall, O. Jonsson, H. Simon, Proceedings of the RNB-5 conf. Divonne 2000 to be published in NIM]
- [32] J. R. J. Bennett, Nucl. Instrum. and Meth. **B 126**, 105 (1997).
- [33] W. Talbert et al., Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.
- [34] O. Kester et al., these proceedings.
- [35] G. Savard et al., Proc. of the RNB-5 conf. Divonne 2000 to be published in Nucl. Phys. A.