

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Mechanical & Materials Engineering Faculty
Publications

Mechanical & Materials Engineering,
Department of

11-25-2014

Modular and Cooperative Medical Devices and Related Systems and Methods

Shane M. Farritor
Lincoln, NE, sfarritor@unl.edu

Mark Rentschler
Boulder, CO

Amy Lehman
York, NE, alehman2@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/mechengfacpub>



Part of the [Mechanics of Materials Commons](#), [Nanoscience and Nanotechnology Commons](#), [Other Engineering Science and Materials Commons](#), and the [Other Mechanical Engineering Commons](#)

Farritor, Shane M.; Rentschler, Mark; and Lehman, Amy, "Modular and Cooperative Medical Devices and Related Systems and Methods" (2014). *Mechanical & Materials Engineering Faculty Publications*. 425.
<https://digitalcommons.unl.edu/mechengfacpub/425>

This Article is brought to you for free and open access by the Mechanical & Materials Engineering, Department of at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Mechanical & Materials Engineering Faculty Publications by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.



US008894633B2

(12) **United States Patent**
Farritor et al.

(10) **Patent No.:** **US 8,894,633 B2**
(45) **Date of Patent:** ***Nov. 25, 2014**

(54) **MODULAR AND COOPERATIVE MEDICAL DEVICES AND RELATED SYSTEMS AND METHODS**

(75) Inventors: **Shane M. Farritor**, Lincoln, NE (US);
Mark Rentschler, Boulder, CO (US);
Amy Lehman, York, NE (US)

(73) Assignee: **Board of Regents of the University of Nebraska**, Lincoln, NE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 403 days.

This patent is subject to a terminal disclaimer.

4,246,661 A	1/1981	Pinson
4,258,716 A	3/1981	Sutherland
4,278,077 A	7/1981	Mizumoto
4,538,594 A	9/1985	Boebel et al.
4,568,311 A	2/1986	Miyaki
4,623,183 A	11/1986	Amori
4,736,645 A	4/1988	Zimmer
4,771,652 A	9/1988	Zimmer
4,852,391 A	8/1989	Ruch et al.
4,896,015 A	1/1990	Taboada et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP	2286756 A1	2/2011
JP	2004144533	5/1990

(Continued)

(21) Appl. No.: **12/971,917**

(22) Filed: **Dec. 17, 2010**

(65) **Prior Publication Data**

US 2011/0237890 A1 Sep. 29, 2011

Related U.S. Application Data

(60) Provisional application No. 61/287,628, filed on Dec. 17, 2009.

(51) **Int. Cl.**
A61B 17/00 (2006.01)

(52) **U.S. Cl.**
USPC **606/1**

(58) **Field of Classification Search**
CPC A61B 19/22
USPC 606/1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,870,264 A	3/1975	Robinson
3,989,952 A	11/1976	Hohmann

OTHER PUBLICATIONS

Abbott et al., "Design of an Endoluminal NOTES Robotic System," from the Proceedings of the 2007 IEEE/RSJ Int'l Conf. on Intelligent Robot Systems, San Diego, CA, Oct. 29-Nov. 2, 2007, pp. 410-416.

(Continued)

Primary Examiner — Gary Jackson


Assistant Examiner — John R Downey

(74) *Attorney, Agent, or Firm* — Davis, Brown, Koehn, Shors & Roberts, P.C.; Sean D. Solberg

(57) **ABSTRACT**

The various embodiments disclosed herein relate to modular medical devices, including various devices with detachable modular components and various devices with pivotally attached modular components. Additional embodiments relate to procedures in which various of the devices are used cooperatively. Certain embodiments of the medical devices are robotic in vivo devices.

16 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,897,014 A	1/1990	Tietze	6,132,441 A	10/2000	Grace
4,922,755 A	5/1990	Oshiro et al.	6,156,006 A	12/2000	Brosens et al.
4,990,050 A	2/1991	Tsuge et al.	6,159,146 A	12/2000	El Gazayerli
5,019,968 A	5/1991	Wang et al.	6,162,171 A	12/2000	Ng et al.
5,108,140 A	4/1992	Bartholet	D438,617 S	3/2001	Cooper et al.
5,172,639 A	12/1992	Wiesman et al.	6,206,903 B1	3/2001	Ramans
5,176,649 A	1/1993	Wakabayashi	D441,076 S	4/2001	Cooper et al.
5,178,032 A	1/1993	Zona et al.	6,223,100 B1	4/2001	Green
5,187,032 A	2/1993	Sasaki et al.	D441,862 S	5/2001	Cooper et al.
5,187,796 A	2/1993	Wang et al.	6,238,415 B1	5/2001	Sepetka et al.
5,195,388 A	3/1993	Zona et al.	6,240,312 B1	5/2001	Alfano et al.
5,201,325 A	4/1993	McEwen et al.	6,241,730 B1	6/2001	Alby
5,217,003 A	6/1993	Wilk	6,244,809 B1	6/2001	Wang et al.
5,263,382 A	11/1993	Brooks et al.	6,246,200 B1	6/2001	Blumenkranz et al.
5,271,384 A	12/1993	McEwen et al.	D444,555 S	7/2001	Cooper et al.
5,284,096 A	2/1994	Pelrine et al.	6,286,514 B1	9/2001	Lemelson
5,297,443 A	3/1994	Wentz	6,292,678 B1	9/2001	Hall et al.
5,297,536 A	3/1994	Wilk	6,293,282 B1	9/2001	Lemelson
5,304,899 A	4/1994	Sasaki et al.	6,296,635 B1	10/2001	Smith et al.
5,307,447 A	4/1994	Asano et al.	6,309,397 B1	10/2001	Julian et al.
5,353,807 A	10/1994	DeMarco	6,309,403 B1	10/2001	Minoret et al.
5,363,935 A	11/1994	Schempf et al.	6,312,435 B1	11/2001	Wallace et al.
5,382,885 A	1/1995	Salcudean et al.	6,321,106 B1	11/2001	Lemelson
5,388,528 A	2/1995	Pelrine et al.	6,327,492 B1	12/2001	Lemelson
5,436,542 A	7/1995	Petelin et al.	6,331,181 B1	12/2001	Tierney et al.
5,441,494 A	8/1995	Ortiz	6,346,072 B1	2/2002	Cooper
5,458,131 A	10/1995	Wilk	6,352,503 B1	3/2002	Matsui et al.
5,458,583 A	10/1995	McNeely et al.	6,364,888 B1	4/2002	Niemeyer et al.
5,458,598 A	10/1995	Feinberg et al.	6,371,952 B1	4/2002	Madhani et al.
5,471,515 A	11/1995	Fossum et al.	6,394,998 B1	5/2002	Wallace et al.
5,515,478 A	5/1996	Wang	6,398,726 B1	6/2002	Ramans et al.
5,524,180 A	6/1996	Wang et al.	6,400,980 B1	6/2002	Lemelson
5,553,198 A	9/1996	Wang et al.	6,408,224 B1	6/2002	Okamoto et al.
5,562,448 A	10/1996	Mushabac	6,424,885 B1	7/2002	Niemeyer et al.
5,588,442 A	12/1996	Scovil et al.	6,432,112 B2	8/2002	Brock et al.
5,620,417 A	4/1997	Jang et al.	6,436,107 B1	8/2002	Wang et al.
5,623,582 A	4/1997	Rosenberg	6,441,577 B2	8/2002	Blumenkranz et al.
5,624,398 A	4/1997	Smith et al.	6,450,104 B1	9/2002	Grant et al.
5,632,761 A	5/1997	Smith et al.	6,451,027 B1	9/2002	Cooper et al.
5,645,520 A	7/1997	Nakamura et al.	6,454,758 B1	9/2002	Thompson et al.
5,657,429 A	8/1997	Wang et al.	6,459,926 B1	10/2002	Nowlin et al.
5,657,584 A	8/1997	Hamlin	6,463,361 B1	10/2002	Wang et al.
5,674,030 A	10/1997	Sigel	6,468,203 B2	10/2002	Belson
5,728,599 A	3/1998	Rostoker et al.	6,468,265 B1	10/2002	Evans et al.
5,736,821 A	4/1998	Suyaman et al.	6,470,236 B2	10/2002	Ohtsuki
5,754,741 A	5/1998	Wang et al.	6,491,691 B1	12/2002	Morley et al.
5,762,458 A	6/1998	Wang et al.	6,491,701 B2	12/2002	Tierney et al.
5,769,640 A	6/1998	Jacobus et al.	6,493,608 B1	12/2002	Niemeyer et al.
5,791,231 A	8/1998	Cohn et al.	6,496,099 B2	12/2002	Wang et al.
5,792,135 A	8/1998	Madhani et al.	6,508,413 B2	1/2003	Bauer et al.
5,797,900 A	8/1998	Madhani et al.	6,512,345 B2	1/2003	Borenstein
5,807,377 A	9/1998	Madhani et al.	6,522,906 B1	2/2003	Salisbury, Jr. et al.
5,815,640 A	9/1998	Wang et al.	6,544,276 B1	4/2003	Azizi
5,825,982 A	10/1998	Wright et al.	6,548,982 B1	4/2003	Papanikolopoulos et al.
5,841,950 A	11/1998	Wang et al.	6,554,790 B1	4/2003	Moll
5,845,646 A	12/1998	Lemelson	6,565,554 B1	5/2003	Niemeyer
5,855,583 A	1/1999	Wang et al.	6,574,355 B2	6/2003	Green
5,876,325 A	3/1999	Mizuno et al.	6,587,750 B2	7/2003	Gerbi et al.
5,878,193 A	3/1999	Wang et al.	6,591,239 B1	7/2003	McCall et al.
5,878,783 A	3/1999	Smart	6,594,552 B1	7/2003	Nowlin et al.
5,895,417 A	4/1999	Pomeranz et al.	6,610,007 B2	8/2003	Belson et al.
5,906,591 A	5/1999	Dario et al.	6,620,173 B2	9/2003	Gerbi et al.
5,907,664 A	5/1999	Wang et al.	6,642,836 B1	11/2003	Wang et al.
5,911,036 A	6/1999	Wright et al.	6,645,196 B1	11/2003	Nixon et al.
5,971,976 A	10/1999	Wang et al.	6,646,541 B1	11/2003	Wang et al.
6,001,108 A	12/1999	Wang et al.	6,648,814 B2	11/2003	Kim et al.
6,007,550 A	12/1999	Wang et al.	6,659,939 B2	12/2003	Moll et al.
6,030,365 A	2/2000	Laufer	6,661,571 B1	12/2003	Shioda et al.
6,031,371 A	2/2000	Smart	6,671,581 B2	12/2003	Niemeyer et al.
6,058,323 A	5/2000	Lemelson	6,676,684 B1	1/2004	Morley et al.
6,063,095 A	5/2000	Wang et al.	6,684,129 B2	1/2004	Salisbury, Jr. et al.
6,066,090 A	5/2000	Yoon	6,685,648 B2	2/2004	Flaherty et al.
6,102,850 A	8/2000	Wang et al.	6,685,698 B2	2/2004	Morley et al.
6,107,795 A	8/2000	Smart	6,687,571 B1	2/2004	Byrne et al.
6,132,368 A	10/2000	Cooper	6,692,485 B1	2/2004	Brock et al.
			6,699,177 B1	3/2004	Wang et al.
			6,699,235 B2	3/2004	Wallace et al.
			6,702,734 B2	3/2004	Kim et al.
			6,702,805 B1	3/2004	Stuart

(56)

References Cited

U.S. PATENT DOCUMENTS

6,714,839	B2	3/2004	Salisbury, Jr. et al.	7,039,453	B2	5/2006	Mullick
6,714,841	B1	3/2004	Wright et al.	7,042,184	B2	5/2006	Oleynikov et al.
6,719,684	B2	4/2004	Kim et al.	7,048,745	B2	5/2006	Tierney et al.
6,720,988	B1	4/2004	Gere et al.	7,053,752	B2	5/2006	Wang et al.
6,726,699	B1	4/2004	Wright et al.	7,063,682	B1	6/2006	Whayne et al.
6,728,599	B2	4/2004	Wright et al.	7,066,879	B2	6/2006	Fowler et al.
6,730,021	B2	5/2004	Vassiliades, Jr. et al.	7,066,926	B2	6/2006	Wallace et al.
6,731,988	B1	5/2004	Green	7,074,179	B2	7/2006	Wang et al.
6,746,443	B1	6/2004	Morley et al.	7,077,446	B2	7/2006	Kameda et al.
6,764,441	B2	7/2004	Chiel et al.	7,083,571	B2	8/2006	Wang et al.
6,764,445	B2	7/2004	Ramans et al.	7,083,615	B2	8/2006	Peterson et al.
6,766,204	B2	7/2004	Niemeyer et al.	7,087,049	B2	8/2006	Nowlin et al.
6,770,081	B1	8/2004	Cooper et al.	7,090,683	B2	8/2006	Brock et al.
6,774,597	B1	8/2004	Borenstein	7,097,640	B2	8/2006	Wang et al.
6,776,165	B2	8/2004	Jin	7,105,000	B2	9/2006	McBrayer
6,780,184	B2	8/2004	Tanrisever	7,107,090	B2	9/2006	Salisbury, Jr. et al.
6,783,524	B2	8/2004	Anderson et al.	7,109,678	B2	9/2006	Kraus et al.
6,785,593	B2	8/2004	Wang et al.	7,118,582	B1	10/2006	Wang et al.
6,788,018	B1	9/2004	Blumenkranz	7,121,781	B2	10/2006	Sanchez et al.
6,793,653	B2	9/2004	Sanchez et al.	7,125,403	B2	10/2006	Julian et al.
6,799,065	B1	9/2004	Niemeyer	7,126,303	B2	10/2006	Farritor et al.
6,799,088	B2	9/2004	Wang et al.	7,147,650	B2	12/2006	Lee
6,801,325	B2	10/2004	Farr et al.	7,155,315	B2	12/2006	Niemeyer et al.
6,804,581	B2	10/2004	Wang et al.	7,169,141	B2	1/2007	Brock et al.
6,810,281	B2	10/2004	Brock et al.	7,182,025	B2	2/2007	Ghorbel et al.
6,817,972	B2	11/2004	Snow	7,182,089	B2	2/2007	Ries
6,817,974	B2	11/2004	Cooper et al.	7,199,545	B2	4/2007	Oleynikov et al.
6,817,975	B1	11/2004	Farr et al.	7,206,626	B2	4/2007	Quaid, III
6,820,653	B1	11/2004	Schempf et al.	7,206,627	B2	4/2007	Abovitz et al.
6,824,508	B2	11/2004	Kim et al.	7,210,364	B2	5/2007	Ghorbel et al.
6,824,510	B2	11/2004	Kim et al.	7,214,230	B2	5/2007	Brock et al.
6,832,988	B2	12/2004	Sprout	7,217,240	B2	5/2007	Snow
6,832,996	B2	12/2004	Woloszko et al.	7,239,940	B2	7/2007	Wang et al.
6,836,703	B2	12/2004	Wang et al.	7,250,028	B2	7/2007	Julian et al.
6,837,846	B2	1/2005	Jaffe et al.	7,259,652	B2	8/2007	Wang et al.
6,837,883	B2	1/2005	Moll et al.	7,273,488	B2	9/2007	Nakamura et al.
6,839,612	B2	1/2005	Sanchez et al.	7,311,107	B2	12/2007	Harel et al.
6,840,938	B1	1/2005	Morley et al.	7,339,341	B2	3/2008	Oleynikov et al.
6,852,107	B2	2/2005	Wang et al.	7,372,229	B2	5/2008	Farritor et al.
6,858,003	B2	2/2005	Evans et al.	7,447,537	B1	11/2008	Funda et al.
6,860,346	B2	3/2005	Burt et al.	7,492,116	B2	2/2009	Oleynikov et al.
6,860,877	B1	3/2005	Sanchez et al.	7,566,300	B2	7/2009	Devierre et al.
6,866,671	B2	3/2005	Tiemey et al.	7,574,250	B2	8/2009	Niemeyer
6,870,343	B2	3/2005	Borenstein et al.	7,637,905	B2	12/2009	Saadat et al.
6,871,117	B2	3/2005	Wang et al.	7,645,230	B2	1/2010	Mikkaichi et al.
6,871,563	B2	3/2005	Choset et al.	7,655,004	B2	2/2010	Long
6,879,880	B2	4/2005	Nowlin et al.	7,670,329	B2	3/2010	Flaherty et al.
6,892,112	B2	5/2005	Wang et al.	7,731,727	B2	6/2010	Sauer
6,899,705	B2	5/2005	Niemeyer	7,762,825	B2	7/2010	Burbank et al.
6,902,560	B1	6/2005	Morley et al.	7,772,796	B2	8/2010	Farritor et al.
6,905,460	B2	6/2005	Wang et al.	7,785,251	B2	8/2010	Wilk
6,905,491	B1	6/2005	Wang et al.	7,785,333	B2	8/2010	Miyamoto et al.
6,911,916	B1	6/2005	Wang et al.	7,789,825	B2	9/2010	Nobis et al.
6,917,176	B2	7/2005	Schempf et al.	7,794,494	B2	9/2010	Sahatjian et al.
6,933,695	B2	8/2005	Blumenkranz	7,865,266	B2	1/2011	Moll et al.
6,936,001	B1	8/2005	Snow	7,960,935	B2	6/2011	Farritor et al.
6,936,003	B2	8/2005	Iddan	8,179,073	B2	5/2012	Farritor et al.
6,936,042	B2	8/2005	Wallace et al.	2001/0018591	A1	8/2001	Brock et al.
6,943,663	B2	9/2005	Wang et al.	2001/0049497	A1	12/2001	Kalloo et al.
6,949,096	B2	9/2005	Davison et al.	2002/0003173	A1	1/2002	Bauer et al.
6,951,535	B2	10/2005	Ghodoussi et al.	2002/0026186	A1	2/2002	Woloszko et al.
6,965,812	B2	11/2005	Wang et al.	2002/0038077	A1	3/2002	de la Torre et al.
6,974,411	B2	12/2005	Belson	2002/0065507	A1	5/2002	Azizi
6,974,449	B2	12/2005	Niemeyer	2002/0091374	A1	7/2002	Cooper
6,979,423	B2	12/2005	Moll	2002/0103417	A1	8/2002	Gazdzinski
6,984,203	B2	1/2006	Tartaglia et al.	2002/0111535	A1	8/2002	Kim et al.
6,984,205	B2	1/2006	Gazdzinski	2002/0120254	A1	8/2002	Julien et al.
6,991,627	B2	1/2006	Madhani et al.	2002/0128552	A1	9/2002	Nowlin et al.
6,993,413	B2	1/2006	Sunaoshi	2002/0140392	A1	10/2002	Borenstein et al.
6,994,703	B2	2/2006	Wang et al.	2002/0147487	A1	10/2002	Sundquist et al.
6,994,708	B2	2/2006	Manzo	2002/0151906	A1	10/2002	Demarais et al.
6,997,908	B2	2/2006	Carrillo, Jr. et al.	2002/0156347	A1	10/2002	Kim et al.
7,025,064	B2	4/2006	Wang et al.	2002/0171385	A1	11/2002	Kim et al.
7,027,892	B2	4/2006	Wang et al.	2002/0173700	A1	11/2002	Kim et al.
7,033,344	B2	4/2006	Imran	2002/0190682	A1	12/2002	Schempf et al.
				2003/0020810	A1	1/2003	Takizawa et al.
				2003/0045888	A1	3/2003	Brock et al.
				2003/0065250	A1	4/2003	Chiel et al.
				2003/0089267	A1	5/2003	Ghorbel et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0092964	A1	5/2003	Kim et al.
2003/0097129	A1	5/2003	Davison et al.
2003/0100817	A1	5/2003	Wang et al.
2003/0114731	A1	6/2003	Cadeddu et al.
2003/0139742	A1	7/2003	Wampler et al.
2003/0144656	A1	7/2003	Ocel et al.
2003/0167000	A1	9/2003	Mullick
2003/0172871	A1	9/2003	Scherer
2003/0179308	A1	9/2003	Zamorano et al.
2003/0181788	A1	9/2003	Yokoi et al.
2003/0229268	A1	12/2003	Uchiyama et al.
2003/0230372	A1	12/2003	Schmidt
2004/0024311	A1	2/2004	Quaid
2004/0034282	A1	2/2004	Quaid
2004/0034283	A1	2/2004	Quaid
2004/0034302	A1	2/2004	Abovitz et al.
2004/0050394	A1	3/2004	Jin
2004/0070822	A1	4/2004	Shioda et al.
2004/0099175	A1	5/2004	Perrot et al.
2004/0106916	A1	6/2004	Quaid et al.
2004/0111113	A1	6/2004	Nakamura et al.
2004/0138552	A1	7/2004	Harel et al.
2004/0140786	A1	7/2004	Borenstein
2004/0153057	A1	8/2004	Davison
2004/0173116	A1	9/2004	Ghorbel et al.
2004/0176664	A1	9/2004	Iddan
2004/0215331	A1	10/2004	Chew et al.
2004/0225229	A1	11/2004	Viola
2004/0254680	A1	12/2004	Sunaoshi
2004/0267326	A1	12/2004	Ocel et al.
2005/0014994	A1	1/2005	Fowler et al.
2005/0029978	A1	2/2005	Oleynikov et al.
2005/0043583	A1	2/2005	Killmann et al.
2005/0049462	A1	3/2005	Kanazawa
2005/0054901	A1	3/2005	Yoshino
2005/0054902	A1	3/2005	Konno
2005/0064378	A1	3/2005	Toly
2005/0065400	A1	3/2005	Banik et al.
2005/0083460	A1	4/2005	Hattori et al.
2005/0096502	A1	5/2005	Khalili
2005/0143644	A1	6/2005	Gilad et al.
2005/0154376	A1	7/2005	Riviere et al.
2005/0165449	A1	7/2005	Cadeddu et al.
2005/0288555	A1	12/2005	Binmoeller
2005/0288665	A1	12/2005	Woloszko
2006/0020272	A1	1/2006	Gildenberg
2006/0046226	A1	3/2006	Bergler et al.
2006/0119304	A1	6/2006	Farritor et al.
2006/0149135	A1	7/2006	Paz
2006/0152591	A1	7/2006	Lin
2006/0155263	A1	7/2006	Lipow
2006/0195015	A1	8/2006	Mullick et al.
2006/0196301	A1	9/2006	Oleynikov et al.
2006/0198619	A1	9/2006	Oleynikov et al.
2006/0241570	A1	10/2006	Wilk
2006/0241732	A1	10/2006	Denker et al.
2006/0253109	A1	11/2006	Chu
2006/0258954	A1	11/2006	Timberlake et al.
2007/0032701	A1	2/2007	Fowler et al.
2007/0043397	A1	2/2007	Ocel et al.
2007/0055342	A1	3/2007	Wu et al.
2007/0080658	A1	4/2007	Farritor et al.
2007/0106113	A1	5/2007	Ravo
2007/0123748	A1	5/2007	Meglan
2007/0142725	A1	6/2007	Hardin et al.
2007/0156019	A1	7/2007	Larkin et al.
2007/0156211	A1	7/2007	Ferren et al.
2007/0167955	A1	7/2007	De La Menardiere et al.
2007/0225633	A1	9/2007	Ferren et al.
2007/0225634	A1	9/2007	Ferren et al.
2007/0241714	A1	10/2007	Okeynikov et al.
2007/0244520	A1	10/2007	Ferren et al.
2007/0250064	A1	10/2007	Darois et al.
2007/0255273	A1	11/2007	Fernandez et al.
2008/0004634	A1	1/2008	Farritor et al.

2008/0015565	A1	1/2008	Davison
2008/0015566	A1	1/2008	Livneh
2008/0033569	A1	2/2008	Ferren et al.
2008/0058835	A1	3/2008	Farritor et al.
2008/0058989	A1	3/2008	Oleynikov et al.
2008/0103440	A1	5/2008	Ferren et al.
2008/0111513	A1	5/2008	Farritor et al.
2008/0119870	A1	5/2008	Williams et al.
2008/0132890	A1	6/2008	Woloszko et al.
2008/0164079	A1	7/2008	Jacobsen
2008/0183033	A1	7/2008	Bern et al.
2008/0221591	A1	9/2008	Farritor et al.
2008/0269557	A1	10/2008	Marescaux et al.
2009/0020724	A1	1/2009	Paffrath
2009/0048612	A1	2/2009	Farritor et al.
2009/0054909	A1	2/2009	Farritor et al.
2009/0069821	A1	3/2009	Farritor et al.
2009/0076536	A1	3/2009	Rentschler et al.
2009/0143787	A9	6/2009	De La Pena
2009/0171373	A1	7/2009	Farritor et al.
2009/0236400	A1	9/2009	Cole et al.
2009/0240246	A1	9/2009	Devill et al.
2009/0247821	A1	10/2009	Rogers
2009/0281377	A1	11/2009	Newell et al.
2009/0305210	A1	12/2009	Guru et al.
2010/0010294	A1	1/2010	Conlon et al.
2010/0016659	A1	1/2010	Weitzner
2010/0042097	A1	2/2010	Newton et al.
2010/0056863	A1	3/2010	Dejima et al.
2010/0069710	A1	3/2010	Yamatani et al.
2010/0081875	A1	4/2010	Fowler et al.
2010/0198231	A1	8/2010	Scott
2010/0204713	A1	8/2010	Ruiz
2010/0245549	A1	9/2010	Allen et al.
2010/0318059	A1	12/2010	Farritor et al.
2011/0015569	A1	1/2011	Kirschenman et al.
2011/0077478	A1	3/2011	Freeman et al.
2011/0152615	A1	6/2011	Schostek et al.
2011/0224605	A1	9/2011	Farritor et al.
2011/0237890	A1	9/2011	Farritor et al.
2012/0035582	A1	2/2012	Nelson et al.
2013/0041360	A1	2/2013	Farritor

FOREIGN PATENT DOCUMENTS

JP	5115425	5/1993
JP	6-508049	9/1994
JP	07 136173	5/1995
JP	7306155	11/1995
JP	2004322310	6/2004
JP	2004180781	7/2004
JP	2004329292	11/2004
WO	WO 92/21291	5/1991
WO	WO 02/082979	10/2002
WO	WO 02/100256	12/2002
WO	WO 2005/009211	2/2005
WO	WO 2006 005075	1/2006
WO	WO 2006/079108	1/2006
WO	WO 2006/052927	5/2006
WO	WO 2007/111571	10/2007
WO	WO 2007/149559	12/2007
WO	WO 2009/144729	12/2009
WO	WO 2010/042611	4/2010
WO	WO2010/042611	4/2010
WO	WO 2010/046823	4/2010
WO	WO2010/046823	4/2010
WO	WO 2011/135503	11/2011

OTHER PUBLICATIONS

Abbou et al., "Laparoscopic Radical Prostatectomy with a Remote Controlled Robot," The Journal of Urology, Jun. 2001, 165: 1964-1966.

Allendorf et al., "Postoperative Immune Function Varies Inversely with the Degree of Surgical Trauma in a Murine Model," Surgical Endoscopy 1997; 11: 427-430.

Ang, "Active Tremor Compensation in Handheld Instrument for Microsurgery," Doctoral dissertation, tech report CMU-RI-TR-04-

(56)

References Cited

OTHER PUBLICATIONS

- 28, Robotics Institute, Carnegie Mellon University, May 2004, 167 pp.
- Applicant Amendment after Notice of Allowance under Rule 312, filed Aug. 25, 2008, in related case U.S. Appl. No. 11/695,944, 6 pp.
- Applicant Response to Office Action dated Apr. 17, 2007, in related case U.S. Appl. No. 11/552,379, filed Aug. 8, 2007, 7 pp.
- Applicant Response to Office Action dated Aug. 18, 2006, in related case U.S. Appl. No. 11/398,174, filed Nov. 7, 2006, 8 pp.
- Applicant Response to Office Action dated Aug. 21, 2006, in related case U.S. Appl. No. 11/403,756, filed Nov. 21, 2006, 52 pp.
- Applicant Response to Office Action dated Oct. 29, 2007, in related case U.S. Appl. No. 11/695,944, filed Jan. 22, 2008, 6 pp.
- Atmel 80C5X2 Core, <http://www.atmel.com>, 2006, 186 pp.
- Bailey et al., "Complications of Laparoscopic Surgery," Quality Medical Publishers, Inc., 1995, 25 pp.
- Ballantyne, "Robotic Surgery, Telerobotic Surgery, Telepresence, and Telementoring," *Surgical Endoscopy*, 2002; 16: 1389-1402.
- Bauer et al., "Case Report: Remote Percutaneous Renal Access Using a New Automated Telesurgical Robotic System," *Telemedicine Journal and e-Health* 2001; (4): 341-347.
- Begos et al., "Laparoscopic Cholecystectomy: From Gimmick to Gold Standard," *J Clin Gastroenterol*, 1994; 19(4): 325-330.
- Berg et al., "Surgery with Cooperative Robots," *Medicine Meets Virtual Reality*, Feb. 2007, 1 pg.
- Breda et al., "Future developments and perspectives in laparoscopy," *Eur. Urology* 2001; 40(1): 84-91.
- Breedveld et al., "Design of Steerable Endoscopes to Improve the Visual Perception of Depth During Laparoscopic Surgery," *ASME, Jan. 2004; vol. 126*, pp. 1-5.
- Breedveld et al., "Locomotion through the Intestine by means of Rolling Stents," *Proceedings of the ASME Design Engineering Technical Conferences*, 2004, pp. 1-7.
- Calafiore et al., "Multiple Arterial Conduits Without Cardiopulmonary Bypass: Early Angiographic Results," *Ann Thorac Surg*, 1999; 67: 450-456.
- Camarillo et al., "Robotic Technology in Surgery: Past, Present, and Future," *The American Journal of Surgery*, 2004; 188: 2S-15.
- Cavusoglu et al., "Telesurgery and Surgical Simulation: Haptic Interfaces to Real and Virtual Surgical Environments," In McLaughlin, M. L., Hespanha, J. P., and Sukhatme, G., editors. *Touch in virtual environments*, IMSC Series in Multimedia 2001, 28 pp.
- Cavusoglu et al., "Robotics for Telesurgery: Second Generation Berkeley/UCSF Laparoscopic Telesurgical Workstation and Looking Towards the Future Applications," *Industrial Robot: An International Journal*, 2003; 30(1): 22-29.
- Chanthasopeephan et al. (2003), "Measuring Forces in Liver Cutting: New Equipment and Experimental Results," *Annals of Biomedical Engineering* 31: 1372-1382.
- Choi et al., "Flexure-based Manipulator for Active Handheld Microsurgical Instrument," *Proceedings of the 27th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBS)*, Sep. 2005, 4 pp.
- CrystalEyes, <http://www.reald.com>, 2007 (Stereoscopic visualization for CAVEs, theaters and immersive environments), 1 pg.
- Cuschieri, "Technology for Minimal Access Surgery," *BMJ*, 1999, 319: 1-6.
- Dakin et al., "Comparison of laparoscopic skills performance between standard instruments and two surgical robotic systems," *Surg Endosc.*, 2003; 17: 574-579.
- Dumpert et al., "Improving In Vivo Robot Vision Quality," from the *Proceedings of Medicine Meets Virtual Reality*, Long Beach, CA, Jan. 26-29, 2005, 1 pg.
- Dumpert et al., "Stereoscopic In Vivo Surgical Robots," *IEEE Sensors Special Issue on In Vivo Sensors for Medicine*, Jan. 2007, 10 pp.
- Examiner Interview Summary dated Aug. 6 and Aug. 12, 2008, in related case U.S. Appl. No. 11/695,944, 1 pg.
- Examiner Interview Summary dated May 9, 2008, in related case U.S. Appl. No. 11/695,944, 1 pg.
- Examiner Interview Summary dated Nov. 30, 2006, in related case U.S. Appl. No. 11/398,174, 2 pp.
- Falcone et al., "Robotic Surgery," *Clin. Obstet. Gynecol.* 2003, 46(1): 37-43.
- Faraz et al., "Engineering Approaches to Mechanical and Robotic Design for Minimally Invasive Surgery (MIS)," Kluwer Academic Publishers (Boston), 2000, 13 pp.
- Fearing et al., "Wing Transmission for a Micromechanical Flying Insect," *Proceedings of the 2000 IEEE International Conference on Robotics & Automation*, Apr. 2000; 1509-1516.
- Fireman et al., "Diagnosing small bowel Crohn's disease with wireless capsule endoscopy," *Gut* 2003; 52: 390-392.
- Flynn et al., "Tomorrow's surgery: micromotors and microrobots for minimally invasive procedures," *Minimally Invasive Surgery & Allied Technologies*, 1998; 7(4): 343-352.
- Franklin et al., "Prospective Comparison of Open vs. Laparoscopic Colon Surgery for Carcinoma: Five-Year Results," *Dis Colon Rectum*, 1996; 39: S35-S46.
- Franzino, "The Laprotek Surgical System and the Next Generation of Robotics," *Surg Clin North Am*, 2003 83(6): 1317-1320.
- Fraulob et al., "Miniature assistance module for robot-assisted heart surgery," *Biomed. Tech.* 2002, 47 Suppl. 1, Pt. 1: 12-15.
- Fukuda et al., "Mechanism and Swimming Experiment of Micro Mobile Robot in Water," *Proceedings of the 1994 IEEE International Conference on Robotics and Automation*, 1994: 814-819.
- Fukuda et al., "Micro Active Catheter System with Multi Degrees of Freedom," *Proceedings of the IEEE International Conference on Robotics and Automation*, May 1994, pp. 2290-2295.
- Fuller et al., "Laparoscopic Trocar Injuries: A Report from a U.S. Food and Drug Administration (FDA) Center for Devices and Radiological Health (CDRH) Systematic Technology Assessment of Medical Products (STAMP) Committee," U.S. Food and Drug Administration, available at <http://www.fda.gov>, Finalized: Nov. 7, 2003; Updated: Jun. 24, 2005, 11 pp.
- Glukhovskiy et al., "The development and application of wireless capsule endoscopy," *Int. J. Med. Robot. Comput. Assist. Surgery*, 2004; 1(1): 114-123.
- Gong et al., "Wireless endoscopy," *Gastrointestinal Endoscopy* 2000; 51(6): 725-729.
- Grady, "Doctors Try New Surgery for Gallbladder Removal," *The New York Times*, Apr. 20, 2007, 3 pp.
- Guber et al., "Miniaturized Instrument Systems for Minimally Invasive Diagnosis and Therapy," *Biomedizinische Technic.* 2002, Band 47, Ergänzungsband 1: 198-201.
- Guo et al., "Fish-like Underwater Microrobot with 3 DOF," *Proceedings of the 2002 IEEE International Conference on Robotics & Automation*, May 2002: 738-743.
- Guo et al., "Micro Active Guide Wire Catheter System—Characteristic Evaluation, Electrical Model and Operability Evaluation of Micro Active Catheter," *Proceedings of the 1996 IEEE International Conference on Robotics and Automation*, Apr. 1996: 2226-2231.
- Hanly et al., "Robotic Abdominal Surgery," *The American Journal of Surgery* 188 (Suppl. to Oct. 1994): 19S-26S, 2004.
- Hanly et al., "Value of the SAGES Learning Center in introducing new technology," *Surgical Endoscopy*, 2004; 19(4): 477-483.
- Heikkinen et al., "Comparison of laparoscopic and open Nissen fundoplication two years after operation: A prospective randomized trial," *Surgical Endoscopy*, 2000; 14: 1019-1023.
- Hissink, "Olympus Medical develops capsule camera technology," Dec. 2004, accessed Aug. 29, 2007, <http://www.letsgodigital.org>, 3 pp.
- Horgan et al., "Technical Report: Robots in Laparoscopic Surgery," *Journal of Laparoendoscopic & Advanced Surgical Techniques*, 2001; 11(6): 415-419.
- International Preliminary Report on Patentability from related case PCT/US2007/014567, mailed Jan. 8, 2009, 11 pp.
- International Search Report and Written Opinion from international application No. PCT/US07/14567, mailed Apr. 28, 2008, 19 pp.
- International Search Report and Written Opinion from international application No. PCT/US2007/089191, mailed Nov. 10, 2008, 20 pp.
- International Search Report and Written Opinion of international application No. PCT/US2008/073369, mailed Nov. 12, 2008, 12 pp.

(56)

References Cited

OTHER PUBLICATIONS

- International Search Report and Written Opinion of international application No. PCT/US2008/073334, mailed Jan. 12, 2009, 11 pp.
- International Search Report and Written Opinion of international application No. PCT/US2008/069822, mailed Aug. 5, 2009, 12 pp.
- Ishiyama et al., "Spiral-type Micro-machine for Medical Applications," 2000 International Symposium on Micromechatronics and Human Science, 2000: 65-69.
- Jagannath et al., "Peroral transgastric endoscopic ligation of fallopian tubes with long-term survival in a porcine model," *Gastrointestinal Endoscopy*, 2005; 61(3): 449-453.
- Kalloor et al., "Flexible transgastric peritoneoscopy: a novel approach to diagnostic and therapeutic interventions in the peritoneal cavity," *Gastrointestinal Endoscopy*, 2004; 60(1): 114-117.
- Kang et al., "Robotic Assistants Aid Surgeons During Minimally Invasive Procedures," *IEEE Engineering in Medicine and Biology*, Jan.-Feb. 2001; pp. 94-104.
- Kantsevov et al., "Endoscopic gastrojejunostomy with survival in a porcine model," *Gastrointestinal Endoscopy*, 2005; 62(2): 287-292.
- Kantsevov et al., "Transgastric endoscopic splenectomy," *Surgical Endoscopy*, 2006; 20: 522-525.
- Kazemier et al. (1998), "Vascular Injuries During Laparoscopy," *J. Am. Coli. Surg.* 186(5): 604-5.
- Kim, "Early Experience with Telem manipulative Robot-Assisted Laparoscopic Cholecystectomy Using da Vinci," *Surgical Laparoscopy, Endoscopy & Percutaneous Techniques*, 2002; 12(1):33-40.
- Ko et al., "Per-Oral transgastric abdominal surgery," *Chinese Journal of Digestive Diseases*, 2006; 7: 67-70.
- Lafuillarde et al., "Laparoscopic Nissen Fundoplication: Five-year Results and Beyond," *Arch/Surg*, Feb. 2001; 136:180-184.
- Leggett et al. (2002), "Aortic injury during laparoscopic fundoplication," *Surg. Endoscopy* 16(2): 362.
- Li et al. (2000), "Microvascular Anastomoses Performed in Rats Using a Microsurgical Telem manipulator," *Comp. Aid. Surg.* 5: 326-332.
- Liem et al., "Comparison of Conventional Anterior Surgery and Laparoscopic Surgery for Inguinal-hernia Repair," *New England Journal of Medicine*, 1997; 336 (22): 1541-1547.
- MacFarlane et al., "Force-Feedback Grasper Helps Restore the Sense of Touch in Minimally Invasive Surgery," *Journal of Gastrointestinal Surgery*, 1999; 3: 278-285.
- Mack et al., "Present Role of Thoracoscopy in the Diagnosis and Treatment of Diseases of the Chest," *Ann Thorac Surgery*, 1992; 54: 403-409.
- Mack, "Minimally Invasive and Robotic Surgery," *JAMA*, Feb. 2001; 285(5): 568-572.
- Mei et al., "Wireless Drive and Control of a Swimming Microrobot," *Proceedings of the 2002 IEEE International Conference on Robotics & Automation*, May 2002: 1131-1136.
- Melvin et al., "Computer-Enhanced vs. Standard Laparoscopic Antireflux Surgery," *J Gastrointest Surg* 2002; 6: 11-16.
- Menciassi et al., "Locomotion of a Leffed Capsule in the Gastrointestinal Tract: Theoretical Study and Preliminary Technological Results," *IEEE Int. Conf. on Engineering in Medicine and Biology*, San Francisco, CA, pp. 2767-2770, Sep. 2004.
- Menciassi et al., "Robotic Solutions and Mechanisms for a Semi-Autonomous Endoscope," *Proceedings of the 2002 IEEE/RSJ Intl. Conference on Intelligent Robots and Systems*, Oct. 2002; 1379-1384.
- Menciassi et al., "Shape memory alloy clamping devices of a capsule for monitoring tasks in the gastrointestinal tract," *J. Micromech. Microeng.* 2005, 15: 2045-2055.
- Meron, "The development of the swallowable video capsule (M2A)," *Gastrointestinal Endoscopy* 2000; 52 6: 817-819.
- Micron, <http://www.micron.com>, 2006, 1/4-inch VGA NTSC/PAL CMOS Digital Image Sensor, 98 pp.
- Miller, Ph.D., et al., "In-Vivo Stereoscopic Imaging System with 5 Degrees-of-Freedom for Minimal Access Surgery," *Dept. of Computer Science and Dept. of Surgery, Columbia University, New York, NY*, 7 pp.
- Munro (2002), "Laparoscopic access: complications, technologies, and techniques," *Curro Opin. Obstet. Gynecol.*, 14(4): 365-74.
- Nio et al., "Efficiency of manual vs robotical (Zeus) assisted laparoscopic surgery in the performance of standardized tasks," *Surg Endosc*, 2002; 16: 412-415.
- Office Action dated Apr. 17, 2007, received in related case U.S. Appl. No. 11/552,379, 5 pp.
- Office Action dated Apr. 3, 2009, received in related case U.S. Appl. No. 11/932,516, 43 pp.
- Office Action dated Aug. 18, 2006, received in related case U.S. Appl. No. 11/398,174, 6 pp.
- Office Action dated Aug. 21, 2006, received in related case U.S. Appl. No. 11/403,756, 6 pp.
- Office Action dated Oct. 29, 2007, received in related case U.S. Appl. No. 11/695,944, 6 pp.
- Office Action dated Oct. 9, 2008, received in related case U.S. Appl. No. 11/932,441, 4 pp.
- Oleynikov et al., "In Vivo Camera Robots Provide Improved Vision for Laparoscopic Surgery," *Computer Assisted Radiology and Surgery (CARS)*, Chicago, IL, Jun. 23-26, 2004b.
- Oleynikov et al., "In Vivo Robotic Laparoscopy," *Surgical Innovation*, Jun. 2005, 12(2): 177-181.
- Oleynikov et al., "Miniature Robots Can Assist in Laparoscopic Cholecystectomy," *Journal of Surgical Endoscopy*, 19-4: 473-476, 2005.
- O'Neill, "Surgeon takes new route to gallbladder," *The Oregonian*, Jun. 2007, 2 pp.
- Orlando et al., (2003), "Needle and Trocar Injuries in Diagnostic Laparoscopy under Local Anesthesia: What Is the True Incidence of These Complications?" *Journal of Laparoendoscopic & Advanced Surgical Techniques* 13(3): 181-184.
- Park et al., "Trocar-less Instrumentation for Laparoscopy: Magnetic Positioning of Intra-abdominal Camera and Retractor," *Ann Surg*, Mar. 2007; 245(3): 379-384.
- Park et al., "Experimental studies of transgastric gallbladder surgery: cholecystectomy and cholecystogastric anastomosis (videos)," *Gastrointestinal Endoscopy*, 2005; 61(4): 601-606.
- Patronik et al., "Development of a Tethered Epicardial Crawler for Minimally Invasive Cardiac Therapies," *IEEE*, pp. 239-240.
- Patronik et al., "Crawling on the Heart: A Mobile Robotic Device for Minimally Invasive Cardiac Interventions," *MICCAI*, 2004, pp. 9-16.
- Patronik et al., "Preliminary evaluation of a mobile robotic device for navigation and intervention on the beating heart," *Computer Aided Surgery*, 10(4): 225-232, Jul. 2005.
- Peirs et al., "A miniature manipulator for integration in a self-propelling endoscope," *Sensors and Actuators A*, 2001, 92: 343-349.
- Peters, "Minimally Invasive Colectomy: Are the Potential Benefits Realized?" *Dis Colon Rectum* 1993; 36: 751-756.
- Phoe et al., "Analysis and Development of Locomotion Devices for the Gastrointestinal Tract," *IEEE Transaction on Biomedical Engineering*, vol. 49, No. 6, Jun. 2002, pp. 613-616.
- Phoe et al., "Development of Microrobotic Devices for Locomotion in the Human Gastrointestinal Tract," *International Conference on Computational Intelligence, Robotics and Autonomous Systems (CIRAS 2001)*, Nov. 28-30, 2001, Singapore.
- Platt et al., "In Vivo Robotic Cameras can Enhance Imaging Capability During Laparoscopic Surgery," in the *Proceedings of the Society of American Gastrointestinal Endoscopic Surgeons (SAGES) Scientific Conference*, Ft. Lauderdale, FL, Apr. 13-16, 2005, 1 pg.
- Preliminary Amendment filed Apr. 11, 2007, in related case U.S. Appl. No. 11/403,756, 7 pp.
- Preliminary Amendment filed Jul. 30, 2008, in related case U.S. Appl. No. 12/171,413, 4 pp.
- RCE and Amendment filed Jun. 13, 2007, in related case U.S. Appl. No. 11/403,756, 8 pp.
- Rentschler et al., "Mobile In Vivo Biopsy and Camera Robot," *Studies in Health and Infonnatics Medicine Meets Virtual Reality*, vol. 119., pp. 449-454, IOS Press, Long Beach, CA, 2006.

(56)

References Cited

OTHER PUBLICATIONS

- Rentschler et al., Mobile In Vivo Biopsy Robot, IEEE International Conference on Robotics and Automation, Orlando, Florida, May 2006, pp. 4155-4160.
- Rentschler et al., "Miniature in vivo Robots for Remote and Harsh Environments," IEEE Transactions on Information Technology in Biomedicine, Jan. 2006; 12(1): 66-75.
- Rentschler et al., "An In Vivo Mobile Robot for Surgical Vision and Task Assistance," Journal of Medical Devices, Mar. 2007, vol. 1: 23-29.
- Rentschler et al., "In vivo Mobile Surgical Robotic Task Assistance," 1 pg.
- Rentschler et al., "In vivo Robotics during the NEEMO 9 Mission," Medicine Meets Virtual Reality, Feb. 2007, 1 pg.
- Rentschler et al., "In Vivo Robots for Laparoscopic Surgery," Studies in Health Technology and Informatics—Medicine Meets Virtual Reality, ISO Press, Newport Beach, CA, 2004a, 98: 316-322.
- Rentschler et al., "Mechanical Design of Robotic In Vivo Wheeled Mobility," ASME Journal of Mechanical Design, 2006a, pp. I-II.
- Rentschler et al., "Mobile In Vivo Camera Robots Provide Sole Visual Feedback for Abdominal Exploration and Cholecystectomy," Journal of Surgical Endoscopy, 20-I: 135-138, 2006b.
- Rentschler et al., "Mobile In Vivo Robots Can Assist in Abdominal Exploration," from the Proceedings of the Society of American Gastrointestinal Endoscopic Surgeons (SAGES) Scientific Conference, Ft. Lauderdale, FL, Apr. 13-16, 2005b.
- Rentschler et al., "Modeling, Analysis, and Experimental Study of In Vivo Wheeled Robotic Mobility," IEEE Transactions on Robotics, 22 (2): 308-321, 2005c.
- Rentschler et al., "Natural Orifice Surgery with an Endoluminal Mobile Robot," The Society of American Gastrointestinal Endoscopic Surgeons, Dallas, TX, Apr. 2006d, 14 pp.
- Rentschler et al., "Theoretical and Experimental Analysis of In Vivo Wheeled Mobility," ASME Design Engineering Technical Conferences: 28th Biennial Mechanisms and Robotics Conference, Salt Lake City, Utah, Sep. 28-Oct. 2, 2004, pp. 1-9.
- Rentschler et al., "Toward In Vivo Mobility," Studies in Health Technology and Informatics—Medicine Meets Virtual Reality, ISO Press, Long Beach, CA, 2005a, III: 397-403.
- Response to Rule 312 Amendment in related case U.S. Appl. No. 11/695,944, dated Jan. 12, 2009, 2 pp.
- Riviere et al., "Toward Active Tremor Canceling in Handheld Microsurgical Instruments," IEEE Transactions on Robotics and Automation, Oct. 2003, 19(5): 793-800.
- Rosen et al., "Force Controlled and Teleoperated Endoscopic, Grasper for Minimally Invasive Surgery-Experimental Performance Evaluation," IEEE Transactions of Biomedical Engineering, Oct. 1999; 46(10): 1212-1221.
- Rosen et al., "Objective Laparoscopic Skills Assessments of Surgical Residents Using Hidden Markov Models Based on Haptic Information and Tool/Tissue Interactions," Studies in Health Technology and Informatics-Medicine Meets Virtual Reality, Jan. 2001, 7 pp.
- Rosen et al., "Spherical Mechanism Analysis of a Surgical Robot for Minimally Invasive Surgery—Analytical and Experimental Approaches," Studies in Health Technology and Informatics-Medicine Meets Virtual Reality, pp. 442-448, Jan. 2005.
- Rosen et al., "Task Decomposition of Laparoscopic Surgery for Objective Evaluation of Surgical Residents' Learning Curve Using Hidden Markov Model," Computer Aided Surgery, vol. 7, pp. 49-61, 2002.
- Rosen et al., "The Blue DRAGON—A System of Measuring the Kinematics and the Dynamics of Minimally Invasive Surgical Tools In-Vivo," Proc. of the 2002 IEEE International Conference on Robotics and Automation, Washington, DC, pp. 1876-1881, May 2002.
- Ruurda et al., "Robot-Assisted surgical systems: a new era in laparoscopic surgery," Ann R. Coll Surg Engl., 2002; 84: 223-226.
- Ruurda et al., "Feasibility of Robot-Assisted Laparoscopic Surgery," Surgical Laparoscopy, Endoscopy & Percutaneous Techniques, 2002; 12(1):41-45.
- Sackier et al., "Robotically assisted laparoscopic surgery," Surgical Endoscopy, 1994; 8: 63-66.
- Salky, "What is the Penetration of Endoscopic Techniques into Surgical Practice?" Digestive Surgery, 2000; 17:422-426.
- Satava, "Surgical Robotics: The Early Chronicles," Surgical Laparoscopy, Endoscopy & Percutaneous Techniques, 2002; 12(1): 6-16.
- Schippers et al., (1996) "Requirements and Possibilities of Computer-Assisted Endoscopic Surgery," In: Computer Integrated Surgery: Technology and Clinical Applications, pp. 561-565.
- Schurr et al., "Robotics and Telemanipulation Technologies for Endoscopic Surgery," Surgical Endoscopy, 2000; 14: 375-381.
- Schwartz, "In the Lab: Robots that Slink and Squirm," The New York Times, Mar. 27, 2007, 4 pp.
- Sharp LL-151-3D, <http://www.sharp3d.com>, 2006, 2 pp.
- Slatkin et al., "The Development of a Robotic Endoscope," Proceedings of the 1995 IEEE International Conference on Robotics and Automation, pp. 162-171, 1995.
- Smart Pill "Fastastic Voyage: Smart Pill to Expand Testing," <http://www.smartpilldiagnostics.com>, Apr. 13, 2005, 1 pg.
- Southern Surgeons Club (1991), "A prospective analysis of 1518 laparoscopic cholecystectomies," N. Eng. J. Med. 324 (16): 1073-1078.
- Stefanini et al., "Modeling and Experiments on a Legged Microrobot Locomoting in a Tubular Compliant and Slippery Environment," Int. Journal of Robotics Research, vol. 25, No. 5-6, pp. 551-560, May-Jun. 2006.
- Stiff et al., "Long-term Pain: Less Common After Laparoscopic than Open Cholecystectomy," British Journal of Surgery, 1994; 81: 1368-1370.
- Strong, et al., "Efficacy of Novel Robotic Camera vs. a Standard Laproscopic Camera," Surgical Innovation vol. 12, No. 4, Dec. 2005, Westminster Publications, Inc., pp. 315-318.
- Suzumori et al., "Development of Flexible Microactuator and its Applications to Robotics Mechanisms," Proceedings of the IEEE International Conference on Robotics and Automation, 1991: 1622-1627.
- Taylor et al., "A Telerobotic Assistant for Laparoscopic Surgery," IEEE Eng Med Biol, 1995; 279-287.
- Tendick et al. (1993), "Sensing and Manipulation Problems in Endoscopic Surgery: Experiment, Analysis, and Observation," Presence 2(1): 66-81.
- Tendick et al., "Applications of Micromechatronics in Minimally Invasive Sugery," IEEE/ASME Transaction on Mechatronicsm 1998; 3(1): 34-42.
- Thomann et al., "The Design of a new type of Micro Robot for the Intestinal Inspection," Proceedings of the 2002 IEEE Intl. Conference on Intelligent Robots and Systems, Oct. 2002: 1385-1390.
- Way et al (editors), "Fundamentals of Laparoscopic Surgery," Churchill Livingstone Inc., 1995, 14 pp.
- Wolfe et al., "Endoscopic Cholecystectomy: An analysis of Complications," Arch. Surg. Oct. 1991; 126: 1192-1196.
- Worn et al., "Espirit Project No. 33915: Miniaturised Robot for Micro Manipulation (MINIMAN)", Nov. 1998; <http://www.ipr.ira.ujka.de/~microbot/miniman>.
- Yu et al., "Microrobotic Cell Injection," Proceedings of the 2001 IEEE International Conference on Robotics and Automation, May 2001; 620-625.
- Yu, BSN, RN, "M2ATM Capsule Endoscopy a Breakthrough Diagnostic Tool for Small Intestine Imaging," vol. 25, No. 1, Gastroenterology Nursing, pp. 24-27.
- Abbott et al., "Design of an Endoluminal NOTES Robotic System," from the Proceedings of the 2007 IEEE/RSJ Intl Conf. on Intelligent Robot Systems, San Diego, CA, Oct. 29-Nov. 2, 2007, pp. 410-416.
- Allendorf et al., "Postoperative Immune Function Varies Inversely with the Degree of Surgical Trauma in a Murine Model," Surgical Endoscopy 1997; 11:427-430.
- Ang, "Active Tremor Compensation in Handheld Instrument for Microsurgery," Doctoral Dissertation, tech report CMU-RI-TR-04-28, Robotics Institute, Carnegie Mellon University, May 2004, 167pp.
- Applicant Amendment after Notice of Allowance under Rule 312, filed Aug. 25, 2008, in related case U.S. Appl. No. 11/695,944, 6pp.

(56)

References Cited

OTHER PUBLICATIONS

- Applicant Response to Office Action dated Aug. 18, 2006, in related case U.S. Appl. No. 11/398,174, filed Nov. 7, 2006, 8pp.
- Applicant Response to Office Action dated Aug. 21, 2006, in related case U.S. Appl. No. 11/403,756, filed Nov. 21, 2006, 52pp.
- Applicant Response to Office Action dated Oct. 29, 2007, in related case U.S. Appl. No. 11/695,944, filed Jan. 22, 2008, 6pp.
- Atmel 80C5X2 Core, <http://www.atmel.com>, 2006, 186pp.
- Bailey et al., "Complications of Laparoscopic Surgery," Quality Medical Publishers, Inc., 1995, 25pp.
- Bauer et al., "Case Report: Remote Percutaneous Renal Percutaneous Renal Access Using a New Automated Telesurgical Robotic System," *Telemedicine Journal and e-Health* 2001; (4): 341-347.
- Begos et al., "Laparoscopic Cholecystectomy: From Gimmick to Gold Standard," *J Clin Gastroenterol*, 1994; 19(4): 325-330.
- Calafiore et al., "Multiple Arterial Conduits Without Cardiopulmonary Bypass: Early Angiographic Results," *Ann Thorac Surg*, 1999; 67: 450-456.
- Camarillo et al., "Robotic Technology in Surgery: Past, Present and Future," *The American Journal of Surgery*, 2004; 188: 2S-15.
- Cavusoglu et al., "Telesurgery and Surgical Simulation: Haptic Interfaces to Real and Virtual Surgical Environments," In McLaughlin, M.L., Hespanha, J.P., and Sukhatme, G., editors. *Touch in virtual environments*, IMSC Series in Multimedia 2001, 28pp.
- Chanthasopeephan et al., (2003), "Measuring Forces in Liver Cutting: New Equipment and Experimental Results," *Annals of Biomedical Engineering* 31: 1372-1382.
- Choi et al., "Flexure-based Manipulator for Active Handheld Microsurgical Instrument," *Proceedings of the 27th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBS)*, Sep. 2005, 4pp.
- Dumpe et al., "Improving in Vivo Robot Vision Quality," from the *Proceedings of Medicine Meets Virtual Reality*, Long Beach, CA, Jan. 26-29, 2005. 1 pg.
- Examiner Interview Summary dated Nov. 30, 2006, in related case U.S. Appl. No. 11/398,174, 2pp.
- Faraz et al., "Engineering Approaches to Mechanical and Robotic Design for Minimally Invasive Surgery (MIS)," Kluwer Academic Publishers (Boston), 2000, 13pp.
- Fearing et al., "Wing Transmission for a Micromechanical Flying Insect," *Proceedings of the 2000 IEEE International Conference on Robotics & Automation*, Apr. 2000; 1509-1516.
- Fireman et al., "Diagnosing small bowel Crohn's disease with wireless capsule endoscopy," *Gut* 2003; 52: 390-392.
- Flynn et al., "Tomorrow's Surgery: micromotors and microbots for minimally invasive procedures," *Minimally Invasive Surgery & Allied Technologies*.
- Franzino, "The Laprotek Surgical System and the Next Generation of Robotics," *Surg Clin North Am*, 2003 83(6):.
- Fraulob et al., "Miniature assistance module for robot-assisted heart surgery," *Biomed. Tech.* 2002, 47 Suppl. 1, Pt. 1:12-15.
- Fukuda et al., "Micro Active Catheter System with Multi Degrees of Freedom," *Proceedings of the IEEE International Conference on Robotics and Automation*, May, 1994, pp. 2290-2295.
- Fuller et al., "Laparoscopic Trocar Injuries: A Report from a U.S. Food and Drug Administration (FDA) Center for Devices and Radiological Health (CDRH) Systematic Technology Assessment of Medical Products (STAMP) Committee," U.S. Food and Drug Administration, available at <http://www.fda.gov>;ov, Finalized: Nov. 7, 2003; Updated: Jun. 24, 2005, 11 pp.
- Guber et al., "Miniaturized Instrument Systems for Minimally Invasive Diagnosis and Therapy," *Biomedizinische Technik*. 2002, Band 47, Ergänzungsband 1.
- Tendick et al., "Applications of Micromechatronics in Minimally Invasive Surgery," *IEEE/ASME Transactions on Mechatronics*, 1998; 3(1): 34-42.
- U.S. Appl. No. 60/180,960, filed Feb. 2000.
- U.S. Appl. No. 60/956,032, filed Aug. 15, 2007.
- U.S. Appl. No. 60/983,445, filed Oct. 29, 2007.
- U.S. Appl. No. 60/990,062, filed Nov. 26, 2007.
- U.S. Appl. No. 60/990,076, filed Nov. 26, 2007.
- U.S. Appl. No. 60/990,086, filed Nov. 26, 2007.
- U.S. Appl. No. 60/990,106, filed Nov. 26, 2007.
- U.S. Appl. No. 60/990,470, filed Nov. 27, 2007.
- U.S. Appl. No. 61/025,346, filed Feb. 1, 2008.
- U.S. Appl. No. 61/030,588, filed Feb. 22, 2008.
- U.S. Appl. No. 61/030,617, filed Feb. 22, 2008.
- Way et al., (editors), "Fundamentals of Laparoscopic Surgery," Churchill Livingstone Inc., 1995, 14 pp.
- Wolfe et al., "Endoscopic Cholecystectomy: An analysis of Complications," *Arch. Surg.* Oct. 1991; 126: 1192-1196.
- Yu, BSN, RN, "M2ATM Capsule Endoscopy a Breakthrough Diagnostic Tool for Small Intestine Imaging," vol. 25, No. 1, *Gastroenterology Nursing*, pp. 24-27.
- International Search Report and Written Opinion of international application No. PCT/US2010/061137, mailed Feb. 11, 2011, 10 pp.
- Glukhovskiy et al., "The development and application of wireless capsule endoscopy," *Int. J. Med. Robot. Comput. Assist. Surgery*, 2004; 1(1): 114-123.
- Gong et al., "Wireless endoscopy," *Gastrointestinal Endoscopy* 2000; 51(6): 725-729.
- Hanly et al., "Value of the SAGES Learning Center in introducing new technology," *Surgical Endoscopy*, 2004; 19 (4): 477-483.
- Rentschler et al., "Mobile In Vivo Biopsy and Camera Robot," *Studies in Health and Informatics Medicine Meets Virtual Reality*, vol. 119., pp. 449-454, IOS Press, Long Beach, CA, 2006e
- Rentschler et al., "Mobile In Vivo Biopsy Robot," *IEEE International Conference on Robotics and Automation*, Orlando, Florida, May 2006, pp. 4155-4160.
- Rentschler et al., "In Vivo Robots for Laparoscopic Surgery," *Studies in Health Technology and Informatics—Medicine Meets Virtual Reality*, ISO Press, Newport Beach, CA, 2004a, 98: 316-322.
- Rosen et al., "Force Controlled and Teleoperated Endoscopic, Grasper for Minimally Invasive Surgery—Experimental Performance Evaluation," *IEEE Transactions of Biomedical Engineering*, Oct. 1999; 46(10): 1212-1221.
- Rosen et al., "Objective Laparoscopic Skills Assessments of Surgical Residents Using Hidden Markov Models Based on Haptic Information and Tool/Tissue Interactions," *Studies in Health Technology and Informatics—Medicine Meets Virtual Reality*, Jan. 2001, 7 pp.
- Rosen et al., "Spherical Mechanism Analysis of a Surgical Robot for Minimally Invasive Surgery—Analytical and Experimental Approaches," *Studies in Health Technology and Informatics—Medicine Meets Virtual Reality*, pp. 442-448, Jan. 2005.
- Ruurda et al., "Robot-Assisted surgical systems: a new era in laparoscopic surgery," *Ann R. Coll Surg Engl.*, 2002; 84: 223-226.
- Slatkin et al., "The Development of a Robotic Endoscope," *Proceedings of the 1995 IEEE International Conference on Robotics and Automation*, pp. 162-71, 1995.
- Smart Pill "Fantastic Voyage: Smart Pill to Expand Testing," <http://www.smartpilldiagnostics.com>, Apr. 13, 2005, 1 pg.
- Stiff et al., "Long-term Pain: Less Common After Laparoscopic than Open Cholecystectomy," *British Journal of Surgery*, 1994; 81: 1368-1370.
- Tendick et al. (1993), "Sensing and Manipulation Problems in Endoscopic Surgery: Experiment, Analysis, and Observation," *Presence* 2(1): 66-81.
- International Search report and Written Opinion from international application No. PCT/US2012/41911, mailed Mar. 13, 2013.
- International Search Report and Written Opinion from international application No. PCT/US12/46274, mailed Sep. 25, 2012.
- "International Search Report and Written Opinion from international application No. PCT/US07/14567, mailed Apr. 28, 2008, 19 pp."
- International Search Report and Written Opinion issued in PCT/US11/46809, mailed Dec. 8, 2011.
- Micron, <http://www.micron.com>, 2006, 1/4-inch VGA NTSC/PAL CMOS Digital Image Sensor, 98 pp.
- Midday Jeff et al., "Material Handling System for Robotic natural Orifice Surgery", *Proceedings of the 2011 Design of medical Devices Conference*, Apr. 12-14, 2011, Minneapolis, MN, 4 pages.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in PCT/
US2010/061137, mailed Feb. 11, 2011, 10 pages.

Midday, Jeff et al., "Material Handling System for Robotic natural
Orifice Surgery", Proceedings of the 2011 Design of medical Devices
Conference, Apr. 12-14, 2011, Minneapolis, MN, 4 pages.

Palm, William, "Rapid Prototyping Primer" May 1998 (revised Jul.
30, 2002) ([http://www.me.psu.edu/lamancusa/rapidpro/primer/
chapter2.htm](http://www.me.psu.edu/lamancusa/rapidpro/primer/chapter2.htm)).




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG.3




FIG. 4






FIG. 5






FIG. 8C

FIG. 8B

FIG. 8A




FIG. 9




FIG. 10






FIG. 11



UNSTABLE
FIG. 12A



STABLE
FIG. 12B




FIG. 13




FIG.14

1

MODULAR AND COOPERATIVE MEDICAL DEVICES AND RELATED SYSTEMS AND METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to Provisional Application No. 61/287,628, filed on Dec. 17, 2010, which is hereby incorporated herein by reference in its entirety.

GOVERNMENT SUPPORT

This invention was made with government support under Grant No. R21EB5663-2, awarded by the National Institute of Biomedical Imaging and Bioengineering within the National Institutes of Health. Accordingly, the government has certain rights in the invention.

TECHNICAL FIELD

The embodiments disclosed herein relate to various medical devices and related components, including robotic and/or in vivo medical devices and related components. Certain embodiments include various modular medical devices, including modular in vivo and/or robotic devices. Other embodiments relate to modular medical devices in which the various modular components are segmented components or components that are coupled to each other. Further embodiment relate to methods of operating the above devices, including methods of using various of the devices cooperatively.

BACKGROUND

Invasive surgical procedures are essential for addressing various medical conditions. When possible, minimally invasive procedures such as laparoscopy are preferred.

However, known minimally invasive technologies such as laparoscopy are limited in scope and complexity due in part to 1) mobility restrictions resulting from using rigid tools inserted through access ports, and 2) limited visual feedback. Known robotic systems such as the da Vinci® Surgical System (available from Intuitive Surgical, Inc., located in Sunnyvale, Calif.) are also restricted by the access ports, as well as having the additional disadvantages of being very large, very expensive, unavailable in most hospitals, and having limited sensory and mobility capabilities.

There is a need in the art for improved surgical methods, systems, and devices.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a perspective view of a modular medical device, according to another embodiment.

FIG. 1B is a perspective bottom view of the device of FIG. 1A.

FIG. 2A is a perspective top view of the device of FIG. 1A.

FIG. 2B is a perspective side view of the device of FIG. 1A.

FIG. 2C is a perspective close-up view of a portion of the device of FIG. 1A.

FIG. 2D is a perspective view of another modular medical device, according to a further embodiment.

FIG. 3 is a perspective bottom view of the device of FIG. 1A.

FIG. 4 is a perspective side view of the device of FIG. 1A.

FIG. 5 is a top view of the device of FIG. 1A.

2

FIG. 6 is a perspective view of modular medical device control and visualization system, according to one embodiment.

FIG. 7 is a perspective view of a modular medical device, according to one embodiment.

FIGS. 8A-8C are schematic representations of various magnetic attachment mechanisms, according to various embodiments.

FIG. 9 is a perspective view of the device of FIG. 1A.

FIG. 10 is a schematic representation of various forces associated with the device of FIG. 1A, according to one embodiment.

FIG. 11 is a schematic representation of various forces associated with the device of FIG. 1A, according to another embodiment.

FIG. 12A is a schematic representation of various forces associated with a robotic device.

FIG. 12B is a schematic representation of various forces associated with another robotic device, according to one embodiment.

FIG. 13 is a schematic representation of various forces associated with another robotic device, according to another embodiment.

FIG. 14 is a schematic representation of various forces associated with yet another robotic device, according to a further embodiment.

DETAILED DESCRIPTION

The various systems and devices disclosed herein relate to devices for use in medical procedures and systems. More specifically, various embodiments relate to various modular or combination medical devices, including modular in vivo and robotic devices and related methods and systems, while other embodiments relate to various cooperative medical devices, including cooperative in vivo and robotic devices and related methods and systems.

It is understood that the various embodiments of modular and cooperative devices and related methods and systems disclosed herein can be incorporated into or used with any other known medical devices, systems, and methods.

For example, the various embodiments disclosed herein may be incorporated into or used with any of the medical devices and systems disclosed in copending U.S. application Ser. No. 12/192,779 (filed on Aug. 15, 2008 and entitled "Modular and Cooperative Medical Devices and Related Systems and Methods"), Ser. No. 11/932,441 (filed on Oct. 31, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/695,944 (filed on Apr. 3, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/947,097 (filed on Nov. 27, 2007 and entitled "Robotic Devices with Agent Delivery Components and Related Methods"), Ser. No. 11/932,516 (filed on Oct. 31, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/766,683 (filed on Jun. 21, 2007 and entitled "Magnetically Coupleable Robotic Devices and Related Methods"), Ser. No. 11/766,720 (filed on Jun. 21, 2007 and entitled "Magnetically Coupleable Surgical Robotic Devices and Related Methods"), Ser. No. 11/966,741 (filed on Dec. 28, 2007 and entitled "Methods, Systems, and Devices for Surgical Visualization and Device Manipulation"), Ser. No. 12/171,413 (filed on Jul. 11, 2008 and entitled "Methods and Systems of Actuation in Robotic Devices"), 60/956,032 (filed on Aug. 15, 2007), 60/983,445 (filed on Oct. 29, 2007), 60/990,062 (filed on Nov. 26, 2007), 60/990,076 (filed on Nov. 26, 2007), 60/990,086 (filed on Nov. 26, 2007), 60/990,106 (filed on Nov. 26, 2007), 60/990,470 (filed on Nov. 27, 2007), 61/025,346 (filed on Feb. 1, 2008), 61/030,

588 (filed on Feb. 22, 2008), and 61/030,617 (filed on Feb. 22, 2008), all of which are hereby incorporated herein by reference in their entireties.

Certain device implementations disclosed in the applications listed above can be positioned within a body cavity of a patient, including certain devices that can be positioned against or substantially adjacent to an interior cavity wall, and related systems. An “in vivo device” as used herein means any device that can be positioned, operated, or controlled at least in part by a user while being positioned within a body cavity of a patient, including any device that is positioned substantially against or adjacent to a wall of a body cavity of a patient, further including any such device that is internally actuated (having no external source of motive force), and additionally including any device that may be used laparoscopically or endoscopically during a surgical procedure. As used herein, the terms “robot,” and “robotic device” shall refer to any device that can perform a task either automatically or in response to a command.

Certain implementations disclosed herein relate to “combination” or “modular” medical devices that can be assembled in a variety of configurations. For purposes of this application, both “combination device” and “modular device” shall mean any medical device having modular or interchangeable components that can be arranged in a variety of different configurations. The modular components and combination devices disclosed herein also include segmented triangular or quadrangular-shaped combination devices. These devices, which are made up of modular components (also referred to herein as “segments”) that are connected to create the triangular or quadrangular configuration, can provide leverage and/or stability during use while also providing for substantial payload space within the device that can be used for larger components or more operational components. As with the various combination devices disclosed and discussed above, according to one embodiment these triangular or quadrangular devices can be positioned inside the body cavity of a patient in the same fashion as those devices discussed and disclosed above.

FIGS. 1A-7 depict a multi-segmented medical device 10, in accordance with one implementation. According to one embodiment, the device 10 is a robotic device 10 and further can be an in vivo device 10. This device embodiment 10 as shown includes three segments 12A, 12B, 14. Segments 12A and 12B are manipulator segments, while segment 14 is a command and imaging segment. Alternatively, the three segments can be any combination of segments with any combination of components and capabilities. For example, according to an alternative embodiment, the device could have one manipulator segment, one command and imaging segment, and a sensor segment. In a further alternative, the various segments can be any type of module, including any of those modules described above with respect to other modular components discussed herein.

As best shown in FIGS. 1A and 1B, segments 12A, 12B are rotatably coupled with the segment 14 via joints or hinges 16A, 16B. More specifically, segment 12A is rotatable relative to segment 14 about joint 16A around an axis as indicated by arrow B in FIG. 1B, while segment 12B is rotatable relative to segment 14 about joint 16B around an axis as indicated by arrow C in FIG. 1B.

In accordance with one embodiment, the device 10 has at least two configurations. One configuration is an extended or insertion configuration as shown in FIG. 1A in which the three segments 12A, 12B, 14 are aligned along the same axis. The other configuration is a triangle configuration as shown in FIG. 1B in which the manipulator segments 12A, 12B are

each coupled to the segment 14 via the joints 16A, 16B and further are coupled to each other at a coupleable connection 18 at the ends of the segments 12A, 12B opposite the joints 16A, 16B.

As best shown in FIG. 2A, each of the manipulator segments 12A, 12B in this particular embodiment has an operational arm 20, 22 (respectively). Each arm 20, 22 is moveably coupled to its respective segment 12A, 12B at a joint 24A, 24B (respectively) (as best shown in FIG. 4). Further, segment 14 has a pair of imaging components (each also referred to herein as a “camera”) 26A, 26B (as best shown in FIG. 3).

In one embodiment, each arm 20, 22 is configured to rotate at its joint 24A, 24B in relation to its segment 12A, 12B to move between an undeployed position in which it is disposed within its segment 12A, 12B as shown in FIG. 1B and a deployed position as shown in FIG. 2A. In one example, arm 20 is rotatable relative to segment 12A about joint 24A in the direction shown by G in FIG. 4, while arm 22 is rotatable relative to segment 12B about joint 24B in the direction shown by H in FIG. 4. Alternatively, the arms 20, 22 are moveable in relation to the segments 12A, 12B in any known fashion and by any known mechanism.

According to one embodiment as best shown in FIG. 2A, each arm 20, 22 has three components: a proximal portion 20A, 22A, a distal portion 20B, 22B, and an operational component 20C, 22C coupled with the distal portion 20B, 22B, respectively. In this embodiment, the distal portion 20B, 22B of each arm 20, 22 extends and retracts along the arm axis in relation to the proximal portion 20A, 22A while also rotating around that axis in relation to the proximal portion 20A, 22A. That is, distal portion 20B of arm 20 can move back and forth laterally as shown by the letter K in FIG. 4 and further can rotate relative to the proximal portion 20A as indicated by the letter J, while distal portion 22B of arm 22 can move back and forth laterally as shown by the letter L in FIG. 4 and further can rotate relative to the proximal portion 22A as indicated by the letter I.

In accordance with one implementation, the operational components 20C, 22C (also referred to herein as “end effectors”) depicted in FIG. 2A are a grasper 20C and a cautery hook 22C. It is understood that the operational component(s) used with the device 10 or any embodiment herein can be any known operational component for use with a medical device, including any of the operational components discussed above with other medical device embodiments and further including any operational components described in the applications incorporated above. Alternatively, only one of the two arms 20, 22 has an operational component. In a further alternative, neither arm has an operational component.

Alternatively, each arm 20, 22 comprises one unitary component or more than two components. It is further understood that the arms 20, 22 can be any kind of pivotal or moveable arm for use with a medical device which may or may not have operational components coupled or otherwise associated with them. For example, the arms 20, 22 can have a structure or configuration similar to those additional arm embodiments discussed elsewhere herein or in any of the applications incorporated above. In a further alternative, the device 10 has only one arm. In a further alternative, the device 10 has no arms. In such alternative implementations, the segment(s) not having an arm can have other components associated with or coupled with the segment(s) such as sensors or other types of components that do not require an arm for operation.

As discussed above, the segment 14 of the embodiment depicted in FIG. 3 has a pair of cameras 26A, 26B. Alternatively, the segment 14 can have a single camera or more than two cameras. It is understood that any known imaging com-

5

ponent for medical devices, including in vivo devices, can be used with the devices disclosed herein and further can be positioned anywhere on any of the segments or on the arms of the devices.

In a further embodiment, the segment **14** as best shown in FIG. **3** can also include a lighting component **28**. In fact, the segment **14** has four lighting components **28**. Alternatively, the segment **14** can have any number of lighting components **28** or no lighting components. In a further alternative, the device **10** can have one or more lighting components positioned elsewhere on the device, such as one or both of segments **12A**, **12B** or one or more of the arms, etc.

In accordance with a further embodiment as best shown in FIGS. **1B** and **3**, each of the segments **12A**, **12B**, **14** has two cylindrical components—an outer cylindrical component and an inner cylindrical component—that are rotatable in relation to each other. More specifically, the segment **12A** has an outer cylindrical component **30A** and an inner cylindrical component **30B** that rotates relative to the outer component **30A** around an axis indicated by arrow **F** in FIG. **3**. Similarly, the segment **12B** has an outer cylindrical component **32A** and an inner cylindrical component **32B** that rotates relative to the outer component **32A** around an axis indicated by arrow **E** in FIG. **3**. Further, the segment **14** has an outer cylindrical component **34A** and an inner cylindrical component **34B** that rotates relative to the outer component **34A** around an axis indicated by arrow **D** in FIG. **3**.

In use, the embodiments having rotatable cylindrical components as described in the previous paragraph can provide for enclosing any arms, cameras, or any other operational components within any of the segments. Further, any segment having such rotatable components provide for two segment configurations: an open configuration and a closed configuration. More specifically, segment **12A** has an outer cylindrical component **30A** with an opening **36** as shown in FIG. **3** through which the arm **20** can move between its deployed and undeployed positions. Similarly, segment **12B** has an outer cylindrical component **32A** with an opening **38** as shown in FIG. **3** through which the arm **22** can move between its deployed and undeployed positions. Further, segment **14** has an outer cylindrical component **34A** with an opening **40** as shown in FIG. **3** through which the imaging component(s) **26A**, **26B** can capture images of a procedural or target area adjacent to or near the device **10**.

FIG. **1B** depicts the segments **12A**, **12B**, **14** in their closed configurations. That is, each of the inner cylindrical components **30B**, **32B**, **34B** are positioned in relation to the respective outer cylindrical component **30A**, **32A**, **34A** such that each opening **36**, **38**, **40**, respectively, is at least partially closed by the inner component **30B**, **32B**, **34B** such that the interior of each segment **12A**, **12B**, **14** is at least partially inaccessible from outside the segment.

More specifically, in the closed position, inner cylindrical component **30B** of segment **12A** is positioned in relation to outer cylindrical component **30A** such that the arm **20** is at least partially enclosed within the segment **12A**. According to one embodiment, the inner cylindrical component **30B** is configured such that when it is in the closed position as shown in FIG. **1B**, it closes off the opening **36** entirely. In a further embodiment, the inner cylindrical component **30B** in the closed position fluidically seals the interior of the segment **12A** from the exterior.

Similarly, in the closed position, inner cylindrical component **32B** of segment **12B** is positioned in relation to the outer cylindrical component **32A** such that the arm **22** is at least partially enclosed within the segment **12B**. According to one embodiment, the inner cylindrical component **32B** is config-

6

ured such that when it is in the closed position as shown in FIG. **1B**, it closes off the opening **38** entirely. In a further embodiment, the inner cylindrical component **32B** in the closed position fluidically seals the interior of the segment **12B** from the exterior.

Further, in the closed position, inner cylindrical component **34B** of segment **14** is positioned in relation to the outer cylindrical component **34A** such that the imaging component(s) is not positioned within the opening **40**. According to one embodiment, the inner cylindrical component **34B** is configured such that when it is in the closed position as shown in FIG. **1B**, the imaging component(s) and any lighting component(s) are completely hidden from view and not exposed to the exterior of the segment **14**. In a further embodiment, the inner cylindrical component **34B** in the closed position fluidically seals the interior of the segment **14** from the exterior.

In contrast, FIGS. **2A** and **3** depict the segments **12A**, **12B**, **14** in their open configurations. In these configurations, each of the inner cylindrical components **30B**, **32B**, **34B** are positioned such that the openings **36**, **38**, **40** are open.

In use, according to one embodiment, the inner cylindrical components **30B**, **32B**, **34B** can thus be actuated to move between their closed and their open positions and thereby convert the device **10** between a closed or non-operational configuration (in which the operational components such as the arms **20**, **22** and/or the imaging components **26** and/or the lighting components **28** are inoperably disposed within the segments **12A**, **12B**, **14**) and an open or operational configuration (in which the operational components are accessible through the openings **36**, **38**, **40** and thus capable of operating). Thus, according to one implementation, the device **10** can be in its closed or non-operational configuration during insertion into a patient's body and/or to a target area and then can be converted into the open or operational configuration by causing the inner cylindrical components **30B**, **32B**, **34B** to rotate into the open configurations.

Alternatively, one or more or all of the segments do not have inner and outer components that rotate in relation to each other.

It is understood that the various embodiments of the device **10** disclosed herein include appropriate actuation components to generate the force necessary to operate the arms and/or the rotatable cylinders in the segments. In one embodiment, the actuation components are motors. For example, segment **12A** has a motor (not shown) operably coupled with the arm **20** and configured to power the movements of the arm **20**. Similarly, segment **12B** also has a motor (not shown) operably coupled with the arm **22** and configured to power the movements of the arm **22**. In further embodiments, each of the segments **12A**, **12B**, **14** also have motors (not shown) operably coupled to one or both of the inner and outer cylinder of each segment to power the rotation of the cylinders in relation to each other. In one embodiment, each segment can have one motor to power all drivable elements (arms, cylinders, etc.) associated with that segment. Alternatively, a separate motor can be provided for each drivable element.

In one embodiment, the joints **16A**, **16B** are configured to urge the segments **12A**, **12B** from the insertion configuration of FIG. **1A** into the triangular configuration of FIG. **1B**. That is, the joints **16A**, **16B** have torsion springs or some other known mechanism for urging the segments **12A**, **12B** to rotate around their joints **16A**, **16B**. For example, FIG. **2C** depicts one embodiment in which the joint **16A** has torsion springs **42** that are configured to urge segment **12A** toward the triangular configuration.

In use, in accordance with one implementation, the device **10** in the insertion configuration as shown in FIG. **1A** can be

inserted into a patient's body through an incision, a trocar port, or natural orifice in the direction indicated by arrow A. Alternatively, the device **10** can be inserted in the other direction as well. After insertion and/or as the device **10** enters the target area or procedural area in the patient's body, the joints **16A**, **16B** with the torsion springs (or other standard mechanisms) urge the segments **12A**, **12B** from their insertion position to their triangular position. As the segments **12A**, **12B** contact each other to form joint **18**, the two segments are coupled together with mating components that semi-lock the segments **12A**, **12B** together. That is, the two segments **12A**, **12B** can only be separated at the joint **18** by a force sufficient to overcome the semi-lock. Any such known mating component or coupling component, including any mechanical or magnetic mating component(s), can be incorporated into the device **10** for this purpose.

Thus, according to one embodiment, the device **10** can be in its insertion configuration during insertion into the patient. As the device **10** enters the target cavity and exits the port or incision, the torsion springs or other mechanisms at the joints **16A**, **16B** cause the two segments **12A**, **12B** to move toward each other until they couple to form the triangular configuration. The device **10** can then be attached to the abdominal wall by some method such as an external magnetic handle. Alternatively, the device **10** can be positioned anywhere in the cavity of the patient as desired by the user. The device **10** is then used to perform some sort of procedure.

Subsequently, when the procedure is complete, the device **10** can be retracted from the cavity. To do so, the surgeon uses a grasping or retrieval tool such as a Endo Babcock grasper made by Covidien in Mansfield, Mass., to attach to or otherwise grasp the ball **44** at the joint **18** and apply sufficient force to overcome the semi-lock of the joint **18**. Alternatively, any retrieval component can be positioned at the end of segment **12A** or elsewhere on the device **10** for grasping or otherwise coupling to for purposes of removing the device **10** from the patient's body. When the coupling of the semi-lock is overcome, the force urges the segments **12A**, **12B** away from each other, thereby making it possible for the surgeon to pull the ball **44** through a port or incision and out of the patient, thereby forcing the device **10** into its insertion configuration.

The multiple segments provided in the various embodiments of the device disclosed herein result in significantly more payload space than a single cylindrical body. The increased payload space results in increased capabilities for the device in the form of more, bigger, or more complex operational components, more, bigger, or more complex motors, magnets (as described below) and other similar benefits relating to the availability of more space for more, bigger, or more complex components. For example, FIG. **2B** depicts a side view of the device **10** according to one embodiment that shows the payload space available in segment **12B**. More specifically, segment **12B** and its coupled arm **22** have payload spaces **46**, **48**, **50**, **52**, **54** that can be used to accommodate motors, operational components, sensors, magnets (as described below) or any other type of component that could be useful for a procedural device. Similarly, each segment **12A**, **12B**, **14** can have such payload spaces. In addition, the segments **12A**, **12B**, **14** allow for maximization of the payload space available across the segments **12A**, **12B**, **14** by distributing the components such as motors, operational components, or magnets to maximize their effectiveness while minimizing the amount of space required by each such component. For example, it might maximize effectiveness of the device **10** while minimizing the utilized space to have one large motor in one segment that provides force for operation of components in more than one segment.

It is understood that various embodiments of the segmented devices disclosed herein are in vivo devices that can be inserted into and positioned within a patient's body to perform a procedure. In one embodiment, an external controller is also provided that transmits signals to the device **10** to control the device **10** and receives signals from the device **10**. In one embodiment, the controller communicates with the device **10** wirelessly. Alternatively, the controller and the device **10** are coupled via a flexible communication component such as a cord or wire (also referred to as a "tether") that extends between the device **10** and the controller.

It is also understood that various embodiments of the devices disclosed herein can be used in conjunction with known attachment components to attach or otherwise position the device near, against, or adjacent to an interior cavity wall inside the patient. In one embodiment, the attachment components are one or more magnets, disposed within the device, that communicate magnetically with one or more magnets positioned outside the patient's body. The device magnets can be positioned on or in the device in any suitable configuration. For example, the device magnets in one embodiment can be positioned within the segments **12A**, **12B**, **14** at positions **56**, **58**, **60** as shown in FIG. **5**. It is understood that the external magnets can be used outside the body to position and/or move the device **10** inside the body.

It is further understood that various embodiments of the devices disclosed herein can be used in conjunction with known visualization and control components, such as the console **70** depicted in FIG. **6**. The console **70** has a display **72** and magnets **74** and is positioned outside the patient such that the magnets **74** can be in magnetic communication with the device magnets (not shown) disposed within or otherwise coupled with the device **10**. The console **70** can be used to move the device **10** by moving the console **70** outside the body such that the device **10** is urged to move inside the body, because the console magnets **10** are magnetically coupled with the device magnets (not shown) within the device **10** such that the device **10** remains substantially fixed in relation to the console **70**. In addition, it is understood that the triangular (and quadrangular) devices disclosed and described in relation to FIGS. **1A-7** can be used in conjunction with any of the external controller or visualization components and systems disclosed and discussed above and in the applications incorporated above.

The segmented device **10**, according to one embodiment, provides greater stability and operability for the device **10** in comparison to other in vivo devices. That is, a device having more than one segment such as device **10** provides for a configuration with a larger "footprint" for the device **10**, thereby resulting in greater stability and leverage during use of the device **10**. For example, the device **10** with the triangular configuration in FIG. **6** that is urged against the interior cavity wall of the patient by the console magnets **74** has greater stability and leverage in comparison to a device that has a smaller "footprint." That is, the device **10** can have at least three magnets (not shown) disposed at the three corners of the triangular configuration such that when the device **10** is magnetically positioned against the interior cavity wall, the arms of the device **10** can apply greater force to the target tissues while maintaining the position of the device **10** than a corresponding single cylindrical device body.

It is understood that the device embodiments disclosed herein are not limited to a triangular configuration. FIG. **7** depicts a device **80** having a quadrangular configuration with four segments. Similarly, devices are contemplated herein having any number of segments ranging from two segments to any number of segments that can be used for a device that

can be positioned inside a patient's body. For example, a device incorporating the components and structures disclosed herein could have six or eight segments or more.

Several methods of attachment are possible for the triangle robot. A mechanical rod or elongate member having a cross-section of any shape or configuration could be used to support the robot. The elongate member could be rigid or flexible. One example of a rod **43** coupled to a robot **41** is depicted in FIG. 2D, according to one embodiment. The robot could also be placed at the end of other instruments and manual tools as well as at the end of another robot.

In other embodiments, including some discussed above, the attachment mechanism includes magnets. Attaching the robot with magnets can be accomplished in many different ways; some are shown in FIGS. 8A-8C. This can include a magnet external to the patient that is placed against the abdominal wall. This magnet then interacts with the robot to support the robot and hold it in place. The external magnet can interact with a high permeability material on the inside of the patient and attached to the robot as shown in FIG. 8A. The roles could also be reversed and the high permeability material could also be external to the patient and the magnet could be internal.

The external magnet can also interact with a second magnet inside the patient and attached to the robot. This can be done so that opposite poles of the magnet attract using a single pole on each magnet (as shown in FIG. 8B) or by using both poles on each magnet (as shown in FIG. 8C).

The magnet (or high permeability material) associated with the robot does not even need to be attached to the robot. It only needs to interact in such a way as to create a force to stabilize the robot (this stability is described below). For example, when a piece of paper is attached to a refrigerator with a magnet, the magnet is not attached to the paper, but it does create a force that stabilizes the paper on the refrigerator. A similar approach could be used with the robot.

The methods of magnetic attachment described above can be used in many different combinations. For example, any number of magnets (0, 1, 2, 3, . . .) can be used to attach the robot. One obvious approach would be to place a magnet in each corner (or in each segment) of the triangle of the robot, with a trio of external magnets being used external to the patient. However, the triangle (or other open or closed polygons (from 2 sides on up)) is especially well suited to be supported by several different combinations of magnets. For example, a single magnet can be used inside the triangle since the shape of the triangle will provide multi axis support to react the force applied by this single magnet. This is further described in the next section. A "V" configuration or other polygon could give similar support.

Certain embodiments disclosed herein relate to maximization of stability of the various device embodiments while positioned inside the patient's body. Consider the triangle configuration of the in vivo robot **10** described above in detail and shown in FIG. 9. This is one possible attachment method for the robot. Here a single magnet **90** is attached to the robot **10** so that it is attracted to a magnet **92** on the outside of the patient. The magnet **90** on the robot produces a force on the robot **10** in the upward direction.

A simplified Free Body Diagram (FBD) showing a simplified interpretation of the reaction forces is shown in FIG. 10. Here, the magnet **90** produces an upward force on the body of the robot **10** (assumed rigid) F_m . The weight of the robot **10**, W , is also shown acting at the center of mass of the robot **10**. Each corner of the robot is labeled A, B, and C and reaction forces are shown at each corner (F_A , F_B , F_C). These reaction forces could occur along the length of each side in any dis-

tribution depending on the shape of the robot, stiffness of the abdominal wall, and other factors. However, for simplicity, these reaction forces are assumed to be lumped at each corner. Finally, end effector forces (F_{RH} , F_{LH}) are shown as the robot **10** applies forces to the tissue being manipulated during surgery. Also, any external applied moments or dynamic loads would also need to be included. This analysis could be extended to other robot configurations (e.g. a square robot with three manipulators), as will be described in further detail below.

The stability of the robot **10** in FIG. 10 created by the single magnet **90** can be determined using various mathematical techniques. One example of such techniques is set forth in Papadopoulos, E. and Rey, D., "A New Measure of Tipover Stability Margin for Mobile Manipulators," Proc. of the IEEE International Conference on Robotics and Automation, Minneapolis, Minn., April 1996 (which relates to the stability mathematics of large off-road vehicles). Similar techniques can be used to determine the stability of the robot **10**. The simplified version of this analysis is to take sum moments from all external forces (and moments) about each contact line for the robot. A first step in this example would be to sum the moments about the contact line AB (in FIG. 10). If the resulting moment "pushes" the robot into the abdominal wall (such as would be caused by a large magnet force), the configuration is stable and the robot will not fall. If the resulting moment "peels" the robot away from the abdominal wall (such as would be caused by a small magnet force and a large robot weight), the robot would be unstable and would fall away from the abdominal wall. This would then need to be repeated for all contact lines (BC and CA in our example).

The above analysis shows that a single magnet can be used to hold the robot **10** in place.

A simplified example is shown in FIG. 11. Here, the robot **10** is assumed mass-less and is not applying forces with its end effectors. It can be clearly seen that a large magnetic force, F_M , produces moment about the line AB that will cause the robot to rotate into the abdominal wall and therefore make a stable configuration for the robot. The same is true about lines BC and CA.

This example in FIG. 11 is further exemplified by the two possible configurations shown in FIGS. 12A and 12B. In this situation, the robot **94** in FIG. 12A could be created by simply using one segment of the triangle configuration as shown back in FIG. 10 (with attachment magnets at A and B). In FIG. 12A, there are two attachment points (A and B) that hold the robot **94** to the upper abdominal wall (one segment). When the robot's end effector (or hand) **96** applies a force in an arbitrary direction, there will be non-zero moments about the contact line AB. This will cause the robot **94** to rotate about the line AB and could result in some instability.

In contrast, FIG. 12 depicts a device **98** that contains additional structure as represented by point C. In this embodiment, hand forces (F_{Hand}) that produce a moment about the contact line AB can be balanced by a moment created by the reaction force at point C (F_C). Similarly, moments can be balanced and a stable configuration produced when other lines of contact are considered (BC & AC in this case, with other possibilities described below). Again, discrete points (A, B, & C) are described to simplify the description, but any line segment (AB for example) could be a continuous line of contact.

This stability based on one magnet can be recreated in several robot configurations. For example, FIG. 13 shows a configuration similar to FIG. 11, but the "triangle" in FIG. 13 is in an "open" configuration **100** in which point A now becomes two points (A and A'). This configuration **100** will

11

also produce stability if the moments about all contact lines (AB, BC, CA' and A'A) "pushes" the robot into the abdominal wall rather than "peeling" it away.

FIG. 14 depicts another example of a multi-sided polygon 102 that uses a single magnet for stable attachment. The same analysis used above applies here and can be used to show that the robot 102 can be stable. In addition, the stability provided by a single magnet as described with the configurations discussed above can also occur for shapes other than polygons. For example, a "V" or "T" configuration could be used. The shapes could be open or closed.

It is understood that the concept of robot reaction forces (e.g. F_A , F_B , etc) occurring at a single point is an oversimplification for purposes of this discussion. These forces can occur at a continuum across any segment of any portion of the robot (or at discrete points).

In certain embodiments, different combinations of magnet "types" can also be used. For example, the robot could have a magnet at one corner of the robot and two pieces of high permeability material at the other two corners (or sides). Or the robot could have two magnets and one piece of high permeability material, or other combinations.

While multiple embodiments are disclosed, still other embodiments of the present invention will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodiments of the invention. As will be realized, the invention is capable of modifications in various obvious aspects, all without departing from the spirit and scope of the present invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

Although the present invention has been described with reference to preferred embodiments, persons skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

What is claimed is:

1. A segmented medical device, the system comprising:

- (a) a first body segment configured to be disposed inside a cavity of a patient, the segment comprising
 - (i) a first operational component associated with the first body segment; and
 - (ii) a first mating component at a first end of the first body segment;
- (b) a second body segment configured to be disposed inside the cavity of the patient, the segment comprising
 - (i) a second operational component associated with the second body segment; and
 - (ii) a first pivotal coupling at a first end of the second body segment, whereby the second body segment is pivotally coupled to a second end of the first body segment;
- (c) a third body segment configured to be disposed inside the cavity of the patient, the segment comprising
 - (i) a third operational component associated with the third body segment;
 - (ii) a second pivotal coupling at a first end of the third body segment, whereby the third body segment is pivotally coupled to a second end of the second body segment; and
 - (iii) a second mating component at a second end of the third body segment, the second mating component configured to be coupleable with the first mating component; and
- (d) an attachment component associated with the segmented medical device, wherein the attachment component comprises a rod coupled to the segmented medical

12

device, wherein the rod is configured to extend from the segmented medical device out of the cavity of the patient.

2. The segmented medical device of claim 1, wherein the device is configured to move between an open position in which the first and second mating components are not coupled together and a closed position in which the first and second mating components are coupled.

3. The segmented medical device of claim 2, wherein the first, second, and third body segments define an opening in the closed position.

4. The segmented medical device of claim 3, wherein the attachment component is disposed in the opening.

5. The segmented medical device of claim 1, wherein the first pivotal coupling and the second pivotal coupling comprise tensioned components configured to urge the first mating component and the second mating component toward each other.

6. The segmented medical device of claim 1, wherein the first body segment comprises a first inner cylindrical component disposed within a first outer cylindrical component, wherein the first inner cylindrical component is rotatable in relation to the first outer cylindrical component.

7. The segmented medical device of claim 6, wherein the first inner cylindrical component comprises a first inner opening and the first outer cylindrical component comprises a first outer opening, wherein the first inner cylindrical component and the first outer cylindrical component are rotatable such that the first inner opening and first outer opening align, thereby providing access to an interior portion of the first inner cylindrical component.

8. The segmented medical device of claim 7, wherein the first operational component is configured to move between an undeployed position disposed within the interior portion of the first inner cylindrical component and a deployed position in which a portion of the first operational component is disposed outside of the first inner cylindrical component through the first inner opening and first outer opening.

9. A segmented medical device, the system comprising:

- (a) a first body segment configured to be disposed inside a cavity of a patient, the segment comprising
 - (i) a first operational component associated with the first body segment; and
 - (ii) a first mating component at a first end of the first body segment;
- (b) a second body segment configured to be disposed inside the cavity of the patient, the segment comprising
 - (i) a second operational component associated with the second body segment; and
 - (ii) a first pivotal coupling at a first end of the second body segment, whereby the second body segment is pivotally coupled to a second end of the first body segment;
- (c) a third body segment configured to be disposed inside the cavity of the patient, the segment comprising
 - (i) a third operational component associated with the third body segment;
 - (ii) a second pivotal coupling at a first end of the third body segment, whereby the third body segment is pivotally coupled to a second end of the second body segment; and
 - (iii) a second mating component at a second end of the third body segment, the second mating component configured to be coupleable with the first mating component; and
- (d) an attachment component disposed in a substantially central location when the segmented medical device is in

13

a closed configuration in which the first and second mating components are coupled,
 wherein the segmented medical device is configured to move between the closed configuration and an open configuration in which the first and second mating components are not coupled together.

10. The segmented medical device of claim **2**, wherein the first, second, and third body segments define an opening in the closed position, wherein the attachment component is disposed in the substantially central location in the opening.

11. The segmented medical device of claim **9**, wherein the attachment component comprises a single magnet disposed in a substantially central location when the segmented medical device is in a closed configuration.

12. The segmented medical device of claim **1**, wherein

(a) the first body segment comprises a first inner cylindrical component disposed within a first outer cylindrical component, wherein the first inner cylindrical component is rotatable in relation to the first outer cylindrical component;

(b) the second body segment comprises a second inner cylindrical component disposed within a second outer cylindrical component, wherein the second inner cylindrical component is rotatable in relation to the second outer cylindrical component; and

(c) the third body segment comprises a third inner cylindrical component disposed within a third outer cylindrical component, wherein the third inner cylindrical component is rotatable in relation to the third outer cylindrical component.

13. The segmented medical device of claim **12**, wherein

(a) the first inner cylindrical component comprises a first inner opening and the first outer cylindrical component comprises a first outer opening, wherein the first inner cylindrical component and the first outer cylindrical component are rotatable such that the first inner opening and first outer opening align, thereby providing access to an interior portion of the first inner cylindrical component;

14

(b) the second outer cylindrical component comprises a second outer opening, wherein the second inner cylindrical component and the second outer cylindrical component are rotatable such that the second operational component is accessible through the second outer opening; and

(c) the third inner cylindrical component comprises a third inner opening and the third outer cylindrical component comprises a third outer opening, wherein the third inner cylindrical component and the third outer cylindrical component are rotatable such that the third inner opening and third outer opening align, thereby providing access to an interior portion of the third inner cylindrical component.

14. The segmented medical device of claim **13**, wherein

(a) the first operational component is configured to move between an undeployed position disposed within the interior portion of the first inner cylindrical component and a deployed position in which a portion of the first operational component is disposed outside of the first inner cylindrical component through the first inner opening and first outer opening; and

(b) the third operational component is configured to move between an undeployed position disposed within the interior portion of the third inner cylindrical component and a deployed position in which a portion of the third operational component is disposed outside of the third inner cylindrical component through the third inner opening and third outer opening.

15. The segmented device of claim **14**, wherein the first operational component comprises a grasper and the second operational component comprises a cautery hook.

16. The segmented device of claim **1**, wherein the second operational component comprises at least one camera or at least one light.

* * * * *