## Ensemble-based machine learning algorithms for classifying breast tissue based on electrical impedance spectroscopy

Sam Matiur Rahman<sup>1</sup>, Md Asraf Ali<sup>1</sup>, Omar Altwijri<sup>2</sup>, Mahdi Alqahtani<sup>2</sup>, Nasim Ahmed<sup>3</sup>, Nizam U. Ahamed<sup>4</sup>

<sup>1</sup> Department of Software Engineering, Daffodil International University, Dhaka, Bangladesh <sup>2</sup> Biomedical Technology Department, College of Applied Medical Sciences, King Saud University, Riyadh, Saudi Arabia

<sup>3</sup> School of Engineering and Advanced Technology, Massey University, Auckland, New Zealand <sup>4</sup> Faculty of Manufacturing Engineering, University Malaysia Pahang, Pahang, Malaysia

## ABSTRACT

The initial identification of breast cancer and the prediction of its category have become a requirement in cancer research because they can simplify the subsequent clinical management of patients. The application of artificial intelligence techniques (e.g., machine learning and deep learning) in medical science is becoming increasingly important for intelligently transforming all available information into valuable knowledge. Therefore, we aimed to classify six classes of freshly excised tissues from a set of electrical impedance measurement variables using five ensemble-based machine learning (ML) algorithms, namely, the random forest (RF), extremely randomized trees (ERT), decision tree (DT), gradient boosting tree (GBT) and AdaBoost (Adaptive Boosting) (ADB) algorithms, which can be subcategorized as bagging and boosting methods. In addition, the ranked order of the variables based on their importance differed across the ML algorithms. The results demonstrated that the three bagging ensemble ML algorithms, namely, RF ERT and DT, yielded better classification accuracies (78–86%) compared with the two boosting algorithms, GBT and ADB (60–75%). We hope that these our results would help improve the classification of breast tissue to allow the early prediction of cancer susceptibility.

## **KEYWORDS**

Breast tissues; Machine learning; Ensemble learning; Classification; electrical impedence

## REFERENCES

- 1. Oliver, A., Freixenet, J., Martí, R., Zwiggelaar, R. (eds.): A comparison of breast tissue classification techniques. In: International Conference on Medical Image Computing and Computer-Assisted Intervention. Springer (2006)
- Oliver, A., Freixenet, J., Marti, R., Pont, J., Pérez, E., Denton, E.R., et al.: A novel breast tissue density classification methodology. IEEE Trans. Inf. Technol. Biomed. 12(1), 55–65 (2008)
- 3. Ghasemzadeh, A., Azad, S.S., Esmaeili, E.: Breast cancer detection based on Gabor-wavelet transform and machine learning methods. Int. J. Mach. Learn. Cybern. **10**, 1–10 (2018)
- 4. Peto, R., Boreham, J., Clarke, M., Davies, C., Beral, V.: UK and USA breast cancer deaths down 25% in year 2000 at ages 20–69 years. Lancet **355**(9217), 1822 (2000)
- 5. Zou, Y., Guo, Z.: A review of electrical impedance techniques for breast cancer detection. Med. Eng. Phys. **25**(2), 79–90 (2003)