



## UWS Academic Portal

### Use of neutron radiography and tomography to identify fracture network connectivity in low permeability carbonates

Lewis, Helen; Zihms, Stephanie; Couples, Gary; Charalampidou, Elma-Maria; Hall, Stephen; Tudisco, Erika; Edlmann, Katriona; Ando, Edward; Etxegarai, Maddi; Tengattini, Alessandro; Atkins, Duncan

Published: 23/04/2017

#### *Document Version*

Publisher's PDF, also known as Version of record

[Link to publication on the UWS Academic Portal](#)

#### *Citation for published version (APA):*

Lewis, H., Zihms, S., Couples, G., Charalampidou, E-M., Hall, S., Tudisco, E., ... Atkins, D. (2017). *Use of neutron radiography and tomography to identify fracture network connectivity in low permeability carbonates*. Poster session presented at European Geosciences Union General Assembly 2017, Vienna, Austria.

#### **General rights**

Copyright and moral rights for the publications made accessible in the UWS Academic Portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

#### **Take down policy**

If you believe that this document breaches copyright please contact [pure@uws.ac.uk](mailto:pure@uws.ac.uk) providing details, and we will remove access to the work immediately and investigate your claim.

## Use of neutron radiography and tomography to identify fracture network connectivity in low permeability carbonates

Helen Lewis (1), Stephanie Zihms (1), Gary Couples (1), Elma-Maria Charalampidou (1), Stephen Hall (2), Erika Tudisco (6), Katriona Edlmann (3), Edward Ando (4), Maddi Etxegarai (4), Alessandro Tengattini (4), and Duncan Atkins (5)

(1) Institute of Petroleum Engineering, Heriot-Watt University Edinburgh, UK, (2) Division of Solid Mechanics, Lund University Lund Sweden, (3) School of Geosciences, University of Edinburgh, Edinburgh, UK, (4) Laboratoire 3SR, Université Grenoble Alpes, Grenoble, France, (5) Institut Laue-Langevin Grenoble, France, (6) Division of Geotechnics, Lund University, Sweden

For low permeability rocks, open fractures have the potential to provide a dominant flow pathway, but determining effective connectivity, and associated single or multi-phase flow characteristics within an intact sample, is not simple. Flow tests can provide bulk values for any one sample, but general predictability requires considerably more information. X-ray tomography (XRT) has been used to identify fracture patterns and apertures in 3D. Here, in addition to XRT of experimentally-fractured low-permeability laminites, neutron beam radiography and tomography have been used to image flow via sensitivity to protons. To our knowledge this is the first identification of fluid front movement through fracture arrays using neutron tomography.

Specifically, samples of a very fine-grained laminite, a layered carbonate rock deposited in a lake bed environment, with a “grain” size of approximately  $5\mu\text{m}$ , were deformed experimentally under conditions representing 1 to 2 km burial depth, creating a series of shear- and extension- fractures that XRT indicated were at least partly open (Fig 1).

But only destructive assessment (e.g. SEM) could verify this, destroying the ability to test flow capabilities in the process. Neutron tomography, using deuterated and then distilled water (which have slightly different densities and significantly different Neutron absorption) are introduced into the sample base, under pressure control, enabling observation of the progression of deuterated water into the air-filled laminite matrix- and fracture space-network, following by distilled water that mainly flows in the fractures (Fig. 2). Radiography and tomography identify a complex but rational pattern of initial water movement into the matrix laminae that suggests that in unfractured laminite, the fluid front would progress stepwise from one lamina to the next with a relatively fast filling across an entered lamina and relatively slow progression across the overlying lamina. But in the presence of open fractures, when fluid enters the fracture system, it moves up and down along a network of connected fractures, progressing across the sample and also moving into most laminae. Front progression is slowed in the central part of the sample where some stylolitisation is provisionally interpreted, and where the fracture network appears less well developed. Once that central part is entered, filling is rapid, suggesting a stacked low permeability then higher permeability arrangement. The upper part of the sample has a smaller number of potentially open fractures and once fluid enters these fractures, the front travels more rapidly to the top of the sample. When the second fluid is introduced, it follows a similar path but the already saturated rock responds differently, supporting the expectation that multi-phase behaviour will be complex. But note that the two forms of water have a strong tendency to not mix.

In this study, because the sample is intact, we make predictions of the geological characteristics from the flow behaviour, in contrast to the more typical arrangement of predicting flow from observed geological characteristics. However, in common with XRT studies and unlike the destructive analyses, we can subsequently test our geological inferences.