

## Preface

This volume contains the papers presented at Ural-PDC 2018: 4th Ural Workshop on Parallel, Distributed, and Cloud Computing for Young Scientists (<https://ural-pdc.org/2018/>) held on November 15, 2018 in Yekaterinburg, Russia.

Ural-PDC is jointly organized by the Krasovskii Institute of Mathematics and Mechanics and the Ural Federal University. The aim of the workshop is to build the community of young researchers who work on modern problems in parallel, distributed, cloud computing, and to provide an academic forum that fosters them to share their ideas and results.

The key topics of interest are high-performance computing, distributed computing, cloud computing, Big Data processing, parallel computing education, and various applications of parallel and distributed computing. We have received 20 submissions, each of which has been reviewed by at least two program committee members. The committee decided to accept 14 regular papers and an invited paper on online encyclopaedia of numerical algorithms.

Last but not least, we are grateful to our program and organizing committees, who made the workshop possible.

December 12, 2018  
Yekaterinburg, Russia

Dmitry Ustalov  
Andrey Sozykin  
Timofey Epanchintsev  
Mikhail Chernoskutov

## Table of Contents

Formal Model of Problems, Methods, Algorithms and Implementations in the Advancing AlgoWiki Open Encyclopedia . . . . .	1
<i>Andrey Popov, Dmitry Nikitenko, Alexander Antonov and Vladimir Voevodin</i>	
An Approach for Managing Hybrid Supercomputer Resources in Photogrammetric Tasks . . . . .	12
<i>Nikita Voinov, Ivan Selin, Pavel Drobintsev and Vsevolod Kotlyarov</i>	
Primary Automatic Analysis of the Entire Flow of Supercomputer Applications . . . . .	20
<i>Pavel Shvets, Vadim Voevodin and Sergey Zhumatiy</i>	
Solving the Structural Inverse Gravimetry Problem in the Case of Multilayered Medium Using GPU . . . . .	33
<i>Elena Akimova, Vladimir Misilov and Murat Sultanov</i>	
The Comparative Performance Analysis of Data-intensive Applications for IBM Minsky and Newell Systems . . . . .	40
<i>Ilya Afanasyev</i>	
Parallel Substructuring Method With Memory Cost Limits . . . . .	50
<i>Nikita Nedozhogin, Sergey Kopysov and Alexander Novikov</i>	
Parallel Partitioning Without Branching of Inner Boundaries for Arbitrary Domain . . . . .	60
<i>Ilyas Kadyrov, Sergey Kopysov and Alexander Novikov</i>	
Development of Technique for Generating Adaptive Visualization of Three-dimensional Objects in the Cloud Educational Environment . . . . .	67
<i>Vladimir Shardakov, Denis Parfenov, Irina Bolodurina, Igor Parfenov and Veronika Zaporozhko</i>	
Comparison of Approaches to the Analysis of Supercomputers Usage Efficiency by the Example of Lomonosov and Lomonosov-2 Supercomputers	76
<i>Sergei Leonenkov and Sergey Zhumatiy</i>	
Exploring Trade-offs of Compiler Optimizations to Enable Performance Portability for Multi-level Memory Hierarchies . . . . .	85
<i>Aleksei Levchenko</i>	
Development and Research of an Adaptive Traffic Routing Algorithm Based on a Neural Network Approach for a Cloud System Oriented on Processing Big Data . . . . .	98
<i>Denis Parfenov, Irina Bolodurina and Vladimir Shardakov</i>	

Net-Centric Internet of Things for Industrial Machinery Workshop . . . . .	112
<i>Vsevolod Kotlyarov, Igor Chernorutsky, Pavel Drobintsev, Alexey Tolstoles, Irina Khrustaleva and Lina Kotlyarova</i>	
Skin Detection Technique Based on HSV Color Model and SLIC Segmentation Method . . . . .	123
<i>Kseniia Nikolskaia, Nadezhda Ezhova, Anton Sinkov and Maksim Medvedev</i>	
A Web-based System for Launching Large Experiment Series on Supercomputers . . . . .	136
<i>Evgheniy Kuklin and Sergei Pravdin</i>	
Computing Cost and Accounting Challenges for Octoshell Management System . . . . .	146
<i>Yulia Belkina and Dmitry Nikitenko</i>	

## Program Committee

Alexander Bersenev	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Mikhail Chernoskutov	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Pavel Drobintsev	Peter the Great St.Petersburg Polytechnic University
Timofey Epanchintsev	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Aleksandr Igumnov	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Svyatoslav Khamzin	Ural Federal University / Institute of Immunology and Physiology
Evgheniy Kuklin	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Alina Latipova	South Ural State University
Dmitry Nikitenko	Lomonosov Moscow State University
Gleb Radchenko	South Ural State University
Yaroslav Salii	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Alexander Semenov	JSC NICEVT
Vladislav Shchapov	Institute of Continuous Media Mechanics
Andrey Sozykin	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Konstantin Ushenin	Ural Federal University
Dmitry Ustalov	University of Mannheim
Vladimir V. Voevodin	Research Computing Center of Lomonosov Moscow State University
Vladimir Zverev	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University

## Invited Reviewers

Alexander Agarkov	JSC NICEVT
Ameer B. A. Alaasam	South Ural State University
Timur Ismagilov	JSC NICEVT
Alexei Podkorytov	South Ural State University

## Organizing Committee

Mikhail Chernskutov	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Dmitry Ustalov	University of Mannheim
Alexander Bersenev	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Timofey Epanchintsev	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Alexey Grigoriev	Krasovskii Institute of Mathematics and Mechanics
Anna Kotegova	Ural Federal University
Evgeniy Kuklin	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University
Andrey Sozykin	Krasovskii Institute of Mathematics and Mechanics / Ural Federal University

# Parallel Substructuring Method With Memory Cost Limits\*

Nikita Nedozhogin<sup>1</sup>, Sergey Kopysov<sup>1,2</sup>, and Alexander Novikov<sup>1</sup>

<sup>1</sup> Institute of Mechanics Udmurt Federal Research Center UB RAS, Izhevsk, Russia

<sup>2</sup> Udmurt State University, Izhevsk, Russia

nedozhogin@inbox.ru

**Abstract.** In decomposition methods, the memory costs for solving the interface problem are increasing significantly with the number of subdomains increasing. Using of the substructuring method allows you to reduce the number of iterations when the system is being solved. At the same time, the global boundary stiffness matrix takes up more memory in comparison with global stiffness matrix. This imposes restrictions on the maximum size of the problem for which you can apply this method. Different approaches to reduce the costs and limitations of memory on stage of the construction and solving of the interface system exist. A layer-by-layer approach to the partitioning of a triangulated multiply connected domain into connected subdomains without branching of inner boundaries was presented. This makes it possible to avoid conflicts with concurrent operations of the assembly type without using synchronization and critical sections. Parallel algorithm of the construction global boundary stiffness matrix with distributed storage of the matrix are considered when implementing using OpenMP and MPI technologies. This approach allows not only to reduce the limits on the maximum size of the solved problem, but also to resolve conflicts of shared memory access by increasing the number of independent parallel tasks.

**Keywords:** Parallel algorithms · Decomposition method · Substructuring method · OpenMP · MPI

## 1 Introduction

The substructuring method is the non-overlapping domain decomposition [1]. However, the global boundary stiffness matrix has more nonzero elements with smaller dimension in comparison with global stiffness matrix [2]. Due to these properties, even the use of sparse matrix storage formats requires considerable memory costs. Block [3] and hierarchical [4] methods with low-rank approximation have received great development due to the current trends in reducing the amount of memory per processor core. In this paper, parallel substructuring method with distributed storage of the matrix is considered. The distributed

---

\* The reported study was partially funded by RFBR according to the research project 17-01-00402-a.

construction makes it possible to apply this approach not only in the classical substructuring method, but also in the hierarchical or block one, or in the case of constructing a preconditioner on the based on the substructuring method.

The second memory limit is the access speed. To accelerate calculations, it is necessary the number of simultaneous accesses to the same memory area both during reading and writing. To increase the parallelism of the method, it is required to arrange the grid and elements in such a way that independent threads simultaneously work with their own sections of memory without overlapping. In this case, We propose using a layer-by-layer partitioning method. In the course of this method, any unstructured mesh can be arranged.

The paper presents the results of parallel version of the substructuring method realized with the help of OpenMP and MPI technology. The potential for parallelization with the help of CUDA technology for computation on graphic accelerators is considered

## 2 Layer-by-layer Partitioning

We generalize the ordering of the 3D unstructured mesh  $T$  on a subdomains without branching of internal boundaries using layer-by-layer partitioning. We define in  $T$  the some set of the cells  $T^* \subset T$ , assuming  $L_1 = T^*$ . We construct the layers  $L_j = \{\sigma \in T \mid L_j \cap L_c \neq \emptyset \text{ when } j = c \pm 1\}$ ,  $j \in [2, m - 1]$ , according to the Algorithm 1. Here  $m$  - number of the layers,  $\sigma$  - cell of the mesh  $T$ .

---

**Algorithm 1:** Partitioning unstructured mesh  $T$  on layers.

---

**Input data:**  $T$  — unstructured mesh of cells  $\sigma \in T$ ,  $T^*$  — given set  $\{\sigma\} \subset T$ .  
**Result:**  $\{L_j\}$  — set of the layers of cells.

- 1 Define the cells corresponding to the vertices of  $T$ ;
- 2  $\forall \sigma \in T$  find cells having a common vertex;  
 /\* Form the layers of mesh cells \*/
- 3 Let  $j = 1$  and layer  $L_j = T^*$ ;
- while**  $\left(\sum_{c=1}^j |L_c| < |T|\right)$  **do**
- 4   Construct layer  $L_{j+1}$  of cells  $T$ ;
- 5   Let  $j \leftarrow j + 1$ ;

---

The result of the Algorithm 1 is an ordered set of  $m$  layers  $L_j$ , in which the layers adjacent to  $L_j$  have numbers  $j - 1$  and  $j + 1$ . The resulting layers are discrete analogs of a domain of  $\mathbb{R}^3$  of type  $(g, 2) : g \geq 0$ . All the vertices of the cells lie on the surface bounding the layer. In general, layer  $L_j$  consist of a set of sublayers  $\{L_j^{(c)}\}$ , where each sublayer  $L_j^{(c)}$  is the set of cells in  $L_j$  having at least one intersection with the cell in  $L_j$ . If some layer  $L_j$  consists of one sublayer  $L_j^{(c)}$ , we assume that the layer  $L_j$  is connected.

Thus, the problem of forming subdomains of an unstructured mesh  $\{T_i : \bigcup_i T_i = T\}$  based on obtained partitioning on layers  $L_j$  is as follows:

find the union of the layers  $L_j$  in the set of subdomains  $\{T_i\}$  satisfying certain restrictions. One of the conditions is the connectivity of the resulting subdomains  $T_i$ . The number of layers included in the subdomain is bounded below by two layers, which is a sufficient condition for the existence of vertices in  $T_i$  that do not belong to the boundary  $T_i$ .

In order to construct connected union of layers in the subdomain of the mesh, it is necessary to find sublayers and their connections. The algorithm 2 provides a search for sublayers and the definition of their connections using a dual graph  $G_d(V, E)$  of connected cells in  $L_j$  along the faces. Further, the connected components  $G_d(V, E)$  are found. The set of the mesh cells corresponding the connected components  $G_d(V, E)$  will be denoted as sublayers  $L_j^{(c)}$ ,  $c = 1, 2, \dots, \kappa_j$ , where  $\kappa_j = |\{L_j^{(c)}\}|$  — the number of the sublayers in layer  $L_j$ ,  $\kappa^* = \max_j \kappa_j$ .

---

**Algorithm 2:** The union of the layers  $\{L_i\}$  in linked subdomains  $\{T_i\}$ .

---

```

Input data:  $\{L_j\}$  — set of the layers of cells.
Result:  $\{T_i\}$  — set of the mesh  $T$  subdomains.

/* Find sublayers in each layer  $L_j$  */
1 for  $L_j, \forall j \in [1, m]$  do
2   Construct dual graph  $G_d(V, E)$  of the links of the cells of  $L_j$  along the faces;
3   Define connected components  $G_d(V, E)$ ;
4   Assign sublayers  $L_j^{(c)}$  to the connected components  $G_d(V, E)$ ;
5 Construct the graph of sublayers  $G(V, E)$ ;
/* Form subgraphs  $G_i$  of th graph  $G(V, E)$ : */
6  $i = 1, m^* = 1, mark(L_j) = 0, \forall j \in [1, m]$ ;
7 while  $m^* < m$  do
8   /* Find an unmarked layer with  $\kappa_j = \kappa^*$  */
9   while  $\kappa^* > 1$  do
10    Adjoin adjacent layers to the initial layer of the domain;
11    Define  $\kappa^*$  — the number of the connected components  $G_i$ ;
12     $j \leftarrow j + 1$ ;
13     $i \leftarrow i + 1$ ;
if  $v \in V_G \wedge deg(v) = 1 \wedge v \in L_j^{(c)}$  then
  Adjoin  $\{v\} \in L_j$  to  $G_j \in L_{j-1}, j \in [1, i]$ .
Partitioning/ordered mesh  $T$ , assuming  $T_i \in G_i$ .

```

---

The Algorithm 2 extends the partitioning on layers [5] on multi-connected domains. Partitioning without branching on the basis of the neighborhood relation reduces to the use of the Algorithm 1 for the layer-by-layer partitioning of the triangulation  $T$  and the union layers  $L_j, \forall j \in [1, m]$  by the Algorithm 2 in th subdomains  $T_i$ .



### 3 Substructuring Method

Let the mesh domain  $\Omega$  be split into  $n_\Omega$  non-overlapping subdomains

$\Omega = \bigcup_{i=1}^{i \leq n_\Omega} \Omega_i^{(1)}$ , where  $\Omega_i^{(1)} \cap \Omega_j^{(1)} = \emptyset$ , when  $i \neq j$ . Formally unite the sub-

domains, preserving the structure of the decomposition (interior nodes remain interior, boundary – boundary). We introduce the decomposition of the second level with number of the subdomains equal number of the computational mod-

ules  $n_p$  such that  $\Omega = \bigcup_{k=1}^{k \leq n_p} \Omega_k^{(2)}$ , and  $\Omega_k^{(2)} = \bigcup_{i=k \frac{n_\Omega}{n_p}}^{i \leq (k+1) \frac{n_\Omega}{n_p}} \Omega_i^{(1)}$ .

For decomposition the first level, the system of equations is formed in such a way that the unknowns corresponding to the interior and boundary nodes take the form:

$$\begin{pmatrix} {}^1(A_{II}^{(1)}) & 0 & \dots & {}^1(A_{IB}^{(1)}) \\ 0 & {}^2(A_{II}^{(1)}) & \dots & {}^2(A_{IB}^{(1)}) \\ \dots & \dots & \dots & \dots \\ {}^1(A_{BI}^{(1)}) & {}^2(A_{BI}^{(1)}) & \dots & A_{BB}^{(1)} \end{pmatrix} \begin{pmatrix} {}^1 u_I^{(1)} \\ {}^2 u_I^{(1)} \\ \dots \\ u_B \end{pmatrix} = \begin{pmatrix} {}^1 f_I^{(1)} \\ {}^2 f_I^{(1)} \\ \dots \\ f_B \end{pmatrix}.$$

In this system, the unknowns stand for the boundary nodes are found from the solution of the system  $S^{(1)} u_B = \tilde{f}_B$ . Here

$$\tilde{f}_B = \sum_{i=1}^{i \leq n_\Omega} (f_B - {}^i(A_{BI}^{(1)}) {}^i(A_{II}^{(1)})^{(-1) i} f_I^{(1)})$$

is the right-hand-side vector and  $S^{(1)}$  is the global boundary stiffness matrix (also known as the Schur complement matrix [2]) and is the sum of the local boundary stiffness matrices  $S_i^{(1)} = A_{BB}^{(1)} - {}^i(A_{BI}^{(1)}) {}^i(A_{II}^{(1)})^{(-1) i} {}^i(A_{IB}^{(1)})$  such that

$S^{(1)} = \sum_{i=1}^{i \leq n_\Omega} S_i^{(1)}$ , where index  $i$  corresponds to subdomains of the first level.

### 4 Construct Global Boundary Stiffness Matrix

Global boundary stiffness matrix  $S_k^{(2)}$  corresponding to these subdomains are supplemented by zeros up to size global matrix  $S^{(1)}$  in this  $S^{(1)} = \sum_{k=1}^{n_p} S_k^{(2)}$ . Note

that, Matrices  $S_k^{(2)}$  do not depend on each other during the formation stage. This excludes conflicts when reading elements data and writing results of summing of local matrices  $S_i^{(1)}$ .

For reduce computational costs of RAM, each computational modules forms one row  $l$  of the matrix  $S_i^{(1)}$  at the same time. The order of the construction of rows is given by subdomains. Parallel algorithm of the construction for  $n_p$  computational modules using OpenMP technology on the example of two subdomains would be as follows (note that  $n_p \leq n_\Omega$ ):

---

**Algorithm 3:** Parallel algorithm of the global boundary stiffness matrix construction  $S^{(1)} = \sum_{k=1}^{n_p} S_k^{(2)}$  for OpenMP

---

```

// Forming of  $S_1^{(2)}$ 
for  $i = 1 \dots n_\Omega/n_p$  do
1 | Function of the inverse matrix
   |  ${}^i(A_{II}^{(1)})^{-1}$  ;
   | // Parallelize loop by
   |   OpenMP
   | for  $l = 1 \dots n_{B_i}$  do
2 |    $\mathbf{v} = {}^iA_{BI}^{(1)}(l, \cdot)$  ;
3 |    $\mathbf{v} = \mathbf{v} {}^i(A_{II}^{(1)})^{-1}$  ;
4 |    $S_i^{(1)}(l, \cdot) = {}^iA_{BB}^{(1)}(l, \cdot) - \mathbf{v} {}^iA_{IB}^{(1)}$  ;
5 |   Record the  $S_i^{(1)}(l, \cdot)$  elements
   |   in the corresponding row of
   |   the matrix  $S_1^{(2)}$  ;
// Forming of  $S_2^{(2)}$ 
for  $i = n_\Omega/n_p \dots n_\Omega$  do
  Function of the inverse matrix
   ${}^i(A_{II}^{(1)})^{-1}$  ;
  // Parallelize loop by
  OpenMP
  for  $l = 1 \dots n_{B_i}$  do
     $\mathbf{v} = {}^iA_{BI}^{(1)}(l, \cdot)$  ;
     $\mathbf{v} = \mathbf{v} {}^i(A_{II}^{(1)})^{-1}$  ;
     $S_i^{(1)}(l, \cdot) = {}^iA_{BB}^{(1)}(l, \cdot) - \mathbf{v} {}^iA_{IB}^{(1)}$  ;
    Record the  $S_i^{(1)}(l, \cdot)$  elements
    in the corresponding row of
    the matrix  $S_2^{(2)}$  ;

```

---

Based on the computing experiment (See Table 1), run-time costs on each subdomain have the following order (top-down):

1. Inverse of the matrix  ${}^i(A_{II}^{(1)})$  (Step 1 of Algorithm 3);
2. Record the row  $l$  of the local matrix  $S_i^{(1)}(l, \cdot)$  in the corresponding row of the matrix  $S_1^2$  (Step 5 of Algorithm 3);
3. Operations of taking the row from the matrix, the matrix-vectors multiplications and the difference of the vectors (steps 2-4 of Algorithm 3, denote by MatVec).

Taking the row from the matrix, the matrix-vector multiplications and the difference of the vectors (see steps 2-4 of Algorithm 3) are parallelized using OpenMP technology, that for these operations gave an acceleration close to lin-

ear. Also, in the future, it is planned to parallelize these operations for use on graphics accelerators using CUDA technology.

Recording of the row  $l$  of the local matrix  $S_i^{(1)}(l, \cdot)$  to the corresponding row of the matrix  $S_k^{(2)}$  (see step 5 of Algorithm 3) largely depends on the matrix storage formats used. Matrices  $S_k^{(2)}$  is formed in a compressed CSR format, because of its large size. Using arrays of vectors (C++ container `std::vector`) allows to reduce memory costs to a minimum, but the complexity of adding new elements to such storage formats is  $O(n_B)$ , where  $n_B$  is the number of equations corresponding to the boundary nodes. To reduce the costs of adding new elements of the row, we use sorted associative containers (C++ container `std::map`) and not sorted (C++ container `std::unordered_map`). In the sorted container, the complexity of finding and adding a new element is  $O(\ln n_B)$  (due to its red-black tree structure), but it significantly increase memory costs to store to store additional two pointers. The non-sorted container, for these operations has complexity form  $O(1)$  to  $O(n_B)$  (depending on the hash function) and request smaller memory sizes, compared to the container `std::map`, which is optimal for use in the constructing of matrices  $S_k^{(2)}$ .

**Table 1.** Characteristic formation times in one subdomain, sec.

Compute ${}^i(A_{II})^{(-1)}$		MatVec, see Algorithm 3	Assembly $S^{(1)}$
LU	SM		
$n_\Omega = 512$			
95.4972	41.69505	0.340893	1.53655
$n_\Omega = 1024$			
4.07287	1.947	0.130277	0.6955

To inverse the matrix at Step 1 of Algorithm 1, LU-factorization (LU) and Sherman-Morrison (SM) methods [6] were considered.

For a given non-singular matrix  $A$  there exists a decomposition on upper triangular matrix  $U$  and a lower triangular matrix  $L$ . If matrices  $A$ ,  $U$ ,  $L$  are invertible, then  $A^{-1} = U^{-1}L^{-1}$ . In the construction  $L$  and  $U$ , products with nonzero elements of the parent matrix were summed, since the factorization was carried out for matrices stored in the CSR format. Only sequential implementations of the LU-factorization on CPU was considered. This approach showed the best results for small matrices. Features of this algorithm do not allow to effective use all the capabilities of the massively parallel GPU architecture.

A parallel version of the Sherman-Morrison method implemented using OpenMP technology was considered.

---

**Algorithm 4:** Parallel algorithm of Sherman-Morrison method for  $(A_{II}^{(1)})^{-1}$

---

```

1 x, y - vectors of dimension  $n$  ;
  for  $k = 1 \dots n$  do
    // OpenMP
2    $\mathbf{x}^T = A_{II}^{(1)}(k, \cdot) - e_k$ ;
    // OpenMP
3    $\mathbf{y} = \mathbf{x}^T A_{inv}$ ;
    // Loop of OpenMP on  $i$ 
    for  $i = 1 \dots n$  do
      for  $j = 1 \dots n$  do
         $A_{inv}(j, i) = A_{inv}(j, i) - (\mathbf{y}_i * A_{inv}(j, k) / (\mathbf{y}_k + 1))$  ;
4  $(A_{II}^{(1)})^{-1} = A_{inv}$  ;

```

---

LU-factorization is faster than the Sherman-Morrison method in sequential implementations. In spite of it, LU-factorization does not parallelize well. Using parallel version of the Sherman-Morrison method provided a parallel acceleration about two times. To reduce the number of operations and the computational load, matrix  $(A_{II}^{(1)})^{-1}$  is stored in its entirety before the completion of the constructing of  $S_i^{(1)}$  in the current subdomains, since it is not known how many non-zero elements contain an inverse matrix. To solve the system of equations on the inner subdomains nodes  ${}^i A_{II}^{(1)} u_I = {}^i f_I - {}^i A_{IB}^{(1)} u_B$  Krylov subspace methods [7] are used.

In the future, parallelization on the GPU is planned. To increase the parallelism, the order of the formation of the local boundary stiffness matrices will be given by layer-by-layer partitioning. Thus, a block of parallel GPU threads will process one row of the matrix  $S_i^{(1)}$ . In total it will be possible to generate  $\kappa_i$  blocks that are able to write in different places of the same array without overlap and conflicts due to layer-by-layer ordering.

## 5 Solving the $S^{(1)} u_B = \tilde{f}_B$ System

Implementation of conjugate gradients method for solving the system  $S^{(1)} u_B = \tilde{f}_B$  on one of  $n_p$  computing node is shown in Algorithm 5. Here the system matrix is represented in the form  $S^{(1)} = \sum_{k=1}^{n_p} S_k^{(2)}$ . Index  $k$  corresponding to the number of computational module is omitted.

---

**Algorithm 5:** Algorithm of the preconditioned conjugate gradient method for distributed matrix

---

```

1  $u, r, p, q, z \in \mathbb{R}^{n_B}$  ;
2  $i = 0$ ;
3  $r_0 = \tilde{f}_B$  ;
4  $u_0 \leftarrow 0$  ;
5  $z_0 = Mr_0$  ; //  $M \sim (S^{(1)})^{-1}$  -- preconditioner
6  $p_0 = z_0$  ;
7  $\rho_0 = (r_0, z_0)$  ; // sync point
  while  $\|r_i\|_2 / \|f\|_2 > \varepsilon$  do
8   Assembly  $p_i$  ; // Using MPI::Allreduce
9    $q_i = S^{(2)}p_i$  ; //  $k$  independent operations on each MPI
     process
10   $\alpha_i = (r_i, z_i) / (q_i, p_i)$  ; // MPI::Allreduce lead to sync point
11   $u_{i+1} = u_i + \alpha_i p_i$ ;
12   $r_{i+1} = r_i - \alpha_i q_i$ ;
13   $z_{i+1} = Mr_{i+1}$  ; //  $M \sim (S^{(1)})^{-1}$  -- preconditioner
14   $\rho_{i+1} = (r_{i+1}, z_{i+1})$  ; // MPI::Allreduce lead to sync point
15   $\beta_{i+1} = \rho_{i+1} / \rho_i$ ;
16   $p_{i+1} = r_{i+1} + \beta_{i+1} p_i$ ;
17   $i = i + 1$  ;

```

---

In a matrix-vector product (See steps 8-9 of Algorithm 5) operation  $q_i = S^{(1)}p_i$  is performed in two steps. First, the assembly of the vector  $p_i$  from all MPI processes, then  $n_p$  independent operations  $(q_k)_i = S_k^{(2)}p_i$ . The result of products is the set of vectors  $q_k$  such that  $q_k \in \mathbb{R}^{n_B}$  and  $q = \sum_{k=1}^{n_p} q_k$ . Summed of vector  $q$  are not required. Vector is stored by parts on various compute nodes.

Parallelization of the operations with vectors is realized as follows: operands are parts of vectors consisting of components corresponding to mesh nodes of the subdomain  $\Omega_k^{(2)}$  for each parallel MPI process. The result vector assembly are not required, each MPI process jobs with its local vectors, and synchronization occurs when the scalar products  $(r, z)$ ,  $(q, p)$ ,  $(r, r)$  are computed. Scalar products are performed in two steps. First, local scalar products for the part vectors in parallel MPI processes, then summation of the local sums (on this step, implicit synchronization occurs). Inside the MPI process, vectors operations are parallelized using OpenMP technology with number of the thread equal number of the CPU cores on computational nodes.

To parallelize the GPU, it is planned to use an approach similar to that presented in paper [2].

## 6 Results

Numerical experiments were carried out on the test problem of the theory of elasticity. The computational domain had the form of a parallelepiped. Mesh consisted of 539000 hexagonal cells. 8 threads of the OpenMP are running inside each MPI process. In Table 2, the result of experiment are presented for dimension on 512 and 1024 subdomains with using 2, 4, 6 MPI processes. The presented results are obtained on 6 computational nodes, each of which contains two processors Intel Xeon E5-2609 and 64GB RAM. For  $n_\Omega = 512$ , this problem took approximately 100GB of RAM, for  $n_\Omega = 1024$ , problem took approximately 80GB of RAM.

**Table 2.** Time of construction and solve in the Substructuring method

$n_p$	$\sum S_i^{(1)}$		$S^{(1)}u_B = \tilde{f}_B$		${}^i A_{II}^{(1)} u_I = {}^i f_I - {}^i A_{IB}^{(1)} u_B$	
	LU, sec.	SM, sec.	#	Time, sec.	#	Time, sec.
$n_\Omega = 512$						
2	34954.6	14936.8	2324	1640.37	43	4.72359
4	18086.6	7615.15	2325	1391.23	43	2.60635
6	11713.4	5014.66	2325	1498.37	43	1.9185
$n_\Omega = 1024$						
2	5128.47	2818.16	2600	1464.09	35	3.15815
4	2622.52	1411.97	2600	1397.77	35	2.10205
6	1802.32	965.803	2600	1469.18	35	1.74885

The considered algorithm allows to significantly reduce the memory limits for the substructuring method. The partitioning of the matrix  $S^{(1)}$  and its distributed storage makes it possible to realize coarse-grained parallelism at the formation stage of global boundary stiffness matrix, to reduce exchanges and to exclude synchronous access to one memory cell during the local matrices addition. At the same time, an increase in the number of involved computational modules permits achieving an acceleration close to linear at the stage of matrix construction. At the solver stage, the distributed storage of the matrix  $S^{(1)}$  allows solving systems with a dimension proportional to the memory size of the involved computational modules. Scalability is limited to assembling the results of scalar products of vectors and depends only on the restrictions on the speed to data exchange over the network.

## References

1. Toselli A., Widlund O.B.: Domain Decomposition Methods — Algorithms and Theory. Springer Series in Computational Mathematics, Vol. 34 (2005)
2. Kopysov S.P., Kuzmin I.M., Nedozhogin N.S., Novikov A.K., Sagdeeva Y. A.: Hybrid Multi-GPU solver based on Schur complement method. Lecture Notes in Computer Science, vol. 7979, pp. 65-79 (2013)

3. Amestoy P.R., Buttari A., L'Excelent J-Y., Mary T.: On the Complexity of the Block Low-Rank Multifrontal Factorization. *SIAM Journal on Scientific Computing*, vol. 39(4), pp. A1710-A1740 (2017)
4. Chen C., Pouransari H., Rajamanickam S., Boman E.G., Darve E.: A distributed-memory hierarchical solver for general sparse linear systems. *Parallel Computing*, vol. 74, pp. 49-65 (2018)
5. Novikov A.K., Piminova N.K., Kopysov S.P., Sagdeeva Y.A.: Layer-by-layer ordering in parallel finite composition on shared-memory multiprocessors. *IOP Conf. Ser.: Mater. Sci. Eng.*, vol. 158(1), p.158 (2016)
6. Sherman J., Morrison W.J.: Adjustment of an Inverse Matrix Corresponding to a Change in One Element of a Given Matrix. *Ann. Math. Statist.*, vol. 21(1), pp. 124-127 (1950)
7. Saad Y.: *Iterative Methods for Sparse Linear System*, Boston: PWS Publishing company, p. 447 (1996)