

RAIN FADE DYNAMICS FOR KA-BAND SATELLITE COMMUNICATION MITIGATION TECHNIQUE IN EQUATORIAL MALAYSIA

MAWARNI BINTI MOHAMED YUNUS

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Electrical Engineering)

School of Electrical Engineering
Faculty of Engineering
Universiti Teknologi Malaysia

DECEMBER 2018

DEDICATIONS



*So verily, with every difficulty, there is relief. With every difficulty, there is relief
(Al-Insyirah, 94:5-6)*

In loving memory of my father, *Abah* who passed away in December 9, 2015 while I'm struggling on my intricate PhD journey.

Thank you, *Abah* for always had confidence in me and constant to be my source of inspiration and strength to survive. *Al-Fatihah*.

ACKNOWLEDGEMENT

In the Name of ALLAH, the Most Compassionate, the Most Merciful.

Firstly, I would like to express my heartfelt gratitude and sincere appreciation to my main supervisor, **Prof. Dr. Jafri bin Din**. This PhD thesis could not have been written without his invaluable guidance, motivation, kindness and passion throughout the period of my study.

I wish to express my deepest gratitude to my co-supervisor, **Dr. Jong Siat Ling** from Universiti Tun Hussein Onn Malaysia (UTHM) for her valuable comments, ideas, encouragement, enforcing strict validation for each result and thesis reading. I am also grateful to Dr. Jong who had previously attached to Politecnico di Milano for allowing me to use Synthetic Storm Technique coding originally provided by Prof. Emilio Matricianni.

I am also indebted to the members of Radio Wave Propagation research group, UTM especially Dr. Lam Hong Yin, Dr. Manhal Alhilaili, Mr. Idrissa Abu Bakar, Dr. Ibtihal Elshami and others for their valuable assistances, encouragements and guidance. Also to technician, Mr. Yazid bin Mohd Bain who helped me to sort out the technical problems. I'm really thanks them all. My big thanks also goes to Dr. Felix Cuervo from Joanneum Research (JR) for his help and guidance especially regarding equipment and data processing.

I like to convey my heartfelt thanks to my home institution, Universiti Teknikal Malaysia Melaka (UTeM) and Ministry of Higher Education, Malaysia, which gave me their indispensable generous sponsoring throughout my study. I also acknowledge Universiti Teknologi Malaysia (UTM) for providing research grant and also MMICare Committee for their Educational Grant Award during my second year of study. I am also grateful to European Space Agency (ESA) and Joanneum Research (JR), Austria who is funding the Ka-band Propagation Measurement Campaign in UTM-Johor Bahru.

Very special grateful to my family members; my mother, parents-in-law, family, and friends for their prayers, endless support and understandings. Most importantly, none of this would have been possible without the love and patience of my beloved husband, Mohd Hafiz Fikri bin Ismail. May ALLAH grant all his wishes and give him more beautiful days ahead, in return. Not to be forgotten, to my beautiful children; Najla Nafeesa, Khalif Anaqi and Rifqi Iman, thank you for the purest love, patience and sacrifices. May ALLAH bless you all with full of happiness in here and hereafter.

Last but not least, to all those have significantly contributed directly or indirectly towards the completion of this thesis; I am truly grateful to all. Alhamdulillah.

ABSTRACT

Modern satellite communication system in higher frequency (Ka-band and above) is very much impaired by rain attenuation particularly in tropical and equatorial region. The desired Quality of Service (QoS) and system availability can be guaranteed only by resorting to smart strategies, named Propagation Impairment Mitigation Techniques (PIMTs) such as power control, adaptive modulation schemes and link diversity. These requires knowledge of the first- and second-order statistics of rain attenuation. Hence, this work concentrates on those aspects in equatorial Johor Bahru, Malaysia, based on one year Ka-band propagation measurement campaign, utilizing the equipment of Beacon Receiver and 2D-Video-Disdrometer (2DVD). Study begins by investigation the rain fade behaviour such as rain attenuation, fade duration, inter-fade duration and fade slope as well as their seasonal and diurnal variations. It is observed that rain attenuation experienced by the Ka-band link requires fade margin of 26.8 dB for 99.9% link availability with the convective events mostly like to occur during the afternoon hour (12:00 pm to 6:00 pm) at high intensity, shorter duration and relatively high rate of change of attenuation particularly during Northeast Moonsoon. Then, the Stratiform Convective-Synthetic Storm Technique (SC-SST) is proposed to estimate the dynamic characteristics of rain attenuation in equatorial region. The SC-SST is found 11% better than SST and 51% better than ITU-R P.1623-1 model in average value of fade dynamics prediction. Finally, a time diversity technique is recommended to mitigate strong signal fades in equatorial region. The results depicted that 10-minute outage tolerance will significantly lower the fade margin requirement to 15 dB for 99.9% of link availability. Afterwards, the generation of time diversity statistics is modelled which can be best represents by gamma-law in this area. The results can provide system engineers with critical information in the design and implementation of PIMTs, and it is expected that the probability of system outages will be greatly reduced.

ABSTRAK

Sistem komunikasi satelit moden dalam frekuensi yang lebih tinggi (jalur-Ka dan ke atas) sangat terjejas oleh pelemahan hujan terutamanya di kawasan tropika dan khatulistiwa. Kualiti perkhidmatan (QoS) yang dikehendaki dan ketersediaan sistem boleh dijamin hanya dengan menggunakan strategi pintar, bernama Teknik Mitigasi Rosotan Perambatan (PIMT) seperti kawalan kuasa, skim modulasi adaptif dan kepelbagaian pautan. Ini memerlukan pengetahuan mengenai statistik tertib pertama dan kedua gangguan hujan. Oleh itu, kajian ini menumpukan kepada aspek-aspek tersebut di khatulistiwa Johor Bahru, Malaysia, berdasarkan kempen pengukuran perambatan jalur-Ka selama setahun, menggunakan peralatan Penerima Bikon dan 2D-Video-Disdrometer (2DVD). Kajian ini bermula dengan penyiasatan ciri-ciri pemudaran hujan seperti gangguan hujan, tempoh pudar, tempoh antara pudar dan cerun pudar serta variasi bermusim dan diurnal. Didapati bahawa pengurangan hujan yang dialami oleh pautan jalur-Ka memerlukan margin pudar sebanyak 26.8 dB untuk ketersediaan pautan 99.9% dengan hujan perolahakn yang kebanyakannya berlaku pada waktu petang (12:00 hingga 6:00 petang) pada intensiti tinggi, tempoh masa yang pendek dan kadar perubahan perlahan yang agak tinggi terutamanya pada musim Timur Laut. Kemudian, Teknik Ribut Sintetik-Perolakan *Stratiform* (SC-SST) dicadangkan untuk mengganggu ciri-ciri dinamik pengurangan hujan di rantau khatulistiwa. SC-SST didapati 11% lebih baik daripada SST dan 51% lebih baik daripada model ITU-R P.1623-1 dalam purata nilai ramalan dinamik pudar. Akhirnya, teknik kepelbagaian masa adalah disyorkan untuk mengurangkan kesan pudar yang tinggi di kawasan khatulistiwa. Hasilnya didapati bahawa toleransi pemadaman selama 10 minit akan menurunkan keperluan margin kepada 15 dB untuk 99.9% ketersediaan pautan. Selepas itu, penjana statistik kepelbagaian masa dimodelkan yang mana digambarkan terbaik oleh aturan gamma di kawasan ini. Hasilnya dapat memberikan jurutera sistem dengan maklumat penting dalam perancangan dan pelaksanaan PIMTs, dan dijangka kebarangkalian kesan pudar dapat dikurangkan.

TABLE OF CONTENTS

	TITLE	PAGE
	DECLARATION	iii
	DEDICATION	iv
	ACKNOWLEDGEMENT	v
	ABSTRACT	vi
	ABSTRAK	vii
	TABLE OF CONTENTS	ix
	LIST OF TABLES	xii
	LIST OF FIGURES	xiv
	LIST OF ABBREVIATIONS	xx
	LIST OF SYMBOLS	xxii
	LIST OF APPENDICES	xxiii
	CHAPTER 1 INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement	2
	1.3 Research Objectives	5
	1.4 Scopes of Work	5
	1.5 Research Contributions	6
	1.6 Thesis Outline	7
	CHAPTER 2 LITERATURE REVIEW	9
	2.1 Introduction	9
	2.2 Climatology Characteristics of Equatorial Malaysia	9
	2.2.1 Type of Precipitation	11
	2.2.2 Seasonal Variation	14
	2.2.3 Diurnal Variation	15
	2.3 Rain Attenuation Statistics at Ka-Band	16
	2.3.1 First-Order Statistics of Rain Attenuation	17
	2.3.2 Second-Order Statistics of Rain Attenuation	21

2.3.2.1	Fade Duration	21
2.3.2.2	Inter-Fade Duration	25
2.3.2.1	Fade Slope	26
2.4	Rain Attenuation and Fade Dynamics Prediction Model	30
2.4.1	ITU-R Rain Attenuation Prediction Model	31
2.4.2	Synthetic Storm Technique (SST)	32
2.4.3	ITU-R Fade Dynamics Prediction Model	37
2.4.3.1	Fade Duration Model	37
2.4.3.2	Fade Slope Model	39
2.5	Propagation Impairment Mitigation Techniques	39
2.6	Review of Syracuse-3A Satellite	44
2.7	Chapter Summary	46
CHAPTER 3 METHODOLOGY		47
3.1	Introduction	47
3.2	Overview of Methodology	47
3.3	Experimental Setup	50
3.3.1	Setup of Ka-Band Satellite Beacon Receiver	50
3.3.2	Setup of 2D-Video-Disdrometer	54
3.3.3	Availability of Recorded Data	56
3.4	Data Processing	58
3.4.1	Received Signal Data Processing	58
3.4.2	Scintillation Filtering	63
3.4.3	Clear Sky Reference Level and Rain Attenuation	65
3.5	Fade Dynamics Calculation and Distribution	66
3.5.1	Fade Duration	66
3.5.2	Inter-Fade Duration	67
3.5.3	Fade Slope	68
3.6	SC-SST Rain Attenuation Prediction Model	69
3.7	Chapter Summary	72
CHAPTER 4 RESULTS AND DISCUSSION		73
4.1	Introduction	73
4.2	Characteristics of Rain Attenuation and Fade Dynamics	73

4.2.1	Rainfall Rate	74
4.2.1.1	Type of Precipitation	75
4.2.1.2	The Relationship between Rainfall Rate and Rain Attenuation	77
4.2.2	Rain Attenuation	78
4.2.3	Fade Duration	80
4.2.4	Inter-Fade Duration	83
4.2.5	Fade Slope	84
4.2.6	Monthly and Seasonal Variations	89
4.2.7	Diurnal Variation	95
4.3	Prediction of Rain Fade Dynamics	99
4.3.1	Modelling of Fade and Inter-Fade Duration	100
4.3.2	Performance of SC-SST Model	104
4.3.2.1	Fade Duration Distribution	105
4.3.2.2	Inter-Fade Duration Distribution	107
4.3.2.3	Fade Slope Distribution	108
4.3.2.4	Model Testing	110
4.4	Time Diversity Technique	112
4.4.1	Statistical Distribution of Time Diversity	113
4.4.2	Time Diversity Correlation Delay Model	115
4.5	Chapter Summary	119
CHAPTER 5 CONCLUSION AND FUTURE WORKS		121
5.1	Conclusion	121
5.2	Future Works	122
REFERENCES		125
APPENDICES		135

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Criteria to differentiate rain type using radar (Badron <i>et al.</i> , 2015)	13
2.2	Parameters description for the SST prediction model	34
2.3	Several PIMTs available in order to compensate fades on Earth-space	40
2.4	Syracuse-3A Ka-band transponder specification	45
3.1	Syracuse-3A satellite, sites and antenna specifications	50
3.2	Input parameters for the SC-SST prediction model	71
3.3	Constants value for k and α parameters at 20.2 GHz	71
4.1	Comparison of cumulative statistics of rainfall rate	75
4.2	The attenuation exceeded for specific link availability of the year measured from UTM, Johor Bahru	79
4.3	Number of events exceeding a given duration for different attenuation thresholds for measurement in Johor Bahru, satellite Thaicom 2 (Thai2) and satellite Thaicom 3 (Thai3)	82
4.4	Parameters of measurement site	89
4.5	RMS values for fade duration prediction models at given attenuation thresholds.	101
4.6	Parameters of double log-normal fitting to the probability of occurrences of measured fade duration at given attenuation thresholds.	102
4.7	Parameters of power-law and double log-normal fitting to the probability of occurrences of measured inter-fade duration at given attenuation thresholds.	104
4.8	Prediction errors for fade duration statistics at different attenuation thresholds	110
4.9	Prediction errors for fade duration statistics at each individual duration	111
4.10	Prediction errors for inter-fade duration statistics at	111

	different attenuation thresholds	
4.11	Prediction errors for inter-fade duration statistics at each individual duration	111
4.12	Prediction errors for fade slope statistics at different attenuation thresholds	112
4.13	Prediction errors for fade slope statistics at each individual duration	112
4.14	Gamma-fitted distribution parameters	117
4.15	Linear regression coefficient of correlation between α and β parameter with time delay, Δt	118

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Mean annual rainfall map for 40 years obtained from ECMWF databases (ITU-R Study Group 3, 2012).	10
2.2	CCDF of rainfall rate from different climatology regions: Kuala Lumpur (1992-1994), Johor Bahru (2013) Equatorial, and Spino d'Ádda (1994-2000) Temperate.	11
2.3	Comparison between vertical reflectivity of (a) stratiform and (b) convective rain (Khamis <i>et al.</i> , 2014)	12
2.4	Tropical/Equatorial region seasonal wind direction (a) Northeast Monsoon season (b) Southwest Monsoon season (Abdullah <i>et al.</i> , 2011).	15
2.5	Monthly variation of rainfall accumulation on Kuala Lumpur from Malaysia Meteorological Department (MMD, 2012).	15
2.6	Diurnal variations according to seasonal distribution in Singapore (Zhou <i>et al.</i> , 2010).	16
2.7	Rain attenuation statistics measured in Europe at Ku, K, Ka and U frequency bands (Ventouras <i>et al.</i> , 2006).	18
2.8	Cumulative distribution of WINDS rain attenuation from 2009-2011 in Singapore compared with the prediction from ITU-R (Yeo <i>et al.</i> , 2014)	19
2.9	Fade dynamics features (Filip <i>et al.</i> , 2003)	21
2.10	Comparison distribution of total number of fades at 27.5 GHz collected for five years (1994-1998) in Vancouver and Tampa. (Amaya <i>et al.</i> , 2010).	24
2.11	The total fading time of Thaicom-3 beacon at 19.45 GHz (Chodkaveekitya <i>et al.</i> , 2016)	25
2.12	Inter-fade duration statistics from 30 GHz Olympus beacon data measured in Belgium (a) Number of inter-fades (b) Conditional probability (Amaya <i>et al.</i> , 2010)	26

2.13	Cumulative distribution of fade slope at 50 GHz in Southern England (Chambers <i>et al.</i> , 2006)	29
2.14	Conditional distribution of fade slope at different attenuation level measured at 20 GHz in Eindhoven, the Netherlands (Van de Kamp, 2003).	29
2.15	Conditional distribution of standard deviation as a function of attenuation at several time intervals measured at 50 GHz in Madrid, Spain (Garcia-del-Pino <i>et al.</i> , 2010).	30
2.16	Schematic presentation of slant path inputs for ITU-R P.618 prediction model (ITU-R P.618-12, 2015).	32
2.17	Vertical structures of the two layers of precipitation and satellite link geometry of SST model (Matricianni, 2006)	33
2.18	Cumulative distribution of attenuation for synthesized and measured signals collected in Munich, Germany (Sanchez-Lago <i>et al.</i> , 2007).	36
2.19	Cumulative distributions of durations for synthesized and measured time series (Sanchez-Lago <i>et al.</i> , 2007)	36
2.20	Comparison of cumulative distribution of rain attenuation measured in Spino d'Adda (asterisk) with SST prediction of rain attenuation plotted for different wind velocity (dotted line, $v = 4 \text{ m/s}$; dashed line, $v = 6 \text{ m/s}$, solid line, $v = 10.6 \text{ m/s}$)(Matricianni, 1996a).	37
2.21	Time diversity scheme in satellite communication link (Lam <i>et al.</i> , 2013)	42
2.22	Probability exceedence of rain attenuation for time delays in the range 1-60 minutes (Ismail <i>et al.</i> , 2000)	43
2.23	Location and coverage of Syracuse-3A satellite beam	45
3.1	Flow diagram of research methodology for rain fade and fade dynamic characteristics	49
3.2	Block diagram of beacon receiving system	52
3.3	Outdoor unit of beacon receiving system (a) feed protection with plastic shelter (b) antenna dish and feeder	53
3.4	Indoor unit of beacon receiving system	53

3.5	Block diagram of 2DVD system	55
3.6	2DVD system setup (a) 3D view (b) Interior view of Outdoor Unit	55
3.7	2DVD data viewer main screen	56
3.8	Recorded-to-total time ratio of Syracuse-3A received signal on monthly basis.	57
3.9	Recorded-to-total-time ratio of 2DVD rainfall rate on monthly basis.	57
3.10	A sample of received signal and noise floor level during clear sky condition measured using USRP-N210.	58
3.11	Flow chart of the process of rain attenuation time series	60
3.12	Deep fades on signal level (a) causing loss of lock in frequency (b) on 3 rd July 2015	61
3.13	Processing of loss of lock (a) time frame of loss lock detection (flagging) (b) valid signal data on 3 rd July 2015.	62
3.14	(a) Power spectral density (b) corresponding time series of received signal on 13 th July 2015 for Syracuse-3A satellite beacon receiver.	64
3.15	Syracuse-3A beacon received signal level without and with LPF effects on 13 th July 2015	65
3.16	Process of obtaining time series of rain attenuation on 1 st July 2015 for Beacon receiver (a) Time series of received signal (b) Time series of rain rate (c) Time series of rain attenuation obtained from the process	66
3.17	Work flow of SC-SST model (Lam <i>et. al.</i> , 2012)	70
4.1	Cumulative distributions of rainfall rate measured from 2DVD and rain gauge in UTM, Johor Bahru compared with ITU-R prediction.	75
4.2	Monthly distribution of stratiform and convective rainfall events.	76
4.3	Cumulative distribution of rainfall rate by discrimination of rain type events.	76
4.4	Time series of (a) rainfall rate (b) received signal (c)	77

rain attenuation measured on 21st May 2016.

4.5	Cumulative distributions of measured rain attenuation obtained from UTM, Johor Bahru in comparison with measured statistics in Singapore (tropical region), Ottawa (temperate region) and ITU-R P.618-12 model.	79
4.6	Number of fade events exceeding a given duration.	81
4.7	Statistics of fade occurrences measured in UTM-Johor Bahru in comparison with statistics in Madrid, Spain at 3 dB attenuation thresholds.	82
4.8	Number of inter-fade events exceeding a given duration.	84
4.9	Conditional distribution of fade slope with $\Delta t = 2s$ and $\Delta t = 30s$ at attenuation thresholds (a) 1 dB and (b) 5 dB.	85
4.10	Conditional distribution of fade slope for different attenuation thresholds.	86
4.11	Cumulative distribution of fade slope for different attenuation thresholds.	86
4.12	Cumulative distribution of fade rise and fade fall at different attenuation thresholds.	87
4.13	Conditional distributions of fade slope for three different locations that represent two climate regions: Johor Bahru, Malaysia and Delhi, India (tropical) and Eindhoven, Netherlands (temperate).	88
4.14	Standard deviation of fade slope, σ_{ξ} as a function of attenuation for different time intervals, Δt .	90
4.15	Cumulative distributions of measured rain attenuation in monthly basis compared to the worst month statistic predicted by ITU-R P.841-4.	91
4.16	Cumulative distribution of measured rain attenuation in seasonal basis	91
4.17	Wind direction and speed in Johor Bahru on seasonal basis (a) Northeast (b) Southwest (c) Pre-Northeast (d) Pre-Southwest	92
4.18	Hourly rain attenuation at different attenuation thresholds	95

4.19	Cumulative distribution of measured rain attenuation on diurnal basis.	96
4.20	Diurnal variation of fade duration at attenuation thresholds (a) 3 dB and (b) 10 dB.	97
4.21	Diurnal variation of inter-fade duration at attenuation thresholds (a) 3 dB and (b) 10 dB.	97
4.22	Clock hourly standard deviation of fade slope, σ_{ξ} as a function of attenuation on seasonal variation (a) Northeast (b) Southwest (c) Pre-Northeast (d) Pre-Southwest.	99
4.23	Comparison of probability of occurrences of fades exceeding given duration between measurement in Johor Bahru and ITU-R prediction model.	100
4.24	Comparison of probability of occurrences of fades exceeding given duration between measurement in Johor Bahru and CRC prediction model.	101
4.25	Probability of occurrences of fades exceeding given duration for measured and fitted data.	102
4.26	Probability of occurrences of inter-fades exceeding given attenuation for measured and fitted data.	103
4.27	Cumulative distribution of fade duration for measurement in Johor Bahru, ITU-R P.1623-1 model, SC-SST and SST model at attenuation thresholds of (a) 3 dB and (b) 10 dB	106
4.28	Cumulative distribution of inter-fade duration for measurement in Johor Bahru, SC-SST and SST model at attenuation thresholds (a) 3 dB and (b) 10 dB.	107
4.29	Cumulative distribution of absolute fade slope for measurement in Johor Bahru, ITU-R P.1623-1 model, SC-SST and SST model at attenuation thresholds of (a) 3 dB and (b) 10 dB.	109
4.30	Percentage of time exceeded for a given attenuation as a function of time delay.	113
4.31	Diversity gain for a given attenuation as a function of time delay.	114
4.32	Comparison of relative diversity gain between measured statistics in Ka-band and Ku-band (Jong <i>et</i>	115

al., 2015) at UTM-Johor bahru site for attenuation thresholds (a) 2 dB (b) 4 dB.

4.33	Comparison of time exceeded for a given attenuation between measured data in UTM-Johor Bahru with gamma and log-normal approximation.	116
4.34	Time exceeded for a given attenuation for measured and gamma fitted as a function of time delay.	117
4.35	The α and β parameters correlation to time delay.	118

LIST OF ABBREVIATIONS

ATS	-	Application Technology Satellite
ACTS	-	Advanced Communication Technology Satellite
BER	-	Bit Error Rate
CCDF	-	Complementary Cumulative Distribution Function
COMSTAR	-	Commercial Communication Satellite
COST	-	Cooperation in Science and Technology
CRC	-	Communications Research Centre Canada
DAH	-	Dissanayake, Allnut and Haidara
DLPC	-	Downlink Power Control
ECMWF	-	European Centre for Medium-Range Weather Forecasts
ENSO	-	El Niño- Southern Oscillation
ESA	-	European Space Agency
EU	-	European Union
EXCELL	-	Exponential Cell
IF	-	Intermediate Frequency
FFT	-	Fast Fourier Transform
ITALSAT	-	Italian Satellite
ITU-R	-	International Telecommunication Union, Radio Communication Sector
JR	-	Joanneum Research
KLIA	-	Kuala Lumpur International Airport
LNB	-	Low Noise Block Down Converter
MMD	-	Malaysia Meteorological Department
PDF	-	Probability Density Function
PIMT	-	Propagation Impairment Mitigation Technique
PSU	-	Power Supply Unit
QoS	-	Quality of Service
RAL	-	Rutherford Appleton Laboratory
RF	-	Radio Frequency
RHCP	-	Right Hand Circular Polarization

RHI	-	Range Height Indicator
RMS	-	Root Mean Square
SatCom	-	Satellite Communication
SatNex	-	Network of Experts for satellite communications
SC	-	Stratiform-Convective
SIRIO	-	Satellite Italiano di Ricerca Industriale e Operative
SST	-	Synthetic Storm Technique
SYRACUSE	-	Systeme de Radio Communication Utilisant Un Satellite
ULPC	-	Uplink Power Control
UPS	-	Uninterrupted Power Supply
USRP	-	Universal Software Radio Peripheral
UTC	-	Universal Time Coordinated
UTM	-	Universiti Teknologi Malaysia
WINDS	-	Wideband Internetworking Engineering Test and Demonstration Satellite
2DVD	-	2 Dimension Video Disdrometer

LIST OF SYMBOLS

A	-	Attenuation
d, D	-	Duration of fades
f_c	-	Cut-off frequency
P	-	Probability
Q	-	Standard cumulative distribution function
$R_{0.01}$	-	Rain intensity exceeded for 0.01%
Δt	-	Time daly
ξ	-	Fade slope
α	-	Power law exponential coefficient
k	-	Power law multiplier coefficient
x_o	-	Location of ground station
Δx	-	Shift that account the path enters layer A
γ	-	Specific attenuation
L	-	Effective path length
h_r	-	Rain height
h_s	-	Height above mean sea level
μ	-	Mean
σ	-	Standard deviation
f	-	Frequency
θ	-	Elevation angle
φ	-	Latitude and longitude of the Earth station
τ	-	Wave polarization
v	-	Storm translation speed
$g(p)$	-	Relative diversity gain

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	List of Publications and Awards	134
B	Fade Dynamics Model	136
C	Fresnel Ellipsoid	142
D	Verification Test Results	143
E	Link Budget	149
F	Low Pass Filter (LPF)	150
G	Yearly Average Wind Velocity	154
H	Seasonal Fade and Inter-Fade Duration Analysis	155
I	Fade Duration Distribution Fitting	156
J	Inter-Fade Duration Distribution Fitting	157
K	Slant Path Fade Duration Statistics	158
L	Slant Path Inter-Fade Duration Statistics	159
M	Slant Path Fade Slope Statistics	160
N	Probability Distribution Relevant to Radiowave Propagation Modeling (ITU-R P.1057-2, 2007)	161
O	Curve Fitting Techniques	167

CHAPTER 1

INTRODUCTION

1.1 Research Background

The evolution of satellite communication (SatCom) systems using Ka-band frequency is an emerging trend to meet the growing demand of high broadband services. Ka-band feature narrow spot beams (0.5° to 1.5° at 3dB beam width) which allows an extensive frequency reuse with wider spectrum availability than at the Ku-band. These new mode of high throughput satellites enable larger amount of bandwidth to support higher transmission rates thus opening the door to faster, cheaper and efficient communication for the user.

However, the major drawback of this Ka-band is their strong attenuation phenomena due to atmospheric propagation to the ground such as ice depolarization, gaseous attenuation, cloud and fog attenuation, rain attenuation and amplitude scintillation. Among these, rain is the certainly dominant impairment that limits the reliability and high availability of the system. This situation is more intense in the tropical/equatorial regions including Malaysia and this is mostly attributable to the high rainfall intensity and large raindrop size characterizing rainfall events in the tropics (Ismail and Watson, 2000). Thus, large rain attenuation at the Ka-band may not fully compensated by static power margins, instead application of advanced Propagation Impairment Mitigation Techniques (PIMTs) are necessary (Castanet. *et al.*, 2007).

In order to properly design and implement the PIMTs, it is necessary to have precise knowledge of the first- and second-order statistics of rain attenuation (Cheffena and Amaya, 2008). First-order statistics refers to the cumulative distribution of rain-induced attenuation, while second-order statistics describes the fade dynamic characteristics, including fade duration, fade slope, and inter-fade duration. System designers use the information on these distributions when choosing error-correction

codes, especially to specify the best modulation schemes, range of uplink power control (ULPC), and the tracking speed of PIMTs (Cheffena and Amaya, 2008). These are the great concern in the capacity planning and designing robust satellite links to meet the availability requirements to the user.

To that aim, numerous propagation measurement campaigns have been actively carried out to characterize the dynamic behavior of rain attenuation experienced by satellite radio links. Unfortunately, most of the studies have been concentrated in temperate regions that exhibit lower rainfall rates compared with tropical and equatorial region (Matriacianni, 1997; Van de Kamp, 2003; Franklin *et al.*, 2006; Garcia-del-Pino *et al.*, 2010; Gracia-Rubia *et al.*, 2011). A reliable measurement data of Ka-band signals in these regions are very limited and only concentrated on first-order statistic of rain attenuation (Yeo *et al.*, 2014). Adding to that, a study on fade dynamics statistics in tropical/equatorial regions particularly in Malaysia have been carried out in the past but only focuses on Ku-band frequencies (Dao *et al.*, 2013; Mandeep, 2013; Jong *et al.*, 2014).

As consequences, the crucial statistics of fade dynamics at Ka-band frequencies in the tropical/equatorial region remain an interesting topic of investigation. Therefore, this study is to explore those crucial statistics in an equatorial site by exploiting the propagation measurement campaign carried out at Universiti Teknologi Malaysia (UTM) in Johor Bahru, Malaysia. In addition, a mitigation technique namely Time Diversity is explored to mitigate the increased rain fades at Ka-band and improves overall link availability. This work demonstrates that is feasible to use the Ka-band to support SatCom mission operation in tropical/equatorial region.

1.2 Problem Statement

As briefly mentioned above, dynamic characteristics of fading due to atmospheric propagation are of great concern in optimizing system capacity. In this

respect, several problem statements that need to be addressed and resolved in this thesis work are summarized as below:

A study of atmospheric impairments involving the experimental measurement of received signal strength under various weather conditions is needed to develop a better understanding of channel characteristics and improve the design of modern SatCom systems. However, reliable measurement data on Ka-band signals in tropical/equatorial region are still in scarce (Jong *et al.*, 2016). Therefore, this work presents a statistical analysis of rain attenuation based on measurement data of Ka-band propagation measurement campaign that was carried out in Malaysia. The information from rain attenuations statistics will help system designers to determine reliable fade margin required in setting up the best quality of service (QoS) of the link to end users. Recommendation ITU-R S.1557 (2006) was used to calculate propagation attenuation in this study. Ka-band frequency usually provides link availability of 99.7% to 99.9% of the year. The uplink availability is assumed to be 99.95% of the year and the downlink availability is assumed to be 99.8% of the year; this results in an overall system availability of 99.75% of the year (ITU-R, 2006).

Although the statistics distribution of rain attenuation gives important information for the design of link margin, this information should be completed with parameters that allow the characterization of fade dynamics; including fade duration, inter-fade duration and fade slope statistics. The information of fade dynamics is important for system designers to appropriately implement PIMTs in a way to increase system availability and reliability of the system. For example, an assessment of link availability solely based on rain attenuation statistics can leads to very high power margin (Vilar *et al.*, 1988). This misuse of system resources unnecessarily escalates the cost of service. Thus, the knowledge from fade duration statistics that described when and how frequent the service is available could help system designers to decide whether to go for mitigation of fading or wait for the signal recovery. Up to date, only few researchers have performed the analysis of fade dynamics in tropical and equatorial regions (Dao *et al.*, 2013; Mandeep, 2013; Jong *et al.*, 2014) and all of these studies were only focuses on Ku-band frequencies. Higher frequency bands are more susceptible to weather effects than lower frequency bands which consequently leads

to much serious communication link outage during heavy rain events. Hence, precise information on fade dynamics at Ka-band is needed as they will provide different characteristics than in Ku-band.

Besides statistical analysis of fade dynamics from experimental database, it is essential to have an alternative method to predict fade dynamic characteristics as the measured data is not always available. Moreover, many existing fade dynamics prediction model such as ITU-R P.1623-1 (2005) might not satisfies tropical/equatorial statistics, as they were developed mainly based on measurements done in temperate climate. Therefore, the Stratiform-Convective Synthetic Storm Technique (SC-SST) (Lam *et al.*, 2012) is proposed to estimate rain fade dynamics in tropical/equatorial region taking advantage of local weather features from rainfall rate measured data. SC-SST is an adaptation from the conventional dual-layer SST model which has match pretty well not only for long-term first order statistics but as well as fade dynamics statistics particularly in temperate climates (Matricianni, 1997). On the other hand, SC-SST separately considering the types of rain events (i.e. stratiform and convective events) is very much likely to be used in the tropics as it is more suited to the local peculiarities. Adding to that, the use of synthetic models in the present study to characterise fade dynamics particularly for tropical/equatorial climate is not yet very well documented in the literature.

The application of time diversity in SatCom systems to reduce the effect of severe rain attenuation is getting more attention as it can provide high level of gain by an accurate retransmission with low-costs system (Fukuchi, 1992). There are numerous kind of method has been studied in the past to evaluate the performances of time diversity, such as analysis from direct measurement data (Fabbro *et al.*, 2009), through simulation weather radar maps (Luini *et al.*, 2011), and modelling approaches. However, up to now there are no model extensively validated has been proposed in the literature to estimate the performance of time diversity. As the statistical performance is related to local climatology, thus a global database of time diversity is needed. Therefore, it is worthwhile to further investigate and estimate the natural characteristics of time diversity distribution in tropical/equatorial region with respect to the experimental database.

1.3 Research Objectives

The objectives of this research study are listed as:

- (a) To determine rain fade and fade dynamic characteristics for Ka-Band Earth-space propagation link in Johor Bahru, Malaysia.
- (b) To evaluate and validate the performances of SC-SST model in predicting fade dynamic characteristics in equatorial region.
- (c) To provide applicable parameters of time diversity technique of PIMTs based on measured rain attenuation statistics.

1.4 Scopes of Work

The research scopes and limitation of this work are:

- (a) The work focuses on received signal data of Ka-band with frequency of 20.245 GHz (Syracuse-3A satellite) measured in UTM-Johor Bahru, Malaysia for one-year duration (July 2015 – June 2016).
- (b) The beacon receiver has approximate dynamic range of 30 dB and minimum required C/N_o shall be 28 dB.
- (c) The SC-SST prediction model is performed based on one-minute rainfall rate datasets obtained from 2DVD measurement at the same site with same duration.
- (d) Rain rate threshold of 10 mm/h has been selected in the discrimination of stratiform and convective events to generate SC-SST rain attenuation statistics. The selection is based on rain profile model that use an exponential-shaped of rain spatial distribution for convective events (Stutzman and Dishman, 1982). Later it was proven to be an effective technique to be used in the tropics owing

to its simple discrimination threshold yet effectively maintain the prediction accuracy of the stratiform-convection separation (Capsoni *et al.*, 2009; Lam *et al.*, 2013).

- (e) Wind velocity which is one of the input parameters for SC-SST prediction model is extracted from one-year radiosonde data measured at Kuala Lumpur International Airport (KLIA), Sepang at a pressure level of 700 mbar.
- (f) The performance of fade dynamics estimated from SC-SST model with respect to measured data is evaluated by means of figure of merit.

1.5 Research Contributions

Satcom systems operating at higher frequency bands (Ka-band and above) in tropical/equatorial climates are severely degraded by many fade occurrences due to heavy rain. An appropriate PIMTs is needed by the service providers to be used during severe rain fade periods to compensate link impairment thus provide high QoS to end users. In order to establish reliable Earth-space communication services in these heavy rain regions, comprehensive study of the effect of rain attenuation on the satellite propagation path needs to be quantified. To this aim, this work mainly focused on the knowledge of propagation channel characteristics at Ka-band based on local peculiarities, which is important in the implementation of PIMTs. The main contributions have been identified as follows:

- (a) The first contribution focuses on the analysis of rain intensity, rain attenuation, and fade dynamics (i.e. fade duration, fade slope and inter-fade duration) in equatorial site. Statistical analyses are presented on annual, seasonal, monthly and diurnal basis. The information obtained will be useful to system engineers for link budget analysis in order to obtain the required fade margin for optimal system performances in tropical/equatorial region as well as in the design and implementation of PIMTs.

- (b) In second contribution, the SC-SST model is proposed for the prediction of fade dynamics in the absence of measured rain attenuation time series, starting with local rainfall rate time series. SC-SST model seems to be in reasonable agreement with the actual measurement carried out in this particular area. These characteristics provide essential information on expected evolution of fade dynamics which is particularly important in choosing economical link margin and a suitable adaptive power control subsystem.
- (c) The last contribution of this work is the characterization and modeling of time diversity technique based on time correlation of attenuation time series. This approach considers that the conditional statistics follows a gamma law which is extracted during the rain attenuation event. The results can provide system engineers with critical information in the design and implementation of PIMTs, and it is expected that the probability of system outages will be greatly reduced.

1.6 Thesis Organization

This thesis is presented in five chapters. This chapter provides an overview of the research background on the topic of interest and identifies problem statements that need to be resolved. This section outlines the research objectives, scope of work and highlights the contributions of this work. The remaining chapters of the thesis are organized as follows.

Chapter 2 begins by discussed the main features of climatology characteristics in tropical and equatorial region, particularly in equatorial Malaysia. These characteristics include type of precipitation, seasonal and diurnal variations of rain attenuation. Then, a review of fade dynamics characteristics with respect to measured study carried out in temperate and tropical/equatorial region at Ka-band are given. Next followed by the slant path rain attenuation channel model as well as fade dynamic prediction models that have been developed and proposed in the literature, are briefly discussed. Afterward, time diversity technique as one of the PIMTs is also presented. Finally, some brief introduction to Syracuse satellite communication system.

Chapter 3 focuses on the methodology and concept used in this work. It begins by providing an overview of the methodology of this work including the flow chart for ease of understanding. Two sets of equipment are described, Satellite Beacon Receiver and 2D-Video-Disdrometer, which are used to collect time series of received signal and rainfall rate, respectively. Detailed discussions on rain attenuation data processing as well as scintillation filtering and clear sky reference level description are also presented. Afterwards, a specific calculation is provided for the distribution of fade dynamics, especially fade slope which aims to characterize the dynamic characteristics of rain attenuation. In addition, this chapter also provides a brief discussion on the key concept and necessary input parameters for SC-SST rain attenuation prediction model. Finally, specific information on time diversity assessment and modeling which relies on the time correlation of rain attenuation time series are provided.

Chapter 4, which presents the results of this work, is divided into three parts. First, discussion on the statistical analysis of rain intensity, and fade dynamics which includes parameters such as fade duration, inter-fade duration and fade slope. The analysis includes discussion on seasonal, monthly and diurnal variations and its impact on overall system performances. Then, comparison analysis of fade dynamic prediction models from several established literatures together with performances of SC-SST in estimating fade dynamics are also given. Lastly, evaluation on the performances and modeling of time diversity that aims to mitigate rain attenuation on Earth-space path link are presented.

Chapter 5 presents the conclusion and future works. The major works in this thesis are concluded and summarized, followed by some constructive recommendations for future work.

REFERENCES

- Abdullah, N. A., Shuhaimi, S. H., Toh, Y.Y., Shapee, A. H., and Mohamad, M. (2011). The Study of Seasonal Variation of PM10 Concentration in Peninsular Sabah and Sarawak. *Malaysian Meteorology Department*, 9, 1-27.
- Acosta, R. J., Matricianni, E., and Riva, C. (2013). Slant Path Attenuation and Microscale Site Diversity Gain Measured and Predicted in Guam with the Synthetic Storm Technique at 20.7 GHz. *7th European Conference on Antennas and Propagation (EuCAP)*. 8-12 April, Gothenburg, 61-64.
- Alhilali, M., Din, J., Schoenhuber, M. and Lam, H. Y. (2017). Estimation of Milimeter Wave Attenuation Due to Rain using 2D Video Disdroemeter Data in Malaysia. *International Journal of Electrical Engineering and Computer Sciences*.
- Amaya, C. and Nguyen, T. (2010). Propagation Measurements in Ottawa with the Ka-Band Beacon of the ANIK F2 Satellite. *Proceeding of Antenna Technology & Applied Electromagnetics Conference*, 5-8 July, Canada.
- Amaya, C. (2011). Fade Duration and Fade Slope Statistics derived from Long-Term ANIK F2 Satellite Beacon Measurements in Ottawa, Canada. *URSI General Assembly and Scientific Symposium (GASS)*, 13-20 Aug, Istanbul.
- Arapoglou, P. D. M., Panagopoulos, A. and Cottis, P.G. (2008). An Analytical Predictiob Model of Time Diversity Performance for earth-Space Fade Mitigation. *International Journal of Antennas and Propagation*.
- Badron K, Ismail, A. F., Asnawi, A., Nordin, M. A. W., Zahirul Alam, A. H. M. and Khaz, Z. (2015). *Classification of Precipitation Types Detected in Malaysia*. Theory and Applications of Applied Electromagnetics, pp. 13-21.
- Boulangier, X., Gabard, B., Casadebaig, L. and Castanet, L. (2015). Four Years of Total Attenuation Statistics of Earth-Space Propagation Experiments at Ka-Band in Toulouse. *IEEE Transactions on Antennas and Propagation*, 63(5), 2203-2214.
- Braten, L. E., Amaya, C. and Rogers, D. V. (2001). Fade and Inter-Fade Duration at Ka-Band on Satellite Earth Links: Modeling and System Implications. *19th AIAA International Communication Satellite Systems Conference*, May,

Toulouse, France.

- Bryant, G. H., Adimula, I., Riva, C. and Brussaard, G. (2001). Rain Attenuation Statistics from Rain Cell Diameters and Heights. *International Journal of Satellite, Communications and Networking*, 19(3), 263-283.
- Capsoni, C., Fedi, F., Magistroni, C., Paraboni, A. and Pawlina, A. (1987). Data and Theory for a New Model of the Horizontal Structure of Rain Cells for Propagation Applications. *Radio Science*, 22(3), 395-404.
- Capsoni, C., Luini, L., Paraboni, A. and Riva, C. (2006). Stratiform and Convective Rain Discrimination Deduced from Local P(R). *IEEE Transactions on Antennas and Propagation*, 54(11), 3566-3569.
- Capsoni, C., Luini, L., Paraboni, A., Riva, C. and Martelucci, A. (2009). A New Prediction Model of rain Attenuation that Separately Accounts for Stratiform and Convective Rain. *IEEE Transactions on Antennas and Propagation*, 57(1), 196-204.
- Capsoni, C., D'Amico, M., Nebuloni, R. and Riva, C. (2011). Performance of Site Diversity Technique from Time Diversity. *5th European Conference on Antennas and Propagation (EuCAP)*, 11-15 April, Rome, 1463-1466.
- Castanet, L., Lemorton, J. and Bousquet, M. (1998). Fade Mitigation Techniques for New SatCom Services at Ku-Band and above: A Review. *4th Ka-band Utilization Conference*, Venice, Italy, 2-4 Nov.
- Castanet, L. (2007). *Influence of the Variability of the Propagation Channel on Mobile, Fixed Multimedia and Optical Satellite Communications*. Germany: Shaker Verlag GmbH.
- Castanet, L., Csurgai-Horvath, L., Lacoste, F., Riva, C., Fiebig, U., Martellucci, A., Panagopoulos, A., Javornik, T., Jeannin, N., Leitgeb, E., Thompson, P., Pastoriza, V. (2008). Channel modelling activities related to atmospheric effects in the SatNEx project. *3rd European Conference on Antennas and Propagation (EuCAP)*, 23-27 March, Germany.
- Chambers, A. P., Callaghan, S. A., and Otung, I. E. (2006). Analysis of Rain Fade Slope for Ka and V Band Satellite Links in Southern England. *IEEE Transactions on Antennas and Propagation*, 54(5), 1380-1387.
- Cheffena, M., and Amaya, C. (2008). Prediction Model of Fade Duration Statistics for Satellite Links between 10-50 GHz. *IEEE Antennas and Wireless Propagation Letters*, 1, 260-263.

- Chodkaveekityada, P. and Fukuchi, H. (2016a). Differences in the Dynamic Properties of Rain Fade between Temperate and Tropical Regions. *Advances in Space Research*.
- Chodkaveekityada, P. and Fukuchi, H. (2016b). Time Diversity Evaluation for Attenuation Mitigation Method using Attenuation Data in Thailand and Japan.. *International Journal of satellite Communication and Networking*.
- COST 205. (1985). Influence of the Atmosphere on Radio Propagation on Satellite Earth Paths at Frequencies above 10 GHz. ISBN: 92-825-5412-0.
- COST 225. (2002). Radio wave Propagation for SatCom Services at Ku-Band and above. ISBN: 92-9092-608-2.
- Cox, D. C. and Arnold, H. W. (1982). Results from the 19- and 28-GHz COMSTAR Satellite Propagation Experiments at Crawford Hill. *Proceeding of IEEE*, 17 (5), 458-488.
- Crane, R. K. (1982). A Two-Component Rain Model for The Prediction of Attenuation Statistics. *Radio Science*, 17(6), 1371-1378.
- Dao, H., Islam, M. R., and Al-Khateeb, K. A. S (2013). Rain Fade Slope Model in Satellite Path Based on data Measured in Heavy rain Zone. *IEEE Antennas and Wireless Propagation Letters*, 12, 50-53.
- Das, S., Shukla, A. K. and Maitra, A. (2009). Classification of Convective and Stratiform Types of Rain and Their Characteristics Features at a Tropical Location. *4th International Conference on Computers and Devices for Communications*. 14-16 Dec., Kolkata, 1-4.
- Das, D. and Maitra, A. (2014). Time Series Prediction of Rain Attenuation from Rain rate Measurement using Synthetic Storm Technique for a Tropical Location. *International Journal of Electronics and Communication*, 68, 267-282.
- Davarian, F. (1996). Ka-Band Propagation Research using ACTS. *International Journal of Satellite Communication and Networking*, 14(3), 267-282.
- Dintelmann, F. (1981). Analysis of 11 GHz Slant path Fade Duration and Fade Slope. *Electronics Letters*, 17(7), 267-268.
- Dissanayake, A., Allnur, J. and Haidara, F. (1997). A Prediction Model that Combines Rain Attenuation and Other Propagation Impairments along Earth-Satellite Paths. *IEEE Transactions on Antennas and Propagation*, 45(10), 1546-1558.
- Fabbro, V., Castanet, L., Croce, S. and Riva, C. (2009). Characterization and Modelling of Time Diversity statistics for Satellite Communications from 12

- to 50 GHz. *International Journal of Satellite Communications*, 27, 87-101.
- Feil, J., Ippolito, L. J., Hel;mken, H., Mayer, C. E., Horan, S. and Henning, R. E. (1997). Fade Slope Analysis for Alaska, Florida, and New Mexico ACTS Propagation Data at 20 and 27.5 GHz. *Proceedings of the IEEE*, 85(6), 926-935.
- Fiebig, U. –C. and Riva, C. (2004). Impact on Seasonal and Diurnal variations on satellite System Design in V band. *IEEE Transactions on Antennas and Propagation*, 52(4), 923-932.
- Filip, M, Martellucci, A, Willis, M.J., Bousquet, M. (2003) COST 280: propagation impairment mitigation for millimetre wave radio systems. *Twelfth International Conference on Antennas and Propagation (ICAP 2003)*, 2, 573-576.
- Franklin, F. F., Fujisaki, K. and Tateiba, M. (2006). Fade Dynamics on earth-space Paths at Ku-Band in Fukuoka, Japan. *Electronic Letters*, 41(25), 5-6.
- Fukuchi, H. (1992). Slant Path Attenuation Analysis at 20 GHz for Time-Diversity Reception of Future Satellite Broadcasting. *Proceeding of the URSI-F Open Symposium Colloque*, 6.5.1-6.5.4.
- Garcia-del-Pino, P., Riera, J. M., and Benarroch, A. (2010). Fade Slope Statistics on a Slant Path at 50 GHz. *IEEE Antennas and Wireless Propagation Letter*, 9, 1026-1028.
- Garcia-del-Pino, P., Riera, J. M., and Benarroch, A. (2010). Fade and Inter-Fade Duration Statistics on Earth-space Link at 50 GHz. *IET Microwaves, Antennas and Propagation*, 5, 790-794.
- Garcia-Rubia, J. M., Riera, J. M. and Garcia-del-Pino, P. (2017). Fade and Inter-fade Duration Characteristics in a Slant-Path Ka-band Link. *IEEE Transaction on Antennas and Propagation*, 65(12), 7198-7206.
- Garcia-Rubia, J. M., Riera, J. M., Garcia-del-Pino, P., and Benarroch, A. (2011). Propagation in the Ka-Band: Experimental Characterization for Satellite Applications. *IEEE Antennas and Propagation Magazine*, 53(2), 65-76.
- Goldhirsh, J. (1995). Rain Rate Duration Statistics over a Five-Year Period: A Tool for Assessing Slant Path Fade Durations. *IEEE Transactions on Antenna and Propagation*, 43(5), 435-439.
- Green, H. E. (2004). Propagation Impairment on Ka-Band SatCom Links in Tropical and Equatorial Regions. *IEEE Antennas and Propagation Magazine*, 46(2),

2004.

- Ismail, A. F., and Watson, P. A. (2000). Characteristics of Fading and Fade Countermeasures on a Satellite-Earth Link Operating in Equatorial Climate with Reference to Broadcast Applications. *IEEE Proceedings-Microwave Antennas Propag*, 147(5), 369-373.
- Ippolito, L. J. (1981). Effect of Precipitation on 15.3 and 31.65 GHz earth-space transmission with the ATS V Satellite. *Proceeding of IEEE*, 59, 189-205.
- ITU-R. S1557 (2006). System parameters of BSS between 17.3 GHz and 42.5 GHz and associated feeder links. Geneva.
- ITU-R P.1623-1 (2005). Prediction Method of Fade Dynamics on Earth-space Paths. Geneva.
- ITU-R P.311-16 (2016). Acquisition, presentation and analysis of data in studies of Radio wave propagation. Geneva.
- ITU-R P.618-13 (2017). Propagation Data and Prediction Methods required for the Design of Earth-Space Telecommunication Systems. Geneva.
- ITU-R P.838-3 (2005). Specific Attenuation Model for Rain for use in Prediction Methods. Geneva.
- ITU-R P.841-4 (2005). Conversion of annual statistics to worst-month statistics. Geneva.
- ITU Study Group 3 (2012). Fascicle Concerning the Rainfall rate Model Given in Annex 1 to Recommendation ITU-R P. 837-6.
- Jong, S. L., D' Amico, M., Din, J. and Lam, H. Y. (2014) Analysis of Fade Dynamic at Ku-Band in Malaysia. *International Journal of Antennas and Propagation*.
- Jong, S. L. (2015) *Rain Fade Dynamic Characteristics for Ku-Band Satellite Communication Systems in Malaysia*. Ph.D. Thesis. Universiti Teknologi Malaysia.
- Jong, S. L., Lam, H. Y., Din, J. and D' Amico, M. (2016). Investigation of Ka-Band Satellite Communication Propagation in Equatorial Regions. *ARPJN Journal of Engineering and Applied Sciences*, 10(20), 9795-9799.
- Jorge, F., Riva, C. and Rocha, A. (2016). Characterization of Inter-fade Duration for Satellite Communication Systems Design and Optimization in Temperate Climate. *Radio Science*, 51(3), 151-159.
- Khamis, N. H., and Yussuf A. I. O (2014) Determination of Melting Layer Boundaries and Attenuation Evaluation in Equatorial Malaysia at Ku-Band. *Bulletin of*

Electrical Engineering and Informatics, 3 (4), 293-154.

- Kourogiorgas, C., Panagopoulos, A., Livieratos, S. and Chatzarakis, G. E. (2013). On the Outage Probability Prediction of Time Diversity Scheme in Broadband Satellite Communication Systems. *Progress in Electromagnetics Research-C*, 44, 175-184.
- Kuhar, U., Hrovat, A., Kandus, G. and Vilhar, A. (2014). Statistical Analysis of 19.7 GHz Satellite Beacon Measurements in Ljubljana, Slovenia. *8th European Conference on Antennas and Propagation (EuCAP)*, 6-11 April, The Netherlands.
- Lam, H. Y., Luini, L., Din, J., Capsoni, C., and Panagopoulos, A. D. (2012). Investigation of Rain Attenuation in Equatorial Kuala Lumpur. *IEEE Antennas and Wireless Propagation Letters*, 11, 1002-1005.
- Lam, H. Y., Luni, L., Din, J. Capsoni, C. and Panagopoulos, A. D. (2013) Performance of SatCom Systems Implementing Time Diversity in Equatorial Malaysia. *8th European Conference on Antennas and Propagation*. 6-11 April, The Netherlands ,511-514.
- Leitao, M. J. and Watson, P.A. (1996). Method for Prediction of Attenuation on Earth-Space Links Based on Radar Measurements of the Physical Structure of Rainfall. *IEE Proceeding*, 133.
- Luini, L. and Capsoni, C. (2011). Preliminary Results from Physically-Based Methodology for the Evaluation of a Time Diversity System. *5th European Conference on Antennas and Propagation (EuCAP)*, 11-15 April. Rome, 1600-1604.
- Maekawa, Y., Miyamoto, S., Sawai, K. and Fukou, S. (2006). Estimation of rain attenuation characteristics of satellite communication links using X-band meteorological radars. *IEE Proceeding*.
- Mandeep, J. S. (2013). Fade Duration Statistics for Ku-band Satellite Links. *Advances in Space Research*. 52(3). 445-450.
- Marzuki, M., Kozu, T., Shimomai, T, randeu, H., Hashigychi, H and Shibagaki, Y. (2009). Diurnal Variation of Rain Attenuation obtained from Measurement of Raindrop Size Distribution in Equatorial Indonesia. *IEEE Transactions on Antennas and Propagation*, 57(4), 1191-1196.
- Matricianni, E. (1981). Rate of Change of Signal Attenuation from SIRIO at 11.6GHz. *Electronics Letters*, 17, 139-141.

- Matricianni, E. (1996a). Physical Mathematical Model of the Dynamics of Rain Attenuation Based on Rain Rate Time Series and a Two-Layer Vertical Structure of Precipitation. *Radio Science*, 31(2), 281-295.
- Matricianni, E., Mauri, M. and Riva, C. (1996b). Relationship between Scintillation and Rain Attenuation at 19.77 GHz. *Radio Science*, 31(2), 272-279.
- Matricianni, E. (1997). Prediction of Fade Durations due to rain in Satellite Communication System. *Radio Science*, 32(3), 935-941.
- Matricianni, E., Riva, C., and Castanet, L. (2006). Performance of the Synthetic Storm Technique in a Low Elevation Angle 5° Slant Path at 44.5 GHz in the French Pyrenees. *1st European Conference on Antennas and Propagation (EuCAP)*, 11-16 November, Edinburgh, 1-6.
- Matricianni, E., and Riva, C. (2008). The Search for the Most Reliable Long-Term Rain Attenuation CDF of a Slant Path and the Impact on Prediction Models. *IEEE Transaction on Antennas and Propagation*, 53(9), 3075-3079.
- Mauri, M. and Paraboni, A. (1981). Attenuation Statistics from Satellite SIRIO after three years activity in Italy. *Electronic Letters*, 17(13), 440-441.
- Nelson, B. and Stutzman, W. L. (1996). Fade Slope on 10 to 30 GHz Earth Space Communication Links-Measurement and Modelling. *IEE Proceeding of Microwave, Antennas and Propagation*, 143(4), 353-357.
- Ojo, J. S. and Owolawi, P. A. (2015). Application of Synthetic Storm Technique for Diurnal and Seasonal Variation of Slant Path Ka-Band Rain Attenuation Time Series over a Subtropical location in South Africa. *International Journal of Antenna and Propagation*.
- Pan, Q. W., and Allnut, J. E. (2004). 12 GHz Fade Durations and Intervals in the Tropics. *IEEE Transaction on Antennas and Propagation*, 52(3), 693-701.
- Panagopoulos, A. D., Arapoglou, P. -D. M., Cottis, P. G. (2004). Satellite Communications at Ku, Ka, and V-Banda: Propagation Impairments and Mitigation Techniques. *IEEE Communication Surveys & Tutorials*. 6(3), 2-14.
- Paraboni, A. and Riva, C. (1994). A New Method for The Prediction of Fade Duration Statistics in Satellite Links Above 10 GHz. *International Journal of Satellite, Communication and Networking*, 12(4), 387-394.
- Riva, C. (2004). Seasonal and Diurnal Variations of Total Attenuation Measured with the ITALSAT Satellite at Spino d'Adda at 18.7, 39.6 and 49.5 GHz. *International Journal of Satellite Communications and Networking*, 22, 449-

- Rocha, A.C. (2012). XPD at Ka-Band from Extended Earth-Satellite Propagation Campaign. *6th European Conference on Antennas and Propagation (EuCAP)*, 26-30 March. Prague.
- Satellite Tracking System (2017) <http://www.n2vo.com/footprints> (Online accessed).
- Safaai-Jazi, A., Ajaz, H. and Stutzman, W. L. (1995). Empirical Models for Rain Fade Time on Ku- and Ka-Band Satellite Links. *IEEE Transaction on Antennas and Propagation*, 43(12), 1411-1415.
- Schnell, M. and Fiebeg, U. –C. (1997). Fade Slope Statistics of 40 GHz Beacon Signals. *Electronic Letters*, 33(21), 1819-1821.
- Schumacher C., and Houze R. A. Jr. (2003). Stratiform rain in the tropics as seen by the TRMM Precipitation Radar, *Journal of Climate*, 16, 1739–1756.
- Schonhuber, M., Lammer, G. and Randeu, W. (2007). One Decade of Imaging Precipitation Measurement by 2D-Video-Disdrometer. *Advances in Geosciences*, 10, 85-90.
- Steiner, M., Houze, R. A. Jr. and Yuter, S. E. (1995). Climatological Characterization of Three-Dimensional Storm Structure from Operational Radar and Rain Gauge. *Journal of Applied Meteorology*, 34, 1978-2007.
- Stutzman, W. L. and Dishman, W. K. (1982). A Simple Model for the Estimation of Rain-Induced Attenuation along Earth-Space Paths at Millimetre Wavelengths. *Radio Science*, 17(6), 1465-1476.
- Sujimol, M. R., Acharya, R., Singh, G. and Gupta, R. K. (2015). Rain Attenuation using Ka- and Ku- band Frequency Beacons at Delhi Earth Station. *Indian Journal of Radio and Space Physics*, 44(1), 45-50.
- Sweeney, D. G. and Bostian, C. W. (1992). The Dynamics of Rain Induced fades, *IEEE Transaction on Antennas Propagation*, 43(1), 54-62.
- Tanggang, F., Raheleh, F., Ali, M., Jamaluddin, A. F. and Liew, J. (2017). Characteristics of Precipitation Extremes in Malaysia associated with El Nino and La Nina Events. *International Journal of Climatology*.
- Timothy, K. I., Ong, J. T. and Choo, E. B. L. (2000a). Fade and Non-Fade Duration Statistics for earth-Space Satellite Link in Ku-Band. *Electronic Letters*, 36(10), 894-895.
- Timothy, K. I., Ong, J. T. and Choo, E. B. L. (2000b). Descriptive Fade Slope Statistics on ITALSAT Ku_Band Communication Link. *Electronic Letters*, 36(16),

1422-1424.

- Udofia, K. M. and Otung, I. E. (2008). Evaluating Time Diversity Performance on On-Board Processing Satellite to Earth-Station Downlink. *2nd International Conference on Next Generation Mobile Applications, Services and Technologies*. 16-19 Sept, Cardiff, UK.
- Van de Kamp, M. M. J. L. (2003) Statistical Analysis of Rain Fade Slope. *IEEE Transaction on Antennas and Propagation*, 51(8), 1750-1759.
- Ventouras, S., Callaghan, S. A. and Wrench, C. L. (2006). Long-term Statistics of Tropospheric Attenuation from the Ka/U Band ITALSAT Satellite Experiment in the United Kingdom. *Radio Science*, 41(2), 1-19.
- Vilar, E., Burgueno, A., Puigcerver, M. and Austin, J. (1988). Analysis of Jointfall Rate and Duration Statistics: Microwave System Design and Implications. *IEEE Transactions on Communications*, 36(6), 650-661.
- Yeo, J. X., Lee, Y. H. and Ong, J. T. (2014). Rain Attenuation Prediction Model for Satellite Communications in Tropical Regions. *IEEE Transactions on Antennas and Propagation*. 62(11), 5775-5781.
- Yussuf, A. I., and Khamis, N. H. (2012). Rain Attenuation Modelling and Mitigation in the Tropics: Brief Review. *International Journal of Electrical and Computer Engineering*, 2(6), 748-757.
- Yussuf, A. I., Khamis, N. H. and Yahya, A. (2013). Performance Evaluation of rain Attenuation Models in A Tropical Station. *International Journal of Electrical and Computer Engineering*, 4(5), 782-789.
- Zhou, X. X., Lee, Y. H., and Ong, J. T. (2010). Effect of Diurnal of Rainfall in Satellite Systems at Ku- and Ka-Band in Singapore. *Proceeding of Asia-Pacific Microwave Conference*. 7-12 December. Yokohama, 1950-1953.