

International Workshop on Woman in Ceramic Science (WoCeram2019)

April 7-9, 2019/ Budapest, Hungary
Novotel Danube Budapest



Table of content

INVITED TALKS	3
Tanja Lube.....	3
C. Baudín.....	3
Lucyna Jaworska	4
Andreja Gajović et al.....	4
ORAL PRESENTATIONS.....	5
Saeed Mirzaei	5
Iulian Iordache et al.....	5
J. Szymanska et al.....	6
Elżbieta Bączek et al.	7
Carlos Gumiel et al.....	7
Jolanta Cyboron et al.....	8
Katarzyna Pasiut et al.	8
Pinar Kaya et al.	9
Alexandra Kovalcikova et al.	9
Lucie Pejchalová et al.....	10
S. Marković et al.	11
Tinoco Navarro L. K. et al.	11
F.Fülöp et al.....	13
POSTER PRESENTATIONS	14
J. Zygmuntowicz et al.	14
D. Vitiello et al.	14
Georgeta Velciu et al.	15
Alina Dumitru et al.	15
Milena Dojcinovic et al.	16
Maria V. Nikolic et al.	16
Kennedy. B et al.	17
A. Łętocha et al.	17
C. López-Pernía et al.	19
Marina Vukovic et al.....	19
Eva Stastna et al.....	20
Klara Castkova et al.....	21

TUNING THE OPTICAL, ELECTRICAL AND PHOTOELECTROCATALYTIC PROPERTIES OF ZNO MATERIALS BY VARYING OF INTRINSIC DEFECTS CONCENTRATION

S. Marković,¹ V. Rajić,² Lj. Veselinović,¹ I. Stojković-Simatović,³ J. Belošević-Čavor,² S.D. Škapin,⁴ J. Kovač,⁴ M. Nikolić,⁵ and D. Uskoković¹

¹Institute of Technical Sciences of SASA, Belgrade, Serbia

²Vinča Institute of Nuclear Sciences, University of Belgrade, Belgrade, Serbia

³Faculty of Physical Chemistry, University of Belgrade, Belgrade, Serbia

⁴Jožef Stefan Institute, Ljubljana, Slovenia

⁵Institute of Physics, University of Belgrade, Belgrade, Serbia

During the last decade zinc oxide (ZnO) has attracted considerable attention as a promising material for electronic, optoelectronic and spintronic devices. ZnO has a wide bandgap (3.37 eV at room temperature) and relatively large exciton binding energy (60 meV) which enables multifunctional application. Until now ZnO-based materials have been used as UV and blue light emitters, varistors, thermistors, semiconductors, photoanodes, and other. Various approaches have been applied to improve functional properties of zinc oxide, such as: fabrication of ZnO-based heterojunction particles, particles' surface sensitization, hydrogenation, etc. It has been found that intrinsic defects (vacancies, interstitials and antisites) in the crystal structure of a ZnO strongly influenced its electrical and optical properties. Thus, correlation of the intrinsic defects concentration with optical and electrical properties of ZnO materials is of great importance for their further application in opto-electronic devices.

In this study we investigated the influence of intrinsic defects concentration on the optical, electrical and photoelectrocatalytic properties of ZnO materials. To obtain ZnO powder with a high concentration of intrinsic defects microwave processing of precipitate was employed, while for further varying of defects concentration, the powder was thermally treated in three different atmospheres: air, argon and oxygen. The ZnO powder was uniaxially pressed ($P = 100$ MPa) in cylindrical compacts (\varnothing 6 mm and $h \approx 3$ mm) which were sintered in different atmospheres by heating rate of 10 °/min up to 1100 °C, and with dwell time of 1 h. To study a crystal structure of ZnO samples XRD and Raman spectroscopy were used, while for microstructural investigation field emission scanning electron micrographs were recorded. Optical properties were studied using UV-Vis diffuse reflectance spectroscopy. To reveal the role of intrinsic defects in ZnO crystal lattice on functional properties, XPS, photoluminescence, electroluminescence and electrochemical impedance spectra were analyzed. A detailed analysis of the experimental results imply that a high concentration of intrinsic defects, in particular oxygen vacancies, is of the greatest importance for tunable light-emitting diode application and significant for the photoanode properties. To support our experimental observation we performed *ab initio* calculations based on density functional theory (DFT).

SYNTHESIS AND CHARACTERIZATION OF ANATASE-BROOKITE TiO₂ NANOPARTICLES IN PRESENCE OF MCAA

Tinoco Navarro L. K., Michalička J., Častova Klara, Cihlař J., Veselý M., Dzik Petr

CEITEC-VUT Brno University of Technology

*Katherine.tinoco@ceitecvr.vut.cz

TiO₂ is well known as a superior material semiconductor. Nevertheless, TiO₂ as catalyst still presents some limitations regarding the accumulation of electrons in the conductive band that leads to recombination of the photoexcited electron-hole pairs during the Advance Oxidation Process-AOP. Furthermore, the extended band-gap energy (3.2 eV) is possible to reduce it in order reach the visible lighth spectrum for improving its photocatalytic activity. Three different crystal forms exist. Anatase, Rutile, and Brookite. However, reports from brookite phase are still scarce. The Anatase-Brookite