

Geophysical Research Abstracts  
Vol. 21, EGU2019-8355, 2019  
EGU General Assembly 2019  
© Author(s) 2019. CC Attribution 4.0 license.



## Assessment of methane emissions from a dairy farm using an inverse dispersion technique

Marcel Bühler (1,2,3), Christoph Häni (1), Thomas Kupper (1), Sabine Schrade (4), Michael Zähler (4), Simon A. Wyss (5), Joachim Mohn (5), Christof Ammann (6), Stefan Brönnimann (2,3)

(1) Bern University of Applied Sciences, School of Agricultural, Forest and Food Sciences HAFL ([marcel.buehler@bfh.ch](mailto:marcel.buehler@bfh.ch)), (2) University of Bern, Oeschger Centre for Climate Change Research (OCCR), Bern, Switzerland, (3) University of Bern, Institute of Geography, Switzerland, (4) Agroscope, Ruminants Group, Switzerland, (5) EMPA, Laboratory for Air Pollution/Environmental Technology, Switzerland, (6) Agroscope, Climate and Agricultural Group, Switzerland

Quantification of gaseous emissions from diffuse sources, for instance from animal and waste operations (AWO) are challenging, e.g. due to their heterogeneity in space and time. Inverse dispersion techniques are a promising option and are becoming more important in determining gaseous emissions from AWO as it is a low-cost and flexible to use method. One possible approach is to use a simple backward Lagrangian stochastic (bLS) model (Häni et al., 2018). To apply this model, a horizontal flat and homogeneous surrounding without any nearby sources is presupposed. However, these criteria are often not fulfilled. In the presented study, the applicability of the bLS model was tested under non-ideal model conditions on methane (CH<sub>4</sub>) emissions of a natural ventilated dairy housing with 40 cows in Switzerland. For the up- and downwind CH<sub>4</sub> concentration measurements, open-path tuneable diode laser spectrometers (GasFinder3.0, Boreal Laser, Inc., Edmonton, Alberta, Canada) were used. Data was collected during 30 days in autumn and 20 days in winter 2018. Results for the autumn and winter campaign were compared with simultaneous in-house CH<sub>4</sub> emission measurements conducted with a tracer ratio method. The tracer ratio technique is well-established to quantify diffuse emissions and has shown high accuracy in an extended validation study (Mohn et al., 2018). Therefore, this campaign provides the unique opportunity to compare temporal trends of CH<sub>4</sub> emissions and interpret bLS results with respect to non-ideal model conditions.

### Literature cited:

Häni, C., Flechard, C., Neftel, A., Sintermann, J., Kupper, T. 2018. Accounting for field-scale dry deposition in backward Lagrangian Stochastic dispersion modelling of NH<sub>3</sub> emissions. *Atmosphere* 9(4).

Mohn, J., Zeyer, K., Keck, M., Keller, M., Zähler, M., Poteko, J., Emmenegger, L., Schrade, S. 2018. A dual tracer ratio method for comparative emission measurements in an experimental dairy housing. *Atmos. Environ.* 179: 12-22.