



UNIVERSITI PUTRA MALAYSIA

***ADSORPTION AND BIODEGRADATION OF POLLUTANTS FROM
LIVESTOCK WASTEWATER BY AGED REFUSE BIOREACTOR***

ANIJIOFOR SANDRA CHINENYENWA

FK 2018 176



**ADSORPTION AND BIODEGRADATION OF POLLUTANTS FROM
LIVESTOCK WASTEWATER BY AGED REFUSE BIOREACTOR**

By

ANIJIOFOR SANDRA CHINENYENWA

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of
Doctor of Philosophy**

September 2018

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia.



DEDICATION

Dedicated to God Almighty,
my darling husband and precious children,
my loving mother and lovely sister Amaka,
for undying love and support throughout the period of my study



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Doctor of Philosophy

ADSORPTION AND BIODEGRADATION OF POLLUTANTS FROM LIVESTOCK WASTEWATER BY AGED REFUSE BIOREACTOR

By

ANIJIOFOR SANDRA CHINENYENWA

September 2018

Chairman : Nik Norsyahariati Nik Daud, PhD
Faculty : Engineering

This study investigated the characteristics of landfilled solid wastes, “aged refuse”, for adsorption and biodegradation processes, as an affordable livestock wastewater treatment option. Presently, the UPM dairy farm discharges about 2000-2200 L/day of untreated wastewater into a nearby river, raising serious environmental concerns, especially regarding water pollution. The parameters studied were pH, chemical oxygen demand (COD), biochemical oxygen demand (BOD), total suspended solids (TSS), total dissolved solids (TDS), turbidity, total nitrogen (TN), ammonia nitrogen (NH₃-N), total phosphorous (TP) and total coliform. Three sources of livestock wastewater (Dairy farm, chicken slaughter house and fishpond), were examined, while the aged refuse was collected from Air Hitam sanitary landfill, Selangor, Malaysia.

The results revealed aged refuse characteristics such as pH 7.14, moisture content 29.5%, organic content 9.90%, total coliform 7.1×10^6 CFU/100 mL, which are suitable conditions for biodegradation. Hydraulic conductivity 0.31 cm/s, porosity (n) 51%, and bulk density (ρ) 1.23 g/cm³, are suitable conditions for free water flow and air diffusion. The available exchangeable cations (Ca, Mg, K, Na), will promote ion exchange while low metal concentrations of (Pb = 0.858, Cr = 14.0, Cu = 1.10 and Zn = 12.16 mg/kg), will reduce interference. The scanning electron microscopy (SEM), showed available pore spaces, and BET surface area 3.376 m²/g, which are suitable for adsorption, while the Fourier Transform Infra-red (FTIR), revealed functional groups of carbonyl, carboxyl and hydroxyl groups, with strong adsorption capacity.

The batch adsorption study indicated the effects of pH, dosage and contact time on removal efficiency, and optimum conditions were; pH 6, dosage 2-4 g/100 mL, adsorbent size ≤ 2 mm, contact time 10-180 minutes, agitation speed 250 rpm and ambient temperature conditions. The maximum removal efficiency were about 94%

(COD, BOD), 91% (TSS, TDS), 97% colour and 88% NH₃-N. The correlation coefficient R² (0.9026 to 0.9999) for Langmuir, and (0.9422 to 0.9999) for Freundlich isotherms, fitted well to experimental data.

Furthermore, an aged refuse bioreactor (15 cm diameter and 80 cm height), was developed and used for livestock wastewater treatment at a loading rate of 4 L m³/day and flow rate of 0.1 L/min. The reactor was very effective after over 10 hours retention time which resulted in high removal rates > 90% for COD, BOD₅, TSS, Turbidity, Colour, TP and total coliform, TDS = 62%, NH₃-N = 60% and TN = 46%. The effluent quality for most of the parameters meet the Malaysian effluent discharge standard B, while alternating aerobic and anaerobic systems were recommended in future development for enhanced nitrogen removal.

The Malaysian aged refuse has very significant characteristics such as adequate pore structure and surface characteristics, huge bacteria population, high porosity, high moisture and organic content, and has shown efficient adsorption and biodegradation processes in different livestock wastewater treatment. Moreover, it is a simple and affordable wastewater treatment technology, and therefore proposed for UPM dairy farm to experiment on a larger scale, for future development and application.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

PENJERAPAN DAN BIODEGRADASI BAHAN PENCEMAR DARI AIR SISA TERNAKAN MENGGUNAKAN BIOREAKTOR SISA BERUMUR

Oleh

ANIJIOFOR SANDRA CHINENYENWA

September 2018

Pengerusi : Nik Norsyahariati Nik Daud, PhD
Fakulti : Kejuruteraan

Kajian ini menyiasat ciri-ciri sisa pepejal yang ditanam, “sampah berumur”, untuk proses penjerapan dan biodegradasi, sebagai pilihan rawatan air sisa ternakan yang mampu. Terkini, ladang tenusu UPM melepaskan kira-kira 2000-2200 L/hari air sisa yang tidak dirawat ke dalam sungai berdekatan. Ini menimbulkan kebimbangan yang serius terhadap alam sekitar, terutamanya dalam pencemaran air. Parameter yang dikaji ialah pH, permintaan oksigen kimia (COD), permintaan oksigen biologi (BOD), jumlah pepejal terampai (TSS), jumlah pepejal terlarut (TDS), kekeruhan, jumlah nitrogen (TN), ammonia nitrogen (NH₃-N) jumlah fosforus (TP) dan jumlah koliform. Tiga sumber air kumbahan ternakan (ladang tenusu, rumah penyembelihan ayam dan kolam ikan) telah dikaji, sementara sisa berumur telah diambil dari Tapak Pelupusan Sanitari Air Hitam, Selangor, Malaysia.

Keputusan menunjukkan ciri-ciri sisa berumur seperti pH 7.14, kandungan lembapan 29.5%, kandungan organik 9.90%, jumlah koliform 7.1×10^6 CFU/100 mL, yang merupakan keadaan yang sesuai untuk biodegradasi. Keberaliran hidraulik 0.31 cm/s, keliangan (n) 51%, dan ketumpatan pukal (ρ) 1.23 g/cm³, adalah keadaan yang sesuai untuk aliran air bebas dan penyebaran udara. Kation tersedia yang boleh ditukar (Ca, Mg, K, Na), akan menggalakkan pertukaran ion manakala kepekatan logam rendah (Pb = 0.858, Cr = 14.0, Cu = 1.10 dan Zn = 12.16 mg/kg) akan mengurangkan gangguan. Mikroskop elektron pengimbasan (SEM), menunjukkan ruang liang sedia ada dan kawasan permukaan BET 3.376 m²/g, yang sesuai untuk penjerapan, manakala Penjelmaan Fourier Inframerah (FTIR), menunjukkan kumpulan fungsian karbonil, karboksil, hidroksil dengan kapasiti penjerapan yang kuat.

Kajian penjerapan kumpulan menunjukkan kesan pH, dos dan masa sentuhan terhadap kecekapan penyingkiran, dan keadaan yang optimum adalah; pH 6, dos 2-4 g/100 mL, saiz penjerap ≤ 2 mm, masa sentuhan 10-180 minit, kelajuan goncang 250 rpm dan

pada suhu ambien. Kecekapan penyingkiran maksimum adalah sekitar 94% (COD, BOD), 91% (TSS, TDS), 97% warna dan 88% $\text{NH}_3\text{-N}$. Pekali korelasi R^2 (0.9026 hingga 0.9999) bagi Langmuir, dan (0.9422 hingga 0.9999) bagi isotherm Freundlich, sesuai dengan data eksperimen.

Seterusnya, bioreaktor sisa berumur (diameter 15 cm dan ketinggian 80 cm), telah dibina dan digunakan untuk merawat air sisa ternakan pada kadar pemuatan 4 L m^3/hari dan kadar aliran 0.1 L/min. Reaktor sangat berkesan selepas penahanan masa selama 10 jam dan menghasilkan kadar penyingkiran yang tinggi, iaitu > 90% untuk COD, BOD_5 , TSS, kekeruhan, warna, TP dan jumlah koliform, TDS = 62%, $\text{NH}_3\text{-N}$ = 60% dan TN = 46%. Kualiti efluen bagi kebanyakan parameter memenuhi piawaian pelepasan efluen Malaysia B, sementara itu, sistem aerobik dan anaerobik adalah disyorkan untuk pembangunan di masa hadapan bagi mempertingkatkan penyingkiran nitrogen.

Sisa berumur Malaysia mempunyai ciri-ciri yang sangat signifikan seperti struktur liang dan ciri-ciri permukaan yang mencukupi, populasi bakteria yang banyak, keliangan yang tinggi serta kelembapan dan kandungan organik yang tinggi telah menunjukkan proses penjerapan dan biodegradasi yang efisien dalam rawatan air sisa ternakan yang berbeza. Dan lagi, ia merupakan teknologi rawatan air sisa yang mudah dan mampu milik. Oleh kerana itu, kaedah ini dicadangkan untuk ladang ternakan UPM dalam skala yang besar untuk pembangunan dan aplikasi di masa hadapan.

ACKNOWLEDGEMENTS

My profound gratitude goes to Almighty God, the most merciful and giver of life, from whom all good things come, who sustained me with good health, wisdom, knowledge and understanding throughout my study period in Malaysia.

The constructive efforts, advice and kindness of my academic supervisor/advisor Dr Nik Norsyahariati Bin Nik Daud, made me zealous and for which I will forever be thankful. My heartfelt gratitude also goes to my supervisory team; Dr Syazwani Idrus, Dr Amimul Ahsan and Assoc. Prof. Dr Hasfalina Che Man, for their guidance, corrections and contributions which made this study and thesis a success. It was indeed a beautiful research journey throughout my period of candidature, may God Almighty reward you greatly.

The scholarship and grant received from both Nigerian and Malaysian governments are appreciated. The Tertiary Education Trust Fund TETFUND, of the Federal Republic of Nigeria made it possible for me to explore outside the shores of Nigeria and for this, I appreciate the efforts of the Management of Federal Polytechnic, Birnin Kebbi, Kebbi State, Nigeria. Also, the grant received from the Universiti Putra Malaysia under the Putra Grant Scheme (Geran Penyelidikan Individu Berprestasi Tinggi) - No.: GP- I/2014/941800, stimulated this research towards a successful conclusion.

I am indeed grateful to Mr Aminuddin Amdan of Public Health Laboratory, and also, staff of Construction Materials and Geotechnical Laboratories of the Department of Civil Engineering, Material Characterization Laboratory of the Department of Chemical Engineering, as well as the Soil Physics Laboratory of the Faculty of Agriculture UPM, for their assistance during the course of generating data and laboratory analysis for this research. The entire Staff of the Department of Civil Engineering, Universiti Putra Malaysia are highly recognised for the respective roles they played in making my study and stay in Malaysia successful and memorable, especially the GCEC and GECEU 2017 teams.

I am most highly indebted to my family, my husband Dr Chinedu Ike, who believes that a woman must explore her potentials and with this he encouraged me to pursue better education abroad. I appreciate his undying love, support and encouragement throughout the period of study especially when things became tough. I am grateful to my young daughters; Chimamanda and Chibuife, whose ever smiling portraits kept me smiling through tough times and made me even stronger. I believe that someday when you are grown up, you will understand why I had to be away, thank you for being patient and hopeful, “the storm is over” and I made it. I most humbly appreciate God for the “Famous Five” Chimaobim Destiny, Chidubem Ed, Chimamanda Krista, Chimamanda Praise and Chibuife Kristine for the love and joy they bring to my life each day, I love you angels.

This journey would not have been successful without my younger sister Mrs Amaka Chime who took care of my children, together with her three kids while I was away and at the same time pursued her master's degree in Nigeria. Her book "Harassed" added strength to my struggle, I reminded myself that if she could write a book amidst all she had to cope with, then I had no excuse to fail or give up. Thank you so much dear, you are indeed more than a sister and may God reward you. I appreciate in a special way my mother, Mrs Adaora Anijiofor for all the love and sacrifices she made for my sisters and I, and her strong belief that the girl-child deserves education to whatever level she so desires. I appreciate my elder sister Dr Nneka Osondu and my niece Chidalu and also the entire family of Chief R.M. Ike (my in-laws), for all the love, support and encouragement they showed me and my family while I was away.

My family is my greatest source of strength and I thank you all for the bond of friendship we share. I love you all. Words cannot explain how indebted I am, may God reward you all abundantly for making this dream come true.

I certify that a Thesis Examination Committee has met on 14 September 2018 to conduct the final examination of Anijiofor Sandra Chinenyenwa on her thesis entitled "Adsorption and Biodegradation of Pollutants from Livestock Wastewater by Aged Refuse Bioreactor" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Doctor of Philosophy.

Members of the Thesis Examination Committee were as follows:

Raizal Saifulnaz bin Muhammad Rashid, PhD

Associate Professor Ir.
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Luqman Chuah Abdullah, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Zurina binti Zainal Abidin, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Ataur Rahman, PhD

Associate Professor
University of Western Sydney
Australia
(External Examiner)



RUSLI HAJI ABDULLAH, PhD
Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 22 November 2018

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee were as follows:

Nik Norsyahariati Nik Daud, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Syazwani Idrus, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Hasfalina Che Man, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

ROBIAH BINTI ROBIAH, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature : _____ Date: _____

Name and Matric No.: Anijiofor Sandra Chinenyenwa, GS43361

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research was conducted under our supervisor;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 Revision 2012-2013) are adhered to;

Signature : _____
Name of
Chairman of
Supervisory
Committee : Dr. Nik Norsyahariati Nik Daud

Signature : _____
Name of
Member of
Supervisory
Committee : Dr. Syazwani Idrus

Signature : _____
Name of
Member of
Supervisory
Committee : Associate Professor Dr. Hasfalina Che Man

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vii
DECLARATION	ix
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xvii
 CHAPTER	
1 GENERAL INTRODUCTION	1
1.1 Background of Study	1
1.2 Statement of Research Problems	3
1.3 Aim and Objectives	5
1.4 Scope of the Study	6
1.5 Thesis Structure	6
 2 LITERATURE REVIEW	 8
2.1 Solid Waste Generation and Composition	8
2.2 Solid Waste Disposal Methods	9
2.3 Aged Refuse (AR)	11
2.3.1 Aged Refuse Characteristics and Composition	11
2.3.2 Aged Refuse Bioreactors (ARB)	14
2.4 Adsorption Phenomenon	16
2.4.1 Adsorption Isotherms	18
2.4.2 Langmuir and Freundlich Models	18
2.4.2.1 Langmuir Isotherm	19
2.4.2.2 Freundlich Isotherm	20
2.5 Livestock Wastewater	21
2.5.1 Livestock Wastewater Generation	22
2.5.2 Livestock Wastewater Composition	22
2.5.3 Definitions of Basic Parameters in Livestock Wastewater	26
2.5.3.1 Physical Parameters	26
2.5.3.2 Chemical Parameters	27
2.5.3.3 Biological Parameters	29
2.6 Livestock Wastewater Treatment	29
2.6.1 Preliminary Treatment	30
2.6.2 Filtration	30
2.6.3 Biological Treatment Processes	31
2.7 Wastewater Treatment by Adsorption	34
2.7.1 Factors Affecting Adsorption Process	35

2.8	Wastewater Treatment using the ARB	36
2.8.1	Factors Affecting Pollutants Removal Efficiency in the ARB	40
2.9	Environmental Effects of Uncontrolled Livestock Wastewater Disposal	42
2.9.1	Environmental Degradation	42
2.9.2	Waterborne Diseases	42
2.10	Summary	44
3	METHODOLOGY	45
3.1	Sources of Sample Collection	47
3.1.1	Aged Refuse Material (Air Hitam Sanitary Landfill Site)	47
3.1.2	Livestock Wastewater Sample	48
3.1.2.1	UPM Livestock Farm (Ladang 16)	48
3.1.2.2	UPM Farm (Ladang 10), Fish farm	50
3.1.2.3	Slaughterhouse Wastewater	51
3.2	Sampling Procedures and Preparations	52
3.2.1	Aged Refuse Collection	52
3.2.2	Aged Refuse preparation	53
3.2.3	Wastewater Samples	54
3.2.4	Nearby Surface Water Sample	56
3.3	Experimental Procedures	56
3.3.1	Aged Refuse Characterization	57
3.3.1.1	Physical Properties	57
3.3.1.2	Chemical Properties	58
3.3.1.3	Biological Properties	60
3.3.1.4	Mechanical Properties	60
3.3.1.5	Structural Properties	61
3.3.2	Livestock Wastewater Analysis	61
3.3.2.1	Determination of Physical Parameters	61
3.3.2.2	Determination of Chemical parameters	62
3.3.2.3	Determination of Biological Parameters	64
3.4	Adsorption Experiments	65
3.4.1	Batch Experiments	65
3.4.2	Determination of Optimum Conditions for Adsorption	65
3.4.2.1	Effect of pH	66
3.4.2.2	Effect of Dosage	66
3.4.2.3	Effect of Contact Time	66
3.5	Aged Refuse Bioreactor (ARB) Design	66
3.5.1	Design Calculations	67
3.5.2	Experimental Procedure for AR Bioreactor	68
3.6	Summary	71

4	RESULTS AND DISCUSSIONS	72
4.1	Experimental Results and Data for Preliminary Investigations	72
4.1.1	Livestock Wastewater Composition	72
4.1.2	Water Quality Evaluation for Nearby Surface Water within the Dairy Farm	75
4.2	Experimental Results and Data Analysis on Aged Refuse Characterization	77
4.3	Experimental Results and Analysis on Adsorption Studies	86
4.3.1	Effect of Operating Parameters on Removal Efficiency of Pollutants	86
4.3.2	Effect of pH on Pollutant Removal Efficiency	86
4.3.3	Effect of dosage on pollutant removal efficiency	90
4.3.4	Effect of Contact Time on Pollutant Removal Efficiency	93
4.3.5	Langmuir and Freundlich Adsorption Isotherms	98
4.3.6	Fishpond Wastewater Adsorption Isotherms	98
4.3.7	Chicken slaughterhouse wastewater Adsorption Isotherms	106
4.3.8	Dairy Farm Wastewater Adsorption Isotherms	114
4.4	Experimental Results and Data Analysis of Aged Refuse Bioreactor Treatment	123
4.4.1	Results and Analysis of ARB for Dairy Farm Wastewater (Case Study)	129
4.4.2	Characterization of the AR after Reactor Treatment	137
4.5	Summary	138
5	CONCLUSIONS AND RECOMMENDATIONS	139
5.1	Conclusions	139
5.2	Recommendations	141
5.3	Novelty of this study	142
	REFERENCES	144
	APPENDICES	166
	BIODATA OF STUDENT	182
	LIST OF PUBLICATIONS	183

LIST OF TABLES

Table	Page	
2.1	Solid waste disposal target for Malaysia in 2020	10
2.2	Landfills in Malaysia	10
2.3	Characteristics of AR according to age	12
2.4	Physiochemical characteristics of screened aged refuse	13
2.5	Composition of aged refuse from a closed landfill site in Selangor	13
2.6	Differences between physical and chemical adsorption	17
2.7	Adsorption isotherm model equations	21
2.8	Livestock wastewater characteristics	24
2.9	Discharge standard for industrial effluent or mixed effluent of standards A and B	25
2.10	Summary of pore size and target application for types of filtration	31
2.11	Summary of treatment efficiency for wastewaters using the ARB	39
3.1	Parameters investigated for aged refuse and wastewater samples	56
4.1	Composition of livestock wastewater and acceptable discharge standards for Malaysia	73
4.2	Water Quality Analysis of the Dairy Farm River	76
4.3	Characterization of the Aged Refuse	79
4.4	Optimum operating conditions for maximum pollutant reduction efficiency from livestock wastewater	97
4.5	Adsorption Isotherm Model Equations	105
4.6	Summary of calculated values of Langmuir and Freundlich constants for FPW	105
4.7	Summary of calculated values of Langmuir and Freundlich constants for SHW	113
4.8	Summary of calculated values of Langmuir and Freundlich constants for DFW	121
4.9	Livestock wastewater treatment efficiency using AR bioreactor	124
4.10	Characteristics of the AR before and after bioreactor treatment	137

LIST OF FIGURES

Figure	Page	
2.1	Comparison between solid waste compositions in two regions	9
2.2	Flow diagram of developmental process of the AR	11
2.3	Composition of AR of 8 years of placement	12
2.4	Schematic representation of the pioneer aged refuse bio-filter	15
2.5	Global human and agricultural sources of faecal pollution	44
3.1	Flow chart of study	46
3.2	Air Hitam Sanitary Landfill Layout and phases, Selangor Malaysia	47
3.3(a)	Study Map for UPM Dairy Farm (Ladang 16)	48
3.3(b)	River source: Discharge point for dairy farm wastewater	49
3.4	A section of the dairy farm where the animals are washed	50
3.5	Study Map for Fish pond wastewater, (Ladang 10), UPM	51
3.6	Map showing the location for chicken slaughterhouse wastewater	52
3.7	Aged refuse sampling procedures (a) excavating the soil surface and (b) sample storage process	53
3.8	Aged Refuse Preparation; (a) drying at room temperature and (b) manual sorting process	54
3.9	Livestock wastewater sampling (a) Collection point at dairy farm (b) Dairy wastewater (c) Slaughterhouse wastewater and (d) Fishpond wastewater samples	55
3.10	Schematic representation of proposed Aged Refuse bioreactor	68
3.11	Schematic diagram of experimental set up of the ARB	70
4.1	pH concentrations for livestock wastewater	74
4.2	Physical composition of studied aged refuse	78
4.3	SEM analysis of the AR at different resolutions, (a) 300 (b) 1k (c) 3k and (d) 10k magnification	82
4.4	The EDX analysis of the AR	83
4.5	FTIR result of the AR showing the functional groups	84
4.6	Zeta potential of Aged Refuse	85
4.7	Effect of pH on pollutant removal efficiency (a) DFW (b) SHW and (c) FPW	88

4.8	Effect of adsorbent dosage on removal efficiency (a) DFW (b) SHW and (c) FPW	91
4.9	Effect of contact time on removal efficiency (a) DFW (b) SHW and (c) FPW	95
4.10	Adsorption isotherms for COD, BOD, TSS, TDS, colour and NH ₃ -N for Fishpond wastewater:	99
4.11	Adsorption isotherms for COD, BOD, TSS, TDS, colour and NH ₃ -N for Slaughterhouse wastewater	107
4.12	SEM images (a) Before and (b) After adsorption for SHW	114
4.13	Adsorption isotherms for COD, BOD, TSS, TDS, colour and NH ₃ -N for Dairy farm wastewater	115
4.14	SEM images (a) Before and (b) After adsorption for DFW	122
4.15	pH and Temperature variations during reactor treatment	130
4.16	Concentration variation trend and removal rates for Turbidity	131
4.17	Concentration variation trend and removal rates for TSS	131
4.18	Concentration variation trend and removal rates for TDS	131
4.19	Concentration variation trend and removal rates for Colour	132
4.20	Concentration variation trend and removal rates for COD	133
4.21	Concentration variation trend and removal rates for BOD	133
4.22	Concentration variation trend and removal rates for NH ₃ -N	134
4.23	Concentration variation trend and removal rates for TN	134
4.24	Concentration variation trend and removal rate and for TP	135
4.25	Concentration variation trend and removal rate for total coliform reduction	136

LIST OF ABBREVIATIONS

AAS	Atomic Absorption Spectrometry
AR	Aged Refuse
ARB	Aged Refuse Biofilter/Bioreactor
AHSL	Air Hitam Sanitary Landfill
FPW	Fishpond wastewater
SHW	Slaughterhouse wastewater
DFW	Dairy farm wastewater
TSS	Total suspended solids
LOI	Loss On Ignition
OM	Organic Matter
ADMI	American Dye Manufacturers Institute
TDS	Total dissolved solids
COD	Chemical oxygen demand
BOD	Biochemical oxygen demand
DO	Dissolved oxygen
TN	Total Nitrogen
TP	Total Phosphorous
NH ₃ -N	Ammonia Nitrogen
BET	Brunauer-Emmett-Teller
CEC	Cation Exchange Capacity
FTIR	Fourier transform infrared
ATR	Attenuated total reflectance
MSW	Municipal Solid Waste
MSWM	Municipal Solid Waste Management
NSWMD	National Solid Waste Management Department
MHLG	Ministry of Housing and Local Government
SEM	Scanning Electron Microscopy
EDX	Electron Dispersive X-ray
MEQR	Malaysian Environmental Quality Regulation
NWQS	National Water Quality Standards
APHA	American Public Health Association
ASTM	American Society for testing of Materials
ISO	International Standards Organization
ICP-OES	Inductively Coupled Plasma-Optical Emission Spectrometry

ICP MS	Inductively Coupled Plasma Mass Spectrometry
GHG	Green House Gas
OECD	Organization for Economic Development
FAO	Food and Agricultural Organization
HLR	Hydraulic Loading Rate
NLR	Nitrogen Loading Rate
WWTP	Wastewater treatment plant
UNDP	United Nations Development Programme
GPS	Global Positioning System
CFU	Coliform Forming Unit



© COPYRIGHT UPM

CHAPTER 1

GENERAL INTRODUCTION

1.1 Background of Study

Due to the rising population rates in developing countries, numerous challenges are being faced to contain the threat in increased solid waste generation. As a fast-developing country, average solid waste generation rates for Malaysia ranges between 0.5-1.9 kg/cap/day, depending on the province, (United Nations Development Programme, 2008; Manaf et al., 2009). Meanwhile, landfilling is the cheapest form of solid waste disposal in Malaysia, and accounts for over 80% of municipal solid wastes disposal. However, the National Solid Waste Management Department, stated that 131 out of 296 existing landfills in Malaysia have been closed due to congestions and construction of new landfills is practically impossible due to large land required and high cost (MHLG, 2014). These problems have necessitated the on-going search for reuse of landfilled materials, which has benefitted the exploration of “Aged Refuse” (AR). Aged refuse are solid wastes deposited in the landfill, which decomposes and become stabilized over a period of placement, mainly after 8-10 years of placement, (Zhao et al., 2002; Wang and Zhao, 2004).

On the other hand, the 2011 annual report of the Organisation for Economic Cooperation and Development (OECD), in partnership with the Food and Agricultural Organisation (FAO) of the United Nations, stated that livestock prices will increase by 30% between 2011 and 2020 (OECD-FAO, 2011). As a result, Malaysia has experienced significant growth in the livestock industry due to the increasing demand for meat and other livestock products. However, such activities produce large volumes of highly polluted wastewater mostly organic, inorganic and nutrients. According to Mukhopadhyay et al., (2003) and Sarkar et al., (2006), livestock wastewater consists of faeces, urine and water used in washing animals and livestock farming. Thus, depending on the type of feed, the degree of processing and many other factors, livestock wastewater has high concentrations of Chemical Oxygen Demand (COD), Biochemical Oxygen Demand (BOD), Oil and Grease, Total Phosphorous (TP), Total Nitrogen (TN), Ammonia Nitrogen (NH₃-N), Total Suspended Solids(TSS), Total Dissolved Solids (TDS), Colour and Microbial Population (MP).

Consequently, disposal of such highly polluted wastewater into the environment has become a fundamental environmental issue of enormous concern. Most chicken slaughterhouses are located within residential areas, and wastewater from such activities are disposed into sewerages without pre-treatment. Also, most farmhouses are in rural areas without adequate facilities to control wastewater produced from such activities. Therefore, water pollution from animal sources has continued to generate global concern, calling for stringent measures for livestock wastewater disposal, as most rural populations depend on groundwater sources for domestic use.

Furthermore, livestock wastewater treatment has been a growing challenge over the years because of the varying influent concentrations coupled with high discharge conditions for effluent. There are variety of options for wastewater treatment such as: chemical precipitation, coagulation/flocculation, aeration, filtration, ion exchange, electrochemical treatment, adsorption and biodegradation (Al-Shamrani et al., 2002; Rivas et al., 2003; Wang and Shao, 2004; Kurniawan et al., 2006; Babarinde et al., 2006; Gupta and Suhas, 2009; Bashir et al., 2013). Nonetheless, due to high operational and maintenance costs, excessive use of chemicals, reduced efficiency with time, large sludge production and complexity in the use of some of the methods, adsorption and biodegradation processes have become more efficient and preferred wastewater treatment methods.

Adsorption is a physiochemical process which occur at an interface between two phases (liquid-liquid, gas-liquid or liquid-solid), (Barakat, 2011). The main components of adsorption are surface characteristics and pore structure and adsorption equilibrium is a fundamental factor in designing adsorption operations (Ushakumary 2013). Moreover, the advantages of adsorption are numerous and include; low capital, simple design and operation, limited sludge, high effluent quality, favourable at wide range of pH and effective in removal of metals even at low concentrations (Devi et al., 2008; Ali et al., 2012, Gupta and Nayak, 2012; Ideriah et al., 2012; Foo et al., 2013). However, the efficiency in adsorption also lies on the development of cheap, affordable, abundant and environmentally friendly adsorbents.

Biodegradation is the process by which organic substances are broken down into smaller compounds by living microbial organisms (Marinescu et al., 2009). Numerous microorganisms, comprising fungi, bacteria and yeasts are involved in biodegradation process, which can be aerobically (with oxygen), or anaerobically (without oxygen). Some microorganisms have natural ability to degrade several organic pollutants due to their formation and can also adapt to unfavourable environments. However, their efficiency depends on many factors such as; chemical nature and the concentration of pollutants, their availability to microorganisms, and the physicochemical characteristics of the environment (El Fantroussi and Agathos, 2005).

Filtration on the other hand, is one of the oldest forms of water purification, which involves a solid-liquid separation process in which the liquid passes through a porous medium to remove suspended solids in the water. This removal of particles within a filter bed involves; transport of the suspended particles to the filter and attachment of particles to the surface (Yao et al., 1971). There are several filtration methods, however, the selection of the appropriate method is based on design.

The Aged Refuse Bioreactor (ARB) has the configuration of a trickling filter which supports bacterial growth, and allows the wastewater to seep down by the force of gravity. The ARBs developed earlier were rectangular or square shaped however, modern ARB's are cylindrical for easy water distribution which has been a major drawback of the former, and has a filter attached at the bottom so that the suspended

solids not trapped at the top of the column as the wastewater trickles down are further removed at the bottom by filtration.

Indeed, ARB advantages include; low investment and maintenance costs, simple construction and operational processes, low sludge production, high efficiency in pollutants removal, availability and environmentally safe. The effectiveness of the AR from regions within China have been reported (Zhao and Shao, 2004, Zhao et al., 2007; Sun et al., 2011; Xie et al., 2013; Wang et al., 2012), for leachate treatment, however, its application in livestock wastewater treatment is yet to be maximized.

1.2 Statement of Research Problems

The alarming rate of disposal of untreated livestock wastewater into community sewerages and flowing water, has become an enormous environmental issue. Slaughterhouses and dairy farms generate large volumes of highly concentrated wastewater which are discharged into water bodies or sewerage systems without pre-treatment, and results in blockages of wastewater pipes and reduced lifespan of such materials. Such practices are harmful to aquatic life, poses environmental problems and present challenges for the relevant authorities in sustaining the quality of surface water used for domestic activities as well as for recreational activities (WHO 2012).

Malaysia, does not practice a centralised livestock farming system and is faced with many challenges regarding livestock wastewater treatment. The Minister for Agriculture and Agro-based Industry, Datuk Seri Ismail Sabri Yaakob, noted that 80% of the 2,000 poultry slaughterhouses in Malaysia are not licensed with the Veterinary Services Department (VSD). The 1998/1999 outbreak of Nipah disease originating from pig farms, placed numerous restrictions on pig farming in certain areas, regulated by Veterinary Services (Mohd-Nor et al., 2000). Most disease outbreaks and epidemics experienced in developing countries result from the effects of surface and groundwater pollution, especially from livestock wastewater sources. The principal inorganic compounds found in livestock wastewater are nitrates, nitrogen and ammonium nitrogen which are incredibly harmful to human health. Therefore, strategies for economically viable and affordable treatment processes for such wastewaters must be developed and put into practice.

Conventional livestock treatment methods are becoming obsolete due to variations in composition and volume of different livestock wastewater, coupled with high operational and maintenance costs, complexity in application which has limited their usage. Interestingly, the use of the ARB could be a better alternative as notably been focussed on landfill leachate treatment as shown in the extensive data available in literature (Zhao et al., 2002; Wang and Zhao 2004; Xie et al., 2012; Sun et al., 2011) but, its application in livestock wastewater treatment is insufficient and limited. Moreover, due to the varying characteristics of solid waste generated from region to

region, there is a need to investigate the Malaysian AR for adsorption and biodegradation characteristics for application in livestock wastewater treatment.

Previous lab scale investigations on the applicability of the aged refuse bioreactor for leachate treatment in Malaysia faced numerous challenges. Abu Mansor (2013) used a square shaped aged refuse bioreactor of dimensions (40cm x 40 cm x 60 cm) for landfill leachate treatment and recorded low pollutant removal rates of only 33-49% COD, 25-48% BOD, 31-48% TSS and 39-67% TDS. Also, Nik Daud and Misban (2015), recorded only 45% NH₃-N removal from landfill leachate and the reactor experienced clogging and fouling problems which deteriorated effluent quality as a result of the size of the AR used. The following drawbacks were summarized from previous studies involving the use of ARB in Malaysia; (i) parameters investigated were insufficient to adequately assess its efficiency (ii) no attached filtration device at the bottom (iii) poor water distribution due to square shape in (Abu Mansor 2013) (iv) insufficient retention times due to low AR height (v) clogging and fouling problems (vi) inadequate characterization of the AR to streamline its applicability.

Therefore, this study focuses on addressing some of the drawbacks and development of a modified AR bioreactor for enhanced pollutants removal. Therefore, a novel material characterization of Malaysian AR is intended in this study, for detailed characteristics such as pH, porosity, density, hydraulic conductivity, organic content, moisture content, bacteria population (total coliform), functional groups FTIR, cation exchange capacity CEC, exchangeable cations, carbon content, heavy metals presence, surface morphology SEM and EDX and surface characteristics, which are ideal requirements for adsorption and biodegradation. Furthermore, a modified lab-scale AR reactor would be developed and constructed taking into consideration suggestions for improvement and further works by Abu Mansor, (2013). The ARB will be investigated for effectiveness in livestock wastewater treatment as a novel study, and is intended to cover a wider range of pollutants such as organic pollutants (COD, BOD), inorganic pollutants (TSS, TDS, Turbidity, Color), nutrients (NH₃-N, TN, TP) and microbes. Also, this wide range of pollutants covered in the treatment design will comprise three different livestock farms (Fish farm, Dairy farm and Chicken Slaughterhouse), for effective exploration of variations in different livestock wastewater.

Consequently, this study differs from previous studies particularly explored in China using different AR biofilters, and mostly centred on landfill leachate treatment. No investigations on batch adsorption study to determine adsorption effects of the AR, or AR bioreactor experiments on livestock wastewater, notably the fishpond and chicken slaughterhouse wastewater has been previously studied anywhere to my knowledge. Moreover, it is important to consider variations in different livestock wastewater in the design of such treatment plants for enhanced efficiency. Secondly, the material characterization aspect of this study, with regards to the Malaysian landfilled AR is a novel study which covers extensive research properties of the material. No detailed research work on AR characterization has been categorically carried out in Malaysia.

This characterization is very important in promoting potentials for future development of the AR bioreactor and also to initiate possibilities for bioreactor landfills.

In addition, the specific research problem in this study is the discharge of large volumes of untreated livestock wastewater from the UPM livestock farm (Ladang 16), of the Faculty of Agriculture, Universiti Putra Malaysia into a flowing river source close to the farm. The study will also carry out investigations on the level of contamination of the river. Consequently, the development of this technology will provide an alternative and affordable wastewater treatment option for the farm and ensure safe wastewater discharge into the environment.

1.3 Aim and Objectives

This research is aimed at providing economic and affordable treatment alternative for livestock wastewater through the development of an aged refuse bioreactor. The study involved two major technological practices in wastewater treatment; adsorption and biodegradation. The first step involved batch adsorption study to determine the correlation between adsorption isotherms using aged refuse as adsorbents, while the second step involved the use of a laboratory scale aged refuse bioreactor for livestock wastewater treatment.

The specific objectives are;

- 1) To determine the varying influent composition of different livestock wastewater from three selected sources (dairy farm, fish farm and chicken slaughterhouse), over a period of time in terms of pH, TSS, TDS, colour, turbidity, BOD, COD, TN, NH₃-N, TP and total coliform.
- 2) To evaluate AR characteristics such as physical (moisture content, bulk density and porosity), chemical (pH, organic content, CNS, CEC, heavy metals, BET, FTIR, zeta potential), biological (total coliform), mechanical (hydraulic conductivity) and structural (SEM and EDX).
- 3) To carry out batch sorption studies, determine the effects of pH, AR dosage and contact time on pollutants removal efficiency and model experimental data into Freundlich and Langmuir isotherm models.
- 4) To develop a lab-scale aged refuse bioreactor for livestock wastewater treatment and assess the quality of effluent in terms of pH, TSS, TDS, colour, turbidity, BOD, COD, TN, NH₃-N, TP and total coliform.

1.4 Scope of the Study

This work focused on adsorption and biodegradation techniques for livestock wastewater treatment using AR as media. This involved a sorption study using the AR as media for the adsorption of pollutants, and also, the use of a laboratory scale modified AR bioreactor for column treatment.

The livestock wastewater was sampled from three livestock sources; the UPM livestock farm (Ladang 16), the UPM Fish farm (Ladang 10), both located within the UPM, and a chicken slaughter house located at Bukit Serdang, a suburb close to the university. The AR was obtained from the Air Hitam Sanitary Landfill in Selangor which has been closed for 10 years.

The investigations carried out for the wastewater were; Chemical Oxygen Demand (COD), Biochemical Oxygen Demand (BOD), Hydrogen ion concentration (pH), Temperature, Colour, Total Suspended Solids (TSS), Total Dissolved Solids (TDS), Turbidity, Total Nitrogen (TN), Total Phosphorus (TP), Ammonia Nitrogen (NH₃-N), and microbial population, while oil and grease was analysed for chicken slaughterhouse wastewater only.

For the AR, investigations carried out were; moisture content, pH, bulk density (ρ), porosity (n), organic content, Cation Exchange Capacity (CEC) and exchangeable cations, Brunauer-Emmett-Teller (BET) specific surface area (SSA), hydraulic conductivity, Carbon-Nitrogen-Sulphur (CNS), elemental analysis (Zn, Cu, Cd, Pb, and Cr), microbial population, as well as surface morphology (SEM/EDX), functional groups (FTIR) and zeta potential.

For the adsorption studies, the influence of various parameters such as; pH, adsorbent dosage and contact time were investigated at different time intervals. The river source point of discharge for the dairy farm was also investigated for pollutant load concentration. Graphical analysis using Excel workbook, linear regression analysis, adsorption isotherms and models (Freundlich and Langmuir) only, were used to analyse, compare and validate experimental data.

1.5 Thesis Structure

This thesis is structured in five chapters.

The First chapter covers general introduction which includes major issues in areas of solid waste management, landfill management, wastewater treatment and management. It highlights the need for the study through an in-depth problem

statement which justifies the study. Furthermore, the aim and the specific objectives were clearly defined while the scope and limitations were also precisely stated.

Chapter Two covers a comprehensive analysis of solid waste generation, collection, disposal and management issues as a bedrock for the future of the AR technology. Secondly, landfill issues and concerns as it affects landfill congestions and closure were highlighted in the light of available literature. Also, livestock wastewater generation and subsequent disposal in relation to available technologies for treatment was extensively discussed. Although available literature for the treatment of livestock wastewater using the AR is very limited, appraisal of a lot of successful studies on its usage for leachate treatment provided the literature for discussions on the subject.

Chapter Three covers the methods, materials, sampling procedure which formed the investigational techniques. The sampling procedure for both AR and livestock wastewater and also all experimental procedure for AR characterization, livestock wastewater composition, adsorption and bio-filtration processes are all discussed in this chapter.

Chapter Four presents a detailed analysis of the results of the experiments and investigations carried out as detailed in Chapter Three. This includes the results of livestock wastewater composition and AR characterization, results on the effect of operating parameters on removal efficiencies, graphical representations of the isotherms for Langmuir and Freundlich models and a presentation of the results from the bio-filtration experiment. It also covers results from sampling of the river source for the dairy farm wastewater discharge.

Chapter Five summarizes all the results obtained with very detailed conclusions and gives apt recommendations for actual practice and specific areas for further research.

REFERENCES

- Abu Mansor, S.N.B. (2013). The use of aged refuse as a biofilter for treating landfill leachate. Master's Thesis, Universiti Putra Malaysia.
- Abushammala, M.F.M., Basri, N.E.A., Basri, H., El-Shafie, A.H., and Kadhum, A.A.H. (2011). Regional landfills methane emission inventory in Malaysia. *Waste Manage Res.*, 29, 863–873.
- Achour, M., Khelifi, O., Bouazizi, I., and Hamdi, M. (2000). Design of an integrated bioprocess for the treatment of tuna processing liquid effluents. *Process Biochem*, 35, 1013–1017.
- Adamson, A.W., and Gast, A.O. (1997). Physical chemistry of surfaces, 6th edition, John Wiley and Sons, New York.
- Adelaja, O.A., Amoo, I.A, and Aderibigbe, A.D. (2011). Biosorption of Lead (II) ions from aqueous solution using *Moringa oleifera* pods. *Archives Appl Sci Res.*, 3(6), 50–60
- Agamuthu, P. (2001). *Solid waste: principles and management with Malaysian case studies*. Kuala Lumpur, University of Malaya Press.
- Agamuthu, P., Khidzir, K.M., and Fauziah, S.H. (2009). Drivers of sustainable waste management in Asia. *Waste Management and Research*, 27, 625-633.
- Agouridis, C. T., Workman, S.R., Warner, R.C., and Jennings, G.D. (2005). Livestock grazing management impact on stream water quality: A review. *J. Am. Water Res. Assoc.*, 41, 591–606.
- Ajay Kumar, M., Kadirvelu, K., Mishra, G.K., Chitra, R., and Nagar, P.N. (2008). Adsorptive removal of heavy metals from aqueous solution by treated sawdust. *Journal of Hazardous Materials*, 50, 604-611.
- Allen, S.J., Mckay, G., and Porter, J.F., (2004). Adsorption isotherm models for basic dye consumption by peat in single and binary component systems. *Journal of Colloid and Interface Science*, 280(2), 322-333.
- Al-Ansari, M. S. (2012). Improving solid waste management in Gulf co-operation council states: Developing integrated plans to achieve reduction in greenhouse gases. *Modern Applied Science*, 6(2), 60-68.
- Albright, W.H., Benson, C.H., Gee, G.W., Abichou, T., McDonald, E.V., Tyler, S.W., Bilgili, M.S., Demir, A., and Ozkaya, B. (2006). Quality and quantity of leachate in aerobic pilot-scale landfills. *Environ. Manage.*, 38, 189–196.

- Ali, I., Asim, M., and Khan, T.A. (2012). Low cost adsorbents for the removal of organic pollutants from wastewater. *J. Environ. Manage.*, 113, 170-183.
- Al-Mutairi, N.Z., Hanoda, M., and Al-Ghusain, I. (2004). Coagulant selection and sludge conditioning in a slaughterhouse wastewater treatment plant. *Bioresources Technology*, 95 (2), 115-119.
- Alomá, I., Martín-Lara, M., Rodríguez. I., Blázquez, G., and Calero, M. (2012). Removal of nickel (II) ions from aqueous solutions by biosorption on sugarcane bagasse. *J Taiwan Inst Chem Eng.* 43(2), 275–281.
- Al-Shamrani, A. A., James, A., and Xiao, H. (2002). Destabilisation of oil–water emulsions and separation by dissolved air flotation. *Water Research*, 36(6), 1503-1512.
- Altin, O., Ozbelge, H.O., and Dogu, T. (1998). Use of general purpose adsorption isotherms for heavy metal-clay mineral interactions. *J. colloid interface sci.*, 198, 130-140.
- Ameen, S., and Ahmad, J. (2008). Characterization and assessment of treatability of wastewater generated in Amman slaughterhouse. *Dirasat, Engineering Sciences*, 35(2), 71 – 83.
- American Public Health Association, APHA (2005). *Standard Methods for the Examination of Water and Wastewater*, APHA, Washington DC, USA, 46.
- American Public Health Association/American Water Works Association/Water Environment Federation APHA, AWWA-WEF, (1998). *Standard Methods for the Examination of Water and Wastewater*, twentieth ed., Washington, DC, USA.
- American Public Health Association, APHA, (1999). *Standard Method for the Examination of Water and Wastewater*, Washington DC, USA.
- American Public Health Association, APHA, (1992). Method 2120B Colour: Visual comparison method. *Standard Method for the Examination of Water and Wastewater*, 18th Edition Washington DC, USA.
- Amuda, O.S., and Alade, A. (2006). Coagulation/flocculation process in the treatment of abattoir wastewater. *Desalination*, 196, 22-31.
- Andal, N.M., and Charulatha, S. (2014). Efficacy of agricultural waste in the removal of hexavalent chromium – A review. *Res. Rev.: Journal of Chemistry*, 2 (4), 1-5.
- Asian Development Bank. (2004). *The Garbage Book: Solid Waste Management in Metro Manila*. ADB, Manila, Philippines.

- ASTM D 1556-07 *Standard test method for density and unit weight of soil in place by sand cone method*. American Society for testing and Materials, 1916 Race st. Philadelphia, PA 19103.
- ASTM D 2974-87. Standard test method for Moisture Content, Ash and Organic Matter of peat and other organic soils. American Society for testing and Materials, 1916 Race St. Philadelphia, PA 19103.
- Asubiojo, O., and Ajelabi, O. (2009). Removal of heavy metals from industrial wastewaters using natural adsorbents. *Toxicol Environ Chem.*, 91(5), 883–890.
- Azouaou, N., Sadaoui, Z., Djaafri, A., and Mokaddem, H. (2010). Adsorption of cadmium from aqueous solution onto untreated coffee grounds: Equilibrium, kinetics and thermodynamics. *Journal of Hazardous Materials*, 184, 126-134.
- Babarinde, N.A., Babalola, J.O., and Sanni, R.A. (2006). Biosorption of lead ions from aqueous solution by maize leaf. *Int J Phys Sci.*, 1(1), 23–26.
- Babel, S., and Kurniawan, T.A. (2004). Cr (VI) removal from synthetic wastewater using coconut shell charcoal and commercial activated carbon modified with oxidizing agents and/or chitosan. *Chemosphere*, 54, 951-967.
- Babu, B.V., and Gupta, S. (2008). Adsorption of Cr (VI) using activated neem leaves: Kinetic studies. *Adsorption*, 14, 85-92.
- Bacchin, P., Aimar, P., and Field, R.W. (2006). Critical and sustainable fluxes: Theory, experiments and applications. *Journal of Membrane Science*, 281, 42–69.
- Baddour, E.M., Farhoud, N., Sharholy, M., and Abdel-Magid, I.M. (2016). Biological treatment of poultry slaughterhouses wastewater by using aerobic moving bed biofilm reactor. *International Research Journal of Public and Environmental Health*, 3(5), 96-106.
- Baker, R.W., Cussler, E.L., Eykamp, W., Koros, W.J., Riley, R.L., and Strathmann, H. (1991). Membrane separation systems - Recent developments and future directions. Noyes Data Corporation, Park Ridge, New Jersey.
- Barakat, .M.A. (2011). New trends in removing heavy metals from industrial wastewater. *Arabian Journal Chemistry*, 4, 361-377.
- Baral, S.S., Dasa, S.N., and Rath, P. (2006). Hexavalent chromium removal from aqueous solution by adsorption on treated sawdust. *Biochem. Eng. J.*, 31 (3), 216-222
- Barlaz, M. A., Schaefer, D. M., and Ham, R. K. (1989). Bacterial population development and chemical characteristics of refuse decomposition in a simulated sanitary landfill. *Appl. Environ. Microbiol.*, 55 (1), 55–65.

- Bashir, M.J.K., Aziz, H.A., Aziz, S.Q., and Abu Amr, S.S. (2013). An overview of electro-oxidation processes performance in stabilized landfill leachate treatment. *Desalin. Water Treat.*, 51, 2170-2184.
- Bayramoglu, M., Eyvas, M., and Kobta, M. (2006). Treatment of the textile wastewater by electrocoagulation economical evaluation. *The Chemical Engineering Journal*, 128(2-3), 155-161.
- Bernet, N., and Béline, F. (2009). Challenges and innovations on biological treatment of livestock effluents. *Bioresource Technology*, 100, 5431–5436.
- Blake, G.R., and Hartge, K.H. (1986). Bulk density. In Klute, A. (ed). *Methods of soil Analysis, Part 1. Physical & Mineralogical Methods*, 2nd Edn ASA-SSSA, Wisconsin, 363-375.
- Bogner, J., Matthews, E., (2003). Global methane emissions from landfills: New methodology and annual estimates 1980–1996. *Glob. Biogeochem. Cycle*, 17 (2), 1065–1083.
- Bolster, C.H., and Hornberger, G.M. (2007). On the use of Linearized Langmuir equation. *Soil Sci. Soc. Am. J.*, 71 (6), 1796-1806.
- Borongon, G., and Okumura, S. AIT/UNEP PRC.AP, (2010). *Municipal Waste Management Report: Status quo & Issues in Southeast and East Asian Countries*. (Eds.) ISBN: 978- 974-8257-73-0.
- Brahmaiah, T., Spurthi, L., Chandrika, K., Ramanaiah, S. and Sai Prasad, K.S. (2015). Kinetics of heavy metals removal from the wastewater using low cost adsorbent. *World Journal of Pharmacy and Pharmaceutical Sciences*, 4(11), 1600-1610.
- British Standards (BS 1377), (1990). *Methods for Tests for soils for Civil Engineering purpose*. British Standard Institution, London.
- Bulut, E., Ozacar, M., Sengil, I.A. (2008). Adsorption of malachite green onto bentonite: Equilibrium and kinetic studies and process design. *Micropor. Mesopor. Mater.*, 115, 234-246.
- Burton, C.H., and Turner, C. (2003). *Anaerobic treatment options for animal manures*. In: Beck, J.A.F., Martinez, J., Martens, W., Pahl, O., Piccinini, S., Svoboda, I. (Eds.), *Manure management – Treatment strategies for sustainable agriculture*. Silsoe Research Institute, Wrest Park, Silsoe, Bedford, UK, pp. 273–320.
- Bustillo-Lecompte, C., Mehrab, M., Mehrvar, M., and Quinones-Bolanos E. (2016). Slaughterhouse wastewater characterization and treatment. An economic and public health necessity of meat processing industries in Ontario, Canada. *Journal of Geoscience and Environment Protection*, 4, 175-186.

- Caixeta, C.E.T., Cammarota, M.C., and Xavier, A.M.F. (2002). Slaughterhouse wastewater treatment: Evaluation of a new three-phase separation system in UASB reactor. *Journal of Bioresource Technology*, 81, 61-69.
- Chaffi, M., Gourich, B., Essadki, A.H., Vial, C., and Fabregat, A. (2011). Comparison of electrocoagulation using iron and aluminium electrodes with chemical coagulation for the removal of a highly soluble acid dye. *Desalination*, 281, 285–292.
- Chai, X.L., and Zhao, Y.C. (2006) Adsorption of phenolic compound by aged-refuse. *Journal of Hazardous Materials*, B (137), 410–417.
- Chan, Y.J., Chong, M.F., Law, C.L., and Hassel, D.G. (2009). A review on anaerobic–aerobic treatment of industrial and municipal wastewater. *Chemical Engineering Journal*, 155(1-2), 1-18.
- Chen, Y.X., Wu, S.W., Wu, W.X., Sun, H., and Ding, Y. (2009). Denitrification capacity of bioreactors filled with refuse at different landfill ages. *Journal of Hazardous Materials*, 172,159-165.
- Chowdhury, P., Viraraghavan, T., and Srinivasan, A. (2010). Biological treatment processes for fish processing wastewater – A review. *Bioresource Technology*, 101, 439-449.
- Chynoweth, D.P., Wilkie, A.C., and Owens, J.M. (1999). Anaerobic treatment of piggery slurry – Review. *Asian-Aus. J. Anim. Sci.*, 12, 607–628
- Cleaveland, S., Laurenson, M. K., and Taylor, L. H. (2001). Diseases of humans and their Domestic mammals: pathogen characteristics, host range and the risk of emergence. *Philos. Trans. R. Soc. Lon. B. Biol. Sci.*, 356, 991–999.
- Couillard, D., Gariépy, S., and Tran, F.T. (1989). Slaughterhouse effluent treatment by thermophilic aerobic process. *Water Research*, 23(5), 573-579.
- Dakiky, M., Khamis, M., Manassra, A., and Mereb, M. (2002). Selective adsorption of chromium (vi) in industrial wastewater using low-cost abundantly available adsorbents. *Advanced Environmental Research*, 6, 533-540.
- De Nardi, I.R., Fuzi, T.P., and Del Nery, V. (2008). Performance evaluation and operating strategies of dissolved-air flotation system treating poultry slaughterhouse wastewater. *Resources conservation & Recycling*, 52(3), 533-544.
- Department of Environment Malaysia, National water quality standard for Malaysia NWQS-(1985). Development of Water Quality Criteria and Standards for Malaysia.

- Department of Statistics, Malaysia: Official portal, current population estimates Malaysia 2014- 2016. Retrieved from: <http://www.dosm.gov.my/>
- Department of Statistics, (2010). *Preliminary Count Report, Population and Housing Census, Malaysia, 2010*. Retrieved from: <http://www.statistics.gov.my>.
- Devare, M., and Bahadir, M. (1994). Biological monitoring of landfill leachate using plants and luminescent bacteria. *Chemosphere*, 28, 261–271
- Devi, R., Singh, V., and Kumar, A. (2008). COD and BOD reduction from coffee processing wastewater using Avacado peel carbon. *Bioresource Technology*, 99, 1853-1860.
- Devi, R. and Dahiya, R.P. (2008). COD and BOD removal from domestic wastewater generated in decentralized sectors. *Bioresource Technology*, 99, 344-349.
- Dodds, W.K., and Welch, E.B. (2000). Establishing nutrient criteria in streams. *J N Am Benthol Soc.*, 19, 186–196.
- Donglin, Z, Cheng, S., Houhu, Z., Zhilin, W., Bo, J. Y.Z. (2012). Roles of vegetation, flow type and filled depth on livestock wastewater treatment through multi-level mineralized refuse-based constructed wetlands. *Ecological Engineering*, 39, 7-15.
- EA, (2009). Perak – *Solid Waste Management Plan (P-SWMP)*, EA-SWMC, EU-Asia. Economic and Social Aspects.
- Economic Planning Unit of the Prime Minister’s Department, Malaysia, EPU (2007). Ninth Malaysia Plan 2006 – 2010. Retrieved from: <http://www.epu.jpm.my/rm9/html/english.htm>
- El Fantroussi S and Agathos SN. (2005). Is bioaugmentation a feasible strategy for pollutant removal and site remediation? *Current Opinion in Microbiology*, 8, 268-275.
- El-Naas, M.H., Al-Zuhair, S., Alhajja, M.A. (2010). Reduction of COD in refinery wastewater through adsorption on date-pit activated carbon. *Journal of Hazardous Materials*, 172, 1538-1543.
- El-Said, A.G., Badaway, N.A., and Garamon, B. (2010). Adsorption of cadmium (II) and mercury (II) onto natural adsorbent rice husk ash (RHA) from aqueous solutions: Study in single and binary system. *Journal of American Science*, 12, 400-409.
- Erses, A.S., Onay, T.T., and Yenigun, O. (2008). Comparison of aerobic and anaerobic degradation of municipal solid waste in bioreactor landfills. *Bioresour. Technol.*, 99, 5418-5426.

- Environmental Protection Agency, EPA, (1997). Wastewater treatment manual: Primary, Secondary & Tertiary treatment. EPA, Ardavan Wexford, Ireland. ISBN: 1 899965 467.
- Environmental Protection Agency, EPA, (2000). *Feedlots point source category study*. Profile of the agricultural livestock production industry, EPA, 310-R-00-002. Retrieved from: <http://nepis.epa.gov>.
- Environmental Protection Agency, EPA, (2009). *Diverting Waste from Landfill: Effectiveness of waste management policies in the European Union*, Copenhagen.
- European Union. Directive 2000/60/EC of the European Parliament and of the Council of 23 October 2000 establishing a framework for community action in the field of water policy. *Off. J. Eur. Commun. L.*, 327, 1–73.
- FAO, (2004). *Livestock waste management in East Asia*. Project preparation report, Food and Agricultural Organization of the United Nations, Rome.
- FAO, (2006). *Livestock's long shadow- Environmental issues and options*. Eds. Steinfeld, H., Gerber, P., Wassenaar, T., Castel, V., Rosales, M., and de Haan, C. Food and Agriculture Organisation, Rome, p.390- 414.
- Food and Agricultural Organisation of the United Nations. FAO (2009). *Statistics on agricultural production and trade, Rome*. Retrieved from: <http://www.faostat.fao.org>
- Fauziah, S.H., and Agamuthu, P. (2012). Trends in sustainable landfilling in Malaysia, a developing country. *Waste Management and Research*, 30(7), 656-663.
- Federal Interagency Stream restoration working group (FISRWG 1998). *Stream Corridor Restoration: Principles, Processes, and Practices*, ISBN-0-934213-59-3.
- Fernandez, F. (2010). Report on the use of nitrification and urease inhibitors on corn in Illinois. University of Illinois report.
- Foo, K., Lee, L.K., and Hameed, B. (2013). Preparation of banana frond activated carbon by microwave induced activation for the removal of boron and total iron from landfill leachate. *Chem. Eng. J.*, 223, 604-610.
- Freundlich, H. (1907). Ueber die adsorption in Loesungen. *Z. physik. Chem.*, 57, 385-470.
- Fuchs, W., Binder, H., Marrias, G., and Braun, R. (2003). Anaerobic treatment of wastewater with high organic content using a stirred reactor coupled with a membrane filtration unit. *Journal of Water Research*, 37, 902-908.

- Gate Information Services (GTZ,) (2001). Anaerobic treatment of slaughterhouse waste and wastewater. Naturgerechte Technologien, Bau- und Wirtschaftsberatung GmbH, Frankfurt Germany. Retrieved from: <http://www.gtz.de/gate/gateid.afp>.
- Genovese, C.V., and González, J.F. (1998). Solids removal by coagulation from fisheries waste waters. *Waters SA*, 24(4), 371-381.
- Goeschl, R. (2012). *System, Technology and Experience of 17 Mt of Landfill mining projects*. In: Conference paper of the symposium on urban mining SUM' 2012, Italy, Bergamo, May, 21-23, 2012.
- Gotmare, M., Dhoble, R.M., and Pittule, A.P., (2011). Biomethanation of dairy waste water through UASB at mesophilic temperature range. *Int. J. Adv. Eng. Sci. Technol.*, 8, 1-9.
- Grossmann, D., Hudson J.F., and Marks, D.H. (1974). Waste generation models for solid waste collection. *J. Env. Eng., Div.-ASCE*, 100, 1219-1226.
- Guellide Ulson.de Souza, S.M.A., Peruzzo, L.C., and Ulson de Souza, A.A. (2008). Numerical study of the adsorption of dyes from textile effluents. *Appl. Math. Model.*, 32, 1711-1718.
- Gupta, V.K., and Suhas., (2009). Application of low-cost adsorbents for dye removal- a review. *Journal of Environmental Management*, 90(8), 2313-2342.
- Gupta, V.K., Nayak, A., 2012. Cadmium removal and recovery from aqueous solutions by novel adsorbents prepared from orange peel and Fe₂O₃ nanoparticles. *Chemical Engineering Journal*, 180, 81-90.
- Hamoda, M., and Al-Awadi, S.M. (1995). Wastewater management in a dairy farm. *Water Science & Technology*, 32(11), 1-11.
- Han, Z., Liu, D., and Liu, Q.B. (2012). A removal mechanism for organics and nitrogen in treating leachate using a semi-aerobic aged refuse biofilter. *Journal of Environmental Management*, 114, 336-342.
- Hansen, H.C.B., Raben-Lange, B., Raulund-Rasmussen K et al (1994) Monosilicate adsorption by ferrihydrite and goethite at pH 3-6. *Soil Science*, 158, 40-46
- Hao, C., Guoliang, D., Jie, Z., Aiguo, Z., Junyong, W., and Hua, Y. (2010). Removal of copper (II) ions by a biosorbent-Cinnamomum camphora. *Journal of Hazardous Materials*, 177, 228-236.
- Harrington, R., and McInnes, R. (2009). Integrated constructed wetlands (ICW) for livestock wastewater management. *Bioresource Technology*, 100, 5498-5505.

- Hatfield, (2009). Final Risk Assessment report for Air Hitam Sanitary Landfill Site, Selangor, Malaysia.
- He, Y., Zhao, Y.C., Zhou, G.M., and Huang, M.S. (2011) Field assessment of stratified aged-refuse-based reactor for landfill leachate treatment. *Waste Manag. Res.*, 29(12), 1294–1302.
- Heavey, M. (2003). Low-cost treatment of landfill leachate using peat. *Waste Management*, 23, 447-454.
- Hena, S., Fatimah S., and Tabasum S. (2015). Cultivation of algae consortium in a dairy farm wastewater for biodiesel production. *Water Resources and Industry*, 10, 1-14.
- Henze, M.; and Comeau, Y. (2008). Wastewater characterization. In *Biological Wastewater Treatment: Principles, Modeling, And Design*, Henze, M., van Loosdrecht, M. C. M., Ekama, G. A., Brdjanovic, D., Eds.; IWA Publishing: London, 33–52.
- Hogland, W. (2002). Remediation of an old landfill: soil analysis, leachate quality and gas production. *Environ. Sci. Pollut. Res. Int.*, 1, 49–54.
- Hosseini, S.E., Wahid, M.B., and Aghili, N. (2013). The scenario of greenhouse gases reduction in Malaysia. *Renewable & Sustainable Energy Reviews*, 28, 400-409.
- Huang, R., Yang, B., Liu, Q., and Liu, Y. (2014). Simultaneous adsorption of aniline and Cr (VI) ion respectively by activated carbon/chitosan composite. *Journal of Applied Polymer Science*, 131, 39903.
- Hunter, R.J. (1989). *Foundations of Colloid Science*. Oxford University Press.
- Ideriah, T., David, O., and Ogbonna, D. (2012). Removal of heavy metal ions in aqueous solutions using palm fruit fibre as adsorbent. *J Environ Chem. Ecotoxicol.*, 4(4), 82–90.
- Imura, H., Yedla, S., Shinirakawa, H., and Memon, M.A. (2005). Urban environmental issues and trends in Asia – An overview. *International Review for Environmental Strategies*, 5, 357-382.
- International Union of Pure and Applied Chemistry (IUPAC), (1992). *Compendium of chemical technologies*, 2nd Edition.
- Ismail, F.B (2014). Aged refuse as a medium to remediate leachate contaminated by heavy metals. Master's Thesis, Universiti Putra Malaysia.
- Ives, K. J. (1975). *The Scientific Basis of Filtration*, NATO Advanced Study Institute Series E, Vol. 2. Noordhoff, Leiden.

- Jones, P., Geysen, D., Tielemans, Y., Steven, V., Pontikes, Y., Blanpain, B., Quaghebeur, M., and Hoekstra, N. (2013). Enhanced landfill mining in view of multiple resource recovery: A critical review. *Journal of Cleaner Production*, 55, 45 – 55.
- Judd, S., and Jefferson, B. (2003). Membrane for industry wastewater recovery and reuse. Elsevier Science Inc, New York, USA, 2003 7–25.
- Kaur, K., Mor, S., and Ravindra, K. (2016). Removal of Chemical Oxygen Demand from landfill leachate using cow-dung ash as a low-cost adsorbent. *Journal of colloids and interface science*, 469, 338-343.
- Karmali, M. A., Gannon, V., and Sargeant, J. M. (2010). Verocytotoxin-producing Escherichia coli (VTEC). *Vet. Microbiol.*, 140, 360–370.
- Kirby, B.J. (2010). Micro- and Nanoscale Fluid Mechanics: Transport in Microfluidic Devices. Cambridge University Press. ISBN 978-0-521-11903-0.
- Klute, A., and Dirksen, C. (1986). *Hydraulic Conductivity & diffusivity: Laboratory Methods*. In Klute, A. (ed). *Methods of soil Analysis, Part 1. Physical & Mineralogical Methods*, 2nd Edn ASA-SSSA, Wisconsin, pp 687-734.
- Knight, R.L., Payne, V.W.E., Borer, R.E., Clarke, R.A., and Pries, J.H. (2000). Constructed wetlands for livestock wastewater management. *Ecological Engineering*, 15, 41–55.
- Kobya, M., Senturk, E., and Bayramoglu, M. (2006). Treatment of poultry slaughterhouse wastewaters by electrocoagulation. *Journal of Hazardous Materials*, 133(1), 172-176.
- Kralik, M. (2014). Adsorption, chemisorption, and catalysis. *Chemical Papers*, 68 (12), 1625–1638.
- Kratochvil, D., and Volesky, B. (1998). Advances in the biosorption of heavy metals *Trends Biotechnol.*, 16 (7), 291-300.
- Kretzschmar, R., Barmettler, K., Grolimund, D., Yan, Y. D., Borkovec, M., and Sticher, H. (1997). Experimental determination of colloid deposition rates and collision efficiencies in natural porous media. *Water Resources Research*, 33, 1129–1137.
- Kumar, K.V. (2006). Comments on adsorption of acid dye onto organobentonite. *Journal of Hazardous Materials*, 137(1), 638-639.
- Kumar, K.V., and Sivanesan, S. (2007). Isotherms for Malachite Green onto rubber wood (*Hevea brasiliensis*) sawdust: Comparison of linear and non-linear methods. *Dyes Pig.*, 72, 124-129.

- Kurniawan, T.A., Chan, G., Lo, W.H., and Babel, S. (2006). Physico-chemical treatment techniques for wastewater laden with heavy metals. *Chemical Engineering Journal*, 118(1), 83–98.
- Kushwaha, J.P., Srivastava, V.C., and Mall, I.D. (2010). Treatment of dairy wastewater by commercial activated carbon and bagasse fly ash: Parametric, kinetic and equilibrium modelling, disposal studies. *Bioresource Technology*, 101, 3474–3483.
- Laner, D., Crest, M., Scharff, Hejjo, S., Morris, J.W.F., and Barlaz, M.A. (2012). A review of approaches for long term management of municipal solid waste landfills. *Waste Management*, 32(3), 498-512.
- Langmuir, I. (1918). The adsorption of gases on plane surfaces of glass, mica and platinum. *J. Am. Chem. Soc.*, 40, 1361-1403.
- Leal, M. C. M. R., Freire, D. M. G., Cammarota, M. C., Anna, G. L., and Sant, Jr. (2006). Effect of enzymatic hydrolysis on anaerobic treatment of dairy wastewater. *Process Biochem.*, 41, 1173–1178.
- Li, G., Hou, F., Guo, Z., Yao, G., and Sang, N. (2011). Analyzing nutrient distribution in different particle-size municipal aged refuse. *Waste Management*, 31, 2203-2207.
- Li, H., Zhao, Y., Shi, L., and Gu, Y. (2009). Three-stage aged refuse biofilter for the treatment of landfill leachate. *Journal of Environmental Sciences*, 21, 70-75.
- Li, H., Gu, Y., Zhao, Y., and Wen, Z. (2010). Leachate treatment using a demonstration aged refuse biofilter. *Journal of Environmental Science*, 22, 1116-1122.
- Li, J.P., Healy, M.G., Zhan, X.M., and Rodgers, M. (2008). Nutrient removal from slaughterhouse wastewater in an intermittently aerated sequencing batch reactor. *Bioresource Technology*, 99 (16), 7644–50.
- Liang, Y., Wong, J.W., and Wei, L. (2005). Silicon-mediated enhancement of cadmium tolerance in maize (*Zea mays* L.) grown in cadmium contaminated soil. *Chemosphere* 58, 475–483.
- Limousin, G., Gandet, L., Szenknect, S., Barthes V., and Krissmissa, M. (2007). A review on physical bases, modelling and measurement. *Applied Geochem.* 22, 249-275.
- López-López, J.A., Vallejo-Rodríguez, R and Méndez-Romero, D.C. (2010). Evaluation of a combined anaerobic and aerobic system for the treatment of slaughterhouse wastewater. *Environmental Technology*, 31(3), 319-326.

- López-Ramírez, A., Coello-Oviedo, M.D., and Quiroga-Alonso, J.M. (2006). Comparative studies of reverse osmosis membranes for wastewater reclamation. *Desalination*, 191 (1–3), 137–147.
- Lou, Z.Y., Chai, X.L., Niu, D.J., Ou, Y.Y., and Zhao, Y.C. (2009). Size-fractionation and characterization of landfill leachate and the improvement of Cu²⁺ adsorption capacity in soil and aged refuse. *Waste Management*, 29, 143–152.
- Lou, Z, wang, L., Zhu, N, and Zhao, Y. (2015). Material recycling from renewable landfill and associated risks: A review. *Chemosphere*, 131, 91-103.
- Lyklema, J. (1995). *Fundamentals of Interface and Colloid Science*. Academic Press.
- Malaysian Government/DANIDA, (2008). *Solid Waste Management Component: Industrial waste survey in Melaka*. Report no. 15.
- Malaysia Environmental Quality Regulation, (2009). *Malaysia Sewage and Industrial Effluent Discharge Standards, 2009* Retrieved from: www.water-treatment.com.cn/resources
- Manaf, L.A., Amimul, A., Azmin, S.W.N, Samah, M. A. A., and Agamuthu, P. (2013). Real data composition of municipal solid waste (MSW) generated in Balakong, Selangor, Malaysia. *Life Science Journal*, 10(4), 1687-1694.
- Manaf, L.A., Mohd Armi, A.S, and Nur Ilyana, M.Z (2009). Municipal solid waste management in Malaysia: Practices and challenges. *Waste Management*, 29(11), 2902–2906.
- Manjunath, N. T., Mehrotra, I. and Mathur, R. P. (2000). Treatment of wastewater from slaughterhouse by DAFUASB system. *Journal of Water Research*, 34, 1930-1936.
- Mann, A.G., Tam, C.C., Higgins, C.D., and Lodrigues, L.C. (2007).The association between drinking water turbidity and gastrointestinal illness: A systematic review. *BMC Public Health.*, 7 (256), 1 – 7.
- Maria, M., Nuria, M., Soraya, H., and Nuria, F. (2006). Removal of lead (II) and cadmium (II) from aqueous solutions using grape stalk waste. *Journal of Hazardous Materials*, 133, 203-211.
- Marin, P., Alkaky, L., Guerrero, L., Chamy, R., and Schiappacasse, M.C. (1999). Design and start-up of an anaerobic fluidized bed reactor. *Water Science & Tech.* 40(8), 63-70.
- Marinescu, M., Dumitru, M., and Lacatusu, A. (2009). Biodegradation of petroleum hydrocarbons in an artificial polluted soil. *Research Journal of Agricultural Science*, 41(2), 157-162.

- Martínez-Suller¹, L., Provololo¹, G., Carton, O.T., Brennan, O., Kirwan, L., and Richards, K.G., (2010). The composition of dirty water on dairy farms in Ireland. *Irish Journal of Agriculture and Food Research*, 49, 67-80.
- Masirin, M.I.HJ., Ridzuan, M.B., Mustaphar, S., and Adon, R. (2008). An Overview of Landfill Management and technology: A Malaysian case study at Ampar Tenang. Proceedings of 1st National seminar on Environment, Development and Sustainability: Ecological, Economic and Social Aspects.
- Masse, D. I., and Masse, L. (2000). Treatment of slaughterhouse wastewater in anaerobic sequencing batch reactor. *Journal of Canadian Agricultural Engineering*, 42(3), 131-137.
- Masse, L. Masse, D. I. and Kennedy, K. J. (2003). Effect of hydrolyziz pretreatment on fat degradation during anaerobic digestion of slaughterhouse wastewater. *Process. Biochem.* 38, 1365–1372.
- Masse, L. Kennedy, K.J. and Chou, S. (2001). Testing of alkaline and enzymatic hydrolyziz pretreatments for oil particles in slaughterhouse wastewater. *Bioresource Technology*, 77, 145–155.
- McGechan, M.B., and Lewis, D.R. (2002). Transport of particulate and colloid sorbed contaminants through soil, Part 1: General principles. *Biosystems Engineering*, 83 (3), 255–273.
- McKeague, J.A., and Cline, M.G. (1963). Silica in soil solutions. I. The form and concentration of dissolved silica in aqueous extracts of some soils. *Can. J. Soil Sci.*, 43, 70–82.
- Mike L. (2006). Treatment of slaughter-house wastewater. Retrieved from www.ndsu.edu/pubweb/bezbarau/document.
- Ming, L., Youcai, Z., Qiang, G., Xiaoqing, Q., and Dongjie, N. (2008). Bio-hydrogen production from food waste and sewage sludge in the presence of aged refuse excavated from refuse landfill. *Renewable Energy*, 33(12), 2573-2579.
- Ming, T.T., Hyun, K.T., and Joo, L.M. (2007). Characterization of livestock wastewater at various stages of wastewater treatment plant. *The Malaysian Journal of Analytical Sciences*, 11(1), 23-28.
- Ministry of Housing and Local Government (MHLG). *National solid waste management department 2014 Reports*. Retrieved from <http://www.kpkt.gov.my/jspn/main.php%20>.
- Mitchell and Stapp, 1992. Field Manual for Water Quality Monitoring. United States Environmental Protection Agency (U.S. EPA), Washington, DC. "Terms of Environment." Retrieved from: <http://www.epa.gov/OCEPATERMS>.

- Mittal, A. (2006). Adsorption kinetics of removal of a toxic dye, malachite green, from wastewater by using hen feathers. *Journal of Hazardous Material*, 133, 196-202.
- Mittal, A., Kaur, D., Malviya, A., Mittal, J., and Gupta, Y.K. (2009). Adsorption studies on the removal of coloring agent phenol red from wastewater using waste materials as adsorbents. *J. Colloid Interface Sci.*, 337(2), 345-354.
- Mohammad, M.M.R., Parisa, R., Atefeh, A., and Ali, R.K. (2011). Kinetics and equilibrium studies on biosorption of cadmium, lead, and nickel ions from aqueous solutions by intact and chemically modified brown algae. *Journal of Hazardous Materials*, 185, 401-407.
- Mohammad-Taha, M.P. Integrated Solid waste management: Issues and Challenges. *Solid waste and public cleansing management corporation (SWCORP)*. Government press, 2016. Retrieved from: nehapmalaysia.moh.gov.my
- Mohan, D., and Pittman, C.U. Jr. (2006). Activated carbons and low cost adsorbents for remediation of tri- and hexavalent chromium from water. *Journal of Hazardous Materials*, 137(2), 762-811.
- Mohd. Nor, N.M., Gan, C.H., and Ong, B.L. (2000). Nipah virus infection of pigs in Peninsular Malaysia. *Disease Information, OIE*, 13, 12.
- Monroy, O., Johnson, K. A., Wheatley, A. D., Hawkes, F., and Caine, M. (1994). The anaerobic filtration of dairy waste: Results of a pilot trial. *Bioresource Technology*, 50, 43-251.
- Mor, S., Ravindra, K., and Bishnoi, N.R. (2007). Adsorption of chromium from aqueous solution by activated alumina and activated charcoal. *Bioresource Technology*, 98(4), 954-957.
- Mukhopadhyay, R., Talukdar D., Chatterjee, B.P., and Guha, A.K. (2003). Whey processing with chitosan and isolation of lactose. *Process Biochem.*, 39, 381-385.
- Mulu, B.D., (2013). Batch sorption experiments: Langmuir and Freundlich isotherm studies for the adsorption of textile metal ions onto teff straw (*Eragrostis tef*) agricultural waste. *Journal of Thermodynamics*, doi.org/10.1155/2013/375830.
- Naqvi, S., and Sejian, V. (2011). Global climate change: Role of livestock. *Asian Journal of Agricultural Sciences*, 3(1), 19-25.
- National Solid Waste Management Department, (NSWMD), (2011). *Landfill sites in Johor*, Ministry of Housing and Local Government. Kuala Lumpur, Malaysia. Retrieved from www.kpkt.gov.my.

- Ncibi, M.C. (2008). Applicability of some statistical tools to predict optimum adsorption isotherm after linear and non-linear regression analysis. *Journal of Hazardous Materials*, 1:153 (1-2), 207-212.
- Ngo, T. D. T. (2004). *Integrated use of constructed wetlands for livestock wastewater treatment and fodder production*. Master Thesis, Universiti Putra Malaysia, Malaysia.
- Ngoc, U. N., and Schnitzer, H. (2009). Sustainable Solutions for Solid Waste Management in Southeast Asian countries. *Waste Management*, 29, 1982–1995.
- Nik Daud, N.N., and Misban, N.K.M. (2015). Leachate treatment using aged refuse biofilter. *International Journal of Engineering and Technology*, 12(1), 13-17.
- Nik Daud, N.N., Nursheela, A.M., Amimul, A., and Syazwani, I. (2015). Leachate treatment using aged refuse (AR) as a biofilter medium. *Polish Journal of Environmental Studies*, 24 (2), 605-609.
- Noor, Z.Z., Yusuf, R.O., Abba, A.H., Hassan, M.A.A., and Din, M.F.M. (2013). An overview for energy recovery from municipal solid wastes (MSW) in Malaysia scenario. *Renewable Energy Reviews*, 20, 378-384.
- OECD-FAO, (2011). *Agricultural outlook, 2011-2020*. Wayne J. Trade and Agricultural Directorate, Organization for Economic Co-operation and Development- Food and Agriculture Organization of the United Nations. Retrieved from: www.agri-outlook.org
- Ogboo, C.A., and Hussain, H.A.K. (2013). Review of municipal solid waste management options in Malaysia, with an emphasis on sustainable waste-to-energy options. *Journal of Material Cycles and Waste Management*, 16(4), 693-710.
- Othman, I., Anuar, A.N., Ujang, Z., Rosman, N.H., Harun, H., and Chelliapan, S. (2013). Livestock wastewater treatment using aerobic granular sludge. *Bioresources Technology*, 133, 630-634.
- Ozezn, A.S., Erdem, B., and Ozean, A. (2005). Adsorption of acid blue 193 from aqueous solution onto BTMA- bentonite. *Colloids Surf. A: Physiochem. Eng. Aspects*, 266, 73-81.
- Palenzuela-Rollon, A., (1999). *Anaerobic Digestion of Fish Processing Wastewater with Special Emphasis on Hydrolysis of Suspended Solids*. Taylor and Francis, London.
- Parande, A.K., Sivashnmugam, A., Beulah, H., and Palaniswamy, N. (2009). Performance evaluation of low cost adsorbents in reduction of COD in sugar industrial effluent. *Journal of Hazardous Materials*, 168, 800-805.

- Pattananuwat, N., Kawai, T., Hatamoto, M., Stutsubo, K., Takahashi, M., Harada, H., and Yamaguchi, T. (2013). Development of combined anaerobic-aerobic system for treating industrial molasses wastewater. *Journal of water and Environmental Technology*, 11(6), 519-528.
- Pohland, F.G., and Harper, S.R. (1985). *Critical Review and Summary of Leachate and Gas Production from Landfills*. EPA/600/2-86/073, US Environmental Protection Agency, Cincinnati.
- Pozo, R. D., and Diez, V. (2005). Integrated anaerobic-aerobic fixed-film reactor for slaughterhouse wastewater treatment. *Journal of Water Research*, 39, 1114-1122.
- Prechthai, T., Padmasri, M., and Visvanathan, C. (2008). Quality assessment of mined MSW from an open dumpsite for recycling potential. *Resources, Conservation and Recycling*, 53, (1-2), 70-78.
- Pruss-Ustun, A., Bos, R., Gore, F., and Bartram, J. (2008). Safer Water, Better Health. Geneva, World Health Organization.
- Pukkalanun, N., Inkapatanakul, W., Piputsitee, C., and Chunkao, K. (2013). An analysis of the environmental vulnerability index of a small island: Lipe Island, Kho Sarai Sub-District, Mueang District, Satun Province, Thailand. *Modern Applied Science*, 7(2), 33-38.
- Quaghebeur, M., Laenen, B., Geysen, D., Nielsen, P., Pontikes, Y., van Gerven, T., and Spooren, J. (2013). Characterization of landfilled materials: Screening of the enhanced landfill mining potential. *Journal of Cleaner Production*, 55, 72-83.
- Radovic, L.R in: Schwarz, J.A., Contescu A. (Eds.) (1999). *Chemistry and physics of carbon*. Vol. 24 Marcel Dekker, New York p 529
- Rahman, M., Awang, M., Mohosina, B., Kamaruzzaman, B., Nik, W., and Adnan, C.(2012). Waste palm shell converted to high efficient activated carbon by chemical activation method and its adsorption capacity tested by water filtration. *APCBEE Procedia*, 1, 293-298.
- Rajakumar, R., Meenambal, T., Rajesh Banu, J., and Yeom, I.T. (2011). Treatment of poultry slaughterhouse wastewater in upflow anaerobic filter under low upflow velocity. *Int. J. Environ. Sci. Tech.*, 8(1), 149-158.
- Ramaraju, B., Manoj, K. R., and Subrahmanyam, C. (2014). Low cost adsorbents from agricultural wastes for the removal of dyes. *Environmental Progress & Sustainable Energy* 33 (1), 38-46

- Reddy, K.R., Hettiarachohi, H., Parakalla, N.S., Gangathulas, J., and Bogner, J.E. (2009). Geotechnical properties of fresh municipal solid waste at Orchid Hills landfill site USA. *Waste management*, 29, 952-959.
- Reninhart, D.R., McCreanor, P.T. and Townsend, K.T. (2002). The bioreactor landfill: its status and future. *Waste Management & Research*, 20, 172– 186.
- Renou, S., Givaudan, J.G., Poulain, S., Dirassouyan, F., and Moulin, P. (2008). Landfill leachate treatment: Review and opportunity. *Journal of Hazardous Materials*, 150, 468–493.
- Rivas, F.J., Beltran, F.J., Gimeno, O., and Alvarez, P. (2003). Optimization of Fenton's reagent usage as a pre-treatment for fermentation brines. *Journal of Hazardous Materials*, 96, 277–290.
- Ruiz, I., Veiga, M. C., de Santiago, P., and Blázquez. (1997). Treatment of slaughterhouse wastewater in a UASB reactor and an anaerobic filter. *Bioresources Technology*, 60 (3), 251-258.
- Ruthven, D. M. (1984). Principles of adsorption & adsorption processes. Hoboken, NJ, USA: Wiley.
- Russel, W.B., Saville, D.A., and Schowalter, W.R. (1989). Colloidal Dispersions. Cambridge University Press.
- Sachs, D. P. (1999). Edaphos: Dynamic of a natural soil system, pp. 152-153.
- Saeed, A., Akhter, M.W., and Iqbal, M. (2005). Removal and recovery of heavy metals from aqueous solution using papaya wood as a new biosorbent. *Sep Purif Technol.*, 45(1), 25–31.
- Saeed, M.O., Hassan M.N., and Mujeebu, M.A. (2009). Assessment of municipal solid waste generation and recyclable materials potential in Kuala Lumpur, Malaysia. *Waste Management*, 29(7), 2209-2213.
- Saifuddin, M.N., and Kumaran, P. (2005). Removal of heavy metal from industrial wastewater using chitosan coated oil palmshell charcoal. *Electronic Journal of biotechnology*, 1, 43-53.
- Sarioglu, M. (2005). Removal of ammonium from municipal wastewater using natural Turkish (Dogantepe) zeolite. *Separation & Purification Technology*, 41, 1-11.
- Sarkar, B., Chakrabarti, P., Vijaykumar, A., and Kale, V. (2006). Wastewater treatment in dairy industries: Possibility of reuse. *Desalination*, 195, 141-152.
- Savant, N.K., Snyder, G.H., and Datnoff, L.E. (1997). Silicon management and sustainable rice production. *Advance Agronomy* 58, 151–199

- Sawyer, C.N., McCarty, P.L., and Parkin, G.F. (2003). *Chemistry for Environmental Engineering and Science*, (5th ed.). New York: McGraw-Hill.
- Sayed, S.K.J., and de Zeeuw, W. (1988). The performance of a continuously operated Flocculent sludge UASB reactor with slaughterhouse wastewater. *Biological Wastes*, 24, 199-212.
- Seif, H., and Moursy, A. (2001). Treatment of slaughterhouse wastes. *Sixth International Water Technology Conference, IWTC 2001, Alexandria, Egypt*.
- Seik, F. (1997). Recycling of domestic wastes: Early experiences in Singapore. *Habitat International*, 21(3), 277–289.
- Shahir, M. S. Z. (2010). Study on Solid Waste Generation in Kuantan, Malaysia: It's Potential for Energy Generation. *International Journal of Engineering Science and Technology*, 2(5), 1338-1346.
- Sharon, B. (1996). Testing the waters: Chemical and physical vital signs of a river, Montpelier, Vermont: River Watch Network.
- Shao, F., Zhang, D.G., and Zhao, Y.C. (2002). Experimental study on livestock and poultry wastewater treatment by aged refuse based bioreactor. *Tech. Equip. Environ. Pollut. Control*, 2, 32-36.
- Shao, H., and Zhang, D. (2012). Study on the adsorption of livestock wastewater by Bentonite coated chitosan. *Advanced Material Research*, 356-360.
- Shin, J.H., Lee, S.M., Jung, J.Y., Chung, Y.C., and Noh, S.H. (2005). Enhanced COD and nitrogen removals for the treatment of swine wastewater by combining submerged membrane bioreactor (MBR) and anaerobic upflow bed filter (AUBF) reactor. *Process Biochemistry*, 40, 3769-3776.
- Sivakumar, D. (2013). Adsorption study on municipal solid waste leachate using Moringa oleifera seed. *International J. Environ. Sci. Technology*, 10, 113-124.
- Sombatsompop, K., Songpi, A., Reabroi, S., and Inkong-ngam. P. (2011). A comparative study of sequencing batch reactor and moving bed sequencing batch reactor for piggery wastewater treatment. *Maejo International Journal of Science and Technology*, 5(2), 191-203.
- Song, L.Y., Shi, L., Zhao, Y.C., and Li, H.J. (2011). Novel engineering controls to increase leachate contaminant degradation by refuse: From lab test to in situ engineering application. *Ecological Engineering*, 37(11), 1914– 1919.
- Soyoung, L., Maniquiz, M.C., and Lee-Hyung, K. (2010). Characteristics of contaminants in water and sediment of a constructed wetland treating piggery wastewater effluent. *Journal of Environmental Sciences*, 22 (6), 940-945.

- Stathi, P., Papadas, I.T., Tselepidou, A., and Deligiannakis, Y. (2010). Heavy-metal uptake by a high cation-exchange-capacity Montmorillonite: The role of permanent charge sites, *Global NEST Journal*, 12, (3), 248-255.
- Steinmann, P., Keiser, J., Bos, R., Tanner, M., and Utzinger, J. (2006). Schistosomiasis and water resources development: systematic review, meta-analysis, and estimates of people at risk. *Lancet. Infect. Dis.*, 6, 411–425.
- Sun, Y., Sun, X., and Zhao, Y. (2011). Composition of semi-aerobic and anaerobic degradation of refuse with recirculation after leachate treatment by aged refuse bioreactor. *Waste Management*, 31, 1202–1209.
- Taylor, L. H., Latham, S. M., and Woolhouse, M. E. (2001). Risk factors for human disease emergence. *Philos. Trans. R. Soc. Lond., B, Biol. Sci.*, 356, 983–989.
- Tchobanoglous, G., Theisen, H., and Vigil, S. (1993). *Integrated solid waste management engineering principles and management issues*. New York: McGraw-Hill.
- Tran, H., You, S.J., Hosseini-Bandelgharaei A.-H., and Chao, H.-P. (2017). Mistakes and inconsistencies regarding adsorption of contaminants from aqueous solutions: A critical review. *Water Research*, 120(1) 88-116.
- Tritt, W.P., and Schuchardt, F. (1992). Materials flow and possibilities of treating liquid and solid wastes from slaughterhouses in Germany. A review. *Bioresource Technology*, 41, 235-245.
- Tubaña, B.S., and Heckman, J.R. (2015), Silicon in Soils and Plants. In: Silicon and Plant Diseases, F.A. Rodrigues, L.E. Datnoff (eds.) Springer International Publishing Switzerland, 7-15.
- UNDP, (2008). *Developing a Solid Waste Management Model for Penang*, United Nations Development Programme, Malaysia.
- UNEP, (2005). *Solid Waste Management* (Vol. II). United Nations Environment Programme- Division of Technology, Industry and Economics- International Environmental Technology Centre. Osaka: CalRecovery, Inc.
- UNEP (2011). Towards a Green Economy. Investing in energy and Resource Efficiency. Retrieved from www.unep.org/towardsagreeneconomy
- UN-HABITAT, (2010). *Collection of Municipal Solid Waste in Developing Countries*. United Nations Human Settlements Programme (UN-HABITAT), Nairobi.
- United States Environmental Protection Agency (U.S. EPA), Washington, DC. "Drinking Water Contaminants." 2009-09-11. Retrieved from: <http://www.epa.gov/safewater/mcl.html>

- United States Department of Agriculture, (USDA), (2000). *Agricultural Waste Management Field Handbook*. Retrieved from: <http://www.nrcs.usda.gov>
- U.S. Food and Drug Administration Centre for Food Safety & Applied Nutrition, Foodborne Pathogenic Microorganisms and Natural Toxins Handbook (“Bad Bug Book”). <http://vm.cfsan.fda.gov/~mow/intro.html>
- USEPA, (2012). Solid Waste and Emergency Response. United States Environmental protection Agency. Retrieved from: www.epa.gov/globalwarming
- Ushakumary, E.R. (2013). Wastewater treatment using low cost natural adsorbents. Ph.D Thesis, Cochin University of Science and Technology, India.
- Van der Stelt, B., Temminghoff, E.J.M., Van Vliet, P.C.J., and Van Riemsdijk, W.H. (2007). Volatilization of ammonia from manure affected by manure additives, temperature and mixing. *Bioresource Technology*, 98, 3449-3455.
- Vinten, A. J. A.; and Nye, P. H. (1985). Transport and deposition of dilute colloidal suspensions in soils. *Journal of Soil Science*, 36, 531–541.
- Volesky, B. (2007). Biosorption and me. *Water Resources*, 41(18), 4017-4029.
- Wang, L.K. (2009). *Heavy Metals in the Environment*. Boca Raton, FL: CRC Press.
- Wang, C., Zhao, Y., Xie, B., Peng, Q., Hassan, M., and Wang, X. (2014). Nitrogen removal pathway of anaerobic ammonium oxidation in on-site aged refuse bioreactor. *Bioresource Technology*, 159, 266–271.
- Wang, F., Sun, Y., and Zhou, R. (2012). Experimental study on the treatment of chromium containing wastewater by aged refuse. *Procedia Environmental Science*, 16, 598– 605.
- Wang, M., and Zhao, Y.C. (2004) Treatment of coke plant-wastewater using aged-refuse based bioreactor. *Environ Technol.*, 1, 25–28.
- Wang, S., Yang, X., Lin, X., Hu, Y., Luo, C., Xu, G., Zhang, Z., SU, A., Chang, X., Chao, Z., and Duan, J. (2009). Methane emission by plant communities in an alpine meadow on the Qinghai-Tibetan Plateau: A new experimental study of alpine meadows and oat pasture. *Biology Letters*, 5(4), 535–548.
- Wang, Y., Gao, P., Fan, M., and Jin, H. (2011). Preliminary study of purification for livestock wastewater of immobilized microcystis aeruginosa. *Procedia Environmental Sciences* 11, 1316-1321.
- Webber, T.W., and Chakravorti, R.K. (1974). Pore and solid diffusion models for fixed-bed adsorbents. *AIChE Journal*, 20(2), 228–238.

- Wei, X.M., Lin, C., Duan, N., Peng, Y.X., and Ye, X.Y. (2010). Application of aerobic biological filter for treating swine farms wastewater. *Procedia Environmental Sciences*, 2, 1569–1584.
- World Health Organization, (WHO), (2012). *Animal Waste, Water Quality and Human Health*. (Ed). Al Dufour, Jamie Bartram, Robert Bos and Victor Gannon. IWA Publishing, London, UK. ISBN: 9781780401232.
- Xie, B., Lv, Z., Hu, C., Yang, X., and Li, X. (2013). Nitrogen removal through different pathways in an aged refuse bioreactor treating mature landfill leachate. *Applied Microbiology and Biotechnology*, 97, 9225–9234.
- Xie, B., Xiong, S.Z., and Liang, S.B. (2012). Performance and bacterial compositions of aged refuse reactors treating mature landfill leachate. *Bioresource Technology*, 103(1), 71–77.
- Yang, Y.J., and Zhao, Y.C. (2006). Study on the operation parameter of an aged-refuse biofilter for livestock wastewater treatment. *Jiangsu Chemical Industry*, 5, 13 Retrieved from: <http://www.cnki.com.cn>
- Yang, X.-e., Wu, X., Hao, H.-l., He, Z.-l. (2008). Mechanisms and assessment of water eutrophication. *Journal of Zhejiang University Science B*, 9(3), 197-209.
- Yin, C., Aroua, M., Daud, W. (2008). Enhanced adsorption of metal ions onto polyethyleneimine-impregnated palm shell activated carbon: Equilibrium studies. *Water Air Soil Pollution*, 192 (1–4), 337–348.
- Zamali T., Mohd Lazim, A., and Abu Osman, M.T. (2009). An overview of municipal solid wastes generation in Malaysia. *Jurnal Teknologi*, 51(F), 1-15.
- Zeldowitsch, J. (1934). Adsorption site energy distribution, *Acta Phys. Chim. URSS* 1, 961 973.
- Zeng, G., Ma, J., Xiong, B., and Tian, Y. (2015). Experimental study on engineering mechanical properties of aged refuse. *EJGE*, 20(12), 4361-4368.
- Zhang, H., and Zhao, Y.C. (2004). Comprehensive utilization of the aged refuse in MSW landfill. *J. Shangdong Univ. Archit. Eng.*, 19, 46–50.
- Zhang, H.H., Tian, J.S., Zhang, Y.M., Wu, Z.L., Kong, X.J., Chao, J.Y., Hu, Y., and Li, D.L. (2012). Removal of phosphorus and nitrogen from domestic wastewater using a mineralized refuse based bioreactor. *Environmental Technology*, 33(2), 173-181.
- Zhang, J., Xiao, J.J., Gao, J.M., and Zhang, X.D. (2014). Phenol adsorption on nitrogen-enriched activated carbon prepared from bamboo residues. *BioResources*, 9(1), 969-983.

- Zhang, T., Ding, L., Ren, H., and Xiong, X. (2009). Ammonium nitrogen removal from coking wastewater by chemical precipitation recycle technology. *Water research*, 43(20), 5209-5215.
- Zhao, Y., Chai, X., and Niu, D. (2006). The basic characteristics of the aged refuse. *Journal of Tongji University (Natural Science)*, 34(10), 1360-1364.
- Zhao, Y., Lou, Z., Guo, Y., and Xu, D. (2007). Treatment of sewage using an aged-refuse-based bioreactor. *Journal of Environmental Management*, 82(1), 32–38.
- Zhao, Y.C. (2002). Excavation and characterization of refuse in closed landfill. *Journal of environmental sciences*, 14(3), 302-308.
- Zhao, Y.C., Li, H., Wu, J., and Gu, G.W. (2002) Treatment of leachate by aged refuse-based biofilter. *Journal of Environmental Engineering*, 128, 662–668.
- Zhao, Y.C., and Shao, F. (2004) Use of an aged-refuse biofilter for the treatment of feedlot wastewaters. *Environ Eng Sci.*, 21(3), 349–360.
- Zhu, D., Sun, C., Zhang, H., Wu, Z., Jia, B., and Zhang, Y. (2012). Roles of vegetation, flow type and filled depth on livestock wastewater treatment through multi-level mineralized refuse based constructed wetlands. *Ecological Engineering* 39, 7–15.

BIODATA OF STUDENT

Anijiofor Sandra Chinenyenwa, obtained her first degree (B.ENG), in Civil Engineering in 1998 from the Enugu State University of Science and Technology, Enugu State, Nigeria. She obtained her second degree (M. Eng.), in Water Resources and Environmental Engineering in 2010 from the Federal University of Science and Technology, Minna, Niger State, Nigeria. She is presently a Principal Lecturer at the Department of Civil Engineering, Federal Polytechnic, Birnin Kebbi, Nigeria where she has worked since 2000.

In 2015, she enrolled as a doctoral student of Sanitary and Environmental Engineering, Department of Civil Engineering, Universiti Putra, Malaysia. Her research area is Environmental Engineering; Solid waste management, Landfill management and Wastewater treatment. This thesis focused on livestock wastewater treatment by adsorption and biodegradation using landfilled solid wastes. She has several published works and professional affiliations including NSE, ASCE and COREN. She is married and blessed with children.

LIST OF PUBLICATIONS

- Nik Daud, N.N., Anijiofor S.C., and Ahsan A., (2015). An overview of treatment efficiencies for various wastewaters using aged refuse based bioreactors. *Journal of Desalination and Water Purification*, 1(1): 12-20. [Google scholar](#).
- Nik Daud, N.N and Anijiofor S.C., (2017). Livestock wastewater generation and farm management: The gap Analysis. *ISHS Acta Horticulturae*, 1152, (36): 265-272. [Scopus](#)
- Anijiofor, S.C., Nik Daud, N.N., Idrus S and Ahsan A., (2017). Aged refuse characterization as resource for wastewater treatment and landfill remediation. *International Journal of Waste Resources*, 17, 269. [Google scholar](#)
- Nik Daud, N.N. and Anijiofor, S.C., (2018). Chicken slaughterhouse wastewater disposal: The challenges ahead. *Asian Journal of Agriculture and Biology*, Special issue, 42-45. [Scopus](#)
- Anijiofor, S.C., Nik Daud, N.N., Idrus S and Che Man, H., (2018). Recycling of fishpond wastewater by adsorption of pollutants using aged refuse as an alternative low-cost adsorbent. *Sustainable Environment Research*, <http://doi.org/10.1016/j.serj.2018.05.005> (online) [Scopus](#)
- Anijiofor, S.C., Nik Daud, N.N., Idrus S and Che Man, H. (2018). Material recovery potentials for landfilled solid wastes for farmwater recovery and reuse. *International Journal of Environmental Research and Health*. (Submitted) [ISI](#)
- Anijiofor, S.C., Che Man, H., Nik Daud, N.N., and Idrus S. (2018). Molecular diversity and compositional analysis of microbiota in aged refuse revealed by amplicon sequencing. *Applied Microbiology and Biotechnology*. (Submitted) [ISI](#)
- Anijiofor, S.C., Nik Daud, N.N., Idrus S and Ahsan A., (2017). Adsorption of COD and BOD from chicken slaughterhouse wastewater using stabilized solid waste materials. (Conference paper), GCEC 2017.
- Anijiofor, S.C. and Nik Daud, N.N., (2017). Geotechnical properties of closed landfill materials for recycling purposes. In proceedings of the fourth GEGEU International Research Seminar, pp. 30-36.
- Anijiofor, S.C. and Nik Daud, N. (2018). Adsorption-desorption characteristics of landfill soil. In proceedings of the fifth GEGEU International Research Seminar, pp. 156-163.
- Anijiofor, S.C., Nik Daud, N.N., Idrus S and Che Man, H. Influence of operational conditions on pollutant adsorption efficiency from livestock wastewater. (Upcoming, November 7th – 9th, 2018). (Conference paper) ICEC 2018.

International Conferences/Seminar

International Conference on Environmental and Occupational Health (ICEOH 2016), 11th – 13th April, 2016, held at Putrajaya Marriott Hotel, Malaysia. (Presenter).

The 3rd International Conference on Food and Agricultural Engineering (CAFEi 2016), 23rd – 25th August, 2016, held at Seri Pacific Hotel, Kuala Lumpur, Malaysia. (Presenter).

Global Civil Engineering Conference (GCEC 2017), 26th – 28th July, 2017, held at Seri Pacific Hotel, Kuala Lumpur, Malaysia. (Presenter).

4th GEGEU International Research Seminar 2017 (GEGEU 17), 26th October, 2017, held at Palm Garden Hotel, IOI, Resort City, Putrajaya, Malaysia. (Presenter).

5th GEGEU International Research Seminar 2018 (GEGEU 18), 30th October, 2018, Sherwood Hotel, Bangi. (Presenter).

1st International Civil Engineering Conference (ICEC) 2018. 7th – 9th November 2018, at the Federal University of Technology, Minna, Niger State, Nigeria. (Upcoming) (Presenter).



UNIVERSITI PUTRA MALAYSIA

STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT

ACADEMIC SESSION : _____

TITLE OF THESIS / PROJECT REPORT :

ADSORPTION AND BIODEGRADATION OF POLLUTANTS FROM LIVESTOCK
WASTEWATER BY AGED REFUSE BIOREACTOR

NAME OF STUDENT: ANIJIOFOR SANDRA CHINENYENWA

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

1. This thesis/project report is the property of Universiti Putra Malaysia.
2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

*Please tick (✓)

CONFIDENTIAL

(Contain confidential information under Official Secret Act 1972).

RESTRICTED

(Contains restricted information as specified by the organization/institution where research was done).

OPEN ACCESS

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :

PATENT

Embargo from _____ until _____
(date) (date)

Approved by:

(Signature of Student)
New IC No/ Passport No.:

(Signature of Chairman of Supervisory Committee)
Name:

Date :

Date :

[Note : If the thesis is CONFIDENTIAL or RESTRICTED, please attach with the letter from the organization/institution with period and reasons for confidentially or restricted.]