

**PRODUCTION OF ANTI-FUNGAL AGENT BY  
*SCHIZOPHYLLUM COMMUNE* AGAINST WOOD-  
DEGRADING FUNGI OF RUBBERWOOD**

**TEOH YI PENG @ TENG YI PENG**

**UNIVERSITI SAINS MALAYSIA  
2014**

**PRODUCTION OF ANTI-FUNGAL AGENT BY  
*SCHIZOPHYLLUM COMMUNE* AGAINST WOOD-  
DEGRADING FUNGI OF RUBBERWOOD**

**by**

**TEOH YI PENG @ TENG YI PENG**

**Thesis submitted in fulfillment of the requirements for  
the degree of Doctor of Philosophy**

**FEBRUARY 2014**

## ACKNOWLEDGEMENT

First of all, I would like to express my deepest gratitude to my beloved parents, Teng Ah Ba and Kee Mooi Choo for their endless love, and tolerance. Not to forget my sister, brother, and loved one, Zhong Xian for their persevering support, encouragement and unconditional support all this while.

I am greatly indebted to my dedicated supervisor, Assoc. Prof. Dr. Mashitah Mat Don for her support, guidance, encouragement, advice, and also generosity in sharing knowledge during period of my PhD degree. Special thanks for the willingness to spare her time and energy in correcting my paper and thesis in the midst of her business and unhealthiness. Sincere thanks also to my site-supervisor, Dr. Salmiah Ujang for her friendly help and support without any reluctance.

Not forgetting to thank the dean of School of Chemical Engineering (USM), Prof. Dr. Azlina and technical staff especially to Ms. Yusnadia, Mr. Shamsul, Mr. Roqib, and Ms. Latifah. This project would have never been completed without their valuable support and advice during period of my studies. Furthermore, I also wish to acknowledge to NSF scheme for the financial support.

Last but not least, I would like to thank my dear friends Stephanie, Kamila, Kak Yus, Kiew Ling, and Peck Loo that support behind me and give me advices and suggestions to conduct a proper experiment throughout the studies. To all the people, who have helped me throughout my PhD research, directly or indirectly; your contribution shall not be forgotten. Thank you very much!!!

Teoh Yi Peng

February 2014

## TABLE OF CONTENT

	<b>Page</b>
ACKNOWLEDGEMENTS	i
TABLE OF CONTENT	ii
LIST OF TABLES	xi
LIST OF FIGURES	xv
LIST OF PLATES	xix
LIST OF ABBREVIATIONS	xx
LIST OF SYMBOLS	xxiii
ABSTRAK	xxv
ABSTRACT	xxviii
<b>CHAPTER 1 – INTRODUCTION</b>	
1.1 Research background	1
1.2 Problem statement	9
1.3 Research objectives	13
1.4 Scope of study	13
1.5 Organization of the thesis	15
<b>CHAPTER 2 – LITERATURE REVIEW</b>	
2.1 Development of rubberwood in Malaysia	17
2.1.1 Rubber plantation revenue	17
2.1.2 Potential characteristics of rubberwood	20

2.1.3 Rubberwood-based industry	23
2.1.4 Wood-degrading fungi of rubberwood	26
2.1.5 Rubberwood preservation method	27
2.2 Higher fungi	35
2.2.1 Growth of higher fungi	36
2.2.2 <i>Schizophyllum commune</i>	38
2.3 Antifungal agent	39
2.3.1 Antifungal activity of flavonoids	43
2.3.2 Analysis of antifungal activity using antimicrobial susceptibility method (ASM)	44
2.4 Extraction process of bioactive compounds from natural resources	45
2.4.1 Extraction methods used for bioactive compounds	45
2.4.2 Choice of solvents	47
2.5 Fungal growth via fermentation process	49
2.5.1 Effect of different parameters	50
2.5.1 (a) Effect of media composition	50
2.5.1 (b) Effect of physical condition	53
2.5.2 Types and design of bioreactor	56
2.5.2 (a) Bubble column bioreactor	57
2.5.2 (b) Oxygen transfer study	59
2.6 Optimization of fermentation process	61
2.6.1 One-factor-at-a-time (OFAT) method	61
2.6.2 Design of experiment (DoE)	62

2.6.2 (a) Plackett-Burman design (PBD)	63
2.6.3 (b) Response surface methodology (RSM)	63
2.6.4 (c) Box-Behnken design (BBD)	64
2.6.3 Artificial intelligence (AI)	65
2.6.4 Evolutionary algorithms (EAs)	66
2.7 Summary	67

### **CHAPTER 3 – MATERIALS AND METHODS**

3.1 Chemicals and equipment used	68
3.2 Process methodology flow chart	69
3.3 Fungal strain used	71
3.4 Mycelia suspension preparation	71
3.5 Shake flask cultivation condition	71
3.6 Extraction of antifungal agent from biomass	72
3.7 Screening of antifungal agent from selected wood-degrading fungi	72
3.7.1 Wood-degrading fungi used	72
3.7.2 Fermentation and extraction of antifungal agent	72
3.8 Optimization of media composition on <i>Schizophyllum commune</i> growth in shake flask culture	73
3.8.1 Plackett-Burman design (PBD)	73
3.8.2 One-factor-at-a-time (OFAT) method	75
3.8.3 Response surface methodology (RSM)	75
3.9 Optimization of physical conditions on <i>Schizophyllum commune</i> growth in	

shake flask culture	76
3.10 Optimization of extraction parameters for the production of antifungal agent from <i>Schizophyllum commune</i> biomass	77
3.10.1 Verification of the models	78
3.11 Selected empirical model on the extraction kinetics	79
3.11.1 Parabolic diffusion model	79
3.11.2 Power law model	80
3.11.3 Peleg's model	81
3.11.4 Elovich's model	81
3.11.5 Model validation	82
3.12 Bubble column bioreactor	82
3.13 Selected empirical model on fermentation kinetics	85
3.13.1 Microbial growth kinetics	86
3.13.1 (a) Malthusian model	86
3.13.1 (b) Logistic model	86
3.13.1 (c) Modified Logistic model	87
3.13.1 (d) Chavez-Parga's Modified Logistic (CPML) model	88
3.13.1 (e) Combined Continuous Logistic and Fermi (CCLF) model	89
3.13.1 (f) Kono and Asai model	90
3.13.2 Product formation kinetics	91
3.13.2 (a) Logistic incorporated Luedeking-Piret (LLP) model	92
3.13.2 (b) Modified Logistic incorporated Luedeking-Piret (MLLP) model	93

3.13.2 (c) Chavez-Parga's Modified Logistic incorporated Luedeking-Piret (CMLLP) model	93
3.13.2 (d) Luedeking-Piret with Time Delay (LPTD) model	93
3.13.2 (e) Logistic incorporated Zhang's Modified Luedeking-Piret (LZMLP) model	94
3.13.3 Substrate utilization kinetics	95
3.13.3 (a) Logistic incorporated Modified Luedeking-Piret (LMLP) model	96
3.13.3 (b) Modified Logistic incorporated Modified Luedeking-Piret (MLMLP) model	96
3.13.3 (c) Combined Continuous Logistic and Fermi incorporated Modified Luedeking-Piret (CCLFMLP) model	97
3.13.3 (d) Logistic incorporated Zhang's Modified Luedeking-Piret (LZMLP) model	98
3.13.4 Substrate inhibition kinetics	99
3.13.4 (a) Monod model	99
3.13.4 (b) Noncompetitive model	100
3.13.4 (c) Haldane model	100
3.14.3 (d) Mulchandani model	101
3.14 Analytical method	101
3.14.1 Test for antifungal activity	101
3.14.1 (a) Poison food technique	101
3.14.1 (b) Broth microdilution assay	102

3.14.2 Determination of bioactive compounds	103
3.14.2 (a) Analysis using gas chromatography-mass spectrometry (GC-MS)	103
3.14.2 (b) Analysis using UV-visible spectrophotometer for determination of DDMP	104
3.14.2 (c) Analysis using high performance liquid chromatograph (HPLC) for determination of DDMP	104
3.14.3 Determination of total flavonoid content (TFC)	105
3.14.4 Determination of biomass concentration	105
3.14.5 Determination of glucose concentration	106
3.14.6 Determination of volumetric oxygen transfer coefficient	106
3.14.7 Effectiveness of antifungal agent produced onto the rubberwood block panel	107
3.14.7 (a) Treatment of rubberwood block panel	107
3.14.7 (b) Evaluation of the test	108

## **CHAPTER 4 – RESULTS AND DISCUSSION**

4.1 Screening of antifungal producing fungus	110
4.1.1 Antifungal activity using food poison technique	110
4.1.2 Antifungal activity using broth microdilution assay	114
4.1.3 Analysis of bioactive compounds from biomass extract of <i>Schizophyllum commune</i>	119
4.1.3 (a) Analysis using gas chromatography-mass spectrometry	

(GC-MS)	119
4.1.3 (b) Analysis using high performance liquid chromatograph	
(HPLC)	124
4.2 Optimization of media composition on growth of <i>Schizophyllum commune</i>	
in shake flask culture	125
4.2.1 Screening of media composition using Plackett-Burman design	
(PBD)	125
4.2.2 Selection of media composition using one-factor-at-a-time (OFAT)	
method	128
4.2.3 Optimization of media composition on growth of <i>Schizophyllum</i>	
<i>commune</i> using Response Surface Methodology (RSM)	131
4.2.4 Model validation	136
4.3 Optimization of physical conditions on growth of <i>Schizophyllum commune</i>	
in shake flask culture	136
4.3.1 Selection of physical conditions using one-factor-at-a-time (OFAT)	
method	136
4.3.2 Optimization of physical conditions for growth of <i>Schizophyllum</i>	
<i>commune</i> using Response Surface Methodology (RSM)	141
4.3.3 Model verification	145
4.4 Optimization of extraction parameters for production of antifungal agent	146
4.4.1 Selection of extraction parameters using one-factor-at-a-time (OFAT)	
method	146
4.4.1 (a) Effect of methanol concentration	146

<i>Extraction yield</i>	146
<i>Antifungal agent production</i>	147
<i>Effect of Schizophyllum commune biomass extract against wood-degrading fungi</i>	148
4.4.1 (b) Effect of extraction temperature	149
<i>Extraction yield</i>	149
<i>Antifungal agent production</i>	150
4.4.1 (c) Effect of mixing rate	151
<i>Extraction yield</i>	151
<i>Antifungal agent production</i>	151
4.4.2 Optimization of extraction process using Response Surface Methodology (RSM)	153
4.4.3 Model verification	162
4.5 Selected empirical kinetic models for the extraction of antifungal agent from <i>Schizophyllum commune</i> biomass	162
4.6 Batch fermentation of <i>Schizophyllum commune</i> in bubble column bioreactor	168
4.6.1 Effect of aeration rate	168
4.6.2 Effect of temperature	173
4.6.3 Effect of initial glucose concentration	177
4.7 Volumetric oxygen transfer coefficient ( $k_{LA}$ ) of <i>Schizophyllum commune</i> in a bubble column bioreactor	181
4.8 Kinetics and modeling of growth, antifungal agent production, substrate utilization, and substrate inhibition by <i>Schizophyllum commune</i> in a bubble	

column bioreactor	185
4.8.1 Selected empirical model for fermentation kinetics	185
4.8.2 Model analysis	186
4.8.2 (a) Microbial growth kinetics	186
4.8.2 (b) Product formation kinetics	191
4.8.2 (c) Substrate utilization kinetics	198
4.8.2 (d) Substrate inhibition kinetics	203
4.8.2 (e) Model validation	205
4.9 Effectiveness of antifungal agent onto the rubberwood block panel	206
<b>CHAPTER 5 – CONCLUSIONS AND RECOMMENDATIONS</b>	
5.1 Conclusions	209
5.2 Future recommendations	213
<b>REFERENCES</b>	214
<b>APPENDICES</b>	
Appendix A: Standard calibration curve	240
Appendix B: Derivation of empirical model for fermentation kinetics	243
Appendix C: Simulations of experimental data using Polymath	250
<b>LIST OF PUBLICATIONS</b>	251

## LIST OF TABLES

		<b>Page</b>
Table 2.1	Total rubber trees planted in Malaysia from 2001 to 2010	19
Table 2.2	Planted area of rubber trees in Peninsular Malaysia, Sabah, and Sarawak from 2001 to 2010	19
Table 2.3	Physical and mechanical properties of rubberwood	21
Table 2.4	Compressive strength properties of rubberwood clone PB 260 at different ages	22
Table 2.5	Export value contribution of the Malaysian rubberwood subsector from 2005 to 2009	24
Table 2.6	Projected industrial demand and availability of rubberwood for primary processing industries in Malaysia from 1995 to 2008	26
Table 2.7	Percentage weight loss of rubberwood test blocks by a range of wood-degrading fungi over 10 weeks	28
Table 2.8	Chemical preservation of wood from deterioration	29
Table 2.9	Weight loss in test blocks of rubberwood over 4 weeks	30
Table 2.10	Effective dose at 50% inhibition (ED <sub>50</sub> ) for pyrolytic oil on different fungi	32
Table 2.11	Phylogeny of fungi	36
Table 2.12	Structural features, activities and proposed mechanism of action of various phytochemicals from natural products	40
Table 2.13	Functions related to macro- and microelements used in the cultivation of microorganism	50
Table 2.14	Bioreactor configurations and their applications	57
Table 2.15	Biochemical applications of bubble column bioreactor	59
Table 2.16	Statistical tools used in bioprocesses	63
Table 3.1	List of chemicals used in this study	68

Table 3.2	List of equipments used in this study	69
Table 3.3	List of locally isolated wild fungal strains used in this study	71
Table 3.4	Plackett-Burman experimental design matrix for screening the media composition for growth of <i>Schizophyllum commune</i>	74
Table 3.5	Variables and their levels used for Box-Behnken design for optimization of media composition	76
Table 3.6	Variables and their levels used for Box-Behnken design for optimization of physical conditions	77
Table 3.7	Variables and their levels used for Box-Behnken design for optimization of antifungal agent extraction parameters	78
Table 3.8	Patterns of the growth with regard to $r$ value	88
Table 3.9	Product formation patterns as indicated by $\alpha$ and $\beta$ values	92
Table 4.1	Radial growth inhibition of biomass extracts against wood-degrading fungi	111
Table 4.2	Antifungal activities from biomass extracts of selected wood-degrading fungi among themselves	115
Table 4.3	Chemical compounds identified in the <i>Schizophyllum commune</i> biomass extract via GC-MS analysis	121
Table 4.4	Plackett-Burman experimental design matrix for screening the media composition for growth of <i>Schizophyllum commune</i> , with biomass as a response	126
Table 4.5	Analysis of variances (ANOVA) for the Plackett-Burman factorial model	127
Table 4.6	Box-Behnken design based on three-level media composition, with biomass as a response	132
Table 4.7	Analysis of variances (ANOVA) for quadratic regression model of biomass produced by <i>Schizophyllum commune</i> in shake flask culture	133
Table 4.8	Validation of the data and constructed model	136
Table 4.9	Box-Behnken design matrix based on three-level physical conditions, with biomass as a response	142

Table 4.10	Analysis of variance (ANOVA) of response surface quadratic model of <i>Schizophyllum commune</i> growth	143
Table 4.11	Validation of the data and model constructed	145
Table 4.12	Antifungal activity from <i>Schizophyllum commune</i> biomass extract at different methanol concentration against selected wood-degrading fungi	149
Table 4.13	Experimental design for three-level, three variables box-behnken design, and the extraction yield, TFC, and DDMP represented as responses	153
Table 4.14	Analysis of variances (ANOVA) for quadratic regression model of extraction yield of <i>Schizophyllum commune</i> biomass	154
Table 4.15	Analysis of variances (ANOVA) for quadratic regression model of TFC of <i>Schizophyllum commune</i> biomass	155
Table 4.16	Analysis of variances (ANOVA) for quadratic regression model of DDMP of <i>Schizophyllum commune</i> biomass	155
Table 4.17	Validation of the data and model constructed	162
Table 4.18	Selected empirical extraction kinetic models in linearized forms	163
Table 4.19	Summary of model parameters and statistical correlation values for each empirical extraction kinetic model	165
Table 4.20	Effect of aeration rate on the oxygen uptake rate (OUR), volumetric oxygen transfer coefficient ( $k_La$ ), and oxygen transfer rate (OTR) during cultivation of <i>Schizophyllum commune</i> in a bubble column bioreactor	183
Table 4.21	Estimated parameters for the growth of <i>Schizophyllum commune</i> in a bubble column bioreactor at different initial glucose concentration based on Logistic, Modified Logistic, Chavez-Parga's Modified Logistic, Combined Continuous Logistic and Fermi, and Kono and Asai model	187
Table 4.22	Estimated parameters for the production of TFC by <i>Schizophyllum commune</i> in a bubble column bioreactor at different initial glucose concentration based on Logistic incorporated Luedeking-Piret, Modified Logistic incorporated Luedeking-Piret, Chavez-Parga's Modified Logistic incorporated Luedeking-Piret, Luedeking-Piret with Time Delay, Logistic	192

incorporated Zhang's Modified Luedeking-Piret model

Table 4.23	Estimated parameters for the production of DDMP by <i>Schizophyllum commune</i> in a bubble column bioreactor at different initial glucose concentration based on Logistic incorporated Luedeking-Piret, Modified Logistic incorporated Luedeking-Piret, Chavez-Parga's Modified Logistic incorporated Luedeking-Piret, Luedeking-Piret with Time Delay, Logistic incorporated Zhang's Modified Luedeking-Piret model	193
Table 4.24	Estimated parameters for glucose utilization by <i>Schizophyllum commune</i> in a bubble column bioreactor at different initial glucose concentration based on Logistic incorporated Modified Luedeking-Piret, Modified Logistic incorporated Modified Luedeking-Piret, Combined Continuous Logistic and Fermi incorporated Modified Luedeking-Piret, and Logistic incorporated Zhang's Modified Luedeking-Piret model	199
Table 4.25	Estimated kinetic parameters from the different growth models	204
Table 4.26	Antifungal activity scoring of <i>Schizophyllum commune</i> biomass extracts towards <i>Pycnoporus sanguineus</i> after 3 weeks of incubation	207

## LIST OF FIGURES

		<b>Page</b>
Figure 2.1	Zones of growth in fungal pellets	38
Figure 2.2	Plot of growth rate versus temperature for microbes in different temperature classes	55
Figure 3.1	Process flow diagram of the methods used in this study	70
Figure 3.2	Schematic diagram of 2 l bubble column bioreactor	84
Figure 4.1	GC-MS chromatogram of the <i>Schizophyllum commune</i> biomass extract	120
Figure 4.2	Mass spectrum for (a) biomass extract of <i>Schizophyllum commune</i> , and (b) triacetin (a standard) with its structure from the NIST library	122
Figure 4.3	Mass spectrum for (a) biomass extract of <i>Schizophyllum commune</i> , and (b) DDMP (a standard) with its structure from the NIST library	123
Figure 4.4	HPLC chromatogram for (a) a purified DDMP from a sample (RT: 3.886 min), and (b) a standard DDMP (RT: 3.904 min)	124
Figure 4.5	Pareto plot for Plackett-Burman parameter estimates for ten medium components	128
Figure 4.6	Effect of yeast extract concentration on growth of <i>Schizophyllum commune</i> in shake flask culture	129
Figure 4.7	Effect of glucose concentration on growth of <i>Schizophyllum commune</i> in shake flask culture	130
Figure 4.8	Effect of $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ concentration on growth of <i>Schizophyllum commune</i> in shake flask culture	131
Figure 4.9	(a) A three-dimensional plot showing the interaction between yeast extract and glucose at 0.50 g/l $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ on biomass. (b) The three-dimensional plot showing the interaction between yeast extract and $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ at 40 g/l on biomass. (c) The three-dimensional plot showing the interaction between glucose and $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ at 20 g/l yeast extract on biomass.	135

Figure 4.10	Effect of initial pH on growth of <i>Schizophyllum commune</i> in shake flask culture	137
Figure 4.11	Effect of incubation temperature on growth of <i>Schizophyllum commune</i> in shake flask culture	138
Figure 4.12	Effect of agitation on growth of <i>Schizophyllum commune</i> in shake flask culture	141
Figure 4.13	(a) The 3D plot showing the interaction between pH and incubation temperature at 150 rpm on biomass. (b) The 3D plot showing the interaction between pH and agitation at 30 °C on biomass. (c) The 3C plot showing the interaction between incubation temperature and agitation at pH 6.5 on biomass.	144
Figure 4.14	Effect of methanol concentration on the extraction yield of <i>Schizophyllum commune</i> biomass	147
Figure 4.15	Effect of methanol concentration on the extraction of TFC and DDMP of <i>Schizophyllum commune</i> biomass	148
Figure 4.16	Effect of extraction temperature on the extraction yield of <i>Schizophyllum commune</i> biomass	150
Figure 4.17	Effect of extraction temperature on the extraction of TFC and DDMP of <i>Schizophyllum commune</i> biomass	151
Figure 4.18	Effect of mixing rate on the extraction yield of <i>Schizophyllum commune</i> biomass	152
Figure 4.19	Effect of mixing rate on the extraction of TFC and DDMP of <i>Schizophyllum commune</i> biomass	152
Figure 4.20	(a) A three-dimensional surface plot of extraction yield as a function of methanol concentration and extraction temperature. (b) A three-dimensional surface plot of extraction yield as a function of methanol concentration and mixing rate. (c) A three-dimensional surface plot of extraction yield as a function of extraction temperature and mixing rate.	157
Figure 4.21	(a) A three-dimensional surface plot of TFC as a function of methanol concentration and extraction temperature. (b) A three-dimensional surface plot of TFC as a function of methanol concentration and mixing rate. (c) A three-dimensional surface plot of TFC as a function of extraction temperature and mixing rate.	159

Figure 4.22	(a) A three-dimensional surface plot of DDMP as a function of methanol concentration and extraction temperature. (b) A three-dimensional surface plot of DDMP as a function of methanol concentration and mixing rate. (c) A three-dimensional surface plot of DDMP as a function of extraction temperature and mixing rate.	161
Figure 4.23	Extraction yield versus extraction time profile for <i>Schizophyllum commune</i> biomass under the optimized condition (70.75 % (v/v) methanol, temperature of 29 °C, mixing rate 145 rpm)	163
Figure 4.24	Total flavonoid content (TFC) versus extraction time profile for <i>Schizophyllum commune</i> biomass under the optimized condition (70.75 % (v/v) methanol, temperature of 29 °C, mixing rate 145 rpm)	164
Figure 4.25	DDMP versus extraction time profile for <i>Schizophyllum commune</i> biomass under the optimized condition (70.75 % (v/v) methanol, temperature of 29 °C, mixing rate 145 rpm)	164
Figure 4.26	Comparison between the experimental (symbol) and simulated (line) data for the extraction of antifungal agent under optimized condition based on the linearized form of kinetic equations: (a) Parabolic diffusion model, (b) Power law model, (c) Peleg's model, and (d) Elovich's model	167
Figure 4.27	Effect of aeration rate on the (a) growth, (b) TFC, and (c) DDMP production by <i>Schizophyllum commune</i> in a bubble column bioreactor	171
Figure 4.28	Effect of aeration rate on (a) glucose consumption and (b) partial dissolved oxygen by <i>Schizophyllum commune</i> in a bubble column bioreactor	173
Figure 4.29	Effect of temperature on the (a) growth, (b) TFC, and (c) DDMP production by <i>Schizophyllum commune</i> in a bubble column bioreactor	175
Figure 4.30	Effect of temperature on (a) glucose consumption and (b) partial dissolved oxygen by <i>Schizophyllum commune</i> in a bubble column bioreactor	177
Figure 4.31	Effect of initial glucose concentration on the (a) growth, (b) TFC, and (c) DDMP production by <i>Schizophyllum commune</i> in a bubble column bioreactor	179

Figure 4.32	Effect of initial glucose concentration on (a) glucose consumption and (b) partial dissolved oxygen by <i>Schizophyllum commune</i> in a bubble column bioreactor	181
Figure 4.33	Effect of $k_{LA}$ on the (a) growth and (b) TFC, and DDMP production by <i>Schizophyllum commune</i> in a bubble column bioreactor	184
Figure 4.34	Growth profiles of <i>Schizophyllum commune</i> at different initial glucose concentration using a (a) Logistic model, (b) Modified Logistic model, and (c) Chavez-Parga's Modified Logistic model	188
Figure 4.35	Growth profiles of <i>Schizophyllum commune</i> at different initial glucose concentration using Combined Continuous Logistic and Fermi model	189
Figure 4.36	Growth profiles of <i>Schizophyllum commune</i> at different initial glucose concentration using Kono and Asai model	190
Figure 4.37	Profiles of TFC production by <i>Schizophyllum commune</i> at different initial glucose concentration using (a) Logistic incorporated Luedeking-Piret, (b) Modified Logistic incorporated Luedeking-Piret, and (c) Chavez-Parga's Modified Logistic incorporated Luedeking-Piret model	194
Figure 4.38	Profiles of DDMP production by <i>Schizophyllum commune</i> at different initial glucose concentration using (a) Logistic incorporated Luedeking-Piret, (b) Modified Logistic incorporated Luedeking-Piret, and (c) Chavez-Parga's Modified Logistic incorporated Luedeking-Piret model	195
Figure 4.39	Profiles of (a) TFC and (b) DDMP production by <i>Schizophyllum commune</i> at different initial glucose concentration using Leudeking-Piret with Time Delay model	196
Figure 4.40	Profiles of (a) TFC and (b) DDMP production by <i>Schizophyllum commune</i> at different initial glucose concentration using Logistic incorporated Zhang's Modified Luedeking-Piret model	197
Figure 4.41	Profiles of glucose utilization by <i>Schizophyllum commune</i> at different initial glucose concentration using a (a) Logistic incorporated Modified Luedeking-Piret model, (b) Modified Logistic incorporated Modified Luedeking-Piret model	200
Figure 4.42	Profiles of glucose utilization by <i>Schizophyllum commune</i> at different initial glucose concentration using Combined	201

Continuous Logistic and Fermi incorporated Modified Luedeking-Piret model

Figure 4.43	Profiles of glucose utilization by <i>Schizophyllum commune</i> at different initial glucose concentration using Logistic incorporated Zhang's Modified Luedeking-Piret model	202
Figure 4.44	Comparison of specific growth rate for the experimental and simulated data from substrate inhibition models at different initial glucose concentration	205

**LIST OF PLATES**

		<b>Page</b>
Plate 3.1	Experimental setup of bubble column bioreactor with Biostat-B control panel board	85
Plate 4.1	Growth inhibition of (a) <i>Lentinus sajor-caju</i> and (b) <i>Pycnoporus sanguineus</i> by the biomass extract of <i>Schizophyllum commune</i> . C indicated as control (a plate that contained only pure methanol and MEA); the others are biomass extract at concentration of 1, 3, and 5 $\mu\text{g}/\mu\text{l}$	113
Plate 4.2	<i>Schizophyllum commune</i> growth morphology during submerged cultivation under different shaken condition: (a) 0 rpm, (b) 50 rpm, (c) 150 rpm, and (d) 250 rpm	140
Plate 4.3	Treatment of rubberwood using five set concentration of <i>Schizophyllum commune</i> biomass extract for (a) 0 day (control), (b) 7 days, (c) 21 days, and (d) 30 days	208

## LIST OF ABBREVIATIONS

AI	Artificial intelligence
ANN	Artificial neural network
ANOVA	Analysis of variance
ASM	Antimicrobial susceptibility method
BB	Boric acid borax
BBD	Box-Behnken design
C:N	Carbon : Nitrogen
CCA	Copper-chromium-arsenic
CCD	Central Composite design
CCLF	Combined Continuous Logistic and Fermi
CCLFMLP	Combined Continuous Logistic and Fermi incorporated Modified Luedeking-Piret
CMLLP	Chavez-Parga's Modified Logistic incorporated Luedeking-Piret
CPML	Chavez-Parga's Modified Logistic
DDMP	4H-pyran-4-one, 2,3-dihydro-3,5-dihydroxy-6-methyl-
DMSO	Dimethyl sulfoxide
DNS	Dintrosalicylic acid
DO	Dissolved oxygen
DoE	Design of experiment
EAs	Evolutionary algorithms
ED <sub>50</sub>	Effective dose at 50% inhibition

EPS	Exopolysaccharides
FL	Fuzzy logic
FRIM	Forest Research Institute Malaysia
GA	Genetic algorithm
GC-MS	Gas chromatography-mass spectrometry
HPLC	High performance liquid chromatograph
ITA	Investment Tax Allowance
LLP	Logistic incorporated Luedeking-Piret
L-M	Levenberg-Marquardt
LMLP	Logistic incorporated Modified Luedeking-Piret
LPTD	Luedeking-Piret with Time Delay
LZMLP	Logistic incorporated Zhang's Modified Luedeking-Piret
MDF	Medium-density fiberboard
MEA	Malt extract agar
MIC	Minimum inhibitory concentration
MLLP	Modified Logistic incorporated Luedeking-Piret
MLMLP	Modified Logistic incorporated Modified Luedeking-Piret
MMLP	Monod incorporated Modified Luedeking-Piret
MOE	Modulus of elasticity
MOR	Modulus of rupture
MTT	3-(4,5-dimethylthylthiazolyl-2)-2,5-diphenyltetrazolium bromide
NAP	National Agricultural Policy
NIST	National Institute Standard and Technology

OD	Optical density
OFAT	One-factor-at-a-time
OPM	Oscillating pressure method
OTR	Oxygen transfer rate
OUR	Oxygen uptake rate
PBD	Plackett-Burman design
PIA	Promotion of Investment Act
pO <sub>2</sub>	Polarographic dissolved oxygen
PPO	Polyphenol oxidase
PS	Pioneer Status
RISDA	Rubber Industry Smallholders Development Authority
RMSD	Root mean square deviation
RRIM	Rubber Research Institute of Malaysia
RSM	Response surface methodology
TFC	Total flavonoid content

## LIST OF SYMBOLS

$A_i$	Extraction kinetic parameter related to parabolic diffusion model (1/min <sup>0.5</sup> )
$A_0$	Washing coefficient related to parabolic diffusion model (1/min <sup>0.5</sup> )
$A_1$	Diffusion rate constant related to parabolic diffusion model (1/min <sup>0.5</sup> )
$\alpha$	Coefficients represent the growth related term (g/g)
$B$	Parameter of the power law model incorporating the characteristics of the extraction system (1/min <sup>n</sup> )
$\beta$	Coefficients represent the non-growth related term (g/g.h)
$C^*$	Saturation dissolved oxygen concentration (mg/l)
$C_L$	Dissolved oxygen concentration (mg/l)
$C_{LSS}$	Dissolved oxygen concentration at steady state (mg/l)
$E_0, E_1$	Extraction kinetic parameters of Elovich's model
$k$	Kinetic parameter related to initial specific growth rate
$k_L a$	Volumetric oxygen transfer coefficient (1/s)
$K_1$	Peleg's rate constant (min.g/mg)
$K_2$	Peleg's capacity constant (g/mg)
$K_I$	Inhibition constant
$K_s$	Saturation constant (g/l)
$\mu$	Specific growth rate (1/h)
$\mu_F$	Decline rate constant (1/h)
$\mu_L$	Unrestricted growth rate (1/h)
$\mu_o$	Initial specific growth rate (1/h)

$\mu_{max}$	Maximum growth rate (1/h)
$m_s$	Maintenance coefficient (g/g.h)
$n$	Diffusion exponent of the power law model
$P$	Product concentration (g/l)
$P\ value$	Mean relative percentage deviation (%)
$r$	Index of the inhibitory effect
$R^2$	Linear correlation coefficient
$S$	Substrate concentration (g/l)
$S_m$	Critical inhibition concentration (g/l)
$t$	Time (h)
$t_c$	Time to reach 50% survival (h)
$T$	Temperature ( $^{\circ}$ C)
$X$	Biomass concentration (g/l)
$X_c$	Critical cell concentration (g/l)
$y$	Product concentration ( $\mu$ g/mg)
$Y_{P/S}$	Product yield coefficient (g/g)
$Y_{X/S}$	Biomass yield coefficient (g/g)
$\Delta$	Energy spilling-associated coefficient of substrate consumption
$\sigma$	Variance

## **PENGHASILAN AGEN ANTI-KULAT OLEH *SCHIZOPHYLLUM COMMUNE* KE ATAS KULAT PEREPUT KAYU BAGI POKOK GETAH**

### **ABSTRAK**

Kulit pereput kayu adalah merupakan suatu ancaman yang serius kepada kayu getah. Penggunaa pengawet kimia oleh industri pemuliharaan kayu getah perlulah berhati-hati kerana ia memberikan kesan kepada kesihatan dan masalah alam sekitar. Pengawalan secara biologi adalah merupakan cara alternatif untuk menyelesaikan masalah ini. Di dalam kajian ini, dua belas spesies kulit pereput kayu tempatan yang liar telah dipencil dan disaring akan keupayaannya untuk menghasilkan agen antikulat. Keputusan menunjukkan ekstrak metanol bagi biojisim *Schizophyllum commune* memberikan aktiviti antikulat yang tinggi diantara kulit-kulit yang diuji dengan kepekatan rencatan minimum (KMM) dalam julat dari 0.1 ke 5.0 µg/µl. Sebatian kimia yang terdapat di dalam ekstrak biojisim telah dianalisa melalui kromatografi gas-permeteran spektrum jisim (GC-MS) dan kromatografi cecair berprestasi tinggi (HPLC). 4H-pyran-4-one, 2,3-dihidro-3,5-dihidroksi-6-metil- (DDMP), satu pecahan flavonoid, telah didapati di dalam ekstrak biojisim. Strategi pengoptimuman berdasarkan kaedah satu-faktor-di-satu-masa (OFAT) dan statistik telah diguna untuk mengoptimumkan pertumbuhan *S. commune* di dalam kultur kelalang goncang. Berdasarkan rekabentuk “Plackett-Burman”, pembolehubah-pembolehubah seperti ekstrak yis, glukosa, dan MgSO<sub>4</sub>·7H<sub>2</sub>O memberikan kesan yang signifikan bagi pertumbuhan kulit ini. Nilai-nilai optimum bagi pembolehubah proses ini telah diperolehi menggunakan metodologi permukaan sambutan yang bergandingan dengan rekabentuk “Box-Behnken”. Bagi pengekstrakan agen antikulat, keadaan optimumnya ialah pada 70.75% metanol, 29 °C, dan 145 putaran/min. Kesemua kajian pengoptimuman telah disah dan didapati data eksperimen

adalah berpadanan dengan model-model terpilih dengan peratusan ralat kurang daripada 1%. Kinetik pengesktrakan juga telah dikaji dengan menggunakan model resapan “Parabolic”, model hukum Tenaga, model Pelag, dan model Elovich. Kesemua model adalah berpadanan dengan data eksperimen, dimana hukum Tenaga memberikan nilai  $R^2$  tertinggi dan RMSD yang terendah. Untuk mempertingkatkan penghasilan bagi biojisim, flavonoid total (TF), dan DDMP yang lebih tinggi, prestasi bagi 2 l bioreaktor turus gelembung telah dikaji. Keputusan menunjukkan penghasilan biojisim (32.38 g/l), TF (1.33  $\mu\text{g}$  QE/mg sampel), and DDMP (1.28  $\mu\text{g}$ /mg sampel) yang tertinggi telah diperolehi di dalam kultur yang tumbuh pada 30 °C. Lanjutan daripada itu, pekali pemindahan oksigen ( $k_{La}$ ) bagi *S. commune* juga telah dikaji untuk mengetahui keupayaan pemindahan oksigen di dalam bioreaktor dengan mengambil kira kesan kadar pengudaraan. Didapati bahawa biojisim dan penghasilan agen antikulat yang maximum adalah pada 4 l/min dengan nilai  $k_{La}$  0.04 1/s. Beberapa model tak-berstruktur bagi pertumbuhan, produk, penggunaan dan perencatan substrat bagi kulat ini telah dikaji pada kepekatan glukosa di julat 20-100 g/l. Di antara pelbagai model kinetik yang diuji, model Logistic untuk pertumbuhan mikrob, model “Logistic incorporated Zhang’s Modified Luedeking-Piret” untuk produk dan penggunaan substrat, serta model Mulchandani untuk perencatan substrat memberikan jangkaan kinetik fermentasi yang tepat dengan nilai  $R^2$  yang tinggi dan RMSD yang rendah. Keputusan juga menunjukkan penghasilan agen antikulat oleh *S. commune* dengan menggunakan glukosa sebagai substrat adalah perkaitan pertumbuhan-produk campuran dengan  $\alpha$  dan  $\beta \neq 0$ . Ekstrak biojisim yang terhasil kemudiannya telah tindakbalaskan ke atas blok kayu getah untuk menguji akan keberkesanannya. Keputusan menunjukkan ekstrak biojisim yang

mengandung agen antikulat, DDMP berkeupayaan merencat pertumbuhan kulat-kulat pereput kayu getah yang lain.

## **PRODUCTION OF ANTI-FUNGAL AGENT BY *SCHIZOPHYLLUM COMMUNE* AGAINST WOOD-DEGRADING FUNGI OF RUBBERWOOD**

### **ABSTRACT**

Wood-degrading fungi are serious threat to rubberwood. Chemical preservatives commonly used in rubberwood preserving industry become awareness as it give impact to health and environmental problem. Biological control may be used as an alternative method to solve this problem. In this study, twelve locally isolated wild strains of wood-degrading fungi were screened for their capability to produce antifungal agent. Results showed that methanol extract of *Schizophyllum commune* biomass provided the highest antifungal activity among the tested fungi with minimum inhibitory concentration (MIC) ranging from 0.1 to 5.0 µg/µl. Chemical compound presence in the biomass extract was analyzed via gas chromatography-mass spectrometry (GC-MS) and high performance liquid chromatograph (HPLC). It was found that 4H-pyran-4-one, 2,3-dihydro-3,5-dihydroxy-6-methyl- (DDMP), a flavonoid fraction, was presence in the biomass extract. Optimization strategy based on one-factor-at-a-time (OFTA) method and statistical tool were employed to optimize the growth of *S. commune* in shake flask culture. Based on Plackett-Burman design (PBD), the variables such as yeast extract, glucose and MgSO<sub>4</sub>·7H<sub>2</sub>O significantly affected the fungus growth. The optimal values of these process variables were determined using Response Surface Methodology (RSM) coupled with Box-Behnken design (BBD). For the extraction of antifungal agent, the optimum conditions were 70.75% (v/v) methanol, 29 °C, and 145 rpm. All optimization studies were verified and the experimental data fitted well to the selected models with error percentage less than 1%. The extraction kinetics was also investigated using the Parabolic diffusion model, Power law model, Peleg's model,

and Elovich's model. All empirical models gave a good fit to the experimental data, in which the Power law model gave the highest  $R^2$  and lowest RMSD values. To achieve higher production of biomass, total flavonoid (TF), and DDMP, the performance of a 2 l bubble column bioreactor was investigated. Results revealed that the highest production of biomass (35.11 g/l), TF (1.33  $\mu\text{g QE/mg sample}$ ), and DDMP (1.28  $\mu\text{g/mg sample}$ ) were achieved in culture grown at 30 °C. Furthermore, the oxygen transfer coefficient ( $k_{La}$ ) of *S. commune* was also studied to investigate the oxygen transfer capabilities in the bioreactor considering the effect of aeration rate. It was found that the maximal biomass and antifungal agent production was achieved at 4 l/min with  $k_{La}$  value of 0.04 1/s. Several unstructured models for growth, product formation, substrate utilization, and substrate inhibition of the tested fungus were studied for glucose concentration ranged 20-100 g/l. Among various kinetic models tested, the Logistic model for microbial growth, the Logistic incorporated Zhang's Modified Luedeking-Piret model for product formation and substrate utilization, and the Mulchandani model for substrate inhibition provided accurate approximation of the fermentation kinetics with high  $R^2$  and low RMSD values. The result also showed that antifungal agent production by *S. commune* using glucose as a substrate was mixed-growth product associated with  $\alpha$  and  $\beta \neq 0$ . The produced methanol extract of the biomass was then applied on the rubberwood block to investigate its effectiveness. Results showed that the biomass extract containing antifungal agent, DDMP, was able to inhibit the growth of other tested wood-degrading fungi of rubberwood.

# CHAPTER 1

## INTRODUCTION

### 1.1 Research background

Rubberwood (*Hevea brasiliensis*), a native of the Amazon valley of South America, was introduced to India in the latter half of the 19<sup>th</sup> century (Edwin and Muhamed Ashraf, 2006), and now is widely cultivated in mostly twenty countries of the world including Malaysia for natural rubber and wood panels production (Akhter, 2005).

Traditionally, rubberwood was a source of fuel, either in the form of firewood for the rural community or for the rubber sheet-curing and brick-making industries. It was also converted into charcoal for use in steel-making industry (Hoi, 1999; Hong, 1999; Hong and Sim, 1999; Hoi, 2002). Lew (1992) estimated that 67% of the total rubberwood consumed annually was used as fuelwood in Peninsular Malaysia before the development of the rubberwood industry. The processing of rubberwood in Malaysia began in the early 1970s (Ho and Roslan, 1999). It was firstly processed into block board cores and converted into chips for pulp and paper making (Mohd Nor, 1999). In the late 1970s, rubberwood was processed into sawn timber for export. As reported by Hong and Sim (1999), the export of rubberwood sawn timber in the year 1980–1995 increased more than tenfold in terms of volume and export values because rubberwood was used as a raw material in wood product manufacturing. The sawing process converted logs into sawn timber. In the process, undesirable defects such as knots, pith, and tapping marks are removed. At present, sawn rubberwood timber is widely used in the manufacture of furniture, doors, window frames,

moldings, novelty items, and household utility items, whereas rubberwood logs are used to produce veneers, which are usually applied in the manufacture of plywood, hardboard, and solid moldings (Hong and Sim, 1999; Mohd Nor, 1999; Rahim, 1999; Hoi, 2002; Zhao, 2008).

The Malaysian rubber industry is well-known internationally for its developed and progressive R&D programs that enabled the country to establish itself as the world leader in rubber production, processing, and manufacturing technologies. Recently, the planting of rubber trees solely for wood extraction has been certainly a viable investment for investors when fully integrated with downstream rubberwood processing and product manufacturing (Hong and Sim, 1999). Kadir (1998) pointed out that so far, rubberwood was merely considered a residue of the rubber industry and commanded a poor price in the open market. The true value of the wood manifested only after it has been processed into semi-finished or final products. The rubber tree has an advantage over many other timber species because it can be exploited for both timber and latex. However, in the case of trees grown only for wood, the return on investment was improved if the wood is offered at a price competitive to other timber species (Hong and Sim, 1999). With this motivation, several plantation companies, such as Golden Hope Plantations and Guthrie, have moved into downstream processing of medium-density fiberboard (MDF) to take advantage of the lucrative value-added profits (Kadir, 1998).

Anthony (1998) reported that the Malaysian furniture industry was still considered to be at an early stage of development. In fact, the successful achievements in the processing and utilization of rubberwood through the R&D

efforts of the Forest Research Institute Malaysia (FRIM) have provided the growth impetus for the industry to scale greater heights in the future. On the other hand, the Malaysian furniture industry played an important role at the international level since it was able to turn cheap and plentiful timber into a value-added product at a competitive price (Hong, 1995). This generated several arguments on the trend of increasing rubberwood costs and questions on the long-term sustainability of the whole rubber and rubberwood-based furniture industry. Exports of the furniture industry grew by leaps and bounds from a cottage industry of RM120 million in 1986 to more than RM2.8 billion in 1997. With this, it has been estimated that the export of Malaysian furniture had continued to increase between 10% and 15% annually to reach an annual export turnover of RM4.1 billion in the future (Anthony, 1998). For example, the curved furniture components, such as chair backs and legs, were commonly made by laminating veneers, which raised the demand of rubberwood veneers and thus prompted the furniture industry to produce its own rubberwood veneers (Ho and Roslan, 1999). The main features of this industry that have emerged over the past decade are the remarkable upsurge in production output, the utilization of advanced technology, and the continuous upgrading of the sector. These developments indicated a prospectively vibrant sector of the industry. In 2008, export of furniture shot up to RM 8.7 billion, of which 80% was rubberwood-based furniture (Gan, 2009). On the other hand, the situation on the ground was complicated by several challenges ahead.

The biodegradation problem is one of the main reasons why rubberwood is less attractive for wood processing industries and was almost neglected in the past, although it was abundant in supply and easily available (Killmann, 2001; Hong,

1995). The high carbohydrate (sugar and starch) reserved deposited in the parenchyma is the major factors governing the high decay susceptibility of rubberwood (Salmiah, 1997). Zaidon *et al.* (2003) stated that these rubberwood products are generally less susceptible to biodeterioration agents than solid wood unless they are used in situations where exposure to moisture or risk of deterioration is likely.

Wood-degrading fungi that cause severe breakdown of wood are characterized either as brown rot and white rot (generally caused by Basidiomycetes) fungi or as soft rot (caused by Ascomycetes and Fungi Imperfecti) fungi (Hong *et al.*, 1999). Wong (1988) showed that the susceptibility of rubberwood to the three major types of wood rot fungi is in the following order of severity, in which the substrate mass loss due to soft rot (*Chaetomium globosum*) > white rot (*Pycnoporus sanguineus*) > brown rot (*Tyromyces palustris*). Salmiah (1997) stated that the capacity of both white rot and brown rot fungi to decompose rubberwood is reduced compared with the effect on temperate timbers (e.g., sweetgum and southern yellow pine). This might be because many tropical woods contain a higher proportion of tannins and phenolic compounds that have better fungistatic effects compared with temperate woods. As such, rubberwood appeared to be the most susceptible to soft rot decay compared with other nondurables such as punggai (*Coelostegia griffi thii*), jelutong (*Dyera costulata*), and kayu arang (*Diospyros* spp.). However, against the white rot fungus *Coriolus versicolor*, rubberwood has been found to be more susceptible than non-durable jelutong and ramin (*G. bancanus*) (Hong *et al.*, 1999). Therefore, it is necessary for rubberwood to be treated with appropriate preservatives for protection against the attacks of biodeteriorating organisms.

In Malaysia, there are several processes involved in treating rubberwood, either in the form of logs or sawn timber, such as dip treatment, dip-diffusion, pressure treatment, vacuum-pressure, oscillating pressure method (OPM), and double-vacuum process (Salamah *et al.*, 1993; Hafizoglu, 2005). For temporary protection from staining of cut ends of logs, 3% sodium pentachlorophenoxide or 2% captafol in a bituminous compound was applied (Gnanaharan and Mathew, 1982). Freshly felled logs can be kept under water in log ponds to protect them against splitting and attacks by insects and fungi (Mohd Dahlan *et al.*, 1999). For sawn timbers, it was necessary to treat them immediately after sawing to prevent the penetration of staining fungus. As an example, sawn rubberwood can be protected through the dipping process for a few seconds in a solution of 0.5–1% sodium pentachlorophenate and 2% borax in water before kiln seasoning, which is a drying process occurred in a large oven-like structure with controlling the air circulation, humidity, and temperature. Pressure impregnation for total protection gives satisfactory results for rubberwood due to its permeability (George, 1985; Mohd Dahlan *et al.*, 1999).

An economical schedule for the industrial-scale treatment of rubberwood using boron compounds in the form of disodium octaborate tetrahydrate ( $\text{Na}_2\text{B}_8\text{O}_{13}\cdot 4\text{H}_2\text{O}$ ), disodium tetraborate decahydrate ( $\text{Na}_2\text{B}_4\text{O}_7\cdot 10\text{H}_2\text{O}$ ), and boric acid ( $\text{H}_3\text{BO}_3$ ) has been developed, particularly for indoor applications, to protect from insects borers and fungi (Gnanaharan and Dhamodaran, 1993; Mohd Dahlan *et al.*, 1999). In addition, highly toxic, but safe once fixed, copper-chromium-arsenic (CCA) preservatives are widely used in many countries due to their efficacy and cost

effectiveness (Gnanaharan and Dhamodaran, 1993). Mohd Dahlan *et al.* (1999) reported that CCA-treated rubberwood was rarely used in making furniture because of the unnatural color of the treated wood, but it can be used for construction or structural purposes to ensure resistance against termites and other biodeteriorating organisms.

Filamentous fungi are major source of bioactive secondary metabolites, and researchers has established the existence of biochemical pathways solely for the purpose of producing mycotoxins and other natural products in fungi through the study of ecological chemical interactions (Frisvad *et al.*, 2008). In this approach, fungi have been widely applied in agriculture as bio-control for pest management.

The first investigations on the potential of basidiomycetes as sources of antibiotics were performed by Anchel, Hervey, and Wilkins in 1941, whereby they succeeded in the isolation and identification of pleuromutilin, a diterpene that was useful in the treatment of mycoplasma infections in animals and served for the development of the first commercial antibiotic of basidiomycetes origin (Rosa *et al.*, 2003). As reviewed by Schuffler and Anke (2009), from 1940 until the early of 1950s, more than 2000 basidiomycetes fruiting bodies were screened for the production of antibiotics and resulted in the discovery of pleuromutilin, the lead compound for the semi-synthetic tiamulin used in veterinary practise and recently also in humans.

According to Reddy and Mathew (2001), there has been much interest in the possible use of wood-degrading fungi as biodegradation agent, particularly in the

case of white rot fungi. Based on study done by Lara *et al.* (2003), wood-degrading fungi had unique capacity for degrading wood and its basic constituents, cellulose and lignin. These fungi used the cellulose fraction as a source of carbon and have the ability to completely degrade the lignin so as to access to the cellulose molecule. Additionally, Pointing (2001) stated that the white rot fungi belonging to the basidiomycetes group exhibited the most efficient and extensive lignin degradation. In fact, Song *et al.* (1998) previously reported that basidiomycetes divisions exhibited the anti-tumour properties by producing lentinan, schizophyllan, and meshima during secondary metabolite. These compounds can be used as the active ingredients of bioherbicides, bioinsecticides, and biofungicides products (Bennett *et al.*, 2001). Furthermore, with the great scientific and technical development of fungal isolation and taxonomy over a broad range of genera, more and more species of higher fungi within the Basidiomycota division showed antimicrobial properties and considered as new and tremendous source of potent bioactive natural resources (Rosa *et al.*, 2003; Rosecke and Konig, 2000).

*Schizophyllum commune* is a species of basidiomycetes belonging to the Schizophyllaceae of Agaricales (Hao *et al.*, 2010). It has been reported to be a filamentously growing fungus that produced exopolysaccharides (EPS), and secreted the  $\beta$ -glucans as a uniform, primary molecular structure. This EPS possessed a  $\beta$ -(1 $\rightarrow$ 3)-linked backbone with single  $\beta$ -(1 $\rightarrow$ 6)-linked glucose side chains, in which upon 100% oxidation would result in a large number of aldehyde groups that exhibited antibacterial properties (Hao *et al.*, 2010; Jayakumar *et al.*, 2010). The EPS has numerous potential applications that included emulsifiers, lubricants, stabilizer, and thickening agents (Kumari *et al.*, 2008; Jayakumar *et al.*, 2010).

Concerning pharmaceutical applications, the EPS has been used to treat a number of diseases, including AIDS, and also to enhance the effect of vaccines and anticancer therapies (Hao *et al.*, 2010). As reported by Lorenzen and Anke (1998) and Kumari *et al.* (2008), schizophyllan is a high molecular weight  $\beta$ -1,3-glucan (ranging from 6 to 12 x 10<sup>6</sup> g/mol) isolated from the mycelia of *S. commune* which shows antitumor properties. The mode of action seemed to involve the stimulation of the host animal's immune response rather than a direct inhibition of tumor cell growth. Additionally, Shittu *et al.* (2005) reported that a sizofiran, antitumour polysaccharide extracted from the culture broth of *S. commune* served as an effective immune-therapeutic agent for cervical carcinoma because it stimulated a rapid recovery of the immunological status impaired by radiotherapy. In addition, it was also reported that several different polysaccharide antitumour agents, such as hetero- $\beta$ -glucans and their protein complexes, have been developed from the fruiting bodies, mycelia and medium of *S. commune*, particularly in China and Japan (Fagade and Oyelade, 2009).

On the other hand, *Pycnoporus sanguineus* is also very common on dead trees and plays an important ecological role in degrading woody forest litter (Djarwanto and Tachibana 2009; Hii, 2012). Meanwhile, the antimicrobial activity of *P. sanguineus* had been known since 1946, when poliporin was isolated against gram-positive and gram-negative bacteria and without toxicity to experimental animals (Rosa *et al.*, 2003). The basidiomes of *P. sanguineus* had been in use for a long time to prevent haemorrhages by Brazilian indigenous people and by America and African indigenous tribes for treatment of several ailments (Rosa *et al.*, 2003;

Smania *et al.*, 1995). Besides that, another wood-degrading fungus found in Malaysia, *Trametes versicolor*, is the most common species of the family Polyporaceae. Several biological activities was found from its extract, such as antibacterial, antifungal, antioxidant, antitumor, antiviral, kidney and liver tonic and also immune support (Farghali and Masek, 1998; Hsieh and Wu, 2001). Furthermore, Nyanhongo *et al.* (2007) reported that there is a number of evidence that showed *Trametes* was among the most versatile of white-rotters with ongoing intensive research into bioremediation application.

Thus, exploration, conservation, and utilization of the fungi belonging to basidiomycetes can be expected to prove beneficial for human as well as the environment.

## **1.2 Problem statement**

In Malaysia, rubberwood is now one of the most popular timbers used for the manufacture of quality furniture and other components. The attractive features of the rubberwood lay in its creamish colour and good woodworking properties. This had prompted many industries to use it as substitute for the highly priced remim timber. In fact, it has carved a niche for itself, and is the timber for many wood products (Hong and Sim, 1999).

In rubberwood, there is no distinction between the sapwood and heartwood (Killmann and Hong, 2000). It is considered that rubberwood contained only sapwood (Anonymous, 1982), and like the sapwoods of all timbers, is non-durable (Mohd Dahlan and Tam, 1987; Wong, 1988). Also, rubberwood is very prone to

attack by fungi and wood borers in green and dry condition (Ho, 1999). Commonly, the wood-degrading fungi such as *Pycnoporus sanguineus*, *Lenzites palisotii* and *Ganoderma applanatum* could rapidly destroy the rubberwood. As reported by a few researchers, the high carbohydrate (sugar and starch) reserve deposited in the parenchyma is major factor governing the high decay susceptibility of rubberwood (Azizol and Rahim, 1989; Wong, 1993). In view of the high severity of the decay problem, there is a need for prompt preservative treatment against the attack of biodeteriorating organisms.

Boron and copper-chromium-arsenic (CCA) are reported to be important compounds in rubberwood preservation (Zaidon *et al.*, 2003; Hwang *et al.*, 2007). Boron is odourless and is relatively less toxic when compared to some of the other preservatives, e.g. lindane, which poses serious health hazard to the workers performing the treatment and the processing of treated timber. While CCA treated rubberwood is rarely used because of the unnatural colour of the treated wood. If the timber is to be used for construction or structural purpose it is best to treat with CCA to ensure resistance against termites and other biodeteriorating organisms (Mohd Dahlan, 1999). However, these compounds have become less popular nowadays due to their toxicity and hazardous effect to human beings (Zaidon *et al.*, 2008). Hence, there is a need to search for an alternative of rubberwood preservation especially from our natural resources.

In addition, biocontrol agents are promising alternatives to chemical control of molds and wood-degrading fungi (Tripathi and Dubey, 2004). As reported by Verma *et al.* (2007), fungal-based biological control agents have gained wide

acceptance due to their broader spectrum in terms of disease control and production yield. Biofungicides are usually produced from secondary metabolites of fungi under an active culture cultivation process in which the fungi are not essential for vegetative growth in pure culture (Carlile *et al.*, 2001). *Trichoderma* biofungicides have been the modest biological control agents over the past 20 years (Ricard and Ricard, 1997; Verma *et al.*, 2007). For example, *Trichoderma harzianum* ATCC 20746 has been developed for the treatment of strawberries against gray mold *Botrytis cinerea* (Ricard and Ricard, 1997). There are also various fungal species that can be utilized as biological control agents, which may provide effective activity against various pathogenic microorganisms, such as *Ampelomyces quisqualis*, *A. niger*, *Candida oleophila*, *Chaetomium cupreum*, *C. globosum*, *Coniothyrium minitans*, *Cryptococcus albidus*, *Gliocladium virens*, *Gliocladium catenulatum*, *Fusarium oxysporum*, *Phlebotomus gigantea*, *Pythium oligandrum*, *Rhodotorula glutinis*, *T. harzianum*, and *Trichoderma polysporum* (Ricard and Ricard, 1997; Hofstein and Chapple, 1998; Carlile *et al.*, 2001; Soyong *et al.*, 2005; Kaewchai *et al.*, 2009). Based on the above observations, the biological control concept can be applied to the rubberwood industry for mold inhibition; however, at present, there are no reports on the usage of biological antifungal agent for rubberwood treatment.

On the other hand, filamentous fungus fermentation is a complex process as compared to bacterial and yeast fermentation (Xu and Yang, 2007). It is reported that a complex medium composition is needed for fungal fermentation during secondary metabolites (Zhang *et al.*, 2011). Meanwhile, Marwick *et al.* (1999) stated that if the harvesting of secondary metabolites be the main purpose, then the specific nutrient (e.g. carbon or nitrogen source) supply to sustain growth sometimes had to be limited

to keep the cell in stationary phase, while the substrate needed for the formation of the desired product has to be present in excess. For example,  $K_2HPO_4$  serves as phosphorous source and mainly controlling the production of secondary metabolites rather than the mycelia growth rate (Xu and Yang, 2007). In addition, physical condition during fermentation and extraction process plays a crucial role in controlling the quantity and quality of the desired product. Thus, the optimization study on different parameters for fungal fermentation and product formation should be investigated.

Bubble column bioreactor is a promising device for gas-liquid mass transfer and is being considered in biochemical application, especially for fermentation process (Kantarci *et al.*, 2005). It is an elongated non-mechanically stirred bioreactor with an aspect ratio of height/diameter through which is a unidirectional flow of gases (Nanou *et al.*, 2012). Additionally, bubble column bioreactor provides several advantages as compared to other types of bioreactors. First and foremost, it has an excellent heat and mass transfer characteristic, followed by the low operating and maintenance cost required due to lack of moving parts and compactness (Kantarci *et al.*, 2005; Nanou *et al.*, 2012). Furthermore, bubble column bioreactor with a bubble-free aeration through membrane provides suitable alternative for transferring gas without inducing cell damage through shear stress. It had been reported that batch bioreactor study was convenient systems for determination of the suitable conditions for maximum productivity (Chattopadhyay *et al.*, 2002). The knowledge gained in kinetics and production rate makes possible the application of principles and practices in understanding the critical parameters influencing mycelia growth and product yield in batch system.

### **1.3 Research objectives**

In view of the above observations, this study was carried out with the following objectives:

1. To screen for the presence of antifungal agent from twelve locally isolated wild strains of wood-degrading fungi.
2. To optimize the chemical and physical parameters for enhancement of growth of selected fungus in shake flask culture using a statistical method.
3. To optimize the antifungal agent extraction parameters using a statistical tool, select and validate various kinetic models for batch solvent extraction process.
4. To investigate the fungal growth and antifungal agent production by the selected fungus in a 2 l bubble column bioreactor.
5. To select and validate kinetic models of growth, antifungal agent production, glucose utilization, and substrate inhibition in a bubble column bioreactor.
6. To determine the effectiveness of antifungal agent produced on the rubberwood block panel.

### **1.4 Scope of study**

The preamble of this study was to investigate the ability of selected filamentous fungi to inhibit the growth of wood-degrading fungi of rubberwood. The antifungal activity was examined using minimum inhibitory concentration (MIC) assay coupled with broth dilution method using 96-well microtitre plate.

Firstly, process optimization of various variables using one-factor-at-a-time (OFAT) method on the production of biomass including media composition (e.g., yeast extract, malt extract, glucose, peptone,  $\text{KH}_2\text{PO}_4$ ,  $\text{K}_2\text{HPO}_4$ ,  $\text{Na}_2\text{HPO}_4 \cdot 12\text{H}_2\text{O}$ ,  $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ ,  $(\text{NH}_4)_2\text{SO}_4$ , and  $\text{KCl}$ ) and fermentation conditions (e.g., pH, incubation temperature, and agitation rate) were studied in order to obtain the optimum conditions for fungus growth under shake flask cultivation. Process optimizations using a statistical approach with selected independent parameters during fermentation process was also discussed. Response surface methodology (RSM) coupled with Box-Behken Design (BBD) were used in this study.

Secondly, the effect of extraction parameters (e.g., solvent concentration, extraction temperature, and mixing rate) on the production of antifungal agent was also carried out in order to obtain the optimum conditions for antifungal agent produced. Process optimizations using a statistical approach with selected independent parameters during extraction process was also discussed. Response surface methodology (RSM) coupled with Box-Behken Design (BBD) were used in this study. In order to describe the kinetics and mechanism of extraction process, several empirical models was simulated with the experimental data, such as parabolic diffusion model, power law model, Peleg's model, and Elovich's equation. The validity of each model was elucidated by the linear correlation coefficient ( $R^2$ ), root mean square deviation (RMSD), and mean relative percentage deviation ( $P$ ) value.

Thirdly, the production of antifungal agent was also studied in a bubble column bioreactor by employing one-factor-at-a-time (OFAT) method. Batch cultivations were characterized by constantly changing environmental conditions,

such as aeration rate, temperature, and glucose concentration. Next, the kinetic studies of cell growth, product formation, substrate utilization, and substrate inhibition using bubble column bioreactor were carried out to evaluate the fermentation characteristics. The models were then tested and the results obtained for each parameter was compared. The validity of each model was clarified by the linear correlation coefficient ( $R^2$ ), root mean square deviation (RMSD), and variance ( $\sigma$ ) value.

Finally, the antifungal agent produced was applied onto the rubberwood block panel to study its effectiveness against selected wood-degrading fungi.

## **1.5 Organization of the thesis**

There are five chapters in this thesis and each chapter describes the sequence of this research.

**Chapter 1** presents the expansion of rubberwood in Malaysia and the existing preservation methods during industrial processing. The use of higher fungi as a source of antifungal agent is also described. This chapter also presents the problem statement, research objectives, scope of research and thesis organization.

**Chapter 2** covers an overview of related knowledge of Malaysia's rubberwood industry and its limitation. This chapter also reports about the potential ability of filamentous fungi, the extraction method used for bioactive compound production and the bioreactor system for fungal fermentation.

**Chapter 3** presents the materials and methods describing the experimental procedure in the research for antifungal agent production. This chapter also contains the analytical and characterization methods of sample.

**Chapter 4** presents the results and discussion covering the experimental data and results obtained for screening of antifungal agent in shake flask culture. The optimization data with different parameters on mycelia growth and product formation are reported from the Design of Experiment. The empirical model on the extraction kinetics under optimized condition also been presented. This chapter also discusses the factors that influence the fungal growth and product formation in a bubble column bioreactor. The kinetic and modelling for growth, product formation, substrate utilization, and substrate inhibition are also highlighted. This chapter also covers the effectiveness study for the antifungal agent produced.

**Chapter 5** presents the overall conclusions that were based on the findings obtained in this study (Chapter 4). Recommendations for future research are also given in this chapter.

## CHAPTER 2

### LITERATURE REVIEW

#### 2.1 Development of rubberwood in Malaysia

##### 2.1.1 Rubber plantation revenue

The rubber tree (*Hevea brasiliensis*), which belongs to the family Euphorbiaceae, is indigenous to the Amazon forests of Brazil and represents the major source of natural rubber in the world (De Vis *et al.*, 2006). In 1877, nine seedlings of rubber were planted behind the house of the British resident Sir Hugh Low in Kuala Kangsar, Perak, Peninsular Malaysia, and these are believed to be the oldest rubber trees in Malaysia (Kiam, 2002). Then, systematic breeding and selection works of rubber clones to improve productivity has been on-going process in the Malaysian Rubber Board for almost nine decades. Since it embarked on the process, six series of clones with a total of 185 clones had been developed and recommended to the industry (Malaysian Rubber Board, 2011). In 1980s, the Rubber Research Institute of Malaysia (RRIM) sent a delegation to Brazil to source for more materials to widen its clonal stock for breeding purposes. More than 20 clones of rubber trees were planted in Malaysia (Hong, 1999).

Initially, rubber trees were extensively grown for the production of natural rubber. Latex could be collected economically from a rubber tree for 25–30 years, with its production decreasing gradually; a considerable quantity of rubberwood is obtained during replantation (Akhter, 2005). A mature rubber tree (>25-years old) in Malaysia is about 30 m tall with an average branch-free bole of 3 m at breast height. The trees in Malaysian rubber plantations are much smaller in size and have been

bred for the production of latex without considering the volume of wood produced (Hong, 1999). In 1991, the total area planted with rubber trees in Malaysia was reported to be 1,820,000 ha (Ismariah and Norini, 1999). However, the area of rubber trees under cultivation by estates and small holdings in Malaysia decreased from 1,389,000 ha in 2001 to 1,021,000 ha in the year 2009 (Table 2.1), a 26.4% decrease in the total area of rubber cultivation in Malaysia (FAO, 2010; Malaysian Rubber Board, 2011). This might have resulted from some estates converting to more profitable commodities such as oil palm. However, the future demand for rubberwood is expected to grow, particularly with the scarcity of indigenous timber species (Ismariah and Norini, 1999). Thus the criteria for breeding of rubber trees would in the future include those for production of wood in addition to latex (Hong, 1995; Killmann and Hong, 2000). Another factor that promotes rubber tree replanting is the market price of rubberwood. Smallholders of rubber plantations will demand the highest price possible, as rubber trees are worth RM1000–4000/m<sup>3</sup>, depending on the quality and quantity of rubberwood as well as the locality of the holdings (Yahaya, 1998). Taking the economic life of rubber trees as 25 years, Yahaya (1998) estimated that rubberwood production could be up to 3,207,000 m<sup>3</sup> in 2012, of which 581,000 m<sup>3</sup> (18.12%) would be from estates and 2,626,000 m<sup>3</sup> (81.88%) would be from smallholdings.

There was a slight difference in the rubber tree plantation areas among the different parts of Malaysia (Table 2.2). From 2007 to 2009, the total planted area in Peninsular Malaysia decreased by 22.25%, while in Sabah and Sarawak the total planted area remained stable. This might be due to the availability of large tracts of land which are suitable for commercial agriculture in East Malaysia (Sabah and

Sarawak). In fact, to overcome the declining areas of plantation, management of sustainable forest plantation was also practiced. In tandem with the development, additional new planting areas of 0.25 billion m<sup>2</sup> in Sabah and 0.05 billion m<sup>2</sup> in Sarawak, established by government agencies under the Ninth Malaysia Plan, were reported to enable additional production of rubber and rubberwood (The Star, 2009). This stabilized the plantation areas from 2007 to 2010.

Table 2.1. Total rubber trees planted in Malaysia from 2001 to 2010 (FAO, 2010; Malaysian Rubber Board, 2011)

Year	Estates (billion m <sup>2</sup> )	Small Holdings (billion m <sup>2</sup> )	Grand Total (billion m <sup>2</sup> )
2001	0.96	12.94	13.89
2002	0.85	12.64	13.49
2003	0.78	12.47	13.26
2004	0.64	12.14	12.79
2005	0.57	12.14	12.71
2006	0.54	12.09	12.64
2007	0.53	11.95	12.48
2008	0.61	11.86	12.47
2009	0.61	9.60	10.21
2010	0.62	9.67	10.29

Table 2.2. Planted area of rubber trees in Peninsular Malaysia, Sabah, and Sarawak from 2001 to 2010 (Malaysian Rubber Board, 2011)

Year	Peninsular Malaysia (billion m <sup>2</sup> )	Sabah (billion m <sup>2</sup> )	Sarawak (billion m <sup>2</sup> )
2001	11.52	0.87	1.50
2002	11.39	0.63	1.47
2003	11.05	0.64	1.57
2004	10.57	0.65	1.57
2005	10.49	0.65	1.57
2006	10.43	0.65	1.57
2007	10.20	0.71	1.57
2008	10.19	0.71	1.57
2009	7.93	0.71	1.57
2010	7.75	0.94	1.59

### 2.1.2 Potential characteristics of rubberwood

Rubberwood (*H. brasiliensis*), like any other wood, is a lignocellulosic material, non-homogeneous in nature and orthotopic in structure. Its density is not uniform and its mechanical properties varied longitudinally, radially, and tangentially (Mohd Shukari, 1999). After 25 years, rubber trees normally had clear boles 3 to 10 m in height and a diameter of up to 50 cm at breast height (Lim and Ani, 1999). The structural elements within rubberwood consist of 61.5% fibers, 9.5% vessels, and 29.0% parenchyma cells. The fiber length varies from 1.10 to 1.78 mm, the fiber width is from 26 to 30  $\mu\text{m}$ , and the cell wall thickness ranges from 5.1 to 7.0  $\mu\text{m}$ . The wood is fine, straight-grained, and light yellowish to white in colour, similar to the civit (*Swintonia floribunda*) or champa (*Michelia champaca*), with an approximate specific gravity of 0.56 (Mohd Nor, 1999).

The bending properties, compressive and shear strength, and hardness of the rubberwood, as shown in Table 2.3, indicated that it had good overall woodworking and machining qualities for sawing, boring, turning, nailing, and glazing. In addition, its strength and mechanical properties are also suitable for use in furniture making (Mohd Shukari, 1999; Hong, 1995). According to Hong (1995) and Killmann (2001), timber with an air-dry density of 560–650  $\text{kg}/\text{m}^3$  is classified as medium-dense timber. As can be seen in Table 2.3, rubberwood (under air-dry seasoning conditions) has a density of 640  $\text{kg}/\text{m}^3$ , which falls into the medium-dense timber category. Air-dried rubberwood, with a moisture content of 17.2%, has higher modulus of rupture (MOR) and modulus of elasticity (MOE) values at 66  $\text{N}/\text{mm}^2$  and 9240  $\text{N}/\text{mm}^2$ , respectively, than green wood (Mohd Shukari, 1999). In addition, this medium-dense

timber is suitable for wide application as it can easily be steam bent or stained to resemble any other timber (Gnanaharan and Dhamodaran, 1993; Nganthavee, 2002).

Table 2.3. Physical and mechanical properties of rubberwood (Mohd Shukari, 1999)

Properties	Seasoning Condition	
	Green	Air-dry
Moisture content (%)	52.0	17.2
Specific gravity (based on oven-dried weight and volume at test)	0.53	0.55
Density (kg/m <sup>3</sup> )	800	640
Static bending		
Modulus of rupture, MOR (N/mm <sup>2</sup> )	58	66
Modulus of elasticity, MOE (N/mm <sup>2</sup> )	8800	9240
Comparison parallel to grain		
Maximum crushing strength (N/mm <sup>2</sup> )	25.3	32.3
Comparison perpendicular to grain		
Stress at limit of proportionality (N/mm <sup>2</sup> )	3.65	4.69
Side hardness		
Load to embed a 11.28mm diameter steel sphere to one half its diameter (N)	3030	4320
Shear parallel to grain		
Maximum shearing strength (N/mm <sup>2</sup> )	9.0	11.0

Table 2.4 shows the comparative mean strength properties of rubberwood at different ages for the clone PB 260. The specific gravity increased with increasing tree age. This is in agreement with studies carried out by previous researchers (Lim, 1996; Lim and Ani, 1999), who stated that the specific gravity of the same clone (PB 260) tends to increase slightly with age. On the other hand, the MOR, MOE and the compression parallel to grain for this clone are not significantly different for different age groups, whereas the hardness, shear parallel to the grain, and the cleavage are significantly different at the 95% confidence limit between the different age groups. Nevertheless, the overall strength properties are higher in the older than in the younger trees for rubberwood clone PB 260, thus indicating that the old trees are hardier.

Table 2.4. Compressive strength properties of rubberwood clone PB 260 at different ages (Mohd Shukari, 1999)

Properties	Age group			Scheffe' Test
	3 yrs	8 yrs	14 yrs	
Moisture content (%)	13.63±1.18	15.30±0.66	14.58±1.67	n.s.
Specify gravity	0.56±0.02	0.57±0.03	0.58±0.02	n.s.
Modulus of rupture, MOR (N/mm <sup>2</sup> )	81.01±5.00	84.74±9.65	81.28±5.70	s
Modulus of elasticity, MOE (N/mm <sup>2</sup> )	370±810	8534±872	8564±1337	n.s.
Compression parallel to grain (N/mm <sup>2</sup> )	33.04±2.13	33.19±4.21	33.55±2.67	n.s.
Hardness (N)	3849±258	4265±505	4187±226	s
Shear parallel to grain (N/mm <sup>2</sup> )	11.46±0.62	13.19±1.41	12.48±0.93	s
Cleavage (N/mm width)	12.57±1.29	14.16±2.11	14.47±1.45	s

Note: ± refers to the corresponding standard deviations; s – significantly different at 95% confidence limit by Scheffe' Test; n.s. – not significant.

Fresh, sawn rubberwood is white to creamy in colour, sometimes having a pinkish tinge and weathering to a light straw or light brown colour (Lim and Ani, 1999; Killmann and Hong, 2000). The natural colour of rubberwood is one of the principal reasons why it is popular in Japan. All colours are distributed in a sphere known as the solid colour. Whitish wood is often preferred in many applications because it gives a clean and fresh impression, and the wood can easily be stained using dye or pigment (Minemura, 1999). Thus, rubberwood was increasingly used to replace more traditional timber (e.g., *Fagus* spp. and *Quercus* spp.) in a wide variety of applications. As a result, rubberwood became a good substitute for ramin (*Gonystylus bancanus* Baill) due to its favourable qualities and light colour (Killmann and Hong, 2000). Another added advantage of rubberwood is its good dimensional stability; its shrinkage or swelling rate is lower compared with that of other tropical species (Anthony, 1998). Extensive research and aggressive marketing have contributed to making rubberwood one of the most important export timbers

and a substitute for light tropical hardwoods in the production of furniture and indoor building components.

Fresh rubberwood contains 1.0–2.3% free sugars and 7.5–10.2% starch, making it easily attacked by fungi and insects (Anthony, 1998). The free carbohydrate content has also created other problems in terms of the setting of cement in cement-bonded panels manufactured in Malaysia (Akhter *et al.*, 1994). However, this problem may be resolved by open-air storage of the chips, which reduces sugar and starch levels to 0.2% and 1.0%, respectively (Killmann and Hong, 2000).

### **2.1.3 Rubberwood-based industry**

In the past 25 years, rubber trees have been planted for latex and timber purposes, particularly in Peninsular Malaysia, and the finished products of rubberwood have captured a lucrative export market. Currently, the Malaysian rubber industry produces a broad range of products from natural rubber to rubberwood-based products. For example, rubberwood has been established as a major wood product in several countries, particularly for the production of furniture, furniture components, and wood panel products, as well as for construction and decorative use (Balsiger *et al.*, 2000). In fact, a strong demand for rubberwood is based on sawn timber, which was reflected in the increase in exports from 95,700 m<sup>3</sup> in 1984, valued at RM29 million, to about 221,000 m<sup>3</sup>, valued at RM98.7 million, in 1989, which is an increase of approximately 98% by value (Hong, 1995). As reported by Chan *et al.* (2005), in 2004 the rubber products sector contributed RM19.6 billion to the country's export earnings, of which rubberwood products

comprised RM6.5 billion. Table 2.5 showed the export value contributed by the Malaysian rubberwood sector from 2005 to 2009.

Table 2.5. Export value contribution of the Malaysian rubberwood subsector from 2005 to 2009 (Malaysian Rubber Board, 2011)

Product	Export Value Contribution of Rubberwood (RM million)					
	2005	2006	2007	2008	2009	2010*
Sawn timber	386.2	69.8	55.2	27.1	34.3	16.8
Furniture	4,665.3	5,127.4	5,331.9	5,536.9	4,998.6	1291.5
Mouldings	698.1	796.3	915.3	744.1	686.4	170.5
MDF	1,106.7	1,144.9	1,180.9	1,156.1	1,033.4	289.2
Chipboard	266.7	266.9	364.9	391.7	250.9	66.5
Builders' carpentry & joinery	116.1	102.7	101.8	100.5	98.8	22.4
Wooden frame	12.7	12.2	13.2	12.4	16.2	2.9
<b>Total</b>	<b>7,251.8</b>	<b>7,520.2</b>	<b>7,963.2</b>	<b>7,968.8</b>	<b>7,117.8</b>	<b>1859.8</b>

Note: \*January to June

Due to this demand, in addition to new mills established solely for rubberwood processing, a number of traditional sawmills have converted to sawing exclusively rubberwood to maintain production capacity and minimize running cost. In 1993, there were 116 stationary and 26 mobile sawmills that processed only rubberwood (Killmann and Hong, 2000; Killmann, 2001). However, in 1994, there were more than 150 sawmills that processed only rubberwood (Hong, 1995). Meanwhile, there were a number of mobile mills that operated in plantations and smallholdings. Rubberwood became popular for use in several wood panel products. In 1999, Malaysia had medium-density fiberboard (MDF) mills with 13 production lines using primarily rubberwood (Killmann, 2001). For the production of MDF, rubberwood is usually the sole raw material, whereas chipboard usually uses either rubberwood or material from mixed-species groups (Norini, 2002).