

[Conferences](#) > [2019 6th International Confer...](#)

Proposed Model for the Estimation of Rain Attenuation: At Ku-Band at Ota, a Tropical Location

Publisher: IEEE

Cite This

6

Author(s)

[Ometan Oluwafunmilayo Oluwayemisi](#) ; [Omotosho Temidayo Victor](#) ; [Akinwumi Sayo Akinloye](#) ; [Adewusi Oladimeji Mustapha](#) ; [Emetere Moses Eterigho](#) ; [Boyo Adenike](#)

[View All Authors](#)

Abstract:

This study proposes a model for calculating rain attenuation on earth-space path carried out in Covenant University, Ota, Nigeria, a tropical location. The beacon signals from a geostationary satellite - ASTRA 28°E (2E/2F/2G) was monitored, recorded and analysed using a spectrum analyzer operating at frequencies of 12.245 GHz. Rain rates at the station of the antenna receivers were also logged and analysed. The rainfall rate cumulative distributions and the resultant rain attenuation are obtained and presented. The results obtained showed that the cumulative distribution of the measured rainfall rate is not in agreement with ITU-R prediction. Rainfall rate at 0.001 %, 0.01 %, 0.1 % and 1 % were fed into the existing Simple Attenuation Model (SAM) and corresponding rain attenuation were obtained. The measured rain attenuation from the beacon signal was compared with sixteen existing rain attenuation models in literature only SAM model was closed to the measured result at the location. SAM model overestimated and underestimated the rain attenuation for this location at some percentage of time. Hence, a modified SAM model is proposed using newly obtained specific attenuation coefficients. The proposed modified model is found to be close to the measured rain attenuation.

Published in: [2019 6th International Conference on Space Science and Communication \(IconSpace\)](#)

Date of Conference: 28-30 July 2019

Date Added to IEEE Xplore: 30 December 2019

ISBN Information:

ISSN Information:

INSPEC Accession Number: 19277407

DOI: [10.1109/IconSpace.2019.8905931](https://doi.org/10.1109/IconSpace.2019.8905931)

Publisher: IEEE

Conference Location: Johor Bahru, Malaysia, Malaysia

I. Introduction

The troposphere is the lowest atmosphere where major weather and climatic conditions take place. This weather conditions affect propagation of electromagnetic signal which in turn has an adverse effect on communication links. Of all the weather condition, rain causes the most severe effect such as transmission of errors and reduction or outage in the received signal especially as the frequency (10 GHz and above) for propagation increases. [1]–[2] Terrestrial and satellite communication links offer a wide range of applications for

technological advancement but the impairments (e.g. attenuation) caused must be adequately mitigated. The severity of the attenuation largely depends on the rainfall rate and the frequency of propagation, although there are other factors. The prediction of rain attenuation depends on the meteorological conditions of the station of interest or locality. From research already conducted, rainfall in a temperate region differs considerably from tropical region [3]–[10]. A tropical region is observed to experience high rainfall [11]–[14]. To considerably mitigate the effect of rain attenuation in a locality, a precise rain attenuation model is important. Over the years several rain attenuation prediction models have been predicted and established to account for rain attenuation [15]. Most of these models were formulated with data measured from temperate climate. Greater percentage of these existing models do not achieve good result in the tropics due to high rainfall rate. In this research, the results of rain attenuation at 12.245 GHz frequency band satellite links is analysed. The measured experimental results obtained is compared with SAM model. The result revealed that the SAM model do not calculate the slant path rain attenuation perfectly. Consequently, from the data obtained during extensive satellite link measurement mentioned above, a systematic method is used to recommend a rain attenuation model for the study area. This suggested model attains great accurateness in the climate of the study area which can be used to calculate the cumulative distribution of rain attenuation.

[Novel mitigation technologies for rain attenuation in broadband satellite communication system using from Ka- to W-band](#)

2007 6th International Conference on Information, Communications & Signal Processing

Published: 2007

[Distribution characteristics and performance simulations of rain attenuation at Ka band for satellite communications](#)

Proceedings of 2012 5th Global Symposium on Millimeter-Waves

Published: 2012

[View More](#)

Top Organizations with Patents on Technologies Mentioned in This Article

-

A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.

© Copyright 2020 IEEE - All rights reserved. Use of this web site signifies your agreement to the terms and conditions.