

Physical and Chemical Properties of Cement with Nano Black Rice Husk Ash

Ramadhansyah Putra Jaya^{1,a)}, Mohd Ibrahim Mohd Yusak^{2,b)}, Mohd Rosli Hainin^{2,c)}, Nordiana Mashros^{2,d)}, Muhammad Naqiuddin Mohd Warid^{2,e)}, Mohamad Idris Ali^{1,f)} and Mohd Haziman Wan Ibrahim^{3,g)}

¹Faculty of Civil Engineering and Earth Resources, Universiti Malaysia Pahang, 26300 Pahang, Malaysia

²Faculty of Civil Engineering, Department of Geotechnics and Transportation, Universiti Teknologi Malaysia, 81310 Johor Bahru, Malaysia

³ Faculty of Civil and Environmental Engineering, Department of Material and Structure Engineering, Universiti Tun Hussein Onn Malaysia, 86400 Batu Pahat, Johor Bahru, Malaysia

^{a)}Corresponding author: rsyahputrajaya@gmail.com

^{b)}mohdibrahim.mimy@gmail.com

^{c)}mrosli@utm.my

^{d)}mnordiana@utm.my

^{e)}naqiuddin@utm.my

^{f)}idrisali@ump.edu.my

^{g)}haziman@uthm.edu.my

Abstract. The existing of pores and micro-crack in the hardened cement paste influences the strength itself. Nano silica produced from BRHA has been used in this study. Nano BRHA replacement levels of 0%, 10%, 20% and 30% by weight of cement were applied. The TGA/DTA and XRD has been conducted for hardened cement paste powder to analyses the effect of different partial replacement of Nano BRHA. It was found that the weight loss results for Ca(OH)₂ seems decreasing with increasing in Nano BRHA replacement. The higher CSH percentage contained in cement paste was 10% of Nano BRHA replacement.

6. P. J. Ramadhansyah, A. W. Mahyun, M. Z. M. Salwa, B. H. Abu Bakar, M. A. Megat Johari and M. H. Wan Ibrahim, "Thermal analysis and pozzolanic index of rice husk ash at different grinding time," [Procedia Engineering](#), 50, pp 101- 109 (2012).
7. J. Yang and G. Jiang, "Experimental study on properties of pervious concrete pavement materials," [Cement and Concrete Research](#), vol. 33, pp. 381-386 (2003).
8. P. Chindaprasirt, S. Hatanaka, T. Chareerat, N. Mishima and Y. Yuasa, "Cement paste characteristics and porous concrete properties," [Construction and Building materials](#), 22(5) pp. 894-901 (2008).
9. B. W. Jo and J. H. Lim, "Investigations on the development of powder concrete with nano-SiO₂ particles," [KSCE Journal of Civil Engineering](#) 11(1) pp. 37-42 (2007).
10. S. A. E. Aleem, M. Heikal and W. M. Morsi, "Hydration characteristic, thermal expansion and microstructure of cement containing nano-silica," [Construction and Building Materials](#), 59, pp. 151-160 (2014).
11. R. Yu, P. Spiesz and H. J. H. Brouwers, "Effect of nano silica on the hydration and microstructure development of ultra-high performance concrete (UHPC) with a low binder amount," [Construction and Building Materials](#), 66, pp. 140-150 (2014).
12. F. T. Isfahani, E. Redaelli, W. Li and Y. Sun, "Effects of nanosilica on early age stages of cement hydration," [Journal of Nanomaterials](#), pp. 1-9 (2017).
13. BS EN 13925-1:2003. Non-destructive testing. X-ray diffraction from polycrystalline and amorphous materials. British Standards Institution, UK.
14. K. A. Snyder and P. E. Stutzman, "Hydrated phases in blended cement systems and synthesis saltstone grouts," National Institute of Standards and Technology, Gaithersburg (2013).
15. S. L. Poulsen, V. Kocaba, G. L. Saout, H. J. Jakobsen, K. L. Scrivener and J. Skibsted, "Improved quantification of alite and belite in anhydrous Portland cements by ²⁹Si MAS NMR: Effects of paramagnetic ions," [Solid State Nuclear Magnetic Resonance](#), 36, pp. 32-44 (2009).
16. Z.-h. Shui, R. Zhang, W. Chen and D.-x. Xuan, "Effects of mineral admixtures on the thermal expansion properties of hardened cement paste," [Construction and Building Materials](#), 24, pp. 1761-1767 (2010).
17. M. Frias and J. Cabrera, "Influence of MK on the reaction kinetics in MK/lime and MK-blended cement systems at 20°C," [Cement and Concrete Research](#), 31, pp.519-527 (2001).
18. M. Aly, M. S. J. Hashmi, A. G. Olabi, M. Messeiry, E. F. Abadir and A. I. Hussain, "Effect of colloidal nano-silica on the mechanical and physical behaviour of waste-glass cement mortar," [Materials and Design](#), 33, pp. 127-135 (2012).
19. L. P. Esteves, "On the hydration of water-entrained cement-silica systems: Combined SEM, XRD and thermal analysis in cement pastes," [Thermochimica Acta](#), 518, pp. 27-35 (2011).
20. W. Wongkoe and A. Chaipanich, "Compressive strength, microstructure and thermal analysis of autoclaved and air cured structural lightweight concrete made with coal bottom ash and silica fume," [Materials Science and Engineering A](#), 527, pp. 3676-3684 (2010).
21. R. Vedalakshimi, A. Sundara Raj, S. Srinivasan and K. Ganesh Babu, "Quantification of hydrated cement products of blended cements in low and medium strength concrete using TG and DTA technique," [Thermochimica Acta](#), vol. 407, pp.49-60 (2003).
22. T. I. Forood, R. Elena, L. Federica, Li. Weiwen and B. Luca, "Effects of nanosilica on compressive strength and durability properties of concrete with different water to binder ratios," *Advances in Materials Science and Engineering*, 2016 pp. 1-16 (2016).
23. Sha, W., O'Neill, E.A. and Guo, Z. (1999). Differential scanning calorimetry study of ordinary Portland cement. [Cement and Concrete Research](#), 29, pp. 14877-1489.