

Assessment of chemical inhibitor addition to improve the gas production from biowaste

Zahedi, S^{a,b*}; Dahunsi, S.O^{b,c}; Perez, M^a; Solera, R^a;

^aDepartment of Environmental Technologies, Cadiz University, Spain

^bBiomass and Bioenergy Group, Environment and Technology Research Cluster, Landmark University, Nigeria

^cBiological Sciences Department, Landmark University, Nigeria

*Corresponding author E-mail address: zahedi.diaz@gmail.com

Abstract

The coexistence of sulphate-reducing bacteria and methanogenic archaea in the reactors during the anaerobic digestion from sulphate-containing waste could favor the accumulation of sulfide on the biogas, and therefore reduce its quality. In this study, the effect of sulphate-reducing bacteria inhibitor (MoO_4^{-2}) addition in a two phase system from sulphate-containing municipal solid waste to improve the quality of the biogas has been investigated. The results showed that although SRB and sulphide production decreased, the use of inhibitor was not effective to improve the anaerobic digestion in a two phase system from sulphate-containing waste, since a significant decrease on biogas and organic matter removal were observed. Before MoO_4^{-2} addition the average values of volatile solid were around 12 g/kg, after 5 days of inhibitor use, those values did exceed to 28 g/kg. Molybdate caused acidification in the reactor and it was according to decrease in the pH values. In relation to microbial consortia, the effect of inhibitor was a decrease in Bacteria (44 %; 60% in sulphate-reducing bacteria) and Archaea (38%) populations.

Keywords: biomethanization; inhibition; sulphate-containing solid waste; microbial community structure.

30 **1. Introduction**

31 Conventional bioconversion of waste in anaerobic digestion (AD) systems is widely
32 recognized (Cuetos et al. 2008; Martín-González et al. 2013; Xing et al. 2014) and is
33 characterized by four steps: hydrolysis, acidogenesis, acetogenesis and methanogenesis.
34 The first three steps are carried out by various bacteria species while the fourth step
35 (methanogenesis) is usually dominated by special microorganisms belonging to the
36 Archaea domain (Zahedi et al. 2016). In the first and second steps, hydrolysis and
37 acidification take place by hydrolytic-acidogenic bacteria (HAB), and intermediate
38 products such as volatile fatty acids (VFA), hydrogen (H₂) and carbon dioxide (CO₂)
39 are generated. In the third step, VFA are transformed into acetate, H₂ and CO₂ by
40 acetogenic bacteria. Usually, Propionate-utilizing acetogens (PUA) and butyrate-
41 utilizing acetogens (BUA) are the majority of the acetogens in the anaerobic reactors
42 (Mara and Horan 2003). The methanogens occupy the terminal position in the anaerobic
43 food chain and are normally divided into two main groups based on their substrate
44 conversion capabilities. Acetoclastic methanogens (AUM) are able to convert acetate
45 into methane and carbon dioxide (Montero et al. 2008). Hydrogenotrophic methanogens
46 (HUM) convert H₂/CO₂ to methane. These species play a key role in the overall process
47 by maintaining the very low partial pressures of H₂ (<10 Pa) necessary for the
48 functioning of the intermediate trophic group, the acetogens, which are responsible for
49 the conversion of acids organic and alcohol intermediates to direct methane precursors
50 (Montero et al. 2008).

51 During anaerobic treatment of sulphate-containing wastewaters, sulphate-reducing
52 bacteria (SRB) compete for substrate with other anaerobic bacteria or methanogens.
53 Sulphate competes against organic carbon as an electron acceptor and it leads to the
54 undesirable production of hydrogen sulphide (H₂S).

55 H₂S is a corrosive gas and its presence reduces the potency of biogas as a fuel for
56 boilers or electricity generation in a biogas engine. Besides, it greatly affects the
57 flammability of biogas when used directly in burners (Rasi et al. 2007; Muñoz et al.
58 2015). In addition, H₂S causes malodor and health hazards due to the well-known
59 toxicity and material corrosion tendencies (Auguet et al. 2015). The nutritional
60 requirements of SRB include an inorganic electron acceptor which is usually provided
61 by sulphate ion and an electron donor which essentially consist of VFA or H₂ and
62 occasionally sugars and long chain fatty acids.

63 Two stages of inhibition exist as a result of sulphate reduction (Chen et al. 2008): (i)
64 primary inhibition due to competition for common organic and inorganic substrates
65 from SRB and (ii) secondary inhibition which results from the toxicity of sulphide to
66 various microbial groups. In this regard, many researchers have used molybdate (MoO₄⁻
67 ²) as sulphide inhibitor where different substrates were utilized (Newport and Nedwell
68 1988; Tucker et al. 1998; Ranade et al. 1999; Isa and Anderson 2005; Predicala et al.
69 2008; Rincon et al. 2008; Biswas et al. 2009; Jesus et al. 2015) and all of them show of
70 molybdate successful in inhibiting SRB activity.

71 Nevertheless, data on the outcome of competition between SRB and the
72 microorganisms mentioned above are contradictory in literature (Chen et al. 2008). The
73 considerable variation in the inhibition/toxicity levels reported for sulphate is due to the
74 complexity of AD process where mechanisms such as antagonisms, synergism,
75 acclimation and competition could significantly affect the phenomenon of inhibition.

76 Studies involving use of inhibitors to suppress activity of SRB and, consequently,
77 promote growth of methanogens have been reported in literature (Ranade et al. 1999;
78 Isa and Anderson 2005; Patidar and Tare 2005; Chen et al. 2008). However, other

79 studies documented that SRB and methanogens could have a symbiosis between them
80 (Vossoughi et al. 2003; Zahedi et al. 2013a; Auguet et al. 2015), although these
81 organisms are constantly competing as electron acceptors. Therefore, the feasibility of
82 using SRB inhibitor for the control of sulphate reduction and the improvement of
83 methane production in biological reactor are not established.

84 In view of this, the present study was undertaken to investigate the effect of molybdate
85 supplementation on the two-phase dry-thermophilic AD process of sulphate-containing
86 municipal solid waste. Structure and dynamics of the anaerobic consortia developed
87 along the experiment were analyzed by fluorescent in situ hybridization (FISH)
88 employing different oligonucleotide probes.

89 **2. Methods**

90 **2.1 Experimental equipment**

91 Two laboratory-scale continuously stirred tank reactors were employed (Figure 1). The
92 first reactor, dedicated to the hydrogen production (HP) (first phase), had a 5.5 liters
93 working volume, while the second reactor (second phase) dedicated to the methane
94 production (MP) had a 5 liters working volume, both heated by recirculating water
95 through a thermostatic jacket. PRECISTERM 6000142/6000389 (SELECTA S.A.)
96 baths were used, with a maximum capacity of 7 liters of water. The stainless steel
97 reactors lid have a diameter of 200 mm and contain three openings, one for the biogas
98 outlet, a feed inlet and another opening for the stirring system. The bottoms of the
99 reactors had a discharge valve with a 40 mm i.d., used for sampling. The biogas was
100 collected in 40 liter capacity Tedlar (a polyvinyl fluoride plastic polymer) bags. The
101 stirring systems consisted of an IKA EUROSTAR Power Control visc-P4 overhead
102 stirrer coupled to a stainless steel blade with scrapers which allows homogenization of

103 the waste at a speed of 23 rpm. The system was fed semi-continuously, once per day,
104 and the hydraulic retention times (HRT) were 1.5 (organic loading rate (OLR) = 57
105 g/l/d) and 5 d (OLR = 8 g/l/d) for the first and second phase, respectively.

106 **2.2 Inoculum, substrate and feeding**

107 The seed used as acidogenic and methanogenic inoculum were collected from a two
108 phase dry-thermophilic system of urban wastes. The total solid (TS) and volatile solid
109 (VS) concentrations in the second phase (methanogenic inoculum) were 67 g/kg and 33
110 g/kg as against their concentrations in the first phase (acidogenic inoculum) which were
111 82 g/kg and 50 g/kg, respectively.

112 The tested substrate in the first phase was the urban wastes from the 30 mm trommel of
113 the municipal solid waste treatment plant in Cadiz, Spain. The urban wastes was stored
114 in 25 kg drums at - 4° C to avoid AD by the microorganisms found in the solid waste
115 itself (Zahedi et al. 2013b). The TS concentration of the feed of the first reactor was
116 adjusted to 20 % (which is characteristic of dry AD) by adding tap water. Composition
117 of the substrate (urban solid wastes and water; 20 % of TS) employed in the first phase
118 is shown in Table 1. The substrate used in the second phase was the effluent of the first
119 phase (Table 2). Both reactors were fed once a day (semi-continuous).

120 **2.3 Inhibitor treatment methodology**

121 The effect of continuous dosing molybdate (MoO_4^{2-}) (2.5 mM) to improve the
122 performance in two-phase dry-thermophilic AD of sulphate-containing urban waste was
123 realized. No molybdate was added to the first phase, because under acid conditions the
124 biogas was sulphide-free (Zahedi et al. 2013b). The whole experiment length was 50 d.
125 During the first 45 d no inhibitor was used. In these 45 days two different period were
126 considered: startup (0-20 d) and control/stationary phase (20-45 d). On day 46, sodium

127 molybdate (MW=205.92 g/mol), 2.6 g, was added to the digester so as to have 2.5 mM
128 concentration of the inhibitor in the reactor ($V=5\text{ l}$) (Isa and Anderson 2005). From
129 next day onwards, i.e. from day 47, based on the daily wash out, 0.52 g per 1000 ml of
130 daily feed was added every day, so as to maintain the 2.5 mM inhibitor concentration in
131 the digester.

132 **2.4 Analytical methods**

133 Total and soluble chemical oxygen demand (TCOD, SCOD), alkalinity, sulphate, VS,
134 pH and VFA were performed according to previous studies (Zahedi et al. 2013c;
135 Dahunsi et al. 2016a,b). Determination of total and partial alkalinity and ammonia
136 ($\text{NH}_4^+\text{-N}$) were carried out daily. Fluctuation in the concentration of volatile fatty acids
137 (VFA) was determined using a gas chromatography (GC2010) to which was attached a
138 Fused Silica Capillary Column (Supelco NUKOLTM, 15 x 0.53 x 0.5 μm film
139 thickness) and with a flame ionization detector (200° C) with H_2 as the carrier gas. An
140 initial temperature of 80° C was used and was subsequently increased to 140° C, then
141 160° C and finally to 200° C at a rate of 10° C/min. The analyzed samples were
142 centrifuged and filtered through a 0.45 μm membrane.

143 Production of gas was continuously measured using a gas flow meter (Ritter Company,
144 drum-type wet-test volumetric gas meters), and the composition of the produced gas
145 was determined by gas chromatography separation (SHIMADZU GC-2010). H_2 , CH_4 ,
146 CO_2 , O_2 and N_2 were analyzed by means of a thermal conductivity detector (TCD)
147 employing a Supelco Carboxen 1010 Plot column. Samples were taken using a 1 ml
148 Dynatech Gastight gas syringe under the following operating conditions: split = 100;
149 constant pressure in the injection port (70 kPa); 2 min at 40 °C; ramped at 40 °C/min
150 until 200° C; 1.5 min at 200° C; detector temperature: 250° C; and injector temperature:

151 200° C. Helium was used as carrier gas (266.2 ml/min) (Zahedi et al. 2017b) .
152 Commercial mixtures of H₂, CH₄, CO₂, O₂, N₂ and H₂S (Abelló Linde S.A.) were used
153 to calibrate the system.

154 **2.5 Microbiological analysis and biochemical activity**

155
156 The cellular concentration and percentages of Bacteria and Archaea were quantified by
157 epifluorescence method (FISH) according to the method of Zahedi et al. (Zahedi et al.
158 2013c; Zahedi et al. 2017a). The main steps of FISH of whole cells using 16S rRNA-
159 targeted oligonucleotide probes are cell fixation, permeabilisation and hybridisation
160 with the desired probe(s).

161 The cellular concentration and percentages of *Eubacteria*, *Archaea*, BUA, PUA, SRB,
162 HUM and AUM were obtained by FISH according to Zahedi et al.(Zahedi et al. 2013c;
163 Zahedi et al. 2014). The total population was calculated as the sum of the relative
164 amounts of *Eubacteria* and *Archaea*, because the main anaerobic groups in the
165 anaerobic reactors are contained within these two domains (Griffin et al. 1998).
166 Acetogens were calculated as the sum of the relative amounts of PUA and BUA. HAB
167 were calculated as the difference in the relative amounts of *Eubacteria* and acetogens.

168 **3. Results and discussion**

169 The process performances and the functional *Bacteria* and *Archaea* community
170 structures of the two-phase anaerobic reactors for HP and MP were investigated and
171 analyzed together. The section has been structured into two parts: hydrogenic phase
172 performance and methanogenic phase performance.

173 **3.1 Hydrogenic phase performance**

174 As commented before, no molybdate was added to the first phase, because the biogas
175 was sulphide-free. The characterization physical-chemical and microbiological in the

176 effluent of the first phase are shown in the Table 2. The performance in the first phase
177 was according to Zahedi et al.(Zahedi et al. 2013c) study to 1.5 d HRT. This pH value
178 was close to the ideal pH conditions for HP of 5.5 (Bolzonella et al. 2012). VFA
179 composition was composed mainly of butyric acid (5.1 ± 0 . g/l). The dominant
180 fermentation products were butyric acid and acetic acid with small amounts of propionic
181 also detected (<0.1 g/l). The sulphate values in the effluent were the same with those
182 measured in the feeding; therefore no sulphate consumption was detected (no SBR
183 activity was detected). A high solubilization (increase in SCOD and VFA and decrease
184 in VS) was detected. The butyrate acid concentration was higher than acetic acid
185 concentration and it was in line to other researches of hydrogen production from similar
186 wastes (Cadiz-Spain urban wastes) (Romero Aguilar et al. 2013; Zahedi et al. 2013b;
187 Angeriz-Campoy et al. 2017; Zahedi et al. 2017a). The ratio of butyrate:acetate (g
188 butyrate/g acetate) was 2.5 and it according to the ratios reported by these previous
189 studies. The biogas produced was composed of H_2 and CO_2 without CH_4 and H_2S
190 detection. In terms of yields, biohydrogen in the first reactor was $47 \pm 4\%$ and the HP
191 was 2.0 ± 0.3 L H_2 /l/d).

192 3.2 Methanogenic phase performance

193 3.2.1 Process stability

194 The stability of the process was evaluated based on the evolution of pH and the
195 VFA/alkalinity ratio (VFA/Alk) before (1-45 d) and after (45-50 d) SRB inhibitor
196 addition (Siles Lopez et al. 2009).

197 Fig. 2.a shows the evolution of pH throughout the test. At the beginning (before
198 inhibitor addition) the systems were able to self-regulate and reach a pH of between 7.0
199 and 8.5, the optimal pH for the activity of methanogens (De La Rubia et al. 2009;

200 Dahunsi et al. 2016). After inhibitor addition, the pH of the reactor decreased below 7.0
201 showing microbial inhibition of H₂ and acid consumer organisms.

202 Alkalinity is the capacity to neutralise acids, the total volatile fatty acids (TVFA)/Alk
203 ratio being typically used as a measurement to evaluate anaerobic system stability
204 (Balaguer et al. 1992; Rincón et al. 2008; Siles Lopez et al. 2009). Values between 0.1
205 and 0.4 (equiv. acetic acid/equiv. CaCO₃) indicate favourable operating conditions
206 without the risk of acidification. The evolution of these ratios is shown in Fig 2.b.
207 Before inhibitor addition stability was observed, however from the day after the
208 molybdate was added this ratio decline sharply, demonstrating the non-stability of the
209 second phase (ratios were higher than 0.4). Therefore, the pH values and the acids
210 gathered, thus preventing the activity of the methanogens, as will be explained later.

211 3.2.2 Process performances

212 The highest values for the removal of VS (81±7 %) and SCOD (58±2 %) were obtained
213 before inhibitor addition. These values were similar to those obtained by Brownie
214 (Browne et al. 2014) in biomethane production from the organic fraction of municipal
215 solids waste in semi-continuous systems. Before MoO₄⁻² addition the average values of
216 SCOD and VS in the effluent were around 9 g/l and 12 g/kg respectively, after MoO₄⁻²
217 inhibition on day 50 those values did exceed to 25 g/l and 28 g/kg respectively (Figure
218 3). The reduction in the consumption of the organic matter means inhibition of the
219 anaerobic digestion process.

220 In relation to VFA, the effect of molybdate was an acidification in the reactor (increase
221 in acid content, Figure 4) according to decrease in the pH values. In the present
222 research, before molybdate addition, the concentrations of VFA were in the order
223 propionic > acetic > butyric. Addition of molybdate caused butyric and acetic acids to

224 dominate over propionic acid at the end of the trial. The presence of acetic acid in the
225 effluent shows that non-availability of AUM substrate was not the underlying problem
226 for the inhibition of CH₄ production in these studies, but chronic inhibition of AUM by
227 MoO₄⁻². In addition, butyric increment in the effluent was resulted of the non-
228 availability to the BUA to consume the butyric. The amount of propionic acid generated
229 after molybdate addition was similar to the amount produced before of inhibitor
230 addition, suggesting that acetogenic activity of PUA was sufficient to achieve the
231 normal propionic acid concentrations(Zahedi et al. 2013a).

232 It can clearly be observed that the addition of sodium molybdate on day 45 caused
233 immediate inhibition of sulphate reduction, thereby resulting in increase of sulphate
234 content in the effluent (Figure 5) and total absence of H₂S in the biogas (Figure 6a) on
235 the following day. Before MoO₄⁻² addition the average values of sulphate were around
236 0.7 g/l and on day 50 those values increased to 2.0 g/l. The values of H₂S decreased
237 from 45±5 mL H₂S/l/d on day 45 to 0 mL H₂S/l/d on day 46. Regarding to the MP, the
238 values of the MP also involved a decrease due to inhibitor use (Figure 6b). Before the
239 use of the SRB inhibitor, MP was around 3.5 L CH₄/l/d and after the supplement it was
240 modestly decreased, until the end, where MP did not exceed 0.2 L CH₄/l/d (day 50). It
241 technically shows that adding this amount of inhibitor for this amount of time does not
242 improve biogas production. Future efforts could incorporate dosing periods with
243 smaller amounts of inhibitor added in increasing increments and the observed return of
244 the system to the previous rate of biogas production and quality.

245 3.2.3 Microbial community

246 The evolution of the main microbial group involved in the methanogenic process is
247 described in the Table 3. In the present research, concentrations of different microbial

248 groups were evaluated before and after inhibitor addition. All the results shown are
249 average values. Before inhibitor addition, the ratio of *Eubacteria: Archaea* was 55:45.
250 These results are in accordance to those obtained by Zahedi et al.(Zahedi et al. 2013c) in
251 the second phase reactor of dry-thermophilic anaerobic digestion process of sulphate-
252 containing municipal solid waste and logically, lower than those obtained by Griffin et
253 al.(Griffin et al. 1998) and McMahon et al.(McMahon et al. 2001) in single-phase
254 reactors of organic waste. SRB population values were in line with those (20-28%)
255 obtained by Zahedi et al.(Zahedi et al. 2013c) and Zhang et al.(Zhang et al. 2011) lower
256 than those (14%) obtained by Mohan et al.(Mohan et al. 2005).

257 It should be noted, that after inhibitor addition the microbial proportion in the reactor
258 had not very altered, the microbial consortia and microbial activity were hardly altered.
259 It is necessary to emphasize that although the proportion of microorganisms in the
260 reactor is a key, not only the stability, but also the adequate dynamics (“flexibility”) of
261 the microbial community structure and high values of microbial activity are important
262 for the stable performance of the reactors treating urban wastes¹³.

263 At the end of the trial, the microbial consortia were decreased in 42%. The removal
264 rates of *Bacteria*, *Archaea*, HAB, acetogens, AUM, HUM, SRB, BUA and PUA were
265 44 %, 38%, 48%, 39%, 35%, 41%, 60%, 63% and 15% respectively. The most affected
266 were SRB and BUA and the most resistant group was PUA which is in line with the
267 constant values of propionic acid in the effluent. The reductions in the microbial
268 consortia, the decrease in the MP, H₂S production, pH value, and increase in the
269 sulphate, VS, SCOD and VFA contents all reveal a decrease in the microbial activity,
270 except for PUA.

271 In short, the use of the toxic to improve the biogas of the two-phase dry-thermophilic
272 anaerobic digestion process of sulphate-containing municipal solid is not effective.
273 However, it is to be noted that the harmful effect of molybdate supplementation on the
274 SRB and methanogens and therefore, on the H₂S and CH₄ generation makes this
275 treatment an interesting option on other fields, as sewerage system. Since, anaerobic
276 conditions in sewer pipes favor the accumulation of both H₂S and CH₄ and these
277 compounds have detrimental effects on the sewer system, with different consequences
278 for both the installation and its surroundings (Auguet et al. 2015) (such as malodor,
279 health hazards due to the well-known toxicity of H₂S, and corrosion of both the inner
280 surface of pipes and the inlet zones of waste water treatment plants, etc)

281 **Conclusion**

282 Inhibitor addition has proven successful to remove the undesirable production of
283 hydrogen sulphide (H₂S). However it too resulted in an increase in TVFA/Alk ratio, as
284 well as decrease in pH, organic removal organic matter and biogas generation. All this
285 indicated inhibition of all the steps to AD (except to propionic degradation). Therefore,
286 although molybdate is an effective bactericide for SRB, the use of the toxic would be
287 avoided, since molybdate supplementation did not improve the quality of the biogas,
288 under the circumstances of this experiment. Microbial consortia were decreased in
289 42%. The removal rates of *Bacteria*, *Archaea*, HAB, acetogens, AUM, HUM, SRB,
290 BUA and PUA were 44 %, 38%, 48%, 39%, 35%, 41%, 60%, 63% and 15%
291 respectively.

292

293

294 .

295 **Acknowledgements**

296 Zahedi thanks MIFAS association for people with physical disabilities, especially R.

297 Ferrer and J.Amores (Olot, Girona, Spain).

298 The authors wish to express their gratitude to Spanish Ministry of Economy and

299 Competitiveness, specifically to the Project CTM 2015-64810R financed by the

300 European Regional Development Fund (ERDF) entitled “Hydrogen-Methane

301 Production from Biosolids and Vinasses Anaerobic Co-Digestion”.

302

303 **References**

304 Angeriz-Campoy R, Fdez.-Güelfo LA, Alvarez-Gallego C, Romero LI (2017) New

305 criteria to determine the destabilization of the acidogenic anaerobic co-digestion of

306 organic fraction of municipal solid waste.

307 Auguet O, Pijuan M, Batista J, Borrego CM, Gutierrez O (2015) Changes in microbial

308 biofilm communities during colonization of sewer systems. *Applied and*

309 *Environmental Microbiology* 81:7271–7280. doi: 10.1128/AEM.01538-15

310 Balaguer MD, Vicent MT, París JM (1992) Anaerobic fluidized bed reactor with

311 sepiolite as support for anaerobic treatment of vinasse. *Biotechnology Letters*

312 14:433–438. doi: 10.1007/BF01021260

313 Biswas KC, Woodards NA, Xu H, Barton LL (2009) Reduction of molybdate by

314 sulfate-reducing bacteria. *Biometals* 22:131–139.

315 Bolzonella D, Cavinato C, Fatone F, Pavan P, Cecchi F (2012) High rate mesophilic,

316 thermophilic, and temperature phased anaerobic digestion of waste activated

317 sludge: A pilot scale study. *Waste Management* 32:1196–1201. doi:

318 10.1016/j.wasman.2012.01.006

- 319 Browne JD, Allen E, Murphy JD (2014) Assessing the variability in biomethane
320 production from the organic fraction of municipal solid waste in batch and
321 continuous operation. *Applied Energy* 128:307–314. doi:
322 10.1016/j.apenergy.2014.04.097
- 323 Chen Y, Cheng JJ, Creamer KS (2008) Inhibition of anaerobic digestion process: A
324 review. *Bioresource Technology* 99:4044–4064. doi:
325 10.1016/j.biortech.2007.01.057
- 326 Cuetos MJ, Gomez X, Otero M, Morin A (2008) Anaerobic digestion of solid
327 slaughterhouse waste (SHW) at laboratory scale: Influence of co-digestion with the
328 organic fraction of municipal solid waste (OFMSW). *Biochemical Engineering*
329 *Journal* 40:99–106. doi: 10.1016/j.bej.2007.11.019
- 330 Dahunsi SO, Oranusi S, Owolabi JB, Efeovbokhan VE (2016) Mesophilic anaerobic co-
331 digestion of poultry dropping and Carica papaya peels: Modelling and process
332 parameter optimization study. *Bioresource Technology*. doi:
333 10.1016/j.biortech.2016.05.118
- 334 Dahunsi, S.O.; Oranusi, S.; Owolabi, J.B.; Efeovbokhan, V.E. Comparative biogas
335 generation from fruit peels of Fluted Pumpkin (*Telfairia occidentalis*) and its
336 optimization. *Bioresource Technology* 2016, 221, 517-525.
337
- 338 De La Rubia MA, Raposo F, Rincon B, Borja R (2009) Evaluation of the hydrolytic-
339 acidogenic step of a two-stage mesophilic anaerobic digestion process of sunflower
340 oil cake. *Bioresource Technology* 100:4133–4138. doi:
341 10.1016/j.biortech.2009.04.001
- 342 Griffin M, McMahon K, Mackie R, Raskin L (1998) Methanogenic population

343 dynamics during start-up of anaerobic digesters treating municipal solid waste and
344 biosolids. *Biotechnology and Bioengineering* 57:342–355.

345 Isa MH, Anderson GK (2005) Molybdate inhibition of sulphate reduction in two-phase
346 anaerobic digestion. *Process Biochemistry* 40:2079–2089. doi:
347 10.1016/j.procbio.2004.07.025

348 Jesus EB, Andrade Lima LRP, Bernandez LA, Almeida PF (2015) Inhibition of
349 microbial sulfate reduction by molybdate. *Braz Pet Gas* 9:95–106.

350 Mara D, Horan N (2003) *Handbook of Water and Wastewater Microbiology*. Academic
351 Press-Elsevier, London

352 Martín-González L, Font X, Vicent T (2013) Alkalinity ratios to identify process
353 imbalances in anaerobic digesters treating source-sorted organic fraction of
354 municipal wastes. *Biochemical Engineering Journal* 76:1–5. doi:
355 10.1016/j.bej.2013.03.016

356 McMahon KD, Stroot PG, Mackie RI, Raskin L (2001) Anaerobic codigestion of
357 municipal solid waste and biosolids under various mixing conditions-II: Microbial
358 population dynamics. *Water Research* 35:1817–1827. doi: 10.1016/S0043-
359 1354(00)00438-3

360 Mohan SV, Rao NC, Prasad KK, Sarma PN (2005) Bioaugmentation of an anaerobic
361 sequencing batch biofilm reactor (AnSBBR) with immobilized sulphate reducing
362 bacteria (SRB) for the treatment of sulphate bearing chemical wastewater. *Process*
363 *Biochemistry* 40:2849–2857. doi: 10.1016/j.procbio.2004.12.027

364 Montero B, Garcia-Morales JL, Sales D, Solera R (2008) Evolution of microorganisms
365 in thermophilic-dry anaerobic digestion. *Bioresource Technology* 99:3233–3243.

366 doi: 10.1016/j.biortech.2007.05.063

367 Muñoz R, Meier L, Diaz I, Jeison D (2015) A review on the state-of-the-art of
368 physical/chemical and biological technologies for biogas upgrading. *Reviews in*
369 *Environmental Science and Biotechnology* 14:727–759. doi: 10.1007/s11157-015-
370 9379-1

371 Newport P, Nedwell D (1988) The mechanisms of inhibition of *Desulfovibrio* and
372 *Desulfotomaculum* species by selenate and molybdate. *J Appl Bacteriol* 65:419–
373 423.

374 Patidar SK, Tare V (2005) Effect of molybdate on methanogenic and sulfidogenic
375 activity of biomass. *Bioresource Technology* 96:1215–1222.

376 Predicala B, Nemati M, Stade S, Lague C (2008) Control of H₂S emission from swine
377 manure using Na-nitrate and Na-molybdate. *Journal Hazard Mater* 154:300–309.

378 Ranade DR, Dighe AS, Bhirangi SS, Panhalka VS, Yeole T. (1999) Evaluation of the
379 use of sodium molybdate to inhibit sulphate reduction during anaerobic digestion
380 of distillery waste. *Bioresource Technology* 68:287–291.

381 Rasi S, Veijanen A, Rintala J (2007) Trace compounds of biogas from different biogas
382 production plants. *Energy* 32:1375–1380. doi: 10.1016/j.energy.2006.10.018

383 Rincón B, Borja R, González JM, Portillo MC, Sáiz-Jiménez C (2008) Influence of
384 organic loading rate and hydraulic retention time on the performance, stability and
385 microbial communities of one-stage anaerobic digestion of two-phase olive mill
386 solid residue. *Biochemical Engineering Journal* 40:253–261. doi:
387 10.1016/j.bej.2007.12.019

388 Rincon JRT, Gomez DMC, Caraballo AES, Alvarez JHP (2008) Evaluacion del
389 molibdato y nitrato sobre bacterias sulfato-reductoras asociadas a procesos de
390 corrosion em sistemas industriales. *Reve Argent Microbiol* 52–62.

391 Romero Aguilar MA, Fdez-Guelfo LA, Alvarez-Gallego CJ, Romero García LI (2013)
392 Effect of HRT on hydrogen production and organic matter solubilization in
393 acidogenic anaerobic digestion of OFMSW. *Chemical Engineering Journal*
394 219:443–449. doi: 10.1016/j.cej.2012.12.090

395 Siles Lopez JA, Martin Santos M de los A, Chica Perez AF, Martín Martín A (2009)
396 Anaerobic digestion of glycerol derived from biodiesel manufacturing. *Bioresource*
397 *Technology* 100:5609–5615. doi: 10.1016/j.biortech.2009.06.017

398 Tucker M, Barton L, Thomson B (1998) Removal of U and Mo from water by
399 immobilized *Desulfovibrio desulfuricans* in column reactors. *Biotechnology and*
400 *Bioengineering* 60:88–96.

401 Vossoughi M, Shakeri M, Alemzadeh I (2003) Performance of anaerobic baffled reactor
402 treating synthetic wastewater influenced by decreasing COD/SO₄ ratios. *Chemical*
403 *Engineering and Processing: Process Intensification* 42:811–816. doi:
404 10.1016/S0255-2701(02)00107-1

405 Xing W, Chen X, Zuo J, Wang C, Lin J, Wang K (2014) A half-submerged integrated
406 two-phase anaerobic reactor for agricultural solid waste codigestion. *Biochemical*
407 *Engineering Journal* 88:19–25. doi: 10.1016/j.bej.2014.03.016

408 Zahedi S, García-Morales JL, Sales D, Solera R (2017a) Bioenergy Generation from
409 Municipal Solid Waste and Glycerin Waste: Population Dynamics. *Energy and*
410 *Fuels*. doi: 10.1021/acs.energyfuels.7b01526

411 Zahedi S, Sales D, Romero LI, Solera R (2013a) Optimisation of single-phase dry-
412 thermophilic anaerobic digestion under high organic loading rates of industrial
413 municipal solid waste: Population dynamics. *Bioresource Technology* 146:109–
414 117.

415 Zahedi S, Sales D, Romero LI, Solera R (2013b) Hydrogen production from the organic
416 fraction of municipal solid waste in anaerobic thermophilic acidogenesis: Influence
417 of organic loading rate and microbial content of the solid waste. *Bioresource*
418 *Technology* 129:85–91. doi: 10.1016/j.biortech.2012.11.003

419 Zahedi S, Sales D, Romero LI, Solera R (2013c) Optimisation of the two-phase dry-
420 thermophilic anaerobic digestion process of sulphate-containing municipal solid
421 waste: Population dynamics. *Bioresource Technology* 148:443–452.

422 Zahedi S, Sales D, Romero LI, Solera R (2014) Dark fermentation from real solid
423 waste. Evolution of microbial community. *Bioresource Technology* 151:221–226.
424 doi: 10.1016/j.biortech.2013.10.063

425 Zahedi S, Solera R, García-Morales JL, Ennouri H, Sales D (2017b) Evaluation of the
426 effect of glycerol supplementation on the anaerobic digestion of real municipal
427 solid waste in batch mode. *Fuel* 193:15–21. doi: 10.1016/j.fuel.2016.12.024

428 Zahedi S, Solera R, Micolucci F, Cavinato C, Bolzonella D (2016) Changes in
429 microbial community during hydrogen and methane production in two-stage
430 thermophilic anaerobic co-digestion process from biowaste. *Waste Management*
431 49:40–46. doi: 10.1016/j.wasman.2016.01.016

432 Zhang J, Zhang Y, Quan X, Liu Y, An X, Chen S, Zhao H (2011) Bioaugmentation and
433 functional partitioning in a zero valent iron-anaerobic reactor for sulfate-containing

434 wastewater treatment. *Chemical Engineering Journal* 174:159–165. doi:
435 10.1016/j.cej.2011.08.069

436

437

438 Table 1. Physical-chemical and microbiological characterization of the substrate
 439 employed in the first phase.
 440
 441

Parameter	Value
pH	5.3 (0.6)
TS (g/l)	120 (15)
VS (g/l)	85 (7)
Sulphate (g/l)	1.9 (0.3)
VFA (g acetic acid/l)	1.8 (0.5)
Acetate (g/l)	1.87(0.5)
Propionate (g/l)	0.0 (0.0)
Butyrate (g/l)	0.4 (0.2)
Total population (10⁸ cells/ml)	6 (2)
Eubacteria (%)	78 (3)
Archaea (%)	22 (2)

442 *Average values are shown, with standard deviations in parentheses.*
 443
 444
 445

446 Table 2: Physicochemical and microbiological characterization of the first phase reactor
 447 effluent

Physicochemical parameters								
pH	SCOD (g/l)	VS (g/kg)	Alkalinity (gCaCO ₃ /l)	Sulphate (g/l)	TVFA (g acetic/l)	Acetic (g/l)	Propionic (g/l)	Butyric (g/l)
5.3±0.3	33±2	42±5	4±0	1.9±0.2	10.4±0.9	2.5±0.4	0.1±0.1	5.1±0.5
Microbiological parameters								
Total population (10 ⁸ cells/mL)	<i>Eubacteria</i> (%)	HAB (%)	Acetogens (%)	BUA (%)	PUA (%)	SRB ^a (%)	<i>Archaea</i> (%)	AUM (%)
9.5±0.6	88±2	70±2	18±2	8±1	10±1	14±1	12±1	5±0

448 ^aPercentages compared to total *Eubacteria*.

449

450

451 Table 3: Microbiological characterization of the second phase reactor effluent.

Parameter	Period (Day)					
	1-45*	46	47	48	49	50
Microbiological parameters						
Total population (10⁸ cells/mL)	21.8±2.5	16.3	14.5	14.9	13.9	12.8
<i>Eubacteria</i> (%)	55±2	56	63	51	49	53
HAB (%)	28±1	34	37	27	25	25
Acetogens (%)	27±2	22	26	24	24	28
BUA	14±1	6	9	8	7	9
PUA (%)	13±1	16	17	16	17	19
SRB^a (%)	26±2	18	18	16	17	18
<i>Archaea</i> (%)	45±2	44	37	49	51	48
AUM (%)	24±1	24	21	29	28	27
HUM (%)	21±1	20	15	21	23	21

452 ^aPercentages compared to total *Eubacteria*.

453 *Values corresponding to the analytical determinations in steady conditions (between day 21 and 45).

454

455 **Figure Captions**

456 Figure 1: The laboratory-scale reactors used in this study. Hydrogenic reactor to the left
457 and methanogenic reactor to the right.

458 Figure 2: (a) pH evolution. (b) TVFA/Alk evolution (g acetic/g CaCO₃)

459 Figure 3: (a) SCOD evolution (g/l). (b) Volatile Solid evolution (g/kg).

460 Figure 4: (a) VFA evolution (g/l).

461 Figure 5: (a) Sulphate evolution (g/l).

462 Figure 6: (a) Sulphide production (SP) evolution (ml H₂S/l/d). (b) Methane production
463 (MP) evolution (l CH₄/l/d).

464


465 Figure 1.



466


467

468 Figure 2a




469

470 Figure 2.b




471

472 Figure 3.a




473

474 Figure 3.b




475

476 Figure 4




477

478 Figure 5




479
480
481

482 Figure 6.a



483
484

485 Figure 6.b



486