

Dynamic Scheduling Model for the Construction Industry

Journal:	<i>Built Environment Project and Asset Management</i>
Manuscript ID	BEPAM-02-2019-0021.R2
Manuscript Type:	Research Paper
Keywords:	resource constrained project scheduling problem, Dynamic Scheduling, Particle Swarm, Multi-Objective Optimization, Scheduling, Resource Management

SCHOLARONE™
Manuscripts

Dynamic Scheduling Model for the Construction Industry

Abstract

Purpose:

Basic project control through traditional methods is not sufficient to manage the majority of real-time events in most construction projects. This paper proposes a Dynamic Scheduling (DS) model that utilizes multi-objective optimization of cost, time, resources and cashflow, throughout project construction.

Design/methodology/approach:

Upon reviewing the topic of Dynamic Scheduling, a worldwide Internet survey with 364 respondents was conducted to define end-user requirements. The model was formulated and solution algorithms discussed. Verification was reported using predefined problem sets and a real-life case. Validation was performed via feedback from industry experts.

Findings:

The need for multi-objective dynamic software optimization of construction schedules and the ability to choose among a set of optimal alternatives were highlighted. Model verification through well-known test cases and a real-life project case study showed that the model successfully achieved the required dynamic functionality whether under the small solved example or under the complex case study. The model was validated for practicality, optimization

1
2
3 of various DS schedule quality gates, ease of use, and software integration with contemporary
4 project management practices.
5
6

7
8
9 **Practical/Social implications:**

10
11 Optimized real-time scheduling can provide better resources management including labour
12 utilization and cost efficiency. Furthermore, DS contributes to optimum materials procurement,
13 thus minimizing waste.
14
15
16
17

18
19
20 **Originality/value:**

21
22 The paper illustrates the importance of DS in construction, identifies the user needs, and
23 overviews the development, verification and validation of a model that supports the generation
24 of high quality schedules beneficial to large scale projects.
25
26
27
28
29
30

31
32 **Keywords**

33
34
35 Dynamic Scheduling, Resource-Constrained Project Scheduling Problem (RCPS), Particle
36
37 Swarm, Multi-objective Optimization.
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

Introduction

Schedule delays and cost overruns are common in construction projects, albeit advances in construction equipment and management techniques, and despite the multitude of efforts devoted to the planning and control aspects of construction management (Lee, Mora, & Park, 2006). Construction project scheduling is inherently complex and dynamic, involving multiple feedback processes and nonlinear relationships, yet problems encountered during construction have been treated statically within a partial view of a project (Lyneis, Cooper, & Els, 2001). Most research and practice efforts concentrate on scheduling analysis in a static deterministic environment, such as Critical Path Method (CPM), Resource-Constrained Project Scheduling (RCPS), Line of Balance (LOB), and Critical Chain Project Management (CCPM), whereas, real-time events cause disruptions to static scheduling (Cowling & Johansson, 2002; Vieira, Hermann, & Lin, 2003; Ouelhadj & Petrovic, 2009). Benham et al. argue that network-based scheduling methods were not originally developed for managing the production phase in construction projects, and were however, designed for projects that are highly predictable and static (Benham, Harfield, & Kenley, 2016). Stochastic methods such as PERT, GERT, and others have been developed to deal with the schedule uncertainties with a probabilistic approach. The information required as inputs for stochastic methods as well as the complexity of the processes involved can deem them impractical for the use in regular day to day scheduling practices, especially in projects of considerable size as with construction. Dynamic Scheduling (DS) can be used to handle real-time events and schedule disruptions in an optimal manner. DS, as in many other scheduling

1
2
3 concepts, started and developed in the manufacturing industry with the majority of applications
4
5 and approaches presented in literature mainly focusing on manufacturing systems (Aytug,
6
7 Lawley, McKay, Mohan, & Uzsoy, 2005; Herroelen & Leus, 2005; Ouelhadj & Petrovic, 2009;
8
9 Lagodimos, Mihiotis, & Kosmidis, 2004). Other applications have been cited in computer
10
11 engineering (Webster & Azizoglu, 2001), in logistics (Liang, Huang, & Yang, 2009), in petroleum
12
13 (Aissani, Beldjilali, & Trentesaux, 2009), and in aviation (Bennell & Potts, 2017).
14
15
16

17
18 DS can be summarized as a continuous dynamic process of updating, checking and revising the
19
20 schedule according to the selected scheduling architecture and based on predefined
21
22 rescheduling strategy, policy and rescheduling technique. The scheduling/rescheduling processes
23
24 involve regular deterministic scheduling methods for the analysis, while effects of real-time
25
26 events and uncertainties are mitigated with the continuous schedule adjustments and/or
27
28 optimization (Fahmy, 2014). DS has been categorized in literature into: reactive; proactive; and
29
30 predictive reactive scheduling (Aytug, Lawley, McKay, Mohan, & Uzsoy, 2005; Herroelen & Leus,
31
32 2005; Ouelhadj & Petrovic, 2009). In reactive scheduling no baseline schedule is required, and
33
34 real-time decisions are made on the resource level in more of a 'dispatching' manner, which can
35
36 be seen in small construction companies. The proactive approach is based on producing a
37
38 predictive baseline schedule, with continuous cycles of progress updates usually to activity
39
40 durations and resource levels, but rarely to logic. This is similar to the process of schedule
41
42 updating in construction. The predictive reactive approach produces a baseline schedule and is
43
44 logically revised based on real-time events, similar to the production of revised schedules in the
45
46 construction industry for major real-time disruptions. These approaches do not however, provide
47
48 dynamic optimization of schedules.
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3 DS in construction literature has been quite scarce and has focused on the aforementioned
4
5 approaches using risk management and project time control practices without providing
6
7 optimized schedules (Vanhoucke M. , 2013; Kerhove & Vanhoucke, 2017; Kumar &
8
9 Praveenkumar, 2015). Kumar and Praveenkumar recognized the notion that almost no project
10
11 in the construction industry performs totally as planned due to the different uncertainties faced
12
13 during the execution phase. They attempted, however, to provide dynamic scheduling without
14
15 dynamic optimization of the schedule (Kumar & Praveenkumar, 2015). The same approach of
16
17 performing dynamic scheduling through risk management and project time control was
18
19 introduced in other literatures (Vanhoucke M. , 2013; Kerhove & Vanhoucke, 2017).
20
21
22
23
24

25
26 The problem can be summarized as construction project scheduling being inherently complex
27
28 and dynamic, whereas, most techniques developed are static or deterministic in nature.
29
30 Furthermore, the information required for stochastic methods and their complexity can deem
31
32 them impractical for practical everyday use. DS models for construction are scarce, and in the
33
34 very few instances in literature, the models did not include optimization. Therefore, this paper
35
36 addresses this gap and aims to introduce a model for dynamic scheduling where schedules are
37
38 optimized to handle real-time events. This paper includes multi-objective optimization, based on
39
40 the work of other industries, and building upon current optimization techniques to meet the
41
42 dynamic needs of the construction industry. The mathematical formulation of the model
43
44 addressed specific construction-related issues and responded to the needs identified in a
45
46 questionnaire survey. Optimized real-time scheduling can provide better resources management
47
48 including labour utilization and cost efficiency, providing financial and time benefits to
49
50 contractors and owners. Furthermore, DS contributes to optimum materials procurement, thus
51
52
53
54
55
56
57
58
59
60

1
2
3 minimizing waste and improving the sustainability of the construction industry, and hence,
4
5
6 affecting society as a whole.
7
8

9 10 Schedule Optimization Review

11
12
13 Project scheduling optimization research has mostly aimed to either optimize resource utilization
14
15 or provide the optimum time-cost trade off. The Resource-Constrained Project Scheduling
16
17 Problem (RCPSp) problem, in principle, is an improved version of the original Critical Path Method
18
19 (CPM) after taking the resource limitations into consideration (Hartmann & Briskorn, 2010). The
20
21 Time-Constrained Project Scheduling Problem (TCPSP) aims to handle the balance between
22
23 resource availability constraints of renewable resource and the project time frame (Ranjbar &
24
25 Kianfar, 2007). The Time-Cost Trade-Off problem (TCTP) aims to minimize the project overall
26
27 duration, in terms of project cost. Various models were generated to present and solve the TCTP
28
29 (Demeulemeester, de Reyck, Foubert, Herroelen, & Vanhoucke, 1998; Ranjibar, Kianfar, &
30
31 Shadrokh, 2008). Critical Chain Project Management (CCPM) focuses on the constraints of a
32
33 project which prevent achieving its goals (Rabbani, Ghomi, Jolai, & Lahiji, 2007).
34
35
36
37
38
39

40
41 Researches have expressed its pitfalls in oversimplification of the problem (Herroelen & Leus,
42
43 2005). The, resource optimization problems although well-defined and properly modelled are
44
45 Non-Polynomial Hard (NP-Hard) (Arigues, Demasse, & Neron, 2008) and can be quite costly in
46
47 terms of processing time with large scale construction projects, if an exact solution is required.
48
49 This can be unacceptable with the requirements of dynamic construction projects.
50
51

52
53 Construction project scheduling is inherently complex and dynamic, involving real-time
54
55 disruption, multiple feedback processes and nonlinear relationships, yet problems encountered
56
57
58
59
60

1
2
3 during construction have been treated statically within a partial view of a project (Lyneis, Cooper,
4 & Els, 2001). A research need, thus, exists to attend to the dynamic and complex nature of the
5 construction industry. This need has been addressed by a few scholars, but the approaches were
6 mostly in terms of risk management and project time control, without dynamic optimization of
7 the schedule (Vanhoucke M. , 2013; Kerhove & Vanhoucke, 2017; Kumar & Praveenkumar,
8 2015).

22 **Dynamic Scheduling Review**

23
24
25
26 The types of real-time events and DS categories are discussed in this section. Two main
27 components of any DS system are when and how to respond to real-time events. Accordingly, DS
28 the rescheduling policy and strategy are reviewed. Finally, the rescheduling techniques used in
29 literature are overviewed.

30
31
32
33
34
35
36 Real-time events which cause disruptions to static scheduling have been discussed and
37 categorized differently in several researches (Suresh & Chaudhuri, 1993; Stoop & Wiers, 1996;
38 Cowling & Johansson, 2002; Vieira, Hermann, & Lin, 2003; Ouelhadj & Petrovic, 2009). Based on
39 these researches and from a construction industry point of view, real-time events can be
40 classified into three main categories:

- 41 • Project related events: Additions or omissions to the project's original scope (through change
42 orders, or design changes), changes to the project's due dates or milestones, changes to the
43 predefined sequence of work due to changes in priorities of the project's deliverables, delays

1
2
3 in governmental or authorities approvals, effects of inclement weather, force majeure events
4
5
6 (ex. floods or earthquakes), ...etc.

- 7
- 8 • Resource related events: Shortages of material, arrival of defective material/equipment,
9
10 breakdowns of construction machinery on site, delayed arrivals of specialized resources,
11
12 insufficient capacities of assigned resources, sickness or death of key resources, ...etc.
- 13
- 14
- 15 • Operations related events: Quality rejection of outputs, changes in deliverables
16
17 specifications, prolongations in operations durations (due to incorrect estimates for
18
19 resources productivities, incorrect estimates for equipment set-up times, or manpower
20
21 learning curves), unexpected behaviour of predefined design elements (for example
22
23 unsatisfactory results of soil tests after the completion of ground improvement works), ...etc.
24
25
26
27

28 The categorization of DS is based on the strategy of how or if the schedule baseline is generated
29
30 and how to respond to real-time events. The three main categories of DS have been previously
31
32 discussed in the Introduction section of this paper. The most common DS system is the predictive-
33
34 reactive scheduling approach (Ouelhadj & Petrovic, 2009) and is thus further explained in this
35
36 section. In predictive-reactive scheduling a predictive baseline schedule is initially generated,
37
38 then rescheduled (logically revised) based on real-time events and progress data, as illustrated
39
40 in Figure 1.
41
42
43

44
45
46 Three rescheduling policies were presented in literature to define when to respond to real-time
47
48 events (Church & Uzsoy, 1992; Sabuncuoglu & Bayiz, 2000; Vieira, Hermann, & Lin, 2003; Aytug,
49
50 Lawley, McKay, Mohan, & Uzsoy, 2005):
51
52
53
54
55
56
57
58
59
60

- Periodic rescheduling policy: Rescheduling process is started every predefined time interval regardless of the amount of real-time events occurring during this period.
- Event-driven rescheduling policy: Rescheduling process is triggered with the occurrence of any disruptive real-time event.
- Hybrid rescheduling policy (Rolling time horizon): Rescheduling process takes place periodically regardless of the in between events; however, certain predefined events can trigger the start of a new intermediate rescheduling process.




Figure 1: Predictive-Reactive Dynamic Scheduling

The rescheduling strategy is concerned with the mass of the changes to be made. There are two main rescheduling strategies (Sabuncuoglu & Bayiz, 2000; Cowling & Johansson, 2002; Vieira,

1
2
3 Hermann, & Lin, 2003): Schedule Repair where real-time events are mitigated through minimum
4
5 adjustments to the schedule portion related to the event; and Complete Rescheduling where the
6
7 project schedule is regenerated from scratch. In practice, the latter is practically not preferred
8
9 due to the required time and effort, despite of the fact that it helps in maintaining the near-
10
11 optimum solution.
12
13

14
15
16 The rescheduling technique represents the method or algorithm which a computerized system
17
18 will use to repair/reschedule the project plan. Heuristic algorithms are used as a rescheduling
19
20 technique, which are simple techniques that seek good solutions at a reasonable computational
21
22 cost without being able to guarantee feasibility nor optimality (Reeves, 1995).
23
24
25
26

27 **Research Methodology**

28
29
30
31 In order to develop the DS model, the following research methods were adopted, and are
32
33 expressed in following sections of the paper:
34
35

36
37 Defining end-user requirements: A questionnaire survey was implemented to investigate the
38
39 problem under study from a practical perspective, and identify certain features for the proposed
40
41 model. The survey was issued on the Internet to ease the process of invitations distribution as
42
43 well as the responses collection, to obtain opinions that are not biased towards a particular
44
45 surrounding environment, and to have wide geographical spread and several opinions from
46
47 different expertise levels and roles.
48
49

50
51
52 Model formulation and solution: Based on the defined user requirements and literature review
53
54 a generalized problem mathematical model was compiled with multiple objectives of time, cost,
55
56
57
58
59
60

resources and cashflow. An optimization technique was developed that suits the required operability of the DS model.

Model verification: The model is checked using predefined examples to produce acceptable solutions in terms of optimization quality and in terms of analysis of time, whereas, these solutions are compared to the model output.

Model validation: A case study using actual data from a real project is checked under real-time conditions and the optimization capabilities of the model under dynamic environment. Further, feedback of field experts is sought concerning the model and its practicality via a questionnaire survey.

User Requirements of DS in Construction

The user requirements of DS have been investigated in a questionnaire survey to the construction industry. The survey reviewed the scheduling/rescheduling problem from practical construction point of view and the suitability and practicality of a dynamic scheduling solution to the day-to-day scheduling works. The survey also reviewed the expectations of the functions/features to be present in any proposed dynamic scheduling solution. A webpage was developed for the questionnaire survey and published on the internet to facilitate its spreading. Then invitations were sent to major construction companies and consultancy offices; in addition, other invitations were sent to members of few popular planning/project management forums. The 364 responses of the survey covered construction planners/schedulers in various types of construction organizations with differing seniority and experience levels. The minimum sample size was computed to be 100 for infinite samples (Easterby-Smith, Thorpe, & Lowe, 2002). The

1
2
3 participants were geographically distributed as following: Africa 15.9%; Asia 34.1%; Europe
4
5 32.1%; North America 9.1%; South America 3.0%; and Oceania 5.8%. Participants had various
6
7 seniority levels: top management 11.8%; department management 25.6%; senior level 56.0%;
8
9 and junior level 6.6%. The experience levels of participants were 34.3% with high experience
10
11 (over 15 years); 48.1% with medium experience (5 to 15 years); and 17.6% with low experience
12
13 (less than 5 years). Full details of the survey can be found in Fahmy, Hassan and Bassioni (2014-
14
15 a) and Fahmy, Hassan and Bassioni (2014-b).
16
17
18
19
20

21 The most relevant outcome of the survey was the welcoming of optimization during scheduling
22
23 by 96% of the respondents. Real time events were selected as the main cause of disruption to
24
25 schedules, where less than 0.8% of the participants stated that real-time events does not impact
26
27 schedule integrity, while more than 85% selected that this disruption usually/always happens.
28
29 Thus, directly pointing to the need for dynamic scheduling with relevant optimization.
30
31

32
33 Other relevant results included defining can be summarized in the following points:
34
35
36

- 37 1. Beside the classical scheduling objective of minimize time, more than 83% of the survey
38 responses suggested that cost optimization objective should be also used. Adding additional
39 optimization objectives to identify the schedule's flexibility and/or criticality was a general
40 requirement by more than 50% of the survey's participants. Accordingly, two more
41 objectives should be considered while modeling.
42
43
44
45
46
47
48
- 49 2. With respect to resources analysis, 97.8% selected that it is required to be performed before
50 baseline schedule submission, from which 87.5% acknowledged that the time was always
51
52
53
54
55
56
57
58
59
60

1
2
3 not sufficient to review all resources distribution. Thus, resources distribution (or leveling) is
4
5 one of the most important objectives for an automated scheduling system.
6
7

8
9 3. For cash flow analysis, 91.4% selected that it is required, while 75.8% acknowledged that the
10
11 time was always not sufficient to change the schedule accordingly. Similar response ratios
12
13 were given to the same issues during schedule updates, but with less importance to cash
14
15 flow analysis where 16.8% selected that it is not required during schedule updates.
16
17 Accordingly, cash flow should also be modeled as one of the optimization objectives.
18
19

20
21 4. Optimization of medium and large scale schedules involves large computational burden, and
22
23 the number of activities/resources to be optimized is exponentially proportional to the
24
25 optimization time. More than 59% of participants responded to the fact that the
26
27 optimization algorithm can concentrate on critical/near critical activities leading to project
28
29 milestones; while for the rest of responses were more oriented towards optimizing all
30
31 activities rather than critical activities only. This can be modeled in any proposed solution to
32
33 be optional based on the requirements of each project.
34
35
36
37

38
39 5. With respect to activity modes, about 58% accepted the practicality of using several
40
41 execution modes for activities; which makes it an optional input to the model.
42

43
44 6. For solution architecture, nearly 82% suggested that an appropriate solution should be a
45
46 separate software tool to deal with the optimization process and communicates with the
47
48 planning software for the transfer of optimized solutions; from which 55% accepted this tool
49
50 to be fully integrated with the database of the planning software.
51
52

53
54 7. Finally, most participants suggested that any proposed dynamic scheduling solution should
55
56 suggest several optimized alternatives for the planner to review and make his choice.
57
58
59
60

7.

Dynamic Scheduling Model

Mathematical Formulation

The DS model was mathematically formulated based on the well-accepted Resource Constrained Project Scheduling Problem (RCPSP). Extensions to the RCPSP were taken into account to match the real life problem's characteristics, such as pre-emption (Ballestin, Valls, & Quintanilla, 2008), generalized precedence relations & minimum/maximum time lags (Chassiakos & Sakellariopoulos, 2005; Vanhoucke M., 2006), mode scheduling (Alcaraz, Maroto, & Ruiz, 2003), time/resource trade-off problem (TRTP) (Ranjbar & Kianfar, 2007). Accordingly, the main objectives of the model were formulated in line with the RCPSP and in line with the outcomes of the user requirements survey as follows:

- 1) Minimize Project time span:

$$\text{Minimize } T = S_n$$

- 2) Minimize Project overall cost, which implicitly includes the Resource Investment or Time-Resource Trade-Off problem objective, as well as Time-Cost Trade-Off problem objective (note: FC_i is the fixed cost of activity i , costs which are irrelevant to main resources defined in schedule):

$$\text{Minimize } C = \sum_{i \in V} FC_i + \sum_{k \in R} c_k * \max \{ \sum_{i=1}^n r_{ik} \}$$

- 3) Maximize resources utilization (i.e. minimize Resources Levels):

$$\text{Minimize } RLI = \log \left(\sum_{k \in R} (c_r / T_{min}) \times \sum_{t=0}^T \sum_{i \in V} (r_{ikt})^2 + \sum_{k \in N} u_k \times \sum_{t=0}^T \sum_{i \in V} (r_{ikt})^2 \right)$$

- 1
2
3 4) Cash flow improvement (i.e. minimize Negative Cash Flows):
4
5

$$6 \text{ Minimize } NCF = abs\left(\sum_{t=1}^T \min\{0, CF_t\}\right)$$

- 7
8
9
10 5) Maximizing schedule stability/robustness (represented in its simplest form as the sum of total
11 floats):
12

$$13 \text{ Maximize } SS = \sum_{i \in V} TF_i$$

14
15
16
17 Where:

18
19
20 T = Time span of the schedule

21
22
23 C = Project overall cost

24
25
26 RLI = Resource level

27
28
29 NCF = Negative cash flows

30
31
32 SS = Schedule stability

33
34 V = Set of activities 1 to n, where 1 & n are dummy activities added for simplicity of
35 calculations
36

37
38
39 H = Set of pairs of activities indicating their precedence

40
41
42 K = Set of renewable resources

43
44
45 F_j = Finish date for activity j

46
47
48 d_j = Duration of activity j

49
50
51 S_t = Set of activities in progress within time interval [t-1, t]

52
53
54 r_{ijkm} = Section j of activity i per period requirement from resource k in execution mode

55
56
57 ma_k = Available units from resource k
58
59
60

1
2
3 FC_i = the fixed cost of activity i
4
5

6 TF_i = Total float of activity i
7
8

9 Any other financial related objectives such as Net Present Value (NPV), Discounted Cash-flow
10 (DC) ...etc., were not considered in the model to avoid unnecessary financial complications.
11
12 Extensions were made to the DS model for minimizing schedule's deviation, maximizing schedule
13 flexibility, model simplification into optimizable and non-optimizable activities, and splitting of
14 resources into scarce and abundant resources. Constraints have been incorporated to account
15 for the data date which sets the start of the first activity at time interval zero, the precedence
16 which defines all schedule logic relations, and the sectional sequence which introduces logic ties
17 between activities' sections to assure their sequential order if pre-emption is allowed. Optional
18 constraints mainly represent project specific requirement, such as target completion, target
19 budgeted cost, maximum liquidity available for the project or maximum negative cash flow, set
20 of activities time constraints, and two sets of resources availability constraints. A full account of
21 the mathematical formulation was not included for paper size considerations, but can be found
22 in Fahmy (2014).
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40

41 42 43 ***DS Model Solution*** 44

45
46 The Particle Swarm Optimization (PSO) was selected as a model solution for the following
47 reasons:
48
49

- 50
51
52
53 1. All of the meta-heuristic methods were proven in literature to perform efficiently.
54

55 However, PSO requires only primitive and simple mathematical operators, and it is
56
57
58
59
60

computationally inexpensive in terms of both memory requirements and time (Moslehi & Mahnam, 2011);

2. Hardly any meta-heuristic, other than PSO, was presented to solve both problem categories (RCPSP & TCPSP) with the same algorithm;

3. PSO has been shown to perform well with respect to other methods (Chen, 2011).

An optimization algorithm was developed with the ability to explore the search space generated by the formulated mathematical model for finding the optimum solution as per the model's objectives. A computer program was developed to solve the model via a meta-heuristic solution using Particle Swarm Optimization (PSO) with stacking justification. Furthermore, an improvement to the original PSO was devised and termed The Differential Density PSO (DDPSO) algorithm was developed including the following contributions: Stacking Justification (SJ), a heuristic technique to improve solutions quality for resource-constrained problems; Float Justification (FJ), a heuristic technique to improve solutions quality for time-constrained problems; Rectified Schedule Generation Scheme (RSGS), an improved version of the original SGS, which improves the distribution of the search space; Combined Priority Rules (CPR), a technique to initialize particle swarm initialization for proper spreading of swarm particles among good quality areas of the search space; and Differential Density Particle Swarm Optimization (DDPSO), a modified PSO with the introduction of density parameters to swarm particles to overcome the algorithm's early convergence.

~~(Fahmy, Hassan, & Bassioni, Improving RCPSP solutions quality with stacking justification—Application with particle swarm optimization, 2014-c).~~

~~The Differential Density PSO (DDPSO) algorithm was developed including the following contributions: Stacking Justification (SJ), a heuristic technique to improve solutions quality for resource constrained problems; Float Justification (FJ), a heuristic technique to improve solutions quality for time constrained problems; Rectified Schedule Generation Scheme (RSGS), an improved version of the original SGS, which improves the distribution of the search space; Combined Priority Rules (CPR), a technique to initialize particle swarm initialization for proper spreading of swarm particles among good quality areas of the search space; and Differential Density Particle Swarm Optimization (DDPSO), a modified PSO with the introduction of density parameters to swarm particles to overcome the algorithm's early convergence.~~

The concept behind the proposed model modification is that a high density swarm particle should move slower than a low density particle, and accordingly explore the search space in a higher intensity; so, the density of particle i is inversely proportional to the particles velocity. The final formulation of the *DDPSO* is as follows:

$P = \text{No. of generated schedules} / \text{Schedules limit}$

$$V_{ij}^t = (w \times V_{ij}^{t-1} + r_1 c_1 (L_{ij}^{t-1} - X_{ij}^{t-1}) + r_2 c_2 (G_j^{t-1} - X_{ij}^{t-1})) / \delta_i$$

$$X_{ij}^t = X_{ij}^{t-1} + V_{ij}^t$$

Where V_i is the velocity of particle i ($i \in M$ particles), V_{ij}^t & V_{ij}^{t-1} are the velocities of component j of particle i in iterations t & $t-1$; r_1 & r_2 are two random numbers (from 0 to 1); c_1 & c_2 are two learning coefficients which define the influence of the local and global best solutions on the new velocities; X_{ij}^t & X_{ij}^{t-1} are the positions of component j of particle i in iterations t & $t-1$; L_{ij}^{t-1} is the position of component j in the positions vector of the best solution found by particle i until iteration $t-1$; G_j^{t-1} is the position of component j in the positions vector of the best solution

found globally in the swarm until iteration $t-1$. The pseudocode for the DDPSO algorithm can be expressed as the following:

While total generated schedules < schedules limit

$t = 1$

 For each particle i in forward & backward swarms

 If $t = 1$ Initialize DD swarm particles using CPR

 Update V_i^t & X_i^t

 Generate schedule using RSGS

 Apply selected justification scheme

 Map justified solution into X_i^t

 Calculate particle's fitness

 Update local best L_i^t & global best G^t

 End for

$t = t + 1$

End while

The selected priority can be either a single priority rule or the CPR and the justification scheme can be original justification, stacking justification or a combination of both. The Rectified Schedule Generation Scheme (RSGS) is an unfair distribution of priorities lists after eliminating lists which do not respect precedence, mainly caused by incorrect order of activities.

The optimization outputs vary depending on the quality of outputs achieved. If the algorithm was able to find any feasible solution, then the Pareto Front (PF) would be presented as the optimization output; otherwise, a set of best achieved Non-Feasible Solutions (NFS) would be presented. The PF consists of a set of pairs of objective (or combined objective) and the

1
2
3 corresponding best solution achieved; while the NFS consists of a set of best achieved solutions
4
5
6 ordered by their degree of feasibility.
7
8
9

10 **Dynamic Scheduling Model Verification**

11
12
13 The DS model numerical performance was checked against different static scheduling problem
14
15 sets to confirm the multi-objective solution capabilities of the model from an operational
16
17 research perspective. The model was further tested with real projects data to verify its solution
18
19 capabilities under dynamic environment and from a construction industry perspective.
20
21
22
23
24
25
26
27
28
29

30 ***Verification Using Benchmark Problem Sets***

31
32 Most of the researches published in the scheduling context have used benchmarks problem sets
33
34 generated by two well-known libraries: the PSPLib, and the PSPLib/max. These libraries were
35
36 generated using the problems generators PROGEN (Kolisch, 1997) & PROGEN/max (Kolish,
37
38 Schwindt, & Sprecher, 1998). The optimal values are not known for all these instances, thus the
39
40 best known solutions were used for performance comparison of the calculated lower bounds.
41
42 The PSPLIB's SRCPSP j-30 (480 instances), j-60 (480 instances), j-90 (480 instances) & j-120 (600
43
44 instances) were used for testing the RCPSP category. While for the TCPSP category, the SRIP/max
45
46 j-10 (270 instances), j-20 (270 instances) & j-30 (270 instances) were used.
47
48
49
50

51
52 The testing of the model performance is fully reported in Fahmy, Hassan, & Bassioni (2014-c).
53

54
55 The algorithm of the DS model was compared to the highest performing and highly ranked state-
56
57
58
59
60

1
2
3 of-the-art algorithms for solving single mode RCPSPs and was shown to outperform many of
4
5 these models, whereas, it ranked third among the top 20 models for SRCPSP j-30, the sixth among
6
7 the top 22 model for SRCPSP j-60, and SRCPSP j-120. The use of the DS model was proven to have
8
9 significant improvement to results, especially for small number of generated schedules; while the
10
11 improvement decreased (but still existed) with the amount of generated schedules. This behavior
12
13 is suitable for practical applications where achieving quick good-to-high quality solutions is
14
15 necessary.
16
17
18
19
20

21 ***Verification on Real-Life Project***

22
23 To further verify the model, an example model application on a portion of a real-life project,
24
25 whose identity is confidential, was solved manually and using the DS model software. The
26
27 detailed case study is available in Fahmy (2014). The project was for the development of an
28
29 international airport and considered a mega project including new airfield, terminal building,
30
31 traffic control tower and airport management buildings, together to the refurbishment of the
32
33 existing airfield. The contract value was about 1.3 Billion USD. The Work Break-Down Structure
34
35 (WBS) of the project extended to eight levels. The project schedule contained hundreds of
36
37 resources. Not all resources were marked for optimization throughout the case study testing as:
38
39 constrained resources due to resources availability; constrained resources due to plant
40
41 productivity constraints; and resource to be levelled to minimize resource costs.
42
43
44
45
46
47

48 The application of the DS model on the project involved three main stages corresponding to three
49
50 schedule quality gates:
51
52
53
54
55
56
57
58
59
60

- 1
2
3 1. DS project creation, definition of additional project data and optimization inputs; and
4
5 then performing the baseline schedule optimization and selecting an optimized
6
7 alternative.
8
9
- 10
11 2. Using the selected optimum baseline for progress updating using available historical
12 records for progress, variation orders, and delay events. Then optimization of these
13 updated schedules for the purpose of creating construction look-ahead schedules.
14
15
16
17
18
- 19 3. Selecting one of the progress updates with a major delay event in order to check the
20 functionality for preparing an optimized what-if schedule mitigating this delay event(s).
21
22
23
24

25 The main targets for the optimization process were resources levelling, and minimization of
26 project's direct costs. In addition, minimizing schedule deviation and minimizing total float
27 consumption were added with small weightages to the optimization objectives to avoid the
28 addition of unnecessary resource logic which might be added for resource levelling fine tuning;
29 thus optimum solutions are achieved with the best possible resource levelling with minimum
30 additional logic. During progress updates, minimizing schedule changes weight was increased to
31 avoid large schedule disruption. Finally, minimizing time was not included to objectives because
32 the project works was already time constrained with 9 contractual milestones.
33
34
35
36
37
38
39
40
41
42
43
44

45 According to the project requirements, the baseline optimization process was performed using
46 the following project parameters:
47
48
49

50
51 **Objectives:** Minimize Cost [C] (weight=60%), Resource Levelling [RLI] (35%), Minimize Schedule
52 Deviation [SD] (2%) & Min. Total Float Consumption [TFC] (3%)
53
54
55
56
57
58
59
60

1
2
3 **Constrained Activities:** 9 milestones
4

5
6 **Constrained Resources:** 15 resources
7

8
9
10 **Optimizable Activities:** All (7604 activities)
11

12
13 **Optimizable Resources:** 23 resources (15 constrained & 8 to be levelled)
14
15

16 The Pareto Front consisted of 15 solutions, corresponding to all possible combinations of the
17 optimization objectives (C, RLI, SD & TFC). The most important solutions to discuss are the SD-
18 TFC & the C-RLI-SD-TFC. The SD-TFC solution had 43 schedule changes (42 new & 1 deleted
19 resources logic); where these logic changes are the minimum changes needed to achieve
20 resources constraints. The best achieved solution in the baseline optimization process was
21 selected for progress updates. The DS model was utilized in a couple of updates. The latter of
22 which more than 100 variation orders were received, including major changes to utility networks,
23 additional surcharging to roads and buildings, modifications to stone columns ground
24 improvement areas, changes in specifications and so forth. Figure 2 illustrates the original and
25 optimized schedule for a several types of resources. What-if analysis was conducted using the DS
26 model to check the possibility of mitigating delays by increasing the number of stone columns
27 installation crews. The resulting schedule reduced the delay in the contractual milestone by more
28 than 4 months, with an increase of about 49% in the number of stone columns crews and 19
29 schedule changes (8 added and 11 deleted resource logic relations). The test cases and the case
30 study showed that the model successfully achieved the required dynamic functionality whether
31 under the small solved example or under the complex case study.
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




Figure 2: Sample Original and Optimized Histograms for a Progress Update and What-If schedule Optimization in the Case Study

Management

Model Validation

Validation Approach

The validation of a model can be achieved if it is accepted as reasonable for its intended purpose by people who are knowledgeable about the system under study (McGraw-Hill Encyclopedia of Science and Technology, 2002). This type of validation has been termed as 'Face Validity' of research, where experts observe the model and agree it represents a high degree of what happens in reality and its usability (Lucko & Rojas, 2010). The validity of a study can be conducted using face validity through obtaining the subjective judgement of a non-statistical nature that seeks the opinion of non-researchers regarding the validity of a particular study (Leedy & Ormrod, 2001). Therefore, the DS model was validated by seeking project management field experts' judgement. The model was presented to field experts with verification results, and their feedback obtained concerning model validity and implementation practicality. Feedbacks were received from 15 participants, who have previously worked in more than 39 countries. The experts worked as project management consultants (33%), engineering consultants (27%), general contractors (27%), and specialized contractors (13%). Experts with more than 15 years of experience comprised 60% of the sample, and with 10 to 15 years another 27%. The occupation level included 47% of the sample working as department management, 33% as top management and the remaining 20% senior level. Feedback forms were distributed by emails, with phone interviews when necessary to provide guidance, and responses were collected and analyzed. Upon providing a brief summary of DS, the proposed DS model, and the verification results, the form included questions concerning:

- a) The need for an optimized DS system to improve scheduling process of construction industry;
- b) Assessing the practicality of the proposed DS model within current project management practices;
- c) Investigating the efficiency of the developed model in achieving the objectives of the proposed solution; and
- d) Soliciting comments and/or improvements via open-ended questions on the DS model.

Validation Results

The general outcome of the validation was very positive from most experts/practitioners. The summary of participations' quantitative ratings is illustrated in Table 1. The majority of experts confirmed the necessity for a new system to optimize schedules: 80% for baselines; 87% for revisions; 53% for updates and look-ahead; and 67% for what-if schedules. Furthermore, experts evaluated the practical application of the proposed DS model: 80% for baselines; 87% for revisions; 67% for updates and look-ahead; and 60% for what-if schedules.

Almost all participants acknowledged the effectiveness of the proposed DS system under various schedule quality gates. The model was seen as strongly effective in baseline/revision optimization by 67% and somewhat effective by 33% of the sample. Effectiveness in progress updates/look-ahead optimization was rated as strongly effective by 33%, somewhat effective by 47% of the sample, and 20% providing a not sure answer. The effectiveness of what-if optimization was assured by 60% as strongly effective, by 20% as somewhat effective, by 7% as not effective and

1
2
3 13% not sure of the effectiveness. More than 73% felt that the proposed system can be easily
4
5 used, with 47% requiring some practicing.
6
7

8
9 In the feedback on the software, almost all participants acknowledged the effectiveness of the
10
11 software tool in providing the required functionalities as per the designed DS system's framework
12
13 with 60% responding strongly effective, 33% somewhat effective, and 7% responding as not being
14
15 sure. In terms of the ability to define/modify additional project optimization data 33% gave a
16
17 strongly effective feedback, 67% as somewhat effective and 7% not being sure. Finally, 27%
18
19 deemed the DS model as strongly effective in its ability to view optimized alternatives, 67% as
20
21 somewhat effective, and 7% not being sure.
22
23
24

25
26 The validation survey forms included two open-ended questions for participants to include their
27
28 improvement suggestions or comments for the proposed system. Responses to these questions
29
30 are listed in the following feedback and explanation/discussion:
31
32

- 33
34 1. Added logic might extend the project duration and change the project's critical path, which
35
36 might not be acceptable in some projects.
37

38
39 Explanation: With respect to project duration, in the model and the software tool's design, it
40
41 is up to the user whether or not to constrain the project's end date, and accordingly the
42
43 optimization algorithm will not extend the project's duration. For the critical path changes,
44
45 the algorithm will make some changes to the critical path only if it originally contains resource
46
47 logic relations which can be altered to improve the schedule's quality; and the improved
48
49 alternative will be presented to the user to confirm whether or not these changes can be
50
51 accepted as per the project's conditions and requirements.
52
53
54
55
56
57
58
59
60

- 1
2
3 2. The system should allow manual modifications by users beyond the modifications proposed
4
5
6 in the optimized alternatives.
7

8 Explanation: As per the system's general framework, proposed solutions are exported back
9
10 to the main planning software, where the user reviews and confirm the proposed solutions,
11
12 and can perform any additional manual modifications.
13
14

- 15
16 3. The system's model should include in the schedule's optimization process the associated
17
18 schedule risks.
19

20 Discussion: There are few additional complexities in the construction project management
21
22 processes (such as Risk Management) which can be included in future improved versions of
23
24 the proposed model.
25
26

- 27
28 4. The system should verify that the hard logic & the contractual constraints are not violated.
29

30 Explanation: The system does not alter any of the schedule's hard logic relations; it only alters
31
32 the relations marked by the user as soft logic. For contractual constraints, all constraints
33
34 added by user (time constraints, resource levels, budget, liquidity ...etc.) are considered
35
36 during the analysis; and includes a numerical value (the schedule's feasibility rate) which
37
38 indicates that, if equals to 100%, then the algorithm was able to optimize the schedule in the
39
40 proposed solution without violating any of the provided constraints.
41
42
43

- 44
45 5. The software tool needs some improvement in the graphical reports.
46

47 Discussion: The software tool is a prototype for optimized DS in construction projects. Any
48
49 software developed for commercial use should include several other improvements with
50
51 respect to user interface and graphical presentation of solutions and reports.
52
53
54
55
56
57
58
59
60

Conclusion and Recommendations

Construction projects are extremely dynamic, and the integrity of construction projects' schedules is vulnerable to large disruptions due to real-time events. Thus, a predefined Dynamic Scheduling (DS) strategy for mitigation of schedule disruptions is necessary to ensure efficient planning within construction projects. The few instances of DS in construction literature has focused on proactive and predictive reactive approaches using risk management and project time control practices without providing optimized schedules. This paper proposed a DS model with optimized schedules to manage real-time events.

The user requirements of DS have been investigated in a worldwide Internet survey of the construction industry with 364 responses from varied backgrounds and international experiences. The survey identified the need for multi-objective optimization various baseline and progress schedules, namely: time, cost, resources and cash_flow. Additionally, the need for software tools to support the practical implementation of DS and the suggestion of several optimized alternatives for the planner to review and choose among. Views of respondents were divided on the optimization focus to be critical/near critical activities leading to project milestones, or optimizing all project activities.

A multi-objective DS model was mathematically formulated based on the well-accepted Resource Constrained Project Scheduling Problem (RCPSP) with famous extensions for minimum time, minimum cost, maximum resource utilization, minimum negative cash flows, and maximum schedule stability/robustness in terms of total floats. A computer program was developed to solve the model via a meta-heuristic solution using Particle Swarm Optimization (PSO) with

1
2
3 stacking justification. The Pareto Front (set of feasible solutions), or the best achieved Non-
4
5 Feasible Solutions (NFS) are given to the scheduler to choose from, as indicated in the user
6
7 requirements survey.
8
9

10
11 The model was verified against the well-known scheduling problem sets PSPLib, and the
12
13 PSPLib/max. The DS model was shown to outperform many of these models, whereas, it ranked
14
15 third among the top 20 models for SRCPSP j-30, the sixth among the top 22 model for SRCPSP j-
16
17 60, and SRCPSP j-120. The model was further verified by applying to a 1.3 Billion USD
18
19 international infrastructure real-life project. The optimized baseline was developed and several
20
21 progress update optimizations, in addition to a What-If analysis.
22
23
24
25

26 Finally, the model was validated via expert feedback on the practicality of the model,
27
28 effectiveness of optimization of various DS schedule quality gates, ease of use, and software
29
30 integration with contemporary project management practices. Feedback comments of the
31
32 experts highlighted the issues of possible extension of project duration and contractual
33
34 consequences, allowance of modifications by users to optimized alternatives, integration of
35
36 schedule risks in the optimization process, verification that hard logic and contractual constraints
37
38 are not violated, and required improvements in graphical report. Each of these comments were
39
40 responded to by either a feature in the software, or the interoperable capability of the software
41
42 with professional scheduling packages, or on the basis of the software being a prototype with
43
44 possible improvements upon commercialization.
45
46
47
48
49

50
51 It can be concluded that the suggested DS model can provide better resources management
52
53 including labour utilization and cost efficiency. The model can also contribute to optimum
54
55 materials procurement, thus minimizing waste. Further, it has opened the door to more practical
56
57
58
59
60

1
2
3 optimized schedules in construction processes and to a plethora of knowledge gaps for DS
4
5 applications in construction which require further research. For example, contractual issues
6
7 associated with DS, the use of Artificial Intelligence (AI) applications in DS such as knowledge-
8
9 based systems, case-based reasoning, neural networks, fuzzy logic and hybrid systems. Other
10
11 areas include the integration of Risk Management and tools such as Critical Chain Project
12
13 Management (CCPM) in DS.
14
15
16

17
18 The DS model has several limitations. First, and although a large, international and diversified
19
20 sample was used to define user requirements, the model will always be limited by the sample
21
22 used and subject to further improvements. Second, the model solution is limited by the algorithm
23
24 utilized. Third, other research gaps identified in literatures can provide further limitations to the
25
26 suggested model. Fourth, although the software tool utilized is not very complicated, but might
27
28 require some training to non-experienced planners. Finally, the balance between schedule
29
30 changes and their benefits requires sound knowledge of the overall project's requirements and
31
32 its contractual scheduling limitations, and a good understanding of the DS solution to be able to
33
34 translate the project requirements into a good estimate for the optimization objectives' weights,
35
36 which can serve as another limitation to in-experienced planners.
37
38
39
40
41
42
43
44
45
46
47

48 **References**

49
50
51 Aissani, N. B., Beldjilali, B., & Trentesaux, D. (2009). Dynamic scheduling of maintenance tasks in the
52
53 petroleum industry: A reinforcement approach. *Engineering Applications of Artificial*
54
55 *Intelligence*, 22(7), 1089-1103.
56
57
58
59
60

- 1
2
3 Alcaraz, J., Maroto, C., & Ruiz, R. (2003). Solving the multi-mode resource-constrained project scheduling
4 problem with genetic algorithms. *Journal of the Operational Research Society*, 54, 614-626.
5
6
7 Arigues, C., Demassez, S., & Neron, E. (2008). *Resource-Constrained Project Scheduling*. London: John
8 Wiley and Sons.
9
10 Aytug, H., Lawley, M. A., McKay, K., Mohan, S., & Uzsoy, R. (2005). Executing production schedules in the
11 face of uncertainties: A review and some future directions. *European Journal of Operational*
12 *Research*, 161(1), 86-110.
13
14
15 Ballestin, F., Valls, V., & Quintanilla, S. (2008). Pre-emption in resource-constrained project scheduling.
16 *European Journal of Operational Research*, 189(3), 1136-1152.
17
18
19 Benham, A., Harfield, T., & Kenley, R. (2016). Linear vs. systems approach to production scheduling in
20 construction. *CIB W78 Conference*. Brisbane, Australia.
21
22 Bennell, J. A., & Potts, C. N. (2017, April). Dynamic scheduling of aircraft landings. *European Journal of*
23 *Operational Research*, 258(1), 315-327.
24
25
26 Chassiakos, A., & Sakellariopoulos, S. (2005). Time-cost optimization of construction projects with
27 generalized activity constraints. *Journal of Construction Engineering and Management*, 131,
28 1115-1124.
29
30
31 Chen, R. M. (2011). Particle swarm optimization with justification and designed mechanisms for
32 resource-constrained project scheduling problem. *Expert Systems with Applications*, 38, 7102-
33 7111.
34
35
36 Church, L., & Uzsoy, R. (1992). Analysis of periodic and event-driven rescheduling policies in dynamic
37 shops. *International Journal of Computer Integrated Manufacturing*, 5, 153-163.
38
39
40 Cowling, P., & Johansson, M. (2002). Using real time information for effective dynamic scheduling.
41 *European Journal of Operational Research*, 139(2), 230-244.
42
43
44 Demeulemeester, E., de Reyck, B., Foubert, B., Herroelen, W., & Vanhoucke, M. (1998). New
45 computational results on the discrete time/cost trade-off problem in project networks. *Journal*
46 *of the Operational Research Society*, 49, 614-626.
47
48
49 Easterby-Smith, M., Thorpe, R., & Lowe, A. (2002). *Management Research: An Introduction*. London, UK:
50 Sage Publications.
51
52
53 Fahmy, A. M. (2014). *A Dynamic Scheduling Model for Construction Enterprises*. Loughborough, UK: PhD
54 Thesis, Loughborough University.
55
56
57
58
59
60 Fahmy, A. M., Hassan, T. M., & Bassioni. (2014-b). Questionnaire survey on dynamic scheduling. *Project*
management World Journal, 3(5), May.

- 1
2
3 Fahmy, A. M., Hassan, T. M., & Bassioni, H. (2014-a). Prospects of dynamic scheduling concept in
4 construction industry. *Proceedings of Technology Innovation & Industrial Management (TIIM-*
5 *2014)*, (pp. S4 (154-179)). Seol.
- 6
7
8 Fahmy, A. M., Hassan, T. M., & Bassioni, H. (2014-c). Improving RCPSP solutions quality with stacking
9 justification - Application with particle swarm optimization. *Expert Systems with Applications*,
10 *41(1)*, 5870-5881.
- 11
12
13 Hartmann, S., & Briskorn, D. (2010). A survey of variants and extensions of the resource-constrained
14 project scheduling problem. *European Journal of Operational Research*, *207(1)*, 1-14.
- 15
16 Herroelen, W., & Leus, R. (2005). Project scheduling under uncertainty; Survey and research potentials.
17 *European Journal of Operational Research*, *165(2)*, 289-306.
- 18
19 Kerhove, L., & Vanhoucke, M. (2017). Optimised scheduling for weather sensitive offshore construction
20 projects. *Omega*, *66(A)*, 58-78.
- 21
22
23 Kolisch, R. S. (1997). PSPLIB - A project scheduling problem library: OR software - ORSEP operations
24 research software exchange program. *European Journal of Operational Research*, *96*, 205-216.
- 25
26 Kolish, R., Schwindt, C., & Sprecher, A. (1998). Benchmark instances of project scheduling problems. In
27 J. Weglarz, *Handbook on Recent Advances in Project Scheduling* (pp. 197-212). Kluwer.
- 28
29
30 Kumar, M., & Praveenkumar, T. (2015). A Dynamic Scheduling technique to control time in construction
31 projects. *International Journal of Applied Engineering Research*, *10(62)*, 338-344.
- 32
33
34 Lagodimos, A., Mihiotis, A., & Kosmidis, V. (2004). Scheduling a multi-stage fabrication shop for efficient
35 subsequent assembly operations. *International Journal of Production Economics*, *90(3)*, 345-359.
- 36
37
38 Lee, S., Mora, F., & Park, M. (2006). Dynamic planning and control methodology for strategic and
39 operational construction project management. *Automation in Construction*, *15(1)*, 84-97.
- 40
41
42 Leedy, P. D., & Ormrod, J. E. (2001). *Practical research planning and design* (7th Edition ed.). Upper
43 Saddle River, N.J.: Prentice Hall.
- 44
45
46 Liang, C., Huang, Y., & Yang, Y. (2009). A quay crane dynamic scheduling problem by hybrid evolutionary
47 algorithm for berth allocation planning. *Computers & Industrial Engineering*, *56(3)*, 1021-1028.
- 48
49
50 Lucko, G., & Rojas, E. M. (2010). Research validation: Challenges and opportunities in the construction
51 domain. *Journal of Construction Engineering and Management*, *136(1)*, 127-135.
- 52
53
54 Lyneis, J., Cooper, K., & Els, S. (2001). Strategic management of complex projects: a case study using
55 system dynamics. *System Dynamics Review*, *34(3)*, 237-260.
- 56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

- 1
2
3 Moslehi, G., & Mahnam, M. (2011). A Pareto approach to multi-objective flexible job-shop scheduling
4 problem using particle swarm optimization and local search. *International Journal of Production*
5 *Economics*, 129, 14-22.
6
7
8 Ouelhadj, D., & Petrovic, S. (2009). A survey of dynamic scheduling in manufacturing systems. *Journal of*
9 *Scheduling*, 12, 417-431.
10
11 Rabbani, M., Ghomi, S., Jolai, F., & Lahiji, N. (2007). A new heuristic for resource-constrained project
12 schedulign in stochastic networks using critical chain concept. *European Journal of Operational*
13 *Research*, 176(2), 794-808.
14
15
16 Ranjbar, M., & Kianfar, F. (2007). Solving the discrete time/resource trade-off problem in project
17 scheduling with genetic algorithms. *Applied Mathematics and Computation*, 191(2), 451-456.
18
19
20 Ranjibar, M., Kianfar, F., & Shadrokh, S. (2008). Solving the resource availability cost problem in project
21 scheduling by path relinking and genetic algorithm. *Applied Mathematics and Computation*,
22 196(2), 879-888.
23
24
25 Reeves, C. R. (1995). *Modern Heuristic Techniques for Combinatorial Problems*. London, UK: John Wiley
26 & Sons.
27
28 Sabuncuoglu, I., & Bayiz, M. (2000). Analysis of reactive scheduling problems in a job shop environment.
29 *European Journal of Operational Research*, 126(3), 567-586.
30
31 Stoop, P., & Wiers, V. (1996). The complexity of scheduling in practice. *International Journal of Operations*
32 *& Production Management*, 16(10), 37-53.
33
34
35 Suresh, V., & Chaudhuri, D. (1993). Dynamic scheduling - a survey of research. *International Journal of*
36 *Production Economics*, 32(1), 53-63.
37
38
39 Vanhoucke, M. (2006). Work continuity constraints in project scheduling. *Journal of Construction*
40 *Engineering & Management*, 132, 14-25.
41
42
43 Vanhoucke, M. (2013). *Project Management with Dynamic Scheduling: Baseline Scheduling, Risk Analysis*
44 *and Project Control*. London.: Springer Heidelberg.
45
46
47 Vieira, G. E., Hermann, J. W., & Lin, E. (2003). Rescheduling manufacturing systems: a framework of
48 strategies, policies and methods. *Journal of Scheduling*, 6(1), 36-92.
49
50
51
52
53
54
55
56
57
58
59
60 Webster, S., & Azizoglu, M. (2001). Dynamic programming algorithms for scheduling parallel machines
with family setup times. *Computers & Operations Research*, 28(2), 127-137.

Table 1. Expert Validation Results

Necessity for New System for Schedule Optimization	%
Baseline schedules preparation	80.0%
Revised schedules preparation	86.7%
Progress updates & look-ahead schedules preparation	53.3%
What-if schedules preparation	66.7%
Practical application of proposed DS system	%
Baseline schedules preparation	80.0%
Revised schedules preparation	86.7%
Progress updates & look-ahead schedules preparation	66.7%
What-if schedules preparation	60.0%
Effectiveness in Baseline/Revision Optimization	%
Strongly effective	66.7%
Seems effective	33.3%
Not sure	0.0%
Not effective	0.0%
Effectiveness in Progress Updates/Look-Ahead Optimization	%
Strongly effective	33.3%
Seems effective	46.7%
Not sure	20.0%
Not effective	0.0%
Effectiveness in What-if Optimization	%
Strongly effective	60.0%
Seems effective	20.0%
Not sure	13.3%
Not effective	6.7%
Ease of Use by Construction Projects' Planning Teams	%
Easy to use	26.7%
Easy to use after practicing	46.7%
Complicated and requires a lot of practice	20.0%
Only very experienced planners can use it	6.7%
Effectiveness of Software Integration with Current Project Management Practices	%
Strongly effective	60.0%
Seems effective	33.3%
Not sure	6.7%
Not effective	0.0%
Ability to define/modify additional project/optimization data	%
Strongly effective	33.3%
Seems effective	66.7%
Not sure	0.0%
Not effective	0.0%
Ability to view optimized alternatives	%
Strongly effective	26.7%
Seems effective	66.7%
Not sure	6.7%
Not effective	0.0%