

*25th International Symposium on Analytical and Environmental Problems***PRELIMINARY RESEARCH ON LAMINATE ULTRASONIC WELDING FOR FABRICATION OF SANDWICH COMPOSITE FROM AMORPHOUS RIBBONS AND CRYSTALLINE COPPER FOILS****Nicolaescu Mircea<sup>1,2</sup>, Mina Popescu<sup>1,2</sup>, Corina Orha<sup>1</sup>, Emilia Florina Binchiciu<sup>3</sup>, Cosmin Codrean<sup>2</sup>**

<sup>1</sup> *Department of Condensed Matter, National Institute of Research-Development for Electrochemistry and Condensed Matter Timisoara, Plautius Andronescu 1, 300224 Timisoara, Romania*

<sup>2</sup> *Politehnica University of Timisoara, Faculty of Mechanics, blv. Mihai Viteazu no.30, 300222, Timisoara, Romania*

<sup>3</sup> *National Institute in Welding and Material Testing - ISIM Timisoara, blv. Mihai Viteazu no.30, 300222, Timisoara, Romania*  
*e-mail: mircea.nicolaescu@student.upt.ro*

**Abstract**

With the evolution of society new materials or classes of materials must be developed. The lack of crystalline structure from the amorphous ribbons favors mechanical and electrical properties. The homogeneous structure of amorphous metal alloys offers unique mechanical, anti-corrosive, wear-resistant and magnetic properties, which makes them superior in many applications compared to the crystalline metals that have the same composition.

Yet, the major problem of amorphous metal alloys is their metastable character, these alloys being used only at low temperatures, but by introducing crystalline copper in the fabrication of sandwich composites, the usage temperature would increase.

In this study we present the results on the use of ultrasonic laminate welding for the fabrication of amorphous - crystalline composite materials.

Hybrid multilayer ultrasonic joints of the amorphous metal alloy with a thickness of 25  $\mu\text{m}$ , having the chemical composition 87.2% Ni, 4.2% Fe, 1.3% Cr, 4.5% Si, 2.8% B and crystalline copper with 99.99% purity, with a thickness of 15  $\mu\text{m}$ , were achieved. The amorphous ribbons were produced by the "Planar flow casting" process and the joint was made with an ultrasonic assembly at a frequency of 20 KHz.

The combined samples were characterized by X-ray diffraction (XRD), scanning electron microscopy (SEM), and Vickers micro-hardness.

**Keywords:** ultrasonic welding, amorphous ribbons, composite.