

# ADVANCES IN MATERIALS ENGINEERING

---

## Volume 1

Edited By:  
Zahurin Halim  
Iskandar Idris Yaacob  
Md Abdul Maleque



IIUM PRESS

INTERNATIONAL ISLAMIC UNIVERSITY MALAYSIA

# **ADVANCES IN MATERIALS ENGINEERING VOLUME 1**

Edited By:

Zahurin Halim  
Iskandar Idris Yaacob  
Md Abdul Maleque



**IIUM Press**

Published by:  
IIUM Press  
International Islamic University Malaysia

First Edition, 2011  
©IIUM Press, IIUM

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without any prior written permission of the publisher.

Perpustakaan Negara Malaysia

Cataloguing-in-Publication Data

ISBN: 978 -967-418-167-3

Member of Majlis Penerbitan Ilmiah Malaysia – MAPIM  
(Malaysian Scholarly Publishing Council)

Printed by :

**IIUM PRINTING SDN. BHD.**

No. 1, Jalan Industri Batu Caves 1/3

Taman Perindustrian Batu Caves

Batu Caves Centre Point

68100 Batu Caves

Selangor Darul Ehsan

# Table of Content

<b>Chapter 1</b> Preparation and Characterization of Thermoplastic Natural Rubber (TPNR) Nanocomposites <i>Noor Azlina Hassan, Sahrim Hj. Ahmad, Rozaidi Rasid and Norita Hassan</i>	1
<b>Chapter 2</b> Polymer Clay Nanocomposites: Part I <i>Noor Azlina Hassan and Norita Hassan</i>	6
<b>Chapter 3</b> Effect of Processing Parameters on the Tensile Properties of TPNR Reinforced Short Carbon Fibre Composite <i>Hazleen Anuar, Sahrim Hj. Ahmad and Rozaidi Rasid</i>	11
<b>Chapter 4</b> Effect of Maleic Anhydride Polyethylene on Damping Properties of HDPE/EPDM Nanocomposite <i>Hazleen Anuar, Nur Ayuni Jama, and Shamsul Bahri Abdul Razak</i>	16
<b>Chapter 5</b> Comparative Study on the Effect of Plasticizer on Thermal Properties of Polylactic Acid <i>Hazleen Anuar and Muhammad Rejaul Kaiser</i>	22
<b>Chapter 6</b> Quality of Copper Film Electroplated on Silicon Wafer Using Different Current Densities <i>Shahjahan Mridha</i>	28
<b>Chapter 7</b> Laser Nitriding of Titanium <i>Shahjahan Mridha</i>	39
<b>Chapter 8</b> Composite Coating on Titanium Alloy Using High Power Laser <i>Shahjahan Mridha</i>	45

<b>Chapter 9</b>		
Measurement of Moisture Absorption in Borophosphosilicate Glass (BPGS) Films		50
	<i>Shahjahan Mridha and Shiau Khee Tang</i>	
<b>Chapter 10</b>		58
The Effect of Processing Parameter on Tensile Properties of Thermoplastic Natural Rubber Nanocomposites		
	<i>Noor Azlina Hassan, Sahrim Hj. Ahmad, Rozaidi Rasid and Norita Hassan</i>	
<b>Chapter 11</b>		64
Comparison of Mechanical Properties Between Untreated and Sulphuric Acid Treated Short Carbon Fiber Reinforced Thermoplastic Natural Rubber (TPNR) Composite		
	<i>Noor Azlina Hassan, Norita Hassan, Sahrim Hj. Ahmad and Rozaidi Rasid</i>	
<b>Chapter 12</b>		69
Water Absorption of TPNR Reinforced Short Carbon Fibre Composite		
	<i>Hazleen Anuar, Sahrim Hj. Ahmad and Rozaidi Rasid</i>	
<b>Chapter 13</b>		74
Enhanced Tensile Strength with Sulphuric Treated Short Carbon Fibre		
	<i>Hazleen Anuar, Sahrim Hj. Ahmad and Rozaidi Rasid</i>	
<b>Chapter 14</b>		79
Effect of Fibre Length on Tensile Properties of TPNR-Kenaf Fibre Composite		
	<i>Hazleen Anuar, Sahrim Hj. Ahmad and Rozaidi Rasid</i>	
<b>Chapter 15</b>		84
Effect of Nanoclay on Mechanical Properties of PLA-Clay Nanocomposite		
	<i>Hazleen Anuar and Muhammad Rejaul Kaiser</i>	
<b>Chapter 16</b>		90
Extraction of Glucose From Kenaf Core by Using Chemical Pre – Treatment Process		
	<i>Nurhafizah Seeni Mohamed, Hazleen Anuar, Maizirwan Mel, Rashidi Othman, Nur Aisyah Mohd Norddin, Nur Aimi Mohd Nasir, Mohd Adlan Mustafa Kamalbhryn</i>	
<b>Chapter 17</b>		96
Wear of Nitride Coating Produced by Ti-Al Melt Synthesis in Nitrogen Environment		
	<i>Shahjahan Mridha</i>	
<b>Chapter 18</b>		103
Effect of Dispersant on Protein Foaming-Consolidation Porous Alumina Containing Hydrothermal Derived Hydroxyapatite Nanopowder		
	<i>Iis Sopyan and Ahmad Fadli</i>	

<b>Chapter 19</b>	109
Effect of Yolk Addition on Protein Foaming-Consolidation Porous Alumina-Calcium Phosphate Composites	
	<i>Iis Sopyan and Ahmad Fadli</i>
<b>Chapter 20</b>	115
Investigation of the Effect of Starch Addition on Protein Foaming-Consolidation Porous Alumina Containing Hydroxyapatite Nanopowder	
	<i>Ahmad Fadli', Iis Sopyan, Nur Syahidah and Nur Nadia</i>
<b>Chapter 21</b>	120
The Influence of Hydroxyapatite Loading on Protein Foaming-Consolidation Porous Alumina Sintered at 1300°C	
	<i>Ahmad Fadli 'and Iis Sopyan</i>
<b>Chapter 22</b>	126
High Density Polyethylene (HDPE) as an Alternative Material in Fuel Tank Production	
	<i>Afiqah Afdzahuddin and Md Abdul Maleque</i>
<b>Chapter 23</b>	132
Porous Alumina-Hydroxyapatite Composites via Protein Foaming-Consolidation Method: Effect of HA Loading on Physical Properties	
	<i>Iis Sopyan, Ahmad Fadli and Nur Izzati Zulkifli</i>
<b>Chapter 24</b>	137
Preparation and Characterisation of Low Density Polyethylene/Layered Silicate Nanocomposites	
	<i>Salina Sharifuddin , Iskandar Idris Yaacob</i>
<b>Chapter 25</b>	144
Effects of Sodium Dodecyl Benzene Sulphonate (NaDBs) on Li Imide-PMMA Based Solid Polymer Electrolyte	
	<i>Fauziah Mohd Yusof and Iskandar Idris Yaacob</i>
<b>Chapter 26</b>	149
Effect of Milling Time on Mechanochemically Synthesized Nanohydroxyapatite Bioceramics	
	<i>Iis Sopyan, S. Adzila and M. Hamdi</i>
<b>Chapter 27</b>	
Morphological Analysis of Mechanochemically Synthesized Nanohydroxyapatite Bioceramics	155
	<i>Iis Sopyan, S. Adzila and M. Hamdi</i>
<b>Chapter 28</b>	160
Sodium Doped Nanohydroxyapatite Bioceramics through Mechanochemical Synthesis	
	<i>S. Adzila, Iis Sopyan and M. Hamdi</i>

<b>Chapter 29</b>	165
Thermal Profile Analysis of Composite Brake Rotor	
<i>Md Abdul Maleque and Abdul Mu'min Adebisi</i>	
<b>Chapter 30</b>	172
The Effect of Fibre Content on Thermal Property of Coir Fibre Reinforced Cement-Albumen Composite	
<i>Faridatul Faezah Razali, Nur Humairah Abdul Razak and Zuraida Ahmad</i>	
<b>Chapter 31</b>	178
Pulsed Electrodeposition	
<i>Suryanto</i>	
<b>Chapter 32</b>	184
Electroless Nickel Based Coatings From Solution Containing Sodium Hypophosphite	
<i>Suryanto</i>	
<b>Chapter 33</b>	189
Characterization and Utilization of Fly Ash	
<i>Suryanto</i>	
<b>Chapter 34</b>	195
Workability of Coir Fibre- Reinforced Cement-Albumen Composite	
<i>Nur Humairah Abdul Razak and Zuraida Ahmad</i>	
<b>Chapter 35</b>	201
Preparation of Rice Husk for Raw Material of Silicon	
<i>Hadi Purwanto and Nor Fazilah Mohd Selamat</i>	

# Preparation and Characterization of Thermoplastic Natural Rubber (TPNR) Nanocomposites

Noor Azlina Hassan<sup>1</sup>, Sahrim Hj. Ahmad<sup>2</sup>, Rozaidi Rasid<sup>3</sup> and Norita Hassan<sup>4</sup>

<sup>1</sup>. Faculty of Engineering – International Islamic University Malaysia

<sup>2, 3, 4</sup>. Fakulti Sains dan Teknologi, Universiti Kebangsaan Malaysia

✉ : [noorazlina\\_hassan@iiium.edu.my](mailto:noorazlina_hassan@iiium.edu.my)

---

**Keywords:** Nanocomposites, thermoplastic natural rubber, nanoclay.

**Abstract.** Thermoplastic natural rubber nanoclay filled composite was prepared using a melt blending technique. TPNR was prepared in the ratio of (70:20:10) from LLDPE, NR and LNR as a compatibilizer. The clay used was sodium bentonite (smectite clay). X-ray diffraction of thermoplastic natural rubber matrix and smectite clay indicates that intercalation-exfoliation of the TPNR into silicate interlayers for the nanoclay. The glass transition temperature of TPNR/clay nanocomposites obtained from dynamic mechanical analysis (DMA) was higher than TPNR matrix. The storage modulus of the nanocomposites increased with increasing nanoclay content. The interaction between the matrix and the fillers remarkably affects the dynamic mechanical properties of the nanocomposites.

## Introduction

Polyolefin is one of the most common resins, owing to their low density good processability and low cost. They are widely used in diverse application such as vehicles, agriculture facilities, construction materials, electronic and sporting goods. However, the use of the polyolefin is restricted because of their several drawbacks such as lower strength, poorer heat resistance and others.

Thermoplastic natural rubber (TPNR) is a blend of rubber and thermoplastic and most probably the fastest growing sector in the polymer market [1-3]. The main advantages of these materials are that the thermoplastic machinery for processing does not require factory compounding or vulcanization and the scrap and rejects can be reprocessed. The rubber phase is partially cross-linked and thereby produces a morphology involving microphase separation responsible for the unique properties of the material.

Smectite nanoclay with huge surface area is widely used in polyolefin composites. Its application is now mainly focused on the improvement of mechanical and optical properties such as stiffness, gas barrier, flammability and etc. This paper, described the effect of nanoclay content on the dynamic mechanical properties of TPNR, which provide important information of the viscoelasticity of the composites over a wide temperature range.

## Experiment

**Materials and Preparation.** Linear low density polyethylene (LLDPE) used in this study was supplied by Exxonmobil Chemical Corporation with the density  $0.918\text{gcm}^{-3}$ . The natural rubber (NR) type SMR-L with density  $0.91\text{gcm}^{-3}$  was supplied by Guthrie (M) Bhd. Liquid natural rubber