Alternative Energy

Edited by

A.K.M. Mohiuddin
Asif Hoda



Published by: IIUM Press International Islamic University Malaysia

First Edition, 2011 ©IIUM Press, IIUM

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without any prior written permission of the publisher.

Perpustakaan Negara Malaysia

Cataloguing-in-Publication Data

A.K.M. Mohiuddin and Asif Hoda Alternative Energy A.K.M. Mohiuddin and Asif Hoda Include index Bibliography: p.

ISBN 978-967-418-158-1

Member of Majlis Penerbitan Ilmiah Malaysia – MAPIM (Malaysian Scholarly Publishing Council)

Printed by : IIUM PRINTING SDN. BHD.

No. 1, Jalan Industri Batu Caves 1/3
Taman Perindustrian Batu Caves
Batu Caves Centre Point
68100 Batu Caves
Selangor Darul Ehsan

Table of Contents

Table of Contentsv
Prefaceviii
Chapter 1
The Impact of energy utilization on environment
M.N.A. Hawlader
Chapter 2
Desalination of Seawater to provide fresh water9
M.N.A. Hawlader
Chapter 3
A solar assisted desalination system using heat pump
M.N.A. Hawlader, Leong Chiing Yang
Chapter 4
An experimental study of a phase change storage system
M.N.A. Hawlader and Smita Panga
Chapter 5
Moisture migration in a grain column subjected to drying
M.N.A. Hawlader and Md. Shafique J. Chowdhury
Chapter 6
Solar Drying of Guavas, Papayas and Apples38
M.N.A. Hawlader and Lee Hwee Peng
Chapter 7
Drying under inert environment: the quality of Mango and Rockmelon47
M.N.A. Hawlader and Pan Jiahe
Chapter 8
A low temperature flat plate solar collector
M.N.A. Hawlader, M. Zakir Ullah and Maung Than Htut
Chapter 9
Optimization of an integrated solar heat-pump system
M N A Hawlader and Ye Shaochun
Chapter 10
Comparative study of performance characteristics using Jatropha Oil Methyl Esters
Biodiesel and Diesel 69
A.K.M. Mohiuddin and Azan Mohd
Chapter 11
Comparative Study of Emission Characteristics using Jatropha Oil Methyl Esters Biodiesel
and Diesel
A.K.M. Mohiuddin and Azan Mohd
Chapter 12
Waste Cooking Oil Utilization for Biodiesel Production
A.K.M. Mohiuddin and Nabeel Adeyemi
Chapter 13
Flow Characteristic of Mixing Impeller for Liquid-Liquid Mixing
A.K.M. Mohiuddin and Nabeel Adeyemi
Chapter 14
Solar Energy Management for Poverty Alleviation and Income Generating Activities 91
A.K.M. Mohiuddin

Chapter 15	
Turbulence model for axial mixing impeller in unbaffled vessel	97
A.K.M. Mohiuddin, Nabeel Adeyemi and Muhamad Husaini	
Chapter 16	
Optimization and economic analysis of a solar assisted heat pump drying system 10	03
M.N.A. Hawlader, S. M. A. Rahman and K.A. Jahangeer	
Chapter 17	
A solar heat pump water heater for rural hospitals	17
M.N.A. Hawlader and M. Zakir Ullah	
Chapter 18	
A solar heat-pump system for air-conditioning, water heating and drying	26
M N A Hawlader, K A Jahangeer, Ye Shaochun and Choy Tack Hoon	
Chapter 19	
Engineering design – An approach to the development of creativity	32
M.N.A. Hawlader	
Chapter 20	
Analysis of Engine Performance with NGV	40
Sany Izan Ihsan, Nabila Sulaiman, AKM Mohiuddin and Maizirwan Mel	••
Chapter 21	
Analysis of Engine Performance with Enhanced Fuel	47
Sany Izan Ihsan, Khairussani Farid, Maizirwan Mel, and AKM Mohiuddin	• '
Chapter 22	
CFD analysis of an evacuated solar still.	56
Ahmad F. Ismail, Mirghani I. Ahmed, Yousif A. Abakr	
Chapter 23	
Developments on Solar Operated Water Desalination	63
Mirghani I. Ahmed, Yousif A. Abakr and Ahmad F. Ismail	
Chapter 24	
Theoretical and experimental evaluation of LPG as refrigerant for domestic refrigerators	
and freezers	
M.M. El-Awad, M.I. Ahmed	-
Chapter 25	
Preliminary investigation of biodiesel reactor optimization using combine CFD-Taguchi	
method	
A.K.M. Mohiuddin and Nabeel A Adeyemi	
Chapter 26	
Alternative mixing strategy for biodiesel production: mixed flow impeller characterization	n
A.K.M. Mohiuddin and Nabeel Adeyemi	
Chapter 27	
Experimental Investigation of a Multistage Evacuated Solar Still	97
Yousif, A. Abakr, Ahmad F. Ismaill and Mirghani I. Ahmed	
Chapter 28	
Modelling of electronics heat sink – Influence of the wake function generation on the	
accuracy of CFD analysis20	03
M. I. Ahmed, A. F. Ismail, Y. A. Abakr	
Chapter 29	
The effect of the operating conditions on the apparent viscosity of crude palm oil during	
•	13

Sulaiman Al-Zuhair, Yousif A. Abakr and Mirghani I. Ahmed
Chapter 30
Thermal analysis of a micro device used for detection of colorectal cancer
Mirghani I. Ahmed, Meftah Hrairi
Chapter 31
Performance of different photovoltaic cells operating under the meteorological conditions
of Singapore229
M.N.A Hawlader, Lee Poh Seng and Chua Kok Kiang
Chapter 32
Analyses of motion and drag coefficient of water droplets in a natural draught cooling
tower
Liu Baomin and M. N. A. Hawlader
Chapter 33
A solar assisted heat pump system for desalination
Zakaria Mohd. Amin, M. N. A. Hawlader and Azharul Karim
Chapter 34
Comparative study of combustion characteristics using Jatropha oil methyl esters biodiese
and diesel
A.K.M. Mohiuddin and Azan Mohd
Chapter 35
Performance of evaporator collector and air collector in a solar assisted heat pump dryer.
S. M. A. Rahman and M. N. A. Hawlader

Chapter 25

Preliminary investigation of biodiesel reactor optimization using combine CFD-Taguchi method

AKM Mohiuddin and Nabeel A Adeyemi

Department of Mechanical Engineering, Kulliyyah of Engineering,

International Islamic University Malaysia

Abstract

Biodiesel is currently produced from food and non food oil sources. The process is significantly constrained by reaction kinetics and mass transfer. In the present article, preliminary investigation of the effect of reactor configuration on yield is carried out using waste cooking oil (WCO) at different reaction parameter. The Taguchi design, with temperature, impeller speed and bottom distance as process variables at 3 levels, is used to plan, analyze and optimize the process. Optimum yield was predicted for 60°C, 600 rpm and 25 mm temperature. Statistical analysis reveals the impeller distance as most significant of the variables to affect yield and a 2D computational fluid dynamics (CFD) simulation of the mixing correlated an impeller bottom clearance of 25mm to the highest yield.

Introduction

Waste and non-food vegetable oils, from domestic and industrial palm oil activities is currently complementing raw material for the growing biodiesel industry as a result of increase in global palm oil production, with Malaysia's share of global palm oil market being over 45%. Reports in literature focus on the effects of temperature [1], ratio of alcohol to oil [2], catalyst type and amount [3]. Free Fatty Acid (FFA) [4] and water content [5] and optimization methods [6-8] on biodiesel production from WCO. With particular reference to transesterification of WCO in stirred reactors for biodiesel production, the reaction terminates early as a result of mass transfer and kinetics limitation. This has been postulated to be partly due to the hydrodynamics during mixing for stirred reactors [9]. The traditional method of process study involves the consideration of one variable at a time, which requires a number of combinations of experiments that are time, cost and labor intensive [10].

Computational fluid dynamics (CFD) methods based on the Navier-Stokes equations have become powerful tools for studying fluid flow and reactive mixing in stirred tanks with complex flow structures for different reactor configuration [11]. An advantage of CFD-based methods is that effects of variables such as impellers number and positions, impeller diameter/ vessel diameter ratio, bottom clearance, bottom shape, baffles and mixing intensity can be obtained for complex geometries and thus the problems of scaling up/down are reduced in order to arrive at an optimum mix [12]. An example is the extension of CFD for reactive flow model for fast chemical reaction to describe the flow model coupled with the kinetic of reaction in turbulent liquid flows [13]. However, few reports