

# ADVANCED MACHINING TOWARDS IMPROVED MACHINABILITY OF DIFFICULT-TO-CUT MATERIALS

---

Edited by:

A.K.M. Nurul Amin (Chief Editor)

Dr. Erry Yulian Triblas Adesta

Dr. Mohammad Yeakub Ali



IIUM PRESS

INTERNATIONAL ISLAMIC UNIVERSITY MALAYSIA


**ADVANCED MACHINING**  
**TOWARDS IMPROVED MACHINABILITY OF**  
**DIFFICULT-TO-CUT MATERIALS**

*Edited by:*

*A.K.M. Nurul Amin (Chief Editor)*

*Dr. Erry Yulian Triblas Adesta*

*Dr. Mohammad Yeakub Ali*



**IIUM Press**

Published by:  
IIUM Press  
International Islamic University Malaysia

First Edition, 2011  
©IIUM Press, IIUM

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without any prior written permission of the publisher.

Perpustakaan Negara Malaysia

Cataloguing-in-Publication Data

Advanced Machining Towards Improved Machinability of Difficult-To-Cut Materials: A.K.M.  
Nurul Amin, Erry Yulian Triblas Adesta & Mohammad Yeakub Ali

ISBN: 978-967-418-175-8

Member of Majlis Penerbitan Ilmiah Malaysia – MAPIM  
(Malaysian Scholarly Publishing Council)

Printed by :  
**IIUM PRINTING SDN.BHD.**  
No. 1, Jalan Industri Batu Caves 1/3  
Taman Perindustrian Batu Caves  
Batu Caves Centre Point  
68100 Batu Caves  
Selangor Darul Ehsan  
Tel: +603-6188 1542 / 44 / 45 Fax: +603-6188 1543  
EMAIL: iiumprinting@yahoo.com

<b>SECTION A: HEAT ASSISTED MACHINING</b>	<b>1</b>
<b>1. CHAPTER 1: INFLUENCE OF WORKPIECE PREHEATING ON CHATTER AND MACHINABILITY OF TITANIUM LOY - TI6AL4V</b>	<b>1</b>
<b>2. CHAPTER 2: MACHINABILITY IMPROVEMENT IN END OF MILLING TITANIUM ALLOY TI-6AL-4V THROUGH PREHEATING</b>	<b>9</b>
<b>3. CHAPTER 3: SOME ASPECTS OF IMPROVED MACHINABILITY IN PREHEATED MACHINING OF TITANIUM ALLOY TI-6AL-4V</b>	<b>19</b>
<b>4. CHAPTER 4: MACHINABILITY ASPECTS IN HEAT ASSISTED MACHINING OF HARDENED STEEL AISI H13 USING COATED CARBIDE TOOL</b>	<b>27</b>
<b>5. CHAPTER 5: TOOL WEAR AND SURFACE ROUGHNESS ASPECTS IN HEAT ASSISTED END MILLING OF AISI D2 HARDENED STEEL</b>	<b>35</b>
<b>6. CHAPTER 6: MODELING IN PREHEATED MACHINING OF AISI D2 HARDENED STEEL</b>	<b>43</b>
<b>7. CHAPTER 7: RELATIVE PERFORMANCES OF PREHEATING, CRYOGENIC COOLING AND HYBRID TURNING OF STAINLESS STEEL AISI 304</b>	<b>49</b>
<b>SECTION B: CHATTER AND SELECTED METHODS OF CHATTER SUPPRESSION</b>	<b>57</b>
<b>8. CHAPTER 8: ROLE OF THE FREQUENCY OF SECONDARY SERRATED TEETH IN CHATTER FORMATION DURING TURNING OF CARBON STEEL AISI 1040 AND STAINLESS STEEL</b>	<b>57</b>
<b>9. CHAPTER 9: INFLUENCE OF THE ELASTIC SYSTEM AND CUTTING PARAMETERS ON CHATTER DURING MACHINING OF MILD STEEL</b>	<b>65</b>
<b>10. CHAPTER 10: INFLUENCE OF CHATTER ON TOOL LIFE DURING END MILLING OF ALUMINIUM AND ALUMINIUM ALLOY ON VMC</b>	<b>75</b>

11	<b>CHAPTER 11: A NEW METHOD FOR CHATTER SUPPRESSION AND IMPROVEMENT OF SURFACE ROUGHNESS IN END MILLING OF MILD STEEL</b>	<b>83</b>
12	<b>CHAPTER 12: APPLICATION OF PERMANENT ELECTROMAGNET FOR CHATTER CONTROL IN END MILLING OF MEDIUM CARBON STEEL</b>	<b>91</b>
13	<b>CHAPTER 13: APPLICATION OF PERMANENT ELECTROMAGNET FOR CHATTER CONTROL IN END MILLING OF TITANIUM ALLOY - Ti6Al4V</b>	<b>99</b>
14	<b>CHAPTER 14: CHATTER SUPPRESSION IN END MILLING OF TITANIUM ALLOY Ti6Al4V APPLYING PERMANENT MAGNET CLAMPED ADJACENT TO THE WORKPIECE</b>	<b>107</b>
	<b>SECTION C: MODELING AND OPTIMIZATION IN MACHINING</b>	<b>117</b>
15	<b>CHAPTER 15: A COUPLED ARTIFICIAL NEURAL NETWORK AND RSM MODEL FOR THE PREDICTION OF CHIP SERRATION FREQUENCY IN END MILLING OF INCONEL 718</b>	<b>117</b>
16	<b>CHAPTER 16: APPLICATION OF RESPONSE SURFACE METHODOLOGY COUPLED WITH GENETIC ALGORITHM FOR SURFACE ROUGHNESS OF INCONEL 718</b>	<b>123</b>
17	<b>CHAPTER 17: DEVELOPMENT OF A MATHEMATICAL MODEL FOR THE PREDICTION OF SURFACE ROUGHNESS IN END MILLING OF STAINLESS STEEL SS 304</b>	<b>133</b>
18	<b>CHAPTER 18: DEVELOPMENT OF AN ARTIFICIAL NEURAL NETWORK ALGORITHM FOR PREDICTING THE CUTTING FORCE IN END MILLING OF INCONEL 718 ALLOY</b>	<b>143</b>
19	<b>CHAPTER 19: DEVELOPMENT OF AN ARTIFICIAL NEURAL NETWORK ALGORITHM FOR PREDICTING THE SURFACE</b>	<b>149</b>
20	<b>CHAPTER 20: DEVELOPMENT OF TOOL LIFE PREDICTION MODEL OF TiAlN COATED TOOLS DURING PART C: HIGH SPEED HARD MILLING OF AISI H13 STEEL</b>	<b>155</b>
21	<b>CHAPTER 21: MODELING FOR SURFACE ROUGHNESS IN END-MILLING OF TITANIUM ALLOY Ti-6Al-4V USING UNCOATED WC INSERTS</b>	<b>161</b>

22	<b>CHAPTER 22: MODELING OF SURFACE ROUGHNESS DURING END MILLING OF AISI H13 HARDENED TOOL STEEL</b>	<b>167</b>
23	<b>CHAPTER 23: MODELING OF TOOL LIFE USING RESPONSE SURFACE METHODOLOGY IN HARD MILLING OF AISI D2 TOOL STEEL</b>	<b>175</b>
24	<b>CHAPTER 24: OPTIMIZATION OF SURFACE ROUGHNESS IN HIGH SPEED END MILLING OF TITANIUM ALLOY Ti-6Al-4V UNDER DRY CONDITION</b>	<b>181</b>
25	<b>CHAPTER 25: COMPARISON OF SURFACE ROUGHNESS IN END-MILLING OF TITANIUM ALLOY TI-6AL-4V USING UNCOATED WC-CO AND PCD INSERTS THROUGH GENERATION OF MODELS</b>	<b>189</b>
26	<b>CHAPTER 26: ASSESSMENT OF PERFORMANCE OF UNCOATED AND COATED CARBIDE INSERTS IN END MILLING OF TI-6AL-4V THROUGH MODELLING</b>	<b>195</b>
	<b>SECTION D: CRYOGENIC AND HIGH SPEED MACHINING OF METALS AND NON METALS</b>	<b>203</b>
27	<b>CHAPTER 27: THE EFFECT OF CRYOGENIC COOLING ON MACHINABILITY OF STAINLESS STEEL DURING TURNING</b>	<b>203</b>
28	<b>CHAPTER 28: COMPARISON OF MACHINABILITY OF CERAMIC INSERT IN ROOM TEMPERATURE AND CRYOGENIC COOLING CONDITIONS DURING END MILLING INCONEL 718</b>	<b>209</b>
29	<b>CHAPTER 29: HIGH SPEED END MILLING OF SINGLE CRYSTAL SILICON SING DIAMOND COATED TOOL</b>	<b>217</b>
30	<b>CHAPTER 30: IMPLEMENTATION OF HIGH SPEED OF SILICON USING DIAMOND COATED TOOLS WITH AIR BLOWING</b>	<b>225</b>
31	<b>CHAPTER 31: ELIMINATION OF BURR FORMATION DURING END MILLING OF POLYMETHYL METHACRYLATE (PMMA) THROUGH HIGH SPEED MACHINING</b>	<b>233</b>
32	<b>CHAPTER 32: WEAR MECHANISMS IN END MILLING OF INCONEL 718</b>	<b>239</b>

33	<b>CHAPTER 33: PERFORMANCE OF UNCOATED WC-CO INSERTS IN END MILLING OF ALUMINUM SILICON CARBIDE (ALSiC)</b>	<b>247</b>
34	<b>CHAPTER 34: APPLICATION OF PCD INSERTS IN END MILLING OF ALUMINUM SILICON CARBIDE (ALSIC)</b>	<b>253</b>
35	<b>CHAPTER 35: EFFECTS OF SCRIBING WHEEL DIMENSIONS ON LCD GLASS CUTTING</b>	<b>259</b>

## Chapter 11

# A New Method for Chatter Suppression and Improvement of Surface Roughness in End Milling of Mild Steel

A.K.M. Nurul Amin<sup>1</sup>, Amir Akhyar B Abd Aziz<sup>2</sup>, Md. Asif Mahmud<sup>3</sup>

<sup>1,2,3</sup>Faculty of Engineering - International Islamic University Malaysia (IIUM)

e-mail address of corresponding author: [akamin@iiu.edu.my](mailto:akamin@iiu.edu.my)

---

### 1.0 INTRODUCTION

Chatter is an abnormal tool behaviour which it is one of the most critical problems in machining process and must be avoided to improve the dimensional accuracy and surface quality of the product [1]. The most critical limitation in machining productivity and part quality is the occurrence of the instability phenomenon called regenerative chatter [2]. According to Ravikumar and Bhaskar [2] chatter is a self-excitation phenomenon occurring in machine tools, in which the cutting process tends to decrease the machine structural damping ending with an unstable behaviour. It results in heavy vibrations of the tool, causing an inferior work piece. According to Patwari and Amin [3] chatter is a very important phenomenon that needs to be taken into consideration whenever machining process is being performed. It is very important to avoid chatter in machining as it will effect others parameters which then will increase the cost of production. In a micromilling process, where the spindle rotates an end mill to remove a portion of the workpiece, the unstable phenomenon, regenerative chatter also occurs due to changes in the chip thickness similar with the macro machining [4-5]. Altintas and Chan [6] stated that one of the major limitations on productivity in metal cutting is chatter vibration, which causes poor surface finish and tool damage. Kim et al. [7] explained that most of the drawbacks that come from chatter are excessive tool wear, noise, tool breakage, and deterioration of the surface quality. Moreover chatter also results in reduced material removal rate (MRR), increased costs in terms of time, materials and energy, as well as the environmental impact of dumping non-valid final parts and having to repeat the manufacturing process as quoted from Quintana [8].

### 2.0 EXPERIMENTAL DETAIL

#### 2.1 Experimental Setup

Cutting tests were conducted mainly on Vertical Machining Center (VMC ZPS, Model: 1060) powered by a 30 KW motor with a maximum spindle speed of 8000 rpm. Figure 1 shows the experimental set up cutting test conditions on end milling for machining of titanium alloy (Ti-6Al-4V) with TiN inserts. The main thrust of the experiments was on the study of surface roughness and monitoring of vibrations during end milling operations of medium carbon steel.