

Document details

[Back to results](#) | 1 of 1

[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)

Metrics [?](#)

0 Citations in Scopus

0 Field-Weighted Citation Impact

IOP Conference Series: Materials Science and Engineering
Volume 210, Issue 1, 6 June 2017, Article number 012033
International Technical Postgraduate Conference 2017, Tech-Post 2017; Faculty of Engineering, University of MalayaKuala Lumpur; Malaysia; 5 April 2017 through 6 April 2017; Code 128596

Performance Configuration of Raman-EDFA Hybrid Optical Amplifier for WDM Applications (Conference Paper)

Saidin, N. Taib, N.I.A., Abidin, M.S.Z., Hasbullah, N.F., Ralib, A.A.M.

Department of Electrical and Computer Engineering, International Islamic University Malaysia, Jalan Gombak, Kuala Lumpur, Malaysia

Abstract

[View references \(8\)](#)

A hybrid configuration of Raman amplifier and erbium-doped fiber amplifier (EDFA) is proposed to obtain a better performance in term of gain, noise figure and flat gain. It is based on the optimum parameter configuration of a singly-based Raman amplifier and EDFA. The best parameter for both amplification has been analyze in terms of its input signal power, pump power and their fiber length whereas the best erbium ion density has also been analyze in EDFA setup. All the parameters are varied to some values to get the optimum result. The simulation is done by using Optisystem 14.0 software. The hybrid amplifier consists of Raman amplifier with multi-pump power set up and bidirectional pump power of EDFA with the pump wavelength of 980 nm is designed and simulated in order to obtain higher gain and lower noise figure. From the simulation of the hybrid configuration, the optimum output has been achieved. The hybrid configurations exhibit the average gain of 46 dB and average noise figure of 3 dB. The flat gain obtained is between 1530 nm to 1600 nm which include C-Band and L-Band frequency with the gain bandwidth of 70 nm. © Published under licence by IOP Publishing Ltd.

Reaxys Database Information

[View Compounds](#)

Indexed keywords

Engineering controlled terms: Computer software Erbium Fiber amplifiers Noise figure Raman scattering

Compendex keywords: Hybrid amplifier Hybrid configurations Hybrid optical amplifiers Input signal power L-band frequencies Optimum parameters Pump wavelength Raman amplifier

Engineering main heading: Erbium doped fiber amplifiers

PlumX Metrics

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert](#)

[Set citation feed](#)

Related documents

Multi parameter optimization of Raman Fiber Amplifier using genetic algorithm for S band dense wavelength division multiplexed system

Singh, S. , Saini, S. , Kaler, R.S. (2014) *Optik*

Optical amplifier: A key element of high speed optical network

Kumar, A. , Sharma, A. , Sharma, V.K. (2014) *Proceedings of the 2014 International Conference on Issues and Challenges in Intelligent Computing Techniques, ICICT 2014*

64x10 Gb/s wavelength division multiplexed system by using efficient fiber Raman amplifier

Bindal, A. , Singh, S. (2015) *Optical Engineering*

View all related documents based on references

ISSN: 17578981
Source Type: Conference Proceeding
Original language: English

DOI: 10.1088/1757-899X/210/1/012033
Document Type: Conference Paper
Volume Editors: Latiff A.A.,Harun S.W.
Sponsors: University of Malaya, Faculty of Engineering,University of Malaya, Institute of Research Management and Services (IPPP)
Publisher: Institute of Physics Publishing

- 1 Keiser, G.
(2010) *Optical Fiber Communications*. Cited 1001 times.
(McGraw-Hill Education)
-
- 2 Naji, A.W., Hossain, N.
(2010) *Modeling of Hybrid EDFA/DRA: Theory, Numerical Simulation and Experimental Evaluation*
(Lambert Academic Publishing (LAP))
-
- 3 Singh, S., Kaler, R.S.
Flat-gain L-band raman-EDFA hybrid optical amplifier for dense wavelength division multiplexed system

(2013) *IEEE Photonics Technology Letters*, 25 (3), art. no. 6373695, pp. 250-252. Cited 72 times.
doi: 10.1109/LPT.2012.2231406

[View at Publisher](#)
-
- 4 Martini, M., Castellani, C., Pontes, M., Ribeiro, M., Kalinowski, H.
(2015) *Microwave and Optoelectronics Conf. (IMOC), 2015 SBMO/IEEE MTT-S International*
(IEEE)
-
- 5 Sharma, S.R., Sharma, V.R.
(2016) *2016 Signal Processing and Integrated Networks (SPIN), 2016 3rd Int. Conf. on*
(IEEE)
-
- 6 Kaushik, A., Kapoor, V.
(2016) *Communication and Signal Processing (ICCSP), 2016 Int. Conf. On; 2016*
(IEEE)
-
- 7 Cokrak, A.C., Altuncu, A.
(2004) *Journal of Electrical & Electronics Engineering*, 4.
-
- 8 Islam, M.N.
Raman amplifiers for telecommunications

(2002) *IEEE Journal on Selected Topics in Quantum Electronics*, 8 (3), pp. 548-559. Cited 339 times.
doi: 10.1109/JSTQE.2002.1016358

[View at Publisher](#)

✉ Saidin, N.; Department of Electrical and Computer Engineering, International Islamic University Malaysia, Jalan Gombak, Kuala Lumpur, Malaysia; email:norazlina@iium.edu.my
© Copyright 2017 Elsevier B.V., All rights reserved.