

Document details

< Back to results | 1 of 1

[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)
[Full Text](#)[View at Publisher](#)

International Journal of GEOMATE
Volume 13, Issue 40, December 2017, Pages 167-172

Linear microstrip resonator for UWB RFID tag (Article)

Ibrahimy, M.I., Hossain, A.K.M.Z., Motakabber, S.M.A.

Faculty of Engineering, International Islamic University Malaysia, Malaysia

Abstract

[View references \(17\)](#)

The data storage capacity is directly proportional to the number of bits on board of the tag. The main challenge in UWB tag development is to maintain higher number of bits while keeping the tag within the standard size. Higher number of bits also ensures more security and anti-tempering protection of the tagging. In addition, reducing the dimensions of the tag can lead to the possibilities of fully replacing the existing barcode identification system. A new type of planar shorted parallel coupled line microstrip resonator which can replace the existing planar rectangular type resonator has been proposed in this paper. The theoretical approximation and simulation have been performed. A 20-bit resonator has been designed and developed that works between 4.6GHz and 8.1GHz. It is found that the bit density per unit area (cm^2) is about 6.67 bit/ cm^2 has been achieved. The simulation has been performed by CST MWS 2017. The results would motivate the researchers to develop a higher bit density UWB passive RFID tag. © Int. J. of GEOMATE.

Author keywords

Barcode Planar microstrip resonator Rectangular type resonator RFID tag UWB

Funding details

Funding number	Funding sponsor	Acronym	Funding opportunities
	Ministry of Science and Technology	MOST	See opportunities by MOST ↗

Funding text

This research has been supported by the Malaysian Ministry of Science and Technology under the eScienceFund (SF14-010-0060) and the Research Management Centre, IIUM under the project of RIGS17-006-0581.

ISSN: 21862982**Source Type:** Journal**Original language:** English**DOI:** 10.21660/2017.40.181117**Document Type:** Article**Publisher:** GEOMATE International Society

References (17)

[View in search results format >](#)
[All](#) [Export](#) [Print](#) [E-mail](#) [Save to PDF](#) [Create bibliography](#)
 1 McFarlane, D., Sheffi, Y.

The Impact of Automatic Identification on Supply Chain Operations

(2003) *The International Journal of Logistics Management*, 14 (1), pp. 1-17. Cited 184 times.
doi: 10.1108/09574090310806503

[View at Publisher](#)Metrics [?](#)

0 Citations in Scopus

0 Field-Weighted Citation Impact



PlumX Metrics

Usage, Captures, Mentions,
Social Media and Citations
beyond Scopus.

Cited by 0 documents

Inform me when this document
is cited in Scopus:

[Set citation alert >](#)[Set citation feed >](#)

Related documents

Corrections To “Accurate
Distributed Inductance Of Spiral
Resonators”

Hejazi, Z.M. , Excell, P.S. , Jiang, Z.
(1998) *IEEE Microwave and
Guided Wave Letters*

Chipless radio frequency
identification tag with high
encoding capacity based on three
coding levels

Ibrahim, O.J. , Ismail, A. ,
Kamariah, N.
(2015) *ARPN Journal of
Engineering and Applied
Sciences*

Angle-based Y-shaped chipless
radio frequency identification tag

Feng, C. , Chen, X. , Han, L.
(2015) *IET Microwaves, Antennas
and Propagation*

View all related documents based
on references

- 2 Schmidt, F., Scholl, G.
Wireless SAW Identification and Sensor Systems
(2000) *Intl. Journal of High Speed Electronics and Systems*, 10 (4), pp. 1143-1191. Cited 14 times.
-
- 3 Zheng, L.-R., Shen, M., Duo, X., Tenhunen, H.
Embedded smart systems for intelligent paper and packaging
(2005) *Proceedings - Electronic Components and Technology Conference*, 2, pp. 1776-1782. Cited 4 times.
-
- 4 Schüßler, M., Damm, C., Jakoby, R.
Periodically LC Loaded Lines for RFID Backscatter Applications. in Proceedings of 1st Intl
(2007) *Congress on Advanced Electromagnetic Materials in Microwaves and Optics*, pp. 103-106.
-
- 5 Preradovic, S., Balbin, I., Karmakar, N.C., Swiegers, G.F.
Multiresonator-based chipless RFID system for low-cost item tracking
(2009) *IEEE Transactions on Microwave Theory and Techniques*, 57 (1), art. no. 4814553, pp. 1411-1419. Cited 208 times.
-
- 6 Nikitin, P.V., Lam, S., Rao, K.V.S.
Low cost silver ink RFID tag antennas
(2005) *IEEE Antennas and Propagation Society, AP-S International Symposium (Digest)*, 2 B, art. no. 1552015, pp. 353-356. Cited 78 times.
ISBN: 0780388836; 978-078038883-3
doi: 10.1109/APS.2005.1552015
[View at Publisher](#)
-
- 7 Balbin, I., Karmakar, N.C.
Phase-encoded chipless RFID transponder for large-scale low-cost applications
(2009) *IEEE Microwave and Wireless Components Letters*, 19 (8), art. no. 5175387, pp. 509-511. Cited 93 times.
doi: 10.1109/LMWC.2009.2024840
[View at Publisher](#)
-
- 8 Weng, Y.F., Cheung, S.W., Yuk, T.I., Liu, L.
Design of chipless UWB RFID system using A CPW multi-resonator
(2013) *IEEE Antennas and Propagation Magazine*, 55 (1), art. no. 6474480, pp. 13-31. Cited 20 times.
doi: 10.1109/MAP.2013.6474480
[View at Publisher](#)
-
- 9 Kalansuriya, P., Karmakar, N.C., Viterbo, E.
On the detection of frequency-spectra-based chipless RFID using UWB impaled interrogation
(2012) *IEEE Transactions on Microwave Theory and Techniques*, 60 (12), art. no. 6353612, pp. 4187-4197. Cited 28 times.
doi: 10.1109/TMTT.2012.2222920
[View at Publisher](#)