

[< Back to results](#) | 1 of 1
[Export](#)
[Download](#)
[Print](#)
[E-mail](#)
[Save to PDF](#)
[Add to List](#)
[More... >](#)
[Full Text](#)
[View at Publisher](#)

IOP Conference Series: Materials Science and Engineering
 Volume 290, Issue 1, 30 January 2018, Article number 012021
 International Conference on Advances in Manufacturing and Materials Engineering 2017, ICAMME 2017;
 International Islamic University Malaysia (IIUM), Gombak Campus Kuala Lumpur; Malaysia; 8 August 2017 through 9
 August 2017; Code 134404

An integrated approach for facilities planning by ELECTRE method (Conference Paper) [\(Open Access\)](#)

Elbishari, E.M.Y., Al Hazza, M.H.F., Adesta, E.Y.T., Abdul Rahman, N.S.B.

Department of Manufacturing and Materials Engineering, International Islamic University Malaysia (IIUM), Jalan Gombak, Kuala Lumpur, Malaysia

Abstract

[View references \(14\)](#)

Facility planning is concerned with the design, layout, and accommodation of people, machines and activities of a system. Most of the researchers try to investigate the production area layout and the related facilities. However, few of them try to investigate the relationship between the production space and its relationship with service departments. The aim of this research is to integrate different approaches in order to evaluate, analyse and select the best facilities planning method that able to explain the relationship between the production area and other supporting departments and its effect on human efforts. To achieve the objective of this research two different approaches have been integrated: Apple's layout procedure as one of the effective tools in planning factories, ELECTRE method as one of the Multi Criteria Decision Making methods (MCDM) to minimize the risk of getting poor facilities planning. Dalia industries have been selected as a case study to implement our integration the factory have been divided two main different area: the whole facility (layout A), and the manufacturing area (layout B). This article will be concerned with the manufacturing area layout (Layout B). After analysing the data gathered, the manufacturing area was divided into 10 activities. There are five factors that the alternative were compared upon which are: Inter department satisfactory level, total distance travelled for workers, total distance travelled for the product, total time travelled for the workers, and total time travelled for the product. Three different layout alternatives have been developed in addition to the original layouts. Apple's layout procedure was used to study and evaluate the different alternatives layouts, the study and evaluation of the layouts was done by calculating scores for each of the factors. After obtaining the scores from evaluating the layouts, ELECTRE method was used to compare the proposed alternatives with each other and with the existing layout; ELECTRE compares the alternatives based on their concordance and discordance indices. The alternatives were ranked from best to worst where regarding to the layouts concerned with the manufacturing area B.4 is the best alternative. © Published under licence by IOP Publishing Ltd.

Indexed keywords

Engineering controlled terms: Behavioral research Decision making Fruits Manufacture

Compendex keywords: Effective tool Electre methods Facilities planning Facility planning Integrated approach Multi-criteria decision making methods Production area Total distances

Engineering main heading: Facilities

ISSN: 17578981

Source Type: Conference Proceeding

Original language: English

DOI: 10.1088/1757-899X/290/1/012021

Document Type: Conference Paper

Sponsors:

Publisher: Institute of Physics Publishing

Metrics [?](#)

0 Citations in Scopus
 0 Field-Weighted Citation Impact



PlumX Metrics [v](#)

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)
[Set citation feed >](#)

Related documents

Synchronization of workshops, using facilities planning

Zineb, B. , Abdelghani, C. (2017) *Journal of Physics: Conference Series*

Layout design of variable size manufacturing cells using simulated annealing algorithm

Seo, Y. , Jeong, D. , Hong, D. (2006) *36th International Conference on Computers and Industrial Engineering, ICC and IE 2006*

300mm+ factory layout design and innovations for advanced semiconductor manufacturing

Huang, Y.-J. , Kuo, C.-Y. , Kao, M.-T. (2014) *ASMC (Advanced Semiconductor Manufacturing Conference) Proceedings*

View all related documents based on references

- 1 Tompkins, J.A.
(2003) *Facilities Planning*. Cited 1230 times.
(New York: John)

-
- 2 Hungerländer, P., Rendl, F.
A computational study and survey of methods for the single-row facility layout problem

(2013) *Computational Optimization and Applications*, 55 (1), pp. 1-20. Cited 26 times.
doi: 10.1007/s10589-012-9505-8

[View at Publisher](#)

-
- 3 Kothari, R., Ghosh, D.
A scatter search algorithm for the single row facility layout problem

(2014) *Journal of Heuristics*, 20 (2), pp. 125-142. Cited 18 times.
www.kluweronline.com/issn/1381-1231/
doi: 10.1007/s10732-013-9234-x

[View at Publisher](#)

-
- 4 Anjos, M.F., Fischer, A., Hungerländer, P.
(2016) *Operations Research Proc.*, pp. 17-23.
(Springer International Publishing)

-
- 5 Allahyari, M.Z., Azab, A.
(2017) *Computational Optimization in Engineering-Paradigms and Applications*
(InTech)

-
- 6 Mak, K.L., Wong, Y.S., Chan, F.T.S.
A genetic algorithm for facility layout problems

(1998) *Computer Integrated Manufacturing Systems*, 11 (1-2), pp. 113-127. Cited 60 times.
doi: 10.1016/S0951-5240(98)00018-4

[View at Publisher](#)

-
- 7 McKendall Jr., A.R., Shang, J., Kuppusamy, S.
Simulated annealing heuristics for the dynamic facility layout problem

(2006) *Computers and Operations Research*, 33 (8), pp. 2431-2444. Cited 119 times.
doi: 10.1016/j.cor.2005.02.021

[View at Publisher](#)

-
- 8 Mavridou, T.D., Pardalos, P.M.
Simulated Annealing and Genetic Algorithms for the Facility Layout Problem: A Survey

(1997) *Computational Optimization and Applications*, 7 (1), pp. 111-126. Cited 51 times.

[View at Publisher](#)
-

- 9 Samarghandi, H., Taabayan, P., Jahantigh, F.F.
A particle swarm optimization for the single row facility layout problem

(2010) *Computers and Industrial Engineering*, 58 (4), pp. 529-534. Cited 64 times.
doi: 10.1016/j.cie.2009.11.015

[View at Publisher](#)

- 10 Kulturel-Konak, S., Konak, A.
A new relaxed flexible bay structure representation and particle swarm optimization for the unequal area facility layout problem

(2011) *Engineering Optimization*, 43 (12), pp. 1263-1287. Cited 31 times.
doi: 10.1080/0305215X.2010.548864

[View at Publisher](#)

- 11 Roy, B.
The outranking approach and the foundations of electre methods

(1991) *Theory and Decision*, 31 (1), pp. 49-73. Cited 746 times.
doi: 10.1007/BF00134132

[View at Publisher](#)

- 12 Meyers, F.E.
(2005) *Manufacturing Facilities Design and Material Handling*. Cited 48 times.
(Pearson Education)

- 13 Hugonnard, J.C., Roy, B.
(1982) *Cahiers Scientifiques de la Revue Transports*

- 14 Benayoun, R., Roy, B., Sussman, B.
(1966) *ELECTRE: Une Méthode Pour Guider le Choix en Présence de Points de Vue Multiples*. Cited 50 times.
(SEMA-METRA International, Direction Scientifique) Note de travail 49 1966

© Copyright 2018 Elsevier B.V., All rights reserved.

[< Back to results](#) | 1 of 1

[^ Top of page](#)

About Scopus

[What is Scopus](#)
[Content coverage](#)
[Scopus blog](#)
[Scopus API](#)
[Privacy matters](#)

Language

[日本語に切り替える](#)
[切换到简体中文](#)
[切换到繁體中文](#)
[Русский язык](#)

Customer Service

[Help](#)
[Contact us](#)

