

[< Back to results](#) | 1 of 1[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)[Full Text](#) [View at Publisher](#)IIUM Engineering Journal
Volume 19, Issue 1, 2018, Pages 215-222

Performance of electrical discharge machining (EDM) with nickel added dielectric fluid (Article)

Khan, A.A.^a, Al Hazza, M.H.F.^a [✉](#), Mohiuddin, A.K.M.^b, Fattah, N.A.^a, Daud, M.R.C.^a [👤](#)^aDepartment of Manufacturing and Materials Engineering, International Islamic University Malaysia, Jalan Gombak, Kuala Lumpur, Malaysia^bDepartment of Mechanical Engineering, Faculty of Engineering, International Islamic University Malaysia, Jalan Gombak, Kuala Lumpur, Malaysia

Abstract

[View references \(13\)](#)

In this study, the effect of nickel powder mixed dielectric fluid on Electrical Discharge Machining (EDM) performance of mild steel has been carried out. Peak current, tool/electrode diameter and concentration of powder are the process parameters. The process performance is measured in terms of material removal rate (MRR), tool wear rate (TWR), and surface roughness (SR). The experiment has been designed using a Full Factorial in Design of Experiment (DOE) software. The research outcome is to identify the important process parameters that maximize MRR and minimize TWR and SR. The experiment has been carried out using 2 levels of current (3.5 A and 6.5 A), tool diameters (14 mm and 20 mm) and Nickel powder concentrations (0 g/l and 6 g/l). The weight of the mild steel work piece and copper electrode are measured before and after each run. Based on the results, current is the most significant parameter affecting MRR, TWR, and SR. It was also found that with added nickel powder in the dielectric fluid, the tool life is longer and surface roughness of the work piece is improved. Furthermore, it was shown that both MRR and TWR increased with the increase in tool diameter. However, SR was improved as tool diameter increased but its effect was not very significant. © 2018 International Islamic University Malaysia-IIUM.

Author keywords

Dielectric fluid

EDM

ISSN: 1511788X

Source Type: Journal

Original language: English

DOI: 10.31436/iiumej.v19i1.759

Document Type: Article

Publisher: International Islamic University Malaysia-IIUM

References (13)

[View in search results format >](#) All [Export](#) [Print](#) [E-mail](#) [Save to PDF](#) [Create bibliography](#)

- 1 Sandeep, K.
Current research trends in electrical discharge machining: a review
(2013) *Research journal of Engineering Sciences*, 2 (2), pp. 56-60. Cited 8 times.

Metrics [?](#)

0 Citations in Scopus

0 Field-Weighted
Citation Impact

PlumX Metrics [v](#)

Usage, Captures, Mentions,
Social Media and Citations
beyond Scopus.

Cited by 0 documents

Inform me when this document
is cited in Scopus:[Set citation alert >](#)[Set citation feed >](#)

Related documents

Parametric optimization of
PMEDM process with Nickel
Micro Powder suspended
dielectric and varying triangular
shapes electrodes on EN-19 steelGarg, R.K. , Ojha, K.
(2011) *Journal of Engineering
and Applied Sciences*An investigation into the effect of
nickel micro powder suspended
dielectric and varying triangular
shape electrodes on EDM
performance measures of EN-19
steelOjha, K. , Garg, R.K. , Singh, K.K.
(2012) *International Journal of
Mechatronics and Manufacturing
Systems*Electro-discharge machining of
SUS 304 stainless steel with TaC
powder-mixed dielectricZain, Z.M. , Ndaliman, M.B. ,
Khan, A.A.
(2012) *Advanced Materials
Research*

2 Webzell, S.
(2001) *That First Step into EDM in Machinery*
United Kingdom,UK: Findlay Publications Ltd

3 Livshits, A.L.
(1960) *Introduction in Electro-Erosion Machining of Metals*. Cited 3 times.
Department of Scientific & Industrial Research, Butterworth & Co., London

4 Zhao, W.S, Meng, Q.G, Wang, Z.L
The application of research on powder mixed EDM in rough machining

(2002) *Journal of Materials Processing Technology*, 129 (1-3), pp. 30-33. Cited 123 times.
doi: 10.1016/S0924-0136(02)00570-8

[View at Publisher](#)

5 Kansal, H., Singh, S., Kumar, P.
State of the art concerning powder mixed EDM
(2003) *Proceedings of the International Conference on Emerging Technology (ICET-2003) KIIT*. Cited 5 times.
Bhubansewar, India

6 Sharma, S., Kumar, A., Beri, N., Kumar, D.
Effect of aluminium powder addition in dielectric during electric discharge machining of hastelloy on machining performance using reverse polarity
(2010) *International Journal of Advanced Engineering Technology*, 1 (3), pp. 13-24. Cited 5 times.

7 Mohd Abbas, N., Solomon, D.G., Fuad Bahari, Md.
A review on current research trends in electrical discharge machining (EDM)

(2007) *International Journal of Machine Tools and Manufacture*, 47 (7-8), pp. 1214-1228. Cited 356 times.
doi: 10.1016/j.ijmachtools.2006.08.026

[View at Publisher](#)

8 Peças, P., Henriques, E.
Influence of silicon powder-mixed dielectric on conventional electrical discharge machining

(2003) *International Journal of Machine Tools and Manufacture*, 43 (14), pp. 1465-1471. Cited 109 times.
doi: 10.1016/S0890-6955(03)00169-X

[View at Publisher](#)

9 Jeswani, M.L.
Effect of the addition of graphite powder to kerosene used as the dielectric fluid in electrical discharge machining

(1981) *Wear*, 70 (2), pp. 133-139. Cited 121 times.
doi: 10.1016/0043-1648(81)90148-4

[View at Publisher](#)

- 10 Prihandana, G.S., Mahardika, M., Hamdi, M., Wong, Y.S., Mitsui, K.
Effect of micro-powder suspension and ultrasonic vibration of dielectric fluid in micro-EDM processes-Taguchi approach

(2009) *International Journal of Machine Tools and Manufacture*, 49 (12-13), pp. 1035-1041. Cited 75 times.
doi: 10.1016/j.ijmachtools.2009.06.014

[View at Publisher](#)

- 11 Kansal, H.K., Singh, S., Kumar, P.
Parametric optimization of powder mixed electrical discharge machining by response surface methodology

(2005) *Journal of Materials Processing Technology*, 169 (3), pp. 427-436. Cited 195 times.
doi: 10.1016/j.jimatprotec.2005.03.028

[View at Publisher](#)

- 12 Yan, B.H., Tsai, H.C., Huang, F.Y.
The effect in EDM of a dielectric of a urea solution in water on modifying the surface of titanium

(2005) *International Journal of Machine Tools and Manufacture*, 45 (2), pp. 194-200. Cited 122 times.
doi: 10.1016/j.ijmachtools.2004.07.006

[View at Publisher](#)

- 13 Ojha, K., Garg, R.K., Singh, K.K.
The effect of nickel micro powder suspended dielectric on EDM performance measures of EN-19 steel

(2011) *Journal of Engineering and Applied Sciences*, 6 (1), pp. 27-37. Cited 11 times.
<http://docsdrive.com/pdfs/medwelljournals/jeasci/2011/27-37.pdf>
doi: 10.3923/jeasci.2011.27.37

[View at Publisher](#)

🔍 Al Hazza, M.H.F.; Department of Manufacturing and Materials Engineering, International Islamic University Malaysia, Jalan Gombak, Kuala Lumpur, Malaysia; email:muataz@iiium.edu.my

© Copyright 2018 Elsevier B.V., All rights reserved.

[< Back to results](#) | 1 of 1

[^ Top of page](#)

About Scopus

[What is Scopus](#)
[Content coverage](#)
[Scopus blog](#)
[Scopus API](#)
[Privacy matters](#)

Language

[日本語に切り替える](#)
[切换到简体中文](#)
[切换到繁體中文](#)
[Русский язык](#)

Customer Service

[Help](#)
[Contact us](#)

ELSEVIER

[Terms and conditions](#) [Privacy policy](#)

Copyright © 2018 Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

Cookies are set by this site. To decline them or learn more, visit our [Cookies page](#).

 RELX Group™

