


< Back to results | < Previous 2 of 4 Next >

Export Download Print E-mail Save to PDF Add to List More... >

[Full Text](#) View at Publisher

IOP Conference Series: Materials Science and Engineering
Volume 290, Issue 1, 30 January 2018, Article number 012004
International Conference on Advances in Manufacturing and Materials Engineering 2017, ICAMME 2017;
International Islamic University Malaysia (IIUM), Gombak Campus Kuala Lumpur; Malaysia; 8 August 2017 through 9
August 2017; Code 134404

Optimization of TiO₂ thin film thickness for dye sensitized solar cell applications (Conference Paper) [\(Open Access\)](#)

Al-Bat'Hi, S.A.M. , Ahmed, N., Othman, R., Othman, M.

Department of Manufacturing and Materials Engineering, International Islamic University Malaysia (IIUM), Jalan Gombak, Kuala Lumpur, Malaysia

Abstract

[View references \(13\)](#)

Dye sensitized solar cells (DSSCs) rely on the absorption of photons by the dye molecules which are transported to the conduction band of the TiO₂ electrode. The microstructure, energy gap and the absorption spectra of the TiO₂ electrodes highly affects the efficiency of the cell. In this paper, the absorption spectra and energy gap has been studied by varying the thickness of the TiO₂ paste. Nanocrystalline TiO₂ thin films were deposited on ITO glass substrate with three different thickness (4.54µm, 7.12µm and 12.3µm) by using doctor blade method. After deposition all the samples were sintered at 450°C after deposition to enhance the particle bonding and for achieving better adhesion. The samples were characterized by UV-VIS spectra for determining the absorption spectra and Scanning Electron Microscopy (SEM) for investigating the thickness and the surface morphology. Fabricating the electrodes with different thickness showed significant changes in the energy gap and from the results it can be concluded that the energy gap increases with the increased thickness. The highest energy gap of 2.25eV and absorption 3.791 was achieved by 12.3µm thick sample. The absorption spectra also shows better absorption throughout the whole visible light range but the SEM images suggests that 12.3µm thick sample shows cracks all over the deposited region which will cause current leakage when the cell is assembled. Therefore, the optimum result was achieved by 7.12µm thick sample providing 1.9 eV energy gap and 3.91 absorption peak. © Published under licence by IOP Publishing Ltd.

Indexed keywords

Engineering controlled terms:

Absorption spectra Deposition Electrodes Electromagnetic wave absorption Energy gap
Film thickness ITO glass Light Manufacture Nanocrystals
Nanostructured materials Scanning electron microscopy Solar cells Substrates
Thin films Titanium dioxide

Engineering uncontrolled terms

Absorption peaks Current leakage Different thickness Doctor blade method
Glass substrates Nanocrystalline TiO₂ Particle bondings TiO₂ thin films

Engineering main heading:

Dye - sensitized solar cells

Metrics

0 Citations in Scopus
0 Field-Weighted Citation Impact



PlumX Metrics 

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)

[Set citation feed >](#)

Related documents

Effect on different amount of TiO₂ P25 for dye-sensitized solar cell

Fakhriah, R., Ahmad, M.K., Hamed, N.A.F. (2017) *Journal of Telecommunication, Electronic and Computer Engineering*

Double functions of porous TiO₂ electrodes on CH₃NH solar cells: Enhancement of perovskite crystal transformation and prohibition of short circuiting

Murugadoss, G., Mizuta, G., Tanaka, S. (2014) *APL Materials*

Aqueous, Screen-Printable Paste for Fabrication of Mesoporous Composite Anatase-Rutile TiO₂ Nanoparticle Thin Films for (Photo)electrochemical Devices

Yasin, A., Guo, F., Demopoulos, G.P. (2016) *ACS Sustainable Chemistry and Engineering*

ISSN: 17578981

DOI: 10.1088/1757-899X/290/1/012004

References (13)

View in search results format >

Find more related documents in Scopus based on:

Authors > Keywords >

 All Export Print E-mail Save to PDF Create bibliography

- 1 Sedghi, A., Miankushki, H.N.
The effect of drying and thickness of TiO₂ electrodes on the photovoltaic performance of dye-sensitized solar cells

(2015) *International Journal of Electrochemical Science*, 10 (4), pp. 3354-3362. Cited 12 times.
<http://www.electrochemsci.org/papers/vol10/100403354.pdf>

- 2 Dhungel, S.K., Park, J.G.
Optimization of paste formulation for TiO₂ nanoparticles with wide range of size distribution for its application in dye sensitized solar cells

(2010) *Renewable Energy*, 35 (12), pp. 2776-2780. Cited 41 times.
doi: 10.1016/j.renene.2010.04.031

[View at Publisher](#)

- 3 Dette, C., Pérez-Osorio, M.A., Kley, C.S., Punke, P., Patrick, C.E., Jacobson, P., Giustino, F., (...), Kern, K.
TiO₂ anatase with a bandgap in the visible region

(2014) *Nano Letters*, 14 (11), pp. 6533-6538. Cited 110 times.
<http://pubs.acs.org/journal/nalefd>
doi: 10.1021/nl503131s

[View at Publisher](#)

- 4 Ming-Hsiu, Fu-Lin, Shyh, S.
(2010) *Int. J. Mol. Sci.*, 11 (1), pp. 329-353.

- 5 Peng Qin, Y., Qiang
(2012) *Int. J. Photoenergy*, 12, pp. 3100-3221.

- 6 Ito, S., Chen, P., Comte, P., Nazeeruddin, M.K., Liska, P., Péchy, P., Grätzel, M.
Fabrication of screen-printing pastes from TiO₂ powders for dye-sensitised solar cells

(2007) *Progress in Photovoltaics: Research and Applications*, 15 (7), pp. 603-612. Cited 749 times.
doi: 10.1002/pip.768

[View at Publisher](#)

- 7 Meen, T.H., Tsai, J.K., Tu, Y.S., Wu, T.C., Hsu, W.D., Chang, S.-J.
Optimization of the dye-sensitized solar cell performance by mechanical compression

(2014) *Nanoscale Research Letters*, 9 (1). Cited 6 times.
<http://www.springer.com/materials/nanotechnology/journal/11671>
doi: 10.1186/1556-276X-9-523

[View at Publisher](#)

□ 8 Jena, A., Mohanty, S.P., Kumar, P., Naduvath, J., Gondane, V., Lekha, P., Das, J., (...), Bhargava, P.

Dye sensitized solar cells: A review

(2012) *Transactions of the Indian Ceramic Society*, 71 (1), pp. 1-16. Cited 51 times.
doi: 10.1080/0371750X.2012.689503

[View at Publisher](#)

□ 9 Qiang, Y.Q., Saehana, S.

(2011) *Electrochem. Sci.*, 11, pp. 215-228.

□ 10 Ito, S., Murakami, T.N., Zakeeruddin, S.M., Yazawa, T., Mizuno, M., Kayama, S., Grätzel, M.

Effects of TiO₂ particle size on the performance of dye-sensitized solar cells using ionic liquid electrolytes

(2014) *Nano*, 9 (5), art. no. 1440010. Cited 5 times.
<http://www.worldscinet.com/nano/nano.shtml>
doi: 10.1142/S1793292014400104

[View at Publisher](#)

□ 11 Singh, M., Mohan, M., Ahlawat, D.S.

(2015) *Nt. J. Human. Soc. Sci. Res.*, 5, pp. 35-41.

□ 12 Xu, S., Zhou, C.-H., Yang, Y., Hu, H., Sebo, B., Chen, B.-L., Tai, Q.-D., (...), Zhao, X.

Effects of ethanol on optimizing porous films of dye-sensitized solar cells

(2011) *Energy and Fuels*, 25 (3), pp. 1168-1172. Cited 23 times.
doi: 10.1021/ef101546a

[View at Publisher](#)

□ 13 Gemeiner, P., Mikula, M.

(2013) *J. Chem. Sci.*, 6, pp. 29-34. Cited 13 times.

© Copyright 2018 Elsevier B.V., All rights reserved.

[< Back to results](#) | [< Previous](#) 2 of 4 [Next >](#)

[^ Top of page](#)

About Scopus

[What is Scopus](#)
[Content coverage](#)
[Scopus blog](#)
[Scopus API](#)
[Privacy matters](#)

Language

[日本語に切り替える](#)
[切换到简体中文](#)
[切换到繁體中文](#)
[Русский язык](#)

Customer Service

[Help](#)
[Contact us](#)

