

[Free Full Text from Publisher](#)
[Full Text Options](#)

[Save to EndNote online](#)
[Add to Marked List](#)

◀ 1 of 1 ▶

## A comparison between destructive and non-destructive techniques in determining coating thickness

 By: [Haruer, F I \(Haruer, F. I.\)<sup>\[1\]</sup>](#); [Suryanto \(Suryanto\)<sup>\[1\]</sup>](#); [Ani, MH \(Ani, M. H.\)<sup>\[1\]</sup>](#); [Mahmood, MH \(Mahmood, M. H.\)<sup>\[1\]</sup>](#)
[View ResearcherID and ORCID](#)

INTERNATIONAL CONFERENCE ON ADVANCES IN MANUFACTURING AND MATERIALS ENGINEERING (ICAMME 2017)

Book Group Author(s): IOP

Book Series: IOP Conference Series-Materials Science and Engineering

Volume: 290

Article Number: UNSP 012020

DOI: 10.1088/1757-899X/290/1/012020

Published: 2018

Document Type: Proceedings Paper

### Conference

Conference: International Conference on Advances in Manufacturing and Materials Engineering (ICAMME)

Location: Int Islam Univ, Kuala Lumpur, MALAYSIA

Date: AUG 08-09, 2017

### Abstract

Measuring coating thickness is an important part in research works related to coating applications. In general, techniques for measuring coating thickness may be divided into destructive and non-destructive methods which are commonly used depending on the applications. The objective of this study is to compare two methods measuring the coating thickness of electroplating copper coating on the austenitic stainless-steel substrate. The electroplating was carried out in a solution containing 200 g/L CuSO<sub>4</sub>, 100 g/L H<sub>2</sub>SO<sub>4</sub> at room temperature and current of 40 mA/cm<sup>2</sup> during 20,40,60,80 and 100 mins as coating periods. And the coating thickness was measured by two methods, cross sectional analysis as a destructive technique and weight gain as a non-destructive technique. The results show that at 20 mins coating time interval, the thickness measured by cross sectional method was 16.67 μm and by weight gain method was 17.37 μm, with difference of 0.7 μm and percentage error of 4.11%. This error increased to 5.27% at 100 mins time interval, where the values of the thickness measured by cross sectional and weight gain were 86.33 μm and 81.9 μm respectively, and the difference was 4.43 μm. Moreover, though the weight gain method is fast and gives the indication for the termination of a coating process, information regarding the uniformity, porosity and the presence of cracks cannot be obtained. On the other hand, determining the coating thickness using destructive method will damage the sample.

### Author Information

Reprint Address: Suryanto (reprint author)

+ IUM, Dept Mfg &amp; Mat Engr, Jalan Gombak, Kuala Lumpur 53100, Malaysia.

Addresses:

+ [ 1 ] IUM, Dept Mfg &amp; Mat Engr, Jalan Gombak, Kuala Lumpur 53100, Malaysia

 E-mail Addresses: [surya@ium.edu.my](mailto:surya@ium.edu.my)

### Publisher

IOP PUBLISHING LTD, DIRAC HOUSE, TEMPLE BACK, BRISTOL BS1 6BE, ENGLAND

### Categories / Classification

Research Areas: Engineering; Materials Science

Web of Science Categories: Engineering, Manufacturing; Engineering, Mechanical; Materials Science, Multidisciplinary

### Document Information

Language: English

Accession Number: WOS:000430743400020

ISSN: 1757-8981

### Citation Network

In Web of Science Core Collection

0

Times Cited

Create Citation Alert

9

Cited References

[View Related Records](#)

### Use in Web of Science

Web of Science Usage Count

0

Last 180 Days

0

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection

- Conference Proceedings Citation Index-Science

[Suggest a correction](#)

If you would like to improve the quality of the data in this record, please [suggest a correction](#).

**Other Information**

IDS Number: BK0MJ

Cited References in Web of Science Core Collection: 9

Times Cited in Web of Science Core Collection: 0

[See fewer data fields](#)

◀ 1 of 1 ▶

**Cited References: 9****Showing 9 of 9** [View All in Cited References page](#)*(from Web of Science Core Collection)*

- |    |   |                         |
|----|---|-------------------------|
| 1. | Title: [not available]<br>By: Beamish, D.<br>Metal Finishing Volume: 97 Pages: 548-550 Published: 1999  | <b>Times Cited: 1</b>   |
| 2. | <a href="#">Non-Destructive Techniques Based on Eddy Current Testing</a><br>By: Garcia-Martin, Javier; Gomez-Gil, Jaime; Vazquez-Sanchez, Ernesto<br>SENSORS Volume: 11 Issue: 3 Pages: 2525-2565 Published: MAR 2011   | <b>Times Cited: 216</b> |
| 3. | Title: [not available]<br>Patent Number: 8,969,833<br>Inventor/Assignee: Gongora, G J; Vail, M A.<br>U. S. Patent Published: 2015<br>Washington, DC: U. S. Patent.  | <b>Times Cited: 1</b>   |
| 4. | Title: [not available]<br>By: Haider, F; Ani, M; Mahmood, M; et al.<br>Materials Science and Engineering Volume: 204 Pages: 12-17 Published: 2017<br><a href="#">[Show additional data]</a>   | <b>Times Cited: 1</b>   |
| 5. | <a href="#">Evaluation of the Effects of Copper Electroplating Parameters on the Adhesion Using Response Surface Methodology</a><br>By: Haider, F.I.; Suryanto; Ani, M.H.; et al.<br>Applied Mechanics and Materials Volume: 864 Pages: 121-6 Published: 2017   | <b>Times Cited: 1</b>   |
| 6. | <a href="#">X-ray fluorescence spectrometry in art and archaeology</a><br>By: Mantler, M; Schreiner, M<br>X-RAY SPECTROMETRY Volume: 29 Issue: 1 Pages: 3-17 Published: JAN-FEB 2000  | <b>Times Cited: 170</b> |
| 7. | Title: [not available]<br>By: Petrilli, C.<br>Metal Finishing Volume: 99 Pages: 810-813 Published: 2001   | <b>Times Cited: 1</b>   |
| 8. | <a href="#">Validation of Terahertz Coating Thickness Measurements Using X-ray Microtomography</a><br>By: Russe, Isabelle-Sophie; Brock, Daniela; Knop, Klaus; et al.<br>MOLECULAR PHARMACEUTICS Volume: 9 Issue: 12 Pages: 3551-3559 Published: DEC 2012   | <b>Times Cited: 31</b>  |
| 9. | <a href="#">Research on strategies to improve measurement of coating thickness in hemispherical steel shells for an inclined eddy current sensor</a><br>By: Zhang, Dongli; Wu, Meixian; Li, Hongmei; et al.<br>INTERNATIONAL JOURNAL OF APPLIED ELECTROMAGNETICS AND MECHANICS Volume: 52 Issue: 3-4 Pages: 1409-1415 Published: 2016 | <b>Times Cited: 1</b>   |

**Showing 9 of 9** [View All in Cited References page](#)