



Document details

< Back to results | 1 of 1

[Export](#)
[Download](#)
[Print](#)
[E-mail](#)
[Save to PDF](#)
[Add to List](#)
[More... >](#)
[Full Text](#)
[View at Publisher](#)

Ionic
Volume 25, Issue 6, 1 June 2019, Pages 2657-2667

An investigation on the abnormal trend of the conductivity properties of CMC /PVA-doped NH₄Cl-based solid biopolymer electrolyte system

(Article)

 Mazuki, N.F.^a, Fuzlin, A.F.^a, Saadiah, M.A.^{a,b}, Samsudin, A.S.^a [✉](#) [👤](#)
^aIonic Materials Team, Advanced Materials, Faculty of Industrial Sciences & Technology, Universiti Malaysia Pahang, Kuantan, Pahang 26300, Malaysia

^bDepartment of Chemistry, Centre for Foundation Studies, International Islamic University Malaysia, Gambang, Pahang 26300, Malaysia

Abstract

The present work was carried out to investigate the abnormal trend of electrochemical properties of solid biopolymer electrolytes (SBEs) system -based carboxymethyl cellulose (CMC) blended with polyvinyl alcohol (PVA)-doped NH₄Cl. The SBEs system was prepared via solution casting technique and analyzed through Fourier transform infrared (FTIR) spectroscopy, thermogravimetric analysis (TGA), X-ray diffraction (XRD) analysis, and electrical impedance spectroscopy (EIS). Complexation was observed with the changes of peaks at 1065 cm⁻¹, 1598 cm⁻¹, 2912 cm⁻¹, and 3396 cm⁻¹ that corresponds to C–O–C, C=O of COO⁻ stretching, C–H stretching, and O–H stretching, respectively, of CMC /PVA blend system upon the addition of NH₄Cl. The decrease of the amorphousness and the increase of weight loss demonstrated the abnormal observation of the ionic conductivity when (1–5 wt%) NH₄Cl was added in the SBEs system which was lower than the un-doped SBEs system. It was also observed that the highest ionic conductivity at $8.86 \times 10^{-5} \text{ Scm}^{-1}$ was achieved by the sample containing 6 wt% of NH₄Cl. The temperature dependence of the SBEs system is found to be governed by the Arrhenius rule. Through the IR deconvolution technique, the conductivity of CMC /PVA-NH₄Cl SBEs system was shown to be primarily influenced by the ionic mobility and diffusion coefficient of the ions. © 2018, Springer-Verlag GmbH Germany, part of Springer Nature.


SciVal Topic Prominence ⓘ

Topic: Ionic conductivity | Solid electrolytes | Electrolyte films

Prominence percentile: 99.778 ⓘ

Chemistry database information ⓘ

Substances



Author keywords

Abnormal conductivity | Amorphous phase | Solid biopolymer electrolytes (SBEs) | Thermal stability

Metrics ⓘ View all metrics >

4 Citations in Scopus

2.94 Field-Weighted Citation Impact



PlumX Metrics

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 4 documents

Study on the effect of lithium nitrate in ionic conduction properties based alginate biopolymer electrolytes

 Fuzlin, A.F. , Bakri, N.A. , Sahraoui, B. (2020) *Materials Research Express*

Investigation on favourable ionic conduction based on CMC-K carrageenan proton conducting hybrid solid bio-polymer electrolytes for applications in EDLC

 Zainuddin, N.K. , Rasali, N.M.J. , Mazuki, N.F. (2020) *International Journal of Hydrogen Energy*

Studies on ionic conduction properties of modification CMC-PVA based polymer blend electrolytes via impedance approach

 Mazuki, N.F. , Abdul Majeed, A.P.P. , Nagao, Y. (2020) *Polymer Testing*
[View all 4 citing documents](#)

Inform me when this document is cited in Scopus:

[Set citation alert >](#)
[Set citation feed >](#)

Related documents

Indexed keywords

Find more related documents in Scopus based on:

Engineering controlled terms:

[Biomolecules](#) [Chlorine compounds](#) [Fourier transform infrared spectroscopy](#)
[Ionic conductivity](#) [Polyelectrolytes](#) [Polymer blends](#) [Solid electrolytes](#)
[Temperature distribution](#) [Thermodynamic stability](#) [X ray diffraction analysis](#)

Engineering uncontrolled terms

[Amorphous phase](#) [Biopolymer electrolyte](#) [Carboxymethyl cellulose](#)
[Conductivity properties](#) [Deconvolution techniques](#) [Electrical impedance spectroscopy](#)
[Poly \(vinyl alcohol\) \(PVA\)](#) [Solution-casting technique](#)

Engineering main heading:

[Thermogravimetric analysis](#)

PaperChem Variable:

[Carboxymethyl Cellulose](#) [Chlorine Compounds](#) [Conductivity](#) [Gravimetry](#)
[Polyelectrolytes](#) [Stretching](#) [Systems](#) [Thermal Analysis](#)

[Authors >](#) [Keywords >](#)

ISSN: 09477047

Source Type: Journal

Original language: English

DOI: 10.1007/s11581-018-2734-9

Document Type: Article

Publisher: Institute for Ionics

[Samsudin, A.S.](#); Ionic Materials Team, Advanced Materials, Faculty of Industrial Sciences & Technology, Universiti Malaysia Pahang, Kuantan, Pahang, Malaysia; email:ahmadsalihin@ump.edu.my

© Copyright 2019 Elsevier B.V., All rights reserved.

[Back to results](#) | 1 of 1

[Top of page](#)

About Scopus

[What is Scopus](#)

[Content coverage](#)

[Scopus blog](#)

[Scopus API](#)

[Privacy matters](#)

Language

[日本語に切り替える](#)

[切换到简体中文](#)

[切换到繁體中文](#)

[Русский язык](#)

Customer Service

[Help](#)

[Contact us](#)

ELSEVIER

[Terms and conditions](#) [Privacy policy](#)

Copyright © Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

We use cookies to help provide and enhance our service and tailor content. By continuing, you agree to the use of cookies.

RELX