

Embedding Defeasible Argumentation in the Semantic Web: an ontology-based approach

Sergio Alejandro Gómez^{†1}

Carlos Iván Chesñevar[‡]

Guillermo Ricardo Simari^{†1}

[†]Laboratorio de Investigación y Desarrollo en Inteligencia Artificial (LIDIA)²
Depto. Cs. e Ing. de la Computación – Universidad Nacional del Sur
Alem 1253 (8000) Bahía Blanca - Argentina – E-mail: {sag,grs}@cs.uns.edu.ar

[‡]Grupo de Investigación en Inteligencia Artificial
Departament d'Informàtica — Universitat de Lleida
Campus Cappont – C/Jaume II, 69 – E-25001 Lleida, SPAIN
Tel/Fax: (+34) (973) 70 2764 / 2702 – E-mail: cic@eps.udl.es

Abstract

The Semantic Web is a project intended to create a universal medium for information exchange by giving *semantics* to the content of documents on the Web by means of *ontology definitions*. Ontologies intended for knowledge representation in intelligent agents rely on common-sense reasoning formalizations. *Defeasible argumentation* has emerged as a successful approach to model common-sense reasoning. Recent research has linked argumentation with belief revision in order to model the dynamics of knowledge. This paper outlines an approach which combines ontologies, argumentation and belief revision by defining an ontology algebra. We suggest how different aspects of ontology integration can be defined in terms of defeasible argumentation and belief revision.

Keywords: Defeasible argumentation, Semantic web, Ontology algebra.

1 Introduction

Although the World Wide Web is a vast repository of information, its utility is restricted by limited facilities for searching and integrating different kinds of data, as search for queries is mostly *syntax-based* (e.g., using keywords). The Semantic Web [2] has emerged as a project intended to create a universal medium for information exchange by giving *semantics* to the content of documents on the Web. A common way to provide semantics to documents on the web is through the use of *ontology definitions*. Common problems from common-sense reasoning (e.g., reasoning with uncertainty or with incomplete and potentially inconsistent information) are present when defining ontologies. In recent years, defeasible argumentation has succeeded as approach to formalize such common-sense reasoning [6, 16]. In this preliminary report, we explore different alternatives for defining an ontology algebra whose semantics is based on defeasible argumentation and belief revision. We suggest how different aspects of ontology integration can be defined in terms of defeasible argumentation and belief revision.

2 Defeasible Logic Programming: Fundamentals

Defeasible Logic Programming (DeLP) [9] provides a language for knowledge representation and reasoning that uses *defeasible argumentation* [6, 16, 17] to decide between contradictory conclusions through a *dialectical analysis*. Codifying knowledge by means of a DeLP program provides

¹Partially funded by PICT 2002 Nro. 13096 (Agencia Nacional de Promoción Científica y Tecnológica).

²LIDIA is a member of IICyTI Instituto de Investigación en Ciencia y Tecnología Informática.

a good trade-off between expressivity and implementability. Recent research has shown that DeLP provides a suitable framework for building real-world applications (*e.g.*, clustering algorithms [11], intelligent web search [4] and knowledge management [3]) that deal with incomplete and potentially contradictory information. In a defeasible logic program $\mathcal{P} = (\Pi, \Delta)$, a set Δ of defeasible rules $P \prec Q_1, \dots, Q_n$, and a set Π of strict rules $P \leftarrow Q_1, \dots, Q_n$ can be distinguished. An *argument* $\langle \mathcal{A}, H \rangle$ is a minimal non-contradictory set of ground defeasible clauses \mathcal{A} of Δ that allows to derive a ground literal H possibly using ground rules of Π . Since arguments may be in conflict (concept captured in terms of a logical contradiction), an attack relationship between arguments can be defined. A criterion is usually defined to decide which argument of two conflicting arguments is preferred. In order to determine whether a given argument \mathcal{A} is ultimately undefeated (or *warranted*), a dialectical process is recursively carried out. Given a DeLP program \mathcal{P} and a query H , the final answer to H wrt \mathcal{P} takes such dialectical analysis into account. The answer to a query can be either one of: *yes*, *no*, *undecided*, or *unknown*.

3 Belief Revision: Fundamentals

Belief Revision systems are logical frameworks for modelling the dynamics of knowledge. In dialogues between two agents, it is very common that an agent does not fully accept all the information provided by the other, but rather only parts of it. A *revision operator* is a function that maps sets of sentences K and A to a new set of sentences. In particular, in [8] the mechanism of a revision operator $K \circ A$ by a set of sentences with partial acceptance is defined as follows [8]: (1) the input set A is initially accepted, and (2) all possible inconsistencies of $K \cup A$ are removed. The mechanism of this operator is to add A to K and then eliminate from the result all possible inconsistency by means of an incision function that makes a “cut” over each minimally inconsistent subset of $K \cup A$ [8]. In Falappa *et al.* work, beliefs are split into two distinguished sets: (1) *particular beliefs* K_P , that are represented by ground facts, and (2) *general beliefs* K_G , that will be represented by closed material implications. Thus, each belief base K has the form $K_P \cup K_G$ where $K_P \cap K_G = \emptyset$. When doing a kernel revision by a set of sentences, an incision function is needed to make a cut upon every set; *i.e.*, it necessary to determine which beliefs must be given up in the revision process. There are two possible policies: (1) discard particular beliefs, and (2) discard general beliefs. In the latter, at least one sentence should be discarded. Falappa, Kern-Isberner and Simari [8] propose a refined characterization of revision by preserving retracted beliefs with a different status: retracted general beliefs will be preserved as *defeasible rules*. They also introduce a revision operator that generates defeasible conditionals from a revision operator upon belief bases represented in a first order language. It may be the case that in the revision process a conditional sentence of the form $(\forall(X))(\alpha(X) \rightarrow \beta(X))$ has to be eliminated. This can occur because new incoming information results in an inconsistency. One of the following cases may occur: (1) there exists some individual satisfying α but not satisfying β , and (2) there exists some individual satisfying $\neg\beta$ but not satisfying $\neg\alpha$. Eliminating $(\forall(X))(\alpha(X) \rightarrow \beta(X))$ from the knowledge base would produce too much loss of information. As an alternative, in [8] the authors propose a transformation to change it into $\beta \prec \alpha$.

Definition 1 (Positive/negative transformation [8]) Let $\delta = (\forall X_1 \dots X_n)(\alpha \rightarrow \beta)$ be a material implication in \mathcal{L}^+ . A positive transformation of δ , noted by $T^+(\delta)$, is a sentence of the form $\beta \prec \alpha$; a negative transformation of δ , noted by $T^-(\delta)$, is a sentence of the form $\neg\beta \prec \neg\alpha$.

Definition 2 (Kernel (partial meet) composed revision [8]) Let (K, Δ) be a knowledge structure, (\circ) an operator of kernel (partial meet) revision by a set of sentences for K and A a set of sentences. The kernel (partial meet) composed revision of (K, Δ) wrt A is defined as: $(K, \Delta) \star A = (K', \Delta')$ such that $K' = K \circ A$

- *create* : *d-Ontology*
- *addStrictRule* : *d-Ontology* × *StrictRule* ↦ *d-Ontology*
- *addDefeasibleRule* : *d-Ontology* × *DefeasibleRule* ↦ *d-Ontology*
- *conclusion* : *d-Ontology* × *Fact* ↦ *Answer*
- *translate* : *OWLOntology* ↦ *d-Ontology*
- *isConsistent* : *OWLOntology* ↦ *Bool*
- *areClassesCoherent* : *OWLOntology* ↦ *Bool*
- *integrate* : *d-Ontology* × *d-Ontology* ↦ *d-Ontology*
- *redefine* : *d-Ontology* × *d-Ontology* ↦ *d-Ontology*

Figure 1: Possible signature for an algebra ontology using arguments

and $\Delta' = \Delta \cup \Delta'_1 \cup \Delta'_2$ where:

$$\begin{aligned}\Delta'_1 &= \{\alpha \rightarrow true \mid \alpha \in (K_P \setminus K \circ A)\} \\ \Delta'_2 &= \{T^+(\alpha) \mid \alpha \in (K_G \setminus K \circ A)\} \cup \{T^-(\alpha) \mid \alpha \in (K_G \setminus K \circ A)\}.\end{aligned}$$

The set K' contains the revised undefeasible beliefs, Δ'_1 is the transformation in defeasible rules of particular beliefs (also called *assumptions*) eliminated from K whereas Δ'_2 is the transformation of general beliefs eliminated from K into defeasible rules.

4 An Argument-Based Ontology Algebra for the Semantic Web

An *ontology* is a specification of a conceptualization. In computer science, ontologies establish a joint terminology between members of a community of interest. These members can be human or automated agents. In the context of the semantic web, an OWL ontology [15] is just a collection of information, generally information about classes and properties. In our approach, an ontology will be associated with a DeLP program representing knowledge, in which facts and strict rules are distinguished. More formally:

Definition 3 (*d-Ontology*) A *d-Ontology* is a DeLP program $\mathcal{P} = (K_P \cup K_G, \Delta)$ where K_P stands for particular knowledge (facts about individuals), K_G stands for general knowledge (strict rules about relations holding among individuals), and Δ stands for defeasible knowledge (defeasible rules).

Next we will discuss some elements involved in the formalization of an ontology algebra based on DeLP and Belief Revision. We present a possible signature for our algebra in Fig. 1. The specification of some of these operations is given in a functional programming-like style in Fig. 2.

Next we will briefly analyze some of the operations and their implementations. Operation *create* allows to create an empty ontology (empty DeLP program). Operation *addDefeasibleRule* allows to expand a given ontology by including a new defeasible rule (which can be easily modelled by set union). Operations *addStrictRule* and *integrate* are more complex to define, and are characterized in terms of a \star operator. Part of our current research involves providing a suitable formalization of this operator. To do this, we are using results from belief revision theory as described in Section 3. The *conclusion* operation allows to assign an epistemic status to literals.

Operation *translate* is intended to link an XML-based OWL ontology [15] with a d-Ontology formalization. In the last years, the eXtended Markup Language (XML) has emerged as a standard for data interchange on the Web. XML allows authors to create their own markup. However, from

- $create = (\emptyset, \emptyset)$
- $addDefeasibleRule((\Pi, \Delta), R) = (\Pi, \Delta \cup \{R\})$
- $addStrictRule((\Pi, \Delta), R) = (\Pi, \Delta) \star \{R\}$
- $conclusion(Ont, H) = \text{call DeLP Engine Warrant Procedure}(Ont, H)$
- $translate(OWL Ont) = \text{call Hunter Algorithm}(OWL Ont)$
- $integrate((\Pi_1, \Delta_1), (\Pi_2, \Delta_2)) = (\Pi, \Delta)$, where: $(\Pi, \Delta') = (\Pi_1, \Delta_1) \star \Pi_2$, and, $\Delta = \Delta_1 \cup \Delta_2 \cup \Delta'$

Figure 2: Implementation for some of the operations of the ontology algebra

a computational perspective, user-defined tags carry as much semantics as standard HTML tags, as a computer does not simply know the relationships existing among them solely on the basis of their identifiers. Hunter proposed an algorithm that is capable of translating XML files into a set of first-order facts [12]. We think that this approach could be useful in our setting since it allows to encode an XML document as a set of facts in a d-Ontology.

5 Ongoing research. Conclusions

In this paper we have briefly outlined the main elements of a research line which integrates ontology theory, defeasible argumentation, and belief revision. A formalization of our proposal is underway on the basis of XML-based OWL syntax. In the literature, other authors claim that argumentation seems to be an appropriate tool for solving the problem of *ontology integration* [1]. Nevertheless, the results obtained so far seem still incipient.

Our research is also oriented towards consolidating such ontology integration. Results in this direction have been achieved by defining *interoperability* between ontologies. To reach interoperability two problems must be dealt with [18]: *structural heterogeneity* and *semantic heterogeneity*. Structural heterogeneity concerns the different representation of information as the information described by the same ontology can be represented in different ways. Semantic heterogeneity concerns the intended meaning of the described information; *e.g.*, information about persons can be described in different ontologies. Wiesman and Roos [18] proposes a domain independent method for handling interoperability problems by learning a mapping between ontologies. The learning method is based on exchanging instances of concepts that are defined in the ontologies. Although Wiesman and Roos' proposal is based on likelihood estimations, we think a similar approach could be used in the context of d-Ontologies on the basis of the *P-DeLP* argumentative framework, which extends DeLP knowledge representation capabilities by including vague knowledge and uncertainty [5, 7]. A more involved analysis for ontology integration might need other additional elements (such as resonance measures and similar criteria [13, 14]) that could be embedded into our d-ontologies to enrich their expressivity and representation capabilities.

Part of our current research is also involved with practical applications of defeasible argumentation for XML-based knowledge systems. In [10] we propose extending traditional web-based forms to incorporate defeasible attributes as part of the knowledge that can be encoded in a form. The proposed extension allows the specification of scripts for reasoning about form fields using a defeasible knowledge base, expressed in terms of a Defeasible Logic Program. We contend that defeasible argumentation provides a rich paradigm for modelling inference in the context of the Semantic Web initiative. As we have outlined in this paper, integrating argumentation with ontologies is a complex task which may lead to many promising contributions, such as enriching description of web resources in terms of defeasible rules, and providing a theory for merging ontologies with incomplete and po-

tentially inconsistent information. Research in these directions is currently being pursued.

References

- [1] ANTONIOU, G., BIKAKIS, A., AND WAGNER, G. A Defeasible Logic Programming System for the Web. In *Proceedings of the 16th IEEE International Conference on Tools with Artificial Intelligence (ICTAI 2004)* (2004).
- [2] BERNERS-LEE, T., HENDLER, J., AND LASSILA, O. The Semantic Web. *Scientific American* (17 May 2001).
- [3] CHESÑEVAR, C., BRENA, R., AND AGUIRRE, J. Knowledge distribution in large organizations using defeasible logic programming. In *Procs. of the 18th Canadian Conference in Artificial Intelligence (AI 2005)*. Victoria, British Columbia, Canada (in press). To appear in *LNAI 3501 Springer Series*. (May 2005).
- [4] CHESÑEVAR, C., AND MAGUITMAN, A. ARGUENET: An Argument-Based Recommender System for Solving Web Search Queries. In *Proc. of 2nd Intl. IEEE Conference on Intelligent Systems IS-2004*. Varna, Bulgaria (June 2004), pp. 282–287.
- [5] CHESÑEVAR, C., SIMARI, G., GODO, L., AND ALSINET, T. Argument-based expansion operators in possibilistic defeasible logic programming: Characterization and logical properties. *Proc. of the 8th European Conf. on Symbolic and Quantitative Approaches to Reasoning with Uncertainty (ECSQARU 2005)*, Barcelona, Spain (in press). To appear in *LNAI Springer Series*. (2005).
- [6] CHESÑEVAR, C. I., MAGUITMAN, A., AND LOUI, R. Logical Models of Argument. *ACM Computing Surveys* 32, 4 (Dec. 2000), 337–383.
- [7] CHESÑEVAR, C. I., SIMARI, G., ALSINET, T., AND GODO, L. A Logic Programming Framework for Possibilistic Argumentation with Vague Knowledge. In *Proc. of the Intl. Conference in Uncertainty in Artificial Intelligence (UAI 2004)*. Banff, Canada (June 2004), pp. 76–84.
- [8] FALAPPA, M. A., KERN-ISBERNER, G., AND SIMARI, G. R. Explanations, Belief Revision and Defeasible Reasoning. *Artificial Intelligence* 141 (2002), 1–28.
- [9] GARCÍA, A. J., AND SIMARI, G. R. Defeasible Logic Programming: An Argumentative Approach. *Theory and Practice of Logic Programming* 4, 1 (2004), 95–138.
- [10] GÓMEZ, S., CHESÑEVAR, C., AND SIMARI, G. Incorporating defeasible knowledge and argumentative reasoning in web-based forms. In *Third Workshop on Intelligent Techniques for Web Personalization (ITWP '05)* (Submitted) (2005).
- [11] GÓMEZ, S. A., AND CHESÑEVAR, C. I. A Hybrid Approach to Pattern Classification Using Neural Networks and Defeasible Argumentation. In *The 17th International FLAIRS Conference, Palm Beach, Florida, USA* (May 2004).
- [12] HUNTER, A. Logical fusion rules for merging structured news reports. *Data Knowl. Eng.* 42, 1 (2002), 23–56.
- [13] HUNTER, A. Making argumentation more believable. In *Proc. of the 19th American National Conference on Artificial Intelligence (AAAI 2004)* (2004), MIT Press, pp. 269–274.
- [14] HUNTER, A. Towards higher impact argumentation. In *Proc. of the 19th American National Conference on Artificial Intelligence (AAAI 2004)* (2004), MIT Press, pp. 275–280.
- [15] MCGUINNESS, D. L., AND VAN HARMELEN, F. OWL Web Ontology Language Overview, 2004. <http://www.w3.org/TR/owl-features/>.
- [16] PRAKKEN, H., AND VREESWIJK, G. Logical Systems for Defeasible Argumentation. In *Handbook of Phil. Logic*, D. Gabbay and F. Guenther, Eds. Kluwer, 2002, pp. 219–318.
- [17] SIMARI, G. R., AND LOUI, R. P. A Mathematical Treatment of Defeasible Reasoning and its Implementation. *Artificial Intelligence* 53 (1992), 125–157.
- [18] WIESMAN, F., AND ROOS, N. Domain independent learning of ontology mappings. In *AAMAS'04* (July 19–23, 2004).