

Towards A Non Monotonic Description Logics Model

Martín O. Moguillansky
mom@cs.uns.edu.ar

Marcelo A. Falappa
mfalappa@cs.uns.edu.ar

Laboratorio de Investigación y Desarrollo en Inteligencia Artificial (LIDIA)
Departamento de Ciencias e Ingeniería de la Computación (DCIC)
Universidad Nacional del Sur (UNS)
Consejo de Investigaciones Científicas y Técnicas (CONICET)
Av. Alem 1253 - (B8000CPB) Bahía Blanca - Argentina

Abstract

In order to deal with the *Ontology Change* problem and considering an environment where *Description Logics* (DLs) are used to describe ontologies, the question of how to integrate distributed ontologies appears to be in touch with *Belief Revision* since DL terminologies may define same concept descriptions of a not necessarily same world model. A possible alternative to reason about these concepts is to generate unique concept descriptions in a different terminology. This new terminology needs to be consistently created, trying to deal with the minimal change problem, and moreover, yielding a non-monotonic layer to express ontological knowledge in order to be further updated with new distributed ontologies.

Keywords: Belief Revision, Description Logics, Non Monotonic Reasoning, Ontology Change.

1 INTRODUCTION

In order to reason about different ontologies, probably allocated in different places round the web, we will consider translated OWL ontologies into description logics (DLs). In DLs, the concept of Knowledge Base (**KB**) is composed of two main parts, TBoxes or Terminologies and ABoxes or Assertions. In this paper we focuss our investigation on how to reason about *terminologies*. Here many possibilities come through.

Just think about two distinct terminologies modeling each two different worlds, but containing a same subset of concepts (referred as *Ontology Integration* in [Flo06]). Or just two distinct terminologies modeling the same world, where naturally a common subset of concepts will be described as part of both terminologies (referred as *Ontology Merging* in [Flo06]). Furthermore, it might be probably impossible to get two concepts defined by different persons with exactly the same logic intention. Here is where the theory change arises as relevant protagonist in order to join consistently two terminologies redefining or reinforcing sub-concepts.

The remainder of this paper is disposed as follows. The next section gives a brief description of the DL formalism, continued by section 3 with the analogous description of the theory change model, section 4 contributes to the formalization of merging DL terminologies, and describes an example operation of two different terminologies. Finally section 5 concludes and explains the related and future work in the area.

Partially financed by CONICET (PIP 5050), Universidad Nacional del Sur (PGI 24/ZN11) and Agencia Nacional de Promoción Científica y Tecnológica (PICT 2002 Nro 13096).

2 THE DL BASIC FORMALISM

A Knowledge Representation (KR) system based on Description Logics (DL) provides a formalization to specify the knowledge base (KB) contents, a way to reason about it, and a process to infer implicit knowledge. A KB is composed by two components. A TBox to manage the *terminology* of the application world and an ABox containing the *assertions* about named individuals in terms of the previous concepts.

A *terminology* is composed by atomic *concepts* which denote sets of individuals and atomic *roles* to manage relationships between individuals. Besides, complex concepts and roles are built from the atomics using given constructors. Reasoning tasks are dedicated to determine whether a description is satisfiable (*i.e.* non-contradictory), or whether one description is more general than another one, that is, whether the first subsumes the second.

For an ABox, the problem is to verify the consistency of each set of assertions (*i.e.* test if there is a model for the set) and find out whether a particular individual is an instance of a concept description in the TBox depending on the assertions in the ABox. The environment will interact with the KR by querying the KB and finally by adding and retracting concepts, roles and assertions.

2.1 Description Languages

Description Languages are defined by the constructors they provide. In this paper we will consider a subset of the large DL constructors set investigated so far. The basic Description Language introduced by [SSS91] is the \mathcal{AL} (Attribute Language). Let A be an atomic-concept, R an atomic-role, and C, D complex concepts, the grammar for the \mathcal{AL} language is defined as follows,

$$C, D \rightarrow A | \top | \perp | \neg A | C \sqcap D | \forall R.C | \exists R.\top$$

To define the formal semantics of \mathcal{AL} -concepts we use *interpretations* (\mathcal{I}) that consist of a non-empty set $\Delta^{\mathcal{I}}$ (the domain of the interpretation) and an interpretation function $i^{\mathcal{I}}$, that assigns to every atomic concept A a set $A^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}}$ and to every atomic role R a binary relation $R^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}}$. The interpretation function $\mathcal{I} = (\Delta^{\mathcal{I}}, i^{\mathcal{I}})$ is extended to concept descriptions as follows,

$$\begin{aligned} \top^{\mathcal{I}} &= \Delta^{\mathcal{I}} & \perp^{\mathcal{I}} &= \emptyset \\ (\neg A)^{\mathcal{I}} &= \Delta^{\mathcal{I}} \setminus A^{\mathcal{I}} & (C \sqcap D)^{\mathcal{I}} &= C^{\mathcal{I}} \cap D^{\mathcal{I}} \\ (\forall R.C)^{\mathcal{I}} &= \{a \in \Delta^{\mathcal{I}} \mid \forall b.(a, b) \in R^{\mathcal{I}} \rightarrow b \in C^{\mathcal{I}}\} \\ (\exists R.\top)^{\mathcal{I}} &= \{a \in \Delta^{\mathcal{I}} \mid \exists b.(a, b) \in R^{\mathcal{I}}\} \end{aligned}$$

In [BN02] is exhaustively detailed all language extensions depending on the constructors allowed in it, and namely $\mathcal{AL}[\mathcal{U}][\mathcal{E}][\mathcal{N}][\mathcal{C}][\mathcal{Q}]^1$. In Table 1 a brief summary is given.

Example 1 : Considering a language constructor \mathcal{N} and given a role **completedCourse**, a student of computer science is considered advanced if he has passed 15 courses out of a total of 25, ≥ 15 **completedCourse** $\sqcap \leq 25$ **completedCourse**. For \mathcal{Q} , the number restrictions are concerned with roles limited to a certain concept. In this case, one can also say that a student should pass at least 6 logic courses and 9 computational courses to be considered advanced,

$$\begin{aligned} &\geq 6 \text{ completedCourse.LogicCourse} \sqcap \\ &\geq 9 \text{ completedCourse.ComputationalCourse} \sqcap \\ &\leq 25 \text{ completedCourse} \end{aligned}$$

□

¹The use of \mathcal{C} stands for complement. For \mathcal{N} and \mathcal{Q} , n varies over the nonnegative integers, and $\|X\|$ stands for the cardinality of the set X .

Constructor	Written	Interpreted
Union (\sqcup)	$C \sqcup D$	$(C \sqcup D)^{\mathcal{J}} = C^{\mathcal{J}} \cup D^{\mathcal{J}}$
Negation (\mathcal{C})	$\neg C$	$(\neg C)^{\mathcal{J}} = \Delta^{\mathcal{J}} \setminus C^{\mathcal{J}}$
<i>Existential</i>		
Quantification (\mathcal{E})	$\exists R.C$	$(\exists R.C)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \exists b.(a, b) \in R^{\mathcal{J}} \wedge b \in C^{\mathcal{J}}\}$
Number	$\geq nR$	$(\geq nR)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \ \{b \mid (a, b) \in R^{\mathcal{J}}\}\ \geq n\}$
Restrictions	$\leq nR$	$(\leq nR)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \ \{b \mid (a, b) \in R^{\mathcal{J}}\}\ \leq n\}$
(\mathcal{N})	$= nR$	$(= nR)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \ \{b \mid (a, b) \in R^{\mathcal{J}}\}\ = n\}$
Qualified	$\geq nR.C$	$(\geq nR.C)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \ \{b \mid (a, b) \in R^{\mathcal{J}} \wedge b \in C^{\mathcal{J}}\}\ \geq n\}$
Number	$\leq nR.C$	$(\leq nR.C)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \ \{b \mid (a, b) \in R^{\mathcal{J}} \wedge b \in C^{\mathcal{J}}\}\ \leq n\}$
Restrictions (\mathcal{Q})	$= nR.C$	$(= nR.C)^{\mathcal{J}} = \{a \in \Delta^{\mathcal{J}} \mid \ \{b \mid (a, b) \in R^{\mathcal{J}} \wedge b \in C^{\mathcal{J}}\}\ = n\}$

Table 1: Constructors to extend the expressivity of \mathcal{AL} -languages.

2.2 Terminologies

Terminological axioms indicate how concepts or roles are related to each other following the *inclusion* form, $C \sqsubseteq D$ ($R \sqsubseteq S$), or the *equality* form, $C \equiv D$ ($R \equiv S$), where C and D are concepts (R and S are roles).

An interpretation \mathcal{J} satisfies an inclusion $C \sqsubseteq D$ if $C^{\mathcal{J}} \subseteq D^{\mathcal{J}}$, and it satisfies an equality $C \equiv D$ if $C^{\mathcal{J}} = D^{\mathcal{J}}$. Now given a set of axioms \mathcal{T} , an interpretation \mathcal{J} satisfies \mathcal{T} *iff* \mathcal{J} satisfies each element of \mathcal{T} . If \mathcal{J} satisfies an axiom in \mathcal{T} , then we say that it is a *model* of this axiom in \mathcal{T} . Then two axioms or two set of axioms are *equivalent* if they have the same models.

Definitions are used to describe complex concepts and made abstraction of them using a single name. An atomic concept on the left side of an equality *defines* the complex description explained on its right side.

A set of definitions \mathcal{T} is called a *terminology* or a *TBox* if a symbolic name is defined only once. A terminology \mathcal{T} contains a *cycle* *iff* there exists an atomic concept in \mathcal{T} that uses itself [BN02]; otherwise \mathcal{T} is called *acyclic*. An *acyclic* terminology \mathcal{T} can be *expanded* iteratively through each definition in it, replacing each occurrence of a name on the right hand side with the concepts that it stands for. Now, we say that a terminology \mathcal{T} is *definitorial* if it is *acyclic*, and we call to its semantics *descriptive semantics*. Those semantics that are motivated by the use of intuitively cyclic definitions are called *fixpoint semantics*. We will not consider fixpoint semantics in this paper.

2.3 Role Constructors

Binary relations between concepts are modeled by roles. If every role name is considered a role description or atomic role, and if R and S are roles descriptions, then $R \sqcap S$ (**intersection**), $R \sqcup S$ (**union**), $\neg R$ (**complement**), $R \circ S$ (**composition**), R^+ (**transitive closure**), and R^- (**inverse**) are also role descriptions. An interpretation \mathcal{J} is adapted to the inverse role description as follows,

Inverse (\mathcal{J} or $^{-1}$): $(R^-)^{\mathcal{J}} = \{(b, a) \in \Delta^{\mathcal{J}} \times \Delta^{\mathcal{J}} \mid (a, b) \in R^{\mathcal{J}}\}$

Example 2 : For instance a `hasParent` role is obtained by applying the inverse role constructor to a given `hasChild` role. \square

2.4 Properties for Reasoning

Given a terminology \mathcal{T} , if there is some interpretation of a concept that satisfies the axioms in \mathcal{T} (a model of \mathcal{T}), then the concept denotes a nonempty set for the interpretation, furthermore this concept is known to be *satisfiable* w.r.t. \mathcal{T} . Otherwise it is called *unsatisfiable*. Formally,

Satisfiability [BN02]: A concept C is *satisfiable* w.r.t. \mathcal{T} if there exists a model \mathcal{I} of \mathcal{T} such that $C^{\mathcal{I}}$ is nonempty. In such a case we say that \mathcal{I} is a *model* of C .

Checking (un)satisfiability of concepts might be considered a key inference given that a number of other important inferences for concepts can be reduced to it. For instance, in order to check whether a domain model is correct, or to optimize concepts, we may want to know whether one concept is more general than another. This is called the *subsumption* problem. A concept C is *subsumed* by a concept D if in every model of \mathcal{T} , C is a subset of D .

Subsumption [BN02]: A concept C is *subsumed* by a concept D w.r.t. \mathcal{T} if $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$ for every model \mathcal{I} of \mathcal{T} . In such a case we write $C \sqsubseteq_{\mathcal{T}} D$ or $\mathcal{T} \models C \sqsubseteq D$.

A new kind of reasoning algorithms in DLs raised from the approach of considering satisfiability checking as the main inference. These algorithms are known as Tableaux Algorithms and can be understood as a specialized tableaux calculi.

3 THE BELIEF DYNAMIC MODEL

A **belief base** is a knowledge state represented through a set of sentences not necessarily closed under logical consequence. We also know that a **belief set** is a set of sentences of a determined language, closed under logical consequence. In general, a belief set is infinite being this the main reason of the impossibility to deal with this kind of sets in a computer. Instead, it is possible to characterize the properties that must satisfy each of the change operations on finite representations of a knowledge state.

The classic operations in the theory change are expansions, contractions, and revisions. An **Expansion** operation noted with “+”, adds a new belief to the epistemic state, without guaranteeing its consistency after the operation. A **Contraction** operation, noted with “−”, eliminates a belief α from the epistemic state and those beliefs that make possible its deduction or inference. The sentences to eliminate might represent the *minimal change* on the epistemic state. Finally, a **Revision** operation (“*”) inserts sentences to the epistemic state, guaranteeing consistency (if it was consistent before the operation)[AGM85] [Gar98]. This means that a revision adds a new belief and perhaps it eliminates others to avoid inconsistencies. Other non-classical operations exists, like **Merge** operation [Fuh96][FKS02] noted with “ \circ ”, that fusions belief bases or sets assuring a consistent resultant epistemic state, and a **Consolidation** operation (“!”) that restores consistency to the epistemic state [Han97].

3.1 Kernel Contractions

The **Kernel Contraction** operator is applicable to belief bases and belief sets. It consist of a contraction operator capable of the selection and elimination of those beliefs in K that contribute to infer α .

Definition 3.1.1 - [Han94]: Let K be a set of sentences and α a sentence. The set $K^{\perp}\alpha$, called *set*

of kernels is the set of sets K' such that (1) $K' \subseteq K$, (2) $K' \vdash \alpha$, and (3) if $K'' \subset K'$ then $K'' \not\vdash \alpha$. The set $K^\perp \alpha$ is also called *set of α -kernels* and each one of its elements are called *α -kernel*.

For the success of a contraction operation, we need to eliminate, at least, an element of each α -kernel. The elements to be eliminated are selected by an **Incision Function**.

Definition 3.1.2 - [Han94]: Let K be a set of sentences and “ σ ” be an *incision function* for it such that for any sentence α it verifies, (1) $\sigma(K^\perp \alpha) \subseteq \bigcup(K^\perp \alpha)$ and (2) If $K' \in K^\perp \alpha$ and $K' \neq \emptyset$ then $K' \cap \sigma(K^\perp \alpha) \neq \emptyset$.

Once the incision function was applied, we must eliminate from K those sentences that the incision function selects, *i.e.* the new belief base would consist of all those sentences that were not selected by σ .

Definition 3.1.3 - [Han94]: Let K be a set of sentences, α a sentence, and $K^\perp \alpha$ the set of α -kernels of K . Let “ σ ” be an incision function for K . The operator “ $-\sigma$ ”, called *kernel contraction determined by “ σ ”*, is defined as, $K -_\sigma \alpha = K \setminus \sigma(K^\perp \alpha)$.

Finally, an operator “ $-$ ” is a kernel contraction operator for K if and only if there exists an incision function “ σ ” such that $K - \alpha = K -_\sigma \alpha$ for all sentence α .

3.2 Merging Belief Bases

Fuhrmann defined in [Fuh96] a partial meet merge operation as a union of two bases, not necessarily closed under logic consequence, and a later consistency restoring applying a bottom contraction. Inspired on it we propose a merge operation over two bases, defined by means of the *Kernel Contraction* operator, and determined by an *Incision Function*, as follows.

Definition 3.2.1 - Merge: Let “ $-$ ” be a kernel contraction for the union of two belief bases $K_1 \cup K_2$, determined by an incision function “ σ ”. Then the *Merge for Belief Bases* operator \circ is defined as, $K_1 \circ K_2 = (K_1 \cup K_2) -_\sigma \perp$.

4 CONSISTENT TERMINOLOGY INTEGRATION

In order to reason about two presumably distributed and potentially inconsistent terminologies, a non monotonic operation for integration of both terminologies in a new consistent one is required. For achieving a formal definition of such an operator the following features might be desirable.

- A function that maps a concept name defined in one terminology to another concept name in the second terminology in order to recognize different concept names referring to a same concept of the real world.
- A theory change framework would be an interesting environment for revising beliefs and merging knowledge bases defined as part of the given terminologies.
- Conveniently, a concept defined in a given terminology will be **expanded** in order to generate its correspondent belief base in the theory change. This means that each concept description in it is expressed as a conjunction of basic concept descriptions in the same terminology.
- A translation method for expressing DL concepts as part of a first order logic language might be needed in order to apply the theory change operations.
- Contractions might retract minimal information. This means that an operation for merging terminologies should keep as much as possible knowledge in a consistency restoring process. This property reflects the minimal change requirement of the theory change.

4.1 Basic Definitions

Formal definitions might be interesting to specify reflecting some of the previous features to be the basis of a terminology integration operator.

Definition 4.1.1 - Concept Id.: Let \mathcal{T} be a terminology composed of n distinct definitions, the i^{th} concept description D defined in the terminology \mathcal{T} will be identified as $D_i^{\mathcal{T}}$, where $1 \leq i \leq n$.

Definition 4.1.2 - Names Mapping: Let ξ be a mapping function from a concept name defined in a terminology \mathcal{T}_1 to a different concept name defined in a terminology \mathcal{T}_2 . Then $D_i^{\mathcal{T}_1} = \xi(D_j^{\mathcal{T}_2})$ indicates that $D_i^{\mathcal{T}_1}$ and $D_j^{\mathcal{T}_2}$ are name identifiers of a unique concept of the real world.

Definition 4.1.3 - Consistent Terminology Integration: Let \bowtie be the operator for a *consistent terminology integration* $\mathcal{T}_1 \bowtie \mathcal{T}_2$. Such an operation will be composed of two consecutive sub-operations, *terminology unification* and *terminology consolidation*.

Intuitively, a **terminology unification** consist of copying every concept description from each terminology to a new one except for the application of a *non monotonic concept conjunction*. In such a case, those concepts defined in both terminologies that refers to a same concept in the real framework, identified by a *names mapping function* ξ , are consistently unified in a unique new concept. The following sub-operation is defined as **terminology consolidation**. Here the idea is to restore consistency to the unified terminology \mathcal{T} , capturing and solving inconsistencies that yields the unification process in concept descriptions that refers to a yet unified concept in its right hand side. A tentative unification operation was provided in [MF06] although this version did not consider a more complex case of study that we capture in this paper with the consolidation operation.

4.2 From Description Logics to First Order Logic Languages

DLs are not rule based languages but they may be translated into fragments of first order logics (FOL) in order to make an easier mapping to rule languages. By this, efficient logic programming based reasoners and deductive systems may be defined to make inference about the knowledge representation originally specified by a description language. Table 2, originally specified in [GHV03], summarizes the translation rules above introduced.

DL	FOL
$C \equiv D$	$\forall x. C(x) \leftrightarrow D(x)$
$C \sqsubseteq D$	$\forall x. C(x) \rightarrow D(x)$
C	$C(x)$
$C \sqcap D$	$C(x) \wedge D(x)$
$\neg C$	$\neg C(x)$
$\exists R.C$	$\exists x. (R(y, x) \wedge C(x))$
$\forall R.C$	$\forall x. (R(y, x) \rightarrow C(x))$
$\geq nR$	$\exists y_1, \dots, y_n. (R(x, y_1) \wedge \dots \wedge R(x, y_n)) \wedge (\bigwedge_{1 \leq i < n, i < j \leq n} y_i \neq y_j)$
$\leq nR$	$\forall y_1, \dots, y_{n+1}. (R(x, y_1) \wedge \dots \wedge R(x, y_{n+1})) \rightarrow (\bigvee_{1 \leq i < (n+1), i < j \leq (n+1)} y_i = y_j)$

Table 2: DL - FOL equivalence.

The following definitions describe how our proposal manages DLs concepts descriptions as fragments in the theory change².

Definition 4.2.1 - KB of a Concept Description: Let $C \equiv C_1 \sqcap \dots \sqcap C_n$ be an *expanded* concept

²We adopt a \mathcal{ALCEN} description language, where the classical \mathcal{AL} attribute language is extended by *complement*, *existential quantification*, and *number restriction* concept constructors.

description, then the set $K(C)$ will be the knowledge base for the concept description C such that $\phi_{C_1}, \dots, \phi_{C_n} \in K(C)$, where ϕ_{C_i} is the first order logic translation of the concept C_i .

Observation 4.2.2: A DL conjunction $C_1 \sqcap C_2$ is interpreted in the theory change as $K(C_1) \cup K(C_2)$.

Proof: Let $C \equiv C_1 \sqcap C_2$ be a concept description, and let $C_1 \equiv A_1 \sqcap \dots \sqcap A_n$, and $C_2 \equiv B_1 \sqcap \dots \sqcap B_n$ be their respective atomic concept descriptions. Then the expanded concept description for C is $C \equiv A_1 \sqcap \dots \sqcap A_n \sqcap B_1 \sqcap \dots \sqcap B_n$. Finally using definition 4.2.1 follows that $K(C) = K(C_1) \cup K(C_2)$. \square

4.3 Non Monotonic Concept Conjunction (\boxdot)

Let “ \boxdot ” be a *Non Monotonic Concept Conjunction* DL operator used as part of the terminology unification process and furthermore in the specification of the terminology consolidation, such that $D = D_1 \boxdot D_2$ defines a new *satisfiable* concept description D from consistently unifying concepts D_1 and D_2 by the application of the operator \boxdot .

A consistent conjunction of two such a concept descriptions may intuitively be thought as a merge of the belief bases representing each concept. Afterwards, the resultant belief base should be translated back to the original description language in order to express the result as a new concept description. A translation method from DLs to belief bases in the theory change is necessary, then following the translation rules from a description language to a subset of first order logic rules in table 2, we may obtain the conversions of concept descriptions to belief bases in the theory change.

Definition 4.3.1 - Non Monotonic Concept Conjunction : Let D_1 and D_2 be two concept descriptions and let $K(D_1)$ and $K(D_2)$ be their correspondent belief bases (not necessarily closed under logical consequence). A *non monotonic concept conjunction* operation $D_1 \boxdot D_2$, is interpreted as a merge operation for belief bases, such that $D_1 \boxdot D_2 \Leftrightarrow K(D_1) \circ K(D_2)$.

Observation 4.3.2: If the conjunction $D_1 \sqcap D_2$ is satisfiable³, then the non monotonic conjunction $D_1 \boxdot D_2$ is equivalent to $D_1 \sqcap D_2$.

Proof: Suppose we have two concept descriptions D_1 and D_2 , then by definition 4.2.1 their respective knowledge bases are $K(D_1)$ and $K(D_2)$.

(\Rightarrow) Consider the non monotonic concept conjunction $D_1 \boxdot D_2$, by definition 4.3.1 it may be though as a merge operation of their knowledge bases such that $K(D_1) \circ K(D_2)$. Using definition 3.2.1 (*merge*) we have $(K(D_1) \cup K(D_2)) -_{\sigma} \perp$. Then by definition 3.1.3 (*kernel contraction*) it is equivalent to $(K(D_1) \cup K(D_2)) \setminus \sigma((K(D_1) \cup K(D_2))^{\perp} \perp)$.

Now suppose that (*by hypothesis*) $D_1 \sqcap D_2$ is satisfiable, then by definition 3.1.1 (*set of kernels*) it follows that there is no $K' \subseteq (K(D_1) \cup K(D_2))$ such that $K' \vdash \perp$. Thus, we have no beliefs to select from $(K(D_1) \cup K(D_2))$, and finally by observation 4.2.2 we have $D_1 \sqcap D_2$ (as we wanted to prove). The opposite (\Leftarrow) direction can be similarly proved. \square

The following algorithm describes the operation $D \equiv D_1 \boxdot D_2$ defined in definition 4.3.1 and optimizes it considering the observation 4.3.2.

4.4 Consistent Merging of Terminologies ($\langle \boxtimes \rangle$)

As previously specified, an operation $\mathcal{T} = \mathcal{T}_1 \langle \boxtimes \rangle \mathcal{T}_2$, consist of two sub-operations; *unification* of both terminologies \mathcal{T}_1 and \mathcal{T}_2 in a new one \mathcal{T} , and the respective *consolidation* of \mathcal{T} for consistency restoring. In what follows we provide the correspondent algorithms for both sub-operations.

Observation 4.4.1: If no loss of knowledge is desired in a concept unification process – *i.e.* that the

³A conjunction $D_1 \sqcap D_2$ is satisfiable if there exists a model \mathcal{I} of \mathcal{T} such that $(D_1 \sqcap D_2)^{\mathcal{I}}$ is non empty.

Algorithm 1 Non Monotonic Concept Conjunction $D \equiv D_1 \sqcap D_2$

Input: Two expanded concepts D_1, D_2 .**Output:** D .if $D_1 \sqcap D_2$ is un-satisfiable then $D \Leftarrow K(D_1) \circ K(D_2)$.

else

 $D \Leftarrow D_1 \sqcap D_2$ end if

Algorithm 2 Terminology Unification

Input: Two terminologies \mathcal{T}_1 and \mathcal{T}_2 .**Output:** A unified terminology \mathcal{T} .for all D in \mathcal{T}_1 or \mathcal{T}_2 doif exists a mapping $\xi(D)$ for concept description D then $\mathcal{D}^{\mathcal{T}} \Leftarrow D \sqcap \xi(D)$ is a new concept in \mathcal{T}

else

 $\mathcal{D}^{\mathcal{T}} \Leftarrow D$ is a new concept in \mathcal{T}

end if

end for

conjunction of concept descriptions is unsatisfiable and the non monotonic conjunction will eliminate some beliefs from the epistemic state– then we should not consider these concepts as specifiers of a same concept of the real framework. So we should remove the mapping value in ξ that relate them.

Algorithm 3 Terminology Consolidation

Input: The unified terminology \mathcal{T} .**Output:** The consolidated terminology \mathcal{T} .for all $\mathcal{D}^{\mathcal{T}}$ dofor all $C^{\mathcal{T}} \equiv D \sqcap C_{tail}$, where C_{tail} may be thought as $C_1 \sqcap C_2 \sqcap \dots \sqcap C_n$ doif $\mathcal{D}^{\mathcal{T}} \sqcap C_{tail}$ is satisfiable thenReplace the original definition $C^{\mathcal{T}} \equiv D \sqcap C_{tail}$ by $\mathcal{C}^{\mathcal{T}} \equiv \mathcal{D}^{\mathcal{T}} \sqcap C_{tail}$

else

Let S be $\sigma((K(\mathcal{D}^{\mathcal{T}}) \cup K(C_{tail}))^{\perp\perp})$ where the selection's scope is restricted to $K(\mathcal{D}^{\mathcal{T}})$.Generate $D_1^{\mathcal{T}} \Leftarrow K(\mathcal{D}^{\mathcal{T}}) \setminus S$ in \mathcal{T} .Redefine $\mathcal{D}^{\mathcal{T}} \equiv D_1^{\mathcal{T}} \sqcap S_{DL}$ in \mathcal{T} , where S_{DL} is the description language translation of S .Replace the original definition $C^{\mathcal{T}} \equiv D \sqcap C_{tail}$ by $\mathcal{C}^{\mathcal{T}} \equiv D_1^{\mathcal{T}} \sqcap C_{tail}$.

end if

end for

end for

Observation 4.4.2: Note that the consolidation algorithm adds new concept descriptions noted as \mathcal{C} and \mathcal{D} and these new definitions are considered in later iterations.

4.5 Worked Example

In this section we show how two different terminologies might be consistently merged in a new one following the previous definitions.

The terminology expressed in table 4 shows among other definitions, some main characteristics of *mammals* and *oviparous* animals, and particularly defines *monotremes* to be a conjunction of both

<i>Bird</i>	\equiv	$Animal \sqcap Bipedal \sqcap Oviparous \sqcap hasFeathers \sqcap = 2hasWings$
<i>Mammal</i>	\equiv	$Animal \sqcap \forall giveBirth.LiveBirth$
<i>Oviparous</i>	\equiv	$Animal \sqcap \forall giveBirth.Egg$
<i>Bipedal</i>	\equiv	$= 2hasFoot$
<i>LiveBirth</i>	\equiv	$hasHeartBeat \sqcap hasVoluntaryMovement$
<i>Egg</i>	\equiv	$hasHeartBeat \sqcap \neg hasVoluntaryMovement$

Table 3: A terminology \mathcal{T}_1 (TBox) with concepts about animals.

<i>Platypus</i>	\equiv	$Aquatic \sqcap Monotreme$
<i>Monotreme</i>	\equiv	$Mammal \sqcap Oviparous$
<i>Mammal</i>	\equiv	$Animal \sqcap \geq 2hasMammaryGlands$
<i>Oviparous</i>	\equiv	$Animal \sqcap \geq 1layEggs$

Table 4: A terminology \mathcal{T}_2 (TBox) with concepts about animals.

animal classes. When we try to merge terminologies \mathcal{T}_1 and \mathcal{T}_2 we find that the concept descriptions for *mammals* and *oviparous* in \mathcal{T}_1 yield the following contradiction,

$$hasVoluntaryMovement \sqcap \neg hasVoluntaryMovement$$

4.5.1 Method Application

In what follows we will develop the integration of both terminologies following the previous \triangleleft operation definition in order to see more clearly how the consistency problem is solved. Let consider the following mapping instances, $Mammal^{\mathcal{T}_1} = \xi(Mammal^{\mathcal{T}_2})$ and $Oviparous^{\mathcal{T}_1} = \xi(Oviparous^{\mathcal{T}_2})$.

Then, the unified terminology $\mathcal{T} = \mathcal{T}_1 \triangleleft \mathcal{T}_2$ will have the following concept descriptions,

<i>Bird</i>	\equiv	$Bird^{\mathcal{T}_1}$
<i>Platypus</i>	\equiv	$Platypus^{\mathcal{T}_2}$
<i>Monotreme</i>	\equiv	$Monotreme^{\mathcal{T}_2}$
<i>Mammal</i>	\equiv	$Mammal^{\mathcal{T}_1} \sqcap Mammal^{\mathcal{T}_2}$
<i>Oviparous</i>	\equiv	$Oviparous^{\mathcal{T}_1} \sqcap Oviparous^{\mathcal{T}_2}$
<i>Bipedal</i>	\equiv	$Bipedal^{\mathcal{T}_1}$
<i>LiveBirth</i>	\equiv	$LiveBirth^{\mathcal{T}_1}$
<i>Egg</i>	\equiv	$Egg^{\mathcal{T}_1}$

Table 5: The unified terminology \mathcal{T} from the originals \mathcal{T}_1 and \mathcal{T}_2 .

When merging the two belief bases $K(Mammal^{\mathcal{T}_1})$ and $K(Mammal^{\mathcal{T}_2})$, no inconsistency arises,

$K(Mammal^{\mathcal{T}})$
$Animal(X)$
$hasMammaryGlands(X, y_1)$
$hasMammaryGlands(X, y_2)$
$giveBirth(Y, X) \rightarrow hasHeartBeat(X) \wedge hasVoluntaryMovement(X)$

The resultant unified concept will be translated from the previous belief base to the correspondent description language as, $Mammal^{\mathcal{T}} \equiv Animal \sqcap \geq 2hasMammaryGlands \sqcap \forall giveBirth.$

($hasHeartBeat \sqcap hasVoluntaryMovement$). A similar situation occurs with the belief base for concept description *Oviparous*, and its correspondent translation to DLs, $Oviparous^{\mathcal{T}} \equiv Animal \sqcap \geq 1 layEggs \sqcap \forall giveBirth.(hasHeartBeat \sqcap \neg hasVoluntaryMovement)$.

$$K(Oviparous^{\mathcal{T}})$$

$ \begin{aligned} &Animal(X) \\ &layEggs(X, y_1) \\ &giveBirth(Y, X) \rightarrow hasHeartBeat(X) \wedge \neg hasVoluntaryMovement(X) \end{aligned} $
--

We developed so far the terminology unification, first sub-operation of the terminology integration previously defined. The following step is the application of the terminology consolidation in order to verify and restore consistency to the resultant unified terminology. Here, the concept description for *Monotreme* yields the inconsistency.

$$\begin{aligned}
Monotreme^{\mathcal{T}} &\equiv Animal \sqcap \geq 2 hasMammaryGlands \sqcap \\
&\forall giveBirth.(hasHeartBeat \sqcap hasVoluntaryMovement) \sqcap \\
Animal \sqcap &\geq 1 layEggs \sqcap \forall giveBirth.(hasHeartBeat \sqcap \neg hasVoluntaryMovement)
\end{aligned}$$

Clearly, this concept is unsatisfiable, so from the set $(K(Mammal^{\mathcal{T}}) \cup K(Oviparous^{\mathcal{T}}))^{\perp\perp}$ of \perp -kernels, an appropriate⁴ incision function σ would select rules only from $K(Mammal^{\mathcal{T}})$ in order to avoid the inconsistency in this concept. In such a case the correspondent sentence would be

$$giveBirth(Y, X) \rightarrow hasHeartBeat(X) \wedge hasVoluntaryMovement(X)$$

that comes from the DL concept $\forall giveBirth.(hasHeartBeat \sqcap hasVoluntaryMovement)$ so a new concept $Mammal_1^{\mathcal{T}}$ is defined to be part of the terminology \mathcal{T} without considering the previous selection, such that $Mammal_1^{\mathcal{T}} \equiv Animal \sqcap \geq 2 hasMammaryGlands$. Then the definitive concept for the definition of *Mammal* in \mathcal{T} would be,

$$Mammal^{\mathcal{T}} \equiv Mammal_1^{\mathcal{T}} \sqcap \forall giveBirth.(hasHeartBeat \sqcap hasVoluntaryMovement)$$

Finally, following the consolidation algorithm, the concept description for *Monotreme* in terminology \mathcal{T} would be, $Monotreme^{\mathcal{T}} \equiv Mammal_1^{\mathcal{T}} \sqcap Oviparous^{\mathcal{T}}$.

Note that following the proposed method for terminology integration we do not only eliminate the inconsistency when merging both terminologies, but also keep all information as part of the resultant terminology, by identifying and splitting the problematic concept in two interrelated, revisiting the hierarchy technique of the object oriented paradigm.

5 CONCLUSIONS, RELATED AND FUTURE WORK

A union operation of terminologies probably yields contradictions on concept descriptions and further inconsistency in the resultant terminology. The use of a belief revision framework to define terminologies in order to meet a consistent merge operation is proposed and generates a new *Non-monotonic Description Logics* model as a powerful theory to be applied on future Semantic Web researches.

Ontology Change [Flo06] expresses the necessity of modifying the knowledge described in ontologies responding to different given interests. For instance, ontology changes may arise due to some change originated in the world being modeled, or on users' needs; and/or due to previously unknown knowledge, or bugs found after design steps.

⁴The reader is invited to refer the conclusions of this work to understand this selection.

<i>Bird</i>	\equiv	$Animal \sqcap Bipedal \sqcap Oviparous \sqcap hasFeathers \sqcap = 2hasWings$
<i>Platypus</i>	\equiv	$Aquatic \sqcap Monotreme$
<i>Monotreme</i>	\equiv	$Mammal_1 \sqcap Oviparous$
<i>Mammal₁</i>	\equiv	$Animal \sqcap \geq 2hasMammaryGlands$
<i>Mammal</i>	\equiv	$Mammal_1 \sqcap \forall giveBirth.LiveBirth$
<i>Oviparous</i>	\equiv	$Animal \sqcap \forall giveBirth.Egg \sqcap \geq 1layEggs$
<i>Bipedal</i>	\equiv	$= 2hasFoot$
<i>LiveBirth</i>	\equiv	$hasHeartBeat \sqcap hasVoluntaryMovement$
<i>Egg</i>	\equiv	$hasHeartBeat \sqcap \neg hasVoluntaryMovement$

Table 6: The resultant terminology $\mathcal{T} = \mathcal{T}_1 \triangleleft \mathcal{T}_2$ with concepts about animals.

Many authors are nowadays focusing their efforts in some closely related areas under terms like, ontology translation, evolution, integration and merging. For instance, in [Flo06] an AGM compatible contraction operator for DLs is described, and based on it a DL revision operator is defined in [QLB06], from the generalized AGM postulates in [Flo06]. These two works are some of the newest results obtained so far by considering theory change and DLs as an hybrid framework for belief revision.

Our proposed approach means an interesting alternative in the area, whose most notorious difference relays in the fact of the focalization on *non-prioritized change operations* where the AGM postulates are not fully met. From a naming convention point of view, although most of our work might be thought as *Ontology Merging*, we enclose it in the so called *Ontology Integration*, following the terminology specified in [Flo06], due to some slight overlapping that we consider exists between these terms.

The *incision function* (σ) deserves a special discussion due to its responsibility on the information management of knowledge bases which makes to keep or restore consistency regarding the selections it does. For instance, several merge operators have been proposed in the theory change bibliography, but in this work we proposed a different one based on a kernel contraction determined by an incision function. This is due to our intentions to reduce every belief revision and merge operation to an “intelligent” definition of the incision function, so placing it on top of our future investigations.

Another situation is given by concept descriptions to be consistently merged “retracting” those simple concepts descriptions that presumably generate the inconsistency in the new concept description. This selection is the one being made by the incision function, but here always might be more than one possible election to avoid inconsistency. More formally, $C \Leftarrow K(C_1) \cup K(C_2) -_{\sigma} \perp$ might be solved selecting knowledges from any of the two involved concept descriptions. Here is where *Epistemic Entrenchment* methods arise, in order to properly select, w.r.t. the local environment, the most convenient knowledge and to give only one possible concept description as the operation resultant.

Motivated by the latter examples, a deeper investigation on *Epistemic Entrenchment*⁵ methods could be useful to semi-automate the well functioning of a reasonable incision function (σ) to cut the α -kernels obtained by the use of merge operations. This means that the incision function (σ) will select those sub-concepts with less epistemic entrenchment to be cut off the resulting definition.

To achieve this, we will investigate *confidence levels* on terminologies to be incorporated by the ontology integration requester depending on his confidence about the origin where the ontology came from (author). Furthermore, it would be interesting also to consider confidence levels on concept descriptions incorporated by the ontology designer. By this, we intend to have some extra information

⁵The *Epistemic Entrenchment* method specifies a way to measure the level of importance of a sentence α to belong to the epistemic state.

at the time of evaluating which is the most relevant knowledge to be held after an integration operation.

Acknowledgements: We would like to thank to the anonymous referee for their valuable contribution to this paper.

REFERENCES

- [AGM85] Carlos Alchourrón, Peter Gärdenfors, David Makinson. *On the logic of theory change: Partial Meet Contraction and Revision Functions*, The Journal of Symbolic Logic, 50:510-530, 1985. 1985.
- [BHS03] F. Baader, Ian Horrocks, U. Sattler. *Description Logics as Ontology Languages for the Semantic Web*, Lecture Notes in Artificial Intelligence. Springer, 2003.
- [BN02] F. Baader, W. Nutt. *Basic Description Logics*. In the Description Logic Handbook, Cambridge University Press, 2002, pages 47-100.
- [FKS02] M. Falappa, G. KernIsberner, G. Simari. *Explanations, belief revision and defeasible reasoning*. Artificial Intelligence Journal 141(1-2):1-28, 2002.
- [Flo06] Giorgos Flouris. *On Belief Change and Ontology Evolution*. Doctoral Dissertation, Department of Computer Science, University of Crete, February 2006.
- [Fuh96] André Fuhrmann. *An Essay on Contraction*, The European Association for Logic, Language and Information (FOLLI), ISBN (Paperback): 1575860546, ISBN (Cloth): 1575860554, 1996.
- [Gar98] Peter Gärdenfors. *Knowledge in Flux: Modelling the Dynamics of Epistemic States*. The MIT Press, Bradford Books, Cambridge, Massachusetts, 1988.
- [GHV03] Benjamin N. Grosof, Ian Horrocks, Raphael Volz, and Stefan Decker. *Description Logic Programs: Combining Logic Programs with Description Logic*. In Proceedings 12th International Conference on the World Wide Web (WWW-2003), Budapest, Hungary, May 20-23, 2003.
- [Han94] S. O. Hansson. *Kernel Contraction*, The Journal of Symbolic Logic, 59:845-859, 1994.
- [Han97] S. O. Hansson. *Semi-Revision*. Journal of Applied Non-Classical Logic, 7:151-175, 1997.
- [MF03] M. Moguillansky, M. Falappa. *Aplicación de Operaciones de Cambio en Sistemas Basados en Conocimiento*, IX Congreso Argentino de Ciencias de la Computación, CACIC'2003: 1490-1501, Universidad Nacional de La Plata, Octubre de 2003.
- [MF06] M. Moguillansky, M. Falappa. *On the Use of Belief Revision to Merge Description Logic Terminologies*, WICC'2006: 57-62, Universidad de Moron, Junio de 2006.
- [QLB06] Guilin Qi, Weiru Liu, and David A. Bell. *Knowledge base revision in Description Logics*, In Proceedings of 10th European Conference on Logics in Artificial Intelligence (JELIA'06), Springer Verlag, To appear, 2006.
- [SSS91] Manfred Schmidt-Schauß and Gert Smolka. *Attributive concept descriptions with complements*. Artificial Intelligence, 48(1):1-26, 1991.