



Aalborg Universitet

AALBORG UNIVERSITY  
DENMARK

## Bolig 2020 med godt indeklima og høj brugerkomfort – Målerapport 2

Loukou, Evangelia; Heiselberg, Per Kvols; Jensen, Rasmus Lund

Creative Commons License  
Unspecified

Publication date:  
2018

Document Version  
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

### Citation for published version (APA):

Loukou, E., Heiselberg, P. K., & Jensen, R. L. (2018). *Bolig 2020 med godt indeklima og høj brugerkomfort – Målerapport 2*. Department of Civil Engineering, Aalborg University. DCE Technical Reports No. 253

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

### Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.



**DEPARTMENT OF CIVIL ENGINEERING**  
AALBORG UNIVERSITY

# **Bolig 2020 med godt indeklima og høj brugerkomfort – Målerapport 2**

**Evangelia Loukou  
Per Kvols Heiselberg  
Rasmus Lund Jensen**



Aalborg University  
Department of Civil Engineering  
Architectural Engineering

**DCE Technical Report No. 253**

# **Bolig 2020 med godt indeklima of høj brugerkomfort – Målerapport 2**

by

Evangelia Loukou  
Per Kvols Heiselberg  
Rasmus Lund Jensen

July 2018

© Aalborg University

## **Scientific Publications at the Department of Civil Engineering**

**Technical Reports** are published for timely dissemination of research results and scientific work carried out at the Department of Civil Engineering (DCE) at Aalborg University. This medium allows publication of more detailed explanations and results than typically allowed in scientific journals.

**Technical Memoranda** are produced to enable the preliminary dissemination of scientific work by the personnel of the DCE where such release is deemed to be appropriate. Documents of this kind may be incomplete or temporary versions of papers—or part of continuing work. This should be kept in mind when references are given to publications of this kind.

**Contract Reports** are produced to report scientific work carried out under contract. Publications of this kind contain confidential matter and are reserved for the sponsors and the DCE. Therefore, Contract Reports are generally not available for public circulation.

**Lecture Notes** contain material produced by the lecturers at the DCE for educational purposes. This may be scientific notes, lecture books, example problems or manuals for laboratory work, or computer programs developed at the DCE.

**Theses** are monograms or collections of papers published to report the scientific work carried out at the DCE to obtain a degree as either PhD or Doctor of Technology. The thesis is publicly available after the defence of the degree.

**Latest News** is published to enable rapid communication of information about scientific work carried out at the DCE. This includes the status of research projects, developments in the laboratories, information about collaborative work and recent research results.

Published 2018 by  
Aalborg University  
Department of Civil Engineering  
Sofiendalsvej 9-11  
DK-9200 Aalborg SV, Denmark

Printed in Aalborg at Aalborg University

ISSN 1901-726X  
DCE Technical Report No. 253

# 1. Introduction

The purpose of this report is to register the operation and performance of the project building Bolig 2020 for the period of 3 months from March to May. The building is located in Kildebjerg Søvej 32, Ry.

The aim is the long-term assessment of the indoor environmental quality and energy use of the dwelling. Additionally, the data is examined in order to verify that the systems' and equipment's performance matches their intended operation. The activation of natural ventilation and external shading devices will not be addressed in this report, due to the lack of registered data.

The evaluation of the performance of Bolig 2020 case study is based on a combination of standards and measured data.

The data registration is taking place every 5 minutes, approximately, in all rooms of the dwelling. The registered parameters are the following:

<u>Parameters</u>	<u>Comments</u>
Cold water consumption [m <sup>3</sup> ]	Total amount of water consumption for cold and hot water
Hot water consumption [m <sup>3</sup> ]	
Energy consumption:	
District heating [MWh]	
Floor heating pump [kWh]	
Nilan system [kWh]	Energy consumption for ventilation and production of sanitary hot water
Control system [kWh]	
Kitchen stove [kWh]	Energy consumption for the operation of 2 ovens and the cooking plate
Refrigerator [kWh]	Energy consumption for the refrigerator, wine cooler and exhaust hood
Quooker [kWh]	
Dish washer [kWh]	
Dryer [kWh]	
Washing machine [kWh]	
Other consumption [kWh]	Includes everything else

Temperature [°C], CO <sub>2</sub> level [ppm], Relative humidity level [%] and Damper opening [min/max]:
Room 1
Room 2
Room 3
Master Bedroom
Living Room
Kitchen/ Dining Room

Temperature [°C], Relative humidity level [%] and Damper opening [min/ max]:
Utility Room
Bathroom 1
Bathroom 2

Temperature [°C] and Damper opening [min/ max]:
Wardrobe closet


For the compact unit:
Outdoor air temperature [°C]
Return air temperature [°C] and relative humidity [%]
Hot water temperature [°C]
Supply air temperature [°C]
Heat pump temperature [°C]
Ventilation speed [steps]

This report includes the registered period between the beginnings of March to the end of May. The data is presented both on a monthly level and for the entire period of the 3 months. The indoor environment evaluation is realized on a room basis, while the examined rooms are the most used ones, master bedroom, living room, kitchen and bathroom.

Each chapter addresses one of the examined parameters, including graphs for each examined month, as well as for the entire period (March, April and May). In the Annex are included more relevant graphs which are not in the report.

## 2. Energy Consumption


### 2.1 Energy consumption for ventilation and DHW




**Figure 1:** Energy consumption for ventilation and domestic hot water [kWh/m<sup>2</sup>]

The sanitary hot water is produced by the compact ventilation system through the recovered energy from the exhaust air. If the demand is particularly large, an electrical backup supplements the production of hot water.

### 2.2 Energy consumption for heating




**Figure 2:** Energy consumption for heating [kWh]



**Figure 3:** Energy consumption for heating [kWh/m<sup>2</sup>]


Figures 2 and 3 illustrate the energy consumption for heating, given in [kWh] and [kWh/m<sup>2</sup>], respectively. The values are taken from the data registered for “District Heating”.

### 2.3 Electricity consumption



**Figure 4:** Consumption of electricity during 3 months period time (March, April, May) [kWh]


The energy consumption of white goods includes the kitchen stove, the refrigerator, the Quooker (for production of boiling water), the dishwasher, the dryer and the washing machine. The second column refers to the control of all systems, sensors etc., while the third column includes all the rest.



**Figure 5:** Consumption of electricity of white goods, on room level during 3 months period time (March, April, May) [kWh]

Figure 5 gives the energy consumption for all registered appliances divided in room level.

## 2.4 Water consumption



**Figure 6:** Consumption of cold and hot water [m³]

The consumption of cold water has been calculated by subtracting the amount of hot water from the total amount of water consumption.

# 3. Indoor Environment

For the indoor environmental quality is evaluated the thermal and atmospheric indoor climate. More specifically, the examined parameters are the room temperature [ $^{\circ}\text{C}$ ], CO<sub>2</sub> level [ppm] and relative humidity level [%]. The rooms are examined on a daily level (24 hours), as well as for their expected occupied period. The time from 7:00 to 17:00 is counted as unoccupied, taking into consideration that the occupants are away from home during this period. The following table sums up the corresponding periods for each type of room.

	Scenario 1	Scenario 2
Living Room	24 h	Day: 17 - 23
Kitchen	24 h	Day: 17 - 23
Master bedroom	24 h	Night: 23 - 7

## 3.1 Thermal indoor environment

The thermal criteria are assessed according to the comfort categories given by the standards DS/EN 15251. The following table shows the temperature ranges for the three categories, assuming an activity level of 1.2 met (sedentary activity).

Activity level [met]		1.2		
Category		I	II	III
Operative temperature [ $^{\circ}\text{C}$ ]	Summer	24.5 $\pm$ 1.0	24.5 $\pm$ 1.5	24.5 $\pm$ 2.5
	Winter	22.0 $\pm$ 1.0	22.0 $\pm$ 2.0	22.0 $\pm$ 3.0


The recommended criteria for acceptable deviations for the thermal environment, for Category II, are presented in the following table.

	Criteria	Max. deviation	
		Monthly	Yearly
General Assessment	Class II	3 & 5 %	3 & 5 %
Overheating	25 $^{\circ}\text{C}$	10 %	10 %
	27 $^{\circ}\text{C}$	-	100 h
	28 $^{\circ}\text{C}$	-	25 h
Under heating	20 $^{\circ}\text{C}$	-	100 h
	19 $^{\circ}\text{C}$	-	25 h

The distribution of hours in each of the three categories is given in percentages, in form of bar charts, specifying whether the room temperature lies on the low or high part of the scale.


IV-	III-	II-	I	II+	III+	IV+
$t < 19$	$19 \leq t < 20$	$20 \leq t < 21$	$21 \leq t \leq 23$	$23 < t \leq 24$	$24 < t \leq 25$	$25 < t$

### 3.1.1 March




**Figure 7:** Percentage of time in each Category for tempeature during March

### 3.1.2 April




**Figure 8:** Percentage of time in each Category for tempeature during April

### 3.1.3 May



**Figure 9:** Percentage of time in each Category for tempeature during May

### 3.1.4 Entire period (March, April, May)



**Figure 10:** Percentage of time in each Category for tempeature during 3 months period time (March, April, May)

### 3.2 Atmospheric indoor environment

The indoor air quality is also assessed based on the comfort categories suggested by the standards DS/EN 15251. On the following tables are given the acceptable ranges for CO<sub>2</sub> level and relative humidity, respectively.

Category	Corresponding CO <sub>2</sub> above outdoors level [ppm]
I	350
II	500
III	800
IV	> 800


Category	Design relative humidity for dehumidification [%]	Design relative humidity for humidification [%]
I	50	30
II	60	25
III	70	20
IV	>70	<20

The outdoor CO<sub>2</sub> level is taken as a standard value of 400 ppm and not as the minimum registered value by the sensors in each room. This was decided based on the observation that occasionally some of the sensors would register some unrealistically small values. Actions have been taken in order to verify the proper operation of the sensors and eventually to calibrate or replace them. Therefore, it should be kept in mind that there is some uncertainty concerning the presented results for the CO<sub>2</sub> level.


Next table shows the recommended criteria for acceptable deviations for the atmospheric environment, for Category II.

		Max. deviation
	Criteria	Monthly
CO <sub>2</sub>	Category II	3 & 5 %
	Category II	8 h in a row
Relative Humidity	Category II	3 & 5 %
	Category II	24 h in a row
	RH< 45%	-
	RH> 75%	1%

### 3.2.1 March




**Figure 11:** Percentage of time in each Category for CO<sub>2</sub> level during March




**Figure 12:** Percentage of time in each Category for relative humidity during March

### 3.2.2 April




**Figure 13:** Percentage of time in each Category for CO<sub>2</sub> level during April




**Figure 14:** Percentage of time in each Category for relative humidity during April

### 3.2.3 May




**Figure 15:** Percentage of time in each Category for CO<sub>2</sub> level during May




**Figure 16:** Percentage of time in each Category for relative humidity during May

### 3.2.4 Entire period (March, April, May)



**Figure 17:** Percentage of time in each Category for CO<sub>2</sub> level during 3 months period time (March, April, May)



**Figure 18:** Percentage of time in each Category for relative humidity during 3 months period time (March, April, May)

# 4. Annex

## 4.1 March







Figure 19: Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of March– Master Bedroom



**Figure 20:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of March – Living Room




**Figure 21:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of March – Kitchen/ Dining Room




**Figure 22:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of March – Bathroom 1


## 4.2 April




**Figure 23:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of April – Master Bedroom



**Figure 24:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of April – Living Room



**Figure 25:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of April– Kitchen/ Dining Room



**Figure 26:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of April – Bathroom 1

## 4.3 May







Figure 27: Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of May – Master Bedroom



**Figure 28:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of May – Living Room




**Figure 29:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of May – Kitchen/ Dining Room




**Figure 30:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the month of May – Bathroom 1


#### 4.4 Entire period (March, April, May)




**Figure 31:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the 3 months period (March, April, May) – Master Bedroom



**Figure 32:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the 3 months period (March, April, May) – Living Room



**Figure 33:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the 3 months period (March, April, May) – Kitchen/ Dining Room



**Figure 34:** Graphs for temperature, CO<sub>2</sub> level and relative humidity during the 3 months period (March, April, May) – Bathroom 1

## **Recent publications in the DCE Technical Report Series**

