






[Export to BibTex](#)[Search ScienceDirect](#)[Advanced search](#)[Article outline](#) Show full outline[Highlights](#)[Abstract](#)[Graphical abstract](#)[Keywords](#)[1. Introduction](#)[2. Experimental](#)[3. Results and discussion](#)[4. Conclusion](#)[Acknowledgments](#)[References](#)[Figures and tables](#)

Table 1



## Applied Catalysis B: Environmental

Volume 147, 5 April 2014, Pages 756–763



### Mixed-oxide $Ti_{1-x}W_xO_2$ as support for (photo)-electrochemical processes

S. Mokrane-Soualah<sup>a, b</sup>, A.S. Gago<sup>a, 1</sup>, A. Habrioux<sup>a</sup>, N. Alonso-Vante<sup>a</sup>[Show more](#)**Choose an option to locate/access this article:**[Get Full Text Elsewhere](#)

doi:10.1016/j.apcatb.2013.10.012

[Get rights and content](#)

#### Highlights


- Nanostructured mixed-oxide  $Ti_{1-x}W_xO_2$  ( $0 < x < 0.3$ ) was synthesized by sol-gel.
- W ( $x \leq 0.5$ ) is incorporated into the anatase phase with an expansion of the lattice.
- With W content ( $0.5 < x < 0.3$ ) compressive strains appeared with formation of wolframyl groups.
- The incorporation of W ( $x < 0.3$ ) led to a decrease of the photoresponse and an increase of the conductivity.
- The nanostructured oxides are ceramic substrates for Pt or Ir-based electrodes of PEM fuel cells and electrolyzers.

#### Abstract

In this study, mixed-oxides of  $Ti_{1-x}W_xO_2$  ( $0 \leq x \leq 0.3$ ) nanomaterials have been synthesized via a multistep sol-gel process. The effect of W doping on the anatase structure and on the electrical conductivity of the material was investigated. Photo-electrochemical action spectra and UV-vis spectroscopy were used to determine the band-gap energy of the mixed-oxides. The electrochemical stability of these materials was also investigated before they were tested as substrate for platinum nanocatalysts for oxygen reduction reaction. The metal was deposited onto the support either via the chemical route (carbonyl method) or via UV-irradiation.

#### Graphical abstract

A series of mixed-oxide of  $TiO_2$  has been prepared via a multistep sol-gel chemical process. The effect of W doping on the anatase structure and on the electrical conductivity of the material was investigated.



**Keywords**TiO<sub>2</sub>; Sol-gel; Photoelectrochemistry; ORR; Substrate

Corresponding author. Tel.: +33 54945 3625; fax: +33 54945 3580.

- 1 Present address: Institute of Technical Thermodynamics/Electrochemical Energy Technology, German Aerospace Center (DLR), Pfaffenwaldring 38-40, 70569 Stuttgart, Germany.

Copyright © 2013 Elsevier B.V. All rights reserved.

[About ScienceDirect](#)[Contact and support](#)[Information for advertisers](#)[Terms and conditions](#)[Privacy policy](#)

Copyright © 2014 Elsevier B.V. except certain content provided by third parties. ScienceDirect® is a registered trademark of Elsevier B.V.

Cookies are used by this site. To decline or learn more, visit our [Cookies page](#)**Recommended articles****Hydrogen peroxide assisted rapid synthesis of TiO...**2014, Applied Catalysis B: Environmental [more](#)**Critical role of water in the direct oxidation of CO ...**2014, Applied Catalysis B: Environmental [more](#)**Platinum catalysts promoted by In doped SnO<sub>2</sub> su...**2014, Journal of Power Sources [more](#)[View more articles »](#)

---

**Citing articles (0)**

---

---

**Related book content**

---

