

PAPER • OPEN ACCESS

## Characterisation of a charged particle levitated nano-oscillator

To cite this article: N P Bullier *et al* 2020 *J. Phys. D: Appl. Phys.* **53** 175302

View the [article online](#) for updates and enhancements.



**IOP | ebooks™**

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of every title for free.

# Characterisation of a charged particle levitated nano-oscillator

N P Bullier<sup>✉</sup>, A Pontin<sup>✉</sup> and P F Barker

Department of Physics and Astronomy, University College London, Gower Street, London WC1E 6BT, United Kingdom

E-mail: [nathanael.bullier.15@ucl.ac.uk](mailto:nathanael.bullier.15@ucl.ac.uk), [a.pontin@ucl.ac.uk](mailto:a.pontin@ucl.ac.uk) and [p.barker@ucl.ac.uk](mailto:p.barker@ucl.ac.uk)

Received 1 August 2019, revised 19 January 2020

Accepted for publication 30 January 2020

Published 21 February 2020



## Abstract

We describe the construction and characterisation of a nano-oscillator formed by a Paul trap. The frequency and temperature stability of the nano-oscillator was measured over several days allowing us to identify the major sources of trap and environmental fluctuations. We measure an overall frequency stability of  $2 \text{ ppm h}^{-1}$  and a temperature stability of more than 5 h via the Allan deviation. Importantly, we find that the charge on the nanoscillator is stable over a timescale of at least two weeks and that the mass of the oscillator, can be measured with a 3% uncertainty. This allows us to distinguish between the trapping of a single nanosphere and a nano-dumbbell formed by a cluster of two nanospheres.

Keywords: Paul trap, nanoparticle, quantum mechanics

(Some figures may appear in colour only in the online journal)

## 1. Introduction

Nanoscale levitated optomechanical systems are currently of considerable interest for exploring the macroscopic limits of quantum mechanics [1–3], for sensing of short range forces [4], and for exploring non-equilibrium thermodynamics [5]. Unlike typical optomechanical systems, levitation offers good isolation from the environment while only a few mechanical degrees of freedom need be considered. The ability to turn-off the trapping potential allows field free experiments such as matter-wave interferometry [6, 7] and precision measurements of forces [8]. Optical and magnetic levitation of nanoparticles have been demonstrated with cooling to microKelvin temperatures [9, 10]. While optical levitation is well developed and allows relatively high mechanical frequencies, it is fundamentally limited for many applications by the unavoidable photon recoil heating introduced by the laser used for trapping [11]. Levitation of charged nanoparticles via a Paul trap, is an attractive alternative that minimises or even avoids such heating. A hybrid electro-optical cavity system has been

used to demonstrate cavity cooling of nanoparticles [12, 13]. Similar schemes are being considered for testing mechanisms of wavefunction collapse at macroscopic scales by measuring the reheating rate of a cooled oscillator [14, 15]. In order to perform both of those experiments, the stability and the noise needs to be well characterised. Moreover, a precise knowledge of the mass, the number of charges and their stability over time is required. For instance in the hybrid trap, the cooling process depends on the number of charges. The Paul trap is a promising platform for these studies as it has been a key tool for quantum science and technology [16–18]. It has been utilised for the creation of stable atomic clocks and for the demonstration of important protocols in quantum computation and information [18, 19]. In these traps, atomic and molecular ions can be laser cooled to their ground state and trapped in isolation for days. Key to their utilisation has been that a deep and stable low noise electrical potential can be readily created. Many charged nanoparticle traps [12, 18, 20–26] have been demonstrated but there are few reports characterising their long term stability and noise, which is crucial for applications in quantum optomechanics and for testing fundamental physics.

In this paper we describe the detailed characterisation of a nano-oscillator formed by a Paul trap and assess this platform

 Original content from this work may be used under the terms of the [Creative Commons Attribution 4.0 licence](https://creativecommons.org/licenses/by/4.0/). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

for its use in quantum optomechanics experiments including a hybrid electro-optical trap [12, 13] and for future non-interferometric tests of the macroscopic limits of quantum mechanics [14, 15]. We discuss different ways of measuring the size and mass of the particle and estimate its centre-of-mass temperature based on those results. We describe measurements that determine the stability of the Paul trap over time, and the effects of the loading mechanism and temperature fluctuations.

## 2. Paul trap description

A levitated nano-oscillator is produced by trapping a single charged silica nanoparticle in a Paul trap. Silica nanoparticles are suspended in ethanol at a concentration of  $10 \mu\text{g ml}^{-1}$ . Prior to loading, the solution is left in an ultrasonic bath for 20 min to restore monodispersity. As shown in figure 1, an aerosol of this solution is created by means of electrospray ionisation [23, 27] by applying 1.8 kV (of either polarity) on a needle with a  $100 \mu\text{m}$  internal diameter. This aerosol of particles is entrained into the gas flow which enters a capillary tube that leads directly into the first pumping stage. The capillary is 5 cm long with a  $250 \mu\text{m}$  internal diameter. This first vacuum stage is kept at a pressure of approximately 2 mbar by directly connecting it to a scroll pump. The flux of particles travels through a skimmer with a 0.4 mm aperture. The skimmer isolates the first stage from the main chamber which is initially kept at a pressure of  $\sim 10^{-1}$  mbar during the loading phase. Once in the main chamber, some particles are guided through a 20 cm long quadrupole guide and their motion is damped by collisions with the surrounding gas so that the particles have low enough energy to be captured by the Paul trap where further dissipation occurs [28]. At  $5 \times 10^{-1}$  mbar, given our typical trap parameters and charge-to-mass ratio of  $0.5 \text{ C kg}^{-1}$ , a nanosphere with a velocity between 5 and  $15 \text{ m s}^{-1}$  will have a small enough kinetic energy to remain trapped. (A particle with a velocity of  $5 \text{ m s}^{-1}$  has a kinetic energy that corresponds to the effective depth of our trap). The guide is used as well to increase the flux of particles reaching the trap and is also shown in figure 2(a). Its end is placed  $\sim 3 \text{ mm}$  away from the Paul trap. By operating the guide in a mass filter configuration [29], where a high DC voltage is applied onto two electrodes, one can select a given charge-to-mass ratio. Note that since the trap and the guide have different geometries, the effective stability region is further reduced. We typically trap particles with charge-to-mass ratios in the range  $0.05 < q/m < 2 \text{ C kg}^{-1}$ . Once the trap is loaded, the guide is grounded to avoid any excess micromotion caused by the AC field of the guide. While loading the trap, droplets of solvent can be trapped as well as nanoparticles and can remain for hours in low vacuum. In order to ensure that we only observe bare silica nanoparticles, the pressure is reduced to  $\sim 10^{-4}$  mbar right after trapping to increase the evaporation speed. Currently, the pressure can then be reduced in the main chamber down to  $\sim 10^{-7}$  mbar and the particles can remain trapped at those pressures for weeks without any cooling.

An image of the linear Paul trap used for these studies is shown in figure 2(a). An AC potential is applied onto two rods

diagonally opposed, while the other two are grounded. The effective potential confines a charged particle in the  $x - y$  plane. An additional DC voltage is applied onto two endcap electrodes to trap the particle along the  $z$ -axis. With this geometry, the electric potential  $\Phi(x, y, z, t)$  close to the centre of the trap is given by [30]

$$\Phi(x, y, z, t) = \frac{V_o}{2} \left( 1 + \eta \frac{x^2 - y^2}{r_o^2} \right) \cos(\omega_d t) + \frac{\kappa U_o}{z_o^2} (z^2 - \epsilon x^2 - (1 - \epsilon)y^2), \quad (1)$$

where  $r_o$  is the distance between the centre of the trap and the rod electrodes providing the AC field. The distance between the centre of the trap and the endcap electrodes which provide the DC field is defined to be  $z_o$ .  $V_o \cos(\omega_d t)$  and  $U_o$  are the applied potentials and  $\omega_d$  is the drive frequency, typically in the range of 1 to 10 kHz, and  $\eta$  and  $\kappa$  are geometrical efficiency coefficients [31, 32] quantifying non-perfect quadratic potentials. The trap ellipticity is given by  $\epsilon$ , which is here equal to 0.5 because of the symmetry of the trap in the  $x - y$  plane. Those parameters are obtained from numerical finite element method (FEM) simulations of the electric field with values given in the caption of figure 2.

The trapped particle feels an effective pseudo-potential  $\phi(x, y) = \frac{q}{4m\omega_d^2} |\nabla V(x, y)|^2$  with  $V(x, y) = \frac{V_o}{2} \left( 1 + \eta \frac{x^2 - y^2}{r_o^2} \right)$ , where  $q/m$  is the charge-to-mass ratio of the nanoparticle. The dynamics of the nanosphere in the potential shown in equation (1) are governed by three Mathieu equations with stability parameters  $a_i$  and  $q_i$  [30]. They quantify the stability of the motion along the  $i$ -axis given by the AC and DC potential, respectively and are given by

$$\begin{aligned} a_x = a_y = -\frac{1}{2}a_z = -\frac{q}{m} \frac{4\kappa U_o}{z_o^2 \omega_d^2}, \\ q_x = -q_y = \frac{q}{m} \frac{2\eta V_o}{r_o^2 \omega_d^2}, \quad q_z = 0. \end{aligned} \quad (2)$$


If  $|a_i| \ll 1$  and  $|q_i| \ll 1$ , the secular frequencies can be well approximated by

$$\omega_i \approx \frac{\omega_d}{2} \sqrt{a_i + \frac{1}{2}q_i^2}. \quad (3)$$


The Mathieu equations can be rewritten to incorporate the damping term  $\gamma$ . A new stability parameter  $b_i$  can then be defined as  $b_i = a_i - \frac{\gamma^2}{\omega_d^2}$  to replace the initial  $a_i$  parameter [33]. At pressures lower than 1 mbar we have  $|b_i| \ll 1$  and the effect of the damping on the trap stability becomes negligible.

The electrode supports are realised on a printed circuit board (PCB)<sup>1</sup> whose layout is shown in figures 2(b) and (c). The stainless steel electrodes of the trap are rods of 0.5 mm diameter which seat into the holes of the PCB. One plated through hole on each PCB in the middle of the rods is used as an endcap. The two PCB boards (and therefore the endcaps) are kept at a distance of 7.0 mm. Both the traces and the

<sup>1</sup> The PCB is a RO4003C by Rogers.



**Figure 1.** A schematic of the experimental setup. Nanoparticles suspended in ethanol are electrosprayed at atmospheric pressure. The aerosol is entrained into the first pumping stage which is kept at a pressure of 2 mbar. The charged nanoparticles are directed through a beam skimmer and enter the main vacuum chamber, which is kept at a pressure of  $\sim 10^{-1}$  mbar during the loading phase. It is then guided inside an electric quadrupole guide towards the trap. The nanoparticle is illuminated with a green diode laser along the  $x$ -axis. The motion of the particle is imaged in the  $x - z$  plane with a low-cost CMOS camera placed along the  $y$ -axis.




**Figure 2.** (a) An image of the linear Paul trap loaded with a nanoparticle in its centre. The end of the quadrupole guide can be seen on the right-hand side of the picture. (b) The PCB layout of the internal side of the trap. The five holes at the top of the layout are used for the trap connections. The pad in the centre of the five holes is used as an endcap. The other four holes are used as both holders and electrical connections to the four rods constituting the trap. Tracks made out of gold coated copper are shown in black. (c) The PCB layout on the external side of the trap. The connections to the PCB board are done on the lower part of the PCB on the five lower holes. (d) A scanning electron microscope (SEM) image of the nanoparticles used. The trap parameters discussed in the main text are the following:  $r_o = 1.1$  mm,  $z_o = 3.5$  mm,  $\eta = 0.82$ ,  $\kappa = 0.086$ , and  $\epsilon = 0.5$ .

holes are gold coated to minimise patch potentials [34]. Using a PCB to support the electrodes allows flexibility in making the electrical connections to the rods and keep to a minimum their effect on the potential of the trap. The substrate used here (RO4003C<sup>2</sup>) is a ceramic-filled woven glass that is compatible with ultra-high vacuum [35, 36]. The PCB tracks are separated at least by  $225 \mu\text{m}$  and are chosen to avoid a voltage breakdown at any pressure with the typical AC voltages applied of  $\sim 500$  V peak-to-peak.


### 3. Particle detection and characterisation

The particle is detected by illumination with a green laser diode directed along the  $x$ -axis of the trap. A typical power of 40 mW with a beam waist of  $250 \mu\text{m}$  was used. The motion of the particle in the  $x - z$  plane is monitored by using a low-cost CMOS camera which detects the scattered light in the  $y$ -direction (see figure 1) [37]. This enables us to detect the stochastic motion of the nanoparticle driven by thermal noise and other unknown noises from which we can extract the particle damping  $\gamma$ , frequency of oscillation  $\omega_i$  (along the  $i$ th-axis) and amplitude. The one-sided power spectral density (PSD) of the motion along the  $i$ th-axis can be written as  $S_i(\omega) = |\chi(\omega)|^2 (S_{th} + S_F(\omega))$  where  $\chi(\omega) = (m(\omega_i^2 - \omega^2 - i\gamma\omega))^{-1}$  is the mechanical susceptibility. The thermal force noise is given by  $S_{th} = 4k_B T m \gamma$

<sup>2</sup> See footnote 1.



**Figure 3.** (a) Calibrated displacement spectra of a levitated silica nanoparticle at  $1.2 \times 10^{-2}$  mbar. The figure shows the displacement PSD in blue (green) along the  $z$ -axis ( $x$ -axis). A fit to the PSD is shown in orange from which are extracted the secular frequency and the mechanical damping. (b) The camera is calibrated by moving it by a known amount. The figure shows the sum of the relative distances of the translation stage positions. The fit is shown in orange with the residuals in the inset. The calibration factor is found to be  $(8.75 \pm 0.09) \mu\text{m px}^{-1}$ .



**Figure 4.** Estimation of the particle size. (a) Gas damping as a function of pressure. Linewidth measurements from spectra are shown in blue and green corresponding respectively to the damping along the  $x$  and  $z$ -axis. The fit is shown in orange. The radius found is  $(199 \pm 57)$  nm assuming a density of  $1850 \text{ kg m}^{-3}$  and a spherical shape. (b) Monitoring of the secular frequencies over time along the  $x$  and  $z$ -axis ( $z$ -axis rescaled) shown respectively in orange and blue. A grid with constant separation of  $1.59 \pm 0.07$  Hz is added to the plots. It corresponds to the frequency shift given by one elementary charge. From the frequency shifts, we estimate the mass to be  $(9.6 \pm 0.9) \times 10^{-17}$  kg.

where  $m$  is the particle mass,  $T$  the bath temperature,  $k_B$  the Boltzmann constant, and  $S_F(\omega)$  the force noise of unknown sources.

### 3.1. Calibration of the motion

We calibrate the motion of the particle by placing the camera on a translation stage and displacing it by a known amount. Five time traces are taken at different stage positions. By calculating the mean position of the particle for each time trace, we directly map the stage position onto the camera pixel matrix since the particle behaves like a point source. After a simple linear regression, the example shown in figure 3(b) gives a displacement per pixel of  $(8.75 \pm 0.09) \mu\text{m px}^{-1}$ . Two independent uncertainties are taken into account. The uncertainty of the fit itself, which only accounts for 0.3%, while the uncertainty in the camera focus stability is 1%. This error is estimated by changing the focus on the trapped particle in a controlled manner. The focus is checked over days to correct for drifts in the camera mount or focus. Lastly, by ensuring that the residuals of the fit do not increase when the camera

is displaced away from the nanoparticle, we ensure that distortions due to the camera objective do not have to be taken into account. This method is competitive for measurements of low frequency oscillators in comparison to methods measuring the particle response to a known force, which can depend on more parameters with larger associated uncertainties [38]. We show an example of a calibrated displacement PSD of the nanoparticle in figure 3(a).

### 3.2. Size estimation

Different methods can be used to estimate the size (or mass) of the nanoparticles loaded into the trap with different accuracies [9, 20, 21, 39–41]. We use commercial silica nanospheres by *microParticles GmbH* with nominal density of  $1850 \text{ kg m}^{-3}$  and nominal radius of  $(194 \pm 5)$  nm. An SEM picture of the particles used is shown in figure 2(d). We find a radius of  $(186 \pm 4)$  nm from a sample of 223 imaged nanoparticles.


The particle size can as well roughly be determined by evaluating the gas damping as a function of pressure. This is done by measuring the linewidth of the displacement PSD. It is then

fitted to the expected gas damping law in the free molecular flow regime. Here [42, 43]:  $\gamma_{\text{gas}} = \frac{(1+\frac{\pi}{8})\bar{c}P_g m_g}{k_B T_b a \rho}$ , where the particle mean speed is  $\bar{c} = \sqrt{8k_B T_b/m_g/\pi}$ ,  $a$  and  $\rho$  the particle radius and density, respectively,  $k_B$  the Boltzmann constant,  $P_g$ ,  $m_g$  and  $T_b$  correspond to gas pressure, the mass of the gas molecules and the bath temperature, respectively. The bath temperature  $T_b$  can be assumed to remain at 293 K independently from both the centre-of-mass motion and the internal temperature of the nanosphere [44]. This gives a radius of  $(199 \pm 57)$  nm by assuming a nominal density of  $1850 \text{ kg m}^{-3}$  and a spherical shape (see figure 4(a)). The main uncertainty contribution is due to the pressure measurement (30%, specified by the manufacturer). On top of its large uncertainty, this method has a few drawbacks. It requires the knowledge of the density, which can significantly vary for silica nanospheres [45]. Furthermore, it only works for spheres and it can therefore be challenging to differentiate a single sphere from a cluster. Indeed, in the case of two particles joined together such as a nanodumbbell, the expected linewidth should be smaller by 8% compared to a sphere (independently from the size of the spheres and assuming a stochastic rotational motion of the dumbbell) [42], which is comparable to the statistical uncertainty of the measurement shown here. In comparison, a change in mass by a factor 2 for a spherical object corresponds to a reduction in linewidth by 21%, easier to measure. It is therefore challenging to differentiate with this method a nanodumbbell from a single nanosphere in a Paul trap. It can be more easily differentiated when the alignment with respect to the trap axis is well defined, such as in an optical tweezer [46].


In a Paul trap, a more attractive method to determine the mass consists of directly measuring it from the secular frequency shifts due to charge jumps [20, 40]. For a number of charges larger than  $\sim 50$ , the secular frequency along the  $x$ -axis can be approximated as  $\omega_x \approx \frac{\omega_d}{2\sqrt{2}} q_x$  (see equations (2) and (3)). The frequency shift given by one electron becomes  $\delta\omega_x = \frac{|e| V_0 \eta}{\sqrt{2m} \omega_d r_o^2}$  where  $e$  is the elementary charge. While we have monitored a constant number of charges for days, it can be changed (mostly increased in our case) by leaving the pressure gauge on [47], which gives a typical charging rate of  $\sim 7$  charges  $\text{h}^{-1}$ . Other ways of charging nanoparticles include using an electron gun [40] or a UV light source [9]. The jumps in the secular frequency can be seen in figure 4(b). Assuming that the smallest frequency jump corresponds to a change in a single elementary charge, we measure a mass of  $(9.6 \pm 0.9) \times 10^{-17}$  kg. Two strong motivations to use this method are that thermal equilibrium of the centre-of-mass motion with the bath is not required and no knowledge over the density is required. The systematic error in the mass uncertainty comes from the trap fabrication tolerances of  $\pm 50 \mu\text{m}$  in both the relative position of the holes and their diameter. This gives an uncertainty of 4% on  $r_o$ . The statistical error accounts for 4% and therefore the overall error on the mass is 9%. Using this method, statistical uncertainties as small as 100 ppm with systematic uncertainty of 1% have been demonstrated in mass-spectrometers [20, 40].

The mass of the particle can also be estimated by assuming thermal equilibrium at 293 K with the bath. We verify in the next section the validity of this assumption. However, it is reasonable because the very low intensity ( $40 \text{ W cm}^{-2}$  against  $10 \text{ MW cm}^{-2}$  for a typical optical tweezer) used to illuminate the particle is not sufficient to increase its internal temperature [44]. Moreover, these measurements are taken at a high pressure ( $10^{-2}$  mbar) where the heat transfer to the surrounding gas is very efficient. At this pressure, thermal noise dominates other sources of noise e.g. electrical noise. Following from the equipartition theorem, at thermal equilibrium,  $\frac{1}{2}k_B T_b = \frac{1}{2}m\omega_i^2 \langle i \rangle^2$ , where  $\langle i \rangle$  is the standard deviation of the motion along the  $i$ th-axis. This measurement offers the smallest uncertainty over the different mass measurements used here (3%) with  $m = (9.5 \pm 0.3) \times 10^{-17}$  kg. The mass was obtained after averaging 16 measurements. The total error is composed of a 1% statistical error and a 3% systematic error that takes into account the temperature uncertainty of 2%, an error of 1% on the frequency and of 2% on the variance of the displacement given by the calibration method. The uncertainty on this measurement could easily be reduced down to 2% by using a more precise temperature sensor. Another method, combining the thermal equilibrium assumption with a known force excitation has been demonstrated in [41]. It would however require a precise knowledge of the number of charges to be applied here.

Figure 5 summarises the different measurements described above. The measurements in blue and orange correspond to the measured mass obtained from thermal equilibrium. Those measurements are taken at a pressure of  $1.0 \times 10^{-2}$  mbar, with different camera magnifications and on two different days to check stability of the mass over time. The calibration used for the data in blue (orange) is  $(8.35 \pm 0.08) \mu\text{m px}^{-1}$  ( $(3.11 \pm 0.03) \mu\text{m px}^{-1}$ ). The green region corresponds to the uncertainty of the mass measurement (with one standard deviation) given by the charge jumps (see figure 4(b)). As the particle size distribution, obtained from the SEM images, is narrow and that there is good agreement between the two mass measurements, we have good confidence that this nanoparticle is a nanodumbbell, which can easily form from two particles held by Van der Waals forces [46]. Indeed, assuming a nominal density of  $1850 \text{ kg m}^{-3}$  (provided by the manufacturer), a nanodumbbell made of spheres of radius  $(186 \pm 4)$  nm gives a mass of  $(9.9 \pm 0.8) \times 10^{-17}$  kg (yellow region), which agrees very well with the different mass measurements. The density found when considering the mass given by the charge jumps with the size found on the SEM images gives  $(1781 \pm 196) \text{ kg m}^{-3}$ . Lastly, the grey region corresponds to the expected mass given by the linewidth measurement assuming a cluster of two particles [42]. Those different measurements demonstrate the lack of reliability of the linewidth measurement in a Paul trap, as we have to guess the particle shape. Indeed, if we assume the particle to be spherical, we measure a radius of 199 nm and if we assume a nanodumbbell made of two identical spheres, we estimate the radius (of one nanosphere) to be 182 nm, which corresponds to a relative error in mass of 35%.



**Figure 5.** The mass determination of the nanoparticle. The measurements in blue and orange are obtained by assuming thermal equilibrium of the motion at 293 K with the displacement calibrated with the camera. The measurements are taken on two different days at a pressure of  $1.0 \times 10^{-2}$  mbar. The calibration constant for the measurements in blue (orange) is  $(8.35 \pm 0.08) \mu\text{m px}^{-1}$  ( $(3.11 \pm 0.03) \mu\text{m px}^{-1}$ ). The grey and green regions correspond to the uncertainty of the mass measurements (one standard deviation) with the linewidth measurement (see figure 4(a)) and from the charge jumps (see figure 4(b)), respectively. The yellow region corresponds to the mass estimated of two nanospheres from the SEM image, assuming a nominal density of  $1850 \text{ kg m}^{-3}$  (see figure 2(d)). The equivalent estimated averaged radius of the spheres forming the nanodumbbell is shown on the scale on the right-hand side, assuming a nominal density of  $1850 \text{ kg m}^{-3}$ .



**Figure 6.** (a) The trapped centre-of-mass temperature of the particle as a function of pressure (without cooling). The temperature along the  $x$ -axis ( $z$ -axis) is shown in blue (orange). The motion is thermal ( $(282 \pm 25) \text{ K}$ ) down to  $\sim 10^{-4}$  mbar along the  $z$ -axis and to less than  $\sim 10^{-5}$  mbar along the  $x$ -axis. The temperature of the room at 293 K is indicated in green. (b) The relative Allan deviation of the temperature at  $1.6 \times 10^{-5}$  mbar along the  $x$ -axis ( $z$ -axis) is shown in blue (orange) and at  $7.2 \times 10^{-2}$  mbar in green (red).

The equivalent radii for a single sphere of the nanodumbbell are shown in figure 5.


### 3.3. Temperature estimation and stability

We use the mass measurement from the charge jumps to estimate the centre-of-mass temperature. The temperature is estimated at different pressures without any active cooling mechanism on the particle. The temperature is calculated in figure 6(a) with the motion calibrated with the camera. The blue (orange) data correspond to the motion along the  $x$  ( $z$ -axis). This proves that the motion is thermal ( $(282 \pm 25) \text{ K}$ ) down to  $\sim 10^{-4}$  mbar in the  $z$ -axis and to less than  $\sim 10^{-5}$  mbar in the  $x$ -axis. However, excess force noise increases the effective temperature of

the centre-of-mass motion at lower pressures. Despite the increasing temperature at low pressures as much as  $\sim 10^4 \text{ K}$ , the particle can be kept for weeks at  $10^{-7}$  mbar, as its temperature remains smaller than the equivalent trap depth of  $\sim 10^7 \text{ K}$ .

We are also interested in the stability of the effective temperature over time, as well as the optimum time over which this measurement should be made. In figure 6(b) we show the relative Allan deviation of the temperature  $\sigma_T(\tau)/T_0$  at different pressures. We define the relative Allan deviation of a variable  $V$  as  $\sigma_V(\tau)/V_0$  with  $V_0$  the averaged value of  $V$  and  $\sigma_V(\tau)$  the Allan deviation [48]

$$\sigma_V^2(\tau) = \frac{1}{N-1} \sum_{k=1}^{N-1} \frac{1}{2} \left( \bar{V}_{k+1}^{(\tau)} - \bar{V}_k^{(\tau)} \right)^2, \quad (4)$$



**Figure 7.** (a) Measurements of secular frequencies monitored over 6 d.  $\omega_x/2\pi$  is shown on the left ordinate (blue dataset),  $\omega_z/2\pi$  on the right one (green dataset). The three colour bands mark the time at which the charge-to-mass ratios were measured and are shown in figure 7(b). (b) Fits of the charge-to-mass ratios at different times by changing the end-cap voltage and monitoring the secular motion along the  $z$ -axis. The different times correspond to 15, 90 and 137 h, with charge-to-mass ratios of  $0.10 \text{ C kg}^{-1}$ ,  $0.16 \text{ C kg}^{-1}$  and  $0.18 \text{ C kg}^{-1}$ , respectively, shown going from lighter to darker colours. The stray field is anti-trapping (negative effective potential for a positively charged particle) as it needs to be compensated with a positive voltage to trap the particle. The strength of this stray field decreases over time.

where  $\bar{V}_k^{(\tau)}$  corresponds to the time average value of  $V$  inside  $N - 1$  intervals of varying length  $\tau$  with  $N$ , such that  $N\tau$  corresponds to the total measurement time. The Allan variance quantifies the stability of the system over time by effectively showing the optimal value of time needed to estimate the temperature. The measurements in blue (orange) are taken at  $1.6 \times 10^{-5}$  mbar monitored for 23 h along the  $x$ -axis ( $z$ -axis). We also show measurements at  $7.2 \times 10^{-2}$  mbar in green (red) along the  $x$ -axis ( $z$ -axis). The initial values and slopes match with the expected relative Allan deviation of a thermal oscillator  $\sqrt{\frac{2}{\gamma\tau}}$  [38]. This shows stability of the oscillator for a few hours, limited by the stability in the electrical potential. In comparison, stability over the 100 s range has been reported in optical tweezers, which were believed to be limited by the optical stability of the trap as well as its nonlinearities [38, 41]. Similar stability of  $\sim 100$  s were reported as well in other high frequency optomechanical systems [49].

#### 4. Paul trap stability

The particle stability in the Paul trap depends on several parameters such as the trapping mechanism, the pressure gauge and the material used for the trap itself.

##### 4.1. Stray fields due to the ion gauge and the electrospray loading mechanism


The creation of ions by the vacuum gauge leads to charging of the nanoparticle and changes in the trap potential. This leads to temporal changes in secular frequency as well as in the particle's mean position. The gauge therefore needs to be turned off for stable measurements. We monitor the secular frequencies  $\omega_x$  and  $\omega_z$  for almost one week when the gauge is turned on and off (see figure 7(a)). Both of these secular frequencies show very similar behaviour except initially, right after loading the trap. When the gauge is on, they follow an almost monotonic increase. The stable region shown in figure 7(b) occurs

when the pressure gauge has been turned off. To some extent, it is possible to separate the change in number of charges from a change in the potential. To do this we measured the charge-to-mass ratio at different times ( $t = 15, 90$  and  $137$  h) by changing the endcap potential and measuring the resulting frequency shift. The results are shown in figures 7(a) and (b) along with the respective fits which give an increasing charge-to-mass ratio. We find  $0.10 \text{ C kg}^{-1}$ ,  $0.16 \text{ C kg}^{-1}$  and  $0.18 \text{ C kg}^{-1}$  (10% standard error), from bottom to top. However, an additional stray potential needs to be accounted for, in order to obtain a reasonable agreement with the data. This offset directly quantifies the stray field along the  $z$ -axis as it corresponds to the minimum amount of endcap voltage needed to trap the particle which is ideally 0 V (see figure 7(b)). Here, a positive voltage is needed (8.8, 2.7 and 1.5 V, respectively).

Stray fields are also due to solvent droplets reaching the dielectric support of the trap during the loading phase. If the electrospray is kept in operation for sufficiently long times, the stray field can become quite strong even allowing for trapping in the  $z$ -direction without any additional endcap potential and providing a trap frequency in this axis of the order of  $\sim 100$  Hz. To verify this description we inverted the sign of the high voltage for the electrospray needle for a given time, to neutralise the charge build-up, to then go back to the usual configuration. As expected we found that in such a situation, the stray field given by the electrospray is anti-trapping; meaning more endcap potential is needed to trap the particle, as it is shown in figure 7(b). Furthermore, its strength is slowly decreasing as mentioned above.

##### 4.2. Potential drifts

Right after turning the ion gauge off, we have observed an exponential decay in the trapping field with a time constant of approximately 10 h. This characteristic time, consistently measured over tens of traces is likely to be due to the dielectric material used. Dielectric surfaces should therefore be kept in any trap as far as possible from the nanoparticle. Some of the charging effects during the loading phase could be mitigated



**Figure 8.** (a) Measurement of the secular frequency over time along the  $x$  ( $z$ -axis) is shown in blue (orange) while keeping the particle at a pressure of  $1.6 \times 10^{-5}$  mbar. The measurements are taken right after turning the pressure gauge off. An exponential rise of 10.7 h is fitted along the  $z$ -axis (fit shown in black dotted lines). (b) A plot of the temperature drifts of the room (in orange) and of the secular frequency (in blue) along the  $x$ -axis at the same time. (c) Measurements of the drifts of the particle mean position over time (from dark colours to light ones) in the trap along the  $x$  and  $z$ -directions for the same data set as the one shown in (a). (d) The relative Allan deviation of the secular frequency along the  $x$ -axis ( $z$ -axis) is shown in blue (orange) at  $1.6 \times 10^{-5}$  mbar and in green (red) at  $7.6 \times 10^{-2}$  mbar. *Note:* The data shown in (a), (c) and (d) at  $1.6 \times 10^{-5}$  mbar are from the same data set with the same particle as the one characterised in section 3.

by using both a bent and longer guide, or by using a loading mechanism free of solvent [20, 26]. In figure 8(a), we show the stability of the secular frequencies along the  $x$  and  $z$ -axis right after turning the pressure gauge off. The exponential rise along the  $z$ -axis has a characteristic time of 10.7 h. On top of the exponential rise, a very periodic modulation (period of  $\sim 20$  min) can be seen in the secular frequency along the  $x$ -axis. This modulation is correlated to changes in the temperature of the room as shown in figure 8(b), and is fully attributable to temperature induced changes in the amplitude of the signal generator, high voltage amplifier and other electronics used to provide the trapping AC field. This corresponds to a slow modulation of approximately 1 V (peak to peak) in the amplitude of the signal applied to the trap electrodes (0.2% of the applied signal). Those drifts could easily be reduced with a better temperature stabilisation.

In figure 8(c), we show the averaged position in the  $x - z$  plane over time for the same data as shown in figure 8(a). One sample corresponds to 2.5 min. The time is shown with a colour gradient, starting with black at  $t = 0$ , and ending in yellow at  $t = 23$  h. Correlations can be seen between the drifts in the secular frequency along the  $z$ -axis and the motion along the same axis. The same can be noticed along the  $x$ -axis. This shows that the same potential drifts are responsible for both

changes in the mean position of the nanoparticle in the trap as well as its secular frequencies. Lastly, we show in figure 8(d) the relative Allan deviation  $\sigma_f(\tau)/f_0$  of the two secular frequencies monitored for 23 h with  $f_0$  the averaged frequency. The Allan deviation is calculated on the frequency time traces shown in figure 8(a). We get in this case a frequency stability of more than 20 min with a relative uncertainty on the frequency of  $\sim 30$  ppm along the  $z$ -axis (orange line) and with overall drifts of  $60$  ppm  $h^{-1}$ . Along the  $x$ -axis (blue line), we recover the periodicity ( $\sim 30$  min) also shown in figure 8(a), as the frequency periodically gets closer to its initial value. We show in figure 8(a) the stability of the frequency along the  $z$ -axis ( $x$ -axis) at  $7.2 \times 10^{-2}$  mbar. These data cover 32 h of continuous acquisition that started 33 h after having turned off the pressure gauge, to ensure a better stability. As expected, longer optimal times of at least 5 h were obtained. The optimum time is likely to be even longer since the drifts are not yet limiting the Allan deviation. Furthermore the behaviour above 500 min is likely to be caused by aliasing of the frequency fluctuations. Lastly, in this more stable case, a low frequency drift of  $2$  ppm  $h^{-1}$  ( $21$  ppm  $h^{-1}$ ) was obtained along the  $x$ -axis ( $z$ -axis). This demonstrates, that despite the use of a dielectric and the different stray fields mentioned above, a competitive frequency stability can still be achieved [20].

## 5. Conclusion

To conclude, we have characterised the size, temperature and stability of a charged particle levitated nano-oscillator. Thermal equilibrium and charge jumps can be used to measure efficiently the mass of a nanoparticle in a Paul trap, providing sufficient accuracy to distinguish between masses of one or several particles. In fact, we clearly demonstrate trapping of a nanodumbbell. As shown here, when the oscillator frequency is small enough ( $<1$  kHz), a camera can be used to calibrate the motion accurately. We have shown that the PCB substrate, loading mechanism, temperature fluctuations and ion gauge can modify the trapping potential and therefore the stability of the oscillator. Despite those fluctuations, drifts as small as  $2 \text{ ppm h}^{-1}$  in the trapping frequency were obtained over hours of measurement. Furthermore, a temperature stability larger than five hours were reported with a stable number of charges over weeks. The stray fields discussed above can be mitigated with stronger filtering of the charge-to-mass ratios of nanoparticles in the guide in combination with a longer and bent guide. Furthermore, the internal face of the PCB board can be fully grounded [50] to considerably reduce the stray fields accumulated on the dielectric surface due to both the loading process and the ion gauge. Those changes should increase the overall stability of the system needed for experiments which aim to use nanoparticles in a Paul trap for tests of wavefunction collapse [14, 15]. In addition, the precise knowledge of the mass and number of charges, combined with the methods identified to increase stability will significantly enhance experiments with the hybrid electro-optical trap which aims to cool trapped particles to their ground state [13]. Lastly, the ability to stably trap and characterise the centre-of-mass motion of an anisotropic particle like a nanodumbbell will be useful for future experiments that aim to explore rotational optomechanics in the absence of optical fields [51].

## Acknowledgments

The authors would like to thank Thomas Penny for interesting discussions and Jonathan Gosling for taking the SEM picture. The authors acknowledge funding from the EPSRC Grant No. EP/N031105/1 and from the EU H2020 FET project TEQ (Grant No. 766900). N P B acknowledges funding from the EPSRC Grant No. EP/L015242/1. AP has received funding from the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie Grant Agreement No. 749709.

## ORCID iDs

N P Bullier  <https://orcid.org/0000-0003-4321-671X>  
A Pontin  <https://orcid.org/0000-0002-9705-697X>

## References

- [1] Romero-Isart O, Pflanzner A C, Juan M L, Quidant R, Kiesel N, Aspelmeyer M and Cirac J I 2011 Optically levitating dielectrics in the quantum regime: theory and protocols *Phys. Rev. A* **83** 013803
- [2] Chang D E, Regal C A, Papp S B, Wilson D J, Ye J, Painter O, Kimble H J and Zoller P 2010 Cavity opto-mechanics using an optically levitated nanosphere *Proc. Natl Acad. Sci.* **107** 1005–10
- [3] Barker P F and Shneider M N 2010 Cavity cooling of an optically trapped nanoparticle *Phys. Rev. A* **81** 023826
- [4] Geraci A A, Papp S B and Kitching J 2010 Short-range force detection using optically cooled levitated microspheres *Phys. Rev. Lett.* **105** 101101
- [5] Rondin L, Gieseler J, Ricci F, Quidant R, Dellago C and Novotny L 2017 Direct measurement of Kramers turnover with a levitated nanoparticle *Nat. Nanotechnol.* **12** 1130–3
- [6] Kaltenbaek R et al 2016 Macroscopic quantum resonators (MAQRO): 2015 update *EPJ Quantum Technol.* **3** 5
- [7] Bateman J, Nimmrichter S, Hornberger K and Ulbricht H 2014 Near-field interferometry of a free-falling nanoparticle from a point-like source *Nat. Commun.* **5** 4788
- [8] Ranjit G, Cunningham M, Casey K and Geraci A A 2016 Zeptonewton force sensing with nanospheres in an optical lattice *Phys. Rev. A* **93** 053801
- [9] Slezak B R, Lewandowski C W, Hsu J-F and D'Urso B 2018 Cooling the motion of a silica microsphere in a magneto-gravitational trap in ultra-high vacuum *New J. Phys.* **20** 063028
- [10] Tebbenjohanns F, Frimmer M, Militaru A, Jain V and Novotny L 2019 Cold damping of an optically levitated nanoparticle to microkelvin temperatures *Phys. Rev. Lett.* **122** 223601
- [11] Jain V, Gieseler J, Moritz C, Dellago C, Quidant R and Novotny L 2016 Direct measurement of photon recoil from a levitated nanoparticle *Phys. Rev. Lett.* **116** 243601
- [12] Millen J, Fonseca P Z G, Mavrogordatos T, Monteiro T S and Barker P F 2015 Cavity cooling a single charged levitated nanosphere *Phys. Rev. Lett.* **114** 123602
- [13] Fonseca P Z G, Aranas E B, Millen J, Monteiro T S and Barker P F 2016 Nonlinear dynamics and strong cavity cooling of levitated nanoparticles *Phys. Rev. Lett.* **117** 173602
- [14] Goldwater D, Paternostro M and Barker P F 2016 Testing wave-function-collapse models using parametric heating of a trapped nanosphere *Phys. Rev. A* **94** 010104
- [15] Vinante A, Pontin A, Rashid M, Toroš M, Barker P F and Ulbricht H 2019 Testing collapse models with levitated nanoparticles: detection challenge *Phys. Rev. A* **100** 012119
- [16] Van Dyck R S, Schwinberg P B and Dehmelt H G 1977 Precise measurements of axial, magnetron, cyclotron, and spin-cyclotron-beat frequencies on an isolated 1 meV electron *Phys. Rev. Lett.* **38** 310–4
- [17] Paul W 1990 Electromagnetic traps for charged and neutral particles *Rev. Mod. Phys.* **62** 531–40
- [18] Leibfried D, Blatt R, Monroe C and Wineland D 2003 Quantum dynamics of single trapped ions *Rev. Mod. Phys.* **75** 281–324
- [19] Ludlow A D, Boyd M M, Ye J, Peik E and Schmidt P O 2015 Optical atomic clocks *Rev. Mod. Phys.* **87** 637–701
- [20] Schlemmer S, Illemann J, Wellert S and Gerlich D 2001 Nondestructive high-resolution and absolute mass

- determination of single charged particles in a three-dimensional quadrupole trap *J. Appl. Phys.* **90** 5410–8
- [21] Cai Y, Peng W-P, Kuo S-J, Lee Y T and Chang H-C 2002 Single-particle mass spectrometry of polystyrene microspheres and diamond nanocrystals *Anal. Chem.* **74** 232–8
- [22] Alda I, Berthelot J, Rica R A and Quidant R 2016 Trapping and manipulation of individual nanoparticles in a planar Paul trap *Appl. Phys. Lett.* **109** 163105
- [23] Nagornykh P, Coppock J E and Kane B E 2015 Cooling of levitated graphene nanoplatelets in high vacuum *Appl. Phys. Lett.* **106** 244102
- [24] Bullier N P, Pontin A and Barker P F 2017 Millikelvin cooling of the center-of-mass motion of a levitated nanoparticle *Optical Trapping and Optical Micromanipulation XIV (SPIE)* (<https://doi.org/10.1117/12.2275678>)
- [25] Partner H L, Zoll J, Kuhlicke A and Benson O 2018 Printed-circuit-board linear Paul trap for manipulating single nano- and microparticles *Rev. Sci. Instrum.* **89** 083101
- [26] Bykov D S, Mestres P, Dania L, Schmöger L and Northup T E 2019 Direct loading of nanoparticles under high vacuum into a Paul trap for levitodynamical experiments *Appl. Phys. Lett.* **115** 034101
- [27] Fenn J B, Mann M, Meng C K, Wong S F and Whitehouse C M 1990 Electrospray ionization-principles and practice *Mass Spectrom. Rev.* **9** 37–70
- [28] Danell R M, Danell A S, Glish G L and Vachet R W 2003 The use of static pressures of heavy gases within a quadrupole ion trap *J. Am. Soc. Mass Spectrom.* **14** 1099–109
- [29] March R E 2009 Quadrupole ion traps *Mass Spectrom. Rev.* **28** 961–89
- [30] Berkeland D J, Miller J D, Bergquist J C, Itano W M and Wineland D J 1998 Minimization of ion micromotion in a Paul trap *J. Appl. Phys.* **83** 5025–33
- [31] Syms R R A, Tate T J, Ahmad M M and Taylor S 1998 Design of a microengineered electrostatic quadrupole lens *IEEE Trans. Electron Devices* **45** 2304–11
- [32] Madsen M, Hensinger W, Stick D, Rabchuk J and Monroe C 2004 Planar ion trap geometry for microfabrication *Appl. Phys. B* **78** 639–51
- [33] Hasegawa T and Uehara K 1995 Dynamics of a single particle in a Paul trap in the presence of the damping force *Appl. Phys. B* **61** 159–63
- [34] Turchette Q A *et al* 2000 Heating of trapped ions from the quantum ground state *Phys. Rev. A* **61** 063418
- [35] Rouki C 2003 Ultra-high vacuum compatibility measurements of materials for the CHICSi detector system *Phys. Scr. T* **104** 107
- [36] Westerberg L, Avdeichikov V, Carlén L, Golubev P, Jakobsson B, Rouki C, Siwek A, van Veldhuizen E and Whitlow H 2003 CHICSi—a compact ultra-high vacuum compatible detector system for nuclear reaction experiments at storage rings. I. General structure, mechanics and UHV compatibility *Nucl. Instrum. Methods Phys. Res. A* **500** 84–95
- [37] Bullier N P, Pontin A and Barker P F 2019 Super-resolution imaging of a low frequency levitated oscillator *Rev. Sci. Instrum.* **90** 093201
- [38] Hebestreit E, Frimmer M, Reimann R, Dellago C, Ricci F and Novotny L 2018 Calibration and energy measurement of optically levitated nanoparticle sensors *Rev. Sci. Instrum.* **89** 033111
- [39] Li T, Kheifets S and Raizen M G 2011 Millikelvin cooling of an optically trapped microsphere in vacuum *Nat. Phys.* **7** 527–30
- [40] Seo S-C, Hong S-K and Boo D W 2003 Single nanoparticle ion trap (SNIT): a novel tool for studying *in situ* dynamics of single nanoparticles *Bull. Korean Chem. Soc.* **24** 552–4
- [41] Ricci F, Cuairan M T, Conangla G P, Schell A W and Quidant R 2019 Accurate mass measurement of a levitated nanomechanical resonator for precision force-sensing *Nano Lett.* **10** 6711–5
- [42] Corson J, Mulholland G W and Zachariah M R 2017 Calculating the rotational friction coefficient of fractal aerosol particles in the transition regime using extended Kirkwood–Riseman theory *Phys. Rev. E* **96** 013110
- [43] Epstein P S 1924 On the resistance experienced by spheres in their motion through gases *Phys. Rev.* **23** 710–33
- [44] Millen J, Deesuwan T, Barker P and Anders J 2014 Nanoscale temperature measurements using non-equilibrium brownian dynamics of a levitated nanosphere *Nat. Nanotechnol.* **9** 425–9
- [45] Parnell S R, Washington A L, Parnell A J, Walsh A, Dalglish R M, Li F, Hamilton W A, Prevost S, Fairclough J P A and Pynn R 2016 Porosity of silica Stöber particles determined by spin-echo small angle neutron scattering *Soft Matter* **12** 4709–14
- [46] Ahn J, Xu Z, Bang J, Deng Y-H, Hoang T M, Han Q, Ma R-M and Li T 2018 Optically levitated nanodumbbell torsion balance and GHz nanomechanical rotor *Phys. Rev. Lett.* **121** 033603
- [47] Frimmer M, Luszcz K, Ferreira S, Jain V, Hebestreit E and Novotny L 2017 Controlling the net charge on a nanoparticle optically levitated in vacuum *Phys. Rev. A* **95** 061801
- [48] Allan D 1966 Statistics of atomic frequency standards *Proc. IEEE* **54** 221–30
- [49] Pontin A, Bonaldi M, Borrielli A, Cataliotti F S, Marino F, Prodi G A, Serra E and Marin F 2014 Detection of weak stochastic forces in a parametrically stabilized micro-optomechanical system *Phys. Rev. A* **89** 023848
- [50] Brown K R, Clark R J, Labaziewicz J, Richerme P, Leibbrandt D R and Chuang I L 2007 Loading and characterization of a printed-circuit-board atomic ion trap *Phys. Rev. A* **75** 015401
- [51] Stickler B A, Papendell B, Kuhn S, Schrinski B, Millen J, Arndt M and Hornberger K 2018 Probing macroscopic quantum superpositions with nanorotors *New J. Phys.* **20** 122001