



**EFFECT OF NOZZLE DIAMETER AND VOLUME  
CAVITY AT VARIOUS DISTANCES FOR  
ELECTRONIC COOLING**

**MUHAMMAD HAFIZ BIN MOHD DIN**

**(2014662672)**

**BACHELOR OF MECHANICAL ENGINEERING  
(MANUFACTURING) (HONS.)**

**UNIVERSITI TEKNOLOGI MARA (UITM)**

**JULY 2017**

### **Declaration by the Candidate**

“I declared that this thesis is the result of my own work except the ideas and summaries which I have clarified their sources. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any degree.”

Signed : .....

Date : .....

**Muhammad Hafiz Bin Mohd Din**

UiTM No : 2014662672

## **Acknowledgement**

Alhamdulillah, thanks to Allah, the Merciful, the Beneficent. I have done the entire task and process on my thesis within the given time. It was the tough time for me to complete this thesis because this project was not easy as expected because there were a lot of knowledge need to learn and a lot of experiments need to be done. However, I was done my thesis successfully by helping from other people to support me by giving and sharing knowledge during working time. I would like to acknowledge those people that helped me during that time. Firstly, very thankful to my parent that always support me by giving advice and pray for me. I would like to give a lot of appreciation to Ir. Sh Mohd Firdaus Bin Sh Abdul Nasir for accepting and also supervise me to complete my project. He was very accommodating and be patient with me and my partner project. I'm deeply thankful to him for giving me a lot of information about my project and guide me. Also, thank to my laboratory partner Muhammad Fadhil Luqman and Akhbar for exchange of knowledge. Last but not least, I would like to thank Universiti Teknologi MARA for the opportunity to finish my research and completing my thesis.

## **Abstract**

Synthetic jet actuator working by injecting air to dissipate from heated electronic surface. It contains two main parts which are the case and piezoelectric diaphragm. Major advantage was on the device size that smaller compare to the cooling fan, low on dust trap at cooling device with low operation power consumption. The optimization of design synthetic jet is crucial in order to maximize the heat dissipation for a heated electronic device. This research will cover the synthetic jet effect at various volumes and nozzle diameter with various distances to the heated surface on the heat transfer coefficient value effect of various volumes and nozzle diameter at various distances. There are 25 models design with different cavity volume and nozzle diameter have been fabricated using 3D printer. Result obtained from the temperature drop for each experiment has been shown in heat transfer coefficient value. Result shows that small nozzle diameter with smaller cavity volume give the highest value of heat transfer coefficient. The increasing of heat transfer coefficient value shows the efficiency of the synthetic jet device at the optimum condition in dissipates the heat. However, the effective distance from nozzle to the heated surface was depending on the nozzle diameter and cavity volume. Maximum temperature drop was  $41.57^{\circ}\text{C}$  for synthetic jet model 2mm nozzle diameter and 1mm cavity volume at distance 50mm from nozzle to the heated surface. The maximum value of heat transfer coefficient was  $65.82 \text{ W/m}^2\text{C}$  for the same model and distance.

## Table of Contents

<b>CHAPTER</b>	<b>CONTENT</b>	<b>PAGE</b>
	<b>Declaration by the Candidate</b>	<b>i</b>
	<b>Supervisor Certification</b>	<b>ii</b>
	<b>Acknowledgement</b>	<b>iv</b>
	<b>Abstract</b>	<b>v</b>
	<b>Table of Contents</b>	<b>vi</b>
	<b>List of Figures</b>	<b>viii</b>
	<b>List of Table</b>	<b>x</b>
<b>CHAPTER 1</b>		<b>1</b>
	<b>1.1 Background Study</b>	<b>1</b>
	<b>1.2 Problem Statement</b>	<b>6</b>
	<b>1.3 Objective</b>	<b>6</b>
	<b>1.4 Scope of Work</b>	<b>7</b>
	<b>1.5 Report Outline</b>	<b>7</b>
<b>CHAPTER 2</b>		<b>8</b>
	<b>2.1 Heater Performance</b>	<b>8</b>
	<b>2.2 Synthetic Jet Design on Volume Shape and Diameter Nozzle</b>	<b>11</b>
	<b>2.3 Synthetic Jet Effect to the Volume of Cavity</b>	<b>14</b>
	<b>2.4 Synthetic Jet Performance Effect to Nozzle Diameter</b>	<b>16</b>