

DEFORMATION AND FAILURE BEHAVIOUR OF SUGARCANE BAGASSE  
REINFORCED PP

Juliana Anggono<sup>1</sup>, Ágnes Elvira Farkas<sup>2,3</sup>, András Bartos<sup>2,3</sup>, János Móczó<sup>2,3</sup>, Antoni<sup>4</sup>, Hariyati Purwaningsih<sup>5</sup>, Béla Pukánszky<sup>2,3</sup>

<sup>1</sup>Mechanical Engineering Department, Petra Christian University, Jalan Siwalankerto 121-131, Surabaya 60236, Indonesia

<sup>2</sup>Institute of Materials and Environmental Chemistry, Research Centre for Natural Sciences, Hungarian Academy of Sciences, H-1519 Budapest, P.O. Box 286, Hungary

<sup>3</sup>Laboratory of Plastics and Rubber Technology, Department of Physical Chemistry and Materials Science, Budapest University of Technology and Economics, H-1521 Budapest, P.O. Box 91, Hungary

<sup>4</sup>Civil Engineering Department, Petra Christian University, Jalan Siwalankerto 121-131, Surabaya 60236, Indonesia

<sup>5</sup>Materials and Metallurgical Engineering Department, Sepuluh Nopember Institute of Technology, Jalan Raya ITS Keputih Sukolilo, Surabaya 60111, Indonesia

Corresponding author: (András Bartos or János Móczó)

ABSTRACT

Polypropylene composites were prepared from sugarcane bagasse fibers by extrusion and injection molding. Wood flour was used as reference filler in the study. The fiber content of the composites

changed between 0 and 30 wt% in 5 wt% steps. A maleated polypropylene was used as coupling agent to improve interfacial adhesion. Mechanical properties were characterized by tensile and fracture testing, while local deformation processes were followed by acoustic emission and instrumented impact testing as well as by the analysis of scanning electron micrographs. The results showed that sugarcane bagasse fibers reinforce polypropylene similarly to other natural fibers. They increase stiffness, but decrease tensile yield stress, tensile strength and deformability. Increased interfacial adhesion

Scanning electron micrographs. The average length of the fibers was 4560  $\mu\text{m}$ , while their average diameter was 340  $\mu\text{m}$ . The wood flour used as reference was the Filtracell EFC 1000 grade produced by Rettenmaier and Sohne GmbH, Germany. The average size of the particles was about 210  $\mu\text{m}$  and its aspect ratio, i.e. the ratio of its length and diameter, was 6.8. A polypropylene functionalized with maleic anhydride was used as coupling agent. The Scona 2112 grade maleated PP (MAPP) was supplied by Byk-Chemie GmbH, Germany, and it had a melt flow rate of 4-8 g/10 min at 190 °C and 2.16 kg, and a maleic anhydride content of 0.9-1.2 %. The fiber content of the composites changed from 0 to 30 wt% in 5 wt% steps. The ratio of MAPP/fiber was 0.1 in all composites.