

BIOREACTOR CO-COMPOSTING OF SEWAGE SLUDGE AND RESTAURANT WASTE

By

ABDUL RAHMAN BIN ABDUL RAZAK

**Thesis Submitted to the School of Graduate Studies,
Universiti Putra Malaysia, in Fulfilment of the Requirements for the
Degree of Master of Science**

June 2004




DEDICATION

*My beloved wife, Nur Azanah bte Abdullah @ Azanah bt Oleh
Thanks for your invaluable love, patience, understanding and support*

*My beloved father & mother
Who provided the opportunities & with your blessing and do'a*

*Teachers
For your advice and guidance*

*Friends
Thank you for the support and help*



Abstract of thesis presented to the Senate of Universiti Putra Malaysia
in fulfilment of the requirements for the degree of Master of Science

**BIOREACTOR CO-COMPOSTING OF SEWAGE SLUDGE
AND RESTAURANT WASTE**

By

ABDUL RAHMAN BIN ABDUL RAZAK

June 2003

Chairman : Professor Mohd. Ali Hassan, Ph.D

Faculty : Food Science and Biotechnology

Composting is an environmental-friendly method to tackle the disposal problem of sewage sludges and municipal solid waste. With appropriate nutrients, porosity, density and moisture content during composting, pathogens such as *Salmonella typhi*, *Escherichia coli* etc. will be destroyed and the organic matter will be stabilized producing a compost product that can contribute directly to soil fertility and conditioning. Composting process system has been modernized from the heap or windrow system to the reactor system, which is a comparatively fast process. A 200 liters rotating drum bioreactor/composter was designed, fabricated and used in this co-composting study. This bioreactor was designed in Universiti Putra Malaysia and was fabricated by Amsea Environment Sdn. Bhd. Three different types of dewatered sewage sludges, i.e. septic tank, oxidation pond and activated

sewage sludges were successfully co-composted with municipal solid waste in a two-stage process.

The physicochemical and biological characteristics of these municipal solid waste (restaurant waste) and sewage sludges were measured before being used as raw materials for the co-composting process. For the bioreactor composting, the raw materials were fermented for 7 days inside the 200 liters bioreactor before being matured outside the bioreactor in a windrow pile until fully matured and ready to be used. A 2:1 (w/w) ratio of municipal solid waste and sewage sludge was found to give the best initial C/N ratio for the composting process. The carbon content decreased and the nitrogen content increased towards the end of the composting process, which resulted in the reduction of C/N ratio during the composting process to below 20. The low C/N ratio of the final compost product was very important as the indicator of compost maturity and stability. The breakdown of organic materials inside the bioreactor did not increase the temperature to the thermophilic range (50-60°C), where breakdown of organic matter by microorganisms is at the optimum rate. In order to overcome the temperature problem, heated air was supplied to the bioreactor, increasing the temperature of the composting process. Shredded garden waste was added as bulking agent. Bioreactor co-composting took around 40-45 days to produce matured compost. The characteristics of the sewage sludge compost products were almost similar compared to commercial compost

available in the local market and also complied with the United States Environmental Protection Agency (USEPA) standard. By using bioreactor system the compost products were improved based on nutrient contents and duration of composting process. The planting out performance of spinach with the research compost showed satisfactory results.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk Ijazah Master Sains

**PENGGOMPOSAN BERSAMA ENAPCEMAR KUMBAHAN DAN SISA
PEPEJAL MAJLIS PERBANDARAN MENGGUNAKAN BIOREAKTOR**

Oleh

ABDUL RAHMAN BIN ABDUL RAZAK

Jun 2003

Pengerusi : Profesor Mohd. Ali Hassan, Ph.D

Fakulti : Sains Makanan dan Bioteknologi

Pengkomposan merupakan kaedah mesra alam bagi mengatasi masalah pelupusan enapcemar kumbahan dan sisa pepejal majlis perbandaran. Dengan kandungan nutrien, keporosan, ketumpatan dan kandungan lembapan yang sesuai semasa proses pengkomposan, mikrob yang merbahaya seperti *Salmonella typhi*, *Escherichia coli* dan sebagainya akan dimusnahkan dan bahan organik akan distabil menghasilkan produk kompos yang boleh menyumbang kepada kesuburan tanah. Sistem bagi proses pengkomposan telah dimodenkan dari sistem "windrow" atau timbunan longgokan/batasan kepada sistem reaktor yang terbukti satu proses yang lebih pantas. Dalam kajian ini, sebuah bioreaktor/komposter jenis drum berputar bersaiz 200 liter telah direka dan dibina bagi digunakan didalam penyelidikan pengkomposan bersama ini. Bioreaktor ini telah direka bentuk

di Universiti Putra Malaysia dan telah dibina oleh Amsea Enviroment Sdn. Bhd. Tiga jenis enapcemar kumbahan yang berlainan jenis iaitu tangki septik, kolam pengoksidaan dan enapcemar teraktif telah berjaya dikompos bersama-sama dengan sisa pepejal majlis perbandaran melalui dua fasa berlainan semasa proses pengkomposan.

Ciri-ciri kimia fizikal dan biologi bagi enapcemar kumbahan dan sisa pepejal majlis perbandaran (sisa makanan dari restoran) telah dikenalpasti terlebih dahulu sebelum digunakan sebagai bahan mentah bagi proses pengkomposan bersama. Bagi proses pengkomposan menggunakan bioreaktor, bahan mentah yang telah dicampur bersama-sama telah difermentasikan selama 7 hari di dalam bioreaktor 200 liter sebelum melalui proses kematangan diluar bioreaktor melalui kaedah timbunan longgokan/batasan atau "windrow" sehingga matang sepenuhnya dan sedia digunakan. Nisbah 2:1 bagi sisa pepejal majlis perbandaran dan enapcemar kumbahan telah dikenalpasti sebagai kadar percampuran yang sesuai berdasarkan kepada nisbah karbon:nitrogen bagi proses pengkomposan bersama. Kandungan karbon berkurangan dan kandungan nitrogen meningkat dalam masa proses pengkomposan berlaku, yang menghasilkan pengurangan pada nisbah C/N sehingga kurang dari 20. Nisbah C/N yang rendah dalam hasil produk kompos adalah sangat penting sebagai penunjuk kepada kematangan dan kestabilan kompos. Namun begitu, penguraian bahan mentah di dalam bioreaktor tidak menyebabkan peningkatan suhu

kepada julat termofilik (50-60°C) dimana penguraian bahan organik oleh mikroorganisma berlaku pada kadar yang optima. Bagi mengatasi masalah suhu, udara panas telah dibekalkan ke dalam bioreaktor yang berjaya meningkatkan suhu semasa proses pengkomposan. Sisa serpihan tanaman/kayu telah ditambah sebagai agen pempukul. Pengkomposan bersama menggunakan bioreaktor mengambil masa sekitar 40-45 hari bagi menghasilkan kompos yang matang. Ciri-ciri akhir produk kompos enapcemar kumbahan dan sisa pepejal majlis perbandaran adalah hampir sama berbanding dengan kompos komersil yang ada dipasaran tempatan dan juga menepati piawaian Agensi Perlindungan Alam Sekitar Amerika Syarikat (USEPA). Dengan menggunakan sistem bioreaktor, produk kompos dapat diperbaiki berdasarkan kepada kandungan nutrien dan jangkamasa proses pengkomposan. Ujian tanaman pokok bayam bagi mengukur kualiti hasil produk kompos yang terhasil menunjukkan keputusan yang memuaskan.

ACKNOWLEDGEMENTS

I am thankful to God Almighty, who has helped me all along in my life, in this research and in the preparation of this thesis.

I would like to express my appreciation and gratitude to my chairman, Prof. Dr. Hj. Mohd. Ali Hassan and members of the supervisory committee Prof. Dr. Mohamed Ismail Abdul Karim, Associate Prof. Dr. Arbakariya Arrif and Prof. Dr. Azni Idris for the guidance, suggestion, supervision and encouragement through this project. Also not forgetting, to my colleagues; Mrs. Nor'Aini Abd Rahman, Zainal bin Baharum, Jame'ah Hamed, Ong Ming Hooi, Phang Lai Yee, Norrizan Abdul Wahab, Mrs. Hafizah Kassim, Manisya Zauri, Sim Kean Hong, Cheong Weng Chung; staff of the Department of Biotechnology; Mr. Rosli Aslim, Mrs. Renuga Panjamurti, Mrs. Latifah Hussein, Mrs. Aluyah Marzuki, Mr. Azman and the staff of University Business Centre, Universiti Putra Malaysia; thank you for your help and cooperation in this project.

I would like to express my appreciation to Indah Water Konsortium Sdn. Bhd. (IWK) and Ministry of Science, Technology and Environment (IRPA) for the financial support for this composting project. I would like to extend my special thanks to Dr. Aminuddin Mohd Baki and Ir. Mohamed Haniffa Abdul Hamid from IWK Head Quarters, Mr. Xavier from IWK Taman Tun Dr. Ismail; Mr. Suria, Mr. Razali and Mr. Fadhil from IWK Lembah Pantai

also Mr. Loh Ghim Joo from Amsea Environmental Sdn. Bhd. for their help throughout this study.

All members in Feed Bioprocess Lab. MARDI, especially Pn. Noraini Samat, for the stimulating professional relationship we have had. I sincerely wish them all the best in their future endeavors.

Last but not least, to my beloved wife, Nur Azanah bte Abdullah and all my family members, I am deeply indebted for your sacrifices, understanding, patient and encouragement, for all those years of loving-kindness and for nurturing me to be the person I am now.

I certify that an Examination Committee met on 28th June 2004 to conduct the final examination of Abdul Rahman bin Abdul Razak on his Master of Science thesis entitled “Bioreactor Co-Composting of Sewage Sludge and Restaurant Waste” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Associate Professor Dr. Fatimah Abu Bakar
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Chairman)

Suriani Abdul Aziz, Ph.D.
Associate Professor
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Member)

Rosfarizan Mohamad, Ph.D.
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Member)

Abdul Jalil Abdul Kader, Ph.D.
Professor
Faculty of Science and Technology
Universiti Kebangsaan Malaysia
(Independent Examiner)

GULAM RUSUL RAHMAT ALI, Ph.D.
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

This thesis submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirements for the degree of Master of Science. The members of the Supervisory Committee are as follows:

Mohd. Ali Hassan, Ph.D.

Professor
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Chairman)

Mohamed Ismail Abdul Karim, Ph.D.

Professor
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Member)

Arbakariya Ariff, Ph.D.

Associate Professor
Faculty of Food Science and Biotechnology
Universiti Putra Malaysia
(Member)

Azni Idris, Ph.D.

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

AINI IDERIS, Ph.D.

Professor/ Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledge. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

ABDUL RAHMAN BIN ABDUL RAZAK

Date:

TABLE OF CONTENTS

		Page
DEDICATION		ii
RESEARCH PAPERS PUBLISHED IN JOURNALS		ii
ABSTRACT		iii
ABSTRAK		vi
ACKNOWLEDGEMENTS		ix
APPROVAL		xi
DECLARATION		xiii
LIST OF TABLES		xvii
LIST OF FIGURES		xix
LIST OF ABBREVIATIONS		xxi
CHAPTER		
I	INTRODUCTION	1
II	LITERATURE REVIEW	6
	Introduction	6
	Raw Materials	9
	Municipal Solid Waste (MSW)	9
	Restaurant waste/Food Waste	11
	Sewage Sludge	14
	MSW Management	18
	Co-composting Process	19
	Process of Composting	25
	Benefits of Compost	31
	Composting System	34
	Reactor/In-Vessel Systems	35
	Rotating Drum or “Dano-type” systems	39
	Main Factors Affecting Composting	46
	Temperature	46
	Time	47
	pH	49
	C/N Ratio	50
	Moisture Content	51
	Aeration	52
	Mixing	54

Bulking Agent	54
Size	55
Other Factors	56
Microorganisms	56
Seeding and Reseeding	57
Use of Inocula	57
Quality of Compost	60
III MATERIALS AND METHODS	63
Chemical Reagents	63
Raw Materials for Co-Composting Process	64
Restaurant Waste	64
Dewatered Sewage Sludge	65
Bioreactor Engineering Design	67
Experimental Design of Co-composting Process	70
First Phase of Co-Composting of Sewage Sludges and Restaurant Waste	70
Second Phase of Co-Composting of Sewage Sludges and Restaurant Waste	71
Laboratory Sample Analysis	75
Physical Analysis	75
Observation of Texture, Colour, Odour and Size	75
Sample Analysis	75
Moisture Content and Total Solids	75
Temperature	76
Chemical Analysis	77
pH	77
Total Carbon	77
Total Kjeldahl Nitrogen	79
C/N Ratio	81
Heavy Metals and Nutrients Content	81
Screening of compost	83
Biological Analysis	83
Germination Test	83
Growth Test	84
Determination of Total Microbial Count	85
Commercial Compost	86
OrganoGro 250 Compost	86

IV	RESULTS AND DISCUSSION	87
	Physico-chemical Characterization of Raw Waste	87
	Bioreactor Co-Composting of Septic Tank Sewage Sludge and Restaurant Waste	91
	Bioreactor Co-Composting of Oxidation Pond Sewage Sludge and Restaurant Waste	93
	Bioreactor Co-Composting of Activated Sewage Sludge and Restaurant Waste	96
	Bioreactor Co-Composting of Activated Sewage Sludge and Restaurant Waste With Added Bulking Agent and Heated Air	98
	Performance of Bioreactor during Co-composting Process	100
	Temperature Profiles	100
	pH Profiles	104
	Carbon Profiles	106
	Nitrogen Profiles	108
	Carbon to Nitrogen Ratio Profiles	109
	Moisture Content Profiles	111
	Comparison of Research Compost to the Commercial Compost	113
	Compost Maturity and Stability	116
	Heavy Metals and Nutrients / Minerals	118
	Sieving of Research Compost	120
	Planting Out Performance	122
V	CONCLUSION AND SUGGESTIONS	124
	Conclusion	124
	Suggestions	126
	REFERENCES	128
	APPENDICES	141
	BIODATA OF THE AUTHOR	169
	PUBLICATIONS	170
	R&D INNOVATION EXHIBITION AND AWARDS	171