



**DESIGN AND ANALYSIS OF MANUFACTURING  
FACILITIES FOR FRICTION STIR WELDING  
PROCESS**

**MUHAMMAD 'AFWAN BIN AB RAZAK  
(2013281556)**

**BANCHELOR OF MECHANICAL ENGINEERING  
(MANUFACTURING) (HONOURS)  
UNIVERSITI TEKNOLOGI MARA (UiTM)  
JULY 2017**

### **DECLARATION BY THE CANDIDATE**

“I declare that this thesis is the result of my own work except the ideas and summaries which I have clarified their sources. The thesis has not been accepted for any degree and is not concurrently submitted in the candidature of any degree.”

Signed : .....

Date : .....

**Muhammad ‘Afwan Bin Ab Razak**

UiTM No: 2013281556

## **ACKNOWLEDGEMENT**

First and foremost, thanks God for the time and giving me a chance in completing this final year project. I deeply appreciate the continued support of my supervisor, Mdm Normariah Bt. Che Maideen for spending time and kindly guided me in understanding the project, monitoring my progress, gave encouragement and dedication toward accomplishing this final year project.

Also, all contribution either direct or indirectly is appreciated very much, especially to friends, lecturers and all laboratory technicians for their kindness in helping and giving motivation throughout the completion of the thesis. Special thanks to my dearest friend, Tuan Nur Naillah Bt. Tuan Aziz for the continuous support and encouragement to finish this project.

I am also grateful to my family for their boundless love and support. Words cannot express how grateful I am to be blessed with such amazing parents, Ab Razak Bin Mat Daud and Che Halimah Bt. Che Leh. Thank you for your prayers and support.

## **ABSTRACT**

Friction stir welding, FSW is a solid-state welding process. This welding process involved the penetration of rotating tool which consists of shoulder and prolonged by a pin into a metal plate, followed by advancing speed to weld the metal plate. The aim of this project is to contribute in developing manufacturing facilities for friction stir welding process. A conventional milling machine has been converted to perform a friction stir welding process by designing a suitable rotating tools and jigs and fixtures. In the process, a tool made of H13 steel was designed and used. Then, for the design of jigs and fixtures, a clamping system was applied in order to prevent the workpieces from dispersal or lifting and to ensure that the uniform distribution of temperature and pressure along the specimen throughout the process. The design of the tool, jigs, and fixtures was fabricated and tested by joining two similar plates of aluminum alloys AA6061-T6 to verify the designed. The tests showed promising results with defects-free welds, good strength and smooth surface finish without gap creation between the welded specimens. The percentage of losses of the material during FSW welding process was too small which is 0.67%. The smoothest surface roughness of the specimen weldment was 2.519  $\mu\text{m}$  at 1270 rpm rotating speed and 218 mm/min welding speed. The maximum efficiency of the weldment strength was 65% respected to AA6061-T6 at 218 mm/min welding speed and 1270 rpm rotating speed. These results encourage using and improving the present design for future studies of FSW.

## **TABLE OF CONTENT**

<b>CONTENT</b>	<b>PAGE</b>
ACKNOWLEDGEMENT	I
ABSTRACT	II
TABLE OF CONTENT	III
LIST OF FIGURES	VI
LIST OF TABLES	VIII
LIST OF ABBREVIATIONS	IX
LIST OF ACRONYMS	X
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 PROJECT BACKGROUND	1
1.2 PROBLEM STATEMENT	3
1.3 OBJECTIVE	4
1.4 SCOPE OF WORK	5
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>6</b>
2.1 FSW	6
2.2 BASIC PRINCIPLE OF FSW	7
2.3 MICROSTRUCTURAL ZONE IN FSW	9
2.4 COMPARISON OF FSW TO OTHERS WELDING PROCESSES	12
2.5 TOOL GEOMETRY	12
2.6 CLAMPING SYSTEM AND FIXTURE	14