# NEUROMODULATION: ACTION POTENTIAL MODELING

A Thesis

presented to

the Faculty of California Polytechnic State University,

San Luis Obispo

In Partial Fulfillment

of the Requirement for the Degree

Master of Science in Biomedical Engineering

by

Vladimir Ruzov

March 2014

© 2014 Vladimir Ruzov ALL RIGHTS RESERVED

### COMMITTEE MEMBERSHIP

TITLE:	Neuromodulation: Action Potential Modeling
AUTHOR:	Vladimir Ruzov
DATE SUBMITTED:	March 2014
COMMITTEE CHAIR:	Robert B. Szlavik, Ph.D. Assistant Professor of Biomedical Engineering
COMMITTEE MEMBER:	Lanny Griffin, Ph.D. Professor of Biomedical Engineering
COMMITTEE MEMBER:	David Clague, Ph.D. Biomedical Engineering Graduate Coordinator

#### ABSTRACT

# Neuromodulation: Action Potential Modeling Vladimir Ruzov

There have been many different studies performed in order to examine various properties of neurons. One of the most important properties of neurons is an ability to originate and propagate action potential. The action potential is a source of communication between different neural structures located in different anatomical regions. Many different studies use modeling to describe the action potential and its properties. These models mathematically describe physical properties of neurons and analyze and explain biological and electrochemical processes such as action potential initiation and propagation. Therefore, one of the most important functions of neurons is an ability to provide communication between different neural structures located in different anatomical regions. This is achieved by transmitting electrical signals from one part of the body to another. For example, neurons transmit signals from the brain to the motor neurons (efferent neurons) and from body tissues back to the brain (afferent neurons). This communication process is extremely important for a being to function properly.

One of the most valuable studies in neuroscience was conducted by Alan Hodgkin and Andrew Huxley. In their work, Alan Hodgkin and Andrew Huxley used a giant squid axon to create a mathematical model which analyzes and explains the ionic mechanisms underlying the initiation and propagation of action potentials. They received the 1963 Nobel Prize in Physiology/Medicine for their valuable contribution to medical science. The Hodgkin and Huxley model is a mathematical model that describes how the action potential is initiated and how it propagates in a neuron. It is a

iv

set of nonlinear ordinary differential equations that approximates the electrical characteristics of excitable cells such as neurons and cardiomyocytes.

This work focuses on modeling the Hodgkin and Huxley model using MATLAB extension - Simulink. This tool provides a graphical editor, customizable block libraries, and solvers for modeling and simulating dynamic systems. Simulink model is used to describe the mechanisms and underlying processes involved in action potential initiation and propagation.

Keywords: Hodgkin and Huxley model, Axon properties, Action Potentials.

v

# TABLE OF CONTENTS

LIST OF TABLES	viii
LIST OF FIGURES	ix
Chapter 1 - Background	1
1.1 Introduction	1
1.2 Neurons	4
1.3 Cell Membrane	5
1.4 Voltage Gated Channels	7
1.5 Ion Pumps	9
1.6 Leak Channels	11
1.7 Action Potential	12
1.8 Definition of the Hodgkin-Huxley Model	16
1.9 Voltage Gated Sodium Channel	19
1.10 Voltage Gated Potassium Channel	21
1.11 Leak Channel	23
1.12 Membrane Capacitance	24
1.13 Action Potential Propagation	24
1.14 Propagation Velocity	26
1.15 Time Constant	27
1.16 Space Constant	30
1.17 Propagation Velocity	33
1.18 Action Potential Propagation in Myelinated Fibers	35
1.19 Action Potential Propagation: Neuron Properties	37
Chapter 2 - Modeling	43
2.1 Modeling the Hodgkin and Huxley Model	43
2.2 Modeling Voltage Gated Sodium Channel	44
2.3 Modeling Voltage Gated Potassium Channel	45

2.4 Modeling Leak Channel	. 46
2.5 Modeling Membrane Capacitance	. 47
2.6 Modeling Periodic Stimulation	. 48
2.7 Modeling Temperature Effect	. 50
Chapter 3 – Simulation Results	. 54
3.1 Membrane Conductance	. 54
3.2 Gating Variables	. 55
3.3 Ionic Currents	. 58
3.4 Temperature Effect	. 61
3.5 Current Injection	. 62
3.6 Threshold	. 66
Chapter 4	. 69
4.1 Future Work	. 69
4.2 Conclusion	. 71
References	. 73
Appendix	. 76
Appendix A: Simulink Constants and Variables	. 76
Appendix B: Simulink Model Source Code	. 78

# LIST OF TABLES

1. I	on concentrations	[4]1	0
------	-------------------	------	---

# LIST OF FIGURES

1.	Neuron Components [4]	4
2.	Phospholipid Bilayer [8]	6
3.	Voltage gated Sodium Channel [9]	9
4.	Ion Pump [12]	. 11
5.	Leak channel [13]	. 12
6.	Ion Flow in Action Potential [7]	. 13
7.	Schematic diagram for the Hodgkin-Huxley model. [15]	. 17
8.	Action Potential propagation across a neuron [16]	. 25
9.	Time Constant [16]	. 28
10.	. Length (Space) Constant	. 32
11.	. Action potential propagation in myelinated fiber	. 36
12.	. Schematics of Action potential propagation [4]	. 37
13.	. High Level Schematics of the Hodgkin and Huxley model	.43
14.	. Voltage Gated Sodium channel Simulink model	. 45
15.	. Voltage Gated Potassium Channel Simulink model	.46
16.	. Leak Channel Schematics	.46
17.	. Schematics of membrane capacitance	. 47
18.	. Action Potential	. 48
19.	. The Hodgkin and Huxley model (External stimulation)	.49
20.	. Action potential – periodic stimulation	. 50
21.	. Temperature Effect	.51
22.	. Potassium Channel (with temperature effect)	. 52
23.	. Sodium Channel (with temperature effect)	. 53

24.	Sodium and Potassium conductance and their sum	. 54
25.	Gating variables ( <i>n</i> , <i>m</i> and <i>h</i> ) during action potential activation	. 56
26.	Membrane Action Potential [21]	. 57
27.	Ionic currents	. 58
28.	Ionic currents during the nerve impulse [22]	. 60
29. <sup>-</sup>	Temperature Effect Results	. 61
30. /	Action Potential: temperature effect [23]	. 62
31. /	Action potential during current injection	. 64
32.	Current Injection [24]	. 65
33. <sup>-</sup>	Threshold	. 67
34. <sup>-</sup>	Threshold level [25]	. 68

### Chapter 1 - Background

# **1.1 Introduction**

The action potential is a source of communication between different neural structures located in different anatomical regions. For instance, communication between the brain and musculature is achieved by propagating an electrical signal from the brain to the specific muscle. Neurons are used for processing and transporting action potentials from one part of the body to another. Neurons are also responsible for propagating action potentials from one neuron to another. An action potential can be described as an electrical impulse which is a transient alteration of transmembrane voltage. During this event, the electrical membrane potential of a particular cell changes very rapidly from negative to positive and then reverses back to its baseline (or resting) voltage. This is done in a consistent pattern. There are different kinds of excitable cells that have this unique property, such as muscle cells, neurons and cardiomyocytes.

Cellular communication is a method by which living cells communicate with each other. Therefore an ability to send and receive messages is very important for cells to survive and function properly. Living cells communicate important information such as availability of nutrients and changes in the temperature. This information is communicated with the environment and other living cells. Cellular communications are achieved in different ways such as biochemical signaling and biophysical cellular communication [1]. Evidently, the action potential plays an important role in biophysical cellular communication processes [1]. It's also responsible for activating different intracellular processes such as muscle cells contraction. There are two main types of action potentials. The first type of action potential is generated by voltage-gated sodium channels (NaV) and the second type is generated by voltage gated calcium channels (CaV). The main difference between these two types of action potentials is duration. Sodium based action potential lasts for a very short period of time, less than millisecond [2]. Calcium based action potential on the other hand may last over a period of 100 milliseconds or longer [2]. This paper is focused on the first type of action potentials, generated by voltage gated sodium channels.

Most human and animal cells are electrically polarized and act like small batteries. In other words, they have a specific voltage difference between the extracellular and intracellular environments. This voltage is also known as the membrane potential and it is measured in millivolts. The resting membrane potential is a membrane potential during a static state of a cell [3]. Consequently, during this state the cell membrane potential is at equilibrium. The resting membrane potential is negatively charged since the inside of excitable cells is approximately 70mV more negative than the outside of the cell. Therefore, the resting membrane potential is approximately -70mV. This value varies depending on neuron types and the species [3]. In this dissertation the resting membrane potential is assumed to be constant and equal to -70mV.

So what is the underlying mechanism of action potential initiation? Excitable cells have a means of transporting different types of ions from the intracellular to the extracellular environment and vice versa. This ion transport is achieved by specific ion channels with selective permeability. In other words, only specific types of ions can cross ion channels with selective permeability. For example sodium ions are transported through the cell membrane by the sodium ion channel, whereas potassium ions are transported transported through potassium ion channels. An important factor related to the potential

is the ionic concentration gradient. During normal conditions (resting state) there are a specific number of ions present inside and outside the cell. Since ions are charged particles, the difference in ion concentration between outside and inside of a cell membrane defines a resting voltage potential. There are two forces that move ions across the cell membrane. The first is the concentration gradient and the second is the charge gradient. An equilibrium potential is reached when the net flow of that particular ion is zero. Resting voltage potential is reached when the net flow of all types of ions is zero. In other words, the net flow of sodium, potassium and chloride ions is zero during the resting membrane potential [4].

An action potential is an event during which the electrical membrane potential changes its state from resting state. During this event the membrane potential rises rapidly and then falls. In order to initiate an action potential, the membrane potential has to increase and reach a certain level [4].

As we will see in later sections of this dissertation, action potential occurs in several phases: depolarization, repolarization, etc. All of these stages involve ion transfer from the extracellular environment to the intracellular environment and vice versa. For example, the depolarization phase can be characterized by rapid inflow of sodium ions through sodium ion channels. Repolarization phase on the other hand occurs when potassium ions flow out from the axoplasm through potassium selective ion channels.

In order to better understand all of the mechanisms involved in action potential initiation and propagation, several mathematical models have been developed such as Morris–Lecar model, the FitzHugh–Nagumo model, the Bonhoeffer–van der Pol model [5]. One such models is called the Hodgkin and Huxley model which is a mathematical model that describes how action potential is initiates and propagates along an axon. In

1963 Alan Hodgkin and Andrew Huxley received a Nobel Prize in physiology for their valuable contribution in neuroscience.

### **1.2 Neurons**

Neurons are specialized nerve cells that have an ability to send and receive electrical signals from one neural structure to another. Neurons are also capable of receiving and sending signals to other neurons. Being able to transport and process electrical signals, neurons form a communication network between different organs in the body. Basic neuron structure includes a cell body, an axons and dendrites. The main function for axons is to transmit electrical impulses along its length. The axon is the longest part of a neuron responsible for propagation of the action potential from cell body (also known as the Soma) to axon terminal [6]. Dendrites, on the other hand, are the receiving part of a neuron. In other words, dendrites receive electrical impulses passed by other neurons and propagate them to the cell body.



Figure 1: Neuron Components [4]

The soma, or cell body, is the processing center of a neuron. The unique feature of the cell body is that it is the only part of a neuron that contains a cell nucleus [7]. Most RNA in a neuron is produced by a cell nucleus. Therefore, most proteins are produced in the cell body and then transported to the entire neuron [7]. Another part of a neuron that plays an important role in action potential origination is the axon hillock. It is the part of a neuron from which axon originates. This region is characterized by a high amount of protein synthesis. Another important characteristic of the axon hillock is a presence of a specialized plasma membrane. This plasma membrane contains many voltage gated ion channels and it is responsible for action potential initiation.

Complex interactions between specialized protein structures, which are embedded in a cell membrane, allow initiation and propagation of action potential along neurons. These protein structures vary across a neuron thus giving various electrical properties and functions to different parts of the neuron. Therefore, some of the neuronal structures have excitable properties, while other parts of the neuron do not. In other words, given an external stimulus, excitable parts of a neuron can initiate an action potential. For example, myelinated parts of a neuron are not excitable and therefore are not involved in the action potential generation process. In these sections of a neuron, an action potential is propagated passively by means of electrotonic propagation. Unmyelinated sections of a neuron are called Nodes of Ranvier. These parts of the axon are capable of producing an action potential.

### **1.3 Cell Membrane**

Electrical properties of human and animal cells are mostly determined by the structure of the cell membrane that separates the extracellular and intracellular

environments. A cell membrane is composed of a phospholipid bi-layer. Phospholipids are specialized molecules that are composed of two parts: phosphate and lipids. The phosphate head is a hydrophilic portion of the phospholipid which means that it attracts water molecules, whereas lipid tails are the hydrophobic portion of the phospholipid and they are repelled by the water molecules. Therefore, a phospholipid bilayer is formed due to the fact that lipid tails are repelled by aqueous solutions and are attracted facing each other (inward) whereas the phosphate head of the phospholipid molecule is facing outward [8]. Figure 2 demonstrates how the phospholipid bilayer is formed, identifying hydrophilic phosphate heads and hydrophobic lipid tails.



Figure 2: Phospholipid Bilayer [8]

So how do different ions move across the phospholipid bilayer? The lipid layer acts as an insulator since it is highly resistant to movement of ions. There are a number of different types of proteins embedded in a cell membrane. Some of these proteins form ion channels that provide means for different ion types to cross a cell membrane. Ion channels are large protein molecules embedded in a cell membrane (e.g. voltage gated channels, leak channels, etc.). Channel proteins form small openings for different molecules to pass from the extracellular to the intracellular medium and vice versa. Some of these protein channels are capable of actively moving specific types of ions from one side of the membrane to another [9]. For example, the Na-K-Pump uses energy from adenosine triphosphate (ATP) to transfer sodium and potassium across a cell membrane. Receptor proteins act as molecular event triggers that initiate a specific cell response such as opening a channel such as the ligand gated channel [9]. In other words, the channel stays inactivated until a specific ion or molecule, called a ligand, is bound to the ligand binding site. This process will activate the channel allowing it to open for ions to pass through the cell membrane. Another type of a cell membrane protein is a carrier protein, which acts as a binding site that grabs a specific molecule and pulls it inside the cell into the intracellular medium [9]. Cell recognition proteins such as CD (cluster of differentiation) are useful in identification of cell types. This protein is an important part of the body's immune system. Another type of protein molecule is a voltage gated channel. This type of channels plays an important role in action potential activation and propagation.

### **1.4 Voltage Gated Channels**

Voltage gated ion channels are a special type of ion channel which is embedded in a cell membrane. The key feature of voltage gated channels is that they are activated by a difference in membrane potential [9]. In other words, these types of channels open for some values of membrane potential while for other values of membrane potential these channels remain closed. Figure 3 shows different states of a voltage gated sodium channel. The first image shows the inactive state of a voltage gated ion channel. At this state, the channel remains closed and therefore no ion flow exists. This state is prevalent when the membrane is at rest [9]. The channel quickly begins to open as soon as the membrane potential reaches a specific threshold value. Additionally, voltage gated ion channels are responsible for ion transport between the extracellular and intracellular environments. These channels are permeable to specific types of ions. For example, voltage gated sodium channels (NaV) are permeable to sodium (Na) ions only; whereas voltage gated Calcium channels (CaV) are permeable to calcium (Ca) ions only.

Voltage gated ion channels contribute to action potential generation and/or propagation by initiating a positive feedback loop. The opening of ion channels changes the membrane conductance to ionic current flow. In other words, a change in membrane potential will activate and open voltage gated ion channels and thus increase the membrane conductance to ionic current flow. As a result ions will flow into the axoplasm. The inflow or outflow of ions will lead to a change of an electrochemical gradient. Consequently, increase in electrochemical gradient will contribute to further change in a membrane potential. As a result more voltage gated ion channels will be activated, causing an increase in ion current.

An action potential is initiated when the membrane potential reaches a certain level referred to as the threshold potential. Reaching the threshold level will result in a rapid increase of membrane potential. The biophysical properties of voltage gated ion channels influence the shape of the action potential curve [8]. There are different types of voltage gated ion channels that can produce a positive feedback loop which could lead to initiation of an action potential. An example of such a channel is a voltage gated sodium channel. It contributes to action potential in nerve fibers. Voltage gated calcium channel, on the other hand, is an important component in muscle fibers since calcium initiates the contractile process [10].

#### Voltage-gated Na<sup>+</sup> Channels



**Closed** At the resting potential, the channel is closed.



**Open** In response to a nerve impulse, the gate opens and Na<sup>+</sup> enters the cell.



**Inactivated** For a brief period following activation, the channel does not open in response to a new signal.

Figure 3: Voltage gated Sodium Channel [9]

Voltage-gated potassium channels (KV<sup>+</sup>) open and/or close in response to changes in the transmembrane potential. These channels are potassium selective pores that allow only potassium ions to cross a cell membrane. Furthermore, potassium channels are found in most cell types and control a wide variety of cell functions. In excitable cells such as neurons, they shape the action potential curve and set the resting membrane potential [9]. By contributing to regulation of the action potential duration in cardiac muscle, malfunction of potassium channels may cause life-threatening arrhythmias [6]. Potassium channels may also be involved in maintaining vascular tone by having an impact on contractile properties of smooth muscle cells which are commonly found in arteries and arterioles [11].

### 1.5 Ion Pumps

Another type of transmembrane protein channel is an ion pump. The extracellular environment and the intracellular environment have different ionic composition. For example, Table 1 shows different intracellular and extracellular

concentrations for different ions. Potassium concentration is much higher in the axoplasm, whereas sodium concentration is much higher outside the cell.

	Extracellular Concentration	Intracellular Concentration [mol/m <sup>3</sup> ]
	[mol/m <sup>3</sup> ]	
Na <sup>+</sup>	150	15
K+	5.5	150
Cl-	125	9

Table 1: Ion concentrations [4]

lons move from areas of high concentrations to areas of low concentrations. This process is called diffusion and it continues until the concentration is equalized on both sides [9]. Another process that moves ions in the opposite direction is electrostatic in nature and gives rise to the Nernst Potential. Therefore, there must be a mechanism to maintain a different ion concentration during the resting state. This process is achieved by ion pumps. The main difference between ion pumps and voltage gated channels is that ion pumps move ions across the plasma membrane against the ionic concentration gradient. This is the reason why ion pumps require energy to perform their action and are considered to be active channels. Ion pumps are enzymes that are capable of converting energy from different sources. For instance, Figure 4 illustrates how ATP is used in Na<sup>+</sup>K<sup>+</sup> the pump to move sodium and potassium ions across the membrane against their concentration gradients.



lon composition outside the cell differs from that inside. When e.g. a nerve is stimulated Na<sup>+</sup> flows into the cell. The electrical potential arising across the membrane causes the nerve impulse to propagate itself along the nerve. The normal state is restored when Na<sup>+</sup> has been pumped out and K<sup>+</sup> pumped in.

Figure 4: Ion Pump [12]

Na<sup>+</sup>K<sup>+</sup> pump can be found in all animal cells [12]. The main function of the Na<sup>+</sup>K<sup>+</sup> pump is to maintain a stable resting potential in cells by maintaining a low sodium concentration and high potassium concentration in the intracellular environment. This gradient is maintained by moving three sodium ions out of a cell and moving two potassium ions into the cell. In other words, one positive charge is being removed during a single pump action.

### 1.6 Leak Channels

Another way for ions to cross a cell membrane is through leak channels. These channels are passive, or randomly gated [13]. In other words, these gates open and close at random. Unlike voltage gated channels, there is no specific event that can trigger a leak channel to open or close. This type of ion channel has its own intrinsic rate of change between open and closed states [13]. Figure 5 demonstrates how ions are being transported across the cell membrane via a leak channel. The right image

demonstrates how ions travel in the direction of the concentration gradient, from high ionic concentration to low ionic concentration.



Figure 5: Leak channel [13]

Leak channels allow ions to pass from the extracellular medium to the intracellular medium and vice versa. Since ions flow in the direction of lower concentration, leak channels have a great impact on resting membrane potential.

# **1.7 Action Potential**

The action potential can be described as an electrical impulse which is a transient alteration of transmembrane potential. The action potential is generated by series of consecutive events. The prerequisite for action potential initiation is the membrane potential reaching some threshold value. This value can be approximated by a constant value. The threshold level depends on many different factors such as the type of neuron, its location in the body as well as temperature and other factors. Therefore, in practical circumstances, the threshold level fluctuates [7]. For simplicity

this paper assumes that the threshold level is constant. Figure 6 depicts the movement of different ions during various stages of action potential generation (e.g. depolarization, repolarization, etc.). Threshold level is represented by a dashed line (approximately -60mV) and is located above the level of the resting potential (-70mV).



Figure 6: Ion Flow in Action Potential [7]

The first phase of the action potential initiation process is called depolarization. In order for the depolarization phase to occur, membrane potential needs to meet certain criteria. Therefore, when membrane potential reaches a certain threshold value, voltage gated sodium channels (NaV) will open allowing rapid influx of sodium ions from the extracellular environment to the intracellular environment. As more sodium ions enter the cell, the concentration of sodium ions inside the cell increases. Membrane potential increases since sodium ions are positively charged. The associated positive feedback loop will result in more voltage gated sodium channels opening and thus creating an upward shooting trend in the action potential curve [7]. As a result, the intracellular environment will become more positively charged relative to the extracellular environment. This process will lead to a plasma membrane polarity switch. Voltage gated sodium channels will then deactivate. Since voltage gated sodium channels are opened for only a very short period of time, the bulk sodium concentration during cellular signaling changes only by a tiny amount that is a few orders of magnitude smaller than the bulk concentration [7]. When voltage gated sodium channels close, sodium ions can no longer enter the cell. The depolarization phase is the fastest phase in the action potential generation process.

The next phase of the action potential initiation process is called repolarization. During this phase voltage gated potassium channels open allowing the outflow of potassium ions from the intracellular environment to the extracellular environment. This process decreases the membrane potential of a cell. As a result, the intracellular environment will become more negatively charged relative to the extracellular environment. Just like sodium channels, potassium channels are opened for a very short period of time [7].

The third phase of the action potential initiation process is called hyperpolarization. During this phase, voltage gated potassium channels remain open and the intracellular environment is hyperpolarized. In other words, the membrane potential (-80mV) decreases below the level of the resting potential (-70mV). At this stage potassium ions will enter the cell mostly through leak channels and ion pumps [7]. This process will restore the membrane potential leveling it with the resting potential. This is the slowest phase in the action potential generation process.

Generally, there are enough sodium and potassium ions in both the extracellular and intracellular environments to support multiple action potentials. Action potential can

either fire or not fire. Action potential cannot fire partially neither it can fire too hard or too weak. In other words, the amplitude remains constant [14].

Resting potential is a level at which the membrane potential stays constant unless something disturbs or stimulates the excitable cell. Another important level of membrane potential is the threshold level. Reaching this level will result in the action potential initiation process. A typical value of resting potential at the axon hillock is around -70mV and the threshold value is around -55mV [7].

The shape of the action potential curve depends on many different factors such as properties of excitable cell membrane (e.g. number of voltage gated ion channels, leak channels, membrane capacitance) and temperature [7].

The most studied voltage gated ion channels are located in fast nerve conduction system [2]. As noted earlier in this paper Alan Hodgkin and Andrew Huxley won a Nobel Prize for their valuable contribution in the quantitative description of action potentials of a giant squid axon [2]. Their model is named after them. They developed a series of nonlinear differential equations that encompass the biophysics of the membrane which gives rise to the action potential. These equations approximate electrical properties of excitable cells such as the ones found in neurons and cardiac muscle cells. More specifically, Alan Hodgkin and Andrew Huxley modeled ionic currents involved in action potential initiation and propagation. These currents are:

- sodium current through voltage gated sodium channels
- potassium current through voltage gated potassium channels
- potassium, chloride and sodium currents through leak channels
- current through the cell membrane

### **1.8 Definition of the Hodgkin-Huxley Model**

A semipermeable cell membrane separates the axoplasm from the extracellular medium and acts as a capacitor. If external current is applied to an excitable membrane, it can charge the membrane capacitance and/or diffuse through ion channels. Alan Hodgkin and Andrew Huxley modeled a total membrane current, taking into consideration different ions which utilize various ion channels to cross a cell membrane:

- 1. Sodium channel current (I<sub>Na</sub>)
- 2. Potassium channel current  $(I_{\kappa})$
- 3. Leak channel current (I<sub>leak</sub>)
- 4. Capacitive current

According to the Hodgkin and Huxley model, each of these channels acts independently and carries only a specific type of ions. In other words, a sodium channel can only transport sodium ions. A leak channel on the other hand does not have selective permeability and therefore, different types of ions can move through it. And finally, capacitive current is a current through the phospholipid bilayer of an excitable cell.

Alan Hodgkin and Andrew Huxley represented the membrane model by using basic electrical components such as resistors and capacitors. This model is also known as a parallel conductance model [4]. Figure 7 shows schematics of the Hodgkin and Huxley model using capacitors and resistors. Current (*I*) is an electrical current flowing across the cell membrane during activation. Each channel (e.g. voltage gated sodium channel, voltage gated potassium channel and leak channel) is represented by a resistor and an

associated equilibrium potential is represented by a battery (e.g.  $E_{K}$ ,  $E_{Na}$  and  $E_{I}$ ). The equilibrium potential is the value of  $V_m$  where there is no net flow of ions between the extracellular environment and the intracellular environment.



Figure 7: Schematic diagram for the Hodgkin-Huxley model. [15].

In this paper  $V_m$  is used to describe a membrane potential which is equal to the intracellular potential minus the extracellular potential. Ion equilibrium potentials for sodium, potassium and chloride ions are described by Nernst potentials and defined by the Nernst equation:

$$V_{Na} = -\frac{RT}{zF} ln \frac{c_{i,Na}}{c_{o,Na}} \tag{1}$$

$$V_K = -\frac{RT}{zF} \ln \frac{c_{i,K}}{c_{o,K}}$$
(2)

$$V_{Cl} = -\frac{RT}{zF} ln \frac{c_{i,Cl}}{c_{o,Cl}}$$
(3)

Note that subscripts "c<sub>i</sub>" and "c<sub>o</sub>" represent ion concentration in the intracellular and the extracellular environments respectively. The value of z for sodium and potassium ions is 1. The value of z for chloride ions is -1. Since the internal concentration of chloride is extremely low, it does not play an important role in evaluation of the action potential [4]. Therefore, (3) can be generalized to include not only chloride ions but all non-specific ions crossing the cell membrane. As was previously discussed, leak channels allow a small amount of different types of ions to pass from the intracellular environment to the extracellular environment and vice versa. Consequently, it is assumed that the conductance of a leak channel ( $G_L$ ) is constant. The leak channel voltage ( $V_L$ ) is also assumed to be constant since the sum of all ionic currents is equal to zero during the resting state. In their experiments, Alan Hodgkin and Andrew Huxley determined that the membrane conductance for a potassium channel ( $G_K$ ) and the membrane conductance for a sodium channel ( $G_{Na}$ ) are functions of transmembrane voltage and time [4]. There is no sodium current when  $V_m = V_{Na}$ . Therefore  $I_{Na} = 0$ . There is no potassium current ( $I_K = 0$ ) when  $V_m = V_K$ .

According to Ohm's law, the conductance per unit area for the potassium channels, sodium channels and leak channels can be calculated as shown below.

$$G_{Na} = \frac{I_{Na}}{V_m - V_{Na}} \tag{4}$$

$$G_K = \frac{I_K}{V_m - V_K} \tag{5}$$

$$G_L = \frac{I_L}{V_m - V_L} \tag{6}$$

where  $G_{Na}$ ,  $G_K$ ,  $G_L$  Conductance for sodium, potassium and leak channels [S/cm<sup>2</sup>]

	Current passed by sodium, potassium and leak channels
I <sub>Na</sub> , IK, I <u>L</u>	[mA/cm <sup>2</sup> ]
$V_{Na}$ , $V_{K}$ , $V_{L}$	Voltage for sodium, potassium and leak channels [mV]
Vm	Resting voltage of cell membrane [mV]

The equation for the total transmembrane current can be written as a sum of currents from all channels (sodium, potassium and leak channels) and the membrane capacitance.

$$I_m = C_m \frac{dV_m}{dt} + (V_m - V_{Na})G_{Na} + (V_m - V_K)G_K + (V_m - V_L)G_L$$
(7)

where  $I_m$  membrane current per unit area [mA/cm<sup>2</sup>]

*C<sub>m</sub>* membrane capacitance per unit area [F/cm<sup>2</sup>]

*V<sub>m</sub>* membrane voltage [mV]

 $V_{\textit{Na}},~V_{\textit{K}},~V_{\textit{L}}~$  Nernst voltage for sodium, potassium and leakage ions [mV]

 $G_{Na}$ ,  $G_K$ ,  $G_L$  sodium, potassium, and leakage conductance per unit area [S/cm<sup>2</sup>]

### **1.9 Voltage Gated Sodium Channel**

Sodium ions cross the cell membrane via voltage gated sodium channels. Sodium ion equilibrium is achieved when the condition  $V_m = V_{Na}$  is satisfied. At the sodium equilibrium potential there is no net movement of sodium ions across the cell membrane because for each sodium ion that moves into the cell by diffusion, exactly one sodium ion moves out of the cell due to the electrostatic gradient. Therefore, the net current of sodium during this state is 0 ( $I_{Na} = 0$ ). Any deviation from this state  $(V_m \neq V_{Na})$  will result in a non-zero current in the sodium channel. According to Ohm's Law the current in a sodium channel is equal to:

$$I_{Na} = (V_m - V_{Na})G_{Na} \tag{8}$$

where	$V_m$	membrane voltage [mV]
	I <sub>Na</sub>	current passed by sodium channel [mA/cm <sup>2</sup> ]
	V <sub>Na</sub>	Nernst voltage for sodium ions [mV]

GNa

The Hodgkin and Huxley model is based on the assumption that sodium channels open and close according to the state of the *m*-particle [2]. The *m*-particle is an activation parameter for a sodium channel. Sodium channel *m*-particles have two states: permissive (the state when the sodium channel is open) and non-permissive (the state when the sodium channel is open) and non-permissive (the state when the sodium channel is open) and non-permissive (the state when the sodium channel is closed). The *m*-particle gives the proportion of sodium channels that are in the open state at a particular moment in time. Therefore, (*1-m*) expresses the proportion of sodium channels that are currently in the closed state. Alan Hodgkin and Andrew Huxley assumed that it required three *m*-particles to activate a single sodium channel [2]. In other words, all three *m*-particles need to be in the permissive state in order to activate a single sodium channel. Sodium channels are deactivated by a deactivation particle *h*. This parameter represents the probability of an *h*-particle being in a non-activated state. Therefore, the probability of the *h*-particle being in an activated state is equal to *1-h*. Alan Hodgkin and Andrew Huxley assumed that it required one *h*-particle to deactivate a single sodium channel [2].

sodium conductance per unit area [S/cm<sup>2</sup>]

The relationship between the sodium conductance and the *m*-particles and *h*-particle is represented by (9).

$$G_{Na} = G_{Na \ max} m^3 h \tag{9}$$

where	$G_{\text{Na max}}$	maximum value of sodium conductance [mS/cm <sup>2</sup> ]
	т	obeys (10)
	h	obeys (11)

Sodium channel activation is represented by (10). Sodium channel deactivation is represented by (11).

$$\frac{dm}{dt} = \alpha_m (1-m) - \beta_m m \tag{10}$$

$$\frac{dh}{dt} = \alpha_h (1-h) - \beta_h h \tag{11}$$

Transfer rate coefficients for  $\alpha_h$ ;  $\alpha_m$ ;  $\beta_h$ ;  $\beta_m$  are voltage dependent. Therefore, transfer rate coefficients do not depend on time [4].

# **1.10 Voltage Gated Potassium Channel**

Potassium ions cross the cell membrane via voltage gated potassium channels.

The equilibrium for potassium ions is achieved when  $V_m = V_K$ . During this state, there is no potassium current going through the cell membrane ( $I_K = 0$ ). Any deviation from this state ( $V_m \neq V_K$ ) will result in a non-zero current in the potassium channel.

According to Ohm's Law, the current in a potassium channel is equal to:

$$I_K = (V_m - V_K)G_K \tag{12}$$

where V <sub>m</sub>	membrane voltage [mV]
----------------------	-----------------------

Iκ	Current passed by potassium channel [mA/cm <sup>2</sup> ]
Vĸ	Nernst voltage for potassium ions [mV]
Gκ	potassium conductance per unit area [S/cm <sup>2</sup> ]

The Hodgkin and Huxley model is based on the assumption that potassium channels open and close according to the state of the *n*-particle [2]. The *n*-particle is an activation parameter for a potassium channel. Potassium channel *n*-particles have two states: permissive (the state when the potassium channel is open) and non-permissive (the state when the potassium channel is closed). The *n*-particle defines the proportion of potassium channels that are in the open state at a particular moment in time. Therefore, (*1-n*) defines the proportion of potassium channels that are currently in the closed state. Alan Hodgkin and Andrew Huxley assumed that it required four *n*-particles to activate a single potassium channel [2]. In other words, all four *n*-particles need to be in the permissive state in order to activate a single potassium channel. Potassium channel. Potassium channel.

$$G_K = G_{K \max} n^4 \tag{13}$$

maximum value of potassium conductance where  $~G_{K\,\text{max}}$   $[\text{mS/cm}^2]$ 

obeys (14)

n

The behavior of the potassium channel activation is represented by (14).

$$\frac{dn}{dt} = \alpha_n (1-n) - \beta_n n \tag{14}$$

# 1.11 Leak Channel

where V<sub>m</sub>

Different types of ions (e.g. potassium, calcium, sodium) cross the cell membrane via leak channels. Equilibrium in leak channels is achieved when the following condition is satisfied  $V_m = V_L$ . During this state there is no leak current going through the cell membrane and therefore  $I_L = 0$ . Any deviation from this state ( $V_m \neq V_K$ ) will result in a non-zero current in the leak channel.

According to Ohm's Law, the current in a leak channel is equal to:

$$I_L = (V_m - V_L)G_L \tag{15}$$

I <sub>L</sub>	Current passed by leak channel (mA/cm <sup>2</sup> )

*V*<sub>L</sub> Nernst voltage for ions in leak channel [mV]

membrane voltage [mV]

*G*<sub>L</sub> Leak channel conductance per unit area [S/cm<sup>2</sup>]

# 1.12 Membrane Capacitance

Another component that contributes to the total membrane current is the membrane capacitance.

$$I_m = C_m \frac{dV_m}{dt} \tag{16}$$

where	I <sub>m</sub>	membrane current per unit area [mA/cm <sup>2</sup> ]
	Cm	membrane capacitance per unit area [F/cm <sup>2</sup> ]
	V <sub>m</sub>	membrane voltage [mV]

# **1.13 Action Potential Propagation**

So far we have discussed the action potential origination that involved transmembrane currents only. This is an important building block which can be used to get a more complete neuron model. After initiation, the action potential propagates in outward directions and travels to the synaptic terminal region. It is important to define action potential propagation since the word "propagation" often refers to different actions. In many cases the word "propagation" defines the movement of an object from one point to another. For example, throwing a ball from one location to another defines propagation, or movement of the ball. This definition does not apply to action potential propagation. In case of action potential propagation one can think of a series of events that have to happen in a specific order. Each of these successive events will eventually trigger the next event thus propagating it towards the end point.

Figure 8 demonstrates how action potential propagates gradually along the axons' membrane in outward directions from the point where the stimulus was applied. The action potential propagates in all or nothing fashion [16]. In other words, an action potential cannot propagate partially. A propagating action potential can be stopped as it propagates by a region of unmyelinated fiber such as in patients with multiple sclerosis [6].



Figure 8: Action Potential propagation across a neuron [16]

Under resting conditions, the extracellular environment is positively charged whereas the intracellular environment is negatively charged. This arrangement is due to a high concentration of positively charged sodium ions in the extracellular environment. Let's consider an experiment in which an external stimulus is applied directly to the mid-section of an axon. If this stimulus is high enough to reach a certain level, called the threshold level, then an action potential will fire. As it was previously discussed, the first step will open voltage gated sodium channels which will result in a rapid inflow of sodium ions from the extracellular environment to the intracellular environment. This will result in an increase in membrane potential from its resting state (-70mV) to a positive 40mV [16]. The action potential, at its initiation site, will depolarize the membrane to either side of it and a subsequent action potential will be generated in the newly depolarized regions.

Action potential propagation can be compared to the waves in water. If one would throw a rock in calm water, the concentric circles or the ripples will originate and propagate in an outward direction away from the point where the rock landed. The main difference is that the ripples are usually rapidly distorted in a random manner and eventually destroyed completely. This is not true with an action potential which will propagate throughout the whole length of a neuron until it reaches the axon terminal.

### 1.14 Propagation Velocity

One of the most important properties in action potential propagation is the velocity. The human body has a wide variety of neuron types which can be characterized by the action potential velocity which is the speed at which the impulse is propagated across the entire length of an axon. It is an important factor that defines how fast the information is transferred from one part of the body to another. Some of the key factors influencing action potential propagation velocity are fiber diameter, myelination, age, sex and temperature [17]. Different types of neurons can be found in the human body and each of the neuron type has its unique purpose and properties. Action potential propagation velocity in neurons can vary from 100 meters per second (223.7 miles per hour) to a much lower speed, less than a tenth of a meter per second (0.6 miles per hour) [18]. Why do neurons have such a big difference in the propagation velocity? Different neurons in a human body have their own purpose. Some of the neurons must have a high propagation velocity in order to quickly deliver information from the body to the brain and vice versa. Other types of neurons propagate an action potential at much slower speeds. Axons are typically divided into three classes: type A fibers, type B fibers and type C fibers. Type C fibers have the slowest propagation
velocity, usually below 1.34 m/s [17]. These types of fibers are the autonomic motor neurons that carry an electrical impulse to cardiac muscles, smooth muscle, glands and other peripheral effectors. Some of the sensory neurons are also of type C fibers. They carry information about pain, general touch, pressure and temperature. This type of information is not required to be transferred at high speeds. Type C fibers are the smallest axons whereas type A fibers are usually the largest axons [17]. One of the main differences in the physical properties between type C fibers and type A is an absence of myelin in type C fibers. This directly correlates to the size of an axon fiber. Action potential propagation velocity in an axon increases as the diameter of the axon increases. Type A fibers have the fastest propagation velocity. For example type A sensory neurons carry information about balance, position, delicate touch and pressure. This type of information is required to be transferred in a very short period of time. Therefore, the propagation velocity for this type of information is high.

There are big differences between action potential propagation velocities across different fibers. In order to understand how these differences arise we need to examine properties of the axons. In particular, it is important to understand the concept of the time constant and the space constant.

#### 1.15 Time Constant

Different types of axons have various action potential propagation velocities. Some of the axons propagate an electrical signal very fast (e.g. type A), while the other type of axons propagate an action potential at a much slower speed (e.g. type C). So why does the propagation velocity differ so much? The time constant is an intrinsic property of the membrane and can be used to describe the difference in action potential propagation in neurons.

Before analyzing the time constant it may be beneficial to consider a heat transfer example. Let's consider a block of metal with the initial temperature of 10C°. If this block of metal is placed on a hot plate which has a temperature of 100C°, then the temperature of the metal block will gradually increase until it reaches 100C°. This temperature change from 10C° to 100C° will not occur instantly but rather gradually. Similar behavior is observed with excitable cells. Let's consider an example illustrated in the Figure 9.



Figure 9: Time Constant [16]

The top image illustrates an experimental setup where an excitable cell is stimulated by the induced current and the voltmeter is used to measure a transmembrane voltage as a function of time. It is assumed that all regions within and around the excitable cell are equipotential. In other words, the same potential exists across all points of the excitable cell membrane. In the example above, the recording electrode measures the initial voltage difference of -60mV. This is the resting potential before applying the stimulus. At the time 0 an external current is applied to the excitable cell. This action is analogous to slamming the metal block on the hot plate. Even

though the stimulating current changed instantaneously from 0 to some positive value, the change in membrane potential will occur gradually and will not happen instantly. It will take some time for a voltage potential to change from -60mV to -50mV. Therefore, there is a 10mV depolarization which occurs gradually, as an exponential function of time.

There is a time constant index denoted by the symbol  $\tau$  which represents how quickly the exponential function changes with time. More specifically, a time constant index defines how quickly an action potential reaches 63% of its maximum value. In the previous example, a membrane potential increases from -60mV to -50mV. Therefore, the time constant is equal to the time when -53.7mV is reached. According to the plot illustrated in Figure 9, the time constant is reached at 10msec. Therefore, the smaller the time constant, the faster the action potential reaches 63%. The neuron responds faster to the induced current. So if an excitable cell had a time constant of 5 milliseconds, it would reach 63% of the maximum potential in only 5 milliseconds. The time constant can be compared to the 0-60 car rating. Any car accelerates from 0mph to 60mph for a certain amount of time. The lower the 0-60 time of a given car, the faster it accelerates.

Time constant depends on two properties of a cell membrane: 1) membrane resistance ( $R_m$ ) and 2) membrane capacitance ( $C_m$ ). Membrane resistance opposes the flow of ions from the extracellular environment to the intracellular environment and vice versa. High membrane resistance means low permeability of a cell membrane. Which factors influence the membrane resistance? One of the factors that may contribute to the membrane resistance is the number of ion channels present in the cell membrane [16]. Low number of ion channels in the cell membrane results in low number of ions

crossing the cell membrane within a specific timeframe. Therefore, the membrane resistance is high and the membrane conductance is low.

The time constant also depends on the membrane capacitance [16]. The cell membrane acts as a capacitor since it has an ability to store energy. Membrane capacitance is charged when an external stimulus is applied. Discharging and charging of the membrane capacitance does not occur instantaneously but rather gradually.

The time constant can be represented by a product of membrane resistance and membrane capacitance:

$$\tau = R_m C_m \tag{17}$$

where	Т	time constant
	R <sub>m</sub>	membrane resistance
	$C_m$	membrane capacitance

## 1.16 Space Constant

The space constant or length constant is another quantifier often used in neurobiology to describe properties of axons. The space constant is a mathematical value which quantifies the distance that an electrical impulse will travel along an axon via passive electrical conduction. The space constant, in a cell, dictates the distance across which a membrane depolarization will decay exponentially assuming a DC value of injected current. Therefore, the higher the space constant is, the longer this distance is. Let's consider an example where one end of the metal rod is placed on a hotplate. Let's assume that the initial temperature of the rod is 10C° and the temperature of the hotplate

is 100C°. The metal rod is left on the hotplate for a period of time, enough for the temperature to stabilize. If we were to measure the temperature across the metal rod we could conclude that the temperature decreases with the distance away from the hotplate. This is true due to the fact that the heat loss increases with the distance away from the heat source. Therefore, the temperature gradient can be described as a function of distance.

Similar behavior is observed within excitable cells. Figure 10 represents a nerve cell with electrodes  $v_0$ ,  $v_1$ ,  $v_2$ ,  $v_4$  in different locations along the axon, positioned at 10mm increments away from the cell body. The stimulating electrode is located inside the cell body and is used to deliver an electrical signal to the soma. The stimulating electrode provides enough power to change a membrane potential from -60mV to -50mV. Electrodes  $v_0$  through  $v_4$  are used for recording a voltage potential at different distances away from the cell body. Before stimulation is applied, the neuron has a resting potential of -60mV inside the soma as well as across the entire length of the axon. After an electrical impulse is applied to the soma, the membrane potential is changed from -60mV to -50mV. Is this true for the entire length of an axon? Figure 10 shows that the membrane potential is different at the various distances away from the soma. The cell body will have a voltage potential of -50mV since it is the area where the stimulation was applied. Moving along the axons' length we can notice that the voltage potential decreases as we move away from the soma. For example the membrane potential has a value of -56.3 at 1 mm away from the stimulation site. The membrane potential is very close to -60mV at 2mm away from the stimulation site. Membrane potential is even closer to -60mV at the distances 4mm and further.



Figure 10: Length (Space) Constant

The length constant or space constant is an index that represents how far a membrane depolarization will spread along the axons' length in response to a stimulus. The space constant is denoted by the symbol  $\lambda$ . In the previous example space constant was 1 mm. At this distance the membrane potential will decay by 63% from its maximal value. The membrane potential spreads further for larger space constants. In other words, if the space constant was 2mm then the membrane potential would spread further along the axon and vice versa. Similar to the time constant, the space constant is also a passive property of the cell membrane. Therefore, these properties influence the rate of action potential propagation. The space constant can be compared to the race track surface. If the surface is smooth then the race car will decelerate very slowly due to lack of friction. If the surface is very sandy and muddy, then the car will decelerate much faster due to all the resistance from the sand and mud.

The space constant can be calculated by the following formula:

$$\lambda = \sqrt{\frac{dR_m}{4R_i}}$$
(18)

where	λ	space constant [cm]
	R <sub>m</sub>	membrane resistance [m $\Omega$ ]
	Ri	axoplasm resistance $[m\Omega]$
	d	diameter of an axon [cm]

Intracellular resistance is the opposition of ion propagation in the intracellular environment along the length of the axon. An axon stimulation results in a change in charge distribution which propagates along the axon. During this process some of the charges will defuse back to the extracellular environment whereas the other charges will continue to move along the length of the axons. Therefore, if the membrane resistance is high, then fewer ions will defuse to the extracellular environment and more ions will stay inside the axoplasm. Since the diffusion rate is low, ions move further along the axon.

## **1.17 Propagation Velocity**

So how does the action potential propagation velocity depend on the time constant and the length constant? As it was discussed in previous sections, a small time constant means that the adjacent regions of an axon will depolarize more quickly. More rapid depolarization of the adjacent regions will bring the adjacent regions to the threshold value sooner. Based on this information we can conclude that the small time constant results in a high action potential propagation velocity. The space constant also has a direct impact on the action potential propagation velocity. A large space constant means that the change in a voltage potential spreads to a greater distance away from the stimulation site. This brings the distant regions closer to the threshold level. Based on this information we can conclude that a high space constant results in a high action potential propagation velocity.

Therefore, action potential propagation velocity is inversely proportional to the time constant and directly proportional to the space constant. These relationships can be combined in the following equation for the action potential propagation velocity:

Velocity 
$$\propto \frac{1}{C_m} \sqrt{\frac{d}{4R_m R_i}}$$
 (19)

where *d* diameter of a neuron [cm]

*C*<sub>m</sub> membrane capacitance per unit area [F/cm<sup>2</sup>]

 $R_{\rm m}$  membrane resistance [m $\Omega$ ]

 $R_i$  Intracellular resistance [m $\Omega$ ]

According to (19) we can identify which properties have an impact on an action potential propagation velocity in a neuron. For instance if we were to model a neuron with a high action potential propagation velocity, we could increase the diameter of an axon. There is a limitation to modifying only the diameter of the axon. In order to double the action potential propagation velocity, we must quadruple the diameter. The same principle can be applied to membrane resistance and intracellular resistance. In order to double the velocity, we must decrease the intracellular resistance by 4 times. Therefore, the most efficient way to increase propagation velocity is to decrease the capacitance of the membrane. In order to double action potential propagation velocity, we must half the capacitance of the membrane. One way to decrease membrane capacitance is to introduce some kind of insulation layer to the membrane. This layer is known as myelin sheath.

In order to generate an action potential, any axon is required to have voltage gated sodium channels and voltage gated potassium channels. If these ion channels are blocked by an insulation layer, the action potential will have no location to be initiated.

## **1.18 Action Potential Propagation in Myelinated Fibers**

The central nervous system has different types of neurons each having its distinct characteristics and physical properties. For example, type A and type B neurons are myelinated fibers whereas type C neurons are unmyelinated. As it was discussed in previous sections, type C fibers have the slowest action potential propagation velocity. This property can be explained by the absence of the insulation layer called the myelin. Myelin serves as an electrical insulator which facilitates rapid action potential propagation velocity. Myelin is present in type A and type B neurons, but not in type C neurons [17]. Myelin is composed of a number of layers of the specialized plasma membrane of oligodendrocytes. Oligodendrocytes are specialized cells with most of the cytoplasm excluded [6]. The main function of these cells is to provide the physical support and insulation properties to the axons. The oligodendrocyte membrane contains specialized proteins and lipids that greatly contribute to an orderly packed sheath. Axons are encapsulated in a small blocks of myelin, called internodes. These insulation

blocks are roughly a few hundred microns in length [6]. These internodes are separated by small gaps of unmyelinated sections of axon which are called the nodes of Ranvier. Even though myelinated axons are present in all parts of the human brain, they are most commonly found in the white matter. This is the most common area for the myelin diseases. For example multiple sclerosis is a disease that involves the immune system attacking the central nervous system. More specifically, during multiple sclerosis the myelin is damaged. As a result scar tissues impair action potential propagation [6].



#### Figure 11: Action potential propagation in myelinated fiber

Figure 11 represents action potential propagation in a myelinated fiber. The action potential propagates from the leftmost internode to the right. The action potential propagates actively at the nodes of Ranvier. The mechanism of action potential propagation at the nodes of Ranvier was discussed in previous sections. So how does the action potential propagate within the internodes? These regions of axons have a myelin layer which acts as an insulator and prevent any ion movement across the cell membrane. In fact, internodes do not have any ion channels for ions to move across the cell membrane [6]. Therefore, the action potential is produced at the nodes of Ranvier. Action potential propagation across internodes is achieved by passively spreading the action potential until the next node of Ranvier is reached. Just as the temperature would spread across the metal rod, sodium and potassium ions will be pushed from one node of Ranvier to the next one. As the action potential spreads away from its origin, it will decrease in amplitude. In other words, the action potential will be smaller by the time it

reaches the next node of Ranvier. If action potential is not high enough to reach a certain threshold at the next node of Ranvier, a new action potential will not fire and action potential propagation will be terminated.

This process will repeat itself until one of two conditions is met: 1) the action potential reaches its final destination, the axon terminal, or 2) the action potential stops at a certain node of Ranvier due to the inability to reach the specific threshold required to originate a new action potential.

### **1.19 Action Potential Propagation: Neuron Properties**

The analysis of action potential propagation should consider axial currents as well as transmembrane currents. Figure 12 illustrates the schematics of action potential propagation along an axon. The total length of an axon can be divided into a number of units. Each unit of length can be represented by the Hodgkin and Huxley model.



Figure 12: Schematics of Action potential propagation [4]

Figure 12 shows the schematics of the unit length of an axon. In the schematic  $r_i$  represents the intracellular resistance per unit length, whereas  $r_0$  represents the

extracellular resistance per unit length. The Hodgkin and Huxley model describes the movement of electrical current between extracellular and intracellular environments. The total membrane current per unit length can be described by the following equation [4]:

$$i_m = \frac{1}{r_i + r_o} \frac{\partial^2 V_m}{\partial x^2} = 2\pi a I_m \tag{20}$$

where	i <sub>m</sub>	total membrane current per unit length [μA/cm]	
	I <sub>m</sub>	membrane current per unit area [µA/cm²]	
	r <sub>i</sub>	intracellular membrane resistance $[m\Omega]$	
	r <sub>o</sub>	extracellular membrane resistance $[m\Omega]$	
	а	axon radius [cm]	
	V <sub>m</sub>	membrane voltage [mV]	

The intracellular resistance per unit length is represented in (21)

$$r_i = \frac{\rho_i}{\pi a^2} \tag{21}$$

where  $\rho_i$  axoplasm resistivity [k $\Omega$ cm]

- a axon radius [cm]
- $r_i$  axoplasm resistance per unit length [k $\Omega$ /cm]

In reality the extracellular medium is very wide. Therefore, extracellular resistance per unit area can be omitted ( $r_o = 0$ ) [4]. Solving (20) for  $I_m$  we obtain the equation for propagating nerve impulse:

$$I_m = \frac{a}{2\rho_i} \frac{\partial^2 V_m}{\partial x^2} \tag{22}$$

The Hodgkin and Huxley model is based on the assumption that a neuron has a circular cross-section. Most neuron fibers do not have a perfectly circular shape [2]. Neuron fibers have convoluted elliptical shapes. Under steady conditions, action potential propagation velocity is constant [4]. Therefore, the membrane potential obeys the wave equation:

$$\frac{\partial^2 V_m}{\partial x^2} = \frac{1}{\theta^2} \frac{\partial^2 V_m}{\partial t^2}$$
(23)

(23) is substituted into equation (20) and solved for  $I_m$ . The result is substituted into (7) and forms the equation for action potential propagation.

$$\frac{a}{2\rho_i\theta^2}\frac{\partial^2 V_m}{\partial t^2} = C_m \frac{\partial V_m}{\partial t} + (V_m - V_{Na})G_{Na} + (V_m - V_K)G_K + (V_m - V_L)G_L$$
(24)

- where *a* axon radius [cm]
  - $\rho_i$  axoplasm resistivity [k $\Omega$ cm]
  - $\theta$  velocity of conduction [m/s]

The action potential propagation model can be represented as a sequence of Hodgkin and Huxley models connected in series. The output from each unit is used as an input to the next unit, where each unit is represented by a single instance of the Hodgkin and Huxley model. In more complex geometries, where multiple neurons are connected to multiple neurons, the same principle can be applied. Each neuron can be represented as a series of Hodgkin and Huxley models.

The human body has a wide variety of different neurons with different physical properties. Depending on the location in the body, axons have different characteristics. For instance, the axon length differs greatly depending on where the cell is located in the body [6]. Another variable property of axons is their diameter. These properties have a great impact on action potential propagation [19]. Therefore, it is important to analyze how the physical properties of a neuron influence action potential propagation along the length of the axon.

The diameter of an axon varies from 0.1µm to 20µm for large myelinated fibers in vertebrates [6]. Axons of invertebrates can have even larger diameters. In the case of a squid giant axon which Alan Hodgkin and Andrew Huxley used in their experiments, the size of the axon diameter is measured in the millimeter range [20]. The reason invertebrates have such a large diameter is that invertebrate axons are unmyelinated [20]. As previously stated, myelin contributes greatly to action potential propagation velocity. Action potential propagation velocity is an important factor for different organisms. It influences reflexes and allows organisms to escape from predators. This aspect is important especially for those creatures, whose bodies are unable to produce myelin. Therefore, it may be beneficial to investigate the effect of axon diameter.

So how does the axon diameter influence action potential propagation? One can argue that the larger the axon diameter the lower the membrane resistance inside the cell. In other words, axons with larger diameter have more ion channels that can be activated at the same time. This property leads to a higher number of ions crossing cell membrane at the same time. Therefore the result is a lower membrane resistance.

Another property that influences action potential propagation is intracellular resistance. During the depolarization phase, ion currents move from the depolarized membrane to adjacent polarized areas [19]. This phenomenon results in the depolarization of neighboring areas of an axon. Axoplasmic current also moves away from depolarized to polarized regions. Axoplasmic currents then cross the cell membrane and move into the extracellular environment. This process is known as electrotonic conduction during which ions move passively from depolarized to polarized regions. Electrotonic conduction has three distinct components: 1) ion movement through the extracellular environment; 2) ion movement through the intracellular environment; 3) ion movement across the cell membrane [19].

So which factors influence electrotonic conduction? Extracellular conduction is impacted by the extracellular resistance. Increase in extracellular resistance will result in the decrease in extracellular conductance and therefore weaker electrotonic propagation. The Hodgkin and Huxley model omits this factor since extracellular resistance is very small and constant along the entire length of an axon [4].

On the other hand, intracellular conductance is impacted by axoplasmic resistance. Intracellular resistance or axoplasmic resistance is the electrical resistance of the intracellular environment. The significance of this property is important because it affects the rate at which the action potential propagates along the axon [19]. The

intracellular environment of excitable cell contains a wide variety of molecules. Some of these molecules are electrically conductive (e.g. sodium ions, potassium ions), whereas some of these molecules are not-electrically conductive (e.g. lipids, proteins). Therefore, if the intracellular environment contains a lot of not-electrically conductive molecules, then more ions (both electrically conductive and not-electrically conductive) will travel through the membrane channels. This characteristic will result in high intracellular resistivity and therefore it will decrease the action potential propagation velocity [19].

## **Chapter 2 - Modeling**

## 2.1 Modeling the Hodgkin and Huxley Model

Equation 7 can be modeled using Simulink by utilizing subsystem blocks which would represent the voltage gated sodium channel (NaV), the voltage gated potassium channel (KV), the leak channel (Leak) and the membrane capacitance (Membrane). Each of these blocks, except for the Membrane capacitance block, takes voltage (*V*) as an input and returns current (*I*) as an output. The membrane block takes the sum of current from all ion channels as an input and returns voltage as an output. The scope utility can be used for output verification purposes. Figure 13 illustrates one of the many possible ways to implement the Hodgkin and Huxley model using Simulink.



Figure 13: High Level Schematics of the Hodgkin and Huxley model

Alan Hodgkin and Andrew Huxley developed the following equations for transfer rate coefficients  $\alpha_n$ ;  $\alpha_h$ ;  $\alpha_m$ ;  $\beta_n$ ;  $\beta_h$ ;  $\beta_m$ :

$$\alpha_n = \frac{0.1 - 0.01V'}{e^{(1 - 0.1V')} - 1}$$
(25)

$$\beta_n = \frac{0.125}{e^{0.0125V'}} \tag{26}$$

$$\alpha_m = \frac{2.5 - 0.1V'}{e^{(2.5 - 0.1V')} - 1}$$
(27)

$$\beta_m = \frac{4}{e^{(\frac{V'}{18})}} \tag{28}$$

$$\alpha_h = \frac{0.07}{e^{0.05V'}}$$
(29)

$$\beta_h = \frac{1}{e^{(3-0.1V')} + 1} \tag{30}$$

where	V'	$V' = V_m - V_r [mV]$
	Vr	the resting voltage [mV]
	α <sub>n</sub>	transfer rate coefficient for <i>n</i> -particle from closed to opened state
	$\beta_n$	transfer rate coefficient for <i>n</i> -particle from opened to closed state
	$\alpha_m$	transfer rate coefficient for <i>m</i> -particle from closed to opened state
	$\beta_m$	transfer rate coefficient for <i>m</i> -particle from opened to closed state
	α.	transfer rate coefficient for <i>h</i> -particle from inactivated to activated
	u <sub>h</sub>	state
	ß.	transfer rate coefficient for <i>h</i> -particle from activated to inactivated
	Ph	state

# 2.2 Modeling Voltage Gated Sodium Channel

Figure 14 shows one of the many ways to implement the voltage gated sodium channel using Simulink. The upper portion of the model describes the behavior of

sodium channel activation and the behavior of sodium channel inactivation. The behavior is modeled by implementing equations (10) and (11). The lower part of the model implements the sodium conductance, represented by (9). And finally, the sodium channel is modeled according to equation (8).



Figure 14: Voltage Gated Sodium channel Simulink model

## 2.3 Modeling Voltage Gated Potassium Channel

Figure 15 shows one of the many ways to implement a voltage gated potassium channel using Simulink. The upper portion of the model describes the behavior of potassium channel activation. This behavior is simulated by implementing equation (14). The lower part of the model implements the potassium conductance, represented by equations (13). And finally, the potassium channel is modeled according to (12).



Figure 15: Voltage Gated Potassium Channel Simulink model

# 2.4 Modeling Leak Channel

Figure 16 shows one of the possible ways that to model the leak channel using Simulink. This scheme implements equation 15.



Figure 16: Leak Channel Schematics

## 2.5 Modeling Membrane Capacitance

Figure 17 shows one of the possible ways to model the membrane capacitance using Simulink. The membrane capacitance subsystem block takes the current (*I*) as an input and returns voltage (*V*) as its final result. This subsystem block implements (16) for the voltage ( $V_m$ ). In this model, the current ( $I_m$ ) is divided by the capacitance ( $C_m$ ) and then integrated. The current ( $I_m$ ) consist of the capacitive current.



Figure 17: Schematics of membrane capacitance

The output from the Hodgkin and Huxley model implemented using Simulink is shown in Figure 18. The membrane potential starts rising from its resting state (at -70mV) and reaches its threshold value at approximately -60mV. Reaching the threshold point will initiate an action potential. Voltage gated sodium channels open rapidly and depolarize the excitable cell. This state represents the start of the depolarization phase. Membrane potential reaches its highest point at positive 18mV. At this point voltage gated potassium channels open causing an outflow of potassium ions. This state represents the start of the repolarization phase. The excitable cell repolarization phase potential reaches -80mV. At this point the excitable cell

is hyperpolarized since its membrane potential (-80mV) is lower than its resting membrane potential (-70mV). During the next phase, the action potential depolarizes to its resting state (-70mV). This is the slowest phase which takes more than 12ms to complete. According to the result from the Simulink model we can conclude that it takes approximately 20ms for a single action potential complex to occur. As we will see in later sections, the action potential propagation velocity depends on different experimental conditions (i.e. temperature) and physical properties of a neuron.



**Figure 18: Action Potential** 

An action potential as represented in Figure 18 does not propagate since it is based on the basic Simulink model which does not implement action potential propagation. As we will see later in this paper, the Simulink model needs to be modified in order to simulate action potential propagation.

# 2.6 Modeling Periodic Stimulation

Figure 19 shows the modified Hodgkin and Huxley model that simulates action potentials by periodic stimulation of the excitable cell. The signal builder block defines the stimulation signal that is added to the total current  $I_T$ .



Figure 19: The Hodgkin and Huxley model (External stimulation)

As a result of this change, an action potential is generated every time the Signal Builder outputs a signal. Figure 20 shows the output from the Signal Builder block and the output from the Hodgkin and Huxley model aligned along the x-axis. The x-axis represents time in milliseconds. The simulation runs for 150ms. The initial action potential complex is generated by the Hodgkin and Huxley model without any output from the Signal Builder block. This is possible due to initial conditions of *n*-particle, *m*-particle and *h*-particle. All consecutive action potential complexes are initiated by the periodic stimulation originated by the Signal Builder block. For simplicity, stimulation intervals are selected so that the membrane potential has enough time to return to its resting state of -70mV. In the example below the stimulation interval is set to 20ms.



Figure 20: Action potential – periodic stimulation

## 2.7 Modeling Temperature Effect

Temperature is an important factor which is almost always taken into consideration during experiments. Body temperature influences many processes in the body. In most experimental studies the temperature is held uniform and many human and animal models are evaluated at their normal body temperature, i.e. approximately 37C°. In reality, body temperature may vary in human and/or animal systems. These variations could be caused by different inflammatory responses to a disease, foreign material in the body such as a prosthesis, or other special circumstances, such as surgery. Temperature in cold-blooded living systems, such as the squid, varies with that of the environment. The experimental temperature value used by the Hodgkin and Huxley model is 6.3C° [2].

Temperature differences between the nominal room temperature and the normal human body temperature are sufficient to produce a noticeable difference in numerical results. Temperature variations can be expressed in many different ways. For example,

a sharper action potential peak may represent a higher experimental temperature. Temperature variances may produce significant differences in the experimental results and therefore in the overall performance of living tissue. For that reason, it is important to consider temperature in the model.

The effect of temperature can be represented by (31) [4].

$$3^{(T-6.3)/10}$$
 (31)

where *T* temperature [C°]

In order to take into account the effect of temperature, the Simulink model has to be modified. Figure 21 shows the implementation of the Temperature subsystem.



The effect of the temperature is taken care in the model so that the right-hand sides of the Equations for n, m and h are multiplied by the factor 3 ^ ((T - 6 . 3)/10)

#### Figure 21: Temperature Effect

The model of the Potassium channel has to be modified in order to take into consideration the effect of temperature. The right hand side of the (32) needs to be multiplied by the temperature factor, represented by equation 31 [4].

$$\frac{dn}{dt} = \alpha_n (1-n) - \beta_n n \tag{32}$$

Therefore, the potassium channel subsystem needs to be modified as it is represented in Figure 22. The temperature factor which is represented by the "Temperature" subsystem is multiplied by  $\alpha_n(1-n) - \beta_n n$ .



Figure 22: Potassium Channel (with temperature effect)

The model of Sodium channel has to be modified in order to account for the temperature effect. The right hand side of (33) and (34) have to be multiplied by the temperature factor, represented by (31) [4].

$$\frac{dm}{dt} = \alpha_m (1-m) - \beta_m m \tag{33}$$

$$\frac{dh}{dt} = \alpha_h (1-h) - \beta_h h \tag{34}$$

Therefore, the sodium channel subsystem needs to be modified as it is represented in Figure 23. The temperature factor which is represented by the "Temperature" subsystem is multiplied by  $\alpha_m(1-m) - \beta_m m$  and by  $\alpha_h(1-h) - \beta_h h$ .



#### Figure 23: Sodium Channel (with temperature effect)

These modifications to the Hodgkin and Huxley model are required to enhance the model to take into consideration the effect of temperature. Two variables were conveniently introduced to the Simulink model: "Temperature\_Bit" and "Temperature". The "Temperature\_Bit" variable is used to enable and to disable the analysis of temperature effect. For instance, by setting "Temperature\_Bit" to 1, the user can enable the analysis of temperature effects. Therefore, setting "Temperature\_Bit" to 0 disables the effect of temperature.

The "Temperature" variable is used for setting the experimental temperature. Most of the results described in this work are based on the giant squid axon model. Therefore, 6.3C° is a default temperature value which is used for simulation of action potential initiation and action potential propagation.

# **Chapter 3 – Simulation Results**

## **3.1 Membrane Conductance**

The membrane impedance decreases significantly during action potential activation. This behavior is a result of an increase in the membrane conductance. In other words, the membrane capacitance does not vary during action potential activation. Therefore, membrane capacitance is represented by a constant value in the Hodgkin and Huxley model. Figure 24 shows the increase in sodium conductance ( $G_{Na}$ ), potassium conductance ( $G_K$ ) and their sum ( $G_K + G_{Na}$ ).



Figure 24: Sodium and Potassium conductance and their sum

These increases in conductance are observed during action potential activation. Therefore, sodium conductance ( $G_{Na}$ ) starts its upward trend when voltage gated sodium channels are activated. This leads to a rapid inflow of sodium ions. Potassium conductance ( $G_K$ ) does not start its upward trend at the same time. Instead, potassium conductance starts its rapid increase when the sodium conductance is almost at its maximum level. At this point voltage gated sodium channels are being deactivated. At the same time voltage gated potassium channels are activated and the repolarization phase takes place. Potassium conductance takes more time than the sodium conductance. After the cell membrane is hyperpolarized its resting potential is slowly restored. This is the longest phase in the action potential initiation. Mostly potassium ions are involved in this phase. Potassium ions enter the intracellular environment through leak channels and active pumps.

#### 3.2 Gating Variables

Gating variables *n*, *m* and *h* are activation and inactivation particles that play an important role in opening and closing voltage gated sodium channels and voltage gated potassium channels.

Potassium channels open and close in accordance with the state of particle n [2]. The *n*-particles have two states: the permissive, the state when the potassium channel is open and non-permissive, the state when potassium channel is closed. In order to activate a single potassium channel, four *n* particles need to be in the permissive state.

Sodium channels open and close in accordance with the state of particle m and particle h [2]. Particle m is an activation parameter for the sodium channel. m-particles have two states: permissive (the state when the sodium channel is open) and non-

permissive (the state when the sodium channel is closed). In order to activate a single sodium channel, three m particles need to be in the permissive state. The sodium channel is deactivated by the deactivation particle h. It requires one h particle to deactivate a sodium channel [2].

Figure 25 illustrates how values of these particles change during action potential activation.



Figure 25: Gating variables (*n*, *m* and *h*) during action potential activation

In this model the initial values for the *n*, *m* and *h* particles is set to 0. Membranes of excitable cells continuously exist throughout a lifetime of those cells [2]. In other words, there is no specific mechanism that starts or stops a cell. Therefore, there are no such conditions where all of the three particles (*n*, *m* and *h*) would have a value of 0. The purpose of this simulation is to determine the initial values for the *n*, *m* and *h* particles. The initial values for gating variables *m*, *n*, *h* should be equal to the same values obtained during the resting membrane potential (-70mV). By using the graph represented in Figure 25 we can determine that the values of *n*, *m* and *h* particles should be initialized to 0.3176, 0.0529 and 0.5919 respectively. The simulation presented in this work does not initialize *m*, *n*, *h* variables and therefore the initial values of these parameters is 0.

These simulation results are consistent with the results described in the simulation of the membrane action potential published in "Principles of computational modeling in neuroscience" [21]. Figure 26 displays the time courses of membrane potential, conductance and gating variables during an action potential.



Figure 26: Membrane Action Potential [21]

# **3.3 Ionic Currents**

An action potential involves currents from different ion channels. Ion flows can be broken down into categories based on ion channels (e.g.  $I_{Na}$ ,  $I_{K}$ ,  $I_{Leak}$  and  $I_{Total}$ ). The Hodgkin and Huxley model can be used for studying the behavior of different ion channels. This analysis provides a better understanding of the behavior of different ion channels during action potential initiation.



Figure 27: Ionic currents

Figure 27 illustrates changes in ionic currents during an action potential. The negative current represents an inflow of ions from the extracellular environment to the intracellular environment. The positive current represents an outflow of ions from the

axoplasm to the extracellular environment. A zero-value represents the equilibrium state in which there are no ionic movements across the cell membrane.

When the cell membrane is at rest, the total ion current is equal to zero. During the resting membrane potential the ionic currents are balanced such that there is no net current flow across the membrane. According to the graph the total current ( $I_{total}$ ) is equal to 0 when the cell membrane is at rest. This condition changes when the net ion current changes to the non-zero state. In the simulation described in Figure 27, the depolarization phase starts approximately at 1.1ms. During this stage the sodium current initiates and sodium ions enter the excitable cell. This is represented in the downward slope of the  $I_{Na}$  curve. The repolarization phase starts at approximately 1.5ms. During this stage voltage gated potassium channels open allowing potassium ions to escape into the extracellular environment. At the same time voltage gated sodium channels start to close. The total current ( $I_{total}$ ) represents the sum of currents from all ion channels and is shown in red color on the Figure 27. During the initial phase of depolarization (from 1.1ms to 1.7ms), the total current consists primarily of the sodium current. During this period the  $I_{total}$  curve is in negative value range. The spike on the sodium current curve represents the time when the sodium channels start to deactivate. At 2.8ms the sodium current reaches its highest value of -830µA/cm<sup>2</sup> and then starts to decay. At the same time the potassium current reaches its highest point at 850µA/cm<sup>2</sup> and starts to decline due to inactivation of the voltage gated potassium channels. Voltage gated sodium channels are closed at 4.1ms. Therefore, sodium current through voltage-gated sodium channels is equal to zero. At this point sodium ions can cross the cell membrane only through the leak channels and active pumps. During the action potential some ions leak from axoplasm into the extracellular environment and vice versa. This movement is done primarily through the leak channels. The positive leak

current represents an outflow of ions from the axoplasm to the extracellular environment. In the example shown in Figure 27 this stage starts during repolarization, at approximately 1.5ms. Potassium ions escape from the axoplasm to the extracellular environment. The negative leak current represents an inflow of ions from the extracellular environment to the intracellular environment. In the example shown in Figure 27 this stage starts during hyperpolarization, at approximately 3.7ms. Sodium ions enter the axoplasm and membrane potential is restored to its resting state.

These results are consistent with the results Francisco Bezanilla described in his work "Ionic currents during the nerve impulse" [22]. Simulation results described in these work are similar to the results displayed in Figure 28.



Nature Reviews | Molecular Cell Biology

Figure 28: Ionic currents during the nerve impulse [22]

## **3.4 Temperature Effect**

During their experiments, Alan Hodgkin and Andrew Huxley were using 6.3C° as their baseline temperature. This temperature is consistent with the model presented in this work. In order to investigate the temperature effect, the "Temperature" variable was set to several different values. Initially the temperature variable was set to 6.3 C°. Action potential generated under this condition was used as a reference value.

Figure 29 illustrates the comparison of action potentials generated at 6.3C° and 12.3C°. The difference in scale in the two graphs is noteworthy. We can see that the action potential amplitude is slightly greater in the 6.3C° simulation and it reaches 16.4mV at its highest point. In comparison the action potential reaches only 4mV at its highest point in the 12.3C° simulation. According to the results of this simulation, action potential amplitude decreases with a temperature rise.



Figure 29: Temperature Effect Results

One can also notice that the action potential complex is slightly wider in the 6.3C° experiment. It reaches its lowest point of -80.5mV at 8.2ms. The action potential then

slowly returns to -70 at 20ms. In the 12.3 C° experiment the action potential has a narrow complex which reaches its lowest point of -80.45mV at 7.15ms and reaches -70mV (resting potential) at 14.2ms. At this stage all potassium channels are closed. The only active channels at this time are the leak channels and active pumps. These channels are responsible for restoring the resting state of an action potential.

These simulation results are consistent with the results described in "Warm Body Temperature Facilitates Energy Efficient Cortical Action Potentials" [23].

Figure 30 illustrates the action potential of classical HH model neuron generated at 6, 18, and 27 C°, respectively. Bottom panel shows the corresponding Na+ and K+ currents during action potential generation for temperature at 6, 18, and 27 C°, respectively.



Figure 30: Action Potential: temperature effect [23]

## **3.5 Current Injection**

It is beneficial to investigate how current injection impacts the change in voltage in the excitable cell. In this experiment electrodes are used to introduce an electrical current into the excitable cell. A voltmeter is used for measuring the voltage potential of
the cell. Another way to study current injection is to use the Hodgkin and Huxley model. The model can be modified to introduce an external current. Figure 19 shows the modified Hodgkin and Huxley model which can be used for the current injection experiment.

Figure 31 illustrates the results of injecting different electrical currents into the Hodgkin and Huxley model. The y-axis represents voltage v(t) in millivolts. The x-axis represents time in milliseconds. The simulation runs for 100ms. The first voltage strip demonstrates how the membrane potential changes when 12µA current is injected into the model. This level of injected current results in consistent generation of action potentials. In the second experiment the current was reduced from 12µA to 8µA. The second strip shows the results for the second experiment. In this experiment an action potential is fired consistently but at the lower rate. In other words, there are 8 action potential complexes initiated during the 12µA current injection, while there are only 7 action potential complexes originated with the 8nA current injection.

The third voltage strip of Figure 31 demonstrates the voltage change with the  $4\mu$ A current injection. At this level of current injection, a single action potential complex is generated. The fourth voltage strip of Figure 31 is a reference experiment. There is no current ( $0\mu$ A) injected during the reference experiment. There is no action potential generated during the reference experiment. Therefore, the fourth voltage strip of Figure 31 contains a flat line. The fifth voltage strip of Figure 31 represents a -5 $\mu$ A current injection and just like in the reference experiment, there is no action potential generated.



Figure 31: Action potential during current injection

The current injection can be split into three distinct phases: equilibrium stage, single spike stage and limit cycle stage. The single spike stage is a stage where only a single action potential complex is generated. This stage continues until we get to a point where the action potential fires consistently. At this level of current we have reached a minimum firing rate. So what does the minimum firing rate mean? The action potential can either fire or not. The action potential cannot fire partially or fire with low amplitude. Due to the "all or nothing" principle, there is no visible increase in the action potential amplitude. Instead there is a sudden voltage jump which is consistent with an action potential complex. In the example below this level is reached at 8µA. In other words, action potentials fires continuously at 8µA or higher.

An increase in injected current (*I*) will lead to an increase in firing rate in a neuron. Figure 31 shows that the number of action potential complexes increase from 0 to 8 when the injected current increases from  $0\mu$ A to  $12\mu$ A.

These simulation results are consistent with the results described in "Current Clamp and Modeling Studies of Low-Threshold Calcium Spikes in Cells of the Cat's Lateral Geniculate Nucleus" [24]. Figure 32 illustrates the relationship between current injection (400-ms pulses) and the evoked action potential responses.



Figure 32: Current Injection [24]

### 3.6 Threshold

Threshold level defines the minimum level that a membrane potential has to reach in order for an action potential to fire. If this level is not reached, the potential will return to the resting voltage and an action potential will not fire.

Threshold level depends greatly on resting membrane potential. In all of the simulations discussed in this work, the resting membrane potential was set to -70mV. In other words, -70mV is the initial value used for the membrane potential in all simulations discussed in this dissertation. Threshold level also depends on experimental temperature. During most of the experiments discussed in this work, the temperature level was set to 6.3C°.

In order to identify the threshold level, a set of experiments should be performed where different levels of current (*I*) are injected into the excitable cell. In this work the current is injected in the Simulink model. In order to get the most accurate estimates for the threshold level, the current (*I*) is increased gradually until the action potential initiates.

Let us consider an experiment below. In order to identify the threshold level for the model described in this work, different levels of current have been injected into the model. The results of this experiment are depicted in Figure 33. The y-axis scale of all experiments runs from -100mV to 40mV. Each experiment runs for 15ms. For the baseline experiment there was no current injection. Therefore, the action potential wan not initiated. This can be seen on the first image of Figure 33. In order to determine the threshold level, an external current of 1.5µA was injected into the model. As a result of this stimulation, the potential increased and reached -67.5mV. This simulation is represented in the second image of Figure 33. After an external stimulus is applied,

potential starts to increase until -67.5mV is reached. This increase was due to the external current applied to the excitable cell. After reaching -67.5mV, the potential starts to decline and eventually returns to the resting voltage. The applied current in this experiment was not high enough to produce an action potential. In other words, the potential did not reach the threshold level. Therefore, the external stimulus should be increased even further.

In the next simulation (shown in the third image in Figure 33) the current (*I*) is increased to 2.2567 $\mu$ A. As in the previous example, this level of current (*I* = 2.2567 $\mu$ A) is not sufficient to initiate an action potential. In other words, during this simulation the membrane potential does not reach the threshold level and returns to its resting state (-70mV). An external stimulus is applied and the potential starts to increase from -70mV to -59.178mV. After reaching its highest level of -59.178mV, the potential starts to decay and eventually returns to its resting level. Comparing results with the previous simulation we notice that the voltage potential reaches a higher level (-59.178mV) when a higher current (*I* = 2.2567 $\mu$ A) is applied. In other words, a higher current depolarizes cell more and therefore the membrane potential can reach a higher level. Reaching potential of -59.178mV does not result in an action potential. Therefore, the external stimulus has to be increased.



Figure 33: Threshold

In the last simulation the current (*I*) was increased to 3µA. The results of this experimental run are shown in the last image of Figure 33. An external stimulus, applied to the model, initiates an action potential complex. Therefore, we can conclude that the threshold level was reached by applying an external stimulus of 3µA during a 6.3C° experiment. By examining the test results depicted in the last graph in Figure 33, we can see that the action potential starts its initiation process at approximately -60mV. Voltage gated sodium channels start to open when the membrane potential reaches -59.178mV. This results in a rapid inflow of sodium ions into the cell. On the graph this process is shown as a rapid raise in the action potential curve. Therefore, -59.178mV is the threshold level for a giant squid axon model which is simulated at 6.3C°.

Threshold simulation results are consistent with the theoretical data described in "Nerve Cells and Electric Signaling" [25]. Figure 34 illustrates the changes in the membrane potential in response to a different stimulus strength.



Figure 34: Threshold level [25]

# Chapter 4

### 4.1 Future Work

Without any doubts the Hodgkin and Huxley model is a quantitatively useful model for neuromodulation studies. This model can be extended and improved even further. Future enhancements to the model may include the following work:

- Modeling and analyzing the function of active pumps, such as the sodium and potassium pumps, that are actively involved in maintaining the resting membrane potential.
- Utilizing the Hodgkin and Huxley model in order to study different types of stimulation techniques and their effects on action potential initiation and propagation.
- Extending the Hodgkin and Huxley model to create a closed loop system which would dynamically optimize the stimulation signal depending on an output from the Hodgkin and Huxley model.

The current model lacks the implementation of active pumps, such as Na<sup>+</sup>K<sup>+</sup> pumps. Excitable cell membranes contain multiple ion channel types. One such ion channel is the active pump which is responsible for maintaining a resting membrane potential. It may be beneficial to investigate the significance of active pumps and determine their role in an action potential initiation and propagation. This investigation will involve performing voltage clamp simulations on a giant squid axon model and finding the mathematical relationships between voltage, current and conductance.

A giant squid axon can be used for this simulation. In order to block voltage gated sodium channels, tetrodotoxin (TTX) can be introduced into a giant squid axon.

Tetraethylammonium (TEA) can be used to block voltage gated potassium channels. Tetrodotoxin is an alkaloid neurotoxin that is commonly found in puffer fish and several species of frogs. This molecule has the ability to selectively block voltage gated sodium channels which will prevent sodium ions from crossing the cell membrane from the extracellular environment to the intracellular environment and vice versa [26]. TTX is often used in experiments where the sodium ion concentration is kept constant.

Tetraethylammonium is a quaternary ammonium compound. It has the ability to selectively block voltage gated potassium channels which will prevent potassium ions from crossing from the intracellular environment to the extracellular environment and vice versa [27]. TEA is often used in experiments where the potassium concentration is kept constant.

By deactivating both voltage gated potassium and voltage gated sodium channels it may be possible to investigate and model the impact of active pumps. This study will provide a better understanding of the role of active pumps in the action potential initiation process.

The Simulink model, described in the work, can be improved by introducing a custom signal builder, which can be used to study different types of stimulation techniques and their effects on an action potential initiation and propagation. In today's world of implantable devices it is very important to optimize and maximize a battery life. Prolongation of the battery life would require less battery exchanges and therefore less surgical procedures.

In order to achieve this goal, the battery consumption needs to be minimized. By introducing a custom signal builder we can minimize the level of energy used for cell

stimulation. This can be done by using biphasic stimulation, monophasic stimulation, burst stimulation and combinations of these stimulations.

Most neuromodulation devices are blindly delivering the therapy to patients. These therapy devices do not receive any kind of feedback notifying the device if the therapy was delivered successfully or not. These types of therapies are based on previously programmed values that can only be changed by a human interaction. Ideally, neuromodulation devices would operate with a minimum of human intervention. Apart from inconvenience, there are many risks involved in giving patients the ability to program their own devices. It is not uncommon for people to make mistakes while programming their own devices. Another risk factor is a security. No matter how well the security system is designed, there will always be people trying to find ways to penetrate that security system. This may result in potential risk for a patient. By modifying the programmed therapy, an intruder may unwillingly or willingly create a life threatening situation for a patient. Therefore, it might be worth building a closed loop system that will be able to analyze the result of a delivered therapy and adjust the output accordingly. This study can be achieved by extending the Simulink model and implementing the input side of the circuit. By implementing a close loop system we can eliminate the need for a patient to interfere with a neuromodulation device.

## 4.2 Conclusion

Neural communication involves a transfer of information from the brain to different parts of the body (e.g. arms, legs, vasculature, etc.) and vice versa. This communication is achieved by means of neurons that process and transmit information through electrical and chemical signals. Neural communication has a number of important functions such as sensory communication, motor communication, etc.

Neural communication is necessary for a being to functioning properly. All neural communications are achieved by means of action potentials. The action potential is an event during which an electrical impulse travels from one location in the body to another. By stimulating an excitable cell, the cell membrane goes through a sequence of events such as depolarization from its resting state followed by repolarization back to the resting state. As a result, the polarity of excitable cell is reversed for a brief period of time (from negative to positive) and then returns back to its initial state by reestablishing the rest potential.

One of the most important contributions to neuroscience has been made by Alan Hodgkin and Andrew Huxley. They used a giant squid axon to derive a mathematical model which analyzed and explained the ionic mechanisms underlying the initiation and propagation of action potentials. In 1963, Hodgkin and Huxley received a Nobel Prize in Physiology. The Hodgkin and Huxley model is a mathematical model that describes how the action potential is initiated and propagated in a neuron. It is a set of nonlinear ordinary differential equations that approximates the electrical characteristics of excitable cells.

This model simulates an action potential origination and propagation in an axon. It also provides the ability to investigate different properties of a neuron such as diameter and operating temperature and their impact on the action potential.

There have been many improvements introduced to the Hodgkin and Huxley model. A lot of new and more complex models have been developed over the years. The Hodgkin and Huxley model was the foundation for most of these models.

With the aid of advanced modeling tools such as MATLAB Simulink a lot of useful and complex simulations can be performed. These tools provide a practical way to model different properties of a neuron and to analyze their impact on the electrical signal.

#### References

- M. R. James Neitzel, "Cell Communication," [Online]. Available: http://www.nature.com/scitable/topic/cell-communication-14122659. [Accessed 27 10 2013].
- [2] R. Plonsey and R. C. Barr, "Bioelectricity A Quantative Approach," p. 50, 2007.
- [3] Boundless, "Nerve Impulse Transmission within a Neuron," Boundless, [Online]. Available: https://www.boundless.com/biology/the-nervous-system/how-neuronscommunicate/nerve-impulse-transmission-within-a-neuron-resting-potential/. [Accessed 07 04 2014].
- [4] J. Malmivuo and R. Plonsey, Bioelectromagnetism, New York; Oxford: OXFORD UNIVERSITY PRESS, 1995.
- [5] M. D, Y. A and R. S, "Exploring Biological Neuron Models," [Online]. Available: http://www.iitk.ac.in/directions/feb2006/PRINT~KALRA.pdf. [Accessed 21 11 2013].
- [6] K. Abbas, Robbin's Basic Pathology, Elsevier Health Sciences, 2007.
- [7] N. R. Carlson, Foundations of Physiological Psychology, Allyn & Bacon, 2004, pp. 53-55.
- [8] S. Muskopf, "Chapter 5 Membrane Structure and Function," [Online]. Available: http://www.biologycorner.com/APbiology/cellular/notes\_cell\_membrane.html. [Accessed 9 March 2013].
- [9] C. Biology, "How Neurons Communicate," 10 May 2013. [Online]. Available: http://cnx.org/content/m44748/latest/.
- [10] W. A. Catterall, "Voltage-Gated Calcium Channels," 11 07 2011. [Online]. Available: http://intl-cshperspectives.cshlp.org/content/3/8/a003947.full. [Accessed 07 04 2014].
- [11] C. G. Sobey, "Potassium Channel Function in Vascular Disease," Arteriosclerosis, Thrombosis, and Vascular Biology., no. 10, pp. 28-39, 2000.
- [12] N. Media, "The Nobel Prize in Chemistry 1997," 2013. [Online]. Available: http://www.nobelprize.org/nobel\_prizes/chemistry/laureates/1997/illpres/skou.html.
- [13] C. A. a. Physiology, "The Action Potential," 28 June 2013. [Online]. Available:

http://cnx.org/content/m46526/latest/. [Accessed 29 Sep 2013].

- [14] UIC.edu, "The Body's Communication Systems: The Endocrine and Nervous Systems,"
   [Online]. Available: http://www.uic.edu/classes/bios/bios100/lectures/nervous.htm.
   [Accessed 11 March 2013].
- [15] S. Alford, "The Hodgkin-Huxley equations.". Cell and Molecular Neurobiology.
- [16] J. H. Byrne, "Chapter 3: Propagation of the Action Potential," 1997. [Online]. Available: http://neuroscience.uth.tmc.edu/s1/chapter03.html.
- [17] "Peripheral Axons: Characteristics," 10 12 2013. [Online]. Available: http://neuromuscular.wustl.edu/nother/axon.htm.
- [18] CUNeurons, "Section 2 Myelination & Diameter," CUNeurons, [Online]. Available: https://sites.google.com/site/cuneurons/section-2. [Accessed 15 1 2014].
- [19] S. Sircar, Principles of Medical Physiolog, New York, NY: Thieme, 2008, p. 91.
- [20] L. Squire, Fundamental Neuroscience, Oxford: Elsever Inc, 2013, p. 62.
- [21] B. G. A. G. a. D. W. David Sterratt, "Principles of Computational Modeling in Neuroscience," 2011. [Online]. Available: http://www.compneuroprinciples.org/codeexamples/all/all. [Accessed 11 06 2014].
- [22] F. Bezanilla, "Ionic currents during the nerve impulse," Nature Reviews: Molecular Cell Biology, 01 04 2008. [Online]. Available: http://www.nature.com/nrm/journal/v9/n4/box/nrm2376\_BX2.html. [Accessed 28 03 2014].
- [23] H. A. M. D. Yu Y, "Warm Body Temperature Facilitates Energy Efficient Cortical Action Potentials," *PLoS Comput Biol,* vol. 8, no. 4, 2012.
- [24] C. L. C. ,. J. R. ,. S. M. S. X. J. Zhan, "Current Clamp and Modeling Studies of Low-Threshold Calcium Spikes in Cells of the Cat's Lateral Geniculate Nucleus," *Journal of Neurophysiology*, vol. 81, pp. 2360-2373, 1999.
- [25] M. J. College, "Chapter 7 Nerve Cells and Electric Signaling," Modesto Junior College: MJC, [Online]. Available: http://droualb.faculty.mjc.edu/Course%20Materials/Physiology%20101/Chapter%20Note s/Fall%202011/chapter\_7%20Fall%202011.htm. [Accessed 12 06 2014].
- [26] NCBI, "Tetrodotoxin," [Online]. Available:

http://pubchem.ncbi.nlm.nih.gov/summary/summary.cgi?cid=20382. [Accessed 29 1 2014].

[27] NCBI, "Tetraethylammonium," [Online]. Available: http://pubchem.ncbi.nlm.nih.gov/summary/summary.cgi?cid=5413. [Accessed 29 1 2014].

# Appendix

# Appendix A: Simulink Constants and Variables

```
clear;
```

e ************************************	***	***********
% CONSTANTS		
§ **********************	***	**********
V_initial=0;	00	Initial voltage (mV)
	8 1	used for Anode break
V_resting=-70;	8]	Resting membrane potential (mV)
E_Na=115;	00	Vr - VNa (mV)
E_K=-12;	00	Vr - VK (mV)
E_leak=10.613;	olo 1	Vr - VL (mV)
Cm=1;	8 1	membrane capacitance per unit area (µF/cm²)
$C \log k = 0.3$	0	lookago conductored por unit area (mS/cm2)
<u>G_ieak-0.3</u> ,	°0 .	reakage conductance per unit area(m3/cm )
G_Na=120;	00	sodium conductance per unit area(mS/cm²)
G_K=36;	% ]	potassium conductance per unit area(mS/cm <sup>2</sup> )

00	* * * * * * * * * * * * * * * * * * * *	* *	**>	* * * *	****	* * *	***	**7	***	***	**	**	* * 7	* * *	***	***	**
00	VARIABLES																
00	******	* *	**;	* * * *	****	* * *	* * * *	**7	* * *	***	**	**	* * 7	* * *	* * *	***	**
n_	_initial=0.3176;	0/0	In	itia	al n	n g	gate	7 9	var	ria	bl	е					

m_	_initial=0.0529;	00	Initial	m	gate	variable
h_	_initial=0.5919;	0 0	Initial	h	gate	variable

% TEMPERATURE
Temperature\_Bit=1; % To enable the analysis of the temperature
effect set bit to 1
% and to disable the effect of the
temperature set
% the bit to any value not equal to 1
Temperature=6.3; % Temperature in Celsius

#### Appendix B: Simulink Model Source Code

```
Model {
                         "MyModel"
 Name
 Version
                   7.7
 MdlSubVersion
                         0
 GraphicalInterface {
                           0
   NumRootInports
   NumRootOutports
                           Ω
   ParameterArgumentNames ""
                          "1.258"
   ComputedModelVersion
   NumModelReferences
                           0
   NumTestPointedSignals
                           0
  }
  SavedCharacterEncoding "windows-1252"
  slprops.hdlmdlprops {
   $PropName
                           "HDLParams"
   $ObjectID
                           1
   Array {
     Type
                       "Cell"
     Dimension
                             2
                       "HDLSubsystem"
     Cell
                       "MyModel"
     Cell
                             "mdlProps"
     PropName
   }
  }
  SaveDefaultBlockParams on
  ScopeRefreshTime 0.035000
 OverrideScopeRefreshTime on
 DisableAllScopes off
 DataTypeOverride "UseLocalSettings"
 DataTypeOverrideAppliesTo "AllNumericTypes"
 MinMaxOverflowLogging "UseLocalSettings"
 MinMaxOverflowArchiveMode "Overwrite"
 MaxMDLFileLineLength
                      120
 UserBdParams
"PhysicalModelingChecksum; PhysicalModelingParameterChecksum; PhysicalMod
elingProducts"
  PhysicalModelingChecksum "2725184017"
  PhysicalModelingParameterChecksum "1666047934"
 PhysicalModelingProducts "Simscape"
 Created
                   "Mon Jan 14 21:36:21 2013"
                   "Vladimir"
 Creator
 UpdateHistory
                        "UpdateHistoryNever"
 ModifiedByFormat "%<Auto>"
 LastModifiedBy "ruzovv01"
 ModifiedDateFormat "%<Auto>"
                        "Fri May 09 15:13:27 2014"
 LastModifiedDate
 RTWModifiedTimeStamp 321543468
                        "1.%<AutoIncrement:258>"
 ModelVersionFormat
 ConfigurationManager "None"
                       off
 SampleTimeColors
  SampleTimeAnnotations
                        off
  LibraryLinkDisplay
                        "none"
 WideLines
                  off
```

ShowLineDimensions off ShowPortDataTypes off ShowLoopsOnError on IgnoreBidirectionalLines off ShowStorageClass off ShowTestPointIcons on ShowSignalResolutionIcons on ShowViewerIcons on SortedOrder off ExecutionContextIcon off ShowLinearizationAnnotations on BlockNameDataTip off BlockParametersDataTip off BlockDescriptionStringDataTip off ToolBar on StatusBar on BrowserShowLibraryLinks on BrowserLookUnderMasks on SimulationMode "normal" LinearizationMsg "none" Profile off "MATLABWorkspace" ParamWorkspaceSource "accel.tlc" AccelSystemTargetFile AccelTemplateMakefile "accel default tmf" AccelMakeCommand "make rtw" TryForcingSFcnDF off Object { "DataLoggingOverride" \$PropName \$ObjectID 2 "Simulink.SimulationData.ModelLoggingInfo" \$ClassName "simulink1" model [0.0] overrideMode Array { "Cell" Туре Dimension 1 "simulink1" Cell "logAsSpecifiedByModels " PropName } Array { "Cell" Type Dimension 1 Cell [] "logAsSpecifiedByModelsSSIDs " PropName } off RecordCoverage "/" CovPath "covdata" CovSaveName "dw" CovMetricSettings CovNameIncrementing off CovHtmlReporting on CovForceBlockReductionOff on covSaveCumulativeToWorkspaceVar on CovSaveSingleToWorkspaceVar on CovCumulativeVarName "covCumulativeData" CovCumulativeReport off CovReportOnPause on

CovModelRefEnable "Off" CovExternalEMLEnable off off ExtModeBatchMode ExtModeEnableFloating on ExtModeTrigType "manual" ExtModeTrigMode "normal" ExtModeTrigPort "1" ExtModeTrigElement "any" ExtModeTrigDuration 1000 ExtModeTrigDurationFloating "auto" ExtModeTrigHoldOff 0 ExtModeTrigDelay 0 ExtModeTrigDirection "rising" ExtModeTrigLevel 0 ExtModeArchiveMode "off" ExtModeAutoIncOneShot off ExtModeIncDirWhenArm off ExtModeAddSuffixToVar off ExtModeWriteAllDataToWs off ExtModeArmWhenConnect on ExtModeSkipDownloadWhenConnect off ExtModeLogAll on ExtModeAutoUpdateStatusClock on BufferReuse off ShowModelReferenceBlockVersion off ShowModelReferenceBlockIO off Array { "Handle" Туре Dimension 1 Simulink.ConfigSet { \$ObjectID 3 "1.11.0" Version Array { "Handle" Туре Dimension 10 Simulink.SolverCC { \$ObjectID 4 Version "1.11.0" "1.11 "0.0" Version StartTime "100" "1e-6" StopTime AbsTol FixedStep "auto" InitialStep "auto" MaxNumMinSteps "-1" MaxOrder 5 ZcThreshold "auto" ConsecutiveZCsStepRelTol "10\*128\*eps" MaxConsecutiveZCs "1000" 4 ExtrapolationOrder NumberNewtonIterations 1 MaxStep "auto" MinStep "auto" MaxConsecutiveMinStep "1" RelTol "1e-3" SolverMode "Auto" ConcurrentTasks off "ode45" Solver

```
"ode45"
 SolverName
 SolverJacobianMethodControl "auto"
 ShapePreserveControl "DisableAll"
 ZeroCrossControl
                         "UseLocalSettings"
                      "Nonadaptive"
 ZeroCrossAlgorithm
                       "TrustRegion"
 AlgebraicLoopSolver
 SolverResetMethod
                       "Fast"
 PositivePriorityOrder off
 AutoInsertkaterran
SampleTimeConstraint "Unconstrained
"Whenever possible"
 AutoInsertRateTranBlk off
ļ
Simulink.DataIOCC {
 $ObjectID
                   5
 Version
                   "1.11.0"
 Decimation
                        "1"
 Decimation
ExternalInput
                         "[t, u]"
 FinalStateName
                   "xFinal"
                       "xInitial"
 InitialState
 LimitDataPoints on
                        "1000"
 MaxDataPoints
 LoadExternalInput
                        off
                        off
 LoadInitialState
 SaveFinalState off
 SaveCompleteFinalSimState off
                         "Array"
 SaveFormat
 SignalLoggingSaveFormat "ModelDataLogs"
 SaveOutput
                         on
 SaveState
                   off
 SignalLogging
                         on
 DSMLogging
                        on
 InspectSignalLogs
                       off
 SaveTime on
 ReturnWorkspaceOutputs off
 StateSaveName
                        "xout"
                       "tout"
 TimeSaveName
 OutputSaveName "yout"
 SignalLoggingName "logsout"
                   "dsmout"
 DSMLoggingName
                         "RefineOutputTimes"
 OutputOption
                        "[]"
 OutputTimes
 ReturnWorkspaceOutputsName "out"
                   "1"
 Refine
Simulink.OptimizationCC {
 $ObjectID
                   6
                   "1.11.0"
 Version
 Array {
                     "Cell"
   Туре
                       8
   Dimension
                     "BooleansAsBitfields"
   Cell
   Cell
                     "PassReuseOutputArgsAs"
   Cell
                     "PassReuseOutputArgsThreshold"
   Cell
                     "ZeroExternalMemoryAtStartup"
                     "ZeroInternalMemoryAtStartup"
   Cell
                     "OptimizeModelRefInitCode"
   Cell
                     "NoFixptDivByZeroProtection"
   Cell
```

"UseSpecifiedMinMax" Cell "DisabledProps" PropName } BlockReduction off BooleanDataType on ConditionallyExecuteInputs on InlineParams on UseIntDivNetSlope off UseSpecifiedMinMax off InlineInvariantSignals off OptimizeBlockIOStorage on BufferReuse off EnhancedBackFolding off StrengthReduction off ExpressionFolding on BooleansAsBitfields off "uint T" BitfieldContainerType EnableMemcpy on MemcpyThreshold 64 PassReuseOutputArgsAs "Structure reference" 2147483647 ExpressionDepthLimit FoldNonRolledExpr on LocalBlockOutputs on RollThreshold 5 SystemCodeInlineAuto off StateBitsets off DataBitsets off UseTempVars off ZeroExternalMemoryAtStartup on ZeroInternalMemoryAtStartup on InitFltsAndDblsToZero off NoFixptDivByZeroProtection off EfficientFloat2IntCast off EfficientMapNaN2IntZero on OptimizeModelRefInitCode off "inf" LifeSpan "Inherit from target" MaxStackSize BufferReusableBoundary on SimCompilerOptimization "Off" AccelVerboseBuild off AccelParallelForEachSubsystem on } Simulink.DebuggingCC { \$ObjectID Version "1.11.0" RTPrefix "error" ConsistencyChecking "none" "none" ArrayBoundsChecking "none" SignalInfNanChecking "none" SignalRangeChecking "UseLocalSettings" ReadBeforeWriteMsg "UseLocalSettings" WriteAfterWriteMsg WriteAfterReadMsg "UseLocalSettings" "warning" AlgebraicLoopMsg ArtificialAlgebraicLoopMsg "warning" SaveWithDisabledLinksMsg "warning" SaveWithParameterizedLinksMsg "warning"

```
CheckSSInitialOutputMsg on
                                                "Classic"
       UnderspecifiedInitializationDetection
       MergeDetectMultiDrivingBlocksExec "none"
       CheckExecutionContextPreStartOutputMsg off
       CheckExecutionContextRuntimeOutputMsg
                                                off
       SignalResolutionControl "UseLocalSettings"
       BlockPriorityViolationMsg "warning"
       MinStepSizeMsg "warning"
                              "none"
       TimeAdjustmenters
MaxConsecutiveZCsMsg "error"
"warning"
       TimeAdjustmentMsg
       MaskedZcDiagnostic "warning"
IgnoredZcDiagnostic "warning"
                               "none"
       SolverPrmCheckMsg
       InheritedTsInSrcMsg "warning"
       DiscreteInheritContinuousMsg "warning"
       MultiTaskDSMMsg "error"
       MultiTaskCondExecSysMsg "error"
       MultiTaskRateTransMsg
                               "error"
       SingleTaskRateTransMsg "none"
       TasksWithSamePriorityMsg "warning"
       SigSpecEnsureSampleTimeMsg "warning"
       CheckMatrixSingularityMsg "none"
       IntegerOverflowMsg "warning"
                              "warning"
       Int32ToFloatConvMsg
       ParameterDowncastMsg "error"
                               "error"
       ParameterOverflowMsq
       ParameterUnderflowMsg "none"
       ParameterPrecisionLossMsg "warning"
       ParameterTunabilityLossMsg "warning"
       FixptConstUnderflowMsg "none"
       FixptConstOverflowMsg
                                "none"
       FixptConstPrecisionLossMsg "none"
       UnderSpecifiedDataTypeMsg "none"
       UnnecessaryDatatypeConvMsg "none"
       VectorMatrixConversionMsg "none"
       InvalidFcnCallConnMsg "error"
       FcnCallInpInsideContextMsg "Use local settings"
       SignalLabelMismatchMsg "none"
                               "warning"
       UnconnectedInputMsg
       UnconnectedOutputMsg "warning"
                              "warning"
       UnconnectedLineMsq
       SFcnCompatibilityMsg "none"
                                "none"
       UniqueDataStoreMsg
       BusObjectLabelMismatch "warning"
       RootOutportRequireBusObject "warning"
       AssertControl
                               "UseLocalSettings"
       EnableOverflowDetection off
       ModelReferenceIOMsq "none"
       ModelReferenceMultiInstanceNormalModeStructChecksumCheck
"error"
       ModelReferenceVersionMismatchMessage "none"
       ModelReferenceIOMismatchMessage "none"
       ModelReferenceCSMismatchMessage "none"
       UnknownTsInhSupMsq
                            "warning"
       ModelReferenceDataLoggingMessage "warning"
       ModelReferenceSymbolNameMessage "warning"
       ModelReferenceExtraNoncontSigs "error"
```

```
StateNameClashWarn
                        "warning"
 SimStateInterfaceChecksumMismatchMsg "warning"
 SimStateOlderReleaseMsg "error"
 InitInArrayFormatMsg
                        "warning"
 StrictBusMsq
                        "ErrorLevel1"
                   "WarnAndRepair"
 BusNameAdapt
 NonBusSignalsTreatedAsBus "none"
 LoggingUnavailableSignals "error"
 BlockIODiagnostic
                     "none"
 SFUnusedDataAndEventsDiag "warning"
 SFUnexpectedBacktrackingDiag "warning"
 SFInvalidInputDataAccessInChartInitDiag "warning"
 SFNoUnconditionalDefaultTransitionDiag "warning"
 SFTransitionOutsideNaturalParentDiag "warning"
Simulink.HardwareCC {
 $ObjectID
                   8
 Version
                   "1.11.0"
 ProdBitPerChar
                 8
 ProdBitPerShort 16
                         32
 ProdBitPerInt
                  32
 ProdBitPerLong
 ProdBitPerFloat 32
 ProdBitPerDouble
                         64
                        32
 ProdBitPerPointer
 ProdLargestAtomicInteger "Char"
 ProdLargestAtomicFloat "None"
 ProdIntDivRoundTo "Undefined"
                       "Unspecified"
 ProdEndianess
                        32
 ProdWordSize
 ProdShiftRightIntArith on
 ProdHWDeviceType "32-bit Generic"
 TargetBitPerChar
                       8
 TargetBitPerShort
                       16
 TargetBitPerInt 32
                        32
 TargetBitPerLong
                        32
 TargetBitPerFloat
 TargetBitPerDouble
                        64
                        32
 TargetBitPerPointer
 TargetLargestAtomicInteger "Char"
 TargetLargestAtomicFloat "None"
 TargetShiftRightIntArith on
 TargetIntDivRoundTo "Undefined"
 TargetEndianess "Unspecified"
 TargetWordSize
                   32
 TargetTypeEmulationWarnSuppressLevel 0
 TargetPreprocMaxBitsSint 32
 TargetPreprocMaxBitsUint 32
 TargetHWDeviceType "Specified"
                        off
 TargetUnknown
 ProdEqTarget
                        on
Simulink.ModelReferenceCC {
 $ObjectID 9
                   "1.11.0"
 Version
 UpdateModelReferenceTargets "IfOutOfDateOrStructuralChange"
 CheckModelReferenceTargetMessage "error"
```

```
EnableParallelModelReferenceBuilds off
 ParallelModelReferenceErrorOnInvalidPool on
 ParallelModelReferenceMATLABWorkerInit "None"
 ModelReferenceNumInstancesAllowed "Multi"
                         "Infer from blocks in model"
 PropagateVarSize
 ModelReferencePassRootInputsByReference on
 ModelReferenceMinAlqLoopOccurrences off
 PropagateSignalLabelsOutOfModel off
 SupportModelReferenceSimTargetCustomCode off
Simulink.SFSimCC {
 $ObjectID
                   10
 Version
                   "1.11.0"
 SFSimEnableDebug
                         on
 SFSimOverflowDetection on
 SFSimEcho
                  on
 SimBlas
                   on
 SimCtrlC
                   on
 SimExtrinsic
                        on
 SimIntegrity
                        on
 SimUseLocalCustomCode off
 SimParseCustomCode
                        on
 SimBuildMode
                         "sf incremental build"
Simulink.RTWCC {
                         "Simulink.RTWCC"
 $BackupClass
 $ObjectID
                  11
                   "1.11.0"
 Version
 Array {
                     "Cell"
   Type
                           8
   Dimension
   Cell
                     "IncludeHyperlinkInReport"
                     "GenerateTraceInfo"
   Cell
                     "GenerateTraceReport"
   Cell
                     "GenerateTraceReportS1"
   Cell
                     "GenerateTraceReportSf"
   Cell
                     "GenerateTraceReportEml"
   Cell
                     "GenerateSLWebview"
   Cell
                     "GenerateCodeMetricsReport"
   Cell
                          "DisabledProps"
   PropName
  }
 SystemTargetFile
                       "grt.tlc"
                         off
 GenCodeOnly
 MakeCommand
                         "make rtw"
 GenerateMakefile
                         on
 TemplateMakefile
                         "grt default tmf"
 GenerateReport off
                   off
 SaveLog
 RTWVerbose
                         on
 RetainRTWFile
                         off
 ProfileTLC
                         off
                   off
 TLCDebug
 TLCCoverage
                         off
 TLCAssert
                   off
 ProcessScriptMode
                         "Default"
 ConfigurationMode
                        "Optimized"
 ConfigAtBuild
                         off
```

```
RTWUseLocalCustomCode
                      off
RTWUseSimCustomCode
                       off
IncludeHyperlinkInReport off
LaunchReport
                       off
                       "C"
TargetLang
IncludeBusHierarchyInRTWFileBlockHierarchyMap off
IncludeERTFirstTime off
GenerateTraceInfo
                       off
GenerateTraceReport
                      off
GenerateTraceReportSl off
GenerateTraceReportSf off
GenerateTraceReportEml off
GenerateCodeInfo
                     off
GenerateSLWebview
                      off
GenerateCodeMetricsReport off
RTWCompilerOptimization "Off"
CheckMdlBeforeBuild
                     "Off"
CustomRebuildMode
                       "OnUpdate"
Array {
                   "Handle"
 Type
 Dimension
                         2
 Simulink.CodeAppCC {
   $ObjectID
                           12
                           "1.11.0"
   Version
   Array {
                     "Cell"
   Type
   Dimension
                     21
   Cell
                    "IgnoreCustomStorageClasses"
                   "IgnoreTestpoints"
   Cell
                   "InsertBlockDesc"
   Cell
                   "InsertPolySpaceComments"
   Cell
                    "SFDataObjDesc"
   Cell
                    "MATLABFcnDesc"
   Cell
                    "SimulinkDataObjDesc"
   Cell
                    "DefineNamingRule"
   Cell
                    "SignalNamingRule"
   Cell
                    "ParamNamingRule"
   Cell
                     "InlinedPrmAccess"
   Cell
                     "CustomSymbolStr"
   Cell
   Cell
                     "CustomSymbolStrGlobalVar"
   Cell
                     "CustomSymbolStrType"
   Cell
                     "CustomSymbolStrField"
                     "CustomSymbolStrFcn"
   Cell
   Cell
                     "CustomSymbolStrFcnArg"
   Cell
                     "CustomSymbolStrBlkIO"
   Cell
                     "CustomSymbolStrTmpVar"
   Cell
                     "CustomSymbolStrMacro"
   Cell
                     "RegsInCode"
                     "DisabledProps"
   PropName
    }
   ForceParamTrailComments off
   GenerateComments
                           on
   IgnoreCustomStorageClasses on
   IgnoreTestpoints off
   IncHierarchyInIds
                           off
   MaxIdLength
                     31
   PreserveName
                           off
```

```
PreserveNameWithParent off
     ShowEliminatedStatement off
     IncAutoGenComments off
     SimulinkDataObjDesc
                            off
     SFDataObjDesc
                            off
                           off
     MATLABFcnDesc
     IncDataTypeInIds
                           off
     MangleLength
                             1
     CustomSymbolStrGlobalVar "$R$N$M"
     CustomSymbolStrType "$N$R$M"
     CustomSymbolStrField "$N$M"
CustomSymbolStrFcn "$R$N$
                            "$R$N$M$F"
     CustomSymbolStrFcnArg "rt$I$N$M"
     CustomSymbolStrBlkIO "rtb $N$M"
     CustomSymbolStrTmpVar
                             "$N$M"
                             "$R$N$M"
     CustomSymbolStrMacro
                             "None"
     DefineNamingRule
     ParamNamingRule
                             "None"
                            "None"
     SignalNamingRule
     InsertBlockDesc
                            off
     InsertPolySpaceComments off
     SimulinkBlockComments on
     MATLABSourceComments
                            off
     EnableCustomComments
                             off
     InlinedPrmAccess
                             "Literals"
     RegsInCode off
     UseSimReservedNames
                             off
   ļ
   Simulink.GRTTargetCC {
                             "Simulink.TargetCC"
     $BackupClass
     $ObjectID
                             13
                             "1.11.0"
     Version
     Array {
                       "Cell"
     Type
     Dimension
                      16
                      "GeneratePreprocessorConditionals"
     Cell
                     "IncludeMdlTerminateFcn"
     Cell
                     "CombineOutputUpdateFcns"
     Cell
                     "SuppressErrorStatus"
     Cell
                      "ERTCustomFileBanners"
     Cell
                       "GenerateSampleERTMain"
     Cell
                       "GenerateTestInterfaces"
     Cell
     Cell
"ModelStepFunctionPrototypeControlCompliant"
     Cell
                       "CPPClassGenCompliant"
     Cell
                       "MultiInstanceERTCode"
                       "PurelyIntegerCode"
     Cell
     Cell
                      "SupportComplex"
     Cell
                       "SupportAbsoluteTime"
                       "SupportContinuousTime"
     Cell
                       "SupportNonInlinedSFcns"
     Cell
                      "PortableWordSizes"
     Cell
                      "DisabledProps"
     PropName
     }
     TargetFcnLib
                             "ansi tfl table tmw.mat"
     TargetLibSuffix
                             ....
     TargetPreCompLibLocation ""
```

```
"ANSI C"
     TargetFunctionLibrary
                             "Auto"
     UtilityFuncGeneration
                             "System defined"
     ERTMultiwordTypeDef
     FunctionExecutionProfile off
     CodeExecutionProfiling off
     ERTCodeCoverageTool
                             "None"
     ERTMultiwordLength
                             256
     MultiwordLength
                             2048
     GenerateFullHeader
                             on
     GenerateSampleERTMain
                             off
     GenerateTestInterfaces off
     IsPILTarget
                   off
     ModelReferenceCompliant on
     ParMdlRefBuildCompliant on
     CompOptLevelCompliant
                             on
     IncludeMdlTerminateFcn on
     GeneratePreprocessorConditionals "Disable all"
     CombineOutputUpdateFcns off
     CombineSignalStateStructs
                                   off
     SuppressErrorStatus
                             off
     ERTFirstTimeCompliant
                             off
     IncludeFileDelimiter
                             "Auto"
     ERTCustomFileBanners
                             off
     SupportAbsoluteTime
                             on
     LogVarNameModifier
                             "rt "
     MatFileLogging
                             on
     MultiInstanceERTCode
                             off
     SupportNonFinite
                             on
     SupportComplex
                             on
     PurelyIntegerCode
                             off
     SupportContinuousTime
                             on
     SupportNonInlinedSFcns on
     SupportVariableSizeSignals off
     EnableShiftOperators on
     ParenthesesLevel
                             "Nominal"
     PortableWordSizes
                             off
     ModelStepFunctionPrototypeControlCompliant off
     CPPClassGenCompliant
                             off
     AutosarCompliant
                             off
                             off
     UseMalloc
     ExtMode
                             off
     ExtModeStaticAlloc
                             off
     ExtModeTesting
                             off
     ExtModeStaticAllocSize 1000000
     ExtModeTransport
                             0
     ExtModeMexFile
                             "ext comm"
                             "Level1"
     ExtModeIntrfLevel
     RTWCAPISignals
                             off
     RTWCAPIParams
                             off
     RTWCAPIStates
                             off
     RTWCAPIRootIO
                             off
     GenerateASAP2
                             off
    }
   PropName
                           "Components"
hdlcoderui.hdlcc {
```

} }

\$ObjectID 14 "1.11.0" Version "HDL Coder custom configuration Description component" "HDL Coder" Name Array { Type "Cell" Dimension 1 .... Cell PropName "HDLConfigFile" } "0" HDLCActiveTab } SSC.SimscapeCC { \$ObjectID 15 "1.0" Version Array { Туре "Cell" Dimension 1 "Name" Cell "DisabledProps" PropName } Array { "Handle" Туре Dimension 1 MECH.SimMechanicsCC { \$ObjectID 16 Version "1.11.0" "SimMechanics" Name WarnOnRedundantConstraints on WarnOnSingularInitialAssembly off ShowCutJoints off off VisOnUpdateDiagram VisDuringSimulation off EnableVisSimulationTime on VisSampleTime "0" DisableBodyVisControl off ShowCG on ShowCS on ShowOnlyPortCS off HighlightModel on "0" FramesToBeSkipped "3" AnimationDelay off RecordAVI on CompressAVI AutoFitVis "off" EnableSelection on LastVizWinPosition "[-1 -1 -1 -1]" "[0 0 0]" CamPosition "[0 0 -1]" CamTarget "[0 1 0]" CamUpVector "-1" CamHeight "0" CamViewAngle "[0.9 0.9 0.95]" VisBackgroundColor "[1 0 0]" DefaultBodyColor MDLBodyVisualizationType "Convex hull from body CS

locations"

```
OVRRIDBodyVisualizationType "NONE"
        }
                                "Components"
        PropName
      }
                              "Simscape"
      Name
                              "Full"
      EditingMode
      ExplicitSolverDiagnosticOptions "warning"
      InputDerivativeDiagnosticOptions "warning"
      GlobalZcOffDiagnosticOptions "warning"
      SimscapeLogType "none"
      SimscapeLogName
                      "simlog"
      SimscapeLogDecimation 1
      SimscapeLogLimitData
                             on
      SimscapeLogDataHistory 5000
    }
    PropName
                      "Components"
    }
    Name
                      "Configuration"
                            "Diagnostics"
    CurrentDlgPage
    ConfigPrmDlgPosition
                            [ 400, 132, 1281, 864 ]
  }
                          "ConfigurationSets"
  PropName
}
Simulink.ConfigSet {
  $PropName
                          "ActiveConfigurationSet"
                          3
  $ObjectID
}
BlockDefaults {
                          "black"
  ForegroundColor
                          "white"
  BackgroundColor
  DropShadow
                          off
  NamePlacement
                    "normal"
                          "Helvetica"
  FontName
  FontSize
                          10
                          "normal"
  FontWeight
                          "normal"
  FontAngle
  ShowName
                          on
  BlockRotation
                   0
  BlockMirror
                          off
}
AnnotationDefaults {
                          "center"
  HorizontalAlignment
                          "middle"
  VerticalAlignment
                          "black"
  ForegroundColor
  BackgroundColor
                          "white"
                          off
  DropShadow
                          "Helvetica"
  FontName
  FontSize
                         10
                          "normal"
  FontWeight
                          "normal"
  FontAngle
  UseDisplayTextAsClickCallback off
LineDefaults {
 FontName
                          "Helvetica"
  FontSize
                          9
                          "normal"
  FontWeight
                          "normal"
  FontAngle
```

```
}
BlockParameterDefaults {
  Block {
                          ActionPort
   BlockType
                         "held"
"Only when execution is resumed"
   InitializeStates
PropagateVarSize
    ActionType "unset"
  }
  Block {
    BlockType
                            BusCreator
    Inputs
                            "4"
    DisplayOption
                            "none"
                           "Inherit: auto"
    OutDataTypeStr
    NonVirtualBus
                            off
  }
  Block {
    BlockType
                            Constant
                      "1"
    Value
    VectorParams1D
                            on
                            "Sample based"
    SamplingMode
    OutMin
                            "[]"
                            "[]"
    OutMax
                            "Inherit: Inherit from 'Constant value'"
    OutDataTypeStr
    LockScale
                            off
                      "inf"
    SampleTime
                      "inf"
    FramePeriod
    PreserveConstantTs
                            off
  }
  Block {
                            Demux
    BlockType
                            "4"
    Outputs
                            "none"
    DisplayOption
    BusSelectionMode
                          off
  }
  Block {
                           Fcn
    BlockType
                     "sin(u[1])"
    Expr
                     "-1"
    SampleTime
  }
  Block {
    BlockType
                            FromWorkspace
    VariableName
                            "simulink input"
                      "-1"
    SampleTime
    Interpolate
                      on
    ZeroCross
                            off
    OutputAfterFinalValue "Extrapolation"
  }
  Block {
    BlockType
                            If
                            "1"
    NumInputs
                            "u1 > 0"
    IfExpression
    ShowElse
                            on
    ZeroCross
                            on
                      "-1"
    SampleTime
  }
  Block {
    BlockType
                            Inport
```

```
"1"
  Port
  OutputFunctionCall
                          off
                          "[]"
  OutMin
                          "[]"
  OutMax
                          "Inherit: auto"
  OutDataTypeStr
  LockScale
                          off
  BusOutputAsStruct
                         off
                          "-1"
  PortDimensions
                    "Inherit"
  VarSizeSiq
                    "-1"
  SampleTime
  SignalType
                    "auto"
  SamplingMode
                         "auto"
  LatchByDelayingOutsideSignal off
  LatchInputForFeedbackSignals off
  Interpolate
                    on
}
Block {
  BlockType
                          Integrator
                          "none"
  ExternalReset
  InitialConditionSource "internal"
                          "0"
  InitialCondition
  LimitOutput
                   off
                          "inf"
  UpperSaturationLimit
  LowerSaturationLimit
                          "-inf"
  ShowSaturationPort
                          off
                          off
  ShowStatePort
                          "auto"
  AbsoluteTolerance
  IgnoreLimit
                   off
  ZeroCross
                          on
                                ....
  ContinuousStateAttributes
}
Block {
  BlockType
                          Merge
                          "2"
  Inputs
                          "[]"
  InitialOutput
  AllowUnequalInputPortWidths off
  InputPortOffsets
                         "[]"
}
Block {
  BlockType
                          Outport
                    "1"
  Port
                          "[]"
  OutMin
                          "[]"
  OutMax
                          "Inherit: auto"
  OutDataTypeStr
  LockScale
                          off
                          off
  BusOutputAsStruct
                          "-1"
  PortDimensions
                    "Inherit"
  VarSizeSig
                    "-1"
  SampleTime
                    "auto"
  SignalType
                         "auto"
  SamplingMode
  SourceOfInitialOutputValue "Dialog"
                         "held"
  OutputWhenDisabled
  InitialOutput
                          "[]"
}
Block {
  BlockType
                          Product
```

```
"2"
  Inputs
                         "Element-wise(.*)"
 Multiplication
                         "All dimensions"
  CollapseMode
                   "1"
  CollapseDim
  InputSameDT
                   on
                         "[]"
 OutMin
  OutMax
                         "[]"
                         "Inherit: Same as first input"
  OutDataTypeStr
  LockScale
                         off
  RndMeth
                         "Zero"
  SaturateOnIntegerOverflow
                           on
  SampleTime "-1"
}
Block {
 BlockType
                         Scope
 ModelBased
                   off
  TickLabels
                   "OneTimeTick"
  ZoomMode
                         "on"
                   "on"
 Grid
                         "auto"
 TimeRange
                   "-5"
 YMin
                   "5"
 YMax
  SaveToWorkspace
                         off
  SaveName
                         "ScopeData"
 LimitDataPoints
                         on
                         "5000"
 MaxDataPoints
                   "1"
 Decimation
  SampleInput
                   off
                  "-1"
  SampleTime
}
Block {
 BlockType
                         SubSystem
  ShowPortLabels
                         "FromPortIcon"
                  "ReadWrite"
  Permissions
  PermitHierarchicalResolution "All"
  TreatAsAtomicUnit
                        off
  CheckFcnCallInpInsideContextMsg off
                        "-1"
  SystemSampleTime
                        "Auto"
 RTWFcnNameOpts
                        "Auto"
 RTWFileNameOpts
 RTWMemSecFuncInitTerm "Inherit from model"
 RTWMemSecFuncExecute "Inherit from model"
 RTWMemSecDataConstants "Inherit from model"
 RTWMemSecDataInternal "Inherit from model"
 RTWMemSecDataParameters "Inherit from model"
  SimViewingDevice off
                         "UseLocalSettings"
  DataTypeOverride
  DataTypeOverrideAppliesTo "AllNumericTypes"
 MinMaxOverflowLogging "UseLocalSettings"
 Variant
                         off
  GeneratePreprocessorConditionals off
}
Block {
 BlockType
                         Sum
  IconShape
                         "rectangular"
                         "++"
  Inputs
                         "All dimensions"
  CollapseMode
```

```
"1"
    CollapseDim
    InputSameDT
                      on
                             "Inherit: Inherit via internal rule"
    AccumDataTypeStr
    OutMin
                             "[]"
                             "[]"
    OutMax
    OutDataTypeStr
                             "Inherit: Same as first input"
    LockScale
                             off
    RndMeth
                             "Floor"
    SaturateOnIntegerOverflow
                                   on
    SampleTime
                     "-1"
  }
 Block {
    BlockType
                             UnaryMinus
                      "-1"
    SampleTime
    SaturateOnIntegerOverflow
                                   off
  }
}
System {
                    "MyModel"
 Name
                           [2124, 319, 3456, 1049]
  Location
  Open
                    on
 ModelBrowserVisibility on
 ModelBrowserWidth
                           200
  ScreenColor
                          "white"
  PaperOrientation
                          "landscape"
                          "auto"
  PaperPositionMode
                          "usletter"
  PaperType
                           "inches"
  PaperUnits
                           [0.500000, 0.500000, 0.500000, 0.500000]
  TiledPaperMargins
  TiledPageScale
                          1
  ShowPageBoundaries
                          off
                          "100"
  ZoomFactor
  ReportName
                          "simulink-default.rpt"
                          "1093"
  SIDHighWatermark
  Block {
    BlockType
                             Scope
                       "Action Potential"
    Name
                      "70"
    SID
    Ports
                      [1]
    Position
                             [340, 44, 370, 76]
    Floating
                             off
                             [2180, 588, 3112, 921]
    Location
    Open
                      off
                             "1"
    NumInputPorts
    List {
    ListType
                      AxesTitles
    axes1
                      "%<SignalLabel>"
    }
                             "150"
    TimeRange
                       "-5e+007"
    YMin
                      "7e+008"
    YMax
    SaveName
                             "ScopeData1"
                      "StructureWithTime"
    DataFormat
                      "0"
    SampleTime
  }
 Block {
    BlockType
                             Sum
```

```
"Add"
  Name
                    "75"
  SID
                    [4, 1]
  Ports
                          [230, 352, 260, 398]
  Position
  BlockMirror
                    on
  ShowName
                          off
                          "---+"
  Inputs
  InputSameDT
                    off
                          "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                          Sum
  Name
                    "Add1"
                    "1065"
  SID
  Ports
                    [2, 1]
  Position
                           [260, 43, 290, 72]
  NamePlacement
                          "alternate"
                          off
  ShowName
  InputSameDT
                    off
  OutDataTypeStr
                          "Inherit: Inherit via internal rule"
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                          BusCreator
                    "Bus\nCreator"
  Name
                    "1078"
  SID
  Ports
                    [4, 1]
  Position
                          [390, 546, 395, 584]
                          off
  ShowName
  DisplayOption
                          "bar"
}
Block {
  BlockType
                          Constant
                    "Constant"
  Name
  SID
                    "1066"
                           [110, 39, 205, 61]
  Position
  BackgroundColor
                          "[0.901961, 0.901961, 0.901961]"
  ShowName
                          off
                    "V resting"
  Value
}
Block {
  BlockType
                          Constant
                    "Constant Stimulation"
  Name
  SID
                    "1091"
  Position
                          [865, 375, 945, 405]
  BlockMirror
                    on
                    "3"
  Value
}
Block {
  BlockType
                          Scope
                    "Currents"
  Name
  SID
                    "1077"
  Ports
                    [1]
  Position
                          [530, 548, 560, 582]
  Floating
                          off
                          [610, 157, 1274, 736]
  Location
```

off Open "1" NumInputPorts List { AxesTitles ListType "%<SignalLabel>" axes1 } "10" TimeRange "-1000" YMin "1000" YMax SaveName "ScopeData3" DataFormat "StructureWithTime" "0" SampleTime } Block { BlockType Scope Name "Gating Variables" SID "1071" Ports [3] [520, 313, 550, 347] Position Floating off [1314, 467, 1780, 1064] Location Open off "3" NumInputPorts TickLabels "on" ZoomMode "yonly" List { AxesTitles ListType "%<SignalLabel>" axes1 "%<SignalLabel>" axes2 "%<SignalLabel>" axes3 } "-5~-5~-5" YMin "5~5~5" YMax "StructureWithTime" DataFormat "0" SampleTime } Block { BlockType SubSystem "KV" Name "48" SID Ports [1, 2] [459, 180, 501, 280] Position BlockRotation 270 BlockMirror on NamePlacement "alternate" off MinAlgLoopOccurrences PropExecContextOutsideSubsystem off RTWSystemCode "Auto" FunctionWithSeparateData off Opaque off RequestExecContextInheritance off MaskHideContents off Port { PortNumber 1 ShowPropagatedSignals "on" RTWStorageClass "Auto" "SignalName" DataLoggingNameMode

} System { "KV" Name [278, 98, 1342, 850] Location Open off ModelBrowserVisibility on ModelBrowserWidth 200 "white" ScreenColor PaperOrientation "landscape" PaperPositionMode "auto" PaperType "usletter" PaperUnits "inches" TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000] TiledPageScale 1 ShowPageBoundaries off "100" ZoomFactor Block { BlockType Inport "77" Name "49" SID [65, 188, 95, 202] Position "Port number" IconDisplay } Block { BlockType Fcn "1 - n" Name "182" SID Position [450, 49, 490, 81] "1-u" Expr } Block { BlockType Constant "E K" Name "68" SID [65, 305, 95, 335] Position "[0.901961, 0.901961, 0.901961]" BackgroundColor "E K" Value } Block { BlockType Integrator Name "Integrator" "167" SID Ports [2, 1] [765, 187, 795, 218] Position InitialConditionSource "external" } Block { Product BlockType "Product" Name "977" SID Ports [2, 1] [715, 176, 730, 209] Position ShowName off InputSameDT off OutDataTypeStr "Inherit: Inherit via internal rule" SaturateOnIntegerOverflow off }

```
Block {
       BlockType
                         Product
       Name
                               "Product1"
                         "76"
       SID
       Ports
                               [3, 1]
                         [910, 357, 930, 393]
       Position
       ShowName
                         off
                         "3"
       Inputs
       InputSameDT
                               off
       OutDataTypeStr
                        "Inherit: Inherit via internal rule"
       SaturateOnIntegerOverflow off
      }
     Block {
       BlockType
                         SubSystem
       Name
                               "Temperature Subsystem"
                         "963"
       SID
       Ports
                               [0, 1]
       Position
                         [65, 491, 145, 519]
                         "[0.803922, 0.929412, 0.996078]"
       BackgroundColor
       MinAlgLoopOccurrences off
       PropExecContextOutsideSubsystem off
                              "Auto"
       RTWSystemCode
       FunctionWithSeparateData off
                         off
       Opaque
       RequestExecContextInheritance
                                         off
       MaskHideContents off
       System {
                           "Temperature Subsystem"
         Name
                                 [2375, 212, 3422, 1027]
         Location
         Open
                           off
         ModelBrowserVisibility on
         ModelBrowserWidth
                                 200
                                 "white"
         ScreenColor
                                 "landscape"
         PaperOrientation
                                 "auto"
         PaperPositionMode
                                 "usletter"
         PaperType
                                 "inches"
         PaperUnits
                                 [0.500000, 0.500000, 0.500000,
         TiledPaperMargins
0.5000001
         TiledPageScale
                                 1
         ShowPageBoundaries
                                 off
                                 "100"
         ZoomFactor
         Block {
           BlockType
                                   Constant
           Name
                             "Constant"
           SID
                             "964"
           Position
                                   [80, 200, 175, 230]
           ShowName
                                   off
                             "Temperature_Bit"
           Value
         }
         Block {
           BlockType
                                   Ιf
                             "Tf"
           Name
                             "965"
           SID
           Ports
                             [1, 2]
           Position
                                   [265, 196, 365, 234]
                                   "u1 == 1"
           IfExpression
```
} Block { BlockType SubSystem Name "If Action\nSubsystem" "966" SID Ports [0, 1, 0, 0, 0, 0, 0, 1]Position [465, 242, 535, 278] ShowName off TreatAsAtomicUnit on MinAlqLoopOccurrences off PropExecContextOutsideSubsystem off RTWSystemCode "Auto" FunctionWithSeparateData off Opaque off RequestExecContextInheritance off MaskHideContents off System { Name "If Action\nSubsystem" [648, 110, 1575, 870] Location Open off ModelBrowserVisibility on ModelBrowserWidth 200 ScreenColor "white" PaperOrientation "landscape" PaperPositionMode "auto" "usletter" PaperType "inches" PaperUnits TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000] TiledPageScale 1 ShowPageBoundaries off "100" ZoomFactor Block { BlockType ActionPort Name "Action Port" "967" SID [225, 15, 284, 43] Position "else" ActionType } Block { BlockType Constant Name "Constant" "968" SID [170, 70, 200, 100] Position ShowName off } Block { Outport BlockType Name "Out1" "969" SID [325, 78, 355, 92] Position "Port number" IconDisplay } Line { "Constant" SrcBlock SrcPort 1 "Out1" DstBlock DstPort 1

```
}
  }
}
Block {
  BlockType
                           SubSystem
                    "If Action\nSubsystem1"
  Name
                    "970"
  SID
  Ports
                     [0, 1, 0, 0, 0, 0, 0, 1]
  Position
                           [465, 167, 535, 203]
  ShowName
                           off
  TreatAsAtomicUnit
                           on
  MinAlgLoopOccurrences
                           off
  PropExecContextOutsideSubsystem off
  RTWSystemCode
                           "Auto"
  FunctionWithSeparateData off
  Opaque
                           off
  RequestExecContextInheritance off
  MaskHideContents
                           off
  System {
                    "If Action\nSubsystem1"
  Name
                    [695, 634, 1622, 1394]
  Location
                    off
  Open
  ModelBrowserVisibility on
  ModelBrowserWidth 200
  ScreenColor
                    "white"
  PaperOrientation "landscape"
  PaperPositionMode "auto"
  PaperType
                    "usletter"
                    "inches"
  PaperUnits
  TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000]
  TiledPageScale
                           1
  ShowPageBoundaries
                          off
                    "100"
  ZoomFactor
  Block {
    BlockType
                       ActionPort
                           "Action Port"
    Name
                       "971"
    SID
                       [345, 15, 404, 43]
    Position
                             "then"
    ActionType
  }
  Block {
                       Constant
    BlockType
                             "Constant"
    Name
                       "972"
    SID
    Position
                       [25, 70, 105, 100]
    ShowName
                       off
    Value
                             "Temperature"
  }
  Block {
    BlockType
                       Fcn
                             "Fcn"
    Name
                       "973"
    SID
                       [320, 68, 435, 102]
    Position
    ShowName
                       off
                             "3^{(u-6.3)/10}"
    Expr
  }
  Block {
```

BlockType Outport "Out1" Name "974" SID [715, 78, 745, 92] Position "Port number" IconDisplay } Line { "Constant" SrcBlock SrcPort 1 DstBlock "Fcn" DstPort 1 } Line { SrcBlock "Fcn" SrcPort 1 "Out1" DstBlock DstPort 1 } Annotation { "The effect of the temperature is Name taken care in the model so that the right-hand sides of the Equations f" "or n, m and h are multiplied by the factor $n^3 ^ (T -$ 6.3)/10)" [376, 179] Position } } } Block { BlockType Merge Name "Merge" "975" SID Ports [2, 1] Position [585, 195, 625, 235] } Block { BlockType Scope "Scope" Name "1055" SID Ports [1] [795, 294, 825, 326] Position Floating off [188, 390, 512, 629] Location Open off "1" NumInputPorts List { ListType AxesTitles axes1 "%<SignalLabel>" } "ScopeData6" SaveName "StructureWithTime" DataFormat "0" SampleTime } Block { BlockType Outport "Out1" Name SID "976"

```
Position [770, 2
IconDisplay "Port number"
                    [770, 208, 800, 222]
 }
 Line {
   SrcBlock
                         "Merge"
   SrcPort
                         1
   Points
                         [75, 0]
   Branch {
                  "Out1"
   DstBlock
   DstPort
                     1
   }
   Branch {
                     [0, 95]
   Points
                  "Scope"
   DstBlock
   DstPort
                       1
   }
 }
 Line {
   SrcBlock
                        "If Action\nSubsystem"
   SrcPort
                        1
   Points
                         [15, 0; 0, -35]
   DstBlock
                        "Merge"
   DstPort
                         2
 }
 Line {
                         "If Action\nSubsystem1"
   SrcBlock
   SrcPort
                        1
   Points
                         [15, 0; 0, 20]
                        "Merge"
   DstBlock
                         1
   DstPort
 }
 Line {
                         "If"
   SrcBlock
   SrcPort
                        1
   Points
                        [85, 0; 0, -53]
                        "If Action\nSubsystem1"
   DstBlock
   DstPort
                        ifaction
 }
 Line {
                         "If"
   SrcBlock
                        2
   SrcPort
   Points
                         [130, 0]
                       [130, 0]
"If Action\nSubsystem"
   DstBlock
   DstPort
                        ifaction
 }
 Line {
                        "Constant"
   SrcBlock
   SrcPort
                        1
                         "If"
   DstBlock
                         1
   DstPort
 }
 Annotation {
                  "Analysis of the Effect of temperature"
  Name
   Position
                     [418, 38]
 }
}
```

}

```
Block {
  BlockType
                     Sum
                           "V - V K"
  Name
                     "66"
  SID
  Ports
                           [2, 1]
  Position
                     [205, 296, 220, 329]
  Inputs
                     "+-"
  InputSameDT
                           off
                     "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                     Product
  Name
                           "alpha (1 - n)"
                     "164"
  SID
  Ports
                           [2, 1]
  Position
                     [520, 97, 550, 128]
  InputSameDT
                           off
                     "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                     Sum
  Name
                           "alpha(1 - n) - beta * n"
                     "166"
  STD
  Ports
                           [2, 1]
  Position
                     [615, 167, 630, 198]
                     "+-"
  Inputs
                           off
  InputSameDT
                     "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                     Fcn
  Name
                           "alpha n"
                     "82"
  SID
                     [205, 105, 265, 135]
  Position
                           "(0.1-(0.01*u))/(exp(1-(0.1*u))-1)"
 Expr
}
Block {
                     Product
  BlockType
                           "beta * n"
  Name
                     "165"
  SID
  Ports
                           [2, 1]
                     [455, 172, 485, 203]
  Position
  InputSameDT
                           off
                     "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                     Fcn
                           "beta_n"
  Name
                     "8.3"
  SID
  Position
                     [205, 180, 265, 210]
  Expr
                           "0.125/(exp(0.0125*u))"
}
Block {
```

```
BlockType
                    Constant
                          "g K"
  Name
                    "69"
  SID
                    [65, 370, 95, 400]
  Position
                    "[0.901961, 0.901961, 0.901961]"
  BackgroundColor
                         "G K"
  Value
}
Block {
  BlockType
                    Constant
  Name
                    "n initial"
                    "1079"
  SID
                    [615, 304, 685, 326]
  Position
  BackgroundColor
                    "[0.901961, 0.901961, 0.901961]"
  ShowName
                    off
  Value
                          "n initial"
}
Block {
  BlockType
                    Fcn
                          "n^4"
  Name
                    "183"
  SID
                    [840, 315, 885, 345]
  Position
                          "u^4"
  Expr
}
Block {
                    Outport
  BlockType
                          "I Potassium"
  Name
                    "50"
  SID
                    [970, 368, 1000, 382]
  Position
                          "Port number"
  IconDisplay
}
Block {
                    Outport
  BlockType
  Name
                          "n out"
                    "1070"
  SID
                    [970, 273, 1000, 287]
  Position
                          "2"
  Port
                         "Port number"
  IconDisplay
}
Line {
 Labels
                   [0, 0]
                    "V"
  SrcBlock
  SrcPort
                    1
                    [75, 0]
  Points
  Branch {
   Points
                      [0, 110]
                            "V - V K"
   DstBlock
   DstPort
                      1
  }
  Branch {
                            "beta n"
   DstBlock
                      1
   DstPort
  }
  Branch {
   Points
                     [0, -75]
   DstBlock
                           "alpha n"
   DstPort
                      1
  }
```

} Line { "E K" SrcBlock SrcPort 1 "V - V K" DstBlock DstPort 2 } Line { "Product1" SrcBlock SrcPort 1 "I\_Potassium" DstBlock DstPort 1 } Line { SrcBlock "alpha n" SrcPort 1 DstBlock "alpha (1 - n)" DstPort 2 } Line { "beta\_n" SrcBlock 1 SrcPort "beta \* n" DstBlock DstPort 2 } Line { "alpha (1 - n)" SrcBlock SrcPort 1 [35, 0; 0, 60] Points "alpha(1 - n) - beta \* n" DstBlock DstPort 1 } Line { "beta \* n" SrcBlock SrcPort 1 "alpha(1 - n) - beta \* n" DstBlock 2 DstPort } Line { "1 - n" SrcBlock SrcPort 1 [5, 0; 0, 40] Points "alpha (1 - n)" DstBlock DstPort 1 } Line { "n^4" SrcBlock 1 SrcPort [0, 35] Points "Product1" DstBlock DstPort 1 } Line { "V - V K" SrcBlock SrcPort 1 Points [335, 0; 0, 60] "Product1" DstBlock

```
DstPort
                  2
}
Line {
 SrcBlock
                 "g K"
 SrcPort
                 1
                 "Product1"
 DstBlock
DstPort
                 3
}
Line {
 SrcBlock
                 "Temperature Subsystem"
 SrcPort
                 1
                 [550, 0]
 Points
                 "Product"
 DstBlock
 DstPort
                  2
}
Line {
 SrcBlock
                 "Integrator"
 SrcPort
                 1
 Points
                 [25, 0; 0, 60]
 Branch {
                   [-420, 0; 0, -85]
   Points
   Branch {
                           "beta * n"
    DstBlock
    DstPort
                           1
   }
   Branch {
                          [0, -115]
    Points
                          "1 - n"
     DstBlock
    DstPort
                           1
   }
 }
 Branch {
  Points
                  [0, 15]
   Branch {
    DstBlock
                           "n^4"
    DstPort
                           1
   }
   Branch {
                           "n out"
    DstBlock
                           1
     DstPort
   }
 }
}
Line {
 SrcBlock
                 "Product"
 SrcPort
                  1
                 "Integrator"
 DstBlock
DstPort
                 1
}
Line {
                 "alpha(1 - n) - beta * n"
 SrcBlock
 SrcPort
                 1
                 "Product"
 DstBlock
 DstPort
                  1
}
Line {
 SrcBlock "n initial"
```

```
SrcPort
                     1
                      [60, 0]
    Points
                     "Integrator"
    DstBlock
    DstPort
                      2
  }
  }
}
Block {
  BlockType
                          SubSystem
  Name
                    "Leak"
  SID
                    "51"
  Ports
                    [1, 1]
  Position
                          [599, 180, 641, 280]
  BlockRotation
                          270
  BlockMirror
                    on
  NamePlacement
                          "alternate"
  MinAlgLoopOccurrences
                          off
  PropExecContextOutsideSubsystem off
                          "Auto"
  RTWSystemCode
  FunctionWithSeparateData off
  Opaque
                          off
  RequestExecContextInheritance off
  MaskHideContents
                        off
  Port {
  PortNumber
                   1
  ShowPropagatedSignals "on"
                         "Auto"
  RTWStorageClass
                       "SignalName"
  DataLoggingNameMode
  }
  System {
                    "Leak"
  Name
  Location
                    [546, 277, 1593, 1092]
  Open
                    off
  ModelBrowserVisibility on
  ModelBrowserWidth 200
                   "white"
  ScreenColor
  PaperOrientation "landscape"
  PaperPositionMode "auto"
                    "usletter"
  PaperType
                    "inches"
  PaperUnits
  TiledPaperMargins [0.500000, 0.500000, 0.500000]
  TiledPageScale
                         1
  ShowPageBoundaries
                         off
                   "100"
  ZoomFactor
  Block {
    BlockType
                      Inport
                            "77"
    Name
                      "52"
    SID
                      [75, 123, 105, 137]
    Position
                           "Port number"
    IconDisplay
  }
  Block {
    BlockType
                      Product
    Name
                            "(V - V leak) g leak"
    SID
                      "63"
    Ports
                           [2, 1]
                      [375, 231, 390, 249]
    Position
```

```
off
  InputSameDT
 OutDataTypeStr "Inherit: Inherit via internal rule"
  SaturateOnIntegerOverflow off
}
Block {
 BlockType
                   Sum
 Name
                         "V - V leak"
                   "61"
  STD
 Ports
                         [2, 1]
  Position
                   [230, 160, 240, 180]
 Inputs
                   "+-"
 InputSameDT
                         off
  OutDataTypeStr "Inherit: Inherit via internal rule"
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                   Constant
  Name
                         "V leak"
                   "60"
 SID
                   [65, 215, 115, 245]
  Position
  BackgroundColor "[0.901961, 0.901961, 0.901961]"
                         "E leak"
 Value
}
Block {
  BlockType
                   Constant
                    "g leak"
 Name
                   "62"
  SID
  Position
                   [65, 320, 120, 350]
                   "[0.901961, 0.901961, 0.901961]"
  BackgroundColor
                         "G leak"
  Value
}
Block {
  BlockType
                   Outport
  Name
                         "I Leak "
                   "53"
  SID
                   [505, 233, 535, 247]
  Position
                         "Port number"
  IconDisplay
}
Line {
                   "V leak"
 SrcBlock
  SrcPort
                   1
  Points
                   [50, 0; 0, -55]
                   "V - V leak"
 DstBlock
                   2
  DstPort
}
Line {
                   "77"
 SrcBlock
                   1
  SrcPort
                   [60, 0; 0, 35]
  Points
                   "V - V leak"
 DstBlock
 DstPort
                   1
}
Line {
                   "V - V leak"
 SrcBlock
  SrcPort
                   1
 Points
                   [65, 0; 0, 65]
                   "(V - V leak) g leak"
  DstBlock
```

```
DstPort
                 1
 }
 Line {
                     "g leak"
   SrcBlock
   SrcPort
                     1
   Points
                     [190, 0; 0, -90]
   DstBlock
                     "(V - V leak) g leak"
   DstPort
                     2
  }
 Line {
                     "(V - V leak) g leak"
   SrcBlock
    SrcPort
                     1
                     "I Leak "
   DstBlock
   DstPort
                     1
  }
  }
}
Block {
 BlockType
                         SubSystem
                   "Membrane"
 Name
                   "54"
 SID
                   [1, 1]
 Ports
                         [139, 180, 181, 280]
 Position
 BlockRotation
                         270
                         "[1.000000, 1.000000, 0.501961]"
 BackgroundColor
 MinAlgLoopOccurrences
                         off
  PropExecContextOutsideSubsystem off
 RTWSystemCode
                         "Auto"
 FunctionWithSeparateData off
 Opaque
                         off
 RequestExecContextInheritance off
 MaskHideContents off
  System {
 Name
                   "Membrane"
 Location
                   [-30, 69, 1221, 874]
                   off
 Open
 ModelBrowserVisibility on
 ModelBrowserWidth 200
 ScreenColor
                   "white"
 PaperOrientation "landscape"
  PaperPositionMode "auto"
                   "usletter"
  PaperType
                   "inches"
  PaperUnits
  TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000]
  TiledPageScale
                        1
  ShowPageBoundaries
                        off
  ZoomFactor "100"
  Block {
   BlockType
                     Inport
                            " T "
   Name
                     "55"
    SID
                     [150, 103, 180, 117]
    Position
   IconDisplay
                           "Port number"
  }
 Block {
    BlockType
                     Constant
   Name
                            "Cm"
```

```
"71"
  SID
                    [150, 205, 180, 235]
  Position
                    "[0.901961, 0.901961, 0.901961]"
  BackgroundColor
  Value
                           "Cm"
}
Block {
  BlockType
                    Product
  Name
                           "Divide"
                    "73"
  SID
  Ports
                           [2, 1]
  Position
                    [310, 153, 320, 177]
                    "*/"
  Inputs
  InputSameDT
                          off
  OutDataTypeStr
                    "Inherit: Inherit via internal rule"
                    "Floor"
  RndMeth
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                    Integrator
  Name
                           "Integrator"
                    "74"
  SID
  Ports
                          [2, 1]
                    [460, 155, 490, 190]
  Position
  InitialConditionSource "external"
}
Block {
  BlockType
                    Constant
                           "V1"
  Name
                    "125"
  SID
                     [85, 295, 180, 325]
  Position
                    "[0.901961, 0.901961, 0.901961]"
  BackgroundColor
  ShowName
                    off
                           "V initial"
  Value
}
Block {
  BlockType
                    Outport
                           "V"
  Name
                    "56"
  SID
                    [650, 168, 680, 182]
  Position
                          "Port number"
  IconDisplay
}
Line {
                    " T "
  SrcBlock
  SrcPort
                    1
  Points
                    [55, 0; 0, 50]
  DstBlock
                    "Divide"
  DstPort
                    1
}
Line {
                    "Cm"
  SrcBlock
  SrcPort
                    1
                    [55, 0; 0, -50]
  Points
                    "Divide"
  DstBlock
  DstPort
                    2
}
Line {
                    "V1"
  SrcBlock
```

```
SrcPort
                   1
                    [260, 0]
   Points
                   "Integrator"
   DstBlock
   DstPort
                    2
  }
 Line {
   SrcBlock
                    "Integrator"
   SrcPort
                    1
                    "V"
   DstBlock
   DstPort
                    1
  }
 Line {
                    "Divide"
   SrcBlock
   SrcPort
                    1
   DstBlock
                    "Integrator"
   DstPort
                    1
  }
 Annotation {
                          "Membrane"
  Name
                   [302, 20]
   Position
  }
 Annotation {
                          "Anode break analysis"
   Name
   Position
                   [130, 342]
  }
  }
Block {
 BlockType
                        SubSystem
                  "NaV"
 Name
 SID
                  "45"
 Ports
                  [1, 3]
                        [304, 180, 346, 280]
 Position
 BlockRotation
                        270
 BlockMirror
                 on
                        "alternate"
 NamePlacement
 MinAlqLoopOccurrences off
 PropExecContextOutsideSubsystem off
                       "Auto"
 RTWSystemCode
 FunctionWithSeparateData off
 Opaque
                        off
 RequestExecContextInheritance off
 MaskHideContents off
 Port {
  PortNumber 1
  ShowPropagatedSignals
                        "on"
 RTWStorageClass
                       "Auto"
  DataLoggingNameMode
                      "SignalName"
  }
  System {
                   "NaV"
 Name
                  [278, 98, 1325, 833]
 Location
 Open
                  off
 ModelBrowserVisibility on
 ModelBrowserWidth 200
 ScreenColor "white"
  PaperOrientation "landscape"
```

}

```
PaperPositionMode "auto"
PaperType "usletter"
                "inches"
PaperUnits
TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000]
TiledPageScale 1
ShowPageBoundaries off
             "100"
ZoomFactor
Block {
 BlockType
                    Inport
                          "V"
  Name
  SID
                    "46"
  Position
                    [100, 458, 130, 472]
                         "Port number"
  IconDisplay
}
Block {
  BlockType
                    Fcn
                          "1 - h"
  Name
  SID
                    "181"
                    [480, 270, 525, 300]
  Position
                          "1-u"
  Expr
}
Block {
 BlockType
                   Fcn
                          "1-m"
 Name
                    "180"
  STD
                    [485, 61, 525, 89]
 Position
                          "1-u"
 Expr
}
Block {
  BlockType
                    Constant
                          "E Na"
  Name
                    "59"
  SID
                   [100, 510, 130, 540]
 Position
  BackgroundColor
                   "[0.901961, 0.901961, 0.901961]"
                          "E Na"
  Value
}
Block {
  BlockType
                    Integrator
                      "Integrator"
  Name
                    "168"
  SID
  Ports
                         [2, 1]
                    [795, 192, 825, 223]
 Position
  InitialConditionSource "external"
}
Block {
  BlockType
                    Integrator
                         "Integrator2"
  Name
                    "169"
  SID
                          [2, 1]
  Ports
                    [805, 402, 835, 433]
  Position
 InitialConditionSource "external"
}
Block {
  BlockType
                   Product
  Name
                          "Product"
                    "961"
  SID
  Ports
                          [2, 1]
```

```
[755, 181, 770, 214]
  Position
  ShowName
                   off
  InputSameDT
                         off
 OutDataTypeStr "Inherit: Inherit via internal rule"
  SaturateOnIntegerOverflow off
}
Block {
 BlockType
                  Product
 Name
                    "Product1"
                   "962"
  SID
 Ports
                        [2, 1]
 Position
                   [770, 391, 785, 429]
 ShowName
                   off
 InputSameDT
                        off
 OutDataTypeStr "Inherit: Inherit via internal rule"
 SaturateOnIntegerOverflow off
}
Block {
 BlockType
                   Product
 Name
                        "Product3"
                   "124"
 SID
 Ports
                        [6, 1]
                   [980, 575, 995, 635]
 Position
 ShowName
                   off
                   "6"
 Inputs
                        off
 InputSameDT
 OutDataTypeStr "Inherit: Inherit via internal rule"
 SaturateOnIntegerOverflow off
}
Block {
                   Product
  BlockType
 Name
                    "Product4"
                   "176"
 SID
 Ports
                        [2, 1]
                   [565, 119, 585, 141]
 Position
 ShowName
                   off
 InputSameDT
                         off
                  "Inherit: Inherit via internal rule"
 OutDataTypeStr
 SaturateOnIntegerOverflow off
}
Block {
 BlockType
                   Product
                    "Product5"
 Name
                   "177"
 SID
 Ports
                         [2, 1]
 Position
                   [565, 179, 585, 206]
 ShowName
                   off
 InputSameDT
                        off
                  "Inherit: Inherit via internal rule"
 OutDataTypeStr
 SaturateOnIntegerOverflow off
}
Block {
 BlockType
                   Product
  Name
                    "Product6"
  SID
                   "178"
 Ports
                        [2, 1]
                   [565, 393, 590, 417]
 Position
```

```
off
  ShowName
  InputSameDT
                           off
                    "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                    Product
  Name
                           "Product7"
                    "179"
  SID
  Ports
                           [2, 1]
  Position
                    [565, 304, 585, 331]
  ShowName
                    off
  InputSameDT
                           off
  OutDataTypeStr
                    "Inherit: Inherit via internal rule"
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                    Sum
                           "Subtract4"
  Name
                    "174"
  SID
  Ports
                           [2, 1]
                    [645, 172, 655, 203]
  Position
  ShowName
                    off
                    "+-"
  Inputs
                          off
  InputSameDT
                    "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                    Sum
                           "Subtract5"
  Name
                     "175"
  SID
  Ports
                           [2, 1]
  Position
                    [645, 380, 660, 415]
  ShowName
                    off
                    "+-"
  Inputs
  InputSameDT
                          off
                    "Inherit: Inherit via internal rule"
  OutDataTypeStr
  SaturateOnIntegerOverflow off
}
Block {
                    SubSystem
  BlockType
                           "Temperature Subsystem"
  Name
                    "946"
  SID
  Ports
                           [0, 1]
  Position
                    [100, 696, 180, 724]
                    "[0.803922, 0.929412, 0.996078]"
  BackgroundColor
  MinAlgLoopOccurrences
                         off
  PropExecContextOutsideSubsystem off
                          "Auto"
  RTWSystemCode
  FunctionWithSeparateData off
  Opaque
                    off
  RequestExecContextInheritance
                                     off
  MaskHideContents
                          off
  System {
    Name
                       "Temperature Subsystem"
    Location
                             [783, 172, 1674, 995]
```

off Open ModelBrowserVisibility on ModelBrowserWidth 200 ScreenColor "white" "landscape" PaperOrientation "auto" PaperPositionMode PaperType "usletter" PaperUnits "inches" [0.500000, 0.500000, 0.500000, TiledPaperMargins 0.5000001 TiledPageScale 1 ShowPageBoundaries off ZoomFactor "100" Block { BlockType Constant "Constant" Name SID "949" [80, 200, 175, 230] Position ShowName off "Temperature Bit" Value } Block { BlockType Ιf "Tf" Name "950" STD Ports [1, 2] Position [265, 196, 365, 234] "u1 == 1" IfExpression } Block { SubSystem BlockType "If Action\nSubsystem" Name "951" SID Ports [0, 1, 0, 0, 0, 0, 0, 1][465, 242, 535, 278] Position ShowName off TreatAsAtomicUnit on MinAlqLoopOccurrences off PropExecContextOutsideSubsystem off RTWSystemCode "Auto" FunctionWithSeparateData off Opaque off RequestExecContextInheritance off MaskHideContents off System { Name "If Action\nSubsystem" Location [648, 110, 1575, 870] Open off ModelBrowserVisibility on ModelBrowserWidth 200 "white" ScreenColor PaperOrientation "landscape" PaperPositionMode "auto" PaperType "usletter" PaperUnits "inches" TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000] TiledPageScale 1

ShowPageBoundaries off "100" ZoomFactor Block { BlockType ActionPort Name "Action Port" "952" SID Position [225, 15, 284, 43] "else" ActionType } Block { BlockType Constant Name "Constant" "953" SID Position [170, 70, 200, 100] ShowName off } Block { BlockType Outport "Out1" Name "954" SID [325, 78, 355, 92] Position "Port number" IconDisplay } Line { "Constant" SrcBlock SrcPort 1 "Out1" DstBlock DstPort 1 } } Block { SubSystem BlockType "If Action\nSubsystem1" Name "955" SID Ports [0, 1, 0, 0, 0, 0, 0, 1]Position [465, 167, 535, 203] off ShowName TreatAsAtomicUnit on MinAlgLoopOccurrences off PropExecContextOutsideSubsystem off RTWSystemCode "Auto" FunctionWithSeparateData off Opaque off RequestExecContextInheritance off MaskHideContents off System { Name "If Action\nSubsystem1" [648, 110, 1575, 870] Location Open off ModelBrowserVisibility on ModelBrowserWidth 200 ScreenColor "white" PaperOrientation "landscape" PaperPositionMode "auto" PaperType "usletter" "inches" PaperUnits

}

```
TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000]
            TiledPageScale
                                    1
            ShowPageBoundaries
                                    off
                               "100"
            ZoomFactor
            Block {
             BlockType
                                ActionPort
              Name
                                       "Action Port"
                                 "956"
              STD
                                 [345, 15, 404, 43]
              Position
              ActionType
                                       "then"
            }
            Block {
              BlockType
                                 Constant
              Name
                                       "Constant"
              SID
                                 "957"
              Position
                                 [25, 70, 105, 100]
              ShowName
                                 off
              Value
                                       "Temperature"
            }
            Block {
              BlockType
                                Fcn
                                       "Fcn"
              Name
                                 "958"
              SID
              Position
                                 [320, 68, 435, 102]
              ShowName
                                 off
                                       "3^{(u-6.3)}/10)"
              Expr
            }
            Block {
              BlockType
                                 Outport
                                       "Out1"
              Name
              SID
                                 "959"
                                 [715, 78, 745, 92]
              Position
                                       "Port number"
              IconDisplay
            }
            Line {
                                "Fcn"
              SrcBlock
              SrcPort
                                1
              DstBlock
                                "Out1"
              DstPort
                                1
            }
            Line {
                                 "Constant"
              SrcBlock
              SrcPort
                                 1
                                "Fcn"
              DstBlock
              DstPort
                                 1
            }
            Annotation {
                                       "The effect of the temperature is
             Name
taken care in the model so that the right-hand sides of the Equations
f"
              "or n, m and h are multiplied by the factor\n\n3 ^ ((T -
6.3)/10)"
              Position
                               [376, 179]
            }
            }
          }
          Block {
```

BlockType Merge "Merge" Name "960" SID [2, 1] Ports [585, 195, 625, 235] Position } Block { BlockType Outport "Out1" Name "948" SID Position [770, 208, 800, 222] "Port number" IconDisplay } Line { "Constant" SrcBlock SrcPort 1 "If" DstBlock DstPort 1 } Line { "If" SrcBlock SrcPort 2 [130, 0] Points DstBlock "If Action\nSubsystem" DstPort ifaction } Line { "If" SrcBlock SrcPort 1 [85, 0; 0, -53] "If Action\nSubsystem1" Points DstBlock DstPort ifaction } Line { "If Action\nSubsystem1" SrcBlock SrcPort 1 [15, 0; 0, 20] Points DstBlock "Merge" DstPort 1 } Line { "If Action\nSubsystem" SrcBlock SrcPort 1 [15, 0; 0, -35] "Merge" Points DstBlock DstPort 2 } Line { "Merge" SrcBlock 1 SrcPort "Out1" DstBlock DstPort 1 } Annotation { Name "Analysis of the Effect of temperature" Position [418, 38] }

```
}
}
Block {
  BlockType
                     Sum
                           "V - V Na"
 Name
                     "65"
 SID
  Ports
                           [2, 1]
                     [260, 510, 275, 530]
  Position
                     "+-"
  Inputs
  InputSameDT
                           off
  OutDataTypeStr
                     "Inherit: Inherit via internal rule"
  SaturateOnIntegerOverflow off
}
Block {
  BlockType
                     Fcn
                           "alpha h"
  Name
                     "94"
  SID
  Position
                     [260, 310, 295, 340]
                           "0.07/(exp(0.05*u))"
  Expr
}
Block {
  BlockType
                     Fcn
                           "alpha m"
  Name
                     "93"
  SID
                     [260, 119, 295, 151]
  Position
                           "(2.5-(0.1*u))/(exp(2.5-(0.1*u))-1)"
  Expr
}
Block {
                     Fcn
  BlockType
                           "beta_h"
  Name
                     "95"
  SID
                     [260, 395, 295, 425]
  Position
                           "1/(exp(3-(0.1*u))+1)"
  Expr
}
Block {
  BlockType
                     Fcn
                           "beta m"
  Name
                     "96"
  SID
                     [260, 184, 295, 216]
  Position
                           "4/(exp(u/18))"
  Expr
}
Block {
  BlockType
                     Constant
  Name
                           "q Na"
  SID
                     "58"
  Position
                     [100, 615, 130, 645]
                     "[0.901961, 0.901961, 0.901961]"
  BackgroundColor
  Value
                           "G Na"
}
Block {
  BlockType
                     Constant
                           "h initial"
  Name
                     "1081"
  SID
  Position
                     [635, 504, 700, 526]
  BackgroundColor
                     "[0.901961, 0.901961, 0.901961]"
  ShowName
                     off
  Value
                           "h initial"
```

```
}
Block {
 BlockType
                   Constant
 Name
                         "m initial"
                   "1080"
 SID
 Position
                   [625, 268, 700, 292]
 BackgroundColor
                   "[0.901961, 0.901961, 0.901961]"
 ShowName
                   off
                         "m initial"
 Value
}
Block {
 BlockType
                   Outport
 Name
                         "I_Sodium"
 SID
                   "47"
 Position
                   [1045, 598, 1075, 612]
                         "Port number"
 IconDisplay
}
Block {
 BlockType
                   Outport
                    "h_out"
 Name
                   "1067"
 SID
                   [1045, 458, 1075, 472]
 Position
                         "2"
 Port
 IconDisplay
                         "Port number"
}
Block {
 BlockType
                   Outport
                         "m_out"
 Name
                   "1068"
 SID
                   [1045, 398, 1075, 412]
 Position
                         "3"
 Port
 IconDisplay
                         "Port number"
}
Line {
                   "V"
 SrcBlock
 SrcPort
                  1
                   [25, 0]
 Points
 Branch {
   Points
                    [30, 0; 0, 50]
                          "V - V Na"
   DstBlock
  DstPort
                     1
 }
 Branch {
                     [0, -55; 75, 0]
   Points
   Branch {
    DstBlock
                             "beta h"
     DstPort
                             1
   }
   Branch {
                            [0, -85]
     Points
     Branch {
     DstBlock
                      "alpha h"
     DstPort
                             1
      }
     Branch {
                           [0, -125]
     Points
     Branch {
```

DstBlock DstPort	"beta_m" 1
<pre> } Branch {     Points     DstBlock     DstPort     } } </pre>	[0, -65] "alpha_m" 1
}	
Line { SrcBlock SrcPort DstBlock DstPort }	"E Na" 1 "V - V_Na" 2
Line { SrcBlock SrcPort DstBlock DstPort }	"Product3" 1 "I_Sodium" 1
Line { SrcBlock SrcPort DstBlock DstPort	"alpha_m" 1 "Product4" 2
<pre> } Line {    SrcBlock    SrcPort    DstBlock    DstPort } </pre>	"alpha_h" 1 "Product7" 2
Line { SrcBlock SrcPort DstBlock DstPort }	"beta_m" 1 "Product5" 2
Line { SrcBlock SrcPort DstBlock DstPort }	"beta_h" 1 "Product6" 2
Line { SrcBlock SrcPort DstBlock DstPort	"Product6" 1 "Subtract5" 2
, Line { SrcBlock SrcPort	"Product7" 1

Points [25, 0; 0, 70] DstBlock "Subtract5" DstPort 1 } Line { "Product5" SrcBlock SrcPort 1 "Subtract4" DstBlock DstPort 2 } Line { SrcBlock "Product4" SrcPort 1 Points [25, 0; 0, 50] "Subtract4" DstBlock DstPort 1 } Line { "1-m" SrcBlock SrcPort 1 [10, 0; 0, 50] Points "Product4" DstBlock DstPort 1 } Line { "1 - h" SrcBlock SrcPort 1 Points [10, 0; 0, 25] "Product7" DstBlock DstPort 1 } Line { "V - V Na" SrcBlock SrcPort 1 [340, 0; 0, 100] Points "Product3" DstBlock DstPort 5 } Line { "g Na" SrcBlock SrcPort 1 "Product3" DstBlock DstPort 6 } Line { SrcBlock "Temperature Subsystem" SrcPort 1 Points [555, 0; 0, -295] Branch { "Product" DstBlock 2 DstPort } Branch { Points [0, 5] "Product1" DstBlock DstPort 2 }

```
}
Line {
              "Integrator2"
 SrcBlock
 SrcPort
                 1
 Points
                 [30, 0; 0, 40]
 Branch {
   Points
                  [0, 20]
   Branch {
    Points
                          [0, 130]
     DstBlock
                          "Product3"
    DstPort
                          4
   }
   Branch {
     Points
                          [-405, 0; 0, -80]
     Branch {
                    "Product6"
     DstBlock
     DstPort
                         1
     }
    Branch {
                    "1 - h"
    DstBlock
    DstPort
                         1
     }
   }
 }
 Branch {
  Points
                  [0, 5]
                       "h out"
  DstBlock
  DstPort
                  1
 }
}
Line {
                "Product1"
 SrcBlock
 SrcPort
                 1
                 "Integrator2"
 DstBlock
DstPort
                 1
}
Line {
                 "Subtract5"
 SrcBlock
 SrcPort
                 1
                 "Product1"
 DstBlock
DstPort
                 1
}
Line {
                 "Product"
 SrcBlock
 SrcPort
                 1
                 "Integrator"
 DstBlock
DstPort
                 1
}
Line {
                 "Subtract4"
 SrcBlock
 SrcPort
                 1
                 "Product"
 DstBlock
DstPort
                 1
}
Line {
                "Integrator"
 SrcBlock
 SrcPort
                 1
```

Points [45, 0; 0, 20] Branch { [-405, 0; 0, -60] Points Branch { Points [0, 15] "Product5" DstBlock DstPort 1 } Branch { "1-m" DstBlock DstPort 1 } } Branch { Points [0, 165] Branch { Points [0, 185] Branch { Points [0, 10] Branch { [0, 10] Points DstBlock "Product3" DstPort 3 } Branch { "Product3" DstBlock DstPort 2 } } Branch { "Product3" DstBlock DstPort 1 } } Branch { [0, 10] Points "m out" DstBlock DstPort 1 } } } Line { "m initial" SrcBlock SrcPort 1 [75**,** 0] Points DstBlock "Integrator" DstPort 2 } Line { "h initial" SrcBlock SrcPort 1 [85**,** 0] Points DstBlock "Integrator2" DstPort 2 } Annotation { [798, 414] Position

```
}
      }
    }
   Block {
     BlockType
                              SubSystem
     Name
                        "Signal Builder"
      SID
                        "1092"
      Taq
                        "STV Subsys"
      Ports
                        [0, 1]
      Position
                              [860, 460, 945, 500]
     BlockMirror
                        on
      CopyFcn
                              "sigbuilder block('copy');"
      DeleteFcn
                              "sigbuilder block('delete');"
      LoadFcn
                              "sigbuilder block('load');"
     ModelCloseFcn
                              "sigbuilder block('modelClose');"
     PreSaveFcn
                        "sigbuilder block('preSave');"
      StartFcn
                              "sigbuilder block('start');"
      StopFcn
                              "sigbuilder block('stop');"
                              "sigbuilder block('namechange');"
     NameChangeFcn
      ClipboardFcn
                              "sigbuilder block('clipboard');"
                              "sigbuilder block('open', [70.5 105 547.5
     OpenFcn
236.25 ]);"
                              "sigbuilder block('close');"
     CloseFcn
     MinAlqLoopOccurrences
                              off
      PropExecContextOutsideSubsystem off
      RTWSystemCode
                              "Auto"
      FunctionWithSeparateData off
      Opaque
                              off
      RequestExecContextInheritance off
     MaskHideContents
                              on
                              "Sigbuilder block"
     MaskType
                              "Create and generate interchangeable
     MaskDescription
groups of signals whose waveforms are piecewise linea"
      "r."
     MaskInitialization
                              "if
~strcmp(get param(bdroot(gcbh),'SimulationStatus'),'stopped') tuvar =
sigbuilder blo"
      "ck('maskInit'); end"
     MaskSelfModifiable
                              on
                        "plot(0, 0, 100, 100, [2, 2, 32, 32, 2], [68, 8,
     MaskDisplay
8, 68, 68], [32, 2], [38, 38], [32, 19, 2], [53,"
      " 60, 44], [32, 17, 17, 2], [16, 16, 31, 31]);txt =
getActiveGroup(gcbh);text(2, 100, txt, 'verticalAlignment', 'to"
      "p');"
     MaskIconFrame
                              on
     MaskIconOpaque
                              off
                              "port"
     MaskIconRotate
                              "default"
     MaskPortRotate
                              "autoscale"
     MaskIconUnits
                              "slmaskedcaps(gcbh)"
     MaskCapabilities
      System {
                        "Signal Builder"
     Name
      Location
                        [480, 85, 980, 386]
      Open
                        off
     ModelBrowserVisibility on
     ModelBrowserWidth 200
      ScreenColor
                        "white"
```

```
PaperOrientation "landscape"
  PaperPositionMode "auto"
  PaperType "usletter"
                   "inches"
  PaperUnits
  TiledPaperMargins [0.500000, 0.500000, 0.500000, 0.500000]
  TiledPageScale 1
ShowPageBoundaries off
  ZoomFactor "100"
  SIDHighWatermark "17"
 Block {
   BlockType
                     Demux
   Name
                      "Demux"
   SID
                     "1092:14"
   Taq
                     "STV Demux"
   Ports
                          [1, 1]
                    [150, 42, 160, 618]
   Position
   Outputs
                     "1"
  }
 Block {
   BlockType
                     FromWorkspace
   Name
                     "FromWs"
   SID
                     "1092:2"
                     "STV FromWs"
   Taq
   Position
                    [30, 300, 115, 350]
                          "tuvar"
   VariableName
                           "0"
   SampleTime
   ZeroCross
                     on
                     "DataTag0"
   SigBuilderData
                     "DataTag1"
   VnvData
  }
 Block {
   BlockType
                     Outport
                           "Signal 1"
   Name
                     "1092:15"
   SID
                     "STV Outport"
   Taq
                     [280, 30, 300, 40]
   Position
                           "Port number"
   IconDisplay
  }
 Line {
                    "FromWs"
   SrcBlock
   SrcPort
                     1
                     "Demux"
   DstBlock
   DstPort
                     1
  }
 Line {
   SrcBlock
                     "Demux"
   SrcPort
                    1
   DstBlock
                    "Signal 1"
                    1
   DstPort
  }
  }
}
Block {
 BlockType
                       UnaryMinus
                  "Unary Minus"
 Name
 SID
                   "1083"
                         [210, 565, 240, 595]
 Position
```

ShowName off } Line { "Membrane" SrcBlock SrcPort 1 Points [0, -70; 85, 0] Branch { Points [80, 0] Branch { Points [155**,** 0] Branch { "KV" DstBlock DstPort 1 } Branch { Points [140, 0] DstBlock "Leak" DstPort 1 } } Branch { "NaV" DstBlock 1 DstPort } } Branch { "Add1" DstBlock DstPort 2 } } Line { "Add" SrcBlock SrcPort 1 Points [-40, 0] Branch { [-25, 0] Points "Membrane" DstBlock DstPort 1 } Branch { [0, 205] Points "Unary Minus" DstBlock 1 DstPort } } Line { "NaV" SrcBlock SrcPort 1 [0, 75; -20, 0] Points Branch { "Add" DstBlock DstPort 1 } Branch { Points [0, 190] "Bus\nCreator" DstBlock DstPort 1

} } Line { "KV" SrcBlock SrcPort 1 Points [0, 85; -190, 0] Branch { "Add" DstBlock 2 DstPort } Branch { Points [0, 190] "Bus\nCreator" DstBlock DstPort 2 } } Line { SrcBlock "Leak" SrcPort 1 [0, 95; -310, 0] Points Branch { "Add" DstBlock 3 DstPort } Branch { [0, 190] Points "Bus\nCreator" DstBlock DstPort 3 } } Line { "Add1" SrcBlock SrcPort 1 DstBlock "Action Potential" DstPort 1 } Line { SrcBlock "Constant" SrcPort 1 "Add1" DstBlock DstPort 1 } Line { "NaV" SrcBlock SrcPort 3 Points [0, 35] DstBlock "Gating Variables" DstPort 1 } Line { "KV" SrcBlock SrcPort 2 Points [0, 45] DstBlock "Gating Variables" DstPort 2 } Line {

```
"NaV"
     SrcBlock
     SrcPort
                           2
                          [0, 55]
"Gating Variables"
     Points
     DstBlock
     DstPort
                           3
   }
   Line {
                          "Bus\nCreator"
    SrcBlock
                           1
     SrcPort
                           "Currents"
     DstBlock
     DstPort
                           1
   }
   Line {
     SrcBlock
                          "Unary Minus"
     SrcPort
                          1
                          "Bus\nCreator"
     DstBlock
    DstPort
                           4
   }
   Line {
                          "Constant Stimulation"
    SrcBlock
    SrcPort
                          1
    DstBlock
                          "Add"
    DstPort
                           4
   }
   Annotation {
    Name
                     "Hondgkin and Huxley Model"
    Position
                       [394, 19]
   }
   Annotation {
    Position
                          [262, 63]
   }
   Annotation {
                          [248, 382]
   Position
   }
   Annotation {
                          [357, 77]
    Position
   }
 }
}
# Finite State Machines
#
    Stateflow Version 7.5 (R2010a) dated Mar 5 2011, 00:01:50
#
#
#
Stateflow {
 machine {
   id
                         1
                  "MyModel"
"31-Jan-2013 22:29:51"
   name
   created
                     0
   isLibrary
                        2
  firstTarget
  sfVersion
                       75014001
 }
 target {
```

```
id 2
name "sfun"
description "Default Simulink S-Function Target."
machine 1
linkNode [1 0 0]
}
```